

Package ‘Gammareg’

July 21, 2025

Type Package
Title Classic Gamma Regression: Joint Modeling of Mean and Shape Parameters
License GPL (>= 2)
Version 3.0.1
Date 2020-07-01
Author Martha Corrales and Edilberto Cepeda-Cuervo, with the colaboration of Margarita Marin, Maria Fernanda Zarate, Ricardo Duplat and Campo Elias Pardo.
Maintainer Martha Corrales <martha.corrales@usa.edu.co>
Depends R (>= 4.0.0)
Description Performs Gamma regression, where both mean and shape parameters follows lineal regression structures.
Encoding UTF-8
NeedsCompilation no
Repository CRAN
Date/Publication 2023-12-14 16:06:23 UTC

Contents

Gammareg-package	2
gammahetero1	2
gammahetero2	4
Gammareg	5
print.Gammareg	7
print.summary.Gammareg	8
summary.Gammareg	9
Index	10

Gammareg-package	<i>classic gamma regression: joint modeling of mean and shape parameters</i>
------------------	--

Description

Classic gamma regression package

Details

Package:	Gammareg
Type:	Package
Version:	1.1
Date:	2014-01-23
License:	GPL-2
LazyLoad:	yes

Author(s)

Martha Corrales and Edilberto Cepeda-Cuervo with the colaboration of Maria Fernanda Zarate, Ricardo Duplat and Campo Elias Pardo.

gammahetero1	<i>Classic gamma regression. Log link for the mean</i>
--------------	--

Description

Performs the Classic Gamma Regression for joint modeling of mean and shape parameters.

Usage

```
gammahetero1(formula1, formula2)
```

Arguments

formula1	object of class formula. It describes y_i and x_i for the mean equation of the gamma regression.
formula2	object of class formula. It describes z_i for the shape equation of the gamma regression.

Details

The classic gamma regression allow the joint modeling of mean and shape parameters of a gamma distributed variable, as is proposed in Cepeda (2001), using the Fisher Scoring algorithm, with log link for the mean and log link for the shape.

Value

object of class `Gammareg` with the following:

<code>X</code>	object of class matrix, with the variables for modelling the mean.
<code>Z</code>	object of class matrix, with the variables for modelling the shape.
<code>beta</code>	object of class matrix with the estimated coefficients of beta.
<code>gamma</code>	object of class matrix with the estimated coefficients of gamma.
<code>ICB</code>	object of class matrix with the estimated confidence intervals of beta.
<code>ICG</code>	object of class matrix with the estimated confidence intervals of gamma.
<code>CovarianceMatrixbeta</code>	object of class matrix with the estimated covariances of beta.
<code>CovarianceMatrixgamma</code>	object of class matrix with the estimated covariances of gamma.
<code>AIC</code>	the AIC criteria.
<code>iteration</code>	numbers of iterations to convergence.
<code>convergence</code>	value of convergence obtained.

Author(s)

Martha Corrales <martha.corrales@usa.edu.co> Edilberto Cepeda-Cuervo <ecepedac@unal.edu.co>

References

1. Cepeda-Cuervo, E. (2001). Modelagem da variabilidade em modelos lineares generalizados. Unpublished Ph.D. tesis. Instituto de Matemáticas. Universidade Federal do Rio do Janeiro. <http://www.docentes.unal.edu.co/ecepedac/docs/MODELAGEM20DA20VARIABILIDADE.pdf>. <http://www.bdigital.unal.edu.co>
2. McCullagh, P. and Nelder, N.A. (1989). Generalized Linear Models. Second Edition. Chapman and Hall.

Examples

```
# Simulation Example

X1 <- rep(1,500)
X2 <- log(runif(500,0,30))
X3 <- log(runif(500,0,15))
X4 <- log(runif(500,10,20))
mui <- exp(-5 + 0.2*X2 - 0.03*X3)
alphai <- exp(0.2 + 0.1*X2 + 0.3*X4)
Y <- rgamma(500,shape=alphai,scale=mui/alphai)
X <- cbind(X1,X2,X3)
```

```

Z <- cbind(X1,X2,X4)
formula.mean= Y~X2+X3
formula.shape= ~X2+X4
a=gammahetero1(formula.mean,formula.shape)
a

```

gammahetero2

Classic gamma regression. Identity link for the mean

Description

Performs the Classic Gamma Regression for joint modeling of mean and shape parameters.

Usage

```
gammahetero2(formula1, formula2)
```

Arguments

formula1	object of class formula. It describes yi and xi for the mean equation of the gamma regression.
formula2	object of class formula. It describes zi for the shape equation of the gamma regression.

Details

The classic gamma regression allow the joint modeling of mean and shape parameters of a gamma distributed variable, as is proposed in Cepeda (2001), using the Fisher Scoring algorithm, with log link for the mean and log link for the shape.

Value

object of class Gammareg with the following:

X	object of class matrix, with the variables for modelling the mean.
Z	object of class matrix, with the variables for modelling the shape.
beta	object of class matrix with the estimated coefficients of beta.
gamma	object of class matrix with the estimated coefficients of gamma.
ICB	object of class matrix with the estimated confidence intervals of beta.
ICG	object of class matrix with the estimated confidence intervals of gamma.
CovarianceMatrixbeta	object of class matrix with the estimated covariances of beta.
CovarianceMatrixgamma	object of class matrix with the estimated covariances of gamma.
AIC	the AIC criteria
iteration	numbers of iterations to convergence
convergence	value of convergence obtained

Author(s)

Martha Corrales <martha.corrales@usa.edu.co> Edilberto Cepeda-Cuervo <ecepedac@unal.edu.co>,

References

1. Cepeda-Cuervo, E. (2001). Modelagem da variabilidade em modelos lineares generalizados. Unpublished Ph.D. tesis. Instituto de Matemáticas. Universidade Federal do Rio de Janeiro. <http://www.docentes.unal.edu.co/ecepedac/docs/MODELAGEM20DA20VARIABILIDADE.pdf>. <http://www.bdigital.unal.edu.co>
2. McCullagh, P. and Nelder, N.A. (1989). Generalized Linear Models. Second Edition. Chapman and Hall.

Examples

```
# Simulation Example

X1 <- rep(1,500)
X2 <- runif(500,0,30)
X3 <- runif(500,0,15)
X4 <- runif(500,10,20)
mui <- 15 + 2*X2 + 3*X3
alphai <- exp(0.2 + 0.1*X2 + 0.3*X4)
Y <- rgamma(500,shape=alphai,scale=mui/alphai)
X <- cbind(X1,X2,X3)
Z <- cbind(X1,X2,X4)
formula.mean= Y~X2+X3
formula.shape= ~X2+X4
a=gammahetero2(formula.mean,formula.shape)
a
```

Gammareg

Gammareg

Description

Function to do Classic Gamma Regression: joint mean and shape modeling

Usage

```
Gammareg(formula1,formula2,meanlink)
```

Arguments

formula1	object of class matrix, with the dependent variable.
formula2	object of class matrix, with the variables for modelling the mean.
meanlink	links for the mean. The default links is the link log. The link identity is also allowed as admissible value.

Details

The classic gamma regression allow the joint modelling of mean and shape parameters of a gamma distributed variable, as is proposed in Cepeda (2001), using the Fisher Scoring algorithm, with two differentes link for the mean: log and identity, and log link for the shape.

Value

object of class bayesbetareg with:

coefficients	object of class matrix with the estimated coefficients of beta and gamma.
desvB	object of class matrix with the estimated covariances of beta.
desvG	object of class matrix with the estimated covariances of gamma.
interv	object of class matrix with the estimated confidence intervals of beta and gamma.
AIC	the AIC criteria.
iteration	numbers of iterations to convergence.
convergence	value of convergence obtained.
call	Call.

Author(s)

Martha Corrales <martha.corrales@usa.edu.co> Edilberto Cepeda-Cuervo <ecepdac@unal.edu.co>

References

1. Cepeda-Cuervo, E. (2001). Modelagem da variabilidade em modelos lineares generalizados. Unpublished Ph.D. tesis. Instituto de Matemáticas. Universidade Federal do R o do Janeiro. <http://www.docentes.unal.edu.co/ecepdac/docs/MODELAGEM20DA20VARIABILIDADE.pdf>. <http://www.bdigital.unal.edu.co>
2. McCullagh, P. and Nelder, N.A. (1989). Generalized Linear Models. Second Edition. Chapman and Hall.

Examples

```
#

num.killed <- c(7,59,115,149,178,229,5,43,76,4,57,83,6,57,84)
size.sam <- c(1,2,3,3,3,3,rep(1,9))*100
insecticide <- c(4,5,8,10,15,20,2,5,10,2,5,10,2,5,10)
insecticide.2 <- insecticide^2
synergist <- c(rep(0,6),rep(3.9,3),rep(19.5,3),rep(39,3))

par(mfrow=c(2,2))
plot(density(num.killed/size.sam),main="")
boxplot(num.killed/size.sam)
plot(insecticide,num.killed/size.sam)
plot(synergist,num.killed/size.sam)

mean.for <- (num.killed/size.sam) ~ insecticide + insecticide.2
```

```

dis.for <- ~ synergist + insecticide

res=Gammareg(mean.for,dis.for,meanlink="ide")

summary(glm((num.killed/size.sam) ~ insecticide + insecticide.2,family=Gamma("log")))
summary(res)

# Simulation Example

X1 <- rep(1,500)
X2 <- runif(500,0,30)
X3 <- runif(500,0,15)
X4 <- runif(500,10,20)
mui <- 15 + 2*X2 + 3*X3
alphai <- exp(0.2 + 0.1*X2 + 0.3*X4)
Y <- rgamma(500,shape=alphai,scale=mui/alphai)
X <- cbind(X1,X2,X3)
Z <- cbind(X1,X2,X4)
formula.mean= Y~X2+X3
formula.shape= ~X2+X4
a=Gammareg(formula.mean,formula.shape,meanlink="ide")
summary(a)

```

print.Gammareg

print the Classic gamma regression

Description

Print the Classic Gamma Regression for joint modeling of mean and shape parameters.

Usage

```
## S3 method for class 'Gammareg'
print(x,...)
```

Arguments

x	object of class Gammareg
...	not used.

Value

print the Classic gamma regression

Author(s)

Martha Corrales <martha.corrales@usa.edu.co> Edilberto Cepeda-Cuervo <cepedac@unal.edu.co>

References

1. Cepeda-Cuervo, E. (2001). Modelagem da variabilidade em modelos lineares generalizados. Unpublished Ph.D. tesis. Instituto de Matemáticas. Universidade Federal do Rio do Janeiro. <http://www.docentes.unal.edu.co/ecepedac/docs/MODELAGEM20DA20VARIABILIDADE.pdf>. <http://www.bdigital.unal.edu.co>
2. McCullagh, P. and Nelder, N.A. (1989). Generalized Linear Models. Second Edition. Chapman and Hall.

```
print.summary.Gammareg
```

print the summary of the Classic gamma regression

Description

Print the summary Classic Gamma Regression for joint modelling of mean and shape parameters.

Usage

```
## S3 method for class 'summary.Gammareg'
print(x, ...)
```

Arguments

x	object of class Gammareg
...	not used.

Value

Print the summary Classic Gamma Regression for joint modelling of mean and shape parameters.

Author(s)

Martha Corrales <martha.corrales@usa.edu.co> Edilberto Cepeda-Cuervo <ecepedac@unal.edu.co>

References

1. Cepeda-Cuervo E. (2001). Modelagem da variabilidade em modelos lineares generalizados. Unpublished Ph.D. tesis. Instituto de Matemáticas. Universidade Federal do Rio do Janeiro. <http://www.docentes.unal.edu.co/ecepedac/docs/MODELAGEM20DA20VARIABILIDADE.pdf>. <http://www.bdigital.unal.edu.co>
2. McCullagh, P. and Nelder, N.A. (1989). Generalized Linear Models. Second Edition. Chapman and Hall.

`summary.Gammareg`*Print the Classic gamma regression*

Description

Summarized the Classic gamma regression for joint modelling of mean and shape parameters.

Usage

```
## S3 method for class 'Gammareg'
summary(object, ...)
```

Arguments

<code>object</code>	an object of class <code>Gammareg</code>
<code>...</code>	not used.

Value

<code>call</code>	Call
<code>coefficients</code>	Coefficients
<code>covB</code>	object of class matrix with the estimated covariances of beta.
<code>covG</code>	object of class matrix with the estimated covariances of gamma.
<code>AIC</code>	AIC
<code>iteration</code>	number of iterations
<code>convergence</code>	convergence obtained

Author(s)

Martha Corrales <martha.corrales@usa.edu.co> Edilberto Cepeda-Cuervo <ecepedac@unal.edu.co>

References

1. Cepeda-Cuervo, E. (2001). Modelagem da variabilidade em modelos lineares generalizados. Unpublished Ph.D. tesis. Instituto de Matemáticas. Universidade Federal do Rio de Janeiro. <http://www.docentes.unal.edu.co/ecepedac/docs/MODELAGEM20DA20VARIABILIDADE.pdf>. <http://www.bdigital.unal.edu.co>
2. McCullagh, P. and Nelder, N.A. (1989). Generalized Linear Models. Second Edition. Chapman and Hall.

Index

* Classic estimation

Gammareg, 5
print.Gammareg, 7
print.summary.Gammareg, 8
summary.Gammareg, 9

* Fisher Scoring

gammahetero1, 2
gammahetero2, 4
Gammareg, 5
print.Gammareg, 7
print.summary.Gammareg, 8
summary.Gammareg, 9

* Gamma regression

gammahetero1, 2
gammahetero2, 4
Gammareg, 5
print.Gammareg, 7
print.summary.Gammareg, 8
summary.Gammareg, 9

* Joint modeling

gammahetero1, 2
gammahetero2, 4

* Mean and shape parameters

gammahetero1, 2
gammahetero2, 4
Gammareg, 5
print.Gammareg, 7
print.summary.Gammareg, 8
summary.Gammareg, 9

* joint modeling

Gammareg, 5
print.Gammareg, 7
print.summary.Gammareg, 8
summary.Gammareg, 9

* package

Gammareg-package, 2

Gammareg-package, 2

print.Gammareg, 7
print.summary.Gammareg, 8

summary.Gammareg, 9

gammahetero1, 2
gammahetero2, 4
Gammareg, 5