

Package ‘MazamaTimeSeries’

July 21, 2025

Type Package

Version 0.3.1

Title Core Functionality for Environmental Time Series

Maintainer Jonathan Callahan <jonathan.s.callahan@gmail.com>

Description Utility functions for working with environmental time series data from known locations. The compact data model is structured as a list with two dataframes. A 'meta' dataframe contains spatial and measuring device metadata associated with deployments at known locations. A 'data' dataframe contains a 'datetime' column followed by columns of measurements associated with each ``device-deployment''. Ephemerides calculations are based on code originally found in NOAA's ``Solar Calculator" <<https://gml.noaa.gov/grad/solcalc/>>.

License GPL-3

URL <https://github.com/MazamaScience/MazamaTimeSeries>,
<https://mazamascience.github.io/MazamaTimeSeries/>

BugReports <https://github.com/MazamaScience/MazamaTimeSeries/issues>

Depends R (>= 4.0.0)

Imports dplyr, geodist, lubridate, magrittr, methods, MazamaCoreUtils
(>= 0.5.3), MazamaRollUtils (>= 0.1.4), rlang, stringr

Suggests knitr, markdown, testthat (>= 2.1.0), rmarkdown, roxygen2

Encoding UTF-8

VignetteBuilder knitr

LazyData true

RoxygenNote 7.3.1

NeedsCompilation no

Author Jonathan Callahan [aut, cre],
Hans Martin [ctb],
Eli Grosman [ctb],
Roger Bivand [ctb],
Sebastian Luque [ctb]

Repository CRAN

Date/Publication 2025-05-17 22:00:10 UTC

Contents

Camp_Fire	3
Carmel_Valley	4
example_mts	4
example_raws	5
example_sts	6
MazamaTimeSeries	6
mts_arrange	7
mts_check	8
mts_collapse	9
mts_combine	10
mts_distinct	11
mts_extractDataFrame	12
mts_filterData	13
mts_filterDate	14
mts_filterDatetime	15
mts_filterMeta	17
mts_getDistance	18
mts_isEmpty	19
mts_isValid	19
mts_pull	20
mts_sample	21
mts_select	23
mts_selectWhere	24
mts_setTimeAxis	25
mts_slice_head	26
mts_summarize	27
mts_trim	29
mts_trimDate	29
requiredMetaNames	30
sts_check	31
sts_combine	32
sts_distinct	33
sts_extractDataFrame	34
sts_filter	34
sts_filterDate	35
sts_filterDatetime	37
sts_isEmpty	38
sts_isValid	39
sts_summarize	40
sts_trimDate	41
timeInfo	42

Index

Camp_Fire	<i>Camp Fire example dataset</i>
-----------	----------------------------------

Description

The Camp_Fire dataset provides a quickly loadable version of a *mts_monitor* object for practicing and code examples.

Usage

Camp_Fire

Format

A *mts* object with 360 rows and 134 columns of data.

Details

The 2018 Camp Fire was the deadliest and most destructive wildfire in California's history, and the most expensive natural disaster in the world in 2018 in terms of insured losses. The fire caused at least 85 civilian fatalities and injured 12 civilians and five firefighters. It covered an area of 153,336 acres and destroyed more than 18,000 structures, most within the first 4 hours. Smoke from the fire resulted in the worst air pollution ever for the San Francisco Bay Area and Sacramento Valley.

This dataset was generated on 2022-10-12 by running:

```
library(AirMonitor)

Camp_Fire <-
  monitor_loadAnnual(2018) %>%
  monitor_filter(stateCode == 'CA') %>%
  monitor_filterDate(
    startdate = 20181108,
    enddate = 20181123,
    timezone = "America/Los_Angeles"
  ) %>%
  monitor_dropEmpty()

save(Camp_Fire, file = "data/Camp_Fire.rda")
```

Carmel_Valley

Carmel Valley example dataset

Description

The Carmel_Valley dataset provides a quickly loadable version of a single-sensor *mts_monitor* object for practicing and code examples.

Usage

```
Carmel_Valley
```

Format

An *mts* object with 600 rows and 2 columns of data.

Details

In August of 2016, the Soberanes fire in California burned along the Big Sur coast. It was at the time the most expensive wildfire in US history. This dataset contains PM2.5 monitoring data for the monitor in Carmel Valley which shows heavy smoke as well as strong diurnal cycles associated with sea breezes. Data are stored as an *mts* object and are used in some examples in the package documentation.

This dataset was generated on 2022-10-12 by running:

```
library(AirMonitor)
```

```
Carmel_Valley <-
  airnow_loadAnnual(2016) %>%
  monitor_filterMeta(deviceDeploymentID == "a9572a904a4ed46d_840060530002") %>%
  monitor_filterDate(20160722, 20160815)
```

```
save(Carmel_Valley, file = "data/Carmel_Valley.rda")
```

example_mts

Example mts dataset

Description

The example_mts dataset provides a quickly loadable version of an *mts* object for practicing and code examples.

This dataset was generated on 2021-10-07 by running:

```
library(AirSensor)

communities <- c("Alhambra/Monterey Park", "El Monte")

example_mts <-
  example_sensor_scaqmd %>%
  sensor_filterMeta(communityRegion %in% communities)

# Add required "locationName"
example_mts$meta$locationName <- example_mts$meta$siteName

save(example_mts, file = "data/example_mts.rda")
```

Usage

```
example_mts
```

Format

An *mts* object composed of "meta" and "data" dataframes.

example_raws	<i>Example RAWS dataset</i>
--------------	-----------------------------

Description

The `example_raws` dataset provides a quickly loadable example of the data generated by the **RAWSmet** package. This data is a *sts* object containing hourly measurements from a RAWS weather station in Saddle Mountain, WA, between July 2002 and December 2017.

This dataset was generated on 2022-02-17 by running:

```
library(RAWSmet)

setRawDataDir("~/Data/RAWS")

example_raws <-
  cefa_load(nwsID = "452701") %>%
  raws_filterDate(20160701, 20161001)

save(example_raws, file = "data/example_raws.rda")
```

Usage

```
example_raws
```

Format

An *sts* object composed of "meta" and "data" dataframes.

example_sts	<i>Example sts dataset</i>
-------------	----------------------------

Description

The example_sts dataset provides a quickly loadable version of an *sts* object for practicing and code examples.

This dataset was generated on 2021-01-08 by running:

```
library(AirSensor)

example_sts <- example_pat
example_sts$meta$elevation <- as.numeric(NA)
example_sts$meta$locationName <- example_sts$meta$label

save(example_sts, file = "data/example_sts.rda")
```

Usage

```
example_sts
```

Format

An *sts* object composed of "meta" and "data" dataframes.

MazamaTimeSeries	<i>Core functionality for environmental time series</i>
------------------	---

Description

Utility functions for working with environmental time series data from known locations. The compact data model is structured as a list with two dataframes. A meta' dataframe contains spatial and measuring device metadata associated with deployments at known locations. A 'data' dataframe contains a 'datetime' column followed by columns of measurements associated with each "device-deployment".

Author(s)

Maintainer: Jonathan Callahan <jonathan.s.callahan@gmail.com>

Other contributors:

- Hans Martin <hansmrtn@gmail.com> [contributor]
- Eli Grosman <eligrosman1@gmail.com> [contributor]
- Roger Bivand <roger.bivand@nhh.no> [contributor]
- Sebastian Luque <spluque@gmail.com> [contributor]

See Also

Useful links:

- <https://github.com/MazamaScience/MazamaTimeSeries>
- <https://mazamascience.github.io/MazamaTimeSeries/>
- Report bugs at <https://github.com/MazamaScience/MazamaTimeSeries/issues>

mts_arrange

Order mts time series by metadata values

Description

The variable(s) in ... are used to specify columns of mts\$meta to use for ordering. Under the hood, this function uses [arrange](#) on mts\$meta and then reorders mts\$data to match.

Usage

```
mts_arrange(mts, ...)
```

Arguments

```
mts          mts object.
...          variables in mts$meta.
```

Value

A reordered version of the incoming *mts* time series object. (A list with meta and data dataframes.)

Examples

```
library(MazamaTimeSeries)

example_mts$meta$latitude[1:10]

# Filter for all labels with "SCSH"
byElevation <-
  example_mts %>%
    mts_arrange(latitude)

byElevation$meta$latitude[1:10]
```

mts_check	<i>Check mts object for validity</i>
-----------	--------------------------------------

Description

Checks on the validity of an *mts* object. If any test fails, this function will stop with a warning message.

Usage

```
mts_check(mts)
```

Arguments

mts *mts* object.

Value

Returns TRUE invisibly if the *mts* object is valid.

See Also

[mts_isValid](#)

Examples

```
library(MazamaTimeSeries)

sts_check(example_mts)

# This would throw an error
if ( FALSE ) {

  broken_mts <- example_mts
  names(broken_mts) <- c('meta', 'bop')
  sts_check(broken_mts)

}
```

mts_collapse

*Collapse an mts time series object into a single time series***Description**

Collapses data from all time series in *mts* into a single-time series *mts* object using the function provided in the *FUN* argument. The single-time series result will be located at the mean longitude and latitude unless *longitude* and *latitude* are specified.

Any columns of *mts\$meta* that are constant across all records will be retained in the returned *mts\$meta*.

The core metadata associated with this location (e.g. *countryCode*, *stateCode*, *timezone*, ...) will be determined from the most common (or average) value found in *mts\$meta*. This will be a reasonable assumption for the vast majority of intended use cases where data from multiple devices in close proximity are averaged together.

Usage

```
mts_collapse(
  mts,
  longitude = NULL,
  latitude = NULL,
  deviceID = "generatedID",
  FUN = mean,
  na.rm = TRUE,
  ...
)
```

Arguments

<i>mts</i>	<i>mts</i> object.
<i>longitude</i>	Longitude of the collapsed time series.
<i>latitude</i>	Latitude of the collapsed time series.
<i>deviceID</i>	Device identifier for the collapsed time series.
<i>FUN</i>	Function used to collapse multiple time series.
<i>na.rm</i>	Logical specifying whether NA values should be ignored when <i>FUN</i> is applied.
...	additional arguments to be passed on to the <i>apply()</i> function.

Value

An *mts* time series object representing a single time series. (A list with *meta* and *data* dataframes.)

Note

After *FUN* is applied, values of $\pm\text{Inf}$ and NaN are converted to NA. This is a convenience for the common case where *FUN* = *min*/*max* or *FUN* = *mean* and some of the time steps have all missing values. See the R documentation for *min* for an explanation.

Examples

```
library(MazamaTimeSeries)

mon <-
  mts_collapse(
    mts = example_mts,
    deviceID = "example_ID"
  )

# mon$data now only has 2 columns
names(mon$data)

plot(mon$data, type = 'b', main = mon$meta$deviceID)
```

mts_combine

Combine multiple mts time series objects

Description

Create a combined *mts* from any number of *mts* objects or from a list of *mts* objects. The resulting *mts* object will contain all deviceDeploymentIDs found in any incoming *mts* and will have a regular time axis covering the entire range of incoming data.

If incoming time ranges are non-contiguous, the resulting *mts* will have gaps filled with NA values.

An error is generated if the incoming *mts* objects have non-identical metadata for the same deviceDeploymentID unless replaceMeta = TRUE.

Usage

```
mts_combine(
  ...,
  replaceMeta = FALSE,
  overlapStrategy = c("replace all", "replace na")
)
```

Arguments

...	Any number of valid <i>mts</i> objects.
replaceMeta	Logical specifying whether to allow replacement of metadata associated with deviceDeploymentIDs.
overlapStrategy	Strategy to use when data found in time series overlaps.

Value

An *mts* time series object containing all time series found in the incoming *mts* objects. (A list with meta and data dataframes.)

Note

Data for any deviceDeploymentIDs shared among *mts* objects are combined with a "later is better" sensibility where any data overlaps exist. To handle this, incoming *mts* objects are first split into "shared" and "unshared" parts.

Any "shared" parts are ordered based on the time stamp of their last record. Then `dplyr::distinct()` is used to remove records with duplicate datetime fields.

With `overlapStrategy = "replace all"`, any data records found in "later" *mts* objects are preferentially retained before the "shared" data are finally reordered by ascending datetime.

With `overlapStrategy = "replace missing"`, only missing values in "earlier" *mts* objects are replaced with data records from "later" time series.

The final step is combining the "shared" and "unshared" parts and placing them on a uniform time axis.

Examples

```
library(MazamaTimeSeries)

ids1 <- example_mts$meta$deviceDeploymentID[1:5]
ids2 <- example_mts$meta$deviceDeploymentID[4:6]
ids3 <- example_mts$meta$deviceDeploymentID[8:10]

mts1 <-
  example_mts %>%
  mts_filterMeta(deviceDeploymentID %in% ids1) %>%
  mts_filterDate(20190701, 20190703)

mts2 <-
  example_mts %>%
  mts_filterMeta(deviceDeploymentID %in% ids2) %>%
  mts_filterDate(20190704, 20190706)

mts3 <-
  example_mts %>%
  mts_filterMeta(deviceDeploymentID %in% ids3) %>%
  mts_filterDate(20190705, 20190708)

mts <- mts_combine(mts1, mts2, mts3)

# Should have 1:6 + 8:10 = 9 meta records and the full date range
nrow(mts$meta)
range(mts$data$datetime)
```

Description

This function is primarily for internal use.

Two successive steps are used to guarantee that the `datetime` axis contains no repeated values:

1. remove any duplicate records
2. guarantee that rows are in `datetime` order

Usage

```
mts_distinct(mts)
```

Arguments

`mts` *mts* object

Value

An *mts* object where each record is associated with a unique time. (A list with meta and data dataframes.)

`mts_extractDataFrame` *Extract dataframes from mts objects*

Description

These functions are convenient wrappers for extracting the dataframes that comprise an *mts* object. These functions are designed to be useful when manipulating data in a pipeline chain using `%>%`.

`mts_extractData(mts)` is equivalent to `mts$data`.

`mts_extractMeta(mts)` is equivalent to `mts$meta`.

Usage

```
mts_extractData(mts)
```

```
mts_extractMeta(mts)
```

Arguments

`mts` *mts* object to extract dataframe from.

Value

A dataframe from the *mts* object.

mts_filterData

*General purpose data filtering for mts time series objects***Description**

A generalized data filter for *mts* objects to choose rows/cases where conditions are true. Multiple conditions may be combined with & or separated by a comma. Only rows where the condition evaluates to TRUE are kept. Rows where the condition evaluates to NA are dropped.

Usage

```
mts_filterData(mts, ...)
```

Arguments

mts *mts* object.
 ... Logical predicates defined in terms of the variables in *mts*\$data.

Value

A subset of the incoming *mts* time series object. (A list with meta and data dataframes.)

Note

Filtering is done on variables in *mts*\$data and results in an *incomplete and irregular time axis*.

See Also

[mts_filterMeta](#)

Examples

```
library(MazamaTimeSeries)

# Are there any times when data exceeded 150?
sapply(example_mts$data, function(x) { any(x > 150, na.rm = TRUE) })

# Show all times where da4cadd2d6ea5302_4686 > 150
example_mts %>%
  mts_filterData(da4cadd2d6ea5302_4686 > 150) %>%
  mts_extractData() %>%
  dplyr::pull(datetime)
```

mts_filterDate

*Date filtering for mts time series objects***Description**

Subsets an *mts* object by date. This function always filters to day-boundaries. For sub-day filtering, use `mts_setTimeAxis()`.

Dates can be anything that is understood by `MazamaCoreUtils::parseDatetime()` including either of the following recommended formats:

- "YYYYmmdd"
- "YYYY-mm-dd"

Timezone determination precedence assumes that if you are passing in POSIXct values then you know what you are doing:

1. get timezone from startdate if it is POSIXct
2. use passed in timezone
3. get timezone from mts

Usage

```
mts_filterDate(
  mts = NULL,
  startdate = NULL,
  enddate = NULL,
  timezone = NULL,
  unit = "sec",
  ceilingStart = FALSE,
  ceilingEnd = FALSE
)
```

Arguments

mts	<i>mts</i> object.
startdate	Desired start date (ISO 8601).
enddate	Desired end date (ISO 8601).
timezone	Olson timezone used to interpret dates.
unit	Units used to determine time at end-of-day.
ceilingStart	Logical instruction to apply ceiling_date to the startdate rather than floor_date .
ceilingEnd	Logical instruction to apply ceiling_date to the enddate rather than floor_date .

Value

A subset of the incoming *mts* time series object. (A list with meta and data dataframes.)

Note

The returned data will run from the beginning of startdate until the **beginning** of enddate – *i.e.* no values associated with enddate will be returned. The exception being when enddate is less than 24 hours after startdate. In that case, a single day is returned.

See Also

[mts_setTimeAxis](#)

Examples

```
library(MazamaTimeSeries)

example_mts %>%
  mts_filterDate(
    startdate = 20190703,
    enddate = 20190706
  ) %>%
  mts_extractData() %>%
  dplyr::pull(datetime) %>%
  range()
```

mts_filterDatetime	<i>Datetime filtering for mts time series objects</i>
--------------------	---

Description

DEPRECATED – use [mts_setTimeAxis](#).

Subsets an mts object by datetime. This function allows for sub-day filtering as opposed to mts_filterDate() which always filters to day-boundaries. Both the startdate and the enddate will be included in the subset.

Datetimes can be anything that is understood by MazamaCoreUtils::parseDatetime(). For non-POSIXct values, the recommended format is "YYYY-mm-dd HH:MM:SS".

Timezone determination precedence assumes that if you are passing in POSIXct values then you know what you are doing:

1. get timezone from startdate if it is POSIXct
2. use passed in timezone
3. get timezone from mts

Usage

```
mts_filterDatetime(  
  mts = NULL,  
  startdate = NULL,  
  enddate = NULL,  
  timezone = NULL,  
  unit = "sec",  
  ceilingStart = FALSE,  
  ceilingEnd = FALSE,  
  includeEnd = FALSE  
)
```

Arguments

mts	<i>mts</i> object.
startdate	Desired start datetime (ISO 8601).
enddate	Desired end datetime (ISO 8601).
timezone	Olson timezone used to interpret dates.
unit	Datetimes will be rounded to the nearest unit.
ceilingStart	Logical instruction to apply ceiling_date to the startdate rather than floor_date when rounding.
ceilingEnd	Logical instruction to apply ceiling_date to the enddate rather than floor_date when rounding.
includeEnd	Logical specifying that records associated with enddate should be included.

Value

A subset of the incoming *mts* time series object. (A list with meta and data dataframes.)

Note

This function is deprecated as of **MazamaTimeSeries 0.2.15**. Please use [mts_setTimeAxis](#) to shorten or lengthen the time axis of an *mts* object.

See Also

[mts_filterData](#)

[mts_filterDate](#)

[mts_filterMeta](#)

mts_filterMeta*General purpose metadata filtering for mts time series objects*

Description

A generalized metadata filter for *mts* objects to choose rows/cases where conditions are true. Multiple conditions are combined with & or separated by a comma. Only rows where the condition evaluates to TRUE are kept. Rows where the condition evaluates to FALSE or NA are dropped.

If an empty *mts* object is passed in, it is immediately returned, allowing for multiple filtering steps to be piped together and only checking for an empty *mts* object at the end of the pipeline.

Usage

```
mts_filterMeta(mts, ...)
```

Arguments

<code>mts</code>	<i>mts</i> object.
<code>...</code>	Logical predicates defined in terms of the variables in <code>mts\$meta</code> .

Value

A subset of the incoming *mts* time series object. (A list with meta and data dataframes.)

Note

Filtering is done on variables in `mts$meta`.

See Also

[mts_filterData](#)

Examples

```
library(MazamaTimeSeries)

# Filter for all labels with "SCSH"
scap <-
  example_mts %>%
  mts_filterMeta(communityRegion == "El Monte")

dplyr::select(scap$meta, ID, label, longitude, latitude, communityRegion)

head(scap$data)
```

mts_getDistance	<i>Calculate distances from mts time series locations to a location of interest</i>
-----------------	---

Description

This function uses the [geodist] package to return the distances (meters) between mts locations and a location of interest. These distances can be used to create a mask identifying monitors within a certain radius of the location of interest.

Usage

```
mts_getDistance(
  mts = NULL,
  longitude = NULL,
  latitude = NULL,
  measure = c("geodesic", "haversine", "vincenty", "cheap")
)
```

Arguments

mts	mts object.
longitude	Longitude of the location of interest.
latitude	Latitude of the location of interest.
measure	One of "geodesic", "haversine", "vincenty" or "cheap"

Value

Vector of of distances (meters) named by deviceDeploymentID.

Note

The measure "cheap" may be used to speed things up depending on the spatial scale being considered. Distances calculated with measure = "cheap" will vary by a few meters compared with those calculated using measure = "geodesic".

Examples

```
library(MazamaTimeSeries)

# Garfield Medical Center in LA
longitude <- -118.12321
latitude <- 34.06775

distances <- mts_getDistance(
  mts = example_mts,
  longitude = longitude,
  latitude = latitude
)
```

```
)

# Which sensors are within 1000 meters of Garfield Med Ctr?
distances[distances <= 1000]
```

mts_isEmpty	<i>Test for an empty mts object</i>
-------------	-------------------------------------

Description

Convenience function for `nrow(mts$data) == 0`. This makes for more readable code in functions that need to test for this.

Usage

```
mts_isEmpty(mts)
```

Arguments

`mts` *mts* object

Value

TRUE if no data exist in `mts`, FALSE otherwise.

Examples

```
library(MazamaTimeSeries)

mts_isEmpty(example_mts)
```

mts_isValid	<i>Test mts object for correct structure</i>
-------------	--

Description

The `mts` is checked for the presence of core meta and data columns.

Core meta columns include:

- `deviceDeploymentID` – unique identifier (see [MazmaLocationUtils](#))
- `deviceId` – device identifier
- `locationID` – location identifier (see [MazmaLocationUtils](#))
- `locationName` – English language name

- longitude – decimal degrees E
- latitude – decimal degrees N
- elevation – elevation of station in m
- countryCode – ISO 3166-1 alpha-2
- stateCode – ISO 3166-2 alpha-2
- timezone – Olson time zone

Core data columns include:

- datetime – measurement time (UTC)

Usage

```
mts_isValid(mts = NULL, verbose = FALSE)
```

Arguments

mts	mts object
verbose	Logical specifying whether to produce detailed warning messages.

Value

Invisibly returns TRUE if mts has the correct structure, FALSE otherwise.

See Also

[mts_check](#)

Examples

```
library(MazamaTimeSeries)
print(mts_isValid(example_mts))
```

mts_pull

Extract a column of metadata or data

Description

This function acts similarly to `dplyr::pull()` working on `mts$meta` or `mts$data`. Data are returned as a simple array. Data are pulled from whichever dataframe contains `var`.

Usage

```
mts_pull(mts = NULL, var = NULL)
```

Arguments

mts	<i>mts</i> object.
var	A variable name found in the meta or data dataframe of the incoming <i>mts</i> time series object.

Value

An array of values.

Examples

```
library(MazamaTimeSeries)

# Metadata
example_mts %>%
  mts_pull("communityRegion") %>%
  table() %>%
  sort(decreasing = TRUE)

# Data for a specific ID
example_mts %>%
  mts_pull("da4cadd2d6ea5302_4686")
```

mts_sample	<i>Sample time series for an mts time series object</i>
------------	---

Description

Reduce the number of records (timesteps) in the data dataframe of the incoming *mts* through random sampling.

Usage

```
mts_sample(
  mts = NULL,
  sampleSize = 5000,
  seed = NULL,
  keepOutliers = FALSE,
  width = 5,
  thresholdMin = 3
)
```

Arguments

<code>mts</code>	<i>mts</i> object.
<code>sampleSize</code>	Non-negative integer giving the number of rows to choose.
<code>seed</code>	Integer passed to <code>set.seed</code> for reproducible sampling.
<code>keepOutliers</code>	Logical specifying a graphics focused sampling algorithm that retains outliers (see Details).
<code>width</code>	Integer width of the rolling window used for outlier detection.
<code>thresholdMin</code>	Numeric threshold for outlier detection.

Details

When `keepOutliers = FALSE`, random sampling is used to provide a statistically relevant subsample of the data.

Value

A subset of the given *mts* object.

An *mts* time series object with fewer timesteps. (A list with meta and data dataframes.)

Outlier Detection

When `keepOutliers = TRUE`, a customized sampling algorithm is used that attempts to create subsets for use in plotting that create plots that are visually identical to plots using all data. This is accomplished by preserving outliers and only sampling data in regions where overplotting is expected.

The process is as follows:

1. find outliers using `MazamaRollUtils::findOutliers()`
2. create a subset consisting of only outliers
3. sample the remaining data
4. merge the outliers and sampled data

This algorithm works best when the *mts* object has only one or two timeseries.

The `width` and `thresholdMin` parameters determine the number of outliers detected. For hourly data, a width of 5 and a `thresholdMin` of 3 or 4 seem to find many visually obvious outliers.

Users attempting to optimize plotting speed for lengthy time series are encouraged to experiment with these two parameters along with `sampleSize` and review the results visually.

See `MazamaRollUtils::findOutliers()`.

mts_select

*Reorder and subset time series within an mts time series object***Description**

This function acts similarly to `dplyr::select()` working on `mts$data`. The returned *mts* object will contain only those time series identified by `deviceDeploymentID` in the order specified.

This can be used to specify a preferred order and is helpful when using faceted plot functions based on `ggplot` such as those found in the [AirMonitorPlots](#) package.

Usage

```
mts_select(mts = NULL, deviceDeploymentID = NULL)
```

Arguments

`mts` *mts* object.
`deviceDeploymentID`
 Vector of timeseries unique identifiers.

Value

A reordered (subset) of the incoming *mts* time series object. (A list with meta and data dataframes.)

See Also

[mts_selectWhere](#)

Examples

```
library(MazamaTimeSeries)

# Filter for "El Monte"
El_Monte <-
  example_mts %>%
  mts_filterMeta(communityRegion == "El Monte")

ids <- El_Monte$meta$deviceDeploymentID
rev_ids <- rev(ids)

print(ids)
print(rev_ids)

rev_El_Monte <-
  example_mts %>%
  mts_select(rev_ids)

print(rev_El_Monte$meta$deviceDeploymentID)
```

mts_selectWhere	<i>Data-based subsetting of time series within an mts object.</i>
-----------------	---

Description

Subsetting of *mts* acts similarly to `tidyselect::where()` working on `mts$data`. The returned *mts* object will contain only those time series where FUN applied to the time series data returns TRUE.

Usage

```
mts_selectWhere(mts, FUN)
```

Arguments

<code>mts</code>	<i>mts</i> object.
<code>FUN</code>	A function applied to time series data that returns TRUE or FALSE.

Value

A subset of the incoming *mts* object. (A list with meta and data dataframes.)

See Also

[mts_select](#)

Examples

```
library(MazamaTimeSeries)

# Show all Camp_Fire locations
Camp_Fire$meta$locationName

# Set a threshold
threshold <- 500

# Find time series with data at or above this threshold
worst_sites <-
  Camp_Fire %>%
  mts_selectWhere(
    function(x) { any(x >= threshold, na.rm = TRUE) }
  )

# Show the worst locations
worst_sites$meta$locationName
```

mts_setTimeAxis*Extend/contract mts time series to new start and end times*

Description

Extends or contracts the time range of an *mts* object by adding/removing time steps at the start and end and filling any new time steps with missing values. The resulting time axis is guaranteed to be a regular, hourly axis with no gaps using the same timezone as the incoming *mts* object. This is useful when you want to place separate *mts* objects on the same time axis for plotting.

Dates can be anything that is understood by `MazamaCoreUtils::parseDatetime()` including either of the following recommended formats:

- "YYYYmmdd"
- "YYYY-mm-dd"

Timezone determination precedence assumes that if you are passing in POSIXct values then you know what you are doing:

1. get timezone from startdate if it is POSIXct
2. use passed in timezone
3. get timezone from mts

If either startdate or enddate is missing, the start or end of the timeseries in mts will be used.

If neither startdate nor enddate is a POSIXct value AND no timezone is supplied, the timezone will be inferred from the most common timezone found in mts.

Usage

```
mts_setTimeAxis(mts = NULL, startdate = NULL, enddate = NULL, timezone = NULL)
```

Arguments

mts	<i>mts</i> object.
startdate	Desired start date (ISO 8601).
enddate	Desired end date (ISO 8601).
timezone	Olson timezone used to interpret startdate and enddate.

Value

The incoming *mts* time series object defined on a new time axis. (A list with meta and data dataframes.)

Examples

```
library(MazamaTimeSeries)

# Default range
range(example_mts$data$datetime)

# One-sided extend with user specified timezone
example_mts %>%
  mts_setTimeAxis(enddate = 20190815, timezone = "UTC") %>%
  mts_extractData() %>%
  dplyr::pull(datetime) %>%
  range()

# Two-sided extend with user specified timezone
example_mts %>%
  mts_setTimeAxis(20190615, 20190815, timezone = "UTC") %>%
  mts_extractData() %>%
  dplyr::pull(datetime) %>%
  range()

# Two-sided extend without timezone (uses timezone from mts$meta$timezone)
example_mts %>%
  mts_setTimeAxis(20190615, 20190815) %>%
  mts_extractData() %>%
  dplyr::pull(datetime) %>%
  range()
```

mts_slice_head

Subset time series based on their position

Description

An *mts* object is reduced so as to contain only the first or last *n* timeseries. These functions work similarly to `dplyr::slice_head` and `dplyr::slice_tail` but apply to both dataframes in the *mts* object.

This is primarily useful when the *mts* object has been ordered by a previous call to `mts_arrange` or by some other means.

`slice_head()` selects the first and `slice_tail()` the last timeseries in the object.

Usage

```
mts_slice_head(mts, n = 5)
```

```
mts_slice_tail(mts, n = 5)
```

Arguments

`mts` *mts* object.

`n` Number of rows of `mts$meta` to select.

Value

A subset of the incoming *mts* time series object. (A list with meta and data dataframes.)

Examples

```
library(MazamaTimeSeries)

# Find lowest elevation sites
Camp_Fire %>%
  mts_filterMeta(!is.na(elevation)) %>%
  mts_arrange(elevation) %>%
  mts_slice_head(n = 5) %>%
  mts_extractMeta() %>%
  dplyr::select(elevation, locationName)

# Find highest elevation sites
Camp_Fire %>%
  mts_filterMeta(!is.na(elevation)) %>%
  mts_arrange(elevation) %>%
  mts_slice_tail(n = 5) %>%
  mts_extractMeta() %>%
  dplyr::select(elevation, locationName)
```

<code>mts_summarize</code>	<i>Create summary time series for an mts time series object</i>
----------------------------	---

Description

Individual time series in `mts$data` are grouped by `unit` and then summarized using FUN.

The most typical use case is creating daily averages where each day begins at midnight. This function interprets times using the `mts$data$datetime` `tz` attribute so be sure that is set properly.

Day boundaries are calculated using the specified `timezone` or, if `NULL`, the most common (hopefully only!) time zone found in `mts$meta$timezone`. Leaving `timezone = NULL`, the default, results in "local time" date filtering which is the most common use case.

Usage

```
mts_summarize(
  mts,
  timezone = NULL,
  unit = c("day", "week", "month", "year"),
```

```

    FUN = NULL,
    ...,
    minCount = NULL
  )

```

Arguments

<code>mts</code>	<i>mts</i> object.
<code>timezone</code>	Olson timezone used to interpret dates.
<code>unit</code>	Unit used to summarize by (e.g. "day").
<code>FUN</code>	Function used to summarize time series.
<code>...</code>	Additional arguments to be passed to FUN (_e.g._ <code>na.rm = TRUE</code>).
<code>minCount</code>	Minimum number of valid data records required to calculate summaries. Time periods with fewer valid records will be assigned NA.

Value

An *mts* time series object containing daily (or other) statistical summaries. (A list with meta and data dataframes.)

Note

Because the returned *mts* object is defined on a daily axis in a specific time zone, it is important that the incoming *mts* contain timeseries associated with a single time zone.

Examples

```

library(MazamaTimeSeries)

daily <-
  mts_summarize(
    mts = Carmel_Valley,
    timezone = NULL,
    unit = "day",
    FUN = mean,
    na.rm = TRUE,
    minCount = 18
  )

# Daily means
head(daily$data)

```

mts_trim	<i>Trim mts time series by removing missing values</i>
----------	--

Description

Trims the time range of an *mts* object by removing time steps from the start and end that contain only missing values.

Usage

```
mts_trim(mts = NULL)
```

Arguments

mts *mts* object.

Value

A subset of the incoming *mts* time series object. (A list with meta and data dataframes.)

Examples

```
library(MazamaTimeSeries)

# Untrimmed range
range(example_mts$data$datetime)

# Replace the first 50 data values for all non-"datetime" columns
example_mts$data[1:50, -1] <- NA

# Trimmed range
mts_trimmed <- mts_trim(example_mts)
range(mts_trimmed$data$datetime)
```

mts_trimDate	<i>Trim mts time series object to full days</i>
--------------	---

Description

Trims the date range of an *mts* object to local time date boundaries which are within the time range of the *mts* object. This has the effect of removing partial-day data records at the start and end of the timeseries and is useful when calculating full-day statistics.

By default, multi-day periods of all-missing data at the beginning and end of the timeseries are removed before trimming to date boundaries. If `trimEmptyDays = FALSE` all records are retained except for partial days beyond the first and after the last date boundary.

Day boundaries are calculated using the specified `timezone` or, if `NULL`, `mts$meta$timezone`. Leaving `timezone = NULL`, the default, results in "local time" date filtering which is the most common use case.

Usage

```
mts_trimDate(mts = NULL, timezone = NULL, trimEmptyDays = TRUE)
```

Arguments

<code>mts</code>	<i>mts</i> object.
<code>timezone</code>	Olson timezone used to interpret dates.
<code>trimEmptyDays</code>	Logical specifying whether to remove days with no data at the beginning and end of the time range.

Value

A subset of the incoming *mts* time series object. (A list with meta and data dataframes.)

Examples

```
library(MazamaTimeSeries)

UTC_week <- mts_filterDate(
  example_mts,
  startdate = 20190703,
  enddate = 20190706,
  timezone = "UTC"
)

# UTC day boundaries
range(UTC_week$data$datetime)

# Trim to local time day boundaries
local_week <- mts_trimDate(UTC_week)
range(local_week$data$datetime)
```

requiredMetaNames	<i>Required columns for the 'meta' dataframe</i>
-------------------	--

Description

The 'meta' dataframe found in *sts* and *mts* objects is required to have a minimum set of information for proper functioning of the package. The names of these columns are specified in `requiredMetaNames` and include:

- `deviceDeploymentID` – unique identifier (see [MazmaLocationUtils](#))
- `deviceID` – device identifier
- `locationID` – location identifier (see [MazmaLocationUtils](#))
- `locationName` – English language name

- longitude – decimal degrees E
- latitude – decimal degrees N
- elevation – elevation of station in m
- countryCode – ISO 3166-1 alpha-2
- stateCode – ISO 3166-2 alpha-2
- timezone – Olson time zone

Usage

requiredMetaNames

Format

A vector with 10 elements

Details

requiredMetaNames

sts_check	<i>Check sts object for validity</i>
-----------	--------------------------------------

Description

Checks on the validity of an *sts* object. If any test fails, this function will stop with a warning message.

Usage

```
sts_check(sts)
```

Arguments

sts *sts* object.

Value

Returns TRUE invisibly if the *sts* object is valid.

See Also

[sts_isValid](#)

Examples

```
library(MazamaTimeSeries)

sts_check(example_sts)

# This would throw an error
if ( FALSE ) {

  broken_sts <- example_sts
  names(broken_sts) <- c('meta', 'bop')
  sts_check(broken_sts)

}
```

sts_combine

Combine multiple sts time series objects

Description

Create a merged timeseries using of any number of *sts* objects for a single sensor. If *sts* objects are non-contiguous, the resulting *sts* will have gaps.

An error is generated if the incoming *sts* objects have non-identical deviceDeploymentIDs.

Usage

```
sts_combine(..., replaceMeta = FALSE)
```

Arguments

... Any number of valid SingleTimeSeries *sts* objects associated with a single deviceDeploymentID.
 replaceMeta Logical specifying whether to allow replacement of metadata.

Value

A SingleTimeSeries *sts* time series object containing records from all incoming *sts* time series objects. (A list with meta and data dataframes.)

Note

Data are combined with a "later is better" sensibility where any data overlaps exist. To handle this, incoming *sts* objects are first split into "shared" and "unshared" parts.

Any "shared" parts are ordered based on the time stamp of their last record. Then `dplyr::distinct()` is used to remove records with duplicate datetime fields. Any data records found in "later" *sts* objects are preferentially retained before the "shared" data are finally reordered by ascending datetime.

The final step is combining the "shared" and "unshared" parts.

Examples

```
library(MazamaTimeSeries)

aug01_08 <-
  example_sts %>%
  sts_filterDate(20180801, 20180808)

aug15_22 <-
  example_sts %>%
  sts_filterDate(20180815, 20180822)

aug01_22 <- sts_combine(aug01_08, aug15_22)

plot(aug01_22$data$datetime)
```

sts_distinct	<i>Retain only distinct data records in sts\$data</i>
--------------	---

Description

Three successive steps are used to guarantee that the datetime axis contains no repeated values:

1. remove any duplicate records
2. guarantee that rows are in datetime order
3. average together fields for any remaining records that share the same datetime

Usage

```
sts_distinct(sts)
```

Arguments

sts sts object

Value

An sts object where each record is associated with a unique time. (A list with meta and data dataframes.)

sts_extractDataFrame	<i>Extract dataframes from sts objects</i>
----------------------	--

Description

These functions are convenient wrappers for extracting the dataframes that comprise a *sts* object. These functions are designed to be useful when manipulating data in a pipeline using %>%.

Below is a table showing equivalent operations for each function.

sts_extractData(sts) is equivalent to sts\$data.

sts_extractMeta(sts) is equivalent to sts\$meta.

Usage

```
sts_extractData(sts)
```

```
sts_extractMeta(sts)
```

Arguments

sts *sts* object to extract dataframe from.

Value

A dataframe from the *sts* object.

sts_filter	<i>General purpose data filtering for sts time series objects</i>
------------	---

Description

A generalized data filter for *sts* objects to choose rows/cases where conditions are true. Multiple conditions are combined with & or separated by a comma. Only rows where the condition evaluates to TRUE are kept. Rows where the condition evaluates to NA are dropped.

If an empty *sts* object is passed in, it is immediately returned, allowing for multiple filtering steps to be piped together and only checking for an empty *sts* object at the end of the pipeline.

Usage

```
sts_filter(sts, ...)
```

Arguments

sts *sts* object.

... Logical predicates defined in terms of the variables in sts\$data.

Value

A subset of the incoming sts time series object. (A list with meta and data dataframes.)

Note

Filtering is done on values in sts\$data.

See Also

[sts_filterDate](#)

[sts_filterDatetime](#)

Examples

```
library(MazamaTimeSeries)

unhealthy <- sts_filter(example_sts, pm25_A > 55.5, pm25_B > 55.5)
head(unhealthy$data)
```

sts_filterDate	<i>Date filtering for sts time series objects</i>
----------------	---

Description

Subsets a MazamaSingleTimeseries object by date. This function always filters to day-boundaries. For sub-day filtering, use sts_filterDatetime().

Dates can be anything that is understood by MazamaCoreUtils::parseDatetime() including either of the following recommended formats:

- "YYYYmmdd"
- "YYYY-mm-dd"

Timezone determination precedence assumes that if you are passing in POSIXct values then you know what you are doing.

1. get timezone from startdate if it is POSIXct
2. use passed in timezone
3. get timezone from sts

Usage

```
sts_filterDate(
  sts = NULL,
  startdate = NULL,
  enddate = NULL,
  timezone = NULL,
  unit = "sec",
  ceilingStart = FALSE,
  ceilingEnd = FALSE
)
```

Arguments

sts	MazamaSingleTimeseries <i>sts</i> object.
startdate	Desired start datetime (ISO 8601).
enddate	Desired end datetime (ISO 8601).
timezone	Olson timezone used to interpret dates.
unit	Units used to determine time at end-of-day.
ceilingStart	Logical instruction to apply ceiling_date to the startdate rather than floor_date
ceilingEnd	Logical instruction to apply ceiling_date to the enddate rather than floor_date

Value

A subset of the incoming *sts* time series object. (A list with meta and data dataframes.)

Note

The returned data will run from the beginning of startdate until the **beginning** of enddate – *i.e.* no values associated with enddate will be returned. The exception being when enddate is less than 24 hours after startdate. In that case, a single day is returned.

See Also

[sts_filter](#)
[sts_filterDatetime](#)

Examples

```
library(MazamaTimeSeries)

example_sts %>%
  sts_filterDate(startdate = 20180808, enddate = 20180815) %>%
  sts_extractData() %>%
  head()
```

 sts_filterDatetime *Datetime filtering for sts time series objects*

Description

Subsets a MazamaSingleTimeseries object by datetime. This function allows for sub-day filtering as opposed to sts_filterDate() which always filters to day-boundaries.

Datetimes can be anything that is understood by MazamaCoreUtils::parseDatetime(). For non-POSIXct values, the recommended format is "YYYY-mm-dd HH:MM:SS".

Timezone determination precedence assumes that if you are passing in POSIXct values then you know what you are doing.

1. get timezone from startdate if it is POSIXct
2. use passed in timezone
3. get timezone from sts

Usage

```
sts_filterDatetime(
  sts = NULL,
  startdate = NULL,
  enddate = NULL,
  timezone = NULL,
  unit = "sec",
  ceilingStart = FALSE,
  ceilingEnd = FALSE,
  includeEnd = FALSE
)
```

Arguments

sts	MazamaSingleTimeseries sts object.
startdate	Desired start datetime (ISO 8601).
enddate	Desired end datetime (ISO 8601).
timezone	Olson timezone used to interpret dates.
unit	Units used to determine time at end-of-day.
ceilingStart	Logical instruction to apply ceiling_date to the startdate rather than floor_date
ceilingEnd	Logical instruction to apply ceiling_date to the enddate rather than floor_date
includeEnd	Logical specifying that records associated with enddate should be included.

Value

A subset of the incoming sts time series object. (A list with meta and data dataframes.)

Note

The returned sts object will contain data running from the beginning of startdate until the **beginning** of enddate – *i.e.* no values associated with enddate will be returned. To include enddate you can specify includeEnd = TRUE.

See Also

[sts_filter](#)
[sts_filterDate](#)

Examples

```
library(MazamaTimeSeries)

example_sts %>%
  sts_filterDatetime(
    startdate = "2018-08-08 06:00:00",
    enddate = "2018-08-14 18:00:00"
  ) %>%
  sts_extractData() %>%
  head()
```

sts_isEmpty	<i>Test for empty sts object</i>
-------------	----------------------------------

Description

Convenience function for `nrow(sts$data) == 0`. This makes for more readable code in functions that need to test for this.

Usage

```
sts_isEmpty(sts)
```

Arguments

sts *sts* object

Value

TRUE if no data exist in sts, FALSE otherwise.

Examples

```
library(MazamaTimeSeries)

sts_isEmpty(example_sts)
```

`sts_isValid`*Test sts object for correct structure*

Description

The sts is checked for the presence of core meta and data columns.

Core meta columns include:

- deviceDeploymentID – unique identifier (see [MazmaLocationUtils](#))
- deviceID – device identifier
- locationID – location identifier (see [MazmaLocationUtils](#))
- locationName – English language name
- longitude – decimal degrees E
- latitude – decimal degrees N
- elevation – elevation of station in m
- countryCode – ISO 3166-1 alpha-2
- stateCode – ISO 3166-2 alpha-2
- timezone – Olson time zone

Core data columns include:

- datetime – measurement time (UTC)

Usage

```
sts_isValid(sts = NULL, verbose = FALSE)
```

Arguments

<code>sts</code>	<i>sts</i> object
<code>verbose</code>	Logical specifying whether to produce detailed warning messages.

Value

TRUE if sts has the correct structure, FALSE otherwise.

Examples

```
library(MazamaTimeSeries)

sts_isValid(example_sts)
```

sts_summarize

Create summary time series for an sts time series object

Description

Columns of numeric data in `sts$data` are grouped by unit and then summarized using `FUN`.

Columns with non-numeric data are summarized by just picking the first occurrence in each unit. This preserves the utility of columns containing repeated metadata.

The most typical use case is creating daily averages where each day begins at midnight. Day boundaries are calculated using the specified `timezone` or, if `NULL`, the time zone found in `sts$meta$timezone[1]`. Leaving `timezone = NULL`, the default, results in "local time" date filtering which is the most common use case.

Usage

```
sts_summarize(
  sts,
  timezone = NULL,
  unit = c("day", "week", "month", "year"),
  FUN = NULL,
  ...,
  minCount = NULL
)
```

Arguments

<code>sts</code>	<code>sts</code> object.
<code>timezone</code>	Olson timezone used to interpret dates.
<code>unit</code>	Unit used to summarize by (e.g. "day").
<code>FUN</code>	Function used to summarize time series.
<code>...</code>	Additional arguments to be passed to <code>FUN</code> (e.g. <code>na.rm = TRUE</code>).
<code>minCount</code>	Minimum number of valid data records required to calculate summaries. Time periods with fewer valid records will be assigned NA.

Value

An `sts` time series object containing daily (or other) statistical summaries. (A list with meta and data dataframes.)

sts_trimDate	<i>Trim sts time series object to full days</i>
--------------	---

Description

Trims the date range of a *sts* object to local time date boundaries which are *within* the range of data. This has the effect of removing partial-day data records at the start and end of the timeseries and is useful when calculating full-day statistics.

Day boundaries are calculated using the specified timezone or, if NULL, from `sts$meta$timezone`.

Usage

```
sts_trimDate(sts = NULL, timezone = NULL)
```

Arguments

<code>sts</code>	SingleTimeSeries <i>sts</i> object.
<code>timezone</code>	Olson timezone used to interpret dates.

Value

A subset of the incoming *sts* time series object. (A list with meta and data dataframes.)

Examples

```
library(MazamaTimeSeries)

UTC_week <- sts_filterDate(
  example_sts,
  startdate = 20180808,
  enddate = 20180815,
  timezone = "UTC"
)

# UTC day boundaries
head(UTC_week$data)

# Trim to local time day boundaries
local_week <- sts_trimDate(UTC_week)
head(local_week$data)
```

timeInfo	<i>Get time related information</i>
----------	-------------------------------------

Description

Calculate the local time at the target location, as well as sunrise, sunset and solar noon times, and create several temporal masks.

The returned dataframe will have as many rows as the length of the incoming UTC time vector and will contain the following columns:

- localStdTime_UTC – UTC representation of local **standard** time
- daylightSavings – logical mask = TRUE if daylight savings is in effect
- localTime – local clock time
- sunrise – time of sunrise on each localTime day
- sunset – time of sunset on each localTime day
- solarnoon – time of solar noon on each localTime day
- day – logical mask = TRUE between sunrise and sunset
- morning – logical mask = TRUE between sunrise and solarnoon
- afternoon – logical mask = TRUE between solarnoon and sunset
- night – logical mask = opposite of day

Usage

```
timeInfo(time = NULL, longitude = NULL, latitude = NULL, timezone = NULL)
```

Arguments

time	POSIXct vector with specified timezone,
longitude	Longitude of the location of interest.
latitude	Latitude of the location of interest.
timezone	Olson timezone at the location of interest.

Details

NOAA used the reference below to develop their Sunrise/Sunset

<https://gml.noaa.gov/grad/solcalc/sunrise.html> and Solar Position

<https://gml.noaa.gov/grad/solcalc/azel.html> Calculators. The algorithms include corrections for atmospheric refraction effects.

Input can consist of one location and at least one POSIXct times, or one POSIXct time and at least one location. *solarDep* is recycled as needed.

Do not use the daylight savings time zone string for supplying *dateTime*, as many OS will not be able to properly set it to standard time when needed.

The localStdTime_UTC column in the returned dataframe is primarily for internal use and provides an important tool for creating LST daily averages and LST axis labeling.

Value

A dataframe with times and masks.

Attribution

Internal functions used for ephemerides calculations were copied verbatim from the now deprecated **maptools** package source code in an effort to reduce the number of package dependencies.

Warning

Compared to NOAA's original Javascript code, the sunrise and sunset estimates from this translation may differ by +/- 1 minute, based on tests using selected locations spanning the globe. This translation does not include calculation of prior or next sunrises/sunsets for locations above the Arctic Circle or below the Antarctic Circle.

Local Standard Time

US EPA regulations mandate that daily averages be calculated based on "Local Standard Time" (LST) (*i.e. never shifting to daylight savings*). To ease work in a regulatory context, LST times are included in the returned dataframe.

References

Meeus, J. (1991) *Astronomical Algorithms*. Willmann-Bell, Inc.

Note

NOAA notes that "for latitudes greater than 72 degrees N and S, calculations are accurate to within 10 minutes. For latitudes less than +/- 72 degrees accuracy is approximately one minute."

Author(s)

Sebastian P. Luque <spluque@gmail.com>, translated from Greg Pelletier's <gpel461@ecy.wa.gov> VBA code (available from <https://ecology.wa.gov/Research-Data/Data-resources/Models-spreadsheets/Modeling-the-environment/Models-tools-for-TMDLs>), who in turn translated it from original Javascript code by NOAA (see Details). Roger Bivand <roger.bivand@nhh.no> adapted the code to work with **sp** classes. Jonathan Callahan <jonathan.callahan@gmail.com> adapted the source code from the **maptools** package to work with **MazamaTimeSeries** classes.

Examples

```
library(MazamaTimeSeries)

Carmel <-
  Carmel_Valley %>%
  mts_filterDate(20160801, 20160810)

# Create timeInfo object for this monitor
ti <- timeInfo(
  Carmel$data$datetime,
```

```
Carmel$meta$longitude,
Carmel$meta$latitude,
Carmel$meta$timezone
)

t(ti[6:9,])

# Subset the data based on day/night masks
data_day <- Carmel$data[ti$day,]
data_night <- Carmel$data[ti$night,]

# Build two monitor objects
Carmel_day <- list(meta = Carmel$meta, data = data_day)
Carmel_night <- list(meta = Carmel$meta, data = data_night)

# Plot them
plot(Carmel_day$data, pch = 8, col = 'goldenrod')
points(Carmel_night$data, pch = 16, col = 'darkblue')
```

Index

* datasets

- Camp_Fire, [3](#)
- Carmel_Valley, [4](#)
- example_mts, [4](#)
- example_raws, [5](#)
- example_sts, [6](#)
- requiredMetaNames, [30](#)

arrange, [7](#)

Camp_Fire, [3](#)

Carmel_Valley, [4](#)

ceiling_date, [14](#), [16](#), [36](#), [37](#)

dplyr::slice_head, [26](#)

dplyr::slice_tail, [26](#)

example_mts, [4](#)

example_raws, [5](#)

example_sts, [6](#)

floor_date, [14](#), [16](#), [36](#), [37](#)

MazamaTimeSeries, [6](#)

MazamaTimeSeries-package
(MazamaTimeSeries), [6](#)

mts_arrange, [7](#), [26](#)

mts_check, [8](#), [20](#)

mts_collapse, [9](#)

mts_combine, [10](#)

mts_distinct, [11](#)

mts_extractData (mts_extractDataFrame),
[12](#)

mts_extractDataFrame, [12](#)

mts_extractMeta (mts_extractDataFrame),
[12](#)

mts_filterData, [13](#), [16](#), [17](#)

mts_filterDate, [14](#), [16](#)

mts_filterDatetime, [15](#)

mts_filterMeta, [13](#), [16](#), [17](#)

mts_getDistance, [18](#)

mts_isEmpty, [19](#)

mts_isValid, [8](#), [19](#)

mts_pull, [20](#)

mts_sample, [21](#)

mts_select, [23](#), [24](#)

mts_selectWhere, [23](#), [24](#)

mts_setTimeAxis, [15](#), [16](#), [25](#)

mts_slice_head, [26](#)

mts_slice_tail (mts_slice_head), [26](#)

mts_summarize, [27](#)

mts_trim, [29](#)

mts_trimDate, [29](#)

requiredMetaNames, [30](#)

set.seed, [22](#)

sts_check, [31](#)

sts_combine, [32](#)

sts_distinct, [33](#)

sts_extractData (sts_extractDataFrame),
[34](#)

sts_extractDataFrame, [34](#)

sts_extractMeta (sts_extractDataFrame),
[34](#)

sts_filter, [34](#), [36](#), [38](#)

sts_filterDate, [35](#), [35](#), [38](#)

sts_filterDatetime, [35](#), [36](#), [37](#)

sts_isEmpty, [38](#)

sts_isValid, [31](#), [39](#)

sts_summarize, [40](#)

sts_trimDate, [41](#)

timeInfo, [42](#)