

Package ‘MultiClassROC’

July 21, 2025

Type Package

Title ROC Curves for Multi-Class Analysis

Version 0.1.0

Description Function `multiroc()` can be used for computing and visualizing Receiver Operating Characteristics (ROC) and Area Under the Curve (AUC) for multi-class classification problems. It supports both One-vs-One approach by M.Bishop, C. (2006, ISBN:978-0-387-31073-2) and One-vs-All approach by Murphy P., K. (2012, ISBN:9780262018029).

License GPL-3

Encoding UTF-8

RoxygenNote 7.2.3

Imports `ggplot2`, `pROC`

NeedsCompilation no

Author Marton Varga [cre, aut]

Maintainer Marton Varga <vargamarton0723@gmail.com>

Repository CRAN

Date/Publication 2023-07-21 07:42:35 UTC

Contents

multiroc	1
Index	3

multiroc	<i>ROC Curves for Multi-Class Analysis</i>
----------	--

Description

Function ‘`multiroc`’ can be used for computing and visualizing Receiver Operating Characteristics (ROC) and Area Under the Curve (AUC) for multi-class classification problems. It supports both one-vs-one and one-vs-all approaches.

Usage

```
multiroc(y, x, k, type = c("OvO", "OvA"), plot = TRUE, data)
```

Arguments

y	A string, dependent variable
x	A vector of strings, independent variables
k	The number of categories
type	A string, "OvO" for one-vs-one, "OvA" for one-vs-all approach
plot	A logical, TRUE for the plot of the curves, FALSE for the average AUC
data	A data frame, the dataset to use

Value

plot with ROC curves using ggroc, pROC (if plot=TRUE) or the average AUC (if plot=FALSE)

Examples

```
multiroc(y="Species",
         x=c("Petal.Width", "Petal.Length", "Sepal.Width", "Sepal.Length"),
         k=3, type="OvA",
         plot=TRUE,
         data=iris)
multiroc(y="Species",
         x=c("Petal.Width", "Petal.Length", "Sepal.Width", "Sepal.Length"),
         k=3,
         type="OvO",
         plot=FALSE,
         data=iris)
```

Index

multiroc, 1