

Package ‘NHSRplotthedots’

July 21, 2025

Type Package

Title Draw XmR Charts for NHSE/I 'Making Data Count' Programme

Version 0.1.0

Maintainer Christopher Reading <christopher.reading1@nhs.net>

Description Provides tools for drawing Statistical Process Control (SPC) charts. This package supports the NHSE/I programme 'Making Data Count', and allows users to draw XmR charts, use change points and apply rules with summary indicators for when rules are breached.

URL <https://nhs-r-community.github.io/NHSRplotthedots/>

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.1.2

Imports ggplot2, scales, dplyr, rlang, crayon, utils, NHSRdatasets, assertthat, grid

Suggests covr, lintr, testthat (>= 3.0.0), rmarkdown, knitr, mockery, withr, spelling

VignetteBuilder knitr

Config/testthat/edition 3

Language en-US

NeedsCompilation no

Author Christopher Reading [cre, aut],
Simon Wellesley-Miller [aut],
Zoë Turner [aut] (ORCID: <<https://orcid.org/0000-0003-1033-9158>>),
Tom Jemmett [aut] (ORCID: <<https://orcid.org/0000-0002-6943-2990>>),
Tom Smith [aut],
Chris Mainey [aut] (ORCID: <<https://orcid.org/0000-0002-3018-6171>>),
John MacKintosh [aut],
NHS-R community [cph]

Repository CRAN

Date/Publication 2021-11-03 20:20:10 UTC

Contents

| | |
|-----------------------------|----------|
| ptd_create_ggplot | 2 |
| ptd_rebase | 3 |
| ptd_spc | 4 |
| ptd_spc_colours | 6 |
| ptd_target | 7 |
| Index | 9 |

| | |
|-------------------|-----------------------|
| ptd_create_ggplot | <i>Create ggplot2</i> |
|-------------------|-----------------------|

Description

Creates a ggplot2 object using the parameters passed in.

Usage

```
ptd_create_ggplot(  
  x,  
  point_size = 4,  
  percentage_y_axis = FALSE,  
  main_title,  
  x_axis_label,  
  y_axis_label,  
  fixed_x_axis_multiple = TRUE,  
  fixed_y_axis_multiple = TRUE,  
  x_axis_date_format = "%d/%m/%y",  
  x_axis_breaks = NULL,  
  y_axis_breaks = NULL,  
  icons_size = 8L,  
  icons_position = c("top right", "bottom right", "bottom left", "top left", "none"),  
  colours = ptd_spc_colours(),  
  theme_override = NULL,  
  break_lines = c("both", "limits", "process", "none"),  
  ...  
)
```

Arguments

- x an object created by [ptd_spc\(\)](#)
- point_size Specify the plotting point size for the ggplot output. Default is 2.5.
- percentage_y_axis Specify whether the y axis values are percentages. Accepted values are TRUE for percentage y axis, FALSE for integer y axis. Defaults to FALSE.
- main_title Specify a character string value for the ggplot title.

| | |
|-----------------------|--|
| x_axis_label | Specify a character string value for the x axis title. |
| y_axis_label | Specify a character string value for the y axis title. |
| fixed_x_axis_multiple | Specify whether, if producing a faceted spc, x axis should be fixed for all facet plots. Accepted values are TRUE for fixed x axes or FALSE for individual x axes. |
| fixed_y_axis_multiple | Specify whether, if producing a faceted spc, y axis should be fixed for all facet plots. Accepted values are TRUE for fixed y axes or FALSE for individual y axes. |
| x_axis_date_format | Specify how dates on the x axis should be displayed. Format should be provided as a character string using 'd m Y' etc syntax. |
| x_axis_breaks | Specify an interval value for breaks on the x axis. Value should be a character string expressing interval length and type, e.g. "3 months", "7 days". |
| y_axis_breaks | Specify an interval value for breaks on the y axis. Value should be a numeric vector of length 1, either an integer for integer scales or a decimal value for percentage scales. This option is ignored if faceting is in use. |
| icons_size | The size of the icons, defined in terms of font size. Defaults to 8. |
| icons_position | Where to show the icons, either "top right" (default), "bottom right", "bottom left", "top left", or "none". |
| colours | Specify the colours to use in the plot, use the ptd_spc_colours() function to change defaults. |
| theme_override | Specify a list containing ggplot theme elements which can be used to override the default appearance of the plot. |
| break_lines | whether to break lines when a rebase happens. Defaults to "both", but can break just "limits" lines, "process" lines, or "none". |
| ... | currently ignored |

Value

The ggplot2 object

| | |
|------------|---------------|
| ptd_rebase | <i>Rebase</i> |
|------------|---------------|

Description

Produces an object that can be used for rebasing an SPC chart. This method provides two different ways to rebase:

1. You can either provide a single vector of dates, which will rebase every facet of an SPC with the same dates
2. You can provide named vectors of dates, where the names correspond to the names of the facets, in order to rebase a faceted chart

Usage

```
ptd_rebase(...)
```

Arguments

... either a single vector of dates, or, named vectors of dates. See examples.

Value

a list

Examples

```
# if you aren't using a faceted chart, or you want to rebase each facet at the same dates, then
# you can simply call this method with a vector of dates. For example, to rebase on the 1^st^
# January 2020 and 22^nd^ March 2020:
```

```
ptd_rebase(as.Date(c("2020-01-01", "2020-03-22")))
```

```
# if you are using a faceted chart, and wish to rebase each facet with different dates, then
# you can call this method, naming each vector of dates with the name of the facet. If there are
# facet's that you don't need to rebase you can simply ignore them. For example, if you had a
# chart with facets "a", "b", and "c", and you wanted to rebase "a" on the 1^st^ January 2020,
# and "b" on the 22^nd^ March 2020:
```

```
ptd_rebase(
  "a" = as.Date("2020-01-01"),
  "b" = as.Date("2020-03-22")
)
```

ptd_spc

SPC Plotting Function

Description

ptd_spc returns a plot object or data table with SPC values using NHSI 'plot the dots' logic.

Usage

```
ptd_spc(
  .data,
  value_field,
  date_field,
  facet_field,
  rebase = ptd_rebase(),
  fix_after_n_points = NULL,
  improvement_direction = "increase",
  target = ptd_target(),
```

```

    trajectory,
    screen_outliers = TRUE
  )

```

Arguments

| | |
|------------------------------------|---|
| <code>.data</code> | A data frame containing a value field, a date field, and a category field (if for faceting). There should be no gaps in the time series for each category. |
| <code>value_field</code> | Specify the field name which contains the value data, to be plotted on y axis. Field name can be specified using non-standard evaluation (i.e. no quotation marks). |
| <code>date_field</code> | Specify the field name which contains the date data, to be plotted on x axis. Field name can be specified using non-standard evaluation (i.e. no quotation marks). |
| <code>facet_field</code> | Optional: Specify field name which contains a grouping/faceting variable. SPC logic will be applied to each group separately, with outputs combined. Currently accepts 1 variable only. Field name can be specified using non-standard evaluation (i.e. no quotation marks). |
| <code>rebase</code> | Specify a date vector of dates when to rebase, or, if <code>facet_field</code> is set, a named list of date vectors of when to rebase. Each item in the list should be named after the facet you wish to rebase. See ptd_rebase() . |
| <code>fix_after_n_points</code> | Specify a number points after which to fix SPC calculations. |
| <code>improvement_direction</code> | Specify whether process improvement is represented by an increase or decrease in measured variable, or is neutral. Accepted values are 'increase' for increase as improvement, 'decrease' for decrease as improvement, and 'neutral' where neither direction represents an improvement. Defaults to 'increase'. |
| <code>target</code> | Specify a single value, which will apply the same target to every facet of an SPC chart, or named values of targets, where the names correspond to the names of the facets, in order to have different targets for each facet. See ptd_target() . |
| <code>trajectory</code> | Specify a field name which contains a trajectory value. Field name can be specified using non-standard evaluation (i.e. no quotation marks). |
| <code>screen_outliers</code> | Whether we should screen for outliers or not when calculating the control limits. Defaults to TRUE. |

Details

This function is designed to produce consistent SPC charts across Information Department reporting, according to the 'plot the dots' logic produced by NHSI. The function can return either a plot or data frame.

Value

A `ggplot2` object of the spc charts. This will automatically print the plot, but can also be saved as an object if you want to manipulate it further.

Examples

```
library(NHSRdatasets)
library(dplyr)
data("ae_attendances")

# Pick a trust at random to look at their data for two years
trust1 <- subset(ae_attendances, org_code == "RJZ" & type == 1)

# Basic chart with improvement direction decreasing
ptd_spc(trust1,
  value_field = breaches, date_field = period,
  improvement_direction = "decrease"
)

# Pick a few trust, and plot individually using facet
# Also set the x-axis scale to vary for each and date groups to 3 months
orgs <- c("RAS", "RJZ", "RR1", "RJC", "RQ1")
trusts4 <- filter(ae_attendances, org_code %in% orgs, type == 1)

s <- ptd_spc(trusts4,
  value_field = breaches, date_field = period, facet_field = org_code,
  improvement_direction = "decrease"
)
plot(s, fixed_y_axis_multiple = FALSE, x_axis_breaks = "3 months")

# Save the first chart as an object this time then alter the ggplot theme
my_spc <- ptd_spc(trust1,
  value_field = "breaches", date_field = "period",
  improvement_direction = "decrease"
)

plot(my_spc) + ggplot2::theme_classic()
```

ptd_spc_colours

SPC Colours

Description

Produces a list of colours that controls the geoms in the plot

Usage

```
ptd_spc_colours(
  common_cause = "#7B7D7D",
  special_cause_improvement = "#289de0",
  special_cause_neutral = "#361475",
  special_cause_concern = "#fab428",
  value_line = "#7B7D7D",
  mean_line = "#000000",
```

```

    lpl = "#7B7D7D",
    upl = "#7B7D7D",
    target = "#de1b1b",
    trajectory = "#361475"
)

```

Arguments

| | | |
|-----------------------|--|------------------------|
| common_cause, | special_cause_improvement, | special_cause_neutral, |
| special_cause_concern | | |
| | the colour of the points | |
| value_line | the colour of the line joining the points | |
| mean_line | the colour of the "mean" (average) line | |
| lpl, upl | the colour the the lower and upper process limit lines | |
| target | the colour of the target line | |
| trajectory | the colour of the trajectory line | |

Value

a list of colours

| | |
|------------|---------------|
| ptd_target | <i>Target</i> |
|------------|---------------|

Description

Produces an object that can be used for adding Targets to an SPC chart. This method provides two different ways to add a target:

1. You can either provide a single value, which will apply the same target to every facet of an SPC
2. You can provide named values of targets, where the names correspond to the names of the facets, in order to have different targets for each facet

Usage

```
ptd_target(...)
```

Arguments

... either a single values, or, named values of targets. See examples.

Details

This function is a helper to provide data in the correct format for use with `ptd_spc()`. See **Value** section for details of return type. If you are trying to do something like `ptd_spc(list_of_values)` then you can skip using the function and just use `list_of_values`, so long as the list meets the requirements as listed above.

Value

returns either:

- a single numeric value, in this case all facets in the plot will use this target value
- a named list of single numeric values, where each item is named as for one of the facet's in the plot. If a facet isn't specified then it will not have a target

Examples

```
# if you aren't using a faceted chart, or you want to use the same target for each facet, you
# can simply call this method with a single value. For example, to use a target of 90%:

ptd_target(0.9)

# if you are using a faceted chart, and wish to use a different target for each facet, then you
# can call this method, naming each value with the name of the facet. Any facet that isn't listed
# will not have a target applied to it.

# For example, to apply a target of 25 to the "a" facet and 10 to the "b" facet:

ptd_target(
  "a" = 25,
  "b" = 10
)

# If you already have your data in a list, you do not need to use ptd_target(). But, if you
# wanted to check that your values are valid, you could call it like so:

my_targets <- list("a" = 25, "b" = 10)
do.call(ptd_target, my_targets)

# or, if your targets are in a numeric vector
my_targets <- c("a" = 25, "b" = 10)
do.call(ptd_target, as.list(my_targets))
```


Index

`ptd_create_ggplot`, [2](#)
`ptd_rebase`, [3](#)
`ptd_rebase()`, [5](#)
`ptd_spc`, [4](#)
`ptd_spc()`, [2](#)
`ptd_spc_colours`, [6](#)
`ptd_spc_colours()`, [3](#)
`ptd_target`, [7](#)
`ptd_target()`, [5](#)