

# Package ‘R2Addhaz’

July 21, 2025

**Type** Package

**Title** R2 Measure of Explained Variation under the Additive Hazards Model

**Version** 0.1.0

**Date** 2020-03-20

**Author** Denise Rava

**Maintainer** Denise Rava <drava@ucsd.edu>

**Description**  $R^2$  measure of explained variation under the semiparametric additive hazards model is estimated. The measure can be used as a measure of predictive capability and therefore it can be adopted in model selection process. Rava, D. and Xu, R. (2020) <[doi:10.48550/arXiv.2003.09460](https://doi.org/10.48550/arXiv.2003.09460)>.

**License** GPL-2

**Encoding** UTF-8

**LazyData** true

**RdMacros** Rdpack

**Imports** ahaz, pracma, zoo, caTools, survival, Rdpack (>= 0.7)

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2020-04-07 15:20:02 UTC

## Contents

|                    |   |
|--------------------|---|
| R2addhaz . . . . . | 2 |
| <b>Index</b>       | 3 |

R2addhaz

*Estimate R^2 for additive hazards model***Description**

The function computes R^2 measure of explained variation under the semiparametric additive hazards model.

**Usage**

```
R2addhaz(data)
```

**Arguments**

**data** a data.frame with survival data. The first column needs to be the censored failure time. The second column needs to be the event indicator, 1 if the event is observed, 0 if it is censored. The other columns are covariates.

**Details**

The semiparametric hazards model

$$\lambda(t|Z) = \lambda_0(t) + \beta Z$$

is fitted to the data. The R^2 measure of explained variation is then computed.

**Value**

**R** R^2 measure of explained variation.

**Author(s)**

Denise Rava

**References**

Rava, D., Xu, R. "Explained Variation under the Additive Hazards Model", March 2020, arXiv:2003.09460

**Examples**

```
Z=runif(100,0,sqrt(3)) #generate covariates
u=runif(100,0,1)
t=-log(u)/as.vector((1+Z)) #generate failure time
status=rep(1,100) #censoring indicator
sd<-as.data.frame(cbind(t,status,Z)) #data frame of survival data
R2addhaz(sd)
```

# Index

\* **~AdditiveHazardsModel**

R2addhaz, [2](#)

\* **~R2**

R2addhaz, [2](#)

R2addhaz, [2](#)