

Package ‘RImpact’

July 21, 2025

Type Package

Title Calculates Measures of Scholarly Impact

Version 1.0

Author John Ruscio

Maintainer John Ruscio <ruscio@tcnj.edu>

Description The metrics() function calculates measures of scholarly impact. These include conventional measures, such as the number of publications and the total citations to all publications, as well as modern and robust metrics based on the vector of citations associated with each publication, such as the h index and many of its variants or rivals. These methods are described in Ruscio et al. (2012) <[DOI:10.1080/15366367.2012.711147](https://doi.org/10.1080/15366367.2012.711147)>.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

NeedsCompilation no

Repository CRAN

Date/Publication 2018-10-31 12:40:03 UTC

Contents

GeometricMean	2
HarmonicMean	2
Metrics	3
Index	5

GeometricMean

GeometricMean

Description

Calculates the geometric mean (the n th root of the product of n values).

Usage

GeometricMean(x)

Arguments

x Vector of n values whose geometric mean is to be calculated.

Value

The geometric mean of x .

Author(s)

John Ruscio

References

Ruscio et al. (2012)

Examples

```
GeometricMean(c(1, 3, 9, 27, 81))
```

HarmonicMean

HarmonicMean

Description

Calculates the harmonic mean (the reciprocal of the arithmetic mean of the reciprocals of n values).

Usage

HarmonicMean(x)

Arguments

x Vector of n values whose harmonic mean is to be calculated.

Value

The harmonic mean of x .

Author(s)

John Ruscio

References

Ruscio et al. (2012)

Examples

```
HarmonicMean(c(1, 3, 9, 27, 81))
```

Metrics	<i>Metrics</i>
---------	----------------

Description

Measures scholarly impact using modern citation-based indices.

Usage

```
Metrics(citation.counts, publishing.age = 0, display = TRUE)
```

Arguments

<code>citation.counts</code>	Number of times each article has been cited. (vector)
<code>publishing.age</code>	Age of the first article author has published. (scalar)
<code>display</code>	Whether to display metrics (if TRUE, the default) or direct output to a file (if FALSE).

Value

<code>h.index</code>	h index, the largest number h such that at least h articles are cited h times each (Hirsch, 2005).
<code>tapered.h.index</code>	Tapered h index, credit decreases for citations farther from the origin (Anderson, Hankin, & Killworth, 2008).
<code>f.index</code>	f index, largest value f such that the harmonic mean of the f most highly cited articles is at least f (Tol, 2009).
<code>g.index</code>	g index, largest value g such that the mean citations for the g most highly cited articles is at least g (Egghe, 2006).

hg.index	hg index, geometric mean of h and g (Alonso, Cabrerizo, Herrera-Viedma, & Herrera, 2010).
a.index	a index, mean citations for the papers in Hirsch core (Jin, 2006).
m.index	m index, median citations for papers in Hirsch core (Bornmann, Mutz, Daniel, 2008).
r.index	r index, square root of citations for papers in Hirsch core (Jin, Liang, Rousseau, Egghe, 2007).
weighted.h.index	h index weighted by citation impact (Egghe & Rousseau, 2008).
q2.index	q2 index, geometric mean of h and m indexes (Cabrerizo, Alonso, Herrera-Viedma, & Herrera, 2010).
e.index	e index, excess citations for papers in Hirsch core (Zhang, 2009).
max.product	Maximum product index, maximum product of article's rank and citation count (Kosmulski, 2007).
sqrt.max.product	Rescales maximum product index from an area to a distance measure.
h2.index	h2 index, analogous to h index with more stringent criterion (Kosmulski, 2006).
m.quotient	m quotient, controlling h index for publishing age (Hirsch, 2005).
tapered.m.quotient	Controlling tapered h index for publishing age.

Author(s)

John Ruscio

References

Ruscio et al. (2012)

Examples

```
# Running the Metrics program with illustrative data from Ruscio et al. (2012)
x <- c(24, 18, 12, 8, 6, 5, 5, 4, 4, 3, 2, 2, 1, 1, 1, 0, 0, 0)
Metrics(x)
```

Index

GeometricMean, [2](#)

HarmonicMean, [2](#)

Metrics, [3](#)