

Package ‘Rspotify’

July 21, 2025

Type Package

Title Access to Spotify API

Version 0.1.2

Author Tiago Mendes Dantas

Maintainer Tiago Mendes Dantas <t.mendesdantas@gmail.com>

Description Provides an interface to the Spotify API <<https://developer.spotify.com/documentation/web-api/>>.

License GPL-2

Encoding UTF-8

LazyData true

RoxygenNote 6.1.0

Imports dplyr, plyr, httr, jsonlite, magrittr

NeedsCompilation no

Repository CRAN

Date/Publication 2018-08-13 14:10:12 UTC

Contents

getAlbum	2
getAlbumInfo	2
getAlbums	3
getArtist	3
getFeatures	4
getPlaylists	5
getPlaylistSongs	5
getRelated	6
getTopTracks	6
getTrack	7
getUser	7
searchArtist	8
searchPlaylist	8
searchTrack	9
spotifyOAuth	9

Index[11](#)

getAlbum	<i>Get the tracks from an Album</i>
----------	-------------------------------------

Description

Get Spotify catalog information about an album's tracks.

Usage

```
getAlbum(album_id, token)
```

Arguments

album_id	The Spotify ID for the album.
token	An OAuth token created with spotifyOAuth.

Value

get Album from an artist using their ID

getAlbumInfo	<i>Get additional album info</i>
--------------	----------------------------------

Description

function to get additional album info from an artist using the Album ID

Usage

```
getAlbumInfo(album_id, token)
```

Arguments

album_id	The Spotify ID for the album..
token	An OAuth token created with spotifyOAuth.

Value

'Get an Artist's Albums

getAlbums	<i>Get albums from an Artist</i>
-----------	----------------------------------

Description

function to get albums from an artist using their ID

Usage

```
getAlbums(artist_id, market = "US", token)
```

Arguments

artist_id	The Spotify ID for the artist.
market	Optional. An ISO 3166-1 alpha-2 country code. Supply this parameter to limit the response to one particular geographical market. For example, for albums available in Sweden: market=SE.
token	An OAuth token created with spotifyOAuth.

Value

'Get Albums from an Artist

Examples

```
## Not run:
```

```
foofighters_albums<-getAlbums("7jy3rLJdDQY210gRLCZ9sD",market="US",token)
```

```
## End(Not run)
```

getArtist	<i>Get Spotify catalog information for a single artist</i>
-----------	--

Description

Function to get Spotify catalog information for a single artist identified by their unique Spotify ID.

Usage

```
getArtist(artist_id, token)
```

Arguments

artist_id	The Spotify ID of the artist.
token	An OAuth token created with spotifyOAuth.

Value

Get Spotify catalog information for a single artist identified by its unique Spotify ID.

Examples

```
## Not run:  
  
foofighters<-getArtist("7jy3rLJdDQY210gRLCZ9sD", token)  
  
## End(Not run)
```

getFeatures	<i>Get audio feature information for a single track</i>
-------------	---

Description

function to get audio feature information for a single track identified by its unique Spotify ID.

Usage

```
getFeatures(track_id, token)
```

Arguments

track_id	The Spotify ID for the track.
token	An OAuth token created with spotifyOAuth.

getPlaylists	<i>Get the playlists of a specific user</i>
--------------	---

Description

function to get Info about the playlists of a specific user the user_id

Usage

```
getPlaylists(user_id, offset = 0, token)
```

Arguments

user_id	user id
offset	The index of the first playlist to return. Default: 0 (the first object). Maximum offset: 100.000.
token	An OAuth token created with spotifyOAuth.

Value

get playlist from a specific user using a username

getPlaylistSongs	<i>Get the songs of a specific playlist</i>
------------------	---

Description

function to get songs about a specific playlist

Usage

```
getPlaylistSongs(user_id, playlist_id, offset = 0, token)
```

Arguments

user_id	User id
playlist_id	Playlist id
offset	The index of the first songs to return. Default: 0 (the first object). Maximum offset: 100.000.
token	An OAuth token created with spotifyOAuth.

getRelated	<i>Get Related artists</i>
------------	----------------------------

Description

function to get the related artists of an Artist

Usage

```
getRelated(artist_name, token)
```

Arguments

artist_name	Name of the artist (can use name or Spotify ID of the artist)
token	An OAuth token created with spotifyOAuth.

getTopTracks	<i>Get top tracks of an Artist</i>
--------------	------------------------------------

Description

function to get top tracks of an Artist.

Usage

```
getTopTracks(artist_id, country, token)
```

Arguments

artist_id	Artist ID
country	Country of interest
token	An OAuth token created with spotifyOAuth.

`getTrack`*Get a Track*

Description

Get Spotify catalog information for a single track identified by its unique Spotify ID.

Usage

```
getTrack(track_id, token)
```

Arguments

<code>track_id</code>	The Spotify ID for the track.
<code>token</code>	An OAuth token created with <code>spotifyOAuth</code> .

`getUser`*Get basic information about an User*

Description

function to get User's basic information

Usage

```
getUser(user_id, token)
```

Arguments

<code>user_id</code>	user id
<code>token</code>	An OAuth token created with <code>spotifyOAuth</code> .

Examples

```
## Not run:

my_oauth <- spotifyOAuth(app_id="xxxx",client_id="yyyy",client_secret="zzzz")
save(my_oauth, file="my_oauth")
load("my_oauth")
tiago <- getUser(user_id="t.mendesdantas",token=my_oauth)

## End(Not run)
```

searchArtist	<i>Search for a specific artist</i>
--------------	-------------------------------------

Description

function to get basic info about a searched artist

Usage

```
searchArtist(artist_name, token)
```

Arguments

artist_name	Name of the artist
token	An OAuth token created with spotifyOAuth.

Examples

```
## Not run:

my_oauth <- spotifyOAuth(app_id="xxxx",client_id="yyyy",client_secret="zzzz")
save(my_oauth, file="my_oauth")
load("my_oauth")
foofighters <- searchArtist("Foo+fighters",token=my_oauth)

## End(Not run)
```

searchPlaylist	<i>Search for playlists</i>
----------------	-----------------------------

Description

function to search for playlists given a name

Usage

```
searchPlaylist(playlistName, offset = 0, token = token)
```

Arguments

playlistName	Name of the playlist being searched for
offset	The index of the first Playlist to return. Default: 0 (the first object). Maximum offset: 100.000.
token	An OAuth token created with spotifyOAuth.

searchTrack	<i>Search for a specific Track function to get basic info about a searched track</i>
-------------	--

Description

Search for a specific Track
function to get basic info about a searched track

Usage

```
searchTrack(track, token)
```

Arguments

track	Name of the track
token	An OAuth token created with spotifyOAuth.

Examples

```
## Not run:  
  
my_oauth <- spotifyOAuth(app_id="xxxx",client_id="yyyy",client_secret="zzzz")  
save(my_oauth, file="my_oauth")  
load("my_oauth")  
track <- searchTrack("generator", token=my_oauth)  
  
## End(Not run)
```

spotifyOAuth	<i>Create OAuth token to access Spotify web API</i>
--------------	---

Description

spotifyOAuth creates a long-lived OAuth access token that enables R to make authenticated calls to the Spotify API. The token can be saved as a file in disk to be re-used in future sessions. This function relies on the `httr` package to create the OAuth token

Usage

```
spotifyOAuth(app_id, client_id, client_secret)
```

Arguments

app_id	App ID (this is an internal identification for token if you wish to save authorization)
client_id	Client ID
client_secret	Client Secret

Examples

```
## Not run:

my_oauth <- spotifyOAuth(app_id="xxx",client_id="yyy",client_secret="zzzz")
save(my_oauth, file="my_oauth")
load("my_oauth")
tiago <- getUser(user_id="t.mendesdantas",token=my_oauth)

## End(Not run)
```

Index

`getAlbum`, [2](#)
`getAlbumInfo`, [2](#)
`getAlbums`, [3](#)
`getArtist`, [3](#)
`getFeatures`, [4](#)
`getPlaylists`, [5](#)
`getPlaylistSongs`, [5](#)
`getRelated`, [6](#)
`getTopTracks`, [6](#)
`getTrack`, [7](#)
`getUser`, [7](#)

`searchArtist`, [8](#)
`searchPlaylist`, [8](#)
`searchTrack`, [9](#)
`spotifyOAuth`, [9](#)