

Package ‘aniview’

July 22, 2025

Title Animate Shiny and R Markdown Content when it Comes into View

Version 0.1.0

Description Animate Shiny and R Markdown content when it comes into view using 'animate-css' effects thanks to 'jQuery AnimateView'.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

RoxygenNote 7.1.0

Imports jsonlite, htmltools

Suggests shiny

URL <https://felixluginbuhl.com/aniview>,
<https://github.com/lgnbhl/aniview>

BugReports <https://github.com/lgnbhl/aniview/issues>

NeedsCompilation no

Author Félix Luginbuhl [aut, cre]

Maintainer Félix Luginbuhl <felix.luginbuhl@protonmail.ch>

Repository CRAN

Date/Publication 2020-03-31 15:20:07 UTC

Contents

aniview	2
use_aniview	2
Index	4

`aniview`*Animate an element when it comes into view*

Description

Programmatically animate Shiny and R Markdown content when it comes into view.

Usage

```
aniview(element, animation, ...)
```

Arguments

<code>element</code>	An shiny or rmarkdown element.
<code>animation</code>	An animation from animate.css
<code>...</code>	Additional class element

Examples

```
library(shiny)

ui <- function(){
  fluidPage(
    use_aniview(), # add use_aniview() in the UI
    aniview(h1("Shiny with AniView"), animation = "fadeInUp"),
    aniview(textOutput("text"), animation = "zoomIn")
  )
}

server <- function(input, output, session){
  output$text <- renderText({
    print("An animated text.")
  })
}

if(interactive()) shinyApp(ui, server)
```

`use_aniview`*Use AniView*

Description

Use AniView

Usage

```
use_aniview(animateThreshold = 0, scrollPollInterval = 20)
```

Arguments

`animateThreshold`

integer. +ve numbers delay the animation sequence until the specified number of pixels have come into view. -ve numbers will trigger the animation sequence prior to the element coming into view.

`scrollPollInterval`

integer. frequency at which user scrolling is 'polled' i.e. tested. This is in milliseconds and is an extension to jQuery's in-built 'scroll' event/handler.

Examples

```
library(shiny)

ui <- function(){
  fluidPage(
    use_aniview(), # add use_aniview() in the UI
    aniview(h1("Shiny with AniView"), animation = "fadeInUp"),
    aniview(textOutput("text"), animation = "zoomIn")
  )
}

server <- function(input, output, session){
  output$text <- renderText({
    print("An animated text.")
  })
}

if(interactive()) shinyApp(ui, server)
```

Index

`aniview`, [2](#)

`use_aniview`, [2](#)