

Package ‘arrayhelpers’

July 22, 2025

Type Package

Title Convenience Functions for Arrays

Description Some convenient functions to work with arrays.

Maintainer C. Beleites <claudia.beleites@chemometrix.eu>

Author C. Beleites <claudia.beleites@chemometrix.eu>

Version 1.1-0

Date 2020-02-03

License GPL

LazyLoad yes

LazyData yes

Imports methods, utils, svUnit

URL <http://arrayhelpers.r-forge.r-project.org/>

Encoding UTF-8

Collate 'unittestdata.R' 'arrayhelpers.R' 'apply.R' 'array2df.R'
'array2vec.R' 'colSums.R' 'countrows.R' 'delold.R'
'dropdimnames.R' 'ensuredim.R' 'groupsum.R' 'init.R' 'makeNd.R'
'ndim.R' 'numericindices.R' 'restoredim.R' 'rowsum.R' 'slice.R'
'stack.R' 'ta.R' 'unittests.R'

RoxygenNote 7.0.2

NeedsCompilation no

Repository CRAN

Date/Publication 2020-02-04 16:10:09 UTC

Contents

arrayhelpers-package	2
array2df	2
array2vec	4
arrayhelpers.unittest	5
colSums.matrix-method	5

countRows	7
delold	8
dropdimnames	8
ensuredim	9
groupsum	10
makeNd	11
ndim	12
numericindex	13
peek	14
rowsum,array-method	14
slice	15
ta	16

Index	17
--------------	-----------

arrayhelpers-package *Package arrayhelpers*

Description

Little helper functions to work with arrays

Author(s)

C. Beleites

Maintainer: Claudia Beleites <claudia.beleites@chemometrix.eu>

array2df *array2df*

Description

array2df: Convert multidimensional array into matrix or data.frame The "wide-format" array is converted into a "long-format" matrix or data.frame.

Usage

```
array2df(
  x,
  levels,
  matrix = FALSE,
  label.x = deparse(substitute(x)),
  na.rm = FALSE
)
```

Arguments

x	array
levels	list with the levels for the dimensions of x. If levels[[i]] is NULL no column is produced for this factor. If levels[[i]] is NA, the result column is a numeric with range from 1 to dim(x)[i] If levels[[i]] is TRUE, the levels are taken from the dimnames. names(levels) yield the resulting column names.
matrix	If TRUE, a numeric matrix rather than a data.frame is returned.
label.x	Name for the column containing the x values.
na.rm	should rows where the value of x is NA be removed?

Details

If the resulting data.frame is too large to fit in memory, a matrix might help.

The main benefit of this function is that it uses matrices as long as possible. This can give large advantages in terms of memory consumption.

Value

A data.frame or matrix with `prod(dim(x))` rows and `length(dim(x)) + 1` columns.

Author(s)

Claudia Beleites

See Also

[stack](#)

Examples

```
a <- arrayhelpers:::a
a
array2df (a)
array2df (a, matrix = TRUE)

array2df (a, levels = list(NULL, x = NA, c = NULL), label.x = "value")

array2df (a, levels = list(NULL, x = TRUE, c = c ("foo", "bar")), label.x = "value")

summary (array2df (a,
  levels = list(NULL, x = NA, c = c ("foo", "bar")),
  label.x = "value"))

summary (array2df (a,
  levels = list(NULL, x = NA, c = c ("foo", "bar")),
  label.x = "value",
```

```
matrix = TRUE))
```

array2vec	<i>Converting array and vector Indices Calculate the vector index from array indices, and vice versa.</i>
-----------	---

Description

arrays are numerics with a `dim` attribute and are stored with the first index moving fastest (i.e. by column). They can be indexed both ways.

Usage

```
array2vec(iarr, dim)
```

```
vec2array(ivec, dim)
```

Arguments

<code>iarr</code>	vector with the indices into the array dimensions
<code>dim</code>	vector with the array dimensions, as returned by <code>dim(x)</code>
<code>ivec</code>	scalar with the index into the vector

Value

`array2vec` returns a scalar, `vec2array` a matrix.

Author(s)

C. Beleites

See Also

see [Extract](#) on the difference of indexing an array with a vector or a matrix.

Examples

```
arr <- array(rnorm(24), dim = 2 : 4)
arr

v <- matrix(c(2, 2, 2), nrow = 1)
i <- array2vec(v, dim = dim(arr))
i
arr[v]
arr[i]

arr[c(2, 2, 2)] ## indexing with a vector
```

```
arr[2]

i <- 14
v <- vec2array (i, dim = dim (arr))
v
arr [v]
arr [i]
```

arrayhelpers.unittest *Run the unit tests*

Description

Run the unit tests attached to the functions via [svUnit](#)

Usage

```
arrayhelpers.unittest()
```

Value

invisibly TRUE if the tests pass, NA if [svUnit](#) is not available. Stops if errors are encountered.

Author(s)

Claudia Beleites

See Also

[svUnit](#)

colSums,matrix-method *Row and column sums and means for numeric arrays.*

Description

These functions extend the respective base functions by (optionally) preserving the shape of the array (i.e. the summed dimensions have length 1).

Usage

```
## S4 method for signature 'matrix'
colSums(x, na.rm = FALSE, dims = 1L, drop = TRUE)

colSums.AsIs(x, ...)

## S4 method for signature 'array'
colSums(x, na.rm = FALSE, dims = 1L, drop = TRUE)

## S4 method for signature 'matrix'
colMeans(x, na.rm = FALSE, dims = 1L, drop = TRUE)

colMeans.AsIs(x, ...)

## S4 method for signature 'array'
colMeans(x, na.rm = FALSE, dims = 1L, drop = TRUE)

## S4 method for signature 'matrix'
rowSums(x, na.rm = FALSE, dims = 1L, drop = TRUE)

rowSums.AsIs(x, ...)

## S4 method for signature 'array'
rowSums(x, na.rm = FALSE, dims = 1L, drop = TRUE)

## S4 method for signature 'matrix'
rowMeans(x, na.rm = FALSE, dims = 1L, drop = TRUE)

rowMeans.AsIs(x, ...)

## S4 method for signature 'array'
rowMeans(x, na.rm = FALSE, dims = 1L, drop = TRUE)
```

Arguments

x	an array of two or more dimensions, containing numeric, complex, integer or logical values, or a numeric data frame.
na.rm	logical indicating treatment of missing values
dims	integer: Which dimensions are regarded as ‘rows’ or ‘columns’ to sum over. For row*, the sum or mean is over dimensions <code>dims + 1, ...</code> ; for col* it is over dimensions <code>1 : dims</code> .
drop	If FALSE, the number of dimensions is retained: the length of the dimensions that are summed or averaged is set to 1. TRUE yield the same behaviour as <code>colSums</code>
...	the signature = "AsIs" methods hand on all parameters

Value

like `colSums` if `drop = TRUE`, otherwise an array where the summed dimensions have length 1.

Author(s)

Claudia Beleites

See Also[colSums](#)**Examples**

```
a <- array (1 : 24, 4 : 2)
a

rowSums (a)
rowSums (a, drop = FALSE)

colSums (a)
colSums (a, drop = FALSE)

colSums (a, dim = 2)
colSums (a, dim = 2, drop = FALSE)
```

`countRows`*Count equal rows*

Description

matrices are converted to data.frame.

Usage`countRows(x)`**Arguments**`x` the matrix or data.frame**Value**

data frame with unique rows, their counts and indices into the original data.frame

Note

this function is subject to changes in the future.

Author(s)

Claudia Beleites

delold

Strip the attributes keeping track of the former shape

Description

Convenient for printing

Usage

```
delold(a)
```

Arguments

a the array

Value

a stripped of the old.* attributes.

Author(s)

Claudia Beleites

Examples

```
a <- arrayhelpers:::a
makeNd (a, 2)
delold (makeNd (a, 2))
```

dropdimnames*Drop dimnames if all elements are NULL*

Description

Drop dimnames if all elements are NULL

Usage

```
dropdimnames(x)
```

```
lon(1)
```


Arguments

x	object
l	list

Value

object without empty dimnames
 l on: NULL if all elements of dn are NULL, otherwise dn

Author(s)

Claudia Beleites

ensuredim	<i>Enforce array and convert to vector if appropriate</i>
-----------	---

Description

ensuredim turns vectors into 1d-arrays, and leaves arrays unchanged. drop1d is the inverse: it converts 1d arrays into vectors.

Usage

```
ensuredim(x)

drop1d(x, drop = TRUE)
```

Arguments

x	vector (or array)
drop	if TRUE, 1d arrays are converted into vectors

Value

ensuredim array of at least one dimension
 drop1d vector, if x had only 1 dimension

Author(s)

Claudia Beleites
 Claudia Beleites

groupsum

Extension of rowsum

Description

groupsum extends [rowsum](#): it allows group to be an array of the same shape as x.

Usage

```
groupsum(  
  x,  
  group = NULL,  
  dim = 1L,  
  reorder = TRUE,  
  na.rm = FALSE,  
  ...,  
  drop = !is.array(x)  
)
```

Arguments

x	array to be rowsummed
group	grouping variable (integer or factor) indicating groups of samples.
dim	along which dimension should the group sums be taken? (default: rows)
reorder	should the groups be ordered? see rowsum
na.rm	should NAs be removed?
...	ignored
drop	should 1d arrays drop to vectors?

Value

like [rowsum](#), but further dimensions of the array are preserved.

Author(s)

Claudia Beleites

See Also

[rowsum](#) [rowsum](#)

makeNd	<i>Ensure/collapse an array into n dimensions and restore the old dimensions</i>
--------	--

Description

nameNd ensures a given number of dimensions: If a has less than N dimensions, new dimensions of length 1 are appended. If a has more than N dimensions, the supernumerary dimensions are collapsed onto the last dimension.

Attributes `old.dim` and `old.dimnames` are used by default. `restoredim` is the inverse of `makeNd`.

Usage

```
makeNd(a, N)

restoredim(
  a,
  old = NULL,
  n = 1L,
  ...,
  usedim = TRUE,
  fromend = FALSE,
  drop = FALSE
)
```

Arguments

a	an array (matrix, vector)
N	the desired number of dimensions, 0 to remove the <code>dim</code> and <code>dimnames</code> attributes (i.e. to create a vector).
old	list containing a list with (possibly) elements <code>dim</code> , <code>dimnames</code> , and <code>names</code> . The <code>n</code> th last element of this list is used.
n	how many <code>makeNdim</code> steps to go back?
...	ignored
usedim	use only the specified dimensions
fromend	if TRUE, numeric <code>usedim</code> are counted from the end, see details.
drop	should 1d arrays drop to vectors?

Details

Note that missing attributes as well as `old.dim = NULL` produce a (dimensionless) vector. This is also the case if a lost the `old.*` attributes during computations like `as.numeric`, `c`, etc..

`fromend` together with numeric `usedim` specifies dimensions counting from the end. E.g. `fromend = TRUE` and `usedim = 1 : 3` for an array to be restored to 10d means restoring dimensions 8 : 10. `fromend = TRUE` and `usedim = -(1 : 3)` restores dimensions 1 to 7.

Value

N-dimensional array
an array

Author(s)

Claudia Beleites
Claudia Beleites

Examples

```
v <- arrayhelpers:::v
v
makeNd (v, 1)
dim (makeNd (v, 1))
dim (makeNd (v, 3))

m <- arrayhelpers:::m
m
makeNd (m, 1)
dim (makeNd (m, 1))
makeNd (m, 0)
dim (makeNd (m, 0))
makeNd (m, 3)

a <- arrayhelpers:::a
a
dim (makeNd (a, 1))
dim (makeNd (a, 0))
makeNd (a, 2)
makeNd (a, -2)
makeNd (a, -4)
makeNd (a, 3);

a <- array (1 : 24, 4 : 3)
a
restoredim (makeNd (a, 0))

x <- makeNd (a, 0)
attr (x, "old")
```

ndim

number of dimensions

Description

number of dimensions

Usage

ndim(a)

Arguments

a vector, matrix, or array

Value

integer: length of dim attribute

Author(s)

Claudia Beleites

numericindex *Convert character or logical indices to numeric*

Description

Convert character or logical indices to numeric

Usage

numericindex(x, i, n = names(x))

Arguments

x the object that is to be indexed
i the indices to be converted
n names of the object

Value

numeric indices

Author(s)

Claudia Beleites

peek *A little stack.*

Description

TODO: implement as reference class? Note: pop only removes elements. To retrieve them, use peek.

Usage

```
peek(x, an, n = 1L)
```

```
pop(x, an, n = 1L)
```

```
push (x, an) <- value
```

Arguments

x	the object
an	attribute holding the stack
n	numer of element to peek at and numer of elements to pop (delete), respectively
value	list of things to push on the stack.

Value

push and pop: the object with stack in list an pushed/popped by the n elements
peek: the nth stack element (without popping!)

Author(s)

Claudia Beleites

rowsum,array-method *rowsum for arrays*

Description

This function extends the base function [rowsum](#).

Usage

```
## S4 method for signature 'array'  
rowsum(x, group, reorder = TRUE, na.rm = FALSE, ...)
```

Arguments

x	array to be rowsummed
group	grouping variable (integer or factor) indicating groups of samples.
reorder	should the groups be ordered? see rowsum
na.rm	should NAs be removed?
...	ignored

Value

like [rowsum](#), but further dimensions of the array are preserved.

Author(s)

Claudia Beleites

See Also

[rowsum](#)

slice *alternative to index an array*

Description

slice is an alternative interface to [\[](#) (extract). Dimensions to index must be given by name, i for the first, j for the second and so on.

Usage

```
slice(a, ..., drop = TRUE)
```

```
slice (a, ...) <- value
```

Arguments

a	vector, matrix, or array
...	indexing instructions. The names of the arguments specify the dimension (i = 1st, j = 2nd, ...). The indexing expressions are the same as for [
drop	see [
value	the values to assign

Value

array

Author(s)

Claudia Beleites

Examples

```
slice (arrayhelpers:::a, j = 3 : 2)
tmp <- arrayhelpers:::a
slice (tmp, j = 2 : 3) <- 0
tmp
```

ta *Transpose arrays*

Description

This function provides transposing of arrays or vectors as swapping their first two dimensions. `t (array)` can be enabled via `setMethod`, see the example.

Usage

```
ta(x)
```

Arguments

x an array

Value

the array with the first two dimensions swapped.

Author(s)

Claudia Beleites

See Also

[t](#)

Examples

```
a <- array (1 : 24, 4:2)
a
ta (a)

setMethod ("t", "array", ta)
t (a)
removeMethod ("t", "array")
```


Index

- * **algebra**
 - colSums, matrix-method, 5
 - groupsum, 10
 - rowsum, array-method, 14
- * **arith**
 - colSums, matrix-method, 5
 - groupsum, 10
 - rowsum, array-method, 14
- * **array**
 - array2df, 2
 - array2vec, 4
 - colSums, matrix-method, 5
 - groupsum, 10
 - rowsum, array-method, 14
- * **manip**
 - array2df, 2
- * **package**
 - arrayhelpers-package, 2
- [, 15
- array2df, 2
- array2vec, 4
- arrayhelpers-package, 2
- arrayhelpers.unittest, 5
- colMeans, array-method
 - (colSums, matrix-method), 5
- colMeans, matrix-method
 - (colSums, matrix-method), 5
- colMeans.AsIs (colSums, matrix-method), 5
- colSums, 6, 7
- colSums, array-method
 - (colSums, matrix-method), 5
- colSums, matrix-method, 5
- colSums.AsIs (colSums, matrix-method), 5
- countRows, 7
- delold, 8
- drop1d (ensuredim), 9
- dropdimnames, 8
- ensuredim, 9
- Extract, 4
- groupsum, 10
- lon (dropdimnames), 8
- makeNd, 11
- ndim, 12
- numericindex, 13
- peek, 14
- pop (peek), 14
- push<- (peek), 14
- restoredim (makeNd), 11
- rowMeans, array-method
 - (colSums, matrix-method), 5
- rowMeans, matrix-method
 - (colSums, matrix-method), 5
- rowMeans.AsIs (colSums, matrix-method), 5
- rowsum, 10, 14, 15
- rowsum, array-method, 14
- rowSums, array-method
 - (colSums, matrix-method), 5
- rowSums, matrix-method
 - (colSums, matrix-method), 5
- rowSums.AsIs (colSums, matrix-method), 5
- setMethod, 16
- slice, 15
- slice<- (slice), 15
- stack, 3
- svUnit, 5
- t, 16
- ta, 16
- vec2array (array2vec), 4