

Package ‘brlrmr’

July 22, 2025

Title Bias Reduction with Missing Binary Response

Version 0.1.7

Date 2019-09-09

Description Provides two main functions, `il()` and `fil()`. The `il()` function implements the EM algorithm developed by Ibrahim and Lipsitz (1996) <DOI:10.2307/2533068> to estimate the parameters of a logistic regression model with the missing response when the missing data mechanism is nonignorable. The `fil()` function implements the algorithm proposed by Maity et. al. (2017+) <<https://github.com/arnabkrmaity/brlrmr>> to reduce the bias produced by the method of Ibrahim and Lipsitz (1996) <DOI:10.2307/2533068>.

Depends R (>= 2.10)

Imports boot, brglm, MASS, profileModel, Rcpp, stats

License GPL-3

Encoding UTF-8

LazyData true

RoxygenNote 6.1.1

NeedsCompilation no

Author Arnab Maity [aut, cre],
Vivek Pradhan [aut],
Ujjwal Das [aut]

Maintainer Arnab Maity <arnab.maity@pfizer.com>

Repository CRAN

Date/Publication 2019-09-10 22:50:21 UTC

Contents

em.fil	2
em.fil.interaction	3
em.il	3
em.il.interaction	4
fil	5
il	7

incontinence	9
nhanes	10
simulated.data	10
Index	11

em.fil	<i>em.fil</i>
--------	---------------

Description

It is called by the main function fil and is for internal use.

Usage

em.fil(parameter, X, full.missing.data, observed.data, full.data, family)

Arguments

- parameter The starting values of the parameters as (β, α) where β is the parameters of original model and α is the for the missing data model.
- X The design matrix with the intercept column.
- full.missing.data The augmented response with design matrix and missing indicator 1 for missing data.
- observed.data The observed response with design matrix and missing indicator 0 for observed data.
- full.data The observed response, augmented response with corresponding design matrix and missing indicator 0 for observed data and 1 for missing data.
- family as in [glm](#). brlrmr currently supports only the "binomial" family with links

References

Bias Reduction in Logistic Regression with Missing Responses when the Missing Data Mechanism is Nonignorable.

<code>em.fil.interaction</code>	<i>em.fil.interaction</i>
---------------------------------	---------------------------

Description

It is called by the main function `fil` and is for internal use.

Usage

```
em.fil.interaction(parameter, X, full.missing.data, observed.data, full.data, k, family)
```

Arguments

<code>parameter</code>	The starting values of the parameters as (β, α) where β is the parameters of original model and α is the for the missing data model.
<code>X</code>	The design matrix with the intercept column.
<code>full.missing.data</code>	The augmented response with design matrix and missing indicator 1 for missing data.
<code>observed.data</code>	The observed response with design matrix and missing indicator 0 for observed data.
<code>full.data</code>	The observed response, augmented response with corresponding design matrix and missing indicator 0 for observed data and 1 for missing data.
<code>k</code>	If interaction is present in the missing data model, then the <code>k</code> is the column number of covariate matrix which has interaction with the response.
<code>family</code>	as in glm . <code>brlrmr</code> currently supports only the "binomial" family with links

References

Bias Reduction in Logistic Regression with Missing Responses when the Missing Data Mechanism is Nonignorable.

<code>em.il</code>	<i>em.il</i>
--------------------	--------------

Description

It is called by the main function `fil` and is for internal use.

Usage

```
em.il(parameter, X, full.missing.data, observed.data, full.data, family)
```

Arguments

parameter	The starting values of the parameters as (β, α) where β is the parameters of original model and α is the for the missing data model.
X	The design matrix with the intercept column.
full.missing.data	The augmented response with design matrix and missing indicator 1 for missing data.
observed.data	The observed response with design matrix and missing indicator 0 for observed data.
full.data	The observed response, augmented response with corresponding design matrix and missing indicator 0 for observed data and 1 for missing data.
family	as in glm . brlrmr currently supports only the "binomial" family with links

References

Bias Reduction in Logistic Regression with Missing Responses when the Missing Data Mechanism is Nonignorable.

em.il.interaction	<i>em.il.interaction</i>
-------------------	--------------------------

Description

It is called by the main function fil and is for internal use.

Usage

```
em.il.interaction(parameter, X, full.missing.data, observed.data, full.data, k, family)
```

Arguments

parameter	The starting values of the parameters as (β, α) where β is the parameters of original model and α is the for the missing data model.
X	The design matrix with the intercept column.
full.missing.data	The augmented response with design matrix and missing indicator 1 for missing data.
observed.data	The observed response with design matrix and missing indicator 0 for observed data.
full.data	The observed response, augmented response with corresponding design matrix and missing indicator 0 for observed data and 1 for missing data.
k	If interaction is present in the missing data model, then the k is the column number of covariate matrix which has interaction with the response.
family	as in glm . brlrmr currently supports only the "binomial" family with links

References

Bias Reduction in Logistic Regression with Missing Responses when the Missing Data Mechanism is Nonignorable.

fil	<i>fil</i>
-----	------------

Description

This provides the estimates using IL method and FIL method as described in the reference.

Usage

```
fil(formula, data, parameter = NULL, family = binomial, alpha = 0.05,
    interaction = FALSE, k = NULL, na.action)
```

Arguments

formula	as in lm . The missing values of response are NA.
data	as in lm . The first column of data is binary missing response. The missing observations are denoted by NA. The rest of the columns are covariates or explanatory variables.
parameter	The starting values of the parameters as (β, α) where β is the parameters of original model and α is the for the missing data model.
family	as in glm . <code>brlrmr</code> currently supports only the "binomial" family with links.
alpha	This is used for upper $100(1 - \alpha)\%$ point of standard Normal distribution. The default is 1.96.
interaction	TRUE or FALSE, whether to consider interaction in the missing data model. Currently only one interaction between response and covariates is supported. FALSE by default.
k	Which covariate has interaction with response. Takes integer values. User must assign a value if <code>interaction = TRUE</code> .
na.action	as in lm . Always set to <code>na.pass</code> . Note that setting any other value to <code>na.action</code> will remove the NA's from response and hence will break the code as this package is only intended for missing response data.

Value

n	number of observations.
nmissing	the number of missing observations.
missing.proportion	proportion of missing observations.
beta.hat	parameter estimate of logistic regression of y on x using FIL method.

beta.se.hat	standard error using FIL method.
z.value	Wald Z value using FIL method.
p.value	p value using FIL method.
significance.beta.firth	indicator output whether regressors are significant using FIL method, 1 if significant and 0 if not significant.
LCL	Lower Confidence Limits of 100(1 - alpha)% Confidence Intervals.
UCL	Upper Confidence Limits of 100(1 - alpha)% Confidence Intervals.
alpha.hat	parameter estimate due to missing model using FIL.
alpha.se.hat	standard error of the them.
z.value.alpha	Wald Z value for them.
p.value.alpha	p values for them.

References

Bias Reduction in Logistic Regression with Missing Responses when the Missing Data Mechanism is Nonignorable.

Examples

```
## Not run:
#####
##### Simulated Example #####
#####
data(simulated.data) # load simulated data

# parameter definition
beta0 <- 1
beta1 <- 1
beta2 <- 1
beta3 <- 1
beta4 <- 1

# parameter definition for missing indicator
alpha0 <- -1.1
alpha1 <- -1
alpha2 <- 1
alpha3 <- 1
alpha4 <- 1
alpha5 <- -1

parameter <- c(beta0, beta1, beta2, beta3, beta4,
               alpha0, alpha1, alpha2, alpha3, alpha4, alpha5)

fil(y ~ x1 + x2 + x3 + x4, data = simulated.data, parameter,
    family = binomial(link = "logit"), na.action = na.pass)

## End(Not run)
```

```
#####
#### Real data example with separation ####
#####
data(nhanes) # load nhanes data
fit(hyp ~ age2 + age3, data = nhanes, family = binomial(link = "logit"), na.action = na.pass)

data(incontinence) # load nhanes data
fit(y ~ x1 + x2 + x3, data = incontinence, family = binomial(link = "logit"), na.action = na.pass)
```

il

il

Description

This provides the estimates using IL method as described in the reference.

Usage

```
il(formula, data, parameter = NULL, family = binomial, alpha = 0.05,
interaction = FALSE, k = NULL, na.action)
```

Arguments

formula	as in lm . The missing values of response are NA.
data	as in lm . The first column of data is binary missing response. The missing observations are denoted by NA. The rest of the columns are covariates or explanatory variables.
parameter	The starting values of the parameters as (β, α) where β is the parameters of original model and α is the for the missing data model.
family	as in glm . brlrmr currently supports only the "binomial" family with links.
alpha	This is used for upper 100(1 - alpha)% point of standard Normal distribution. The default is 1.96.
interaction	TRUE or FALSE, whether to consider interaction in the missing data model. Currently only one interaction between response and covariates is supported. FALSE by default.
k	Which covariate has interaction with response. Takes integer values. User must assign a value if interaction = TRUE.
na.action	as in lm . Always set to na.pass. Note that setting any other value to na.action will remove the NA's from response and hence will break the code as this package is only intended for missing response data.

Value

n	number of observations.
nmissing	the number of missing observations.
missing.proportion	proportion of missing observations.
beta.hat	parameter estimate of logsitic regression of y on x using IL method.
beta.se.hat	standard error using IL method.
z.value	Wald Z value using IL method.
p.value	p value using IL method.
significance.beta	is indicator output whether regressors are significant using IL method, 1 if significant and 0 if not significant.
LCL	Lower Confidence Limits of 100(1 - alpha)% Confidence Intervals.
UCL	Upper Confidence Limits of 100(1 - alpha)% Confidence Intervals.
alpha.hat	parameter estimate due to missing model using IL.
alpha.se.hat	standard error of the them.
z.value.alpha	Wald Z value for them.
p.value.alpha	p values for them.
sep	separation indicator = 1 if separation, = 0 otherwise

References

Ibrahim, J. G. and Lipsitz, S. R. (1996). Parameter estimation from incomplete data in binomial regression when the missing data mechanism is nonignorable. *Biometrics*, 52:1071–1078.

Examples

```
## Not run:
#####
##### Simulated Example #####
#####
data(simulated.data) # load simulated data

# parameter definition
beta0 <- 1
beta1 <- 1
beta2 <- 1
beta3 <- 1
beta4 <- 1

# parameter definition for missing indicator
alpha0 <- -1.1
alpha1 <- -1
alpha2 <- 1
alpha3 <- 1
alpha4 <- 1
```



```

alpha5 <- -1

parameter <- c(beta0, beta1, beta2, beta3, beta4,
               alpha0, alpha1, alpha2, alpha3, alpha4, alpha5)

il(y ~ x1 + x2 + x3 + x4, data = simulated.data, parameter,
   family = binomial(link = "logit"), na.action = na.pass)

## End(Not run)

## Not run:
#####
##### Real data example with separation #####
#####
data(nhanes) # load nhanes data
il(hyp ~ age2 + age3, data = nhanes, family = binomial(link = "logit"), na.action = na.pass)
# IL method encounters separation

## End(Not run)

```

incontinence

Incontinence example.

Description

A urinary incontinence study.

Usage

```
incontinence
```

Format

A data frame with 21 observations on the following 4 variables:

y Response (1 = continent, 0 = otherwise)

x1 Lower urinary tract measure

x2 Lower urinary tract measure

x3 Lower urinary tract measure

Source

Heinze, G. (2006). A comparative investigation of methods for logistic regression with separated or nearly separated data. *Statistics in Medicine*, 25:4216–4226.

nhanes	<i>Subset of original NHANES data used in mice package.</i>
--------	---

Description

A small data set with missing values.

Usage

nhanes

Format

A data frame with 25 observations on the following 2 variables:

hyp Hypertensive (0 = no, 1 = yes)

age2 Age group (1 = 40-59, 0 = otherwise)

age3 Age group (1 = 60+, 0 = otherwise)

Source

Schafer, J.L. (1997). *Analysis of Incomplete Multivariate Data*. London: Chapman & Hall. Table 6.14.

simulated.data	<i>We simulate this data for the purpose of illustration of the package</i>
----------------	---

Description

A dataset containing the 100 observations and 4 covariates. The covariates are generated from standard normal distribution. The missing binary response is generated using the simulation process as described in the reference.

Usage

simulated.data

Format

A data frame with 100 observations with 28 missing responses:

Index

* datasets

incontinence, [9](#)

nhanes, [10](#)

simulated.data, [10](#)

em.fil, [2](#)

em.fil.interaction, [3](#)

em.il, [3](#)

em.il.interaction, [4](#)

fil, [5](#)

glm, [2-5](#), [7](#)

il, [7](#)

incontinence, [9](#)

lm, [5](#), [7](#)

nhanes, [10](#)

simulated.data, [10](#)