

Package ‘calendar’

July 22, 2025

Title Create, Read, Write, and Work with 'iCalendar' Files, Calendars and Scheduling Data

Version 0.2.0

Description Provides function to create, read, write, and work with 'iCalendar' files (which typically have '.ics' or '.ical' extensions), and the scheduling data, calendars and timelines of people, organisations and other entities that they represent. 'iCalendar' is an open standard for exchanging calendar and scheduling information between users and computers, described at <<https://icalendar.org/>>.

License Apache License (>= 2.0)

URL <https://github.com/atfutures/calendar>,
<https://atfutures.github.io/calendar/>,
<https://github.com/ATFutures/calendar>

BugReports <https://github.com/ATFutures/calendar/issues>

Depends R (>= 3.4.0)

Imports cli, lubridate, tibble

Suggests covr, knitr, rmarkdown, testthat

VignetteBuilder knitr

Encoding UTF-8

LazyData true

RoxygenNote 7.3.2

NeedsCompilation no

Author Robin Lovelace [aut, cre] (ORCID: <<https://orcid.org/0000-0001-5679-6536>>),
Layik Hama [aut] (ORCID: <<https://orcid.org/0000-0003-1912-4890>>),
Ollie Lloyd [ctb] (ORCID: <<https://orcid.org/0000-0002-9385-1634>>),
Franco Scarafia [ctb] (ORCID: <<https://orcid.org/0009-0005-9822-169X>>),
Serkan Korkmaz [ctb] (ORCID: <<https://orcid.org/0000-0002-5052-0982>>)

Maintainer Robin Lovelace <rob00x@gmail.com>

Repository CRAN

Date/Publication 2024-08-20 04:10:02 UTC

Contents

calendar	2
formats	3
holidays	4
ical	4
ical_example	5
ical_outlook	5
ic_attributes_vec	6
ic_bind_list	7
ic_character	7
ic_char_datetime	8
ic_char_event	8
ic_dataframe	9
ic_date	9
ic_datetime	10
ic_event	10
ic_extract	11
ic_extract_raw	12
ic_find	12
ic_guid	13
ic_list	13
ic_read	14
ic_spec	14
ic_vector	15
ic_write	15
properties	16
properties_core	17
properties_ical	17
Index	18

calendar	<i>ics files with R</i>
----------	-------------------------

Description

iCalendar is an open standard for "exchanging calendar and scheduling information between users and computers". Files adhering to this standard are save as .ics files.

Details

The ical package is for interacting with such files

Author(s)

Maintainer: Robin Lovelace <rob00x@gmail.com> ([ORCID](#))

Authors:

- Layik Hama <layik.hama@gmail.com> ([ORCID](#))

Other contributors:

- Ollie Lloyd <o.lloyd@doctors.org.uk> ([ORCID](#)) [contributor]
- Franco Scarafia <franco.scarafia@hotmail.com> ([ORCID](#)) [contributor]
- Serkan Korkmaz <serkor1@duck.com> ([ORCID](#)) [contributor]

See Also

Useful links:

- <https://github.com/atfutures/calendar>
- <https://atfutures.github.io/calendar/>
- <https://github.com/ATFutures/calendar>
- Report bugs at <https://github.com/ATFutures/calendar/issues>

formats

Convenient datetime formats

Description

Convenient datetime formats

Usage

formats

Format

An object of class `list` of length 8.

Examples

```
formats
formats <- list(
  "ddmmy" = "%d%m%Y",
  "ddmmyyyy" = "%d%m%Y",
  "ddmmyyyy hh" = "%d%m%Y %H",
  "ddmmyyyy hhmm" = "%d%m%Y %H%M",
  "yyyy-mm-dd" = "%Y-%m-%d",
  "yyyy-mm-dd hh:mm" = "%Y-%m-%d %H:%M",
  "yyyy-mm-dd hh" = "%Y-%m-%d %H",
  "yy-mm-dd" = "%y-%m-%d"
)
# usethis::use_data(datetime_formats)
```

holidays

Example ics file on English and Welsh holidays

Description

This file is documented at <https://www.gov.uk/government/publications/open-standards-for-government/exchange-of-calendar-events>

Usage

holidays

Format

An object of class character of length 1.

Examples

```
# dataset was stored as follows:
u = "https://www.gov.uk/bank-holidays/england-and-wales.ics"
# download.file(u, "inst/extdata/england-and-wales.ics")
# holidays = "holidays"
```

ical

Create object of class ical

Description

Create object of class ical

Usage

```
ical(x, ic_attributes = NULL)
```

Arguments

x Lines read-in in from an iCal file

ic_attributes Calendar attributes, e.g. as provided by `ic_attributes_vec()`.

Examples

```
# ical from .ics characters:
class(ical_example)
ic <- ical(ical_example)
attributes(ic)
class(ic)
# ical from data frame:
ic_df <- data.frame(ic)
ic2 <- ical(ic_df)
class(ic2)
attributes(ic2)
```

ical_example	<i>Minimal example of raw ical data</i>
--------------	---

Description

See <https://calendar.google.com/calendar/ical/9sl1qu3qh2vdsnq26bjgvtnos94%40group.calendar.google.com/private-85cbe5d781da1b7efc91e01032cfc264/basic.ics> for the file

Usage

```
ical_example
```

Format

An object of class character of length 22.

Examples

```
# download.file("long_url", "inst/extdata/example.ics")
ical_example = readLines(system.file("extdata", "example.ics", package = "ical"))
# usethis::use_data(ical_example)
```

ical_outlook	<i>Example of event data with multi-line description from Outlook</i>
--------------	---

Description

See [here](#).

Usage

```
ical_outlook
```

Format

An object of class list of length 2.

Examples

```
# ical_outlook_raw <- readLines(long_url)
# ical_outlook_list <- ic_list(ical_outlook_raw)
# ical_outlook <- ical_outlook_list[1:2]
# ical_outlook[[2]][c(1:38)] <- gsub("a|e|i|o|f|l|t|n|b", "a", ical_outlook[[2]][c(1:38)])
# ical_outlook[[2]] <- ical_outlook[[2]][c(1, 5, 35, 36:55)]
# usethis::use_data(ical_outlook)
```

ic_attributes_vec	<i>Extract attributes from ical text</i>
-------------------	--

Description

Extract attributes from ical text

Usage

```
ic_attributes_vec(
  x = NULL,
  ic_attributes = c(BEGIN = "VCALENDAR", PRODID = "ATFutures/calendar", VERSION = "2.0",
    CALSCALE = "GREGORIAN", METHOD = "PUBLISH")
)
```

Arguments

x Lines read-in in from an iCal file

ic_attributes Calendar attributes, e.g. as provided by ic_attributes_vec().

Examples

```
ic_attributes_vec() # default attributes (can be changed)
ic_attributes_vec(ical_example)
```

ic_bind_list

*Bind list of named vectors of variable length into data frame***Description**

Based on: <https://stackoverflow.com/questions/17308551/>

Usage

```
ic_bind_list(x)
```

Arguments

x list of named vectors

Examples

```
ic_bind_list(list(ic_vector(ical_example)))
ics_file <- system.file("extdata", "england-and-wales.ics", package = "ical")
ics_raw = readLines(ics_file)
x <- lapply(ic_list(ics_raw), function(x) {
  ic_vector(x)
})
ic_df <- ic_bind_list(x)
head(ic_df)
x <- lapply(ical_outlook, function(x) {
  ic_vector(x)
})
ic_bind_list(x)
```

ic_character

*Convert ical object to character strings of attributes***Description**

Convert ical object to character strings of attributes

Usage

```
ic_character(ic, zulu = FALSE)
```

Arguments

ic object of class ical
 zulu is the datetime in Zulu time? FALSE by default, which means the calendar's current timezone is used.

Examples

```
ic <- ical(ical_example)
ic_character(ic)
identical(ical_example, ic_character(ic))
```

ic_char_datetime	Convert datetime object to character string
------------------	---

Description

Convert datetime object to character string

Usage

```
ic_char_datetime(x, zulu = FALSE)
```

Arguments

- x datetime object
- zulu is the datetime in Zulu time? FALSE by default, which means the calendar's current timezone is used.

Examples

```
x <- ic_datetime("20180809T160000")
ic_char_datetime(x) == "20180809T160000"
x <- ic_datetime("20180809T160000Z")
ic_char_datetime(x, zulu = TRUE) == "20180809T160000Z"
ic_char_date(as.Date("1985-12-26"))
```

ic_char_event	Convert ical object to character strings of events
---------------	--

Description

Convert ical object to character strings of events

Usage

```
ic_char_event(ic, zulu = FALSE)
```

Arguments

- ic object of class ical
- zulu is the datetime in Zulu time? FALSE by default, which means the calendar's current timezone is used.

Examples

```
ic <- ical(ical_example)
ic_char_event(ic)
ic_char_event(ic[c(1, 1), ])
```

ic_dataframe	<i>Convert iCal lines of text into a data frame</i>
--------------	---

Description

Returns a data frame

Usage

```
ic_dataframe(x)
```

Arguments

x Lines read-in in from an iCal file

Examples

```
ic_dataframe(ical_example)
ic_dataframe(ical_outlook)
ics_file <- system.file("extdata", "england-and-wales.ics", package = "calendar")
x = readLines(ics_file)
x_df = ic_dataframe(x)
head(x_df)
x = data.frame(x_df)
x_df2 = ic_dataframe(x)
identical(x, x_df2)
```

ic_date	<i>Convert ical date into R date</i>
---------	--------------------------------------

Description

Convert ical date into R date

Usage

```
ic_date(x)
```

Arguments

x Lines read-in in from an iCal file

Examples

```
ic_date("20120103")
```

ic_datetime	<i>Convert ical datetime into R datetime Z at the end of an ical stamp stands of Zulu time https://en.wikipedia.org/wiki/Coordinated_Universal_Time#Time_zones which is UTC = GMT https://greenwichmeantime.com/info/zulu/</i>
-------------	---

Description

Convert ical datetime into R datetime Z at the end of an ical stamp stands of Zulu time https://en.wikipedia.org/wiki/Coordinated_Universal_Time#Time_zones which is UTC = GMT <https://greenwichmeantime.com/info/zulu/>

Usage

```
ic_datetime(x)
```

Arguments

x Lines read-in in from an iCal file

Examples

```
ic_datetime("20180809T160000Z")
ic_date("20120103")
```

ic_event	<i>Create ical object from properties_core inputs</i>
----------	---

Description

Create an ical event using either POSIXct type or character type with format parameters.

Usage

```
ic_event(
  uid = ic_guid(),
  start_time = as.POSIXct(round.POSIXt(Sys.time(), units = "hours")),
  end_time = 1,
  format = "%Y-%m-%d %H:%M",
  summary = "ical event",
  more_properties = FALSE,
  event_properties = calendar::properties
)
```

Arguments

uid	the unique id of the event, by default generated by <code>ic_uid()</code>
start_time	start time, by default the start time plus one hour
end_time	a number representing the number of hours after <code>start_time</code> or an datetime object (of class <code>POSIXct</code>) when the event ends. By default set to 1, meaning 1 hour after <code>start_time</code> .
format	required if <code>start_time</code> and <code>end_time</code> are vectors and are not of datetime format " <code>%Y-%m-%d %H:%M</code> ", you can use <code>calendar::formats</code> object for convenience.
summary	short outline of the event
more_properties	add placeholder columns for properties in addition to <code>properties_core</code> , <code>dy</code> default <code>FALSE</code>
event_properties	named vector of additional properties to include. By default These include names stored in the data object <code>properties</code> (a packaged dataset), containing NAs to be subsequently populated.

Format

in case of `start_time` and `end_time` being character values, a format must be provided.

Value

object of class `ics`

Examples

```
ic_event()
s <- lubridate::ymd_h("2019-01-01 00")
ic_event(start_time = s, end_time = 3)
# also accepts this format by default, thanks to lubridate::ymd_h:
ic_event(start_time = "2019-01-01 00")
ic_event(more_properties = TRUE)
ic_event(start_time = "18-10-12", end_time = "18-10-13", format = calendar::formats$`yy-mm-dd`)
```

ic_extract	<i>Extract contents of iCal fields</i>
------------	--

Description

Return formatted data from iCal fields

Usage

```
ic_extract(x, pattern)
```

Arguments

x	Lines read-in in from an iCal file
pattern	A text string to search from (an ical field)

Examples

```
ic_extract(ical_example, "DTSTART")
```

ic_extract_raw	<i>Extract raw contents of iCal fields</i>
----------------	--

Description

Return info from iCal files, return raw unprocessed text.

Usage

```
ic_extract_raw(x, pattern)
```

Arguments

x	Lines read-in in from an iCal file
pattern	A text string to search from (an ical field)

Examples

```
pattern = "TSTAMP"
ic_extract_raw(ical_example, pattern)
```

ic_find	<i>Find contents of iCal fields</i>
---------	-------------------------------------

Description

Find contents of iCal fields

Usage

```
ic_find(x, pattern)
```

Arguments

x	Lines read-in in from an iCal file
pattern	A text string to search from (an ical field)

Examples

```
pattern = "DTSTAMP"
ic_find(ical_example, pattern)
```

ic_guid

*Get an ical GUID***Description**

Provided without any testing. Slight improvement from [SO question](#)

Usage

```
ic_guid()
```

Examples

```
ic_guid()
```

ic_list

*Convert raw ical text into a list of items***Description**

This function breaks-up the iCalendar object into a list. By default it breaks it into events, where the number of events is the number of BEGIN:VEVENT event initiation lines (assumes all events start and end with :VEVENT), as per the specification (see [ic_spec\(\)](#)).

Usage

```
ic_list(x, pattern = ":VEVENT", include_pattern = FALSE)
```

Arguments

x Lines read-in in from an iCal file

pattern A text string to search from (an ical field)

include_pattern should the pattern be included in the output? FALSE by default.

Examples

```
ic_list(ical_example)
ics_file <- system.file("extdata", "england-and-wales.ics", package = "ical")
x = readLines(ics_file)
ics_list = ic_list(x)
ics_list[1:2]
ic_list(x, include_pattern = TRUE)
```

`ic_read`*Read ics file*

Description

Read ics file

Usage

```
ic_read(file)
```

Arguments

`file` ics file to read

Value

object of class ics

Examples

```
f <- system.file("extdata", "england-and-wales.ics", package = "calendar")
ics_df = ic_read(f)
head(ics_df)
```

`ic_spec`*View or download the ical specification*

Description

This function shows the spec underlying iCal files.

Usage

```
ic_spec(mode = "view", spec_url = "https://tools.ietf.org/rfc/rfc5545.txt")
```

Arguments

`mode` character string specifying whether to look at the spec (mode = "view", the default) or read it in (mode = "read")

`spec_url` the location of the latest version of the spec, from tools.ietf.org/rfc/rfc5545.txt by default

ic_vector	<i>Return a named vector from raw iCal text</i>
-----------	---

Description

This is designed to be a helper function for creating data frames ical lists.

Usage

```
ic_vector(x, pattern = "[A-Z]-?[A-Z]")
```

Arguments

x	Lines read-in in from an iCal file
pattern	A text string to search from (an ical field)

Examples

```
x = ical_example[18:19]
ic_vector(x)
```

ic_write	<i>Write ics file</i>
----------	-----------------------

Description

Write ics file

Usage

```
ic_write(ic, file, zulu = FALSE)
```

Arguments

ic	object of class ical
file	ics file to write
zulu	is the datetime in Zulu time? FALSE by default, which means the calendar's current timezone is used.

Examples

```
ic <- ical(ical_example)
ic_write(ic, file.path(tempdir(), "ic.ics"))
f <- system.file("extdata", "example.ics", package = "calendar")
identical(readLines(file.path(tempdir(), "ic.ics")), readLines(f))
f <- system.file("extdata", "england-and-wales.ics", package = "calendar")
ics_df <- ic_read(f)
ic_write(ics_df, file.path(tempdir(), "ic.ics"))
# test similarity between files with diff tool like meld - from shell:
# meld ic.ics inst/extdata/england-and-wales.ics
```

properties

The key 'properties' that are allowed in ical files

Description

The key 'properties' that are allowed in ical files

Usage

```
properties
```

Format

An object of class character of length 54.

Examples

```
# doc = ic_spec(mode = "read")
# key_locations = grepl(pattern = " \\[A-Z]", x = doc)
# summary(key_locations)
# doc_key = doc[key_locations]
# # regexplain::regex_gadget(text = doc_key) # explore
# key_properties = grepl(pattern = "3.7|3.8", x = doc)
# doc_properties = doc[key_locations & key_properties]
# # regexplain::regex_gadget(text = doc_properties) # explore
# properties = regmatches(doc_properties, regexpr('[A-Z][A-Z]+', doc_properties))
# usethis::use_data(properties)
```

properties_core	<i>The key 'properties' that are allowed in ical files</i>
-----------------	--

Description

The key 'properties' that are allowed in ical files

Usage

```
properties_core
```

Format

An object of class list of length 4.

Examples

```
properties_core = list(
  "UID"="UID",
  "DTSTART"="DTSTART",
  "DTEND"="DTEND",
  "SUMMARY"="SUMMARY"
)
```

properties_ical	<i>ical default VCALENDAR properties in one line vectors.</i>
-----------------	---

Description

ical default VCALENDAR properties in one line vectors.

Usage

```
properties_ical
```

Format

An object of class character of length 5.

Examples

```
# properties_ical <- ical_example[1:5]
# properties_ical
# properties_ical[2] <- "PRODID:-//ATFutures/ical //EN"
# usethis::use_data(properties_ical)
```

Index

- * **datasets**
 - formats, [3](#)
 - holidays, [4](#)
 - ical_example, [5](#)
 - ical_outlook, [5](#)
 - properties, [16](#)
 - properties_core, [17](#)
 - properties_ical, [17](#)
- calendar, [2](#)
- calendar-package (calendar), [2](#)
- formats, [3](#)
- holidays, [4](#)
- ic_attributes_vec, [6](#)
- ic_bind_list, [7](#)
- ic_char_date(ic_char_datetime), [8](#)
- ic_char_datetime, [8](#)
- ic_char_event, [8](#)
- ic_character, [7](#)
- ic_dataframe, [9](#)
- ic_date, [9](#)
- ic_datetime, [10](#)
- ic_event, [10](#)
- ic_extract, [11](#)
- ic_extract_raw, [12](#)
- ic_find, [12](#)
- ic_guid, [13](#)
- ic_list, [13](#)
- ic_read, [14](#)
- ic_spec, [14](#)
- ic_spec(), [13](#)
- ic_vector, [15](#)
- ic_write, [15](#)
- ical, [4](#)
- ical_example, [5](#)
- ical_outlook, [5](#)
- properties, [16](#)
- properties_core, [17](#)
- properties_ical, [17](#)