

Package ‘chest’

July 22, 2025

Type Package

Title Change-in-Estimate Approach to Assess Confounding Effects

Version 0.3.7

Description Applies the change-in-effect estimate method to assess confounding effects in medical and epidemiological research (Greenland & Pearce (2016) [doi:10.1146/annurev-publhealth-031914-122559](https://doi.org/10.1146/annurev-publhealth-031914-122559)). It starts with a crude model including only the outcome and exposure variables. At each of the subsequent steps, one variable which creates the largest change among the remaining variables is selected. This process is repeated until all variables have been entered into the model (Wang Z. Stata Journal 2007; 7, Number 2, pp. 183–196). Currently, the 'chest' package has functions for linear regression, logistic regression, negative binomial regression, Cox proportional hazards model and conditional logistic regression.

License GPL-2

Encoding UTF-8

LazyData true

Imports broom, ggplot2, survival, grid, forestplot, MASS, tibble, dplyr

Depends R (>= 2.20)

RoxygenNote 7.2.3

Suggests spelling, knitr, rmarkdown

VignetteBuilder knitr

Language en-US

NeedsCompilation no

Author Zhiqiang Wang [aut, cre]

Maintainer Zhiqiang Wang <menzies.uq@gmail.com>

Repository CRAN

Date/Publication 2023-03-23 09:50:13 UTC

Contents

chest	2
chest_clogit	3
chest_cox	4
chest_forest	5
chest_glm	6
chest_lm	7
chest_nb	8
chest_plot	9
diab_df	11
Index	12

chest	<i>Change-in-Estimate Approach to Assess Confounding Effects</i>
-------	--

Description

In clinical trials and epidemiological studies, the association between an exposure and the outcome of interest in a study can be estimated by *regression coefficients*, *odds ratios* or *hazard ratios* depending on the nature of study designs and outcome measurements. We use a general term *effect estimate* here for any of those measurements in this document. Based on those measurements, we determine if a treatment is effective (or detrimental) or a factor is a risk factor. Imbalanced distributions of other factors could bias the effect estimates, called *confounding*. One way to assess the confounding effect of a factor is to examine the difference in effect estimates between models with and without a specific factor. 'chest' allows users quickly calculate the changes when potential confounding factors are sequentially added to the model in a stepwise fashion. At each step, one variable which creates the largest change (%) of the effect estimate among the remaining variables is added to the model. 'chest' returns a graph and a data frame (table) with effect estimates (95% CI) and change (%) values. The package currently has the following main functions: 'chest_lm' for linear regression, 'chest_glm' for logistic regression and Poisson regression, 'chest_clogit' for matched logistic regression, 'chest_nb' for negative binomial regression and 'chest_cox' for Cox proportional hazards models.

References

Zhiqiang Wang (2007) <<https://doi.org/10.1177/1536867X0700700203>>

Examples

```
? chest_glm
? chest_cox
? chest_clogit
? chest_lm
? chest_nb
? chest_plot
? chest_forest
```

chest_clogit	<i>Assessing confounding effects using conditional logistic regression models</i>
--------------	---

Description

'chest_clogit' is used to fit many *Conditional Logistic Regression* models to assess confounding effects.

Usage

```
chest_clogit(  
  crude,  
  xlist,  
  data,  
  method = "exact",  
  na_omit = TRUE,  
  plus = " + ",  
  indicate = FALSE,  
  ...  
)
```

Arguments

crude	An object of <i>formula</i> for the initial model, generally crude model. However, any other variables can also be included here as the initial model.
xlist	A <i>vector</i> of characters with all variable names of potential confounders.
data	<i>Data frame</i> .
method	See 'clogit', default is the "exact" method.
na_omit	Remove all missing values, default: 'na_omit = TRUE'.
plus	Change the + sign before variable names.
indicate	indicate the calculation progress.
...	Further optional arguments.

Value

A table with effect estimates and their changes at all steps.

See Also

chest
'clogit' in 'survival'

Examples

```
vlist <- c("Age", "Sex", "Married", "Cancer", "CVD", "Education", "Income")
chest_clogit(
  crude = "Endpoint ~ Diabetes + strata(mid)",
  xlist = vlist, data = diab_df
)
```

chest_cox	<i>Assessing confounding effects using Cox Proportional Hazards regression models</i>
-----------	---

Description

'chest_cox' is used to assess confounding effects using Proportional Hazards Regression Model ('coxph' from **'survival'** package). It presents the effect estimates (such as hazard ratios) for the association between exposure and outcome variables by adding other variables (potential confounders) to the model sequentially. The order of variables to be added is based on the magnitudes of the changes in effect estimates.

Usage

```
chest_cox(
  crude,
  xlist,
  data,
  na_omit = TRUE,
  plus = " + ",
  indicate = FALSE,
  ...
)
```

Arguments

crude	An object of <i>formula</i> for initial model, generally crude model. However, any other variables can also be included here as the initial model.
xlist	A <i>vector</i> of characters with variable names of potential confounders.
data	<i>Data frame</i> .
na_omit	Remove all missing values, default: 'na_omit = TRUE'.
plus	Change the + sign before variable names.
indicate	indicate the progress.
...	Further optional arguments for forestplot.

Value

A table with effect estimates and their changes at all steps.

See Also**'survival'****Examples**

```
vlist <- c("Age", "Sex", "Married", "Cancer", "CVD", "Education", "Income")

chest_cox(crude = "Surv(t0, t1, Endpoint) ~ Diabetes", xlist = vlist, data = diab_df)
```

chest_forest	<i>Plot effect estimates and change-in-estimate values (forestplot type)</i>
--------------	--

Description

'chest_forest' plots effect estimates and change-in-estimate values with forestplot package.

Usage

```
chest_forest(
  data,
  var_lab = "Variables",
  est_lab = "Estimate (95% CI)",
  change_lab = "Change, %",
  digits = "%.2f",
  digits_change = "%.1f",
  hrzl_lines = gpar(col = "#444444"),
  plus = " + ",
  ...
)
```

Arguments

data	<i>Object</i> from chest_cox, chest_glm, chest_lm, chest_clogit, or chest_nb, including effect estimate values and change-in-estimate values.
var_lab	<i>Character</i> string for the column name of variables in the graph.
est_lab	<i>Character</i> string for the column name of effect estimates.
change_lab	<i>Character</i> string for the column name of "Changes".
digits	Set the display format for number in the graph other than the "Change" column. Default: "%.2f"
digits_change	Set the format for the "Change" column. Default: "%.1f"
hrzl_lines	A <i>logic</i> to include or remove horizontal line.
plus	Change the + sign before variable names.
...	Further optional arguments for forestplot.

Value

A table with effect estimates and their changes at all steps.

See Also

'forestplot'

Examples

```
vlist <- c("Age", "Sex", "Married", "Cancer", "CVD", "Education", "Income")
results <- chest_cox(crude = "Surv(t0, t1, Endpoint) ~ Diabetes", xlist = vlist, data = diab_df)
chest_forest(results)
```

chest_glm	<i>Assessing confounding effects using Generalized Linear regression models</i>
-----------	---

Description

Please note: 'chest_glm' is used to assess confounding effects using Generalized Linear Models, such as logistic regression and Poisson regression with 'glm'. It presents *odds ratios* or *rate ratios* for the association between exposure and outcome variables by adding other variables (potential confounders) to the model sequentially. The order of variables to be added is based on the magnitudes of the changes in effect estimates.

Usage

```
chest_glm(
  crude,
  xlist,
  data,
  family = "binomial",
  method = "glm.fit",
  na_omit = TRUE,
  indicate = FALSE,
  plus = " + ",
  ...
)
```

Arguments

crude	An object of <i>formula</i> for initial model, generally crude model. However, any other variables can also be included here as the initial model.
xlist	A <i>vector</i> of characters with all variable names of potential confounders.
data	<i>Data frame</i> .
family	Description of the error distribution. Default is "binomial".

method	Method to detect for singularity.
na_omit	Remove all missing values, default: 'na_omit = TRUE'.
indicate	indicate progress.
plus	Change the + sign before variable names.
...	Further optional arguments for forestplot.

Value

A table with effect estimates and their changes at all steps.

See Also

'glm' 'stats'

Examples

```
chest_glm(  
  crude = "Endpoint ~ Diabetes", xlist = c("Age", "Sex", "Married"),  
  na_omit = TRUE, data = diab_df  
)
```

chest_lm	<i>Assessing confounding effects using Linear regression models</i>
----------	---

Description

'chest_lm' is used to assess confounding effects using Linear Regression Models. It presents linear regression coefficients as effect estimates and changes when other variables are added sequentially to the model.

Usage

```
chest_lm(  
  crude,  
  xlist,  
  data,  
  method = "qr",  
  na_omit = TRUE,  
  indicate = FALSE,  
  plus = " + ",  
  ...  
)
```

Arguments

<code>crude</code>	An object of <i>formula</i> for initial model, generally crude model. However, any other variables can also be included here as the initial model.
<code>xlist</code>	A <i>vector</i> of characters with all variable names of potential confounders.
<code>data</code>	<i>Data frame</i> .
<code>method</code>	The method to be used; see ' lm '.
<code>na_omit</code>	Remove all missing values.
<code>indicate</code>	indicate progress
<code>plus</code>	Change the + sign before variable names.
<code>...</code>	Further optional arguments.

Value

A table with effect estimates and their changes at all steps.

See Also

'lm' of '**stats**'

Examples

```
vlist <- c("Age", "Sex", "Married", "Cancer", "CVD", "Education", "Income")
chest_lm(crude = "BMI ~ Diabetes", xlist = vlist, data = diab_df, na_omit = TRUE)
```

chest_nb	<i>Assessing confounding effects using Negative Binomial regression models</i>
----------	--

Description

It fits negative binomial regression models to present *rate ratios* for the association between exposure and outcome variables by adding other variables (potential confounders) to the model sequentially. The order of variables to be added is based on the magnitudes of the changes in effect estimates.

Usage

```
chest_nb(
  crude,
  xlist,
  data,
  method = "glm.fit",
  na_omit = TRUE,
  indicate = FALSE,
  plus = " + ",
  ...
)
```


Arguments

crude	An object of <i>formula</i> for initial model, generally crude model. However, any other variables can also be included here as the initial model.
xlist	A <i>vector</i> of characters with all variable names of potential confounders.
data	<i>Data frame</i> .
method	Method to detect for singularity.
na_omit	Remove all missing values, default: 'na_omit = TRUE'.
indicate	indicate progress.
plus	Change the + sign before variable names.
...	Further optional arguments.

Value

A table with effect estimates and their changes at all steps.

See Also

'glm.nb' of 'MASS'

Examples

```
library(MASS)
df <- quine
results <- chest_nb("Days ~ Lrn", xlist = c("Sex", "Age", "Eth"), data = df)
results$data
```

chest_plot

Plot effect estimate and change-in-estimate values (ggplot type)

Description

Plot effect estimate and change-in-estimate values (ggplot type)

Usage

```
chest_plot(
  data,
  no_values = FALSE,
  ylab = NULL,
  xlab = NULL,
  change_lab = "Change, %",
  digits = "%.2f",
  digits_change = "%.1f",
  plus = " + ",
  nudge_y = 0.4,
```

```

    nudge_x = NULL,
    hjust = 0.5,
    height = 0.06,
    point_size = 3,
    point_shape = 15,
    vline_type = "dashed",
    vline_color = "grey50",
    ebar_color = "grey50",
    zero = 1,
    value_position = NULL,
    ...
)

```

Arguments

data	<i>Object</i> from chest_cox, chest_glm, chest_lm, chest_clogit, or chest_nb, including effect estimate values and change-in-estimate values.
no_values	Suppress effect estimate values in plot, default is FALSE.
ylab	Add y label.
xlab	Add x label.
change_lab	<i>Character</i> string for the column name of "Change" in the graph
digits	Set the display format for number in the graph other than the "Change" column. Default: "%.2f"
digits_change	Set the format for the "Change" column. Default: "%.1f"
plus	Change the + sign before variable names.
nudge_y	Adjust vertical distance between values and point marker.
nudge_x	Adjust horizontal distance between values and point marker.
hjust	Adjust horizontal alignment.
height	Change the height of error bars.
point_size	Change point marker size.
point_shape	Change point marker shape.
vline_type	Change vertical line type.
vline_color	Change vertical line color.
ebar_color	Change error bar color.
zero	x-axis coordinate for vertical non-effect line, see forestplot .
value_position	Change the position of value labels.
...	Further optional arguments for forestplot.

Value

a ggplot object.

See Also**'ggplot2'****Examples**

```
vlist <- c("Age", "Sex", "Married", "Education", "Income")
results <- chest_glm(
  crude = "Endpoint ~ Diabetes",
  xlist = vlist, na_omit = TRUE, data = diab_df
)
chest_plot(results)
```

diab_df

Example data: Health outcomes of 2372 adults with and without diabetes

Description

A data frame with 2372 rows and 14 variables with diabetes status diabetes and mortality status endpoint. For the purpose of demonstrate, assume that we are interested in the association between diabetes and endpoint. Other variables are considered as possible confounders. The purposes of this dataset is to illustrate those functions in **chest** package only. Therefore, we assume it is a cohort design for Cox Proportional Hazard regression, and a case-control design for logistic regression.

Usage

```
diab_df
```

Format

A data frame with 2372 rows and 14 variables:

Diabetes diabetes status 1: with diabetes 0: without diabetes

Endpoint mortality status 1: reached end point, and 0: survived

Age Age, in years

Sex sex, 1: male, 2: Female

BMI Body mass index

Married marital status 1: married, 0: not

Smoke smoking status 1: smoker, 0: non-smoker

CVD cardiovascular disease 1: yes 0: no

Cancer cancer 1: yes, 0: no

Education education 1: high, 0: low

Income income 1: high, 0: low

t0 time (age) at the start of the follow-up

t1 time (age) at the end of the follow-up

mid matched set id, for conditional logistic regression

Index

* datasets

diab_df, [11](#)

chest, [2](#)

chest_clogit, [3](#)

chest_cox, [4](#)

chest_forest, [5](#)

chest_glm, [6](#)

chest_lm, [7](#)

chest_nb, [8](#)

chest_plot, [9](#)

diab_df, [11](#)