

Package ‘chopthin’

July 22, 2025

Type Package

Title The Chopthin Resampler

Version 0.2.2

Date 2017-09-26

Author Axel Gandy and F. Din-Houn Lau

Maintainer Axel Gandy <a.gandy@imperial.ac.uk>

Description Resampling is a standard step in particle filtering and in sequential Monte Carlo. This package implements the chopthin resampler, which keeps a bound on the ratio between the largest and the smallest weights after resampling.

License GPL-3

Imports Rcpp (>= 0.11.2)

LinkingTo Rcpp

Suggests testthat

RoxxygenNote 6.0.1

NeedsCompilation yes

Repository CRAN

Date/Publication 2017-09-28 09:00:36 UTC

Contents

chopthin	2
Index	3

chopthin

The Chopthin Resampler

Description

A fast implementation of the Chopthin resampler. Can be used as the resampling step in particle filters and in sequential Monte Carlo.

Usage

```
chopthin(w, N, eta = 5.828427, normalise = TRUE, checks = TRUE)
```

Arguments

w	a vector of weights
N	target number of particles
eta	upper bound on the ratio between the weights. Must be ≥ 4 . If $\eta = \text{Inf}$ then only thinning is performed, requiring the number of weights to be at least N.
normalise	Flag for controlling if the returned weights should be normalised. If TRUE (default) then the sum of the returned weights will sum to N. If FALSE then the returned weights have the same sum as the original weights (within the numerical precision).
checks	Flag controlling if checks on the input and the result should be performed. Default TRUE.

Value

A list with two elements: new weights and indices of the ancestors of the new particles. The weights are normalised to add up to N.

References

A Gandy and F. D-H Lau. The chopthin algorithm for resampling. IEEE Transactions on Signal Processing, 64(16):4273–4281, 2016

Examples

```
chopthin(runif(10), N=10)
chopthin(runif(10), N=20, 4)
chopthin(runif(10), N=5)
chopthin(runif(10), N=1)
```

Index

chopthin, [2](#)