

Package ‘cubar’

July 22, 2025

Title Codon Usage Bias Analysis

Version 1.1.0

Description A suite of functions for rapid and flexible analysis of codon usage bias. It provides in-depth analysis at the codon level, including relative synonymous codon usage (RSCU), tRNA weight calculations, machine learning predictions for optimal or preferred codons, and visualization of codon-anticodon pairing. Additionally, it can calculate various gene-specific codon indices such as codon adaptation index (CAI), effective number of codons (ENC), fraction of optimal codons (Fop), tRNA adaptation index (tAI), mean codon stabilization coefficients (CSCg), and GC contents (GC/GC3s/GC4d). It also supports both standard and non-standard genetic code tables found in NCBI, as well as custom genetic code tables.

License MIT + file LICENSE

URL <https://github.com/mt1022/cubar>, <https://mt1022.github.io/cubar/>

BugReports <https://github.com/mt1022/cubar/issues>

Encoding UTF-8

LazyData true

LazyDataCompression bzip2

Imports Biostrings (>= 2.60.0), IRanges (>= 2.34.0), data.table (>= 1.14.0), ggplot2 (>= 3.3.5), rlang (>= 0.4.11)

Depends R (>= 4.1.0)

Suggests knitr, rmarkdown, testthat (>= 3.0.0)

VignetteBuilder knitr

RoxygenNote 7.3.2

Config/testthat/edition 3

NeedsCompilation no

Author Hong Zhang [aut, cre] (ORCID: <<https://orcid.org/0000-0002-4064-9432>>),
Mengyue Liu [aut],
Bu Zi [aut]

Maintainer Hong Zhang <mt1022.dev@gmail.com>

Repository CRAN
Date/Publication 2024-12-07 07:50:02 UTC

Contents

aa2codon 3

check_cds 3

codon_diff 4

codon_optimize 5

count_codons 6

create_codon_table 7

est_csc 7

est_optimal_codons 8

est_rscu 9

est_trna_weight 10

get_cai 11

get_codon_table 12

get_cscg 12

get_dp 13

get_enc 14

get_fop 15

get_gc 16

get_gc3s 16

get_gc4d 17

get_tai 18

human_mt 18

plot_ca_pairing 19

rev_comp 20

seq_to_codons 20

show_codon_tables 21

slide 21

slide_apply 22

slide_codon 23

slide_plot 23

yeast_cds 24

yeast_exp 24

yeast_half_life 25

yeast_trna 26

yeast_trna_gcn 27

aa2codon	<i>amino acids to codons</i>
----------	------------------------------

Description

A data.frame of mapping from amino acids to codons

Usage

```
aa2codon
```

Format

a data.frame with two columns: amino_acid, and codon.

amino_acid amino acid corresponding to the codon

codon codon identity

Source

It is actually the standard genetic code.

Examples

```
aa2codon
```

check_cds	<i>Quality control of CDS</i>
-----------	-------------------------------

Description

check_cds performs quality control of CDS sequences by filtering some peculiar sequences and optionally remove start or stop codons.

Usage

```
check_cds(  
  seqs,  
  codon_table = get_codon_table(),  
  min_len = 6,  
  check_len = TRUE,  
  check_start = TRUE,  
  check_stop = TRUE,  
  check_istop = TRUE,  
  rm_start = TRUE,  
  rm_stop = TRUE,  
  start_codons = c("ATG")  
)
```

Arguments

seqs	input CDS sequences
codon_table	codon table matching the genetic code of seqs
min_len	minimum CDS length in nt
check_len	check whether CDS length is divisible by 3
check_start	check whether CDSs have start codons
check_stop	check whether CDSs have stop codons
check_istop	check internal stop codons
rm_start	whether to remove start codons
rm_stop	whether to remove stop codons
start_codons	vector of start codons

Value

DNASTringSet of filtered (and trimmed) CDS sequences

Examples

```
# CDS sequence QC for a sample of yeast genes
s <- head(yeast_cds, 10)
print(s)
check_cds(s)
```

codon_diff	<i>Differential codon usage analysis</i>
------------	--

Description

codon_diff takes two set of coding sequences and perform differential codon usage analysis.

Usage

```
codon_diff(seqs1, seqs2, codon_table = get_codon_table())
```

Arguments

seqs1	DNASTringSet, or an object that can be coerced to a DNASTringSet
seqs2	DNASTringSet, or an object that can be coerced to a DNASTringSet
codon_table	a table of genetic code derived from get_codon_table or create_codon_table.

Value

a data.table of the differential codon usage analysis. Global tests examine whether a codon is used differently relative to all the other codons. Family tests examine whether a codon is used differently relative to other codons that encode the same amino acid. Subfamily tests examine whether a codon is used differently relative to other synonymous codons that share the same first two nucleotides. Odds ratio > 1 suggests a codon is used at higher frequency in seqs1 than in seqs2.

Examples

```
yeast_exp_sorted <- yeast_exp[order(yeast_exp$fpkm),]
seqs1 <- yeast_cds[names(yeast_cds) %in% head(yeast_exp_sorted$gene_id, 1000)]
seqs2 <- yeast_cds[names(yeast_cds) %in% tail(yeast_exp_sorted$gene_id, 1000)]
cudiff <- codon_diff(seqs1, seqs2)
```

codon_optimize	<i>Optimize codons</i>
----------------	------------------------

Description

codon_optimize takes a coding sequence (without stop codon) and replace each codon to the corresponding synonymous optimal codon.

Usage

```
codon_optimize(
  seq,
  optimal_codons,
  codon_table = get_codon_table(),
  level = "subfam"
)
```

Arguments

seq	DNAString, or an object that can be coerced to a DNAString.
optimal_codons	table optimze codons as generated by est_optimal_codons.
codon_table	a table of genetic code derived from get_codon_table or create_codon_table.
level	"subfam" (default) or "amino_acid". Optimize codon usage at which level.

Value

a DNAString of the optimized coding sequence.

Examples

```
cf_all <- count_codons(yeast_cds)
optimal_codons <- est_optimal_codons(cf_all)
seq <- 'ATGCTACGA'
codon_optimize(seq, optimal_codons)
```

count_codons	<i>Count occurrences of different codons</i>
--------------	--

Description

count_codons tabulates the occurrences of all the 64 codons in input CDSs

Usage

```
count_codons(seqs, ...)
```

Arguments

seqs	CDS sequences, DNASTringSet.
...	additional arguments passed to Biostrings::trinucleotideFrequency.

Value

matrix of codon (column) frequencies of each CDS (row).

Examples

```
# count codon occurrences
cf_all <- count_codons(yeast_cds)
dim(cf_all)
cf_all[1:5, 1:5]
count_codons(yeast_cds[1])
```

create_codon_table	<i>create custom codon table from a data frame</i>
--------------------	--

Description

create_codon_table creates codon table from data frame of aa to codon mapping.

Usage

```
create_codon_table(aa2codon)
```

Arguments

aa2codon a data frame with two columns: amino_acid (Ala, Arg, etc.) and codon.

Value

a data.table with four columns: aa_code, amino_acid, codon, and subfam.

Examples

```
head(aa2codon)
create_codon_table(aa2codon = aa2codon)
```

est_csc	<i>Estimate Codon Stabilization Coefficient</i>
---------	---

Description

get_csc calculate codon occurrence to mRNA stability correlation coefficients (Default to Pearson's).

Usage

```
est_csc(
  seqs,
  half_life,
  codon_table = get_codon_table(),
  cor_method = "pearson"
)
```

Arguments

seqs	CDS sequences of all protein-coding genes. One for each gene.
half_life	data.frame of mRNA half life (gene_id & half_life are column names).
codon_table	a table of genetic code derived from get_codon_table or create_codon_table.
cor_method	method name passed to 'cor.test' used for calculating correlation coefficients.

Value

data.table of optimal codons.

References

Presnyak V, Alhusaini N, Chen YH, Martin S, Morris N, Kline N, Olson S, Weinberg D, Baker KE, Graveley BR, et al. 2015. Codon optimality is a major determinant of mRNA stability. *Cell* 160:1111-1124.

Examples

```
# estimate yeast mRNA CSC
est_csc(yeast_cds, yeast_half_life)
```

est_optimal_codons	<i>Estimate optimal codons</i>
--------------------	--------------------------------

Description

est_optimal_codons determine optimal codon of each codon family with binomial regression. Usage of optimal codons should correlate negatively with enc.

Usage

```
est_optimal_codons(
  cf,
  codon_table = get_codon_table(),
  level = "subfam",
  gene_score = NULL,
  fdr = 0.001
)
```

Arguments

cf	matrix of codon frequencies as calculated by count_codons().
codon_table	a table of genetic code derived from get_codon_table or create_codon_table.
level	"subfam" (default) or "amino_acid". For which level to determine optimal codons.
gene_score	a numeric vector of scores for genes. The order of values should match with gene orders in the codon frequency matrix. The length of the vector should be equal to the number of rows in the matrix. The scores could be gene expression levels (RPKM or TPM) that are optionally log-transformed (for example, with log1p). The opposite of ENC will be used by default if gene_score is not provided.
fdr	false discovery rate used to determine optimal codons.

Value

data.table of optimal codons.

Examples

```
# perform binomial regression for optimal codon estimation
cf_all <- count_codons(yeast_cds)
codons_opt <- est_optimal_codons(cf_all)
codons_opt <- codons_opt[optimal == TRUE]
codons_opt
```

 est_rscu

Estimate RSCU

Description

est_rscu returns the RSCU value of codons

Usage

```
est_rscu(
  cf,
  weight = 1,
  pseudo_cnt = 1,
  codon_table = get_codon_table(),
  level = "subfam"
)
```

Arguments

cf	matrix of codon frequencies as calculated by count_codons().
weight	a vector of the same length as seqs that gives different weights to CDSs when count codons. for example, it could be gene expression levels.
pseudo_cnt	pseudo count to avoid dividing by zero. This may occur when only a few sequences are available for RSCU calculation.
codon_table	a table of genetic code derived from get_codon_table or create_codon_table.
level	"subfam" (default) or "amino_acid". For which level to determine RSCU.

Value

a data.table of codon info. RSCU values are reported in the last column.

References

Sharp PM, Tuohy TM, Mosurski KR. 1986. Codon usage in yeast: cluster analysis clearly differentiates highly and lowly expressed genes. Nucleic Acids Res 14:5125-5143.

Examples

```
# compute RSCU of all yeast genes
cf_all <- count_codons(yeast_cds)
est_rscu(cf_all)

# compute RSCU of highly expressed (top 500) yeast genes
heg <- head(yeast_exp[order(-yeast_exp$fpkm), ], n = 500)
cf_heg <- count_codons(yeast_cds[heg$gene_id])
est_rscu(cf_heg)
```

est_trna_weight	<i>Estimate tRNA weight w</i>
-----------------	-------------------------------

Description

est_trna_weight compute the tRNA weight per codon for TAI calculation. This weight reflects relative tRNA availability for each codon.

Usage

```
est_trna_weight(
  trna_level,
  codon_table = get_codon_table(),
  s = list(WC = 0, IU = 0, IC = 0.4659, IA = 0.9075, GU = 0.7861, UG = 0.6295)
)
```

Arguments

trna_level	named vector of tRNA level (or gene copy numbers), one value for each anti-codon. vector names are anticodons.
codon_table	a table of genetic code derived from get_codon_table or create_codon_table.
s	list of non-Waston-Crick pairing panelty.

Value

data.table of tRNA expression information.

References

dos Reis M, Savva R, Wernisch L. 2004. Solving the riddle of codon usage preferences: a test for translational selection. Nucleic Acids Res 32:5036-5044.

Examples

```
# estimate codon tRNA weight for yeasts
est_trna_weight(yeast_trna_gcn)
```

get_cai	<i>Calculate CAI</i>
---------	----------------------

Description

get_cai calculates Codon Adaptation Index (CAI) of each input CDS

Usage

```
get_cai(cf, rscu, level = "subfam")
```

Arguments

cf	matrix of codon frequencies as calculated by count_codons().
rscu	rscu table containing CAI weight for each codon. This table could be generated with est_rscu or prepared manually.
level	"subfam" (default) or "amino_acid". For which level to determine CAI.

Value

a named vector of CAI values

References

Sharp PM, Li WH. 1987. The codon Adaptation Index—a measure of directional synonymous codon usage bias, and its potential applications. Nucleic Acids Res 15:1281-1295.

Examples

```
# estimate CAI of yeast genes based on RSCU of highly expressed genes
heg <- head(yeast_exp[order(-yeast_exp$fpkm), ], n = 500)
cf_all <- count_codons(yeast_cds)
cf_heg <- cf_all[heg$gene_id, ]
rscu_heg <- est_rscu(cf_heg)
cai <- get_cai(cf_all, rscu_heg)
head(cai)
hist(cai)
```

get_codon_table	<i>get codon table by NCBI gene code ID</i>
-----------------	---

Description

get_codon_table creates a codon table based on the given id of genetic code in NCBI.

Usage

```
get_codon_table(gcid = "1")
```

Arguments

gcid	a string of genetic code id. run show_codon_tables() to see available codon tables.
------	---

Value

a data.table with four columns: aa_code, amino_acid, codon, and subfam.

Examples

```
# Standard genetic code
get_codon_table()

# Vertebrate Mitochondrial genetic code
get_codon_table(gcid = '2')
```

get_cscg	<i>Mean Codon Stabilization Coefficients</i>
----------	--

Description

get_cscg calculates Mean Codon Stabilization Coefficients of each CDS.

Usage

```
get_cscg(cf, csc)
```

Arguments

cf	matrix of codon frequencies as calculated by count_codons().
csc	table of Codon Stabilization Coefficients as calculated by est_csc().

Value

a named vector of cscg values.

References

Presnyak V, Alhusaini N, Chen YH, Martin S, Morris N, Kline N, Olson S, Weinberg D, Baker KE, Graveley BR, et al. 2015. Codon optimality is a major determinant of mRNA stability. *Cell* 160:1111-1124.

Examples

```
# estimate CSCg of yeast genes
yeast_csc <- est_csc(yeast_cds, yeast_half_life)
cf_all <- count_codons(yeast_cds)
cscg <- get_cscg(cf_all, csc = yeast_csc)
head(cscg)
hist(cscg)
```

get_dp	<i>Deviation from Proportionality</i>
--------	---------------------------------------

Description

get_dp calculates Deviation from Proportionality of each CDS.

Usage

```
get_dp(
  cf,
  host_weights,
  codon_table = get_codon_table(),
  level = "subfam",
  missing_action = "ignore"
)
```

Arguments

cf	matrix of codon frequencies as calculated by count_codons().
host_weights	a named vector of tRNA weights for each codon that reflects the relative availability of tRNAs in the host organism.
codon_table	a table of genetic code derived from get_codon_table or create_codon_table.
level	"subfam" (default) or "amino_acid". If "subfam", the deviation is calculated at the codon subfamily level. Otherwise, the deviation is calculated at the amino acid level.
missing_action	Actions to take when no codon of a group were found in a CDS. Options are "ignore" (default), or "zero" (set codon proportions to 0).

Value

a named vector of dp values.

References

Chen F, Wu P, Deng S, Zhang H, Hou Y, Hu Z, Zhang J, Chen X, Yang JR. 2020. Dissimilation of synonymous codon usage bias in virus-host coevolution due to translational selection. *Nat Ecol Evol* 4:589-600.

Examples

```
# estimate DP of yeast genes
cf_all <- count_codons(yeast_cds)
trna_weight <- est_trna_weight(yeast_trna_gcn)
trna_weight <- setNames(trna_weight$w, trna_weight$codon)
dp <- get_dp(cf_all, host_weights = trna_weight)
head(dp)
hist(dp)
```

get_enc	<i>Calculate ENC</i>
---------	----------------------

Description

get_enc computes ENC of each CDS

Usage

```
get_enc(cf, codon_table = get_codon_table(), level = "subfam")
```

Arguments

cf	matrix of codon frequencies as calculated by count_codons().
codon_table	codon_table a table of genetic code derived from get_codon_table or create_codon_table.
level	"subfam" (default) or "amino_acid". For which level to determine ENC.

Value

vector of ENC values, sequence names are used as vector names

References

- Wright F. 1990. The 'effective number of codons' used in a gene. *Gene* 87:23-29. - Sun X, Yang Q, Xia X. 2013. An improved implementation of effective number of codons (NC). *Mol Biol Evol* 30:191-196.

Examples

```
# estimate ENC of yeast genes
cf_all <- count_codons(yeast_cds)
enc <- get_enc(cf_all)
head(enc)
hist(enc)
```

get_fop	<i>Fraction of optimal codons (Fop)</i>
---------	---

Description

get_fop calculates the fraction of optimal codons (Fop) of each CDS.

Usage

```
get_fop(cf, op = NULL, codon_table = get_codon_table(), ...)
```

Arguments

cf	matrix of codon frequencies as calculated by count_codons().
op	a character vector of optimal codons. Can be determined automatically by running est_optimal_codons.
codon_table	a table of genetic code derived from get_codon_table or create_codon_table.
...	other arguments passed to est_optimal_codons.

Value

a named vector of fop values.

References

Ikemura T. 1981. Correlation between the abundance of Escherichia coli transfer RNAs and the occurrence of the respective codons in its protein genes: a proposal for a synonymous codon choice that is optimal for the E. coli translational system. J Mol Biol 151:389-409.

Examples

```
# estimate Fop of yeast genes
cf_all <- count_codons(yeast_cds)
fop <- get_fop(cf_all)
head(fop)
hist(fop)
```

get_gc	<i>GC contents</i>
--------	--------------------

Description

Calculate GC content of the whole sequences.

Usage

```
get_gc(cf)
```

Arguments

cf matrix of codon frequencies as calculated by 'count_codons()'.

Value

a named vector of GC contents.

Examples

```
# estimate GC content of yeast genes
cf_all <- count_codons(yeast_cds)
gc <- get_gc(cf_all)
head(gc)
hist(gc)
```

get_gc3s	<i>GC contents at synonymous 3rd codon positions</i>
----------	--

Description

Calculate GC content at synonymous 3rd codon positions.

Usage

```
get_gc3s(cf, codon_table = get_codon_table(), level = "subfam")
```

Arguments

cf matrix of codon frequencies as calculated by count_codons().

codon_table a table of genetic code derived from get_codon_table or create_codon_table.

level "subfam" (default) or "amino_acid". For which level to determine GC content at synonymous 3rd codon positions.

Value

a named vector of GC3s values.

References

Peden JF. 2000. Analysis of codon usage.

Examples

```
# estimate GC3s of yeast genes
cf_all <- count_codons(yeast_cds)
gc3s <- get_gc3s(cf_all)
head(gc3s)
hist(gc3s)
```

get_gc4d

GC contents at 4-fold degenerate sites

Description

Calculate GC content at synonymous position of codons (using four-fold degenerate sites only).

Usage

```
get_gc4d(cf, codon_table = get_codon_table(), level = "subfam")
```

Arguments

cf	matrix of codon frequencies as calculated by count_codons().
codon_table	a table of genetic code derived from get_codon_table or create_codon_table.
level	"subfam" (default) or "amino_acid". For which level to determine GC contents at 4-fold degenerate sites.

Value

a named vector of GC4d values.

Examples

```
# estimate GC4d of yeast genes
cf_all <- count_codons(yeast_cds)
gc4d <- get_gc4d(cf_all)
head(gc4d)
hist(gc4d)
```

get_tai

Calculate TAI

Description

get_tai calculates tRNA Adaptation Index (TAI) of each CDS

Usage

```
get_tai(cf, trna_w)
```

Arguments

cf matrix of codon frequencies as calculated by count_codons().
trna_w tRNA weight for each codon, can be generated with est_trna_weight().

Value

a named vector of TAI values

References

dos Reis M, Savva R, Wernisch L. 2004. Solving the riddle of codon usage preferences: a test for translational selection. Nucleic Acids Res 32:5036-5044.

Examples

```
# calculate TAI of yeast genes based on genomic tRNA copy numbers
w <- est_trna_weight(yeast_trna_gcn)
cf_all <- count_codons(yeast_cds)
tai <- get_tai(cf_all, w)
head(tai)
hist(tai)
```

human_mt

human mitochondrial CDS sequences

Description

CDSs of 13 protein-coding genes in the human mitochondrial genome extracted from ENSEMBL Biomart

Usage

```
human_mt
```

Format

a DNASTringSet of 13 sequences

Source

<<https://www.ensembl.org/index.html>>

Examples

```
head(human_mt)
```

plot_ca_pairing	<i>Plot codon-anticodon pairing relationship</i>
-----------------	--

Description

plot_ca_pairing show possible codon-anticodons pairings

Usage

```
plot_ca_pairing(codon_table = get_codon_table(), plot = TRUE)
```

Arguments

codon_table	a table of genetic code derived from get_codon_table or create_codon_table.
plot	whether to plot the pairing relationship

Value

a data.table of codon info and RSCU values

Examples

```
ctab <- get_codon_table(gcid = '2')
pairing <- plot_ca_pairing(ctab)
head(pairing)
```

`rev_comp`*Reverse complement*

Description

`rev_comp` creates reverse complemented version of the input sequence

Usage

```
rev_comp(seqs)
```

Arguments

`seqs` input sequences, DNASTringSet or named vector of sequences

Value

reverse complemented input sequences as a DNASTringSet.

Examples

```
# reverse complement of codons
rev_comp(Biostrings::DNASTringSet(c('TAA', 'TAG')))
```

`seq_to_codons`*Convert CDS to codons*

Description

`seq_to_codons` converts a coding sequence to a vector of codons

Usage

```
seq_to_codons(seq)
```

Arguments

`seq` DNASTring, or an object that can be coerced to a DNASTring

Value

a character vector of codons

Examples

```
# convert a CDS sequence to a sequence of codons
seq_to_codons('ATGTGGTAG')
seq_to_codons(yeast_cds[[1]])
```

show_codon_tables	<i>show available codon tables</i>
-------------------	------------------------------------

Description

show_codon_tables print a table of available genetic code from NCBI through Biostrings::GENETIC_CODE_TABLE.

Usage

```
show_codon_tables()
```

Value

No return value (NULL). Available codon tables will be printed out directly.

Examples

```
# print available NCBI codon table IDs and descriptions.
show_codon_tables()
```

slide	<i>slide window interval generator</i>
-------	--

Description

slide generates a data.table with start, center, and end columns for a sliding window analysis.

Usage

```
slide(from, to, step = 1, before = 0, after = 0)
```

Arguments

from	integer, the start of the sequence
to	integer, the end of the sequence
step	integer, the step size
before	integer, the number of values before the center of a window
after	integer, the number of values after the center of a window

Value

data.table with start, center, and end columns

Examples

```
slide(1, 10, step = 2, before = 1, after = 1)
```

slide_apply	<i>apply a cub index to a sliding window</i>
-------------	--

Description

slide_apply applies a function to a sliding window of codons.

Usage

```
slide_apply(seq, .f, step = 1, before = 0, after = 0, ...)
```

Arguments

seq	DNAString, the sequence
.f	function, the codon index calculation function to apply, for example, get_enc.
step	integer, the step size in number of codons
before	integer, the number of codons before the center of a window
after	integer, the number of codons after the center of a window
...	additional arguments to pass to the function .f

Value

data.table with start, center, end, and codon usage index columns

Examples

```
slide_apply(yeast_cds[[1]], get_enc, step = 1, before = 10, after = 10)
```

slide_codon	<i>sliding window of codons</i>
-------------	---------------------------------

Description

slide_codon generates a data.table with start, center, and end columns for a sliding window analysis of codons.

Usage

```
slide_codon(seq, step = 1, before = 0, after = 0)
```

Arguments

seq	DNAString, the sequence
step	integer, the step size
before	integer, the number of codons before the center of a window
after	integer, the number of codons after the center of a window

Value

data.table with start, center, and end columns

Examples

```
x <- Biostrings::DNAString('ATCTACATAGCTACGTAGCTCGATGCTAGCATGCATCGTACGATCGTCGATCGTAG')
slide_codon(x, step = 3, before = 1, after = 1)
```

slide_plot	<i>plot sliding window codon usage</i>
------------	--

Description

slide_plot visualizes codon usage in sliding window.

Usage

```
slide_plot(windt, index_name = "Index")
```

Arguments

windt	data.table, the sliding window codon usage generated by slide_apply.
index_name	character, the name of the index to display.

Value

ggplot2 plot.

Examples

```
sw <- slide_apply(yeast_cds[[1]], get_enc, step = 1, before = 10, after = 10)
slide_plot(sw)
```

yeast_cds	<i>yeast CDS sequences</i>
-----------	----------------------------

Description

CDSs of all protein-coding genes in *Saccharomyces_cerevisiae*

Usage

yeast_cds

Format

a DNASTringSet of 6600 sequences

Source

<https://ftp.ensembl.org/pub/release-107/fasta/saccharomyces_cerevisiae/cds/Saccharomyces_cerevisiae.R64-1-1.cds.all.fa.gz>

Examples

```
head(yeast_cds)
```

yeast_exp	<i>yeast mRNA expression levels</i>
-----------	-------------------------------------

Description

Yeast mRNA FPKM determined from rRNA-depleted (RiboZero) total RNA-Seq libraries. RUN1_0_WT and RUN2_0_WT (0 min after RNA Pol II repression) were averaged and used here.

Usage

yeast_exp

Format

a data.frame with 6717 rows and three columns:

gene_id gene ID

gene_name gene name

fpkm mRNA expression level in Fragments per kilobase per million reads

Source

<<https://www.ncbi.nlm.nih.gov/geo/query/acc.cgi?acc=GSE57385>>

References

Presnyak V, Alhusaini N, Chen YH, Martin S, Morris N, Kline N, Olson S, Weinberg D, Baker KE, Graveley BR, et al. 2015. Codon optimality is a major determinant of mRNA stability. *Cell* 160:1111-1124.

Examples

```
head(yeast_exp)
```

yeast_half_life	<i>Half life of yeast mRNAs</i>
-----------------	---------------------------------

Description

Half life of yeast mRNAs in *Saccharomyces_cerevisiae* calculated from rRNA-deleted total RNAs by Presnyak et al.

Usage

```
yeast_half_life
```

Format

a data.frame with 3888 rows and three columns:

gene_id gene id

gene_name gene name

half_life mRNA half life in minutes

Source

<<https://doi.org/10.1016/j.cell.2015.02.029>>

References

Presnyak V, Alhusaini N, Chen YH, Martin S, Morris N, Kline N, Olson S, Weinberg D, Baker KE, Graveley BR, et al. 2015. Codon optimality is a major determinant of mRNA stability. *Cell* 160:1111-1124.

Examples

```
head(yeast_half_life)
```

yeast_trna	<i>yeast tRNA sequences</i>
------------	-----------------------------

Description

Yeast tRNA sequences obtained from gtRNAdb.

Usage

```
yeast_trna
```

Format

a RNAStringSet with a length of 275.

Source

<<http://gtrnadb.ucsc.edu/genomes/eukaryota/Scere3/sacCer3-mature-tRNAs.fa>>

References

Chan PP, Lowe TM. 2016. GtRNAdb 2.0: an expanded database of transfer RNA genes identified in complete and draft genomes. *Nucleic Acids Res* 44:D184-189.

Examples

```
yeast_trna
```

yeast_trna_gcn	<i>yeast tRNA gene copy numbers (GCN)</i>
----------------	---

Description

Yeast tRNA gene copy numbers (GCN) by anticodon obtained from gtRNAdb.

Usage

yeast_trna_gcn

Format

a named vector with a length of 41. Value names are anticodons.

Source

<<http://gtrnadb.ucsc.edu/genomes/eukaryota/Scere3/sacCer3-mature-tRNAs.fa>>

References

Chan PP, Lowe TM. 2016. GtRNAdb 2.0: an expanded database of transfer RNA genes identified in complete and draft genomes. *Nucleic Acids Res* 44:D184-189.

Examples

yeast_trna_gcn

Index

* datasets

- aa2codon, [3](#)
- human_mt, [18](#)
- yeast_cds, [24](#)
- yeast_exp, [24](#)
- yeast_half_life, [25](#)
- yeast_trna, [26](#)
- yeast_trna_gcn, [27](#)

aa2codon, [3](#)

check_cds, [3](#)
codon_diff, [4](#)
codon_optimize, [5](#)
count_codons, [6](#)
create_codon_table, [7](#)

est_csc, [7](#)
est_optimal_codons, [8](#)
est_rscu, [9](#)
est_trna_weight, [10](#)

get_cai, [11](#)
get_codon_table, [12](#)
get_cscg, [12](#)
get_dp, [13](#)
get_enc, [14](#)
get_fop, [15](#)
get_gc, [16](#)
get_gc3s, [16](#)
get_gc4d, [17](#)
get_tai, [18](#)

human_mt, [18](#)

plot_ca_pairing, [19](#)

rev_comp, [20](#)

seq_to_codons, [20](#)
show_codon_tables, [21](#)

slide, [21](#)
slide_apply, [22](#)
slide_codon, [23](#)
slide_plot, [23](#)

yeast_cds, [24](#)
yeast_exp, [24](#)
yeast_half_life, [25](#)
yeast_trna, [26](#)
yeast_trna_gcn, [27](#)