

Package ‘datazoom.amazonia’

July 22, 2025

Title Simplify Access to Data from the Amazon Region

Version 1.1.0

Description Functions to download and treat data regarding the Brazilian Amazon region from a variety of official sources.

License MIT + file LICENSE

URL <https://www.econ.puc-rio.br/datazoom/>

Depends R (>= 4.0)

Imports data.table, dplyr, Hmisc, janitor, magrittr, purrr, readr, readxl, sf, sidrar, stringi, stringr, tibble, tidyr, utils, XML

Suggests foreign, googledrive, knitr, RCurl, rmarkdown, terra

LinkingTo Rcpp

VignetteBuilder knitr

Encoding UTF-8

LazyData true

RoxygenNote 7.2.3

NeedsCompilation yes

Author Igor Rigolon Veiga [aut, cre],
DataZoom (PUC-Rio) [fnd],
Guilherme Jardim [aut],
Daniel AC Barbosa [aut],
Bruno Alcantara Duarte [aut],
Fredie Didier [aut],
Tito Bruni [aut],
Luiz Guilherme Lopes Moussatche [aut],
Victor Aliende da Matta [aut],
Anna Carolina Dutra Saraiva [aut],
Arthur Carvalho Brito [aut],
Francisco de Lima Cavalcanti [aut],
Maria Mittelbach [aut]

Maintainer Igor Rigolon Veiga <igor.rilave@hotmail.com>

Repository CRAN

Date/Publication 2023-12-12 21:20:06 UTC

Contents

dbc2dbf	2
load_aneel	4
load_baci	4
load_br_trade	5
load_cempre	6
load_censoagro	7
load_climate	9
load_datasus	10
load_degrad	11
load_deter	12
load_epe	13
load_ibama	14
load_iema	15
load_imazon	15
load_ips	16
load_mapbiomas	17
load_pam	18
load_pevs	19
load_pibmunic	20
load_population	22
load_ppm	23
load_prodes	24
load_seeg	25
load_sigmine	26
municipalities	26
municipalities_biomes	27
read.dbc	28
Index	30

dbc2dbf	<i>Decompress a DBC (compressed DBF) file</i>
---------	---

Description

This function allows you decompress a DBC file into its DBF counterpart. Please note that this is the file format used by the Brazilian Ministry of Health (DATASUS), and it is not related to the FoxPro or CANDb DBC file formats.

Usage

```
dbc2dbf(input.file, output.file)
```

Arguments

- | | |
|-------------|--|
| input.file | The name of the DBC file (including extension) |
| output.file | The output file name (including extension) |

Details

DBC is the extension for compressed DBF files (from the 'XBASE' family of databases). This is a proprietary file format used by the brazilian government to make available public healthcare datasets (by it's agency called DATASUS).

It uses internally the PKWare's Data Compression Library (DCL) "implode" compression algorithm. When decompressed, it becomes a regular DBF file.

Value

Return TRUE if succeeded, FALSE otherwise.

Author(s)

Daniela Petruzalek, <daniela.petruszalek@gmail.com>

Source

The internal C code for dbc2dbf is based on blast decompressor and blast-dbf (see *References*).

References

The PKWare ZIP file format documentation (contains the "implode" algorithm specification) available at <https://support.pkware.com>, current version <https://pkware.cachefly.net/webdocs/casestudies/APPNOTE.TXT>.

blast source code in C: <https://github.com/madler/zlib/tree/master/contrib/blast>

blast-dbf, DBC to DBF command-line decompression tool: <https://github.com/eaglebh/blast-dbf>

See Also

`read.dbc`

Examples

```
## Not run:
# Input file name
in.f <- system.file("files/sids.dbc", package = "read.dbc")

# Output file name
out.f <- tempfile(fileext = ".dbc")

# The call return logi = TRUE on success
if (dbc2dbf(input.file = in.f, output.file = out.f)) {
  print("File decompressed!")
  file.remove(out.f)
}

## End(Not run)
```

load_aneel	<i>ANEEL</i>
------------	--------------

Description

National Electric Energy Agency - ANEEL

Usage

```
load_aneel(dataset, raw_data = FALSE, language = "eng")
```

Arguments

dataset	A dataset name ("energy_development_budget", "energy_generation" or "energy_enterprises_distributed")
raw_data	A boolean setting the return of raw (TRUE) or processed (FALSE) data.
language	A string that indicates in which language the data will be returned. Portuguese ("pt") and English ("eng") are supported.

Examples

```
## Not run:
# download treated data about energy generation
clean_aneel <- load_aneel(
  dataset = "energy_generation",
  raw_data = FALSE
)

## End(Not run)
```

load_baci	<i>BACI - Global international trade</i>
-----------	--

Description

Loads disaggregated data on bilateral trade flows for more than 5000 products and 200 countries.

Usage

```
load_baci(dataset = "HS92", raw_data = FALSE, time_period, language = "eng")
```

Arguments

dataset	A dataset name ("HS92").
raw_data	A boolean setting the return of raw (TRUE) or processed (FALSE) data.
time_period	A numeric indicating for which years the data will be loaded, in the format YYYY. Can be any vector of numbers, such as 2010:2012.
language	A string that indicates in which language the data will be returned. Portuguese ("pt") and English ("eng") are supported.

Value

A tibble.

Examples

```
## Not run:
# download treated data for 2016 (takes a long time to download)
clean_baci <- load_baci(
  raw_data = FALSE,
  time_period = 2016
)

## End(Not run)
```

load_br_trade

Comex - Brazilian external trade

Description

Loads data on all products imported to or exported from Brazil.

Usage

```
load_br_trade(dataset, raw_data = FALSE, time_period, language = "eng")
```

Arguments

dataset	A dataset name ("comex_export_mun", "comex_import_mun", "comex_export_prod" or "comex_import_prod").
raw_data	A boolean setting the return of raw (TRUE) or processed (FALSE) data.
time_period	A numeric indicating for which years the data will be loaded, in the format YYYY. Can be any vector of numbers, such as 2010:2012.
language	A string that indicates in which language the data will be returned. Portuguese ("pt") and English ("eng") are supported.

Value

A tibble.

Examples

```
## Not run:
# download treated (raw_data = FALSE) exports data by municipality (dataset = "comex_export_mun")
# from 2020 to 2021 (time_period = 2020:2021)
data <- load_br_trade(
  dataset = "comex_export_mun",
  raw_data = FALSE,
  time_period = 2020:2021
)
# download treated (raw_data = FALSE) imports data by municipality (dataset = "comex_import_mun")
# from 2020 to 2021 (time_period = 2020:2021)
data <- load_br_trade(
  dataset = "comex_import_mun",
  raw_data = FALSE,
  time_period = 2020:2021
)

## End(Not run)
```

load_cempre

CEMPRE - Central Register of Companies

Description

Loads information on companies and other organizations and their respective formally constituted local units, registered with the CNPJ - National Register of Legal Entities.

Usage

```
load_cempre(
  dataset = "cempre",
  raw_data = FALSE,
  geo_level,
  time_period,
  language = "eng",
  sectors = FALSE
)
```

Arguments

dataset	A dataset name ("cempre").
raw_data	A boolean setting the return of raw (TRUE) or processed (FALSE) data.

geo_level	A string that defines the geographic level of the data. Can be one of "country", "state" or "municipality".
time_period	A numeric indicating for which years the data will be loaded, in the format YYYY. Can be any vector of numbers, such as 2010:2012.
language	A string that indicates in which language the data will be returned. Portuguese ("pt") and English ("eng") are supported.
sectors	A boolean that defines if the data will be return separated by sectors (TRUE) or not (FALSE).

Value

A tibble.

Examples

```
## Not run:
# Download raw data (raw_data = TRUE) at the country level
# from 2008 to 2010 (time_period = 2008:2010).
data <- load_cempre(
  raw_data = TRUE,
  geo_level = "country",
  time_period = 2008:2010
)

# Download trested data (raw_data = FALSE) by state (geo_level = "state")
# from 2008 to 2010 (time_period = 2008:2010) in portuguese (language = "pt").
# In this example, data is split by sector (sectors = TRUE)
data <- load_cempre(
  raw_data = FALSE,
  geo_level = "state",
  time_period = 2008:2010,
  language = "pt",
  sectors = TRUE
)

## End(Not run)
```

load_censoagro

Censo Agropecuario

Description

Loads information on agricultural establishments and activities

Usage

```
load_censoagro(
  dataset,
  raw_data = FALSE,
  geo_level,
  time_period,
  language = "eng"
)
```

Arguments

dataset	A dataset name ("agricultural_land_area", "agricultural_area_use", "agricultural_employees_tractors", "agricultural_producer_condition", "animal_species", "animal_products", "vegetable_production_area", "vegetable_production_permanent", "vegetable_production_temporary", "livestock_production").
raw_data	A boolean setting the return of raw (TRUE) or processed (FALSE) data.
geo_level	A string that defines the geographic level of the data. Can be of "country" or "state". • For dataset "livestock_production", can be one of "country", "state", or "municipality"
time_period	A numeric indicating for which years the data will be loaded, in the format YYYY. Can be any vector of numbers, such as 2010:2012.
language	A string that indicates in which language the data will be returned. Portuguese ("pt") and English ("eng") are supported.

Value

A tibble.

Examples

```
## Not run:
# Download total land area data at the country level in year 2006
data <- load_censoagro(
  dataset = "agricultural_land_area",
  raw_data = TRUE,
  geo_level = "country",
  time_period = 2006
)

# Download temporary production crops data by state (geo_level = "state") in year 2006
  in portuguese (language = "pt").
data <- load_censoagro(
  dataset = "vegetable_production_temporary",
  raw_data = FALSE,
  geo_level = "state",
  time_period = 1996,
  language = "pt"
)
```

```
## End(Not run)
```

```
## We should include support for microregion/mesoregion
```

load_climate

TerraClimate - Climate monitoring

Description

Spatial data on climate variables, extracted from Climatology Lab's TerraClimate.

Usage

```
load_climate(
  dataset,
  raw_data = FALSE,
  time_period,
  language = "eng",
  legal_amazon_only = FALSE
)
```

Arguments

dataset	A dataset name, choosing which variable will be loaded. One of ("max_temperature", "min_temperature", "wind_speed", "vapor_pressure_deficit", "vapor_pressure", "snow_water_equivalent", "shortwave_radiation_flux", "soil_moisture", "runoff", "precipitation", "potential_evaporation", "climatic_water_deficit", "water_evaporation", "palmer_drought_severity_index"). For extra details, try <code>vignette("TERRACLIMATE")</code> .
raw_data	A boolean setting the return of raw (TRUE) or processed (FALSE) data.
time_period	A numeric indicating for which years the data will be loaded, in the format YYYY. Can be any vector of numbers, such as 2010:2012.
language	A string that indicates in which language the data will be returned. Portuguese ("pt") and English ("eng") are supported.
legal_amazon_only	A boolean setting the return of Legal Amazon Data (TRUE) or Country's Data (FALSE). Defaults to FALSE

Value

A tibble.

Examples

```
## Not run:
# Downloading maximum temperature data from 2000 to 2001
max_temp <- load_climate(dataset = "max_temperature", time_period = 2000:2001)

# Downloading precipitation data only for the legal Amazon in 2010
amz_precipitation <- load_climate(
  dataset = "precipitation",
  time_period = 2010,
  legal_amazon_only = TRUE
)

## End(Not run)
```

load_datasus

DATASUS - Mortality, hospitalizations and hospital beds

Description

Loads DATASUS data on health establishments, mortality, access to health services and several health indicators.

Usage

```
load_datasus(
  dataset,
  time_period,
  states = "all",
  raw_data = FALSE,
  keep_all = FALSE,
  language = "eng"
)
```

Arguments

dataset	A dataset name, can be one of ("datasus_sim_do", "datasus_sih", "datasus_cnes_lt"), or more. For more details, try vignette("DATASUS").
time_period	A numeric indicating for which years the data will be loaded, in the format YYYY. Can be any vector of numbers, such as 2010:2012.
states	A string specifying for which states to download the data. It is "all" by default, but can be a single state such as "AC" or any vector such as c("AC", "AM").
raw_data	A boolean setting the return of raw (TRUE) or processed (FALSE) data.
keep_all	A boolean choosing whether to aggregate the data by municipality, in turn losing individual-level variables (FALSE) or to keep all the original variables. Only applies when raw_data is TRUE.
language	A string that indicates in which language the data will be returned. Portuguese ("pt") and English ("eng") are supported.

Value

A tibble.

Examples

```
## Not run:
# download raw data for the year 2010 in the state of AM.
data <- load_datasus(
  dataset = "datasus_sim_do",
  time_period = 2010,
  states = "AM",
  raw_data = TRUE
)

# download treated data with the number of deaths by cause in AM and PA.
data <- load_datasus(
  dataset = "datasus_sim_do",
  time_period = 2010,
  states = c("AM", "PA"),
  raw_data = FALSE
)

# download treated data with the number of deaths by cause in AM and PA
# keeping all individual variables.
data <- load_datasus(
  dataset = "datasus_sim_do",
  time_period = 2010,
  states = c("AM", "PA"),
  raw_data = FALSE,
  keep_all = TRUE
)

## End(Not run)
```

load_degrad

Degrad - Forest Degradation in the Brazilian Amazon

Description

Loads information on forest degradation in the Brazilian Amazon, replaced by DETER-B in December 2016.

Usage

```
load_degrad(
  dataset = "degrad",
  raw_data = FALSE,
  time_period,
```

```

    language = "eng"
  )

```

Arguments

dataset	A dataset name ("degrad").
raw_data	A boolean setting the return of raw (TRUE) or processed (FALSE) data.
time_period	A numeric indicating for which years the data will be loaded, in the format YYYY. Can be any vector of numbers, such as 2010:2012.
language	A string that indicates in which language the data will be returned. Portuguese ("pt") and English ("eng") are supported.

Value

A list of tibbles (if raw_data = TRUE) or a tibble (if raw_data = FALSE).

Examples

```

## Not run:
# download treated data (raw_data = TRUE) related to forest degradation
# from 2010 to 2012 (time_period = 2010:2012).
data <- load_degrad(
  dataset = "degrad",
  raw_data = FALSE,
  time_period = 2010:2012
)

## End(Not run)

```

load_deter	<i>DETER - Forest Degradation in the Brazilian Amazon</i>
------------	---

Description

Loads data on changes in forest cover in the Legal Amazon and the Cerrado biome.

Usage

```
load_deter(dataset, raw_data = FALSE, language = "eng")
```

Arguments

dataset	A dataset name ("deter_amz", "deter_cerrado") with information about the Legal Amazon and Cerrado, respectively
raw_data	A boolean setting the return of raw (TRUE) or processed (FALSE) data.
language	A string that indicates in which language the data will be returned. Portuguese ("pt") and English ("eng") are supported.

Value

A sf object.

Examples

```
## Not run:
# Download treated data (raw_data = FALSE) from Amazonia (dataset = "deter_amz")
deter_amz <- load_deter(
  dataset = "deter_amz",
  raw_data = FALSE
)

## End(Not run)
```

load_epe	<i>EPE</i>
----------	------------

Description

Electrical Energy Monthly Consumption per Class

Usage

```
load_epe(dataset, raw_data = FALSE, geo_level = "state", language = "eng")
```

Arguments

dataset	A dataset name, ("energy_consumption_per_class") or ("national_energy_balance")
raw_data	A boolean setting the return of raw (TRUE) or processed (FALSE) data.
geo_level	A geographical level, ("state") or ("subsystem"), only available for "energy_consumption_per_class"
language	A string that indicates in which language the data will be returned. Portuguese ("pt") and English ("eng") are supported.

Examples

```
## Not run:
# download treated data about energy consumption at the state level
clean_epe <- load_epe(
  dataset = "energy_consumption_per_class",
  geo_level = "state",
  raw_data = FALSE
)

## End(Not run)
```

load_ibama	<i>IBAMA - Brazilian Institute for the Environment and Renewable Natural Resources</i>
------------	--

Description

Loads information on environmental fines in the Amazon region

Usage

```
load_ibama(dataset, raw_data = FALSE, states = "all", language = "eng")
```

Arguments

dataset	A dataset name ("embargoed_areas", "distributed_fines", or "collected_fines")
raw_data	A boolean setting the return of raw (TRUE) or processed (FALSE) data.
states	A string specifying for which states to download the data. It is "all" by default, but can be a single state such as "AC" or any vector such as c("AC", "AM"). Does not apply to the "embargoed_areas" dataset.
language	A string that indicates in which language the data will be returned. Currently, only Portuguese ("pt") and English ("eng") are supported.

Value

A tibble.

Examples

```
## Not run:
# Download treated embargoes data (raw_data = FALSE) in english (language = "eng")
data <- load_ibama(
  dataset = "embargoed_areas", raw_data = FALSE,
  language = "eng"
)

# Download treated collected fines data from "BA"
data <- load_ibama(
  dataset = "collected_fines", raw_data = FALSE,
  states = "BA", language = "pt"
)

## End(Not run)
```

load_iema*IEMA - Institute of Environment and Water Resources*

Description

Loads information on electric energy access at the municipality level in the Amazon region

Usage

```
load_iema(dataset = "iema", raw_data = FALSE, language = "eng")
```

Arguments

dataset	A dataset name ("iema")
raw_data	A boolean setting the return of raw (TRUE) or processed (FALSE) data.
language	A string that indicates in which language the data will be returned. Portuguese ("pt") and English ("eng") are supported.

Value

A tibble.

Examples

```
## Not run:  
# Download treated data  
data <- load_iema(raw_data = FALSE)  
  
## End(Not run)
```

load_imazon*IMAZON - Deforestation pressure by municipality*

Description

Loads data categorizing each municipality by the level of deforestation pressure it faces

Usage

```
load_imazon(dataset = "imazon_shp", raw_data = FALSE, language = "eng")
```

Arguments

dataset	There is one dataset available ("amazon_shp")
raw_data	A boolean setting the return of raw (TRUE) or processed (FALSE) data.
language	A string that indicates in which language the data will be returned. Portuguese ("pt") and English ("eng") are supported.

Value

A tibble.

Examples

```
## Not run:
# Download treated data
data <- load_imazon(raw_data = FALSE)

## End(Not run)
```

load_ips

IPS - Amazon Social Progress Index

Description

Loads information on the social and environmental performance of the Legal Amazon.

Usage

```
load_ips(
  dataset = "all",
  raw_data = FALSE,
  time_period = c(2014, 2018, 2021, 2023),
  language = "eng"
)
```

Arguments

dataset	A dataset name ("all", "life_quality", "sanit_habit", "violence", "educ", "communic", "mortality", or "deforest")
raw_data	A boolean setting the return of raw (TRUE) or processed (FALSE) data.
time_period	Year to download. Can be 2014, 2018, 2021, 2023, or a vector with some combination thereof
language	A string that indicates in which language the data will be returned. Portuguese ("pt") and English ("eng") are supported.

Value

A tibble.

Examples

```
## Not run:
# Download raw data from 2014
data <- load_ips(dataset = "all", raw_data = TRUE, time_period = 2014)

# Download treated deforest data from 2018 in portuguese
data <- load_ips(
  dataset = "deforest", raw_data = FALSE,
  time_period = 2018, language = "pt"
)

## End(Not run)
```

load_mapbiomas	<i>MAPBIOMAS - The Annual Land Cover and Use Mapping Project in Brazil</i>
----------------	--

Description

Loads information about land cover and use

Usage

```
load_mapbiomas(
  dataset,
  raw_data = FALSE,
  geo_level = "municipality",
  language = "eng"
)
```

Arguments

dataset	A dataset name ("mapbiomas_cover", "mapbiomas_transition", "mapbiomas_irrigation", "mapbiomas_deforestation_regeneration", "mapbiomas_mining", "mapbiomas_water" or "mapbiomas_fire")
raw_data	A boolean setting the return of raw (TRUE) or processed (FALSE) data.
geo_level	A string that defines the geographic level of the data • For dataset "mapbiomas_cover", can be "municipality" or "state" (faster download) • For dataset "mapbiomas_transition", can be "municipality" or "state" (faster download)

- For dataset "mapbiomas_deforestation_regeneration", can only be "municipality"
 - For dataset "mapbiomas_mining", can be "indigenous_land" or "municipality"
 - For dataset "mapbiomas_irrigation", can be "state" or "biome"
 - For dataset "mapbiomas_water", can be "municipality", "state" or "biome"
 - For dataset "mapbiomas_fire", can only be "state"
- language A string that indicates in which language the data will be returned. Portuguese ("pt") and English ("eng") are supported.

Value

A tibble.

Examples

```
## Not run:
# download treated Mapbiomas Cover data in English
data <- load_mapbiomas(
  dataset = "mapbiomas_cover",
  raw_data = FALSE,
  geo_level = "municipality",
  language = "eng"
)

# download treated data on mining on indigenous lands
data <- load_mapbiomas("mapbiomas_mining",
  raw_data = FALSE,
  geo_level = "indigenous_land"
)

## End(Not run)
```

load_pam	<i>PAM - Municipal Agricultural Production</i>
----------	--

Description

Loads information on the quantity, value and area of temporary and permanent crops cultivated.

Usage

```
load_pam(dataset, raw_data = FALSE, geo_level, time_period, language = "eng")
```

Arguments

dataset	A dataset name ("all_crops", "permanent_crops", "temporary_crops" or many individual crop possibilities (see vignette(load_pam))). You can also use SIDRA codes (see https://sidra.ibge.gov.br/pesquisa/pam/tabelas)
raw_data	A boolean setting the return of raw (TRUE) or processed (FALSE) data.
geo_level	A string that defines the geographic level of the data. Can be one of "country", "state" or "municipality".
time_period	A numeric indicating for which years the data will be loaded, in the format YYYY. Can be any vector of numbers, such as 2010:2012.
language	A string that indicates in which language the data will be returned. Portuguese ("pt") and English ("eng") are supported.

Value

A tibble consisting of geographic units that present positive values for any of the variables in the dataset.

Examples

```
## Not run:
# download treated data at the state level from 2010 to 2011 for all crops
data <- load_pam(
  dataset = "all_crops",
  raw_data = FALSE,
  geo_level = "state",
  time_period = 2010:2011,
  language = "eng"
)

## End(Not run)
```

load_pevs

*PEVS - Forestry Activities***Description**

Loads information on the amount and value of the production of the exploitation of native plant resources and planted forest massifs, as well as existing total and harvested areas of forest crops.

Usage

```
load_pevs(dataset, raw_data = FALSE, geo_level, time_period, language = "eng")
```

Arguments

dataset	A dataset name ("pevs_forest_crops", "pevs_silviculture" or "pevs_silviculture_area"). You can also use SIDRA codes (see https://sidra.ibge.gov.br/pesquisa/pevs/quadros/brasil/2019)
raw_data	A boolean setting the return of raw (TRUE) or processed (FALSE) data.
geo_level	A string that defines the geographic level of the data. Can be one of "country", "region", "state", or "municipality".
time_period	A numeric indicating for which years the data will be loaded, in the format YYYY. Can be any vector of numbers, such as 2010:2012.
language	A string that indicates in which language the data will be returned. Portuguese ("pt") and English ("eng") are supported.

Value

A tibble consisting of geographic units that present positive values for any of the variables in the dataset.

Examples

```
## Not run:
# Download treated (raw_data = FALSE) silviculture data (dataset = 'pevs_silviculture')
# by state (geo_level = 'state') from 2012 (time_period = 2012)
# in portuguese (language = "pt")
data <- load_pevs(
  dataset = "pevs_silviculture",
  raw_data = FALSE,
  geo_level = "state",
  time_period = 2012,
  language = "pt"
)

# Download raw (raw_data = TRUE) forest crops data by region from 2012 to 2013 in english
data <- load_pevs(
  dataset = "pevs_forest_crops",
  raw_data = TRUE,
  geo_level = "region",
  time_period = 2012:2013
)

## End(Not run)
```

Description

Loads information on gross domestic product at current prices, taxes, net of subsidies, on products at current prices and gross value added at current prices, total and by economic activity, and respective shares.

Usage

```
load_pibmunic(  
  dataset = "pibmunic",  
  raw_data = FALSE,  
  geo_level,  
  time_period,  
  language = "eng"  
)
```

Arguments

dataset	A dataset name ("pibmunic") with Municipal GDP information. You can also use SIDRA codes (See https://sidra.ibge.gov.br/pesquisa/pib-munic/tabelas)
raw_data	A boolean setting the return of raw (TRUE) or processed (FALSE) data.
geo_level	A string that defines the geographic level of the data. Can be one of "country", "state" or "municipality".
time_period	A numeric indicating for which years the data will be loaded, in the format YYYY. Can be any vector of numbers, such as 2010:2012.
language	A string that indicates in which language the data will be returned. Portuguese ("pt") and English ("eng") are supported.

Value

A tibble.

Examples

```
## Not run:  
# download treated municipal GDP data at the state level for 2010 to 2012  
data <- load_pibmunic(  
  raw_data = FALSE,  
  geo_level = "state",  
  time_period = 2010:2012  
)  
  
## End(Not run)
```

load_population	<i>Population</i>
-----------------	-------------------

Description

Loads information on (estimated) population

Usage

```
load_population(  
  dataset = "population",  
  raw_data = FALSE,  
  geo_level,  
  time_period,  
  language = "eng"  
)
```

Arguments

dataset	A dataset name ("population").
raw_data	A boolean setting the return of raw (TRUE) or processed (FALSE) data.
geo_level	A string that defines the geographic level of the data. Can be one of "country", "state" or "municipality".
time_period	A numeric indicating for which years the data will be loaded, in the format YYYY. Can be any vector of numbers, such as 2010:2012.
language	A string that indicates in which language the data will be returned. Portuguese ("pt") and English ("eng") are supported.

Value

A tibble.

Examples

```
## Not run:  
# Download raw data (raw_data = TRUE) at the country level  
# from 2008 to 2010 (time_period = 2008:2010).  
data <- load_population(  
  raw_data = TRUE,  
  geo_level = "country",  
  time_period = 2008:2010  
)  
  
# Download trested data (raw_data = FALSE) by state (geo_level = "state")  
# from 2008 to 2010 (time_period = 2008:2010) in portuguese (language = "pt").  
data <- load_population(  
  raw_data = FALSE,
```

```

    geo_level = "state",
    time_period = 2008:2010,
    language = "pt"
  )

  ## End(Not run)

```

load_ppm

PPM - Municipal Livestock Production

Description

Loads information on animal farming inventories and livestock products (IBGE).

Usage

```
load_ppm(dataset, raw_data = FALSE, geo_level, time_period, language = "eng")
```

Arguments

dataset	A dataset name ("ppm_livestock_inventory", "ppm_sheep_farming", "ppm_animal_orig_production", "ppm_cow_farming" or "ppm_aquaculture". You can also use SIDRA codes (see https://sidra.ibge.gov.br/pesquisa/ppm/tabelas/brasil/2021)
raw_data	A boolean setting the return of raw (TRUE) or processed (FALSE) data.
geo_level	A string that defines the geographic level of the data. Can be one of "country", "state" or "municipality".
time_period	A numeric indicating for which years the data will be loaded, in the format YYYY. Can be any vector of numbers, such as 2010:2012.
language	A string that indicates in which language the data will be returned. Portuguese ("pt") and English ("eng") are supported.

Value

A tibble consisting of geographic units that present positive values for any of the variables in the dataset.

Examples

```

## Not run:
# Download treated data (raw_data = FALSE) about aquaculture (dataset = "ppm_aquaculture")
# from 2013 to 2015 (time_period = 2013:2015) in english
# with the level of aggregation being the country (geo_level = "country").
data <- load_ppm(
  dataset = "ppm_aquaculture",
  raw_data = FALSE,
  geo_level = "country",
  time_period = 2013:2015
)

```

```

)

# Download raw data about sheep farming by state from 1980 to 1995 in portuguese (language = "pt")
data <- load_ppm(
  dataset = "ppm_sheep_farming",
  raw_data = TRUE,
  geo_level = "state",
  time_period = 1980:1995,
  language = "pt"
)

## End(Not run)

```

load_prodes	<i>PRODES - Deforestation Monitoring Project in the Legal Amazon by Satellite</i>
-------------	---

Description

Loads data on deforestation in the Legal Amazon region.

Usage

```
load_prodes(dataset, raw_data = FALSE, language = "eng")
```

Arguments

dataset	A dataset name ("deforestation").
raw_data	A boolean setting the return of raw (TRUE) or processed (FALSE) data.
language	A string that indicates in which language the data will be returned. Portuguese ("pt") and English ("eng") are supported.

Value

A tibble with the selected data.

Examples

```

## Not run:
# Download treated data (raw_data = FALSE)
# in portuguese (language = 'pt').
data <- load_prodes(
  raw_data = FALSE,
  language = "pt"
)

## End(Not run)

```

load_seeg	<i>Greenhouse gas emission estimates (SEEG)</i>
-----------	---

Description

Loads data of estimates of emission of greenhouse gases

Usage

```
load_seeg(dataset, raw_data = FALSE, geo_level, language = "eng")
```

Arguments

dataset	A dataset name ("seeg", "seeg_farming", "seeg_industry", "seeg_energy", "seeg_land", "seeg_residuals"). On which "seeg" contains all five sectors (only works with <code>raw_data = TRUE</code>) and the others are filtered specifically by a main source of emission.
raw_data	A boolean setting the return of raw (TRUE) or processed (FALSE) data.
geo_level	A string that defines the geographic level of the data. Can be one of "country", "state" or "municipality".
language	A string that indicates in which language the data will be returned. Portuguese ("pt") and English ("eng") are supported.

Value

A tibble.

Examples

```
## Not run:
# Download raw data (raw_data = TRUE) of greenhouse gases (dataset = "seeg")
# by state (geo_level = "state")
data <- load_seeg(
  dataset = "seeg",
  raw_data = TRUE,
  geo_level = "state"
)

# Download treated data (raw_data = FALSE) of industry greenhouse gases (dataset = "seeg_industry")
data <- load_seeg(
  dataset = "seeg_industry",
  raw_data = FALSE,
  geo_level = "state"
)

## End(Not run)
```

load_sigmine	<i>SIGMINE - Mining Geographic Information System</i>
--------------	---

Description

Loads information the mines being explored legally in Brazil, including their location, status, product being mined and area in square meters.

Usage

```
load_sigmine(dataset = "sigmine_active", raw_data = FALSE, language = "eng")
```

Arguments

dataset	A dataset name ("sigmine_active")
raw_data	A boolean setting the return of raw (TRUE) or processed (FALSE) data.
language	A string that indicates in which language the data will be returned. Portuguese ("pt") and English ("eng") are supported.

Value

A tibble.

Examples

```
## Not run:
# Download treated data (raw_data = FALSE) in portuguese (language = "pt").
data <- load_sigmine(
  dataset = "sigmine_active",
  raw_data = FALSE,
  language = "pt"
)

## End(Not run)
```

municipalities	<i>IBGE codes and Legal Amazon identification of Brazilian municipalities</i>
----------------	---

Description

A dataset containing each municipality's IBGE code, state, mesoregion, microregion, as well as a binary variable for whether it is part of the Legal Amazon. Mostly for our functions' internal use.

Usage

```
municipalities
```

Format

A data frame with 5570 rows and 12 variables:

code_muni IBGE 7-digit municipality code
name_muni municipality name
code_state 2-digit state code
abbrev_state state abbreviations (e.g. "AM")
name_state full name of the states
code_region 1-digit regional code
name_region name of the region
legal_amazon takes value 1 for municipalities in the legal amazon, 0 otherwise
municipality_mapbiomas municipality name in MAPBIOMAS data
code_micro 5-digit microregion code
name_micro name of the microregion
code_meso 4-digit mesoregion code
name_meso name of the mesoregion

Source

Package geobr and <https://www.ibge.gov.br/geociencias/cartas-e-mapas/mapas-regionais/15819-amazonia-legal.html?=&t=acesso-ao-produto>

municipalities_biomes *IBGE codes and MAPBIOMAS id of Brazilian municipalities and biomes*

Description

A dataset containing each municipality-biome's IBGE code, state, biome, name and MAPBIOMAS ID. Mostly for our functions' internal use.

Usage

```
municipalities_biomes
```

Format

A data frame with 6537 rows and 4 variables:

feature_id MAPBIOMAS biome-municipality ID
code_muni IBGE 7-digit municipality code
abbrev_state state abbreviations (e.g. "AM")
municipality_mapbiomas municipality name in MAPBIOMAS data
biome biome

Source

Package geobr and <https://mapbiomas.org/>

read.dbc	<i>Read Data Stored in DBC (Compressed DBF) Files</i>
----------	---

Description

This function allows you to read a DBC (compressed DBF) file into a data frame. Please note that this is the file format used by the Brazilian Ministry of Health (DATASUS), and it is not related to the FoxPro or CANDb DBC file formats.

Usage

```
read.dbc(file, ...)
```

Arguments

file	The name of the DBC file (including extension)
...	Further arguments to be passed to read.dbf

Details

DBC is the extension for compressed DBF files (from the 'XBASE' family of databases). This is a proprietary file format used by the Brazilian government to make available public healthcare datasets (by its agency called DATASUS). read.dbc relies on the dbc2dbf function to decompress the DBC into a temporary DBF file.

After decompressing, it reads the temporary DBF file into a data.frame using read.dbf from the foreign package.

Value

A data.frame of the data from the DBC file.

Note

DATASUS is the name of the Department of Informatics of the Brazilian Health System and is responsible for publishing public healthcare data. Besides the DATASUS, the Brazilian National Agency for Supplementary Health (ANS) also uses this file format for its public data.

This function was tested using files from both DATASUS and ANS to ensure compliance with the format, and hence ensure its usability by researchers.

As a final note, neither this project, nor its author, has any association with the Brazilian government.

Author(s)

Daniela Petruzalek, <daniela.petruszalek@gmail.com>

See Also

dbc2dbf

Examples

```
## Not run:
# The 'sids.dbc' file is the compressed version of 'sids.dbf' from the "foreign" package.
x <- read.dbc(system.file("files/sids.dbc", package = "read.dbc"))
str(x)
summary(x)

# This is a small subset of U.S. NOAA storm database.
storm <- read.dbc(system.file("files/storm.dbc", package = "read.dbc"))
head(x)
str(x)

## Don't run!
## The following code will download data from the "Declarations of Death" database for
## the Brazilian state of Parana, year 2013. Source: DATASUS / Brazilian Ministry of Health
url <- "ftp://ftp.datasus.gov.br/dissemin/publicos/SIM/CID10/DORES/DOPR2013.dbc"
download.file(url, destfile = "DOPR2013.dbc")
dopr <- read.dbc("DOPR2013.dbc")
head(dopr)
str(dopr)

## End(Not run)
```

Index

- * **datasets**
 - municipalities, [26](#)
 - municipalities_biomes, [27](#)
- * **datasus**
 - read.dbc, [28](#)
- * **dbc**
 - dbc2dbf, [2](#)
 - read.dbc, [28](#)
- * **dbf**
 - dbc2dbf, [2](#)

dbc2dbf, [2](#)

load_aneel, [4](#)
load_baci, [4](#)
load_br_trade, [5](#)
load_cempre, [6](#)
load_censoagro, [7](#)
load_climate, [9](#)
load_datasus, [10](#)
load_degrad, [11](#)
load_deter, [12](#)
load_epe, [13](#)
load_ibama, [14](#)
load_iema, [15](#)
load_imazon, [15](#)
load_ips, [16](#)
load_mapbiomas, [17](#)
load_pam, [18](#)
load_pevs, [19](#)
load_pibmunic, [20](#)
load_population, [22](#)
load_ppm, [23](#)
load_prodes, [24](#)
load_seeg, [25](#)
load_sigmine, [26](#)

municipalities, [26](#)
municipalities_biomes, [27](#)

read.dbc, [28](#)