

Package ‘diario’

July 22, 2025

Type Package

Title 'R' Interface to the 'Diariodeobras' Application

Version 0.1.0

Date 2025-01-09

Description Provides a set of functions for securely storing 'API' tokens and interacting with the <<https://diariodeobras.net>> system. Includes convenient wrappers around the 'httr2' package to perform authenticated requests, retrieve project details, tasks, reports, and more.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.2

Imports tibble, httr2, keyring

URL <<https://github.com/StrategicProjects/diario>>

Config/Needs/website tidyverse/tidytemplate

NeedsCompilation no

Author Andre Leite [aut, cre],
Felipe Ferreira [aut],
Hugo Vaconcelos [aut],
Diogo Bezerra [aut],
Roger Azevedo [aut]

Maintainer Andre Leite <leite@castlab.org>

Repository CRAN

Date/Publication 2025-01-15 18:10:05 UTC

Contents

diario_get_company	2
diario_get_entities	2
diario_get_projects	3
diario_get_project_details	3
diario_get_reports	4

diario_get_report_details	5
diario_get_task_details	5
diario_get_task_list	6
diario_perform_request	7
diario_retrieve_token	8
diario_store_token	8
Index	9

diario_get_company	<i>Get company details</i>
--------------------	----------------------------

Description

This function retrieves company details from the Diario API.

Usage

```
diario_get_company()
```

Value

A list containing company details.

Examples

```
## Not run:  
company <- diario_get_company()  
  
## End(Not run)
```

diario_get_entities	<i>Get all registered entities (cadastrados)</i>
---------------------	--

Description

This function retrieves all registered entities from the Diario API.

Usage

```
diario_get_entities()
```

Value

A list containing the entities data.

Examples

```
## Not run:
entities <- diario_get_entities()

## End(Not run)
```

diario_get_projects	<i>Get list of projects (obras)</i>
---------------------	-------------------------------------

Description

This function retrieves a list of projects from the Diario API.

Usage

```
diario_get_projects()
```

Value

A tibble containing the projects data.

Examples

```
## Not run:
projects <- diario_get_projects(query = list(status = "active"))

## End(Not run)
```

diario_get_project_details	<i>Get details of a specific project</i>
----------------------------	--

Description

This function retrieves details of a specific project by its ID from the Diario API.

Usage

```
diario_get_project_details(project_id)
```

Arguments

project_id	A valid non-empty string with the project ID.
------------	---

Value

A list containing the project details.

Examples

```
## Not run:  
project <- diario_get_project_details("66face5fe26175e0a904d398")  
  
## End(Not run)
```

diario_get_reports	<i>Get reports of a specific project</i>
--------------------	--

Description

This function retrieves reports of a specific project with optional parameters for limit and order.

Usage

```
diario_get_reports(project_id, limit = 50, order = "desc")
```

Arguments

project_id	A valid non-empty string with the project ID.
limit	An integer specifying the maximum number of reports to retrieve. Default is 50.
order	A character string specifying the order of the reports (e.g., "asc" or "desc"). Default is "desc".

Value

A tibble containing the reports.

Examples

```
## Not run:  
reports <- diario_get_reports("6717f864d163f517ae06e242", limit = 10, order = "asc")  
  
## End(Not run)
```

`diario_get_report_details`*Get details of a specific report*

Description

This function retrieves details of a specific report by report ID within a project.

Usage

```
diario_get_report_details(project_id, report_id)
```

Arguments

<code>project_id</code>	A valid non-empty string with the project ID.
<code>report_id</code>	A valid non-empty string with the report ID.

Value

A list containing the report details.

Examples

```
## Not run:  
report <- diario_get_report_details("6717f864d163f517ae06e242", "67648080f0971de9d00324c2")  
  
## End(Not run)
```

`diario_get_task_details`*Get details of a specific task*

Description

This function retrieves details of a specific task by task ID within a project.

Usage

```
diario_get_task_details(project_id, task_id)
```

Arguments

<code>project_id</code>	A valid non-empty string with the project ID.
<code>task_id</code>	A valid non-empty string with the task ID.

Value

A list containing task details.

Examples

```
## Not run:  
task <- diario_get_task_details("66cf438223aa80386306e647", "66cf44209e4fedefb306bcd3")  
  
## End(Not run)
```

diario_get_task_list *Get the task list of a specific project*

Description

This function retrieves the task list of a specific project by its ID.

Usage

```
diario_get_task_list(project_id)
```

Arguments

project_id A valid non-empty string with the project ID.

Value

A tibble containing the task list.

Examples

```
## Not run:  
tasks <- diario_get_task_list("66cf438223aa80386306e647")  
  
## End(Not run)
```

diario_perform_request*Perform an API request to Diario*

Description

This function performs an authenticated request to the specified endpoint of the Diario API.

Usage

```
diario_perform_request(  
  endpoint,  
  query = list(),  
  method = "GET",  
  body = NULL,  
  verbosity = 0  
)
```

Arguments

endpoint	A non-empty character string specifying the API endpoint.
query	A named list of query parameters (optional).
method	The HTTP method to use (e.g., "GET", "POST", "PUT", "DELETE"). Default is "GET".
body	A list representing the JSON body for request methods that support a body (e.g., POST).
verbosity	Verbosity level for the request (0 = none, 1 = minimal). Default is 0.

Value

A list (by default) containing the response from the API. If the content is JSON, it will be returned as an R object. If not, an error is raised.

Examples

```
## Not run:  
diario_perform_request("v1/obras", query = list(status = "active"))  
  
## End(Not run)
```

`diario_retrieve_token` *Retrieve the API token for Diario*

Description

This function retrieves the stored authentication token using the keyring package. If no valid token (or keyring) is found, it will return NULL and print a message in English indicating that no valid token was found.

Usage

```
diario_retrieve_token()
```

Value

A character string containing the API token, or NULL if no valid token is found.

Examples

```
token <- diario_retrieve_token()
```

`diario_store_token` *Store the API token for Diario*

Description

This function stores the provided authentication token using the keyring package. If the token cannot be stored (for example, because the keyring is not accessible), it prints a message instead of throwing an error, and returns FALSE.

Usage

```
diario_store_token(token)
```

Arguments

`token` A character string containing the API token to be stored.

Value

TRUE (invisibly) if the token was stored successfully; FALSE otherwise.

Examples

```
# Attempt to store a token:  
diario_store_token("your-api-token")
```

Index

diario_get_company, [2](#)
diario_get_entities, [2](#)
diario_get_project_details, [3](#)
diario_get_projects, [3](#)
diario_get_report_details, [5](#)
diario_get_reports, [4](#)
diario_get_task_details, [5](#)
diario_get_task_list, [6](#)
diario_perform_request, [7](#)
diario_retrieve_token, [8](#)
diario_store_token, [8](#)