

Package ‘echarts4r’

July 22, 2025

Title Create Interactive Graphs with 'Echarts JavaScript' Version 5

Date 2023-06-08

Version 0.4.5

Description

Easily create interactive charts by leveraging the 'Echarts Javascript' library which includes 36 chart types, themes, 'Shiny' proxies and animations.

License Apache License (>= 2.0)

Encoding UTF-8

Imports htmlwidgets, dplyr (>= 0.7.0), purrr, countrycode, broom, shiny, scales, corrplot, htmltools, jsonlite, rstudioapi

Suggests tidyr, testthat, knitr, rmarkdown, covr, data.tree, leaflet, tibble

Depends R (>= 4.1.0)

RoxygenNote 7.2.3

URL <https://echarts4r.john-coene.com/>,
<https://github.com/JohnCoene/echarts4r>

BugReports <https://github.com/JohnCoene/echarts4r/issues/>

NeedsCompilation no

Author John Coene [aut, cph],

David Munoz Tord [cre, ctb] (ORCID:

[<https://orcid.org/0000-0001-7954-8295>](https://orcid.org/0000-0001-7954-8295)),

Wei Su [ctb],

Helgasoft [ctb],

Xianying Tan [ctb] (ORCID: [<https://orcid.org/0000-0002-6072-3521>](https://orcid.org/0000-0002-6072-3521)),

Robin Cura [ctb] (ORCID: [<https://orcid.org/0000-0001-5926-1828>](https://orcid.org/0000-0001-5926-1828)),

Mathida Chuk [ctb],

Robert Koetsier [ctb] (ORCID: [<https://orcid.org/0000-0002-4477-5401>](https://orcid.org/0000-0002-4477-5401)),

Jelle Geertsma [ctb]

Maintainer David Munoz Tord <david.munoztord@mailbox.org>

Repository CRAN

Date/Publication 2023-06-16 23:30:02 UTC

Contents

angle_axis	4
band	5
band2	6
callbacks	7
connections	8
echarts4r-shiny	10
echarts4rBox	11
echarts4rBoxOutput	13
e_animation	13
e_append1_p	14
e_area	16
e_aria	18
e_axis	18
e_axis_3d	20
e_axis_labels	22
e_axis_pointer	22
e_axis_stagger	23
e_bar	23
e_bar_3d	25
e_boxplot	27
e_brush	28
e_button	29
e_calendar	30
e_candle	31
e_capture	32
e_cloud	33
e_color	34
e_color_range	35
e_common	36
e_correlations	36
e_country_names	37
e_datazoom	37
e_dims	38
e_dispatch_action_p	39
e_draft	40
e_draw_p	40
e_error_bar	41
e_execute	43
e_facet	43
e_flip_coords	44
e_flow_gl	45
e_focus_adjacency_p	48
e_format_axis	50
e_funnel	51
e_gauge	52
e_geo	53

e_geo_3d	54
e_get_data	55
e_get_zr	56
e_globe	56
e_graph	57
e_graphic_g	59
e_grid	61
e_grid_3d	62
e_heatmap	63
e_hide_grid_lines	65
e_highlight_p	66
e_histogram	67
e_inspect	69
e_labels	70
e_leaflet	71
e_legend	72
e_line	73
e_lines	75
e_lines_3d	77
e_lines_gl	80
e_liquid	81
e_list	81
e_lm	82
e_locale	84
e_map	85
e_map_register	88
e_mark_p	89
e_mark_point	91
e_merge	94
e_modularity	94
e_morph	95
e_parallel	96
e_pictorial	97
e_pie	100
e_polar	101
e_radar	102
e_radar_opts	103
e_remove	104
e_resize	105
e_restore	105
e_river	106
e_sankey	107
e_scatter	108
e_scatter_3d	112
e_scatter_gl	115
e_showtip_p	116
e_show_loading	118
e_single_axis	120

e_step 121

e_sunburst 122

e_surface 125

e_text_style 126

e_theme 126

e_title 128

e_toolbox_feature 128

e_tooltip 129

e_tree 131

e_treemap 132

e_utc 134

e_visual_map 134

e_visual_map_range 136

e_zoom 137

graph_action 138

highlight_action 139

init 140

legend_action 143

mapbox 144

map_actions 145

nesting 146

pie_action 147

radius_axis 148

renderEcharts4rBox 149

timeline-opts 149

tooltip_action 150

Index 152

angle_axis	<i>Angle axis</i>
------------	-------------------

Description

Customise angle axis.

Usage

```
e_angle_axis(e, serie, show = TRUE, ...)
```

```
e_angle_axis_(e, serie = NULL, show = TRUE, ...)
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
serie	Serie to use as axis labels.
show	Whether to display the axis.
...	Any other option to pass, check See Also section.

See Also[Additional arguments](#)**Examples**

```
df <- data.frame(x = 1:100, y = seq(1, 200, by = 2))

df |>
  e_charts(x) |>
  e_polar(FALSE) |>
  e_angle_axis(FALSE) |>
  e_radius_axis(FALSE) |>
  e_line(y, coord.system = "polar", smooth = TRUE) |>
  e_legend(show = FALSE)

df <- data.frame(x = LETTERS[1:5], y = runif(5))

df |>
  e_charts(x) |>
  e_polar() |>
  e_angle_axis(x) |>
  e_radius_axis() |>
  e_line(y, coord.system = "polar", smooth = TRUE)
```

band

*Confidence bands***Description**

Add confidence bands

Usage

```
e_band(
  e,
  min,
  max,
  stack = "confidence-band",
  symbol = c("none", "none"),
  areaStyle = list(list(color = "rgba(0,0,0,0)"), list()),
  legend = list(FALSE, FALSE),
  ...
)

e_band_(
  e,
  min,
  max,
```

```
    stack = "confidence-band",
    symbol = c("none", "none"),
    areaStyle = list(list(color = "rgba(0,0,0,0)"), list()),
    legend = list(FALSE, FALSE),
    ...
  )
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
min, max	series.
stack	Name of stack.
symbol	Whether to show symbols on lower and upper band lines.
areaStyle	The style of lower and upper bands, i.e.: color.
legend	Whether to show min and max in legend.
...	All options must be of vectors or lists of length 2 where the first argument is for the lower bound and the second for the upper bound, see examples.

Examples

```
df <- data.frame(
  x = 1:10,
  y = runif(10, 5, 10)
) |>
  dplyr::mutate(
    lwr = y - runif(10, 1, 3),
    upr = y + runif(10, 2, 4)
  )

df |>
  e_charts(x) |>
  e_line(y) |>
  e_band(lwr, upr)
```

band2	<i>Area bands</i>
-------	-------------------

Description

Add area bands

Usage

```
e_band2(e, lower, upper, ...)

e_band2_(
  e,
```

```
    lower,
    upper,
    name = NULL,
    legend = TRUE,
    y_index = 0,
    x_index = 0,
    coord_system = "cartesian2d",
    itemStyle = list(borderWidth = 0.5),
    ...
  )
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
lower, upper	series of lower and upper borders of the band
...	additional options
name	name of the serie.
legend	Whether to add serie to legend.
x_index, y_index	Indexes of x and y axis.
coord_system	Coordinate system to plot against.
itemStyle	mostly used for borderWidth, default 0.5

Examples

```
data(EuStockMarkets)
as.data.frame(EuStockMarkets) |>
  dplyr::slice_head(n = 200) |>
  dplyr::mutate(day = 1:dplyr::n()) |>
  e_charts(day) |>
  e_line(CAC, symbol = "none") |>
  e_band2(DAX, FTSE, color = "lemonchiffon") |>
  e_band2(DAX, SMI, color = "lightblue", itemStyle = list(borderWidth = 0)) |>
  e_y_axis(scale = TRUE) |>
  e_datazoom(start = 50)
```

callbacks	<i>Callbacks</i>
-----------	------------------

Description

Binds events to chart interactions.

Usage

```
e_on(e, query, handler, event = "click")

e_off(e, query, handler, event = "click")
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
query	Condition that triggers the handler
handler	JavaScript handler, passed to JS .
event	Event that triggers the handler.

See Also

[official documentation](#)

Examples

```
cars |>
  e_charts(speed) |>
  e_scatter(dist) |>
  e_on(
    list(seriesName = "dist"),
    "function(){alert('Serie clicked')}")
)
```

connections	<i>Connect charts</i>
-------------	-----------------------

Description

Connect charts together.

Usage

```
e_connect(e, ids)

e_group(e, group)

e_connect_group(e, group)

e_disconnect_group(e, group = NULL)

e_arrange(..., rows = NULL, cols = NULL, width = "xs", title = NULL)
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
ids	Scalar, vector or list of ids of chart to connect with.
group	Group name.
...	Any echarts objects.
rows, cols	Number of rows and columns.
width	Width of columns, one of xs, md, lg.
title	Title of charts.

Value

e_arrange: in an interactive session, returns a `htmltools::browsable`, in `rmarkdown` returns a container (`htmltools::div`).

Functions

- `e_connect`: connects charts by ids, *cannot* be disconnected.
- `e_group`: assigns a group to chart.
- `e_connect_group`: connects chart with another group.
- `e_disconnect_group`: disconnects chart from group.
- `e_arrange`: arrange charts.

Note

`e_arrange` may not work properly in the RStudio viewer.

Examples

```
# linked datazoom
e1 <- cars |>
  e_charts(
    speed,
    height = 200
  ) |>
  e_scatter(dist) |>
  e_datazoom(show = FALSE) |>
  e_group("grp") # assign group

e2 <- cars |>
  e_charts(
    dist,
    height = 200
  ) |>
  e_scatter(speed) |>
  e_datazoom() |>
  e_group("grp") |> # assign group
  e_connect_group("grp") # connect

if (interactive()) {
  e_arrange(e1, e2, title = "Linked datazoom")
}
```

echarts4r-shiny

Shiny bindings for echarts4r

Description

Output and render functions for using echarts4r within Shiny applications and interactive Rmd documents.

Usage

```
echarts4rOutput(outputId, width = "100%", height = "400px")
```

```
renderEcharts4r(expr, env = parent.frame(), quoted = FALSE)
```

```
echarts4rProxy(
  id,
  data,
  x,
  timeline = FALSE,
  session = shiny::getDefaultReactiveDomain(),
  reorder = TRUE
)
```

```
echarts4r_proxy(
  id,
  data,
  x,
  timeline = FALSE,
  session = shiny::getDefaultReactiveDomain(),
  reorder = TRUE
)
```

Arguments

outputId	output variable to read from.
width, height	Must be a valid CSS unit (like '100%', '400px', 'auto') or a number, which will be coerced to a string and have 'px' appended.
expr	An expression that generates a echarts4r
env	The environment in which to evaluate expr.
quoted	Is expr a quoted expression (with quote())? This is useful if you want to save an expression in a variable.
id	Target chart id.
data	A data.frame.
x	Column name containing x axis.
timeline	Set to TRUE to build a timeline, see timeline section.

session	Shiny session.
reorder	Set the FALSE to not reorder numeric x axis values.

Callbacks

- `id_brush`: returns data on brushed data points.
- `id_legend_change`: returns series name of legend selected/unselected.
- `id_clicked_data`: returns data of clicked data point.
- `id_clicked_data_value`: returns value of clicked data point.
- `id_clicked_row`: returns row number of clicked data point.
- `id_clicked_serie`: returns name of serie of clicked data point.
- `id_mouseover_data`: returns data on hovered data point.
- `id_mouseover_data_value`: returns value of hovered data point.
- `id_mouseover_row`: returns row o hovered data point.
- `id_mouseover_serie`: returns name of serie of hovered data point.

Proxies

The `echarts4rProxy` function returns a proxy for chart which allows manipulating a drawn chart, adding data, adding or removing series, etc. without redrawing the entire chart.

- `e_append1_p` & `e_append2_p`
- `e_showtip_p` & `e_hidetip_p`
- `e_highlight_p` & `e_downplay_p`
- `e_focus_adjacency` & `e_unfocus_adjacency`
- `e_dispatch_action_p`
- `e_execute`
- `e_remove_serie_p`

echarts4rBox

Box

Description

Renders a data box in shiny.

Usage

```
echarts4rBox(
  data,
  x,
  y,
  text = "",
  subtext = "",
  type = c("bar", "line", "scatter", "area", "step"),
  ...,
  color = "#ffffff",
  text_color = "#ffffff",
  background_color = "#293c55",
  step = c("start", "middle", "end"),
  title_args = list(),
  tooltip = list(trigger = "axis")
)
```

Arguments

<code>data</code>	A dataframe containing data to plot.
<code>x, y</code>	Bare column name of variables to draw.
<code>text, subtext</code>	Title and subtitle of box.
<code>type</code>	Chart type to draw.
<code>...</code>	Additional arguments to pass to the serie.
<code>color</code>	Color of chart in box.
<code>text_color</code>	Color of text.
<code>background_color</code>	Color of box.
<code>step</code>	Step method, only used if <code>type = "step"</code> .
<code>title_args</code>	Additional arguments to add to the title.
<code>tooltip</code>	Tooltip to use.

See Also

[renderEcharts4rBox](#), [echarts4rBoxOutput](#)

Examples

```
library(shiny)

ui <- fluidPage(
  fluidRow(
    column(3, echarts4rBoxOutput("box1"))
  )
)
```

```

server <- function(input, output) {
  output$box1 <- renderEcharts4rBox({
    echarts4rBox(cars, speed, dist, "Cars", type = "bar")
  })
}
## Not run:
shinyApp(ui, server)

## End(Not run)

```

echarts4rBoxOutput	<i>Box Output</i>
--------------------	-------------------

Description

Place box output in Shiny ui.

Usage

```
echarts4rBoxOutput(id, height = 150)
```

Arguments

id	Id of box.
height	Height of box, any valid CSS value, numerics are treated as pixels.

e_animation	<i>Animation</i>
-------------	------------------

Description

Customise animations.

Usage

```

e_animation(
  e,
  show = TRUE,
  threshold = NULL,
  duration = NULL,
  easing = NULL,
  delay = NULL,
  duration.update = NULL,
  easing.update = NULL,
  delay.update = NULL
)

```

Arguments

<code>e</code>	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
<code>show</code>	Set to show animation.
<code>threshold</code>	Whether to set graphic number threshold to animation. Animation will be disabled when graphic number is larger than threshold.
<code>duration</code>	Duration of the first animation.
<code>easing</code>	Easing method used for the first animation.
<code>delay</code>	Delay before updating the first animation.
<code>duration.update</code>	Time for animation to complete.
<code>easing.update</code>	Easing method used for animation.
<code>delay.update</code>	Delay before updating animation.

See Also

[Additional arguments](#)

Examples

```
mtcars |>
  e_charts(mpg) |>
  e_area(drat) |>
  e_animation(duration = 10000)
```

<code>e_append1_p</code>	<i>Append Proxy</i>
--------------------------	---------------------

Description

Append data dynamically.

Usage

```
e_append1_p(proxy, series_index = NULL, data, x, y, name = NULL)

e_append1_p(proxy, series_index = NULL, data, x, y, name = NULL)

e_append2_p(
  proxy,
  series_index = NULL,
  data,
  x,
  y,
  z,
  scale = NULL,
```

```

    symbol_size = 1
  )

  e_append2_p_(
    proxy,
    series_index = NULL,
    data,
    x,
    y,
    z,
    scale = NULL,
    symbol_size = 1
  )

```

Arguments

proxy	An echarts4r proxy as returned by echarts4rProxy .
series_index	Index of serie to append to (starts from 0).
data	Data.frame containing data to append.
x, y, z	Columns names to plot.
name	if using 'bind' with e.g 'e_scatter' this can be used to supply the colname for the name attribute bind is mapping to
scale	A scaling function as passed to e_scatter .
symbol_size	Multiplier of scaling function as in e_scatter .

Details

Currently not all types of series supported incremental rendering when using appendData. Only these types of series support it: [e_scatter](#) and [e_line](#) of pure echarts, and [e_scatter_3d](#), and [e_line_3d](#) of echarts-gl.

Examples

```

## Not run:
library(shiny)

ui <- fluidPage(
  actionButton("add", "Add Data to y"),
  echarts4rOutput("plot"),
  h4("Brush"),
  verbatimTextOutput("selected"),
  h4("Legend select change"),
  verbatimTextOutput("legend")
)

server <- function(input, output, session) {
  data <- data.frame(x = rnorm(10, 5, 3), y = rnorm(10, 50, 12), z = rnorm(10, 5, 20))

  react <- eventReactive(input$add, {

```

```

    set.seed(sample(1:1000, 1))
    data.frame(x = rnorm(10, 5, 2), y = rnorm(10, 50, 10), z = rnorm(10, 5, 20))
  })

  output$plot <- renderEcharts4r({
    data |>
      e_charts(x) |>
      e_scatter(y, z, scale = NULL) |>
      e_scatter(z) |>
      e_brush()
  })

  observeEvent(input$add, {
    echarts4rProxy("plot") |>
      e_append2_p(0, react(), x, y, z)
  })

  output$selected <- renderPrint({
    input$plot_brush
  })

  output$legend <- renderPrint({
    input$plot_legend_change
  })
}

shinyApp(ui, server)

## End(Not run)

```

e_area

Area

Description

Add area serie. Note that this is NOT an unique series type. Rather, this function is a shorthand for using ‘e_bar()’ with ‘areaStyle = list()’ enabled.

Usage

```

e_area(
  e,
  serie,
  bind,
  name = NULL,
  legend = TRUE,
  y_index = 0,
  x_index = 0,

```

```

    coord_system = "cartesian2d",
    ...
)

e_area_(
  e,
  serie,
  bind = NULL,
  name = NULL,
  legend = TRUE,
  y_index = 0,
  x_index = 0,
  coord_system = "cartesian2d",
  ...
)

```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
serie	Column name of serie to plot.
bind	Binding between datasets, namely for use of e_brush .
name	name of the serie.
legend	Whether to add serie to legend.
x_index, y_index	Indexes of x and y axis.
coord_system	Coordinate system to plot against.
...	Any other option to pass, check See Also section.

See Also

[Additional arguments](#)

Examples

```

C02 |>
  group_by(Plant) |>
  e_charts(conc) |>
  e_area(uptake) |>
  e_tooltip(trigger = "axis")

# timeline
iris |>
  group_by(Species) |>
  e_charts(Sepal.Length, timeline = TRUE) |>
  e_area(Sepal.Width) |>
  e_tooltip(trigger = "axis")

```

<code>e_aria</code>	<i>Aria</i>
---------------------	-------------

Description

W3C defined the Accessible Rich Internet Applications Suite (WAI-ARIA) to make Web content and Web applications more accessible to the disabled. From ECharts 4.0, echarts4r supports ARIA by generating description for charts automatically.

Usage

```
e_aria(e, enabled = TRUE, ...)
```

Arguments

- `e` An echarts4r object as returned by [e_charts](#) or a proxy as returned by [echarts4rProxy](#).
- `enabled` Whether to enable aria helper text.
- `...` Any other option to pass, check See Also section.

Details

There should be an aria-label attribute on the chart DOM, which can help the disabled understand the content of charts with the help of certain devices.

See Also

[official documentation](#)

<code>e_axis</code>	<i>Axis</i>
---------------------	-------------

Description

Customise axis.

Usage

```
e_axis(  
  e,  
  serie,  
  axis = c("x", "y", "z"),  
  index = 0,  
  formatter = NULL,  
  margin = 0,  
  ...  
)
```

```

)

e_axis_(
    e,
    serie = NULL,
    axis = c("x", "y", "z"),
    index = 0,
    formatter = NULL,
    margin = 0,
    ...
)

e_x_axis(e, serie = NULL, index = 0, formatter = NULL, margin = 0, ...)
e_y_axis(e, serie = NULL, index = 0, formatter = NULL, margin = 0, ...)
e_z_axis(e, serie = NULL, index = 0, margin = 0, ...)

e_x_axis(e, serie, index = 0, formatter = NULL, margin = 0, ...)
e_y_axis(e, serie, index = 0, formatter = NULL, margin = 0, ...)
e_z_axis(e, serie, index = 0, margin = 0, ...)

e_rm_axis(e, axis = c("x", "y", "z"))

e_axis_formatter(
    style = c("decimal", "percent", "currency"),
    digits = 0,
    locale = NULL,
    currency = "USD"
)

```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
serie	Column name of serie to range the axis. If used the range of the serie is used as, min an max.
axis	Axis to customise.
index	Index of axis to customise.
formatter	An axis formatter as returned by e_axis_formatter .
margin	Margin to apply to serie: $min = serie - margin$ and $max = serie + margin$
...	Any other option to pass, check See Also section.
style	Formatter style, one of decimal, percent, or currency.
digits	Number of decimals.
locale	Locale, if NULL then it is inferred from <code>Sys.getlocale</code> .
currency	Currency to to display.

Details

The `e_axis_formatter` may not work in RStudio, open the plot in your browser. It will display just fine in Rmarkdown and Shiny.

Functions

- `e_axis` to customise axis
- `e_rm_axis` to remove axis

See Also

[Additional x arguments](#), [Additional y arguments](#)

Examples

```
# range axis based on serie
cars |>
  e_charts(speed) |>
  e_line(dist) |>
  e_x_axis(speed) |>
  e_y_axis(dist)

# use formatter
cars |>
  dplyr::mutate(
    speed = speed / 25
  ) |>
  e_charts(speed) |>
  e_scatter(dist) |>
  e_y_axis(
    formatter = e_axis_formatter("currency")
  ) |>
  e_x_axis(
    formatter = e_axis_formatter("percent", digits = 0)
  )

# plot all labels & rotate
USArrests |>
  head(10) |>
  tibble::rownames_to_column(var = "State") |>
  e_charts(State) |>
  e_area(Murder) |>
  e_x_axis(axisLabel = list(interval = 0, rotate = 45)) # rotate
```

e_axis_3d

Axis 3D

Description

Customise 3D axis.

Usage

```
e_axis_3d(e, axis = c("x", "y", "z"), index = 0, ...)

e_x_axis_3d(e, index = 0, ...)

e_y_axis_3d(e, index = 0, ...)

e_z_axis_3d(e, index = 0, ...)
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
axis	Axis to customise.
index	Index of axis to customise.
...	Any other option to pass, check See Also section.

See Also

[Additional x arguments](#), [Additional y arguments](#), [Additional z arguments](#)

Examples

```
# phony data
v <- LETTERS[1:10]
matrix <- data.frame(
  x = sample(v, 300, replace = TRUE),
  y = sample(v, 300, replace = TRUE),
  z1 = rnorm(300, 10, 1),
  z2 = rnorm(300, 10, 1),
  stringsAsFactors = FALSE
) |>
  dplyr::group_by(x, y) |>
  dplyr::summarise(
    z1 = sum(z1),
    z2 = sum(z2)
  ) |>
  dplyr::ungroup()

trans <- list(opacity = 0.4) # transparency
emphasis <- list(itemStyle = list(color = "#313695"))

matrix |>
  e_charts(x) |>
  e_bar_3d(y, z1, stack = "stack", name = "Serie 1", itemStyle = trans, emphasis = emphasis) |>
  e_bar_3d(y, z2, stack = "stack", name = "Serie 2", itemStyle = trans, emphasis = emphasis) |>
  e_x_axis_3d(axisLine = list(lineStyle = list(color = "blue")))
```

e_axis_labels	<i>Axis Labels</i>
---------------	--------------------

Description

Convenience function to add axis labels.

Usage

```
e_axis_labels(e, x = "", y = "")
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
x, y	Labels of axes.

Examples

```
cars |>
  e_charts(speed) |>
  e_scatter(dist) |>
  e_axis_labels(
    x = "speed",
    y = "distance"
  )
```

e_axis_pointer	<i>Axis pointer</i>
----------------	---------------------

Description

Customise axis pointer.

Usage

```
e_axis_pointer(e, ...)
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
...	Any other option to pass, check See Also section.

See Also

[Additional arguments](#)

`e_axis_stagger`*Stagger Axis Labels*

Description

Stagger axis labels.

Usage

```
e_axis_stagger(e)
```

Arguments

`e` An echarts4r object as returned by [e_charts](#) or a proxy as returned by [echarts4rProxy](#).

Examples

```
df <- data.frame(
  x = c("a very long label", "Another long label"),
  y = 1:2
)

df |>
  e_charts(x, width = 150) |>
  e_bar(y) |>
  e_axis_stagger()
```

`e_bar`*Bar and Line chart*

Description

Add bar serie.

Usage

```
e_bar(
  e,
  serie,
  bind,
  name = NULL,
  legend = TRUE,
  y_index = 0,
  x_index = 0,
  coord_system = "cartesian2d",
  ...
)
```

```

)

e_bar_(
  e,
  serie,
  bind = NULL,
  name = NULL,
  legend = TRUE,
  y_index = 0,
  x_index = 0,
  coord_system = "cartesian2d",
  ...
)

```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
serie	Column name of serie to plot.
bind	Binding between datasets, namely for use of e_brush .
name	name of the serie.
legend	Whether to add serie to legend.
x_index, y_index	Indexes of x and y axis.
coord_system	Coordinate system to plot against.
...	Any other option to pass, check See Also section.

Note

The bar serie expects the data on the x axis to be categorical in R this means a factor or character. If the data on the x axis is numeric everything should work well in most cases but strange behaviour may be observed.

See Also

[Additional arguments](#)

Examples

```

library(dplyr)

mtcars |>
  tibble::rownames_to_column("model") |>
  mutate(total = mpg + qsec) |>
  arrange(desc(total)) |>
  e_charts(model) |>
  e_bar(mpg, stack = "grp") |>
  e_bar(qsec, stack = "grp")

```

e_bar_3d	<i>Bar 3D</i>
----------	---------------

Description

Add 3D bars

Usage

```
e_bar_3d(  
  e,  
  y,  
  z,  
  bind,  
  coord_system = "cartesian3D",  
  name = NULL,  
  rm_x = TRUE,  
  rm_y = TRUE,  
  ...  
)  
  
e_bar_3d_(  
  e,  
  y,  
  z,  
  bind = NULL,  
  coord_system = "cartesian3D",  
  name = NULL,  
  rm_x = TRUE,  
  rm_y = TRUE,  
  ...  
)
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
y, z	Coordinates.
bind	Binding.
coord_system	Coordinate system to use, one of cartesian3D, geo3D, globe.
name	name of the serie.
rm_x, rm_y	Whether to remove x and y axis, defaults to TRUE.
...	Any other option to pass, check See Also section.

See Also

[Additional arguments](#)

Examples

```
## Not run:
# volcano
volcano |>
  as.table() |>
  as.data.frame() |>
  dplyr::mutate(
    Var1 = as.integer(Var1),
    Var2 = as.integer(Var2)
  ) |>
  e_charts(Var1) |>
  e_bar_3d(Var2, Freq) |>
  e_visual_map(Freq)

url <- paste0(
  "https://echarts.apache.org/examples/",
  "data-gl/asset/data/population.json"
)
data <- jsonlite::fromJSON(url)
data <- as.data.frame(data)
names(data) <- c("lon", "lat", "value")

# globe
data |>
  e_charts(lon) |>
  e_globe() |>
  e_bar_3d(lat, value, coord_system = "globe") |>
  e_visual_map()

# get3d
data |>
  e_charts(lon) |>
  e_geo_3d() |>
  e_bar_3d(lat, value, coord_system = "geo3D") |>
  e_visual_map()

# stacked
v <- LETTERS[1:10]
matrix <- data.frame(
  x = sample(v, 300, replace = TRUE),
  y = sample(v, 300, replace = TRUE),
  z1 = rnorm(300, 10, 1),
  z2 = rnorm(300, 10, 1),
  stringsAsFactors = FALSE
) |>
  dplyr::group_by(x, y) |>
  dplyr::summarise(
    z1 = sum(z1),
    z2 = sum(z2)
  ) |>
  dplyr::ungroup()
```

```

trans <- list(opacity = 0.4) # transparency
emphasis <- list(itemStyle = list(color = "#313695"))

matrix |>
  e_charts(x) |>
  e_bar_3d(y, z1, stack = "stack", name = "Serie 1", itemStyle = trans, emphasis = emphasis) |>
  e_bar_3d(y, z2, stack = "stack", name = "Serie 2", itemStyle = trans, emphasis = emphasis) |>
  e_legend()

# timeline
matrix |>
  group_by(x) |>
  e_charts(y, timeline = TRUE) |>
  e_bar_3d(z1, z2) |>
  e_visual_map(z2)

## End(Not run)

```

e_boxplot

Boxplot

Description

Draw boxplot.

Usage

```
e_boxplot(e, serie, name = NULL, outliers = TRUE, ...)
```

```
e_boxplot_(e, serie, name = NULL, outliers = TRUE, ...)
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
serie	Column name of serie to plot.
name	name of the serie.
outliers	Whether to plot outliers.
...	Any other option to pass, check See Also section.

See Also

[Additional arguments](#)

Examples

```
df <- data.frame(
  x = c(1:10, 25),
  y = c(1:10, -6)
)

df |>
  e_charts() |>
  e_boxplot(y, outliers = TRUE) |>
  e_boxplot(x, outliers = TRUE)
```

e_brush	<i>Brush</i>
---------	--------------

Description

Add a brush.

Usage

```
e_brush(e, x_index = NULL, y_index = NULL, brush_link = "all", ...)
```

Arguments

- | | |
|-------------------------------|--|
| <code>e</code> | An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy . |
| <code>x_index, y_index</code> | Indexes of x and y axis. |
| <code>brush_link</code> | Links interaction between selected items in different series. |
| <code>...</code> | Any other option to pass, check See Also section. |

`brush_link`

- \$
- `c(3, 4, 5)`, for interacting series with `seriesIndex` as 3, 4, or 5.
 - `all`, for interacting all series.
 - `none` for disabling.

See Also

[Additional arguments](#)

Examples

```

quakes |>
  e_charts(long) |>
  e_geo(
    boundingCoords = list(
      c(190, -10),
      c(180, -40)
    )
  ) |>
  e_scatter(lat, mag, stations, coord.system = "geo", name = "mag") |>
  e_data(quakes, depth) |>
  e_scatter(mag, mag, stations, name = "mag & depth") |>
  e_grid(right = 40, top = 100, width = "30%") |>
  e_y_axis(type = "value", name = "depth", min = 3.5) |>
  e_brush() |>
  e_theme("dark")

```

e_button	<i>Button</i>
----------	---------------

Description

Add a button to your visualisation.

Usage

```
e_button(e, id, ..., position = "top", tag = htmltools::tags$button)
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
id	A valid CSS id.
...	Content of the button, compliant with <code>htmltools</code> .
position	Position of button, top or bottom.
tag	A Valid <code>htmltools::tags</code> function.

Examples

```

iris |>
  group_by(Species) |>
  e_charts(Sepal.Length) |>
  e_line(Sepal.Width) |>
  e_line(Petal.Length) |>
  e_highlight(series_name = "setosa", btn = "myBtn") |>
  e_button("myBtn", "highlight stuff")

```

e_calendar

*Calendar***Description**

Calendar

Usage

e_calendar(e, range, ...)

Arguments

e An echarts4r object as returned by [e_charts](#) or a proxy as returned by [echarts4rProxy](#).

range Range of calendar format, string or vector.

... Any other option to pass, check See Also section.

See Also[Additional arguments](#)**Examples**

```

dates <- seq.Date(as.Date("2017-01-01"), as.Date("2019-12-31"), by = "day")
values <- rnorm(length(dates), 20, 6)
year <- data.frame(date = dates, values = values)

year |>
  e_charts(date) |>
  e_calendar(range = "2017") |>
  e_visual_map(max = 30) |>
  e_heatmap(values, coord_system = "calendar")

# month
year |>
  e_charts(date) |>
  e_calendar(range = "2017-01") |>
  e_visual_map(max = 30) |>
  e_heatmap(values, coord_system = "calendar")

# range
year |>
  e_charts(date) |>
  e_calendar(range = c("2018-01", "2018-07")) |>
  e_visual_map(max = 30) |>
  e_heatmap(values, coord_system = "calendar")

```

e_candle

*Candlestick***Description**

Add a candlestick chart.

Usage

```
e_candle(e, opening, closing, low, high, bind, name = NULL, legend = TRUE, ...)
```

```
e_candle_(
  e,
  opening,
  closing,
  low,
  high,
  bind = NULL,
  name = NULL,
  legend = TRUE,
  ...
)
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
opening, closing, low, high	Stock prices.
bind	Binding between datasets, namely for use of e_brush .
name	name of the serie.
legend	Whether to add serie to legend.
...	Any other option to pass, check See Also section.

See Also

[Additional arguments](#)

Examples

```
date <- c(
  "2017-01-01",
  "2017-01-02",
  "2017-01-03",
  "2017-01-04",
  "2017-03-05",
  "2017-01-06",
  "2017-01-07"
```

```

)

stock <- data.frame(
  date = date,
  opening = c(200.60, 200.22, 198.43, 199.05, 203.54, 203.40, 208.34),
  closing = c(200.72, 198.85, 199.05, 203.73, 204.08, 208.11, 211.88),
  low = c(197.82, 198.07, 197.90, 198.10, 202.00, 201.50, 207.60),
  high = c(203.32, 200.67, 200.00, 203.95, 204.90, 208.44, 213.17)
)

stock |>
  e_charts(date) |>
  e_candle(opening, closing, low, high) |>
  e_y_axis(min = 190, max = 220)

```

e_capture

Capture event

Description

Add an event capture.

Usage

```
e_capture(e, event)
```

Arguments

e An echarts4r object as returned by [e_charts](#) or a proxy as returned by [echarts4rProxy](#).
event An event name from the [event documentation](#).

Details

Many events can be captured, however not all are integrated, you can pass one that is not implemented with this function.

Examples

```

## Not run:
# add datazoom
library(shiny)

ui <- fluidPage(
  echarts4rOutput("chart"),
  verbatimTextOutput("zoom")
)

server <- function(input, output) {
  output$chart <- renderEcharts4r({

```

```

mtcars |>
  e_charts(mpg) |>
  e_scatter(qsec) |>
  e_datazoom() |>
  e_capture("datazoom")
})

output$zoom <- renderPrint({
  input$chart_datazoom
})
}

if (interactive()) {
  shinyApp(ui, server)
}

## End(Not run)

```

e_cloud

Wordcloud

Description

Draw a wordcloud.

Usage

```
e_cloud(e, word, freq, color, rm_x = TRUE, rm_y = TRUE, ...)
```

```
e_cloud_(e, word, freq, color = NULL, rm_x = TRUE, rm_y = TRUE, ...)
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
word, freq	Terms and their frequencies.
color	Word color.
rm_x, rm_y	Whether to remove x and y axis, defaults to TRUE.
...	Any other option to pass, check See Also section.

See Also

[official documentation](#)

Examples

```
words <- function(n = 5000) {
  a <- do.call(paste0, replicate(5, sample(LETTERS, n, TRUE), FALSE))
  paste0(a, sprintf("%04d", sample(9999, n, TRUE)), sample(LETTERS, n, TRUE))
}

tf <- data.frame(
  terms = words(100),
  freq = rnorm(100, 55, 10)
) |>
  dplyr::arrange(-freq)

tf |>
  e_color_range(freq, color) |>
  e_charts() |>
  e_cloud(terms, freq, color, shape = "circle", sizeRange = c(3, 15))
```

e_color

Color

Description

Customise chart and background colors.

Usage

```
e_color(e, color = NULL, background = NULL, append = TRUE)

## S3 method for class 'echarts4r'
e_color(e, color = NULL, background = NULL, append = TRUE)

## S3 method for class 'echarts4rProxy'
e_color(e, color = NULL, background = NULL, append = TRUE)
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
color	Vector of colors.
background	Background color.
append	Only applicable to 'echarts4rProxy'. Whether to append the 'color' to the existing array (vector) or colors or to replace it.

See Also

[e_theme](#), [Official color documentation](#), [Official background documentation](#)

Examples

```
mtcars |>
  e_charts(drat) |>
  e_line(mpg) |>
  e_area(qsec) |>
  e_color(
    c("red", "blue"),
    "#d3d3d3"
  )
```

e_color_range

Color range

Description

Build manual color range

Usage

```
e_color_range(
  data,
  input,
  output,
  colors = c("#bf444c", "#d88273", "#f6efa6"),
  ...
)

e_color_range_(
  data,
  input,
  output,
  colors = c("#bf444c", "#d88273", "#f6efa6"),
  ...
)
```

Arguments

data	Data.frame in which to find column names.
input, output	Input and output columns.
colors	Colors to pass to colorRampPalette .
...	Any other argument to pass to colorRampPalette .

Examples

```
df <- data.frame(val = 1:10)

e_color_range(df, val, colors)
```

e_common

General options

Description

General options

Usage

```
e_common(font_family = NULL, theme = NULL)
```

Arguments

font_family	Font family.
theme	A theme.

e_correlations

Correlation

Description

Correlation

Usage

```
e_correlations(e, order = NULL, visual_map = TRUE, ...)
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
order	Ordering method, passed to corrMatOrder .
visual_map	Whether to add the visual map.
...	Any argument to pass to e_heatmap and e_visual_map .

Examples

```
cor(mtcars) |>
  e_charts() |>
  e_correlations(
    order = "hclust",
    visual_map = FALSE
  ) |>
  e_visual_map(
    min = -1,
    max = 1
  )
```

e_country_names	<i>Country names</i>
-----------------	----------------------

Description

Convert country names to echarts format.

Usage

```
e_country_names(data, input, output, type = "iso2c", ...)
```

```
e_country_names_(data, input, output = NULL, type = "iso2c", ...)
```

Arguments

data	Data.frame in which to find column names.
input, output	Input and output columns.
type	Passed to countrycode origin parameter.
...	Any other parameter to pass to countrycode .

Details

Taiwan and Hong Kong cannot be plotted.

Examples

```
cns <- data.frame(country = c("US", "BE"))

# replace
e_country_names(cns, country)

# specify output
e_country_names(cns, country, country_name)
```

e_datazoom	<i>Data zoom</i>
------------	------------------

Description

Add data zoom.

Usage

```
e_datazoom(e, x_index = NULL, y_index = NULL, toolbox = TRUE, ...)
```

Arguments

- `e` An echarts4r object as returned by [e_charts](#) or a proxy as returned by [echarts4rProxy](#).
- `x_index, y_index` Indexes of x and y axis.
- `toolbox` Whether to add the toolbox, [e_toolbox_feature](#), (`e_toolbox_feature(e, "dataZoom")`).
- `...` Any other option to pass, check See Also section.

See Also

[Additional arguments](#)

Examples

```
USArrests |>
  e_charts(UrbanPop) |>
  e_line(Assault) |>
  e_area(Murder, y_index = 1, x_index = 1) |>
  e_y_axis(gridIndex = 1) |>
  e_x_axis(gridIndex = 1) |>
  e_grid(height = "35%") |>
  e_grid(height = "35%", top = "50%") |>
  e_toolbox_feature("dataZoom", title = list(zoom = "zoom", back = "back")) |>
  e_datazoom(x_index = c(0, 1))
```

<code>e_dims</code>	<i>Dimensions</i>
---------------------	-------------------

Description

Sets the dimensions of the chart `_internally_`. This will only affect the dimensions of the chart within its parent container. Use the `'height'` and `'width'` arguments of `[e_charts]` if you want to change the dimensions of said parent (recommended).

Usage

```
e_dims(e, height = "auto", width = "auto")
```

Arguments

- `e` An echarts4r object as returned by [e_charts](#) or a proxy as returned by [echarts4rProxy](#).
- `height, width` Dimensions in pixels, percentage or string.

e_dispatch_action_p	<i>Dispatch Action</i>
---------------------	------------------------

Description

Create your own proxies, essentially a wrapper around the [action API](#).

Usage

```
e_dispatch_action_p(proxy, type, ...)
```

Arguments

proxy	An echarts4r proxy as returned by echarts4rProxy .
type	Type of action to dispatch, i.e.: highlight.
...	Named options.

Examples

```
## Not run:

library(shiny)

ui <- fluidPage(
  fluidRow(
    column(8, echarts4rOutput("chart")),
    column(4, actionButton("zoom", "Zoom"))
  )
)

server <- function(input, output, session) {
  output$chart <- renderEcharts4r({
    cars |>
      e_charts(speed) |>
      e_scatter(dist) |>
      e_datazoom()
  })

  observe({
    req(input$zoom)

    echarts4rProxy("chart") |>
      e_dispatch_action_p("dataZoom", startValue = 1, endValue = 10)
  })
}

if (interactive()) {
  shinyApp(ui, server)
}
```

```
## End(Not run)
```

e_draft	<i>Draft</i>
---------	--------------

Description

Add a draft watermark to your graph.

Usage

```
e_draft(e, text = "DRAFT", size = "120px", opacity = 0.4, color = "#d3d3d3")
```

Arguments

- e An echarts4r object as returned by [e_charts](#) or a proxy as returned by [echarts4rProxy](#).
- text Text to display.
- size Font size of text.
- opacity, color Opacity and color of text.

Examples

```
cars |>  
  e_charts(speed) |>  
  e_scatter(dist) |>  
  e_draft()
```

e_draw_p	<i>Draw</i>
----------	-------------

Description

Draw the chart.

Usage

```
e_draw_p(proxy)
```

Arguments

- proxy An echarts4r proxy as returned by [echarts4rProxy](#).

Details

Useful if you set draw to FALSE in [e_charts](#).

Examples

```
## Not run:
library(shiny)

ui <- fluidPage(
  echarts4rOutput("chart"),
  actionButton("draw", "draw")
)

server <- function(input, output) {
  output$chart <- renderEcharts4r({
    mtcars |>
      e_charts(mpg, draw = FALSE) |>
      e_scatter(qsec) |>
      e_datazoom()
  })

  observeEvent(input$draw, {
    echarts4rProxy("chart") |>
      e_draw_p()
  })
}

if (interactive()) {
  shinyApp(ui, server)
}

## End(Not run)
```

e_error_bar

Error bar

Description

Add error bars.

Usage

```
e_error_bar(
  e,
  lower,
  upper,
  name = NULL,
  legend = FALSE,
  y_index = 0,
  x_index = 0,
  coord_system = "cartesian2d",
  ...
)
```

```

)

e_error_bar_(
  e,
  lower,
  upper,
  name = NULL,
  legend = FALSE,
  y_index = 0,
  x_index = 0,
  coord_system = "cartesian2d",
  itemStyle = list(borderWidth = 1.5),
  renderer = "renderErrorBar2",
  ...
)

```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
lower, upper	Lower and upper error bands.
name	name of the serie.
legend	Whether to add serie to legend.
x_index, y_index	Indexes of x and y axis.
coord_system	Coordinate system to plot against.
...	Any other option to pass, check See Also section.
itemStyle	mostly used for borderWidth, default 1.5
renderer	name of render function from renderers.js

Examples

```

df <- data.frame(
  x = factor(c(1, 2)),
  y = c(1, 5),
  upper = c(1.1, 5.3),
  lower = c(0.8, 4.6)
)

df |>
  e_charts(x) |>
  e_bar(y) |>
  e_error_bar(lower, upper)

# timeline
df <- data.frame(
  x = factor(c(1, 1, 2, 2)),
  y = c(1, 5, 3, 4),
  step = factor(c(1, 2, 1, 2)),

```

```

    upper = c(1.1, 5.3, 3.3, 4.2),
    lower = c(0.8, 4.6, 2.4, 3.6)
  )

df |>
  group_by(step) |>
  e_charts(x, timeline = TRUE) |>
  e_bar(y) |>
  e_error_bar(lower, upper)

```

e_execute

*Send***Description**

Send new series to chart.

Usage

```
e_execute(proxy)
```

```
e_execute_p(proxy)
```

Arguments

proxy An echarts4r proxy as returned by [echarts4rProxy](#).

e_facet

*Facet***Description**

Create facets for multiple plots.

Usage

```

e_facet(
  e,
  rows = NULL,
  cols = NULL,
  legend_pos = "top",
  legend_space = 10,
  margin_trbl = c(t = 2, r = 2, b = 5, l = 2),
  h_panel_space = NULL,
  v_panel_space = NULL
)

```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
rows, cols	Number of rows and columns. If both are 'NULL' the number of rows and columns will be determined automatically.
legend_pos	Position of the legend. One of "top", "right", "bottom", "left". Determines to which side the 'legend_space' argument applies.
legend_space	Space between legend and plot area. The entered number will be used as percentage.
margin_trbl	Adjusts the size of the outside margin around the plotting area. Default is 'c(t = 2, r = 2, b = 5, l = 2)'. Numbers are used as percentage of total plotting area. To change only e.g. two sides 'c("r" = 8, "l" = 8)' could be used, other sides will use defaults.
h_panel_space, v_panel_space	Horizontal and vertical spacing between the individual grid elements. Expects numeric input, which will be used as percentage of total plotting area. Default 'NULL' will automatically add some panel spacing for low dimensional grids.

Details

Each serie, i.e.: [e_bar](#) will be plotted against a facet.

Examples

```
group_size <- 20
n_groups <- 13
df <- data.frame("day" = rep(1:group_size, times=n_groups),
                 "temperature" = runif(group_size * n_groups, 10, 40),
                 "location" = rep(LETTERS[1:n_groups], each=group_size))

df |>
  group_by(location) |>
  e_charts(day) |>
  e_line(temperature) |>
  e_facet(rows = 4, cols=4, legend_pos = "top", legend_space = 12)
```

e_flip_coords

Flip coordinates

Description

Flip cartesian 2D coordinates.

Usage

```
e_flip_coords(e)
```

Arguments

e An echarts4r object as returned by [e_charts](#) or a proxy as returned by [echarts4rProxy](#).

Examples

```
df <- data.frame(
  x = LETTERS[1:5],
  y = runif(5, 1, 5),
  z = runif(5, 3, 10)
)

df |>
  e_charts(x) |>
  e_bar(y) |>
  e_line(z) -> plot

plot # normal
e_flip_coords(plot) # flip
```

e_flow_gl

Flow GL

Description

Flow GL

Usage

```
e_flow_gl(
  e,
  y,
  sx,
  sy,
  color,
  name = NULL,
  coord_system = NULL,
  rm_x = TRUE,
  rm_y = TRUE,
  ...
)

e_flow_gl_(
  e,
  y,
  sx,
  sy,
  color = NULL,
  name = NULL,
```

```

    coord_system = NULL,
    rm_x = TRUE,
    rm_y = TRUE,
    ...
)

```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
y	Vector position on the y axis.
sx, sy	Velocity in respective axis.
color	Vector color.
name	name of the serie.
coord_system	Coordinate system to use.
rm_x, rm_y	Whether to remove x and y axis, only applies if coord_system is not null.
...	Any other option to pass, check See Also section.

See Also

[Additional arguments](#)

Examples

```

# coordinates
vectors <- expand.grid(0:9, 0:9)
names(vectors) <- c("x", "y")
vectors$sx <- rnorm(100)
vectors$sy <- rnorm(100)
vectors$color <- log10(runif(100, 1, 10))

vectors |>
  e_charts(x) |>
  e_flow_gl(y, sx, sy, color) |>
  e_visual_map(
    min = 0,
    max = 1,
    # log 10
    dimension = 4,
    # x = 0, y = 1, sx = 3, sy = 4
    show = FALSE,
    # hide
    inRange = list(
      color = c(
        "#313695",
        "#4575b4",
        "#74add1",
        "#abd9e9",
        "#e0f3f8",
        "#ffffbf",

```

```

      "#fee090",
      "#fdae61",
      "#f46d43",
      "#d73027",
      "#a50026"
    )
  )
) |>
e_x_axis(
  splitLine = list(show = FALSE)
) |>
e_y_axis(
  splitLine = list(show = FALSE)
)

# map
latlong <- seq(-180, 180, by = 5)
wind <- expand.grid(lng = latlong, lat = latlong)
wind$slng <- rnorm(nrow(wind), 0, 200)
wind$slat <- rnorm(nrow(wind), 0, 200)
wind$color <- abs(wind$slat) - abs(wind$slng)
rng <- range(wind$color)

trans <- list(opacity = 0.5) # transparency

wind |>
  e_charts(lng, backgroundColor = "#333") |>
  e_geo() |>
  e_flow_gl(
    lat,
    slng,
    slat,
    color,
    itemStyle = trans,
    particleSize = 2
  ) |>
  e_visual_map(
    color,
    # range
    dimension = 4,
    # lng = 0, lat = 1, slng = 2, slat = 3, color = 4
    show = FALSE,
    # hide
    inRange = list(
      color = c(
        "#313695",
        "#4575b4",
        "#74add1",
        "#abd9e9",
        "#e0f3f8",
        "#ffffbf",
        "#fee090",
        "#fdae61",

```

```

      "#f46d43",
      "#d73027",
      "#a50026"
    )
  )
) |>
e_x_axis(show = FALSE) |>
e_y_axis(show = FALSE)

```

e_focus_adjacency_p *Node Adjacency*

Description

Focus or unfocus on node adjacency.

Usage

```
e_focus_adjacency_p(proxy, index, ...)
```

```
e_unfocus_adjacency_p(proxy, ...)
```

Arguments

proxy	An echarts4r proxy as returned by echarts4rProxy .
index	One or more node index to focus on.
...	Any other options, see official documentation and details.

Details

Must pass seriesId, seriesIndex, or seriesName, generally seriesIndex = 0 will work.

Examples

```

value <- rnorm(10, 10, 2)

nodes <- data.frame(
  name = sample(LETTERS, 10),
  value = value,
  size = value,
  grp = rep(c("grp1", "grp2"), 5),
  stringsAsFactors = FALSE
)

edges <- data.frame(
  source = sample(nodes$name, 20, replace = TRUE),
  target = sample(nodes$name, 20, replace = TRUE),
  stringsAsFactors = FALSE
)

```

```
## Not run:

library(shiny)

ui <- fluidPage(
  fluidRow(
    column(
      2,
      numericInput("index", "Node", value = 3, min = 1, max = 9)
    ),
    column(
      2,
      br(),
      actionButton("focus", "Focus")
    ),
    column(
      2,
      br(),
      actionButton("unfocus", "Unfocus")
    )
  ),
  fluidRow(
    column(12, echarts4rOutput("graph"))
  )
)

server <- function(input, output, session) {
  output$graph <- renderEcharts4r({
    e_charts() |>
    e_graph() |>
    e_graph_nodes(nodes, name, value, size, grp) |>
    e_graph_edges(edges, source, target)
  })

  observeEvent(input$focus, {
    echarts4rProxy("graph") |>
    e_focus_adjacency_p(
      seriesIndex = 0,
      index = input$index
    )
  })

  observeEvent(input$unfocus, {
    echarts4rProxy("graph") |>
    e_unfocus_adjacency_p(seriesIndex = 0)
  })
}

if (interactive()) {
  shinyApp(ui, server)
}

## End(Not run)
```

e_format_axis

*Formatters***Description**

Simple formatters as helpers.

Usage

```
e_format_axis(e, axis = "y", suffix = NULL, prefix = NULL, ...)
```

```
e_format_x_axis(e, suffix = NULL, prefix = NULL, ...)
```

```
e_format_y_axis(e, suffix = NULL, prefix = NULL, ...)
```

Arguments

e An echarts4r object as returned by [e_charts](#) or a proxy as returned by [echarts4rProxy](#).

axis Axis to apply formatter to.

suffix, prefix Suffix and prefix of label.

... Any other arguments to pass to [e_axis](#).

Examples

```
# Y = %
df <- data.frame(
  x = 1:10,
  y = round(
    runif(10, 1, 100),
    2
  )
)

df |>
  e_charts(x) |>
  e_line(y) |>
  e_format_y_axis(suffix = "%") |>
  e_format_x_axis(prefix = "A")
```

e_funnel	<i>Funnel</i>
----------	---------------

Description

Add a funnel.

Usage

```
e_funnel(  
  e,  
  values,  
  labels,  
  name = NULL,  
  legend = TRUE,  
  rm_x = TRUE,  
  rm_y = TRUE,  
  ...  
)  
  
e_funnel_(  
  e,  
  values,  
  labels,  
  name = NULL,  
  legend = TRUE,  
  rm_x = TRUE,  
  rm_y = TRUE,  
  ...  
)
```

Arguments

- e An echarts4r object as returned by [e_charts](#).
- values, labels Values and labels of funnel.
- name name of the serie.
- legend Whether to add serie to legend.
- rm_x, rm_y Whether to remove x and y axis, defaults to TRUE.
- ... Any other option to pass to bar or line char types.

Details

No bind argument here, with a funnel bind = labels.

See Also

[Additional arguments](#)

Examples

```
funnel <- data.frame(
  stage = c("View", "Click", "Purchase"),
  value = c(80, 30, 20)
)

funnel |>
  e_charts() |>
  e_funnel(value, stage)
```

e_gauge	<i>Gauge</i>
---------	--------------

Description

Plot a gauge.

Usage

```
e_gauge(e, value, name, rm_x = TRUE, rm_y = TRUE, ...)

e_gauge_(e, value, name, rm_x = TRUE, rm_y = TRUE, ...)
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
value	Value to gauge.
name	Text on gauge.
rm_x, rm_y	Whether to remove x and y axis, defaults to TRUE.
...	Any other option to pass, check See Also section.

See Also

[Additional arguments](#)

Examples

```
e_charts() |>
  e_gauge(57, "PERCENT")

# timeline
data.frame(time = 2015:2017) |>
  group_by(time) |>
  e_charts(timeline = TRUE) |>
  e_gauge(
    c(57, 23, 65),
    c("percent", "percentage", "cases")
  )
```

e_geo

Geo

Description

Initialise geo.

Usage

```
e_geo(e, map = "world", ..., rm_x = TRUE, rm_y = TRUE)
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
map	Map type.
...	Any other option to pass, check See Also section.
rm_x, rm_y	Whether to remove x and y axis, defaults to TRUE.

See Also

[Additional arguments](#)

Examples

```
flights <- read.csv(
  paste0(
    "https://raw.githubusercontent.com/plotly/datasets/",
    "master/2011_february_aa_flight_paths.csv"
  )
)

flights |>
  e_charts() |>
  e_geo() |>
  e_lines(
    start_lon,
    start_lat,
    end_lon,
    end_lat,
    name = "flights",
    lineStyle = list(normal = list(curveness = 0.3))
  )
```

e_geo_3d	<i>Geo 3D</i>
----------	---------------

Description

Initialise geo 3D.

Usage

```
e_geo_3d(e, serie, color, type = "world", rm_x = TRUE, rm_y = TRUE, ...)

e_geo_3d_(
  e,
  serie = NULL,
  color = NULL,
  type = "world",
  rm_x = TRUE,
  rm_y = TRUE,
  ...
)
```

Arguments

- e An echarts4r object as returned by [e_charts](#) or a proxy as returned by [echarts4rProxy](#).
- serie Column name of serie to plot.
- color Color.
- type Map type.
- rm_x, rm_y Whether to remove x and y axis, defaults to TRUE.
- ... Any other option to pass, check See Also section.

See Also

[e_country_names](#), [Additional arguments](#)

Examples

```
choropleth <- data.frame(
  countries = c(
    "France",
    "Brazil",
    "China",
    "Russia",
    "Canada",
    "India",
    "United States",
    "Argentina",
    "Australia"
```

```

    ),
    height = runif(9, 1, 5),
    color = c(
      "#F7FBFF",
      "#DEEBF7",
      "#C6DBEF",
      "#9ECAE1",
      "#6BAED6",
      "#4292C6",
      "#2171B5",
      "#08519C",
      "#08306B"
    )
  )
)

choropleth |>
  e_charts(countries) |>
  e_geo_3d(height, color)

```

e_get_data

*Get data***Description**

Get data passed to [e_charts](#).

Usage

```
e_get_data(e)
```

Arguments

e An echarts4r object as returned by [e_charts](#) or a proxy as returned by [echarts4rProxy](#).

Value

A list of data.frames, one for each group.

Examples

```

echart <- cars |>
  e_charts(speed) |>
  e_scatter(dist) |>
  e_lm(dist ~ speed)

echart

e_get_data(echart)[[1]]

```

e_get_zr

Blank Area

Description

Use this function to capture a click on a blank area of the canvas. Note that this may stops other "click" events from working.

Usage

```
e_get_zr()
```

e_globe

Globe

Description

Add globe.

Usage

```
e_globe(e, environment = NULL, base_texture = NULL, height_texture = NULL, ...)
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
environment	Texture of background.
base_texture	Base texture of globe.
height_texture	Texture of height.
...	Any other option to pass, check See Also section.

See Also

[e_country_names](#), [Additional arguments](#)

Examples

```
## Not run:
url <- paste0(
  "https://echarts.apache.org/examples/",
  "data-gl/asset/data/population.json"
)
data <- jsonlite::fromJSON(url)
data <- as.data.frame(data)
names(data) <- c("lon", "lat", "value")
```

```

data |>
  e_charts(lon) |>
  e_globe(
    displacementScale = 0.04
  ) |>
  e_bar_3d(lat, value, "globe") |>
  e_visual_map(show = FALSE)

## End(Not run)

```

e_graph

Graph

Description

Create a graph.

Usage

```
e_graph(e, layout = "force", name = NULL, rm_x = TRUE, rm_y = TRUE, ...)
```

```

e_graph_gl(
  e,
  layout = "force",
  name = NULL,
  rm_x = TRUE,
  rm_y = TRUE,
  ...,
  itemStyle = list(opacity = 1)
)

```

```

e_graph_nodes(
  e,
  nodes,
  names,
  value,
  size,
  category,
  symbol = NULL,
  legend = TRUE
)

```

```
e_graph_edges(e, edges, source, target, value, size)
```

Arguments

e	An echarts4 object as returned by e_charts.
layout	Layout, one of force, none or circular.
name	Name of graph.
rm_x, rm_y	Whether to remove the x and y axis, defaults to TRUE.
...	Any other parameter.
itemStyle	This option is available for for GL and canvas graph but is only necessary for GL.
nodes	Data.frame of nodes.
names	Names of nodes, unique.
value	Values of nodes or edges.
size	Sizes of nodes or edges.
category	Group of nodes (i.e.: group membership).
symbol	Symbols of nodes.
legend	Whether to add serie to legend.
edges	Data.frame of edges.
source, target	Column names of source and target.

See Also

[Additional arguments](#), [e_modularity](#)

Examples

```
value <- rnorm(10, 10, 2)

nodes <- data.frame(
  name = sample(LETTERS, 10),
  value = value,
  size = value,
  symbol = sample(c("circle", "rect", "triangle"), 10, replace = TRUE),
  grp = rep(c("grp1", "grp2"), 5),
  stringsAsFactors = FALSE
)

value_edges <- sample(1:100, 20, replace = TRUE)
edges <- data.frame(
  source = sample(nodes$name, 20, replace = TRUE),
  target = sample(nodes$name, 20, replace = TRUE),
  value = value_edges,
  size = ceiling(value_edges/20),
  stringsAsFactors = FALSE
)

e_charts() |>
  e_graph() |>
```

```
e_graph_nodes(nodes, name, value, size, grp, symbol) |>
e_graph_edges(edges, source, target, value, size) |>
e_tooltip()

# Use graphGL for larger networks
nodes <- data.frame(
  name = paste0(LETTERS, 1:1000),
  value = rnorm(1000, 10, 2),
  size = rnorm(1000, 10, 2),
  grp = rep(c("grp1", "grp2"), 500),
  stringsAsFactors = FALSE
)

edges <- data.frame(
  source = sample(nodes$name, 2000, replace = TRUE),
  target = sample(nodes$name, 2000, replace = TRUE),
  stringsAsFactors = FALSE
)

e_charts() |>
e_graph_gl() |>
e_graph_nodes(nodes, name, value, size, grp) |>
e_graph_edges(edges, source, target)
```

e_graphic_g

Graphic

Description

Low level API to define graphic elements.

Usage

```
e_graphic_g(e, ...)

e_group_g(e, ...)

e_image_g(e, ...)

e_text_g(e, ...)

e_rect_g(e, ...)

e_circle_g(e, ...)

e_ring_g(e, ...)

e_sector_g(e, ...)
```

```
e_arc_g(e, ...)
```

```
e_polygon_g(e, ...)
```

```
e_polyline_g(e, ...)
```

```
e_line_g(e, ...)
```

```
e_bezier_curve_g(e, ...)
```

Arguments

e An echarts4r object as returned by [e_charts](#) or a proxy as returned by [echarts4rProxy](#).
... Any other option to pass, check See Also section.

Functions

- `e_graphic_g` to initialise graphics, entirely optional.
- `e_group_g` to create group, the children of which will share attributes.
- `e_image_g` to a png or jpg image.
- `e_text_g` to add text.
- `e_rect_g` to add a rectangle.
- `e_circle_g` to add a circle.
- `e_ring_g` to add a ring.
- `e_sector_g`
- `e_arc_g` to create an arc.
- `e_polygon_g` to create a polygon.
- `e_polyline_g` to create a polyline.
- `e_line_g` to draw a line.
- `e_bezier_curve_g` to draw a quadratic bezier curve or cubic bezier curve.

Note

Some elements, i.e.: `e_image_g` may not display in the RStudio browser but will work fine in your browser, R markdown documents and Shiny applications.

See Also

[official documentation](#)

Examples

```
# may not work in RStudio viewer
# Open in browser
cars |>
  e_charts(speed) |>
  e_scatter(dist) |>
  e_image_g(
    right = 20,
    top = 20,
    z = -999,
    style = list(
      image = "https://www.r-project.org/logo/Rlogo.png",
      width = 150,
      height = 150,
      opacity = .6
    )
  )
```

e_grid

*Grid***Description**

Customise grid.

Usage

```
e_grid(e, index = NULL, ...)
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
index	Index of axis to customise.
...	Any other option to pass, check See Also section.

See Also

[Additional arguments](#)

Examples

```
USArrests |>
  e_charts(UrbanPop) |>
  e_line(Assault, smooth = TRUE) |>
  e_area(Murder, y.index = 1, x.index = 1) |>
  e_y_axis(gridIndex = 1) |>
  e_x_axis(gridIndex = 1) |>
  e_grid(height = "40%") |>
  e_grid(height = "40%", top = "55%")
```

e_grid_3d

*Grid***Description**

Customise grid.

Usage

```
e_grid_3d(e, index = 0, ...)
```

Arguments

e An echarts4r object as returned by [e_charts](#) or a proxy as returned by [echarts4rProxy](#).
index Index of axis to customise.
... Any other option to pass, check See Also section.

See Also

[Additional arguments](#)

Examples

```
# phony data
v <- LETTERS[1:10]
matrix <- data.frame(
  x = sample(v, 300, replace = TRUE),
  y = sample(v, 300, replace = TRUE),
  z1 = rnorm(300, 10, 1),
  z2 = rnorm(300, 10, 1),
  stringsAsFactors = FALSE
) |>
dplyr::group_by(x, y) |>
dplyr::summarise(
  z1 = sum(z1),
  z2 = sum(z2)
) |>
dplyr::ungroup()

trans <- list(opacity = 0.4) # transparency
emphasis <- list(itemStyle = list(color = "#313695"))

matrix |>
e_charts(x) |>
e_bar_3d(y, z1, stack = "stack", name = "Serie 1", itemStyle = trans, emphasis = emphasis) |>
e_bar_3d(y, z2, stack = "stack", name = "Serie 2", itemStyle = trans, emphasis = emphasis) |>
e_grid_3d(splitLine = list(lineStyle = list(color = "blue")))
```

e_heatmap

*Heatmap***Description**

Draw heatmap by coordinates.

Usage

```
e_heatmap(
  e,
  y,
  z,
  bind,
  name = NULL,
  coord_system = "cartesian2d",
  rm_x = TRUE,
  rm_y = TRUE,
  calendar = NULL,
  ...
)

e_heatmap_(
  e,
  y,
  z = NULL,
  bind = NULL,
  name = NULL,
  coord_system = "cartesian2d",
  rm_x = TRUE,
  rm_y = TRUE,
  calendar = NULL,
  ...
)
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
y, z	Coordinates and values.
bind	Binding between datasets, namely for use of e_brush .
name	name of the serie.
coord_system	Coordinate system to plot against, takes cartesian2d, geo or calendar.
rm_x, rm_y	Whether to remove x and y axis, only applies if coord_system is not set to cartesian2d.
calendar	The index of the calendar to plot against.
...	Any other option to pass, check See Also section.

See Also[Additional arguments](#)**Examples**

```

v <- LETTERS[1:10]
matrix <- data.frame(
  x = sample(v, 300, replace = TRUE),
  y = sample(v, 300, replace = TRUE),
  z = rnorm(300, 10, 1),
  stringsAsFactors = FALSE
) |>
  dplyr::group_by(x, y) |>
  dplyr::summarise(z = sum(z)) |>
  dplyr::ungroup()

matrix |>
  e_charts(x) |>
  e_heatmap(y, z, itemStyle = list(emphasis = list(shadowBlur = 10))) |>
  e_visual_map(z)

# calendar
dates <- seq.Date(as.Date("2017-01-01"), as.Date("2018-12-31"), by = "day")
values <- rnorm(length(dates), 20, 6)

year <- data.frame(date = dates, values = values)

year |>
  e_charts(date) |>
  e_calendar(range = "2018") |>
  e_heatmap(values, coord_system = "calendar") |>
  e_visual_map(max = 30)

# calendar multiple years
year |>
  dplyr::mutate(year = format(date, "%Y")) |>
  group_by(year) |>
  e_charts(date) |>
  e_calendar(range = "2017", top = 40) |>
  e_calendar(range = "2018", top = 260) |>
  e_heatmap(values, coord_system = "calendar") |>
  e_visual_map(max = 30)

# map
quakes |>
  e_charts(long) |>
  e_geo(
    boundingCoords = list(
      c(190, -10),
      c(180, -40)
    )
  ) |>

```

```

    e_heatmap(
      lat,
      mag,
      coord_system = "geo",
      blurSize = 5,
      pointSize = 3
    ) |>
    e_visual_map(mag)

# timeline
library(dplyr)

axis <- LETTERS[1:10]
df <- expand.grid(axis, axis)

bind_rows(df, df) |>
  mutate(
    values = runif(n(), 1, 10),
    grp = c(
      rep("A", 100),
      rep("B", 100)
    )
  ) |>
  group_by(grp) |>
  e_charts(Var1, timeline = TRUE) |>
  e_heatmap(Var2, values) |>
  e_visual_map(values)

```

e_hide_grid_lines	' Hide Grid Lines
-------------------	-------------------

Description

A convenience function to easily hide grid lines.

Usage

```
e_hide_grid_lines(e, which = c("x", "y"))
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
which	Which axis grid lines to hide.

Examples

```

cars |>
  e_charts(speed) |>
  e_scatter(dist) |>
  e_hide_grid_lines()

```

e_highlight_p	<i>Highlight & Downplay Proxy</i>
---------------	---------------------------------------

Description

Proxies to highlight and downplay series.

Usage

```
e_highlight_p(proxy, series_index = NULL, series_name = NULL)
```

```
e_downplay_p(proxy, series_index = NULL, series_name = NULL)
```

Arguments

proxy	An echarts4r proxy as returned by echarts4rProxy .
series_index	Series index, can be a vector.
series_name	Series Name, can be vector.

Examples

```
## Not run:
library(shiny)

ui <- fluidPage(
  fluidRow(
    column(
      3,
      actionButton("highlightmpg", "Highlight MPG")
    ),
    column(
      3,
      actionButton("highlighthp", "Highlight HP")
    ),
    column(
      3,
      actionButton("downplaympg", "Downplay MPG")
    ),
    column(
      3,
      actionButton("downplayhp", "Downplay HP")
    )
  ),
  echarts4rOutput("plot")
)

server <- function(input, output, session) {
  output$plot <- renderEcharts4r({
    mtcars |>
```

```

    e_charts(mpg) |>
    e_line(displ) |>
    e_line(hp, name = "HP") # explicitly pass name
  })

  # highlight

  observeEvent(input$highlightmpg, {
    echarts4rProxy("plot") |>
    e_highlight_p(series_index = 0) # using index
  })

  observeEvent(input$highlighthp, {
    echarts4rProxy("plot") |>
    e_highlight_p(series_name = "HP") # using name
  })

  # downplay

  observeEvent(input$downplaympg, {
    echarts4rProxy("plot") |>
    e_downplay_p(series_name = "displ")
  })

  observeEvent(input$downplayhp, {
    echarts4rProxy("plot") |>
    e_downplay_p(series_index = 1)
  })
}

if (interactive()) {
  shinyApp(ui, server)
}

## End(Not run)

```

e_histogram

Histogram & Density

Description

Add a histogram or density plots.

Usage

```

e_histogram(
  e,
  serie,
  breaks = "Sturges",

```

```

    name = NULL,
    legend = TRUE,
    bar_width = "99%",
    x_index = 0,
    y_index = 0,
    ...
)

e_density(
  e,
  serie,
  breaks = "Sturges",
  name = NULL,
  legend = TRUE,
  x_index = 0,
  y_index = 0,
  smooth = TRUE,
  ...
)

e_histogram_(
  e,
  serie,
  breaks = "Sturges",
  name = NULL,
  legend = TRUE,
  bar_width = "90%",
  x_index = 0,
  y_index = 0,
  ...
)

e_density_(
  e,
  serie,
  breaks = "Sturges",
  name = NULL,
  legend = TRUE,
  x_index = 0,
  y_index = 0,
  smooth = TRUE,
  ...
)

```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
serie	Column name of serie to plot.

breaks	Passed to hist .
name	name of the serie.
legend	Whether to add serie to legend.
bar_width	Width of bars.
x_index, y_index	Indexes of x and y axis.
...	Any other option to pass, check See Also section.
smooth	Whether to use smoothed lines, passed to e_line .

See Also

[Additional arguments for histogram](#), [Additional arguments for density](#)

Examples

```
mtcars |>
  e_charts() |>
  e_histogram(mpg, name = "histogram") |>
  e_density(mpg, areaStyle = list(opacity = .4), smooth = TRUE, name = "density", y_index = 1) |>
  e_tooltip(trigger = "axis")

# timeline
mtcars |>
  group_by(cyl) |>
  e_charts(timeline = TRUE) |>
  e_histogram(mpg, name = "histogram") |>
  e_density(mpg, name = "density", y_index = 1)
```

e_inspect	<i>To & From JSON</i>
-----------	---------------------------

Description

Get JSON options from an echarts4r object and build one from JSON.

Usage

```
e_inspect(e, json = FALSE, ...)
```

```
echarts_from_json(txt)
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
json	Whether to return the JSON, otherwise returns a list.
...	Additional options to pass to toJSON .
txt	JSON character string, url, or file.

Details

txt should contain the full list of options required to build a chart. This is subsequently passed to the setOption ECharts (JavaScript) function.

Value

e_inspect Returns a list if json is FALSE and a JSON string otherwise. echarts_from_json returns an object of class echarts4r.

Note

Must be passed as last option.

Examples

```
p <- cars |>
  e_charts(dist) |>
  e_scatter(speed, symbol_size = 10)

p # plot

# extract the JSON
json <- p |>
  e_inspect(
    json = TRUE,
    pretty = TRUE
  )

# print json
json

# rebuild plot
echarts_from_json(json) |>
  e_theme("dark") # modify
```

e_labels

Format labels

Description

Format labels

Usage

```
e_labels(e, show = TRUE, position = "top", ...)
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
show	Set to TRUE to show the labels.
position	Position of labels, see official documentation for the full list of options.
...	Any other options see documentation for other options.

Examples

```
mtcars |>
  e_chart(wt) |>
  e_scatter(qsec, cyl) |>
  e_labels(fontSize = 9)

mtcars |>
  group_by(cyl) |>
  e_chart(wt) |>
  e_scatter(qsec, mpg) |>
  e_labels(fontSize = 9)

# timeline
mtcars |>
  group_by(cyl) |>
  e_chart(wt) |>
  e_scatter(qsec, mpg) |>
  e_labels(fontSize = 9)
```

e_leaflet

Leaflet

Description

Leaflet extension.

Usage

```
e_leaflet(e, roam = TRUE, ...)

e_leaflet_tile(
  e,
  template = "https://{s}.tile.openstreetmap.fr/hot/{z}/{x}/{y}.png",
  options = NULL,
  ...
)
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
roam	Whether to allow the user to roam.
...	Any other option to pass, check See Also section.
template	urlTemplate, should not be changed.
options	List of options, including attribution and label.

Note

Will not render in the RStudio, open in browser.

Examples

```
## Not run:
url <- paste0(
  "https://echarts.apache.org/examples/",
  "data-gl/asset/data/population.json"
)
data <- jsonlite::fromJSON(url)
data <- as.data.frame(data)
names(data) <- c("lon", "lat", "value")
data$value <- log(data$value)

data |>
  e_charts(lon) |>
  e_leaflet() |>
  e_leaflet_tile() |>
  e_scatter(lat, size = value, coord_system = "leaflet")

## End(Not run)
```

e_legend

Legend

Description

Customise the legend.

Usage

```
e_legend(e, show = TRUE, type = c("plain", "scroll"), icons = NULL, ...)
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
show	Set to FALSE to hide the legend.
type	Type of legend, plain or scroll.
icons	A optional list of icons the same length as there are series, see example.
...	Any other option to pass, check See Also section.

See Also

[Additional arguments](#)

Examples

```
e <- cars |>
  e_charts(speed) |>
  e_scatter(dist, symbol_size = 5)

# with legend
e

# without legend
e |>
  e_legend(show = FALSE)

# with icon
# path is taken from http://svgicons.sparkk.fr/
path <- paste0(
  "path://M11.344,5.71c0-0.73,0.074-1.122,1.199-1.122",
  "h1.502V1.871h-2.404c-2.886,0-3.903,1.36-3.903,3.646",
  "v1.765h-1.8V10h1.8v8.128h3.601V10h2.403l0.32-2.718h",
  "-2.724L11.344,5.71z"
)

e |>
  e_legend(
    icons = list(path)
  )
```

e_line

Line

Description

Add line serie.

Usage

```
e_line(
  e,
  serie,
  bind,
  name = NULL,
  legend = TRUE,
  y_index = 0,
  x_index = 0,
  coord_system = "cartesian2d",
  ...
)

e_line_(
  e,
  serie,
  bind = NULL,
  name = NULL,
  legend = TRUE,
  y_index = 0,
  x_index = 0,
  coord_system = "cartesian2d",
  ...
)
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
serie	Column name of serie to plot.
bind	Binding between datasets, namely for use of e_brush .
name	name of the serie.
legend	Whether to add serie to legend.
x_index, y_index	Indexes of x and y axis.
coord_system	Coordinate system to plot against.
...	Any other option to pass, check See Also section.

See Also

[Additional arguments](#)

Examples

```
iris |>
  group_by(Species) |>
  e_charts(Sepal.Length) |>
  e_line(Sepal.Width) |>
```

```
e_tooltip(trigger = "axis")

# timeline
iris |>
  group_by(Species) |>
  e_charts(Sepal.Length, timeline = TRUE) |>
  e_line(Sepal.Width) |>
  e_tooltip(trigger = "axis")
```

e_lines

Lines

Description

Add lines.

Usage

```
e_lines(
  e,
  source_lon,
  source_lat,
  target_lon,
  target_lat,
  source_name,
  target_name,
  value,
  coord_system = "geo",
  name = NULL,
  rm_x = TRUE,
  rm_y = TRUE,
  ...
)
```

```
e_lines_(
  e,
  source_lon,
  source_lat,
  target_lon,
  target_lat,
  source_name = NULL,
  target_name = NULL,
  value = NULL,
  coord_system = "geo",
  name = NULL,
  rm_x = TRUE,
  rm_y = TRUE,
  ...
)
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
source_lon, source_lat, target_lon, target_lat	coordinates.
source_name, target_name	Names of source and target.
value	Value of edges.
coord_system	Coordinate system to use, one of geo, or cartesian2d.
name	name of the serie.
rm_x, rm_y	Whether to remove x and y axis, defaults to TRUE.
...	Any other option to pass, check See Also section.

See Also

[Additional arguments](#)

Examples

```

flights <- read.csv(
  paste0(
    "https://raw.githubusercontent.com/plotly/datasets/",
    "master/2011_february_aa_flight_paths.csv"
  )
)

flights |>
  e_charts() |>
  e_geo() |>
  e_lines(
    start_lon,
    start_lat,
    end_lon,
    end_lat,
    airport1,
    airport2,
    cnt,
    name = "flights",
    lineStyle = list(normal = list(curveness = 0.3))
  ) |>
  e_tooltip(
    trigger = "item",
    formatter = htmlwidgets::JS("
      function(params){
        return(
          params.seriesName + '<br />' +
          params.data.source_name + ' -> ' +
          params.data.target_name + ':' + params.value
        )
      }
    ")
  )

```

```
    ")
  )

# timeline
flights$grp <- rep(LETTERS[1:2], 89)

flights |>
  group_by(grp) |>
  e_charts(timeline = TRUE) |>
  e_geo() |>
  e_lines(
    start_lon,
    start_lat,
    end_lon,
    end_lat,
    cnt,
    coord_system = "geo"
  )
```

e_lines_3d

Lines 3D

Description

Add 3D lines.

Usage

```
e_lines_3d(
  e,
  source_lon,
  source_lat,
  target_lon,
  target_lat,
  source_name,
  target_name,
  value,
  name = NULL,
  coord_system = "globe",
  rm_x = TRUE,
  rm_y = TRUE,
  ...
)

e_line_3d(
  e,
  y,
  z,
```

```

    name = NULL,
    coord_system = NULL,
    rm_x = TRUE,
    rm_y = TRUE,
    ...
)

e_lines_3d(
  e,
  source_lon,
  source_lat,
  target_lon,
  target_lat,
  source_name = NULL,
  target_name = NULL,
  value = NULL,
  name = NULL,
  coord_system = "globe",
  rm_x = TRUE,
  rm_y = TRUE,
  ...
)

e_line_3d(
  e,
  y,
  z,
  name = NULL,
  coord_system = NULL,
  rm_x = TRUE,
  rm_y = TRUE,
  ...
)

```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
source_lon, source_lat, target_lon, target_lat	coordinates.
source_name, target_name	Names of source and target.
value	Value of edges.
name	name of the serie.
coord_system	Coordinate system to use, such as cartesian3D, or globe.
rm_x, rm_y	Whether to remove x and y axis, defaults to TRUE.
...	Any other option to pass, check See Also section.
y, z	Coordinates of lines.

See Also

Additional arguments for lines 3D, Additional arguments for line 3D

<https://echarts4r-assets.john-coene.com>

Examples

```
# get data
flights <- read.csv(
  paste0(
    "https://raw.githubusercontent.com/plotly/datasets/",
    "master/2011_february_aa_flight_paths.csv"
  )
)

# Lines 3D
# Globe
# get tetures: echarts4r-assets.john-coene.com
flights |>
  e_charts() |>
  e_globe(
    displacementScale = 0.05
  ) |>
  e_lines_3d(
    start_lon,
    start_lat,
    end_lon,
    end_lat,
    name = "flights",
    effect = list(show = TRUE)
  ) |>
  e_legend(FALSE)

# Geo 3D
flights |>
  e_charts() |>
  e_geo_3d() |>
  e_lines_3d(
    start_lon,
    start_lat,
    end_lon,
    end_lat,
    coord_system = "geo3D"
  )

# groups
flights$grp <- rep(LETTERS[1:2], 89)

flights |>
  group_by(grp) |>
  e_charts() |>
  e_geo_3d() |>
  e_lines_3d(
```

```

      start_lon,
      start_lat,
      end_lon,
      end_lat,
      coord_system = "geo3D"
    )

# line 3D
df <- data.frame(
  x = 1:100,
  y = runif(100, 10, 25),
  z = rnorm(100, 100, 50)
)

df |>
  e_charts(x) |>
  e_line_3d(y, z) |>
  e_visual_map() |>
  e_title("nonsense")

# timeline
df$grp <- rep(LETTERS[1:5], 20)

df |>
  group_by(grp) |>
  e_charts(x) |>
  e_line_3d(y, z) |>
  e_visual_map() |>
  e_title("nonsense")

```

e_lines_gl

Lines WebGL

Description

Draw WebGL lines.

Usage

```
e_lines_gl(e, data, coord_system = "geo", ...)
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
data	A list.
coord_system	Coordinate system to plot against.
...	Any other options (this series type is mostly undocumented).

`e_liquid`*Liquid fill*

Description

Draw liquid fill.

Usage

```
e_liquid(e, serie, color, rm_x = TRUE, rm_y = TRUE, ...)
```

```
e_liquid_(e, serie, color = NULL, rm_x = TRUE, rm_y = TRUE, ...)
```

Arguments

<code>e</code>	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
<code>serie</code>	Column name of serie to plot.
<code>color</code>	Color to plot.
<code>rm_x, rm_y</code>	Whether to remove x and y axis, defaults to TRUE.
<code>...</code>	Any other option to pass, check See Also section.

See Also

[official documentation](#)

Examples

```
df <- data.frame(val = c(0.6, 0.5, 0.4))

df |>
  e_charts() |>
  e_liquid(val) |>
  e_theme("dark")
```

`e_list`*List*

Description

simply pass a list of options, similar to a JSON.

Usage

```
e_list(e, list, append = FALSE)
```

Arguments

- e An echarts4r object as returned by [e_charts](#) or a proxy as returned by [echarts4rProxy](#).
- list A list of options passed to setOptions.
- append if TRUE the list is appended to the options, otherwise it *overwrites* everything.

Examples

```

N <- 20 # data points

opts <- list(
  xAxis = list(
    type = "category",
    data = LETTERS[1:N]
  ),
  yAxis = list(
    type = "value"
  ),
  series = list(
    list(
      type = "line",
      data = round(runif(N, 5, 20))
    )
  )
)

e_charts() |>
  e_list(opts)

```

e_lm

Smooth

Description

Plot formulas.

Usage

```

e_lm(
  e,
  formula,
  name = NULL,
  legend = TRUE,
  symbol = "none",
  smooth = TRUE,
  model_args = list(),
  ...
)

```

```

e_glm(
  e,
  formula,
  name = NULL,
  legend = TRUE,
  symbol = "none",
  smooth = TRUE,
  model_args = list(),
  ...
)

e_loess(
  e,
  formula,
  name = NULL,
  legend = TRUE,
  symbol = "none",
  smooth = TRUE,
  x_index = 0,
  y_index = 0,
  model_args = list(),
  ...
)

```

Arguments

<code>e</code>	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
<code>formula</code>	formula to pass to lm .
<code>name</code>	name of the serie.
<code>legend</code>	Whether to add serie to legend.
<code>symbol</code>	Symbol to use in e_line .
<code>smooth</code>	Whether to smooth the line.
<code>model_args</code>	Arguments to pass to the underlying model.
<code>...</code>	Additional arguments to pass to e_line .
<code>x_index, y_index</code>	Indexes of x and y axis.

Examples

```

iris |>
  group_by(Species) |>
  e_charts(Sepal.Length) |>
  e_scatter(Sepal.Width) |>
  e_lm(Sepal.Width ~ Sepal.Length) |>
  e_x_axis(min = 4)

mtcars |>

```

```
e_charts(displ) |>
e_scatter(mpg, qsec) |>
e_loess(mpg ~ displ, smooth = TRUE, showSymbol = FALSE)

# timeline
iris |>
  group_by(Species) |>
  e_charts(Sepal.Length, timeline = TRUE) |>
  e_scatter(Sepal.Width) |>
  e_lm(Sepal.Width ~ Sepal.Length) |>
  e_x_axis(min = 4, max = 8) |>
  e_y_axis(max = 5)
```

e_locale	<i>Locale</i>
----------	---------------

Description

Change the locale to auto-translate days of the week, etc.

Usage

```
e_locale(e, locale)

e_locale_manual(e, locale, path)
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
locale	Locale to set to.
path	Path to the local file to use.

Details

The "manual" function expects a file to use for translations. You can browse the '.js' files [\[here\]](https://github.com/apache/echarts4r) to have an idea of what they should look like.

Locales

- CS - DE - EN - ES - FI - FR - JA - PT (brazil) - SI - TH - ZH

Examples

```
# top right corner zoom is in
# French
cars |>
  e_charts(speed) |>
  e_scatter(dist) |>
  e_datazoom() |>
```

```
e_locale("FR")
```

e_map

Choropleth

Description

Draw maps.

Usage

```
e_map(e, serie, map = "world", name = NULL, rm_x = TRUE, rm_y = TRUE, ...)
```

```
e_map_(  
  e,  
  serie = NULL,  
  map = "world",  
  name = NULL,  
  rm_x = TRUE,  
  rm_y = TRUE,  
  ...  
)
```

```
e_svg(e, serie, map = "world", name = NULL, rm_x = TRUE, rm_y = TRUE, ...)
```

```
e_svg_(  
  e,  
  serie = NULL,  
  map = "world",  
  name = NULL,  
  rm_x = TRUE,  
  rm_y = TRUE,  
  ...  
)
```

```
e_map_3d(  
  e,  
  serie,  
  map = "world",  
  name = NULL,  
  coord_system = NULL,  
  rm_x = TRUE,  
  rm_y = TRUE,  
  ...  
)
```

```

e_map_3d_(
  e,
  serie = NULL,
  map = "world",
  name = NULL,
  coord_system = NULL,
  rm_x = TRUE,
  rm_y = TRUE,
  ...
)

e_map_3d_custom(
  e,
  id,
  value,
  height,
  map = NULL,
  name = NULL,
  rm_x = TRUE,
  rm_y = TRUE,
  ...
)

```

Arguments

<code>e</code>	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
<code>serie</code>	Values to plot.
<code>map</code>	Map type.
<code>name</code>	name of the serie.
<code>rm_x, rm_y</code>	Whether to remove x and y axis, defaults to TRUE.
<code>...</code>	Any other option to pass, check See Also section.
<code>coord_system</code>	Coordinate system to use, one of cartesian3D, geo3D, globe.
<code>id, value, height</code>	Columns corresponding to registered map.

See Also

[e_country_names](#), [Additional map arguments](#), [Additional map 3D arguments](#)

Examples

```

## Not run:
choropleth <- data.frame(
  countries = c(
    "France",
    "Brazil",
    "China",
    "Russia",

```

```

      "Canada",
      "India",
      "United States",
      "Argentina",
      "Australia"
    ),
    values = round(runif(9, 10, 25))
  )

choropleth |>
  e_charts(countries) |>
  e_map(values) |>
  e_visual_map(min = 10, max = 25)

choropleth |>
  e_charts(countries) |>
  e_map_3d(values, shading = "lambert") |>
  e_visual_map(min = 10, max = 30)

# custom
buildings <- jsonlite::read_json(
  paste0(
    "https://echarts.apache.org/examples/",
    "data-gl/asset/data/buildings.json"
  )
)

heights <- purrr::map(buildings$features, "properties") |>
  purrr::map("height") |>
  unlist()

names <- purrr::map(buildings$features, "properties") |>
  purrr::map("name") |>
  unlist()

data <- dplyr::tibble(
  name = names,
  value = round(runif(length(names), 0, 1), 6),
  height = heights / 10
)

data |>
  e_charts() |>
  e_map_register("buildings", buildings) |>
  e_map_3d_custom(name, value, height) |>
  e_visual_map(
    show = FALSE,
    min = 0.4,
    max = 1
  )

# timeline
choropleth <- data.frame(

```

```

    countries = rep(choropleth$countries, 3)
  ) |>
  dplyr::mutate(
    grp = c(
      rep(2016, nrow(choropleth)),
      rep(2017, nrow(choropleth)),
      rep(2018, nrow(choropleth))
    ),
    values = runif(27, 1, 10)
  )

choropleth |>
  group_by(grp) |>
  e_charts(countries, timeline = TRUE) |>
  e_map(values) |>
  e_visual_map(min = 1, max = 10)

choropleth |>
  group_by(grp) |>
  e_charts(countries, timeline = TRUE) |>
  e_map_3d(values) |>
  e_visual_map(min = 1, max = 10)

## End(Not run)

```

e_map_register

Register map

Description

Register a **geojson** map.

Usage

```

e_map_register(e, name, json, ...)

e_svg_register(e, name, svg)

e_map_register_p(
  name,
  json,
  async = FALSE,
  session = shiny::getDefaultReactiveDomain()
)

e_map_register_ui(name, json, async = FALSE)

```

Arguments

e	An echarts4r object as returned by <code>e_charts</code> .
name	Name of map, to use in <code>e_map</code> .
json, svg	Geojson , or SVG.
...	Additional options passed to registerMap .
async	Whether to read the file asynchronously.
session	A valid Shiny session.

Details

`e_map_register_p` is not truly a proxy as it does not require a chart to function. While the function `e_map_register_ui` is meant to register the map globally in the Shiny UI, not that then `json` must be accessible from the UI (generally `www` folder).

Examples

```
## Not run:
json <- jsonlite::read_json("https://echarts.apache.org/examples/data/asset/geo/USA.json")

USArrests |>
  tibble::rownames_to_column("states") |>
  e_charts(states) |>
  e_map_register("USA", json) |>
  e_map(Murder, map = "USA") |>
  e_visual_map(Murder)

## End(Not run)
```

e_mark_p

Mark

Description

Mark points, lines, and areas with a proxy (`[echarts4rProxy()]`).

Usage

```
e_mark_p(e, type, serie_index, data, ...)
```

```
e_mark_p(e, type, serie_index, data = NULL, ...)
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
type	Type of mark: 'point', 'line' or 'area', defaults to 'point'.
serie_index	Single index of serie to mark on, defaults to 1. Proxy doesn't know series' names, so it only uses index.
data	Location of point, line or area, defaults to NULL.
...	Any other option to pass, check See Also section.

Details

Allows the three type of marks to work with [echarts4rProxy()]

Examples

```
library(shiny)
library(dplyr)

ui <- fluidPage(
  fluidRow(
    column(3, actionButton("pxy", "Marks")),
    column(
      3,
      checkboxInput("tln", "Timeline", value = FALSE)
    )
  ),
  echarts4rOutput("plot")
)

server <- function(input, output) {
  data(EuStockMarkets)

  bb <- as.data.frame(EuStockMarkets) |>
    slice_head(n = 150) |>
    mutate(day = 1:n())

  output$plot <- renderEcharts4r({
    react()
  })

  observeEvent(input$pxy, {
    echarts4rProxy("plot", data = NULL) |>
      e_mark_p(
        type = "line",
        serie_index = 1,
        data = list(type = "average"),
        lineStyle = list(type = "dashed", color = "cyan")
      ) |>
      e_mark_p(
        serie_index = 2,
        data = list(
```

```

      xAxis = bb$day[60],
      yAxis = bb$SMI[60],
      value = "pnt"
    )
  ) |>
  e_mark_p(
    type = "line",
    serie_index = 2,
    data = list(
      list(xAxis = bb$day[10], yAxis = bb$SMI[10]),
      list(xAxis = bb$day[37], yAxis = bb$SMI[37])
    ),
    lineStyle = list(type = "solid", color = "yellow")
  ) |>
  e_mark_p(
    type = "area",
    serie_index = 1,
    data = list(
      list(xAxis = bb$day[95]),
      list(xAxis = bb$day[105])
    ),
    itemStyle = list(color = "lightblue"),
    label = list(formatter = "X-area", position = "middle")
  ) |>
  e_merge()
}))

react <- eventReactive(input$tln, {
  tmp <- bb
  if (input$tln) tmp <- tmp |> group_by(day < 75)

  tmp |>
  e_charts(
    day,
    backgroundColor = "#181818",
    legend = list(textStyle = list(color = "#aaa")),
    timeline = input$tln
  ) |>
  e_y_axis(scale = TRUE, axisLabel = list(color = "#aaa")) |>
  e_line(CAC, symbol = "none", color = "#ff33b8") |>
  e_line(SMI, symbol = "none", color = "green")
}))
}
if (interactive()) {
  shinyApp(ui, server)
}

```

Description

Mark points and lines.

Usage

```
e_mark_point(
  e,
  serie = NULL,
  data = NULL,
  ...,
  title = NULL,
  title_position = NULL
)
```

```
e_mark_line(
  e,
  serie = NULL,
  data = NULL,
  ...,
  title = NULL,
  title_position = NULL
)
```

```
e_mark_area(
  e,
  serie = NULL,
  data = NULL,
  ...,
  title = NULL,
  title_position = NULL
)
```

Arguments

<code>e</code>	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
<code>serie</code>	Serie or vector of series to mark on, defaults to all series.
<code>data</code>	Placement of point, line or area.
<code>...</code>	Any other option to pass, check See Also section.
<code>title</code>	A convenience argument to easily set label, see details.
<code>title_position</code>	Position of title.

Details

To set a label you need to either use the `title` argument or pass a list specifying the label formatter. `label = list(formatter = "label")`. The former is more convenient but more limited, e.g.: you cannot specify the placement of the label. When the `e_mark` series function is used with `e_timeline` at the same time, if the number of marks provided does not match the series, the mark information will follow the setting of the previous frame.

See Also

[Additional point arguments](#), [Additional line arguments](#)

Examples

```
max <- list(
  name = "Max",
  type = "max"
)

min <- list(
  name = "Min",
  type = "min"
)

avg <- list(
  type = "average",
  name = "AVG"
)

mtcars |>
  e_charts(mpg) |>
  e_line(wt) |>
  e_line(drat) |>
  e_line(cyl) |>
  e_mark_point("wt", data = max) |>
  e_mark_point(c("cyl", "drat"), data = min) |>
  e_mark_line(data = avg) |> # applies to all
  e_mark_area(
    serie = "wt",
    data = list(
      list(xAxis = "min", yAxis = "min"),
      list(xAxis = "max", yAxis = "max")
    )
  )

# Serie options, since the mark of "virginica" is not set, the mark setting
# of the previous frame is used
iris |>
  group_by(Species) |>
  e_charts(Sepal.Length, timeline = TRUE) |>
  e_line(Sepal.Width) |>
  e_timeline_serie(
    title = list(
      list(text = "setosa"),
      list(text = "versicolor"),
      list(text = "virginica")
    )
  ) |>
  e_mark_area(
    serie = "setosa",
    data = list(
```

```
        list(xAxis = 4, yAxis = 2),
        list(xAxis = 6, yAxis = 4.5)
    ),
    itemStyle = list(color = "lightgreen")
) |>
e_mark_area(
  serie = "versicolor",
  data = list(
    list(xAxis = 4.5),
    list(xAxis = 7)
  ),
  itemStyle = list(color = "lightblue")
)
```

e_merge	Merge options in chart, used in e_mark
---------	--

Description

Merge options in chart, used in e_mark

Usage

```
e_merge(proxy)
```

Arguments

proxy An echarts4r proxy as returned by [echarts4rProxy](#).

e_modularity	Modularity
--------------	------------

Description

Graph modularity extension will do community detection and partian a graph’s vertices in several subsets. Each subset will be assigned a different color.

Usage

```
e_modularity(e, modularity = TRUE)
```

Arguments

e An echarts4r object as returned by [e_charts](#) or a proxy as returned by [echarts4rProxy](#).
modularity Either set to TRUE, or a list.

Modularity

- resolution Resolution
- sort Whether to sort to communities

Note

Does not work in RStudio viewer, open in browser.

See Also

[Official documentation](#)

Examples

```
nodes <- data.frame(
  name = paste0(LETTERS, 1:100),
  value = rnorm(100, 10, 2),
  stringsAsFactors = FALSE
)

edges <- data.frame(
  source = sample(nodes$name, 200, replace = TRUE),
  target = sample(nodes$name, 200, replace = TRUE),
  stringsAsFactors = FALSE
)

e_charts() |>
  e_graph() |>
  e_graph_nodes(nodes, name, value) |>
  e_graph_edges(edges, source, target) |>
  e_modularity(
    list(
      resolution = 5,
      sort = TRUE
    )
  )
```

e_morph

Morphing

Description

__This is experimental__

Usage

```
e_morph(e, ..., callback, default = 1L)
```

Arguments

e, ...	Graphs (from 'e_graph').
callback	JavaScript callback function as a character string (vector of length 1). This function has access to the 'chart' object, as well as 'opts' an array containing the options of the charts passed to 'e' and '...'.
default	Default chart to show.

Details

Morph between graphs.

Examples

```
mtcars2 <- mtcars |>
  head() |>
  tibble::rownames_to_column("model")

e1 <- mtcars2 |>
  e_charts(model) |>
  e_bar(
    carb,
    universalTransition = TRUE,
    animationDurationUpdate = 1000L
  )

e2 <- mtcars2 |>
  e_charts(model) |>
  e_pie(
    carb,
    universalTransition = TRUE,
    animationDurationUpdate = 1000L
  )

cb <- "()" => {
  let x = 0;
  setInterval(() => {
    x++
    chart.setOption(opts[x % 2], true);
  }, 3000);
}"

e_morph(e1, e2, callback = cb)
```

Description

Draw parallel coordinates.

Usage

```
e_parallel(e, ..., name = NULL, rm_x = TRUE, rm_y = TRUE, opts = list())  
  
e_parallel_(e, ..., name = NULL, rm_x = TRUE, rm_y = TRUE, opts = list())
```

Arguments

- e An echarts4r object as returned by [e_charts](#) or a proxy as returned by [echarts4rProxy](#).
- ... Columns to select from the data passed to [e_charts](#).
- name name of the serie.
- rm_x, rm_y Whether to remove x and y axis, defaults to TRUE.
- opts A list of additional options to pass to the serie.

See Also

[Additional arguments](#)

Examples

```
df <- data.frame(  
  price = rnorm(5, 10),  
  amount = rnorm(5, 15),  
  letter = LETTERS[1:5]  
)  
  
df |>  
  e_charts() |>  
  e_parallel(price, amount, letter, opts = list(smooth = TRUE))
```

e_pictorial	<i>Pictorial</i>
-------------	------------------

Description

Pictorial bar chart is a type of bar chart that custimized glyph (like images, SVG PathData) can be used instead of rectangular bar.

Usage

```

e_pictorial(
  e,
  serie,
  symbol,
  bind,
  name = NULL,
  legend = TRUE,
  y_index = 0,
  x_index = 0,
  ...
)

e_pictorial_(
  e,
  serie,
  symbol,
  bind = NULL,
  name = NULL,
  legend = TRUE,
  y_index = 0,
  x_index = 0,
  ...
)

```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
serie	Column name of serie to plot.
symbol	Symbol to plot.
bind	Binding between datasets, namely for use of e_brush .
name	name of the serie.
legend	Whether to add serie to legend.
x_index, y_index	Indexes of x and y axis.
...	Any other option to pass, check See Also section.

Symbols

- Built-in circle, rect, roundRect, triangle, diamond, pin, arrow.
- SVG Path
- Images Path to image, don't forget to precede it with `image://`, see examples.

See Also

[Additional arguments](#)

Examples

```

# built-in symbols
y <- rnorm(10, 10, 2)
df <- data.frame(
  x = 1:10,
  y = y,
  z = y - rnorm(10, 5, 1)
)

df |>
  e_charts(x) |>
  e_bar(z, barWidth = 10) |>
  e_pictorial(
    y,
    symbol = "rect",
    symbolRepeat = TRUE,
    z = -1,
    symbolSize = c(10, 4)
  ) |>
  e_theme("westeros")

# svg path
path <- "path://M0,10 L10,10 C5.5,10 5.5,5 5,0 C4.5,5 4.5,10 0,10 z"

style <- list(
  normal = list(opacity = 0.5),
  # normal
  emphasis = list(opacity = 1) # on hover
)

df |>
  e_charts(x) |>
  e_pictorial(
    y,
    symbol = path,
    barCategoryGap = "-130%",
    itemStyle = style
  )

# image
# might not work in RStudio viewer
# open in browser
qomo <- paste0(
  "https://ecomfe.github.io/echarts-examples/public/",
  "data/asset/img/hill-Qomolangma.png"
)

kili <- paste0(
  "https://ecomfe.github.io/echarts-examples/public/",
  "data/asset/img/hill-Kilimanjaro.png"
)

```

```

data <- data.frame(
  x = c("Qomolangma", "Kilimanjaro"),
  value = c(8844, 5895),
  symbol = c(
    paste0("image://", qomo),
    paste0("image://", kili)
  )
)

data |>
  e_charts(x) |>
  e_pictorial(value, symbol) |>
  e_legend(FALSE)

# timeline
df <- data.frame(
  x = rep(1:5, 2),
  y = runif(10, 1, 10),
  year = c(
    rep(2017, 5),
    rep(2018, 5)
  )
)

df |>
  group_by(year) |>
  e_charts(x, timeline = TRUE) |>
  e_pictorial(
    y,
    symbol = "rect",
    symbolRepeat = TRUE,
    z = -1,
    symbolSize = c(10, 4)
  )

```

e_pie

Pie

Description

Draw pie and donut charts.

Usage

```
e_pie(e, serie, name = NULL, legend = TRUE, rm_x = TRUE, rm_y = TRUE, ...)
```

```
e_pie_(e, serie, name = NULL, legend = TRUE, rm_x = TRUE, rm_y = TRUE, ...)
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
serie	Column name of serie to plot.
name	name of the serie.
legend	Whether to add serie to legend.
rm_x, rm_y	Whether to remove x and y axis, defaults to TRUE.
...	Any other option to pass, check See Also section.

See Also

[Additional arguments](#)

Examples

```
mtcars |>
  head() |>
  tibble::rownames_to_column("model") |>
  e_charts(model) |>
  e_pie(carb)

# timeline
df <- data.frame(
  grp = c("A", "A", "A", "B", "B", "B"),
  labels = rep(LETTERS[1:3], 2),
  values = runif(6, 1, 5)
)

df |>
  group_by(grp) |>
  e_charts(labels, timeline = TRUE) |>
  e_pie(values)
```

e_polar	<i>Polar</i>
---------	--------------

Description

Customise polar coordinates.

Usage

```
e_polar(e, show = TRUE, ...)
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
show	Whether to display the axis.
...	Any other option to pass, check See Also section.

See Also

[Additional arguments](#)

Examples

```
df <- data.frame(x = 1:10, y = seq(1, 20, by = 2))

df |>
  e_charts(x) |>
  e_polar() |>
  e_angle_axis() |>
  e_radius_axis() |>
  e_line(y, coord.system = "polar", smooth = TRUE)
```

e_radar	<i>Radar</i>
---------	--------------

Description

Add a radar chart

Usage

```
e_radar(
  e,
  serie,
  max = 100,
  name = NULL,
  legend = TRUE,
  rm_x = TRUE,
  rm_y = TRUE,
  ...,
  radar = list()
)

e_radar_(
  e,
  serie,
  max = 100,
  name = NULL,
  legend = TRUE,
  rm_x = TRUE,
  rm_y = TRUE,
  ...,
  radar = list()
)
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
serie	Column name of serie to plot.
max	Maximum value.
name	name of the serie.
legend	Whether to add serie to legend.
rm_x, rm_y	Whether to remove x and y axis, defaults to TRUE.
...	Any other option to pass, check See Also section.
radar	A list of options to pass to the radar rather than the serie, see official documentation alternatively, use the e_radar_opts .

Examples

```
df <- data.frame(
  x = LETTERS[1:5],
  y = runif(5, 1, 5),
  z = runif(5, 3, 7)
)

df |>
  e_charts(x) |>
  e_radar(y, max = 7) |>
  e_radar(z) |>
  e_tooltip(trigger = "item")
```

e_radar_opts	<i>Radar axis</i>
--------------	-------------------

Description

Radar axis setup and options.

Usage

```
e_radar_opts(e, index = 0, ...)
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
index	Index of axis to customise.
...	Any other option to pass, check See Also section.

Examples

```
df <- data.frame(
  x = LETTERS[1:5],
  y = runif(5, 1, 5),
  z = runif(5, 3, 7)
)

df |>
  e_charts(x) |>
  e_radar(y, max = 7) |>
  e_radar(z) |>
  e_radar_opts(center = c("25%", "25%")) |>
  e_tooltip(trigger = "item")
```

e_remove

*Remove Serie***Description**

Remove a serie by name or precising its index.

Usage

```
e_remove_serie_p(proxy, serie_name = NULL, serie_index = NULL)
```

```
e_remove_serie(proxy, serie_name = NULL, serie_index = NULL)
```

Arguments

proxy	An echarts4r proxy as returned by echarts4rProxy .
serie_name	Name of serie to remove.
serie_index	Index of serie to append to (starts from 0).

Examples

```
library(shiny)

ui <- fluidPage(
  actionButton("rm", "Remove z serie"),
  echarts4rOutput("plot")
)

server <- function(input, output, session) {
  data <- data.frame(
    x = rnorm(10, 5, 3),
    y = rnorm(10, 50, 12),
    z = rnorm(10, 50, 5)
  )
```

```
output$plot <- renderEcharts4r({
  data |>
    e_charts(x) |>
    e_scatter(y) |>
    e_scatter(z)
})

observeEvent(input$rm, {
  echarts4rProxy("plot") |>
    e_remove_serie_p(serie_name = "z")
})
}
## Not run:
shinyApp(ui, server)

## End(Not run)
```

e_resize	<i>Resize</i>
----------	---------------

Description

Force resize the chart.

Usage

```
e_resize(proxy)
```

Arguments

proxy An echarts4r proxy as returned by [echarts4rProxy](#).

e_restore	<i>Restore Toolbox</i>
-----------	------------------------

Description

Restore Toolbox.

Usage

```
e_restore(e, btn = NULL)
```

Arguments

- e An echarts4r object as returned by [e_charts](#) or a proxy as returned by [echarts4rProxy](#).
- btn A [e_button](#) id.

Examples

```
cars |>
  e_charts(speed) |>
  e_scatter(dist) |>
  e_datazoom() |>
  e_restore("btn") |>
  e_button("btn", "Reset")
```

e_river	<i>River</i>
---------	--------------

Description

Build a theme river.

Usage

```
e_river(e, serie, name = NULL, legend = TRUE, rm_x = TRUE, rm_y = TRUE, ...)
e_river_(e, serie, name = NULL, legend = TRUE, rm_x = TRUE, rm_y = TRUE, ...)
```

Arguments

- e An echarts4r object as returned by [e_charts](#) or a proxy as returned by [echarts4rProxy](#).
- serie Column name of serie to plot.
- name name of the serie.
- legend Whether to add serie to legend.
- rm_x, rm_y Whether to remove x and y axis, defaults to TRUE.
- ... Any other option to pass, check See Also section.

See Also

[Additional arguments](#)

Examples

```
dates <- seq.Date(Sys.Date() - 30, Sys.Date(), by = "day")
grps <- lapply(LETTERS[1:3], rep, 31) |> unlist()

df <- data.frame(
  dates = rep(dates, 3),
  groups = grps,
  values = runif(length(grps), 1, 50)
)

df |>
  group_by(groups) |>
  e_charts(dates) |>
  e_river(values) |>
  e_tooltip(trigger = "axis")
```

e_sankey

Sankey

Description

Draw a sankey diagram.

Usage

```
e_sankey(
  e,
  source,
  target,
  value,
  layout = "none",
  rm_x = TRUE,
  rm_y = TRUE,
  ...
)

e_sankey_(
  e,
  source,
  target,
  value,
  layout = "none",
  rm_x = TRUE,
  rm_y = TRUE,
  ...
)
```

Arguments

<code>e</code>	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
<code>source, target</code>	Source and target columns.
<code>value</code>	Value change from source to target.
<code>layout</code>	Layout of sankey.
<code>rm_x, rm_y</code>	Whether to remove the x and y axis, defaults to TRUE.
<code>...</code>	Any other option to pass, check See Also section.

See Also

[Additional arguments](#)

Examples

```
sankey <- data.frame(
  source = c("a", "b", "c", "d", "c"),
  target = c("b", "c", "d", "e", "e"),
  value = ceiling(rnorm(5, 10, 1)),
  stringsAsFactors = FALSE
)

sankey |>
  e_charts() |>
  e_sankey(source, target, value)
```

<code>e_scatter</code>	<i>Scatter</i>
------------------------	----------------

Description

Add scatter serie.

Usage

```
e_scatter(
  e,
  serie,
  size,
  bind,
  symbol = NULL,
  symbol_size = 1,
  scale = e_scale,
  scale_js = "function(data){ return data[3];}",
  name = NULL,
  coord_system = "cartesian2d",
  jitter_factor = 0,
```

```
jitter_amount = NULL,
legend = TRUE,
y_index = 0,
x_index = 0,
rm_x = TRUE,
rm_y = TRUE,
...
)

e_effect_scatter(
  e,
  serie,
  size,
  bind,
  symbol = NULL,
  symbol_size = 1,
  scale = e_scale,
  scale_js = "function(data){ return data[3];}",
  name = NULL,
  coord_system = "cartesian2d",
  legend = TRUE,
  y_index = 0,
  x_index = 0,
  rm_x = TRUE,
  rm_y = TRUE,
  ...
)

e_scale(x)

e_scatter_(
  e,
  serie,
  size = NULL,
  bind = NULL,
  symbol = NULL,
  symbol_size = 1,
  scale = e_scale,
  scale_js = "function(data){ return data[3];}",
  name = NULL,
  coord_system = "cartesian2d",
  jitter_factor = 0,
  jitter_amount = NULL,
  legend = TRUE,
  y_index = 0,
  x_index = 0,
  rm_x = TRUE,
  rm_y = TRUE,
```

```

    ...
  )

  e_effect_scatter_(
    e,
    serie,
    size = NULL,
    bind = NULL,
    symbol = NULL,
    symbol_size = 1,
    scale = e_scale,
    scale_js = "function(data){ return data[3];}",
    name = NULL,
    coord_system = "cartesian2d",
    legend = TRUE,
    y_index = 0,
    x_index = 0,
    rm_x = TRUE,
    rm_y = TRUE,
    ...
  )

```

Arguments

<code>e</code>	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
<code>serie</code>	Column name of serie to plot.
<code>size</code>	Column name containing size of points.
<code>bind</code>	Binding between datasets, namely for use of e_brush .
<code>symbol</code>	The symbol to use, default to NULL, can also be circle, rect, roundRect, triangle, diamond, pin, arrow, or none.
<code>symbol_size</code>	Size of points, either an integer or a vector of length 2, if size is <i>not</i> NULL or missing it is applied as a multiplier to scale.
<code>scale</code>	A function that takes a vector of numeric and returns a vector of numeric of the same length. You can disable the scaling by setting it to NULL.
<code>scale_js</code>	the JavaScript scaling function.
<code>name</code>	name of the serie.
<code>coord_system</code>	Coordinate system to plot against, see examples.
<code>jitter_factor, jitter_amount</code>	Jitter points, passed to jitter.
<code>legend</code>	Whether to add serie to legend.
<code>x_index, y_index</code>	Indexes of x and y axis.
<code>rm_x, rm_y</code>	Whether to remove x and y axis, only applies if coord_system is not set to cartesian2d.
<code>...</code>	Any other option to pass, check See Also section.
<code>x</code>	A vector of integers or numeric.

Scaling function

defaults to `e_scale` which is a basic function that rescales size between 1 and 20 for that makes for decent sized points on the chart.

See Also

[Additional arguments scatter](#), [Additional arguments for effect scatter](#)

Examples

```
# scaling
e_scale(c(1, 1000))

mtcars |>
  e_charts(mpg) |>
  e_scatter(wt, qsec)

# custom function
my_scale <- function(x) scales::rescale(x, to = c(2, 50))

echart <- mtcars |>
  e_charts(mpg) |>
  e_scatter(wt, qsec, scale = my_scale)

echart

# rescale color too
echart |>
  e_visual_map(wt, scale = my_scale)

# or
echart |>
  e_visual_map(min = 2, max = 50)

# disable scaling
mtcars |>
  e_charts(qsec) |>
  e_scatter(wt, mpg, scale = NULL)

# jitter point
mtcars |>
  e_charts(cyl) |>
  e_scatter(wt, symbol_size = 5) |>
  e_scatter(wt, jitter_factor = 2, legend = FALSE)

# examples
USArrests |>
  e_charts(Assault) |>
  e_scatter(Murder, Rape) |>
  e_effect_scatter(Rape, Murder, y_index = 1) |>
  e_grid(index = c(0, 1)) |>
  e_tooltip()
```

```

iris |>
  e_charts("Sepal.Length") |>
  e_scatter_(
    "Sepal.Width",
    symbol_size = c(8, 2),
    symbol = "rect"
  ) |>
  e_x_axis(min = 4)

quakes |>
  e_charts(long) |>
  e_geo(
    roam = TRUE,
    boundingCoords = list(
      c(185, -10),
      c(165, -40)
    )
  ) |>
  e_scatter(lat, mag, coord_system = "geo") |>
  e_visual_map(min = 4, max = 6.5)

# timeline
iris |>
  group_by(Species) |>
  e_charts(Petal.Width, timeline = TRUE) |>
  e_scatter(Sepal.Width, Sepal.Length) |>
  e_tooltip(trigger = "axis")

```

e_scatter_3d

Scatter 3D

Description

Add 3D scatter.

Usage

```

e_scatter_3d(
  e,
  y,
  z,
  color,
  size,
  bind,
  coord_system = "cartesian3D",
  name = NULL,
  rm_x = TRUE,
  rm_y = TRUE,

```

```

    legend = FALSE,
    ...
)

e_scatter_3d(
  e,
  y,
  z,
  color = NULL,
  size = NULL,
  bind = NULL,
  coord_system = "cartesian3D",
  name = NULL,
  rm_x = TRUE,
  rm_y = TRUE,
  legend = FALSE,
  ...
)

```

Arguments

<code>e</code>	An <code>echarts4r</code> object as returned by e_charts or a proxy as returned by echarts4rProxy .
<code>y, z</code>	Coordinates.
<code>color, size</code>	Color and Size of bubbles.
<code>bind</code>	Binding.
<code>coord_system</code>	Coordinate system to use, one of <code>geo3D</code> , <code>globe</code> , or <code>cartesian3D</code> .
<code>name</code>	name of the serie.
<code>rm_x, rm_y</code>	Whether to remove x and y axis, defaults to <code>TRUE</code> .
<code>legend</code>	Whether to add serie to legend.
<code>...</code>	Any other option to pass, check See Also section.

See Also

[Additional arguments](#)

Examples

```

v <- LETTERS[1:10]
matrix <- data.frame(
  x = sample(v, 300, replace = TRUE),
  y = sample(v, 300, replace = TRUE),
  z = rnorm(300, 10, 1),
  color = rnorm(300, 10, 1),
  size = rnorm(300, 10, 1),
  stringsAsFactors = FALSE
) |>
  dplyr::group_by(x, y) |>
  dplyr::summarise(

```

```

      z = sum(z),
      color = sum(color),
      size = sum(size)
    ) |>
    dplyr::ungroup()

matrix |>
  e_charts(x) |>
  e_scatter_3d(y, z, size, color) |>
  e_visual_map(
    min = 1,
    max = 100,
    inRange = list(symbolSize = c(1, 30)),
    # scale size
    dimension = 3 # third dimension 0 = x, y = 1, z = 2, size = 3
  ) |>
  e_visual_map(
    min = 1,
    max = 100,
    inRange = list(color = c("#bf444c", "#d88273", "#f6efa6")),
    # scale colors
    dimension = 4,
    # third dimension 0 = x, y = 1, z = 2, size = 3, color = 4
    bottom = 300 # padding to avoid visual maps overlap
  )

airports <- read.csv(
  paste0(
    "https://raw.githubusercontent.com/plotly/datasets/",
    "master/2011_february_us_airport_traffic.csv"
  )
)

airports |>
  e_charts(long) |>
  e_globe(
    globeOuterRadius = 100
  ) |>
  e_scatter_3d(lat, cnt, coord_system = "globe", blendMode = "lighter") |>
  e_visual_map(inRange = list(symbolSize = c(1, 10)))

# timeline
airports |>
  group_by(state) |>
  e_charts(long, timeline = TRUE) |>
  e_globe(
    globeOuterRadius = 100
  ) |>
  e_scatter_3d(lat, cnt, coord_system = "globe", blendMode = "lighter") |>
  e_visual_map(inRange = list(symbolSize = c(1, 10)))

```

`e_scatter_gl`*Scatter GL*

Description

Draw scatter GL.

Usage

```
e_scatter_gl(  
  e,  
  y,  
  z,  
  name = NULL,  
  coord_system = "geo",  
  rm_x = TRUE,  
  rm_y = TRUE,  
  ...  
)
```

```
e_scatter_gl_(  
  e,  
  y,  
  z,  
  name = NULL,  
  coord_system = "geo",  
  rm_x = TRUE,  
  rm_y = TRUE,  
  ...  
)
```

Arguments

<code>e</code>	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
<code>y, z</code>	Column names containing y and z data.
<code>name</code>	name of the serie.
<code>coord_system</code>	Coordinate system to plot against.
<code>rm_x, rm_y</code>	Whether to remove x and y axis, defaults to TRUE.
<code>...</code>	Any other option to pass, check See Also section.

See Also

[Additional arguments](#)

Examples

```

quakes |>
  e_charts(long) |>
  e_geo(
    roam = TRUE,
    boundingCoords = list(
      c(185, -10),
      c(165, -40)
    )
  ) |>
  e_scatter_gl(lat, depth)

# timeline
quakes$year <- rep(c("2017", "2018"), 500)

quakes |>
  group_by(year) |>
  e_charts(long, timeline = TRUE) |>
  e_geo(
    roam = TRUE,
    boundingCoords = list(
      c(185, -10),
      c(165, -40)
    )
  ) |>
  e_scatter_gl(lat, depth)

```

e_showtip_p

*Tooltip Proxy***Description**

Proxies to show or hide tooltip.

Usage

```
e_showtip_p(proxy, ...)
```

```
e_hidetip_p(proxy)
```

Arguments

`proxy` An echarts4r proxy as returned by [echarts4rProxy](#).

`...` Any other option, see [showTip](#).

Examples

```
## Not run:
library(shiny)

ui <- fluidPage(
  fluidRow(
    actionButton("show", "Show tooltip"),
    actionButton("hide", "Hide tooltip")
  ),
  fluidRow(
    echarts4rOutput("plot"),
    h3("clicked Data"),
    verbatimTextOutput("clickedData"),
    h3("clicked Serie"),
    verbatimTextOutput("clickedSerie"),
    h3("clicked Row"),
    verbatimTextOutput("clickedRow")
  )
)

server <- function(input, output, session) {
  output$plot <- renderEcharts4r({
    mtcars |>
      e_charts(mpg) |>
      e_line(displacement, name = "displacement") |>
      e_line(hp) |>
      e_x_axis(min = 10) |>
      e_tooltip(show = FALSE) |>
      e_theme("westeros")
  })

  observeEvent(input$show, {
    echarts4rProxy("plot") |>
      e_showtip_p(
        name = "displacement",
        position = list(5, 5)
      )
  })

  observeEvent(input$hide, {
    echarts4rProxy("plot") |>
      e_hidetip_p()
  })

  output$clickedData <- renderPrint({
    input$plot_clicked_data
  })

  output$clickedSerie <- renderPrint({
    input$plot_clicked_serie
  })
}
```

```

    output$clickedRow <- renderPrint({
      input$plot_clicked_row
    })
  }

  if (interactive()) {
    shinyApp(ui, server)
  }

  ## End(Not run)

```

e_show_loading

*Loading***Description**

Show or hide loading.

Usage

```

e_show_loading(
  e,
  hide_overlay = TRUE,
  text = "loading",
  color = "#c23531",
  text_color = "#000",
  mask_color = "rgba(255, 255, 255, 0.8)",
  zlevel = 0
)

e_hide_loading(e)

```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
hide_overlay	Hides the white overaly that appears in shiny when a plot is recalculating.
text	Text to display.
color	Color of spinner.
text_color	Color of text.
mask_color	Color of mask.
zlevel	Z level.

Details

This only applies to Shiny.

Examples

```
## Not run:

# no redraw
# no loading
library(shiny)
ui <- fluidPage(
  fluidRow(
    column(12, actionButton("update", "Update"))
  ),
  fluidRow(
    column(12, echarts4rOutput("plot"))
  )
)

server <- function(input, output) {
  data <- eventReactive(input$update, {
    data.frame(
      x = 1:10,
      y = rnorm(10)
    )
  })

  output$plot <- renderEcharts4r({
    data() |>
      e_charts(x) |>
      e_bar(y)
  })
}

if (interactive()) {
  shinyApp(ui, server)
}

# add loading
server <- function(input, output) {
  data <- eventReactive(input$update, {
    Sys.sleep(1) # sleep one second to show loading
    data.frame(
      x = 1:10,
      y = rnorm(10)
    )
  })

  output$plot <- renderEcharts4r({
    data() |>
      e_charts(x) |>
      e_bar(y) |>
      e_show_loading()
  })
}
```

```

if (interactive()) {
  shinyApp(ui, server)
}

## End(Not run)

```

e_single_axis

Single Axis

Description

Setup single axis.

Usage

```
e_single_axis(e, index = 0, ...)
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
index	Index of axis to customise.
...	Any other option to pass, check See Also section.

Examples

```

df <- data.frame(
  axis = LETTERS[1:10],
  value = runif(10, 3, 20),
  size = runif(10, 3, 20)
)

df |>
  e_charts(axis) |>
  e_single_axis() |> # add the single axis
  e_scatter(
    value,
    size,
    coord_system = "singleAxis"
  )

```

e_step	<i>Step</i>
--------	-------------

Description

Add step serie.

Usage

```
e_step(  
  e,  
  serie,  
  bind,  
  step = c("start", "middle", "end"),  
  fill = FALSE,  
  name = NULL,  
  legend = TRUE,  
  y_index = 0,  
  x_index = 0,  
  coord_system = "cartesian2d",  
  ...  
)  
  
e_step_(  
  e,  
  serie,  
  bind = NULL,  
  step = c("start", "middle", "end"),  
  fill = FALSE,  
  name = NULL,  
  legend = TRUE,  
  y_index = 0,  
  x_index = 0,  
  coord_system = "cartesian2d",  
  ...  
)
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
serie	Column name of serie to plot.
bind	Binding between datasets, namely for use of e_brush .
step	Step type, one of start, middle or end.
fill	Set to fill as area.
name	name of the serie.

legend Whether to add serie to legend.
x_index, y_index Indexes of x and y axis.
coord_system Coordinate system to plot against.
... Any other option to pass, check See Also section.

See Also

Additional arguments

Examples

```
USArrests |>
  tibble::rownames_to_column("State") |>
  e_charts(State) |>
  e_step(Murder, name = "Start", step = "start", fill = TRUE) |>
  e_step(Rape, name = "Middle", step = "middle") |>
  e_step(Assault, name = "End", step = "end") |>
  e_tooltip(trigger = "axis")

# timeline
iris |>
  group_by(Species) |>
  e_charts(Sepal.Length, timeline = TRUE) |>
  e_step(Sepal.Width) |>
  e_tooltip(trigger = "axis")
```

e_sunburst	<i>Sunburst</i>
------------	-----------------

Description

Build a sunburst.

Usage

```
e_sunburst(
  e,
  styles = NULL,
  names = NULL,
  levels = NULL,
  rm_x = TRUE,
  rm_y = TRUE,
  ...
)

e_sunburst_(
  e,
```

```

    styles = NULL,
    names = NULL,
    levels = NULL,
    rm_x = TRUE,
    rm_y = TRUE,
    ...
  )

```

Arguments

<code>e</code>	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
<code>styles</code>	Vector of style lists, defaults to NULL.
<code>names</code>	Names of items to style, expects a list, defaults to NULL.
<code>levels</code>	Hierarchical levels to style, expects a list, defaults to NULL.
<code>rm_x, rm_y</code>	Whether to remove x and y axis, defaults to TRUE.
<code>...</code>	Any other option to pass, check See Also section.

Details

Charts `e_sunburst`, `e_treemap` and `e_tree` require hierarchical input data. Such structure could be represented thru json lists or nested tibbles (data.frame). Input data may contain styles, see `itemStyle` in examples `jsonl` and `df` below. The number of lists in the `styles` parameter should match the number of elements in `names` and/or `levels`. If both `names` and `levels` are present, name styles will take precedence over level styles. Multiple names may have the same style, see `c('land', 'river')` below. Multiple levels may have the same style, see `c(3,4)` below. `styles` lists contain items such as `color`, or `borderColor` as specified in the [official documentation](#).

See Also

[Additional arguments](#)

Examples

```

# json list hierarchical data representation
jsonl <- jsonlite::fromJSON('[
  {"name": "earth", "value": 30,
    "children": [
      {"name": "land", "value":10,
        "children": [
          {"name": "forest", "value": 3},
          {"name": "river", "value": 7}
        ]},
      {"name": "ocean", "value":20,
        "children": [
          {"name": "fish", "value": 10,
            "children": [
              {"name": "shark", "value":2},
              {"name": "tuna", "value":6}
            ]},
          ]},
    ]}
  ]')

```

```

      {"name": "kelp", "value": 5}
    ]}
  ],
  {"name": "mars", "value": 30,
   "children": [
     {"name": "crater", "value": 20},
     {"name": "valley", "value": 20}
   ]},
  {"name": "venus", "value": 40, "itemStyle": {"color": "blue"} }
]', simplifyDataFrame = FALSE)

```

```

jsonl |>
  e_charts() |>
  e_sunburst() # demo

```

```

# tibble hierarchical data representation
library(dplyr)
df <- tibble(
  name = c("earth", "mars", "venus"),
  value = c(30, 40, 30),
  # 1st level
  itemStyle = tibble(color = c(NA, "red", "blue")),
  # embedded styles, optional
  children = list(
    tibble(
      name = c("land", "ocean"),
      value = c(10, 20),
      # 2nd level
      children = list(
        tibble(name = c("forest", "river"), value = c(3, 7)),
        # 3rd level
        tibble(
          name = c("fish", "kelp"),
          value = c(10, 5),
          children = list(
            tibble(name = c("shark", "tuna"), value = c(2, 6)),
            # 4th level
            NULL # kelp
          )
        )
      )
    ),
    tibble(name = c("crater", "valley"), value = c(20, 20)),
    NULL # venus
  )
)

df |>
  e_charts() |>
  e_sunburst() |>
  e_theme("westeros")

```

```
# with styles
myStyles <- c(list(color = "green"), list(color = "magenta")) # custom styles defined
myNames <- list(c("land", "river"), "crater") # names to style
myLevels <- list(2, c(3, 4)) # hierarchical levels to style

df |>
  e_charts() |>
  e_sunburst(myStyles, myNames, myLevels)
```

e_surface

Surface

Description

Add a surface plot.

Usage

```
e_surface(e, y, z, bind, name = NULL, rm_x = TRUE, rm_y = TRUE, ...)
```

```
e_surface_(e, y, z, bind = NULL, name = NULL, rm_x = TRUE, rm_y = TRUE, ...)
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
y, z	Coordinates.
bind	Binding.
name	name of the serie.
rm_x, rm_y	Whether to remove x and y axis, defaults to TRUE.
...	Any other option to pass, check See Also section.

Examples

```
data("volcano")

surface <- as.data.frame(as.table(volcano))
surface$Var1 <- as.numeric(surface$Var1)
surface$Var2 <- as.numeric(surface$Var2)

surface |>
  e_charts(Var1) |>
  e_surface(Var2, Freq) |>
  e_visual_map(Freq)
```

<code>e_text_style</code>	<i>Text style</i>
---------------------------	-------------------

Description

Define global font style.

Usage

```
e_text_style(e, ...)
```

Arguments

- `e` An echarts4r object as returned by [e_charts](#) or a proxy as returned by [echarts4rProxy](#).
- `...` Any other option to pass, check See Also section.

Note

Do not use `e_arrange` in R markdown or Shiny.

See Also

[official documentation](#)

Examples

```
cars |>
  e_charts(dist) |>
  e_scatter(speed) |>
  e_labels() |>
  e_text_style(
    color = "blue",
    fontStyle = "italic"
  )
```

<code>e_theme</code>	<i>Themes</i>
----------------------	---------------

Description

Add a custom theme or apply a pre-built one.

Usage

```
e_theme(
  e,
  name = c("auritus", "azul", "bee-inspired", "blue", "caravan", "carp", "chalk", "cool",
    "dark-blue", "dark-bold", "dark-digerati", "dark-fresh-cut", "dark-mushroom", "dark",
    "eduardo", "essos", "forest", "fresh-cut", "fruit", "gray", "green", "halloween",
    "helianthus", "infographic", "inspired", "jazz", "london", "macarons", "macarons2",
    "mint", "purple-passion", "red-velvet", "red", "roma", "royal", "sakura", "shine",
    "tech-blue", "vintage", "walden", "wef", "weforum", "westeros", "wonderland")
)

e_theme_custom(e, theme, name = "custom")

e_theme_register(theme, name = "custom")
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
name	Name of theme.
theme	Theme, A json string or a see below.

Details

The function `e_theme_register` can be used to register the theme globally in R markdown or shiny (UI). This is useful because 1) the `e_theme_custom` registers the theme every time and is more computationally expensive.

Functions

- `e_theme` - Use a default theme by name.
- `e_theme_custom` - Use a custom theme.
- `e_theme_register` - Register a theme globally in shiny or R markdown.

See Also

[create your own theme.](#)

Examples

```
mtcars |>
  e_charts(mpg) |>
  e_line(displ) |>
  e_area(hp) |>
  e_x_axis(min = 10) -> p

p |> e_theme("chalk")
p |> e_theme_custom('{ "color": ["#ff715e", "#ffa511"] }')
```

e_title	<i>Title</i>
---------	--------------

Description

Add title.

Usage

```
e_title(e, text = NULL, subtext = NULL, link = NULL, sublink = NULL, ...)
```

Arguments

- e An echarts4r object as returned by [e_charts](#) or a proxy as returned by [echarts4rProxy](#).
- text, subtext Title and Subtitle.
- link, sublink Title and Subtitle link.
- ... Any other option to pass, check See Also section.

See Also

[Additional arguments](#)

Examples

```
quakes |>
  dplyr::mutate(mag = exp(mag) / 60) |>
  e_charts(stations) |>
  e_scatter(depth, mag) |>
  e_visual_map(min = 3, max = 7) |>
  e_title("Quakes", "Stations and Magnitude")
```

e_toolbox_feature	<i>Toolbox</i>
-------------------	----------------

Description

Add toolbox interface.

Usage

```
e_toolbox_feature(e, feature, ...)

e_toolbox(e, ...)
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
feature	Feature to add, defaults to all.
...	Any other option to pass, check See Also section.

Details

Valid feature:

- saveAsImage
- brush
- restore
- dataView
- dataZoom
- magicType

See Also

[Additional arguments](#)

Examples

```
USArrests |>
  e_charts(UrbanPop) |>
  e_line(Assault) |>
  e_area(Murder, y_index = 1, x_index = 1) |>
  e_datazoom(x_index = 0)

mtcars |>
  tibble::rownames_to_column("model") |>
  e_charts(model) |>
  e_line(qsec) |>
  e_toolbox() |>
  e_toolbox_feature(
    feature = "magicType",
    type = list("line", "bar")
  )
```

e_tooltip	<i>Tooltip</i>
-----------	----------------

Description

Customise tooltip

Usage

```
e_tooltip(e, trigger = c("item", "axis"), formatter = NULL, ...)
```

```
e_tooltip_item_formatter(
  style = c("decimal", "percent", "currency"),
  digits = 0,
  locale = NULL,
  currency = "USD"
)
```

```
e_tooltip_choro_formatter(
  style = c("decimal", "percent", "currency"),
  digits = 0,
  locale = NULL,
  currency = "USD"
)
```

```
e_tooltip_pie_formatter(
  style = c("decimal", "percent", "currency"),
  digits = 0,
  locale = NULL,
  currency = "USD",
  ...
)
```

```
e_tooltip_pointer_formatter(
  style = c("decimal", "percent", "currency"),
  digits = 0,
  locale = NULL,
  currency = "USD"
)
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
trigger	What triggers the tooltip, one of item or axis.
formatter	Item and Pointer formatter as returned by e_tooltip_item_formatter , e_tooltip_pointer_formatter or e_tooltip_pie_formatter .
...	Any other option to pass, check See Also section.
style	Formatter style, one of decimal, percent, or currency.
digits	Number of decimals.
locale	Locale, if NULL then it is inferred from Sys.getlocale.
currency	Currency to to display.

Formatters

- [e_tooltip_pie_formatter](#): special helper for [e_pie](#).

- `e_tooltip_item_formatter`: general helper, this is passed to the `tooltip formatter`.
- `e_tooltip_pointer_formatter`: helper for pointer, this is passed to the `label parameter` under `axisPointer`.

See Also

[Additional arguments](#)

Examples

```
# basic
USArrests |>
  e_charts(Assault) |>
  e_scatter(Murder) |>
  e_tooltip()

# formatter
cars |>
  dplyr::mutate(
    dist = dist / 120
  ) |>
  e_charts(speed) |>
  e_scatter(dist, symbol_size = 5) |>
  e_tooltip(
    formatter = e_tooltip_item_formatter("percent")
  )

# axis pointer
cars |>
  e_charts(speed) |>
  e_scatter(dist, symbol_size = 5) |>
  e_tooltip(
    formatter = e_tooltip_pointer_formatter("currency"),
    axisPointer = list(
      type = "cross"
    )
  )
```

e_tree

Tree

Description

Build a tree.

Usage

```
e_tree(e, rm_x = TRUE, rm_y = TRUE, ...)

e_tree_(e, rm_x = TRUE, rm_y = TRUE, ...)
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
rm_x, rm_y	Whether to remove x and y axis, defaults to TRUE.
...	Any other option to pass, check See Also section.

See Also

[Additional arguments](#)

Examples

```
library(dplyr)
df <- tibble(
  name = "earth",
  # 1st level
  children = list(
    tibble(
      name = c("land", "ocean"),
      # 2nd level
      children = list(
        tibble(name = c("forest", "river")),
        # 3rd level
        tibble(
          name = c("fish", "kelp"),
          children = list(
            tibble(
              name = c("shark", "tuna")
            ),
            # 4th level
            NULL # kelp
          )
        )
      )
    )
  )
)

df |>
  e_charts() |>
  e_tree(initialTreeDepth = 3, label = list(offset = c(0, -11)))
```

e_treemap

Treemap

Description

Build a treemap.

Usage

```
e_treemap(
  e,
  styles = NULL,
  names = NULL,
  levels = NULL,
  rm_x = TRUE,
  rm_y = TRUE,
  ...
)

e_treemap_(
  e,
  styles = NULL,
  names = NULL,
  levels = NULL,
  rm_x = TRUE,
  rm_y = TRUE,
  ...
)
```

Arguments

<code>e</code>	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
<code>styles</code>	Vector of style lists, defaults to NULL.
<code>names</code>	Names of items to style, expects a list, defaults to NULL.
<code>levels</code>	Hierarchical levels to style, expects a list, defaults to NULL.
<code>rm_x, rm_y</code>	Whether to remove x and y axis, defaults to TRUE.
<code>...</code>	Any other option to pass, check See Also section.

See Also

[Additional arguments](#)

Examples

```
library(dplyr)
df <- tibble(
  name = c("earth", "mars", "venus"),
  value = c(30, 40, 30),
  # 1st level
  itemStyle = tibble(color = c(NA, "red", "blue")),
  # embedded styles, optional
  children = list(
    tibble(
      name = c("land", "ocean"),
      value = c(10, 20),
      # 2nd level
```

```
children = list(
  tibble(name = c("forest", "river"), value = c(3, 7)),
  # 3rd level
  tibble(
    name = c("fish", "kelp"),
    value = c(10, 5),
    children = list(
      tibble(name = c("shark", "tuna"), value = c(2, 6)),
      # 4th level
      NULL # kelp
    )
  )
),
tibble(name = c("crater", "valley"), value = c(20, 20)),
NULL # venus
)
)

df |>
  e_charts() |>
  e_treemap()
```

e_utc	Use UTC
-------	---------

Description

Use UTC

Usage

e_utc(e)

Arguments

e An echarts4r object as returned by [e_charts](#) or a proxy as returned by [echarts4rProxy](#).

e_visual_map	Visual Map
--------------	------------

Description

Visual Map

Usage

```
e_visual_map(
  e,
  serie,
  calculable = TRUE,
  type = c("continuous", "piecewise"),
  scale = NULL,
  ...
)

e_visual_map_(
  e,
  serie = NULL,
  calculable = TRUE,
  type = c("continuous", "piecewise"),
  scale = NULL,
  ...
)
```

Arguments

<code>e</code>	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
<code>serie</code>	Column name of serie to scale against.
<code>calculable</code>	Whether show handles, which can be dragged to adjust "selected range".
<code>type</code>	One of continuous or piecewise.
<code>scale</code>	A function that takes a vector of numeric and returns a vector of numeric of the same length.
<code>...</code>	Any other option to pass, check See Also section.

Scaling function

defaults to `e_scale` which is a basic function that rescales size between 1 and 20 for that makes for decent sized points on the chart.

See Also

[Additional arguments](#)

Examples

```
# scaled data
mtcars |>
  e_charts(mpg) |>
  e_scatter(wt, qsec, scale = e_scale) |>
  e_visual_map(qsec, scale = e_scale)

# dimension
# color according to y axis
```

```
mtcars |>
  e_charts(mpg) |>
  e_scatter(wt) |>
  e_visual_map(wt, dimension = 1)

# color according to x axis
mtcars |>
  e_charts(mpg) |>
  e_scatter(wt) |>
  e_visual_map(mpg, dimension = 0)

v <- LETTERS[1:10]
matrix <- data.frame(
  x = sample(v, 300, replace = TRUE),
  y = sample(v, 300, replace = TRUE),
  z = rnorm(300, 10, 1),
  color = rnorm(300, 10, 1),
  size = rnorm(300, 10, 1),
  stringsAsFactors = FALSE
) |>
dplyr::group_by(x, y) |>
dplyr::summarise(
  z = sum(z),
  color = sum(color),
  size = sum(size)
) |>
dplyr::ungroup()

matrix |>
  e_charts(x) |>
  e_scatter_3d(y, z, color, size) |>
  e_visual_map(
    z,
    # scale to z
    inRange = list(symbolSize = c(1, 30)),
    # scale size
    dimension = 3 # third dimension 0 = x, y = 1, z = 2, size = 3
  ) |>
  e_visual_map(
    z,
    # scale to z
    inRange = list(color = c("#bf444c", "#d88273", "#f6efa6")),
    # scale colors
    dimension = 4,
    # third dimension 0 = x, y = 1, z = 2, size = 3, color = 4
    bottom = 300 # padding to avoid visual maps overlap
  )
```

Description

Selects data range of visual mapping.

Usage

```
e_visual_map_range(e, ..., btn = NULL)
```

Arguments

- e An echarts4r object as returned by [e_charts](#) or a proxy as returned by [echarts4rProxy](#).
- ... Any options, see [official documentation](#)
- btn A [e_button](#) id.

Examples

```
data("state")

as.data.frame(state.x77) |>
  e_charts(Population) |>
  e_scatter(Income, Frost) |>
  e_visual_map(Frost, scale = e_scale) |>
  e_legend(FALSE) |>
  e_visual_map_range(
    selected = list(60, 120)
  )
```

e_zoom	<i>Zoom</i>
--------	-------------

Description

Zoom on a region.

Usage

```
e_zoom(e, ..., btn = NULL)
```

Arguments

- e An echarts4r object as returned by [e_charts](#) or a proxy as returned by [echarts4rProxy](#).
- ... Any options, see [official documentation](#)
- btn A [e_button](#) id.

Examples

```
cars |>
  e_charts(dist) |>
  e_scatter(speed) |>
  e_datazoom() |>
  e_zoom(
    dataZoomIndex = 0,
    start = 20,
    end = 40,
    btn = "BUTTON"
  ) |>
  e_button("BUTTON", "Zoom in")
```

graph_action

*Nodes Adjacency***Description**

Actions related to [e_graph](#).

Usage

```
e_focus_adjacency(e, ..., btn = NULL)

e_unfocus_adjacency(e, ..., btn = NULL)
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
...	Any options, see official documentation
btn	A e_button id.

Examples

```
value <- rnorm(10, 10, 2)

nodes <- data.frame(
  name = sample(LETTERS, 10),
  value = value,
  size = value,
  grp = rep(c("grp1", "grp2"), 5),
  stringsAsFactors = FALSE
)

edges <- data.frame(
  source = sample(nodes$name, 20, replace = TRUE),
  target = sample(nodes$name, 20, replace = TRUE),
  stringsAsFactors = FALSE
```

```

)

e_charts() |>
  e_graph() |>
    e_graph_nodes(nodes, name, value, size, grp) |>
    e_graph_edges(edges, source, target) |>
    e_focus_adjacency(
      seriesIndex = 0,
      dataIndex = 4
    )

```

highlight_action	<i>Highlight & Downplay</i>
------------------	---------------------------------

Description

Highlight series

Usage

```
e_highlight(e, series_index = NULL, series_name = NULL, btn = NULL)
```

```
e_downplay(e, series_index = NULL, series_name = NULL, btn = NULL)
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
series_index, series_name	Index or name of serie to highlight or list or vector of series.
btn	A e_button id.

Examples

```

iris |>
  group_by(Species) |>
  e_charts(Sepal.Length) |>
  e_line(Sepal.Width) |>
  e_line(Petal.Length) |>
  e_highlight(series_name = "setosa") # highlight group

```

init	<i>Initialise</i>
------	-------------------

Description

Initialise a chart.

Usage

```
e_charts(  
  data,  
  x,  
  width = NULL,  
  height = NULL,  
  elementId = NULL,  
  dispose = TRUE,  
  draw = TRUE,  
  renderer = "canvas",  
  timeline = FALSE,  
  ...,  
  reorder = TRUE  
)
```

Default S3 method:

```
e_charts(  
  data,  
  x,  
  width = NULL,  
  height = NULL,  
  elementId = NULL,  
  dispose = TRUE,  
  draw = TRUE,  
  renderer = "canvas",  
  timeline = FALSE,  
  ...,  
  reorder = TRUE  
)
```

S3 method for class 'Node'

```
e_charts(  
  data,  
  x,  
  width = NULL,  
  height = NULL,  
  elementId = NULL,  
  dispose = TRUE,  
  draw = TRUE,  
  ...  
)
```

```

    renderer = "canvas",
    timeline = FALSE,
    ...,
    reorder = TRUE
)

e_charts_(
  data,
  x = NULL,
  width = NULL,
  height = NULL,
  elementId = NULL,
  dispose = TRUE,
  draw = TRUE,
  renderer = "canvas",
  timeline = FALSE,
  ...,
  reorder = TRUE
)

e_chart(
  data,
  x,
  width = NULL,
  height = NULL,
  elementId = NULL,
  dispose = TRUE,
  draw = TRUE,
  renderer = "canvas",
  timeline = FALSE,
  ...,
  reorder = TRUE
)

e_data(e, data, x)

```

Arguments

<code>data</code>	A <code>data.frame</code> .
<code>x</code>	Column name containing x axis.
<code>width, height</code>	Must be a valid CSS unit (like <code>'100%'</code> , <code>'400px'</code> , <code>'auto'</code>) or a number, which will be coerced to a string and have <code>'px'</code> appended.
<code>elementId</code>	Id of element.
<code>dispose</code>	Set to <code>TRUE</code> to force redraw of chart, set to <code>FALSE</code> to update.
<code>draw</code>	Whether to draw the chart, intended to be used with e_draw_p .
<code>renderer</code>	Renderer, takes <code>canvas</code> (default) or <code>svg</code> .
<code>timeline</code>	Set to <code>TRUE</code> to build a timeline, see timeline section.

...	Any other argument.
reorder	Set the FALSE to not reorder numeric x axis values.
e	An object of class echarts4r as returned by e_charts.

Timeline

The timeline feature currently supports the following chart types.

- `e_bar`
- `e_line`
- `e_step`
- `e_area`
- `e_scatter`
- `e_effect_scatter`
- `e_candle`
- `e_heatmap`
- `e_pie`
- `e_line_3d`
- `e_lines_3d`
- `e_bar_3d`
- `e_lines`
- `e_scatter_3d`
- `e_scatter_gl`
- `e_histogram`
- `e_lm`
- `e_loess`
- `e_glm`
- `e_density`
- `e_pictorial`
- `e_boxplot`
- `e_map`
- `e_map_3d`
- `e_line_3d`
- `e_gauge`

Examples

```
mtcars |>
  e_charts(qsec) |>
  e_line(mpg)
points <- mtcars[1:3, ]
mtcars |>
  e_charts("qsec") |>
  e_line(mpg) |>
  e_data(points, qsec) |>
  e_scatter(mpg, color = "red", symbol_size = 20)
```

legend_action	<i>Legend</i>
---------------	---------------

Description

Legend

Usage

```
e_legend_select(e, name, btn = NULL)

e_legend_unselect(e, name, btn = NULL)

e_legend_toggle_select(e, name, btn = NULL)

e_legend_scroll(e, scroll_index = NULL, legend_id = NULL, btn = NULL)
```

Arguments

<code>e</code>	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
<code>name</code>	Legend name.
<code>btn</code>	A e_button id.
<code>scroll_index</code>	Controle the scrolling of legend when type = "scroll" in <code>e_legend</code> .
<code>legend_id</code>	Id of legend.

Examples

```
e <- C02 |>
  group_by(Type) |>
  e_charts(conc) |>
  e_scatter(uptake)

e |>
  e_legend_unselect("Quebec")

e |>
  e_legend_unselect("Quebec", btn = "btn") |>
  e_button("btn", "Quebec")
```

mapbox

Mapbox

Description

Use mapbox.

Usage

```
e_mapbox(e, token, ...)
```

Arguments

<code>e</code>	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
<code>token</code>	Your mapbox token from mapbox .
<code>...</code>	Any option.

Note

Mapbox may not work properly in the RSudio console.

See Also

[Official documentation](#), [mapbox documentation](#)

Examples

```
## Not run:
url <- paste0(
  "https://echarts.apache.org/examples/",
  "data-gl/asset/data/population.json"
)
data <- jsonlite::fromJSON(url)
data <- as.data.frame(data)
names(data) <- c("lon", "lat", "value")

data |>
  e_charts(lon) |>
  e_mapbox(
    token = "YOUR_MAPBOX_TOKEN",
    style = "mapbox://styles/mapbox/dark-v9"
  ) |>
  e_bar_3d(lat, value, coord_system = "mapbox") |>
  e_visual_map()

## End(Not run)
```

map_actions	<i>Map Actions</i>
-------------	--------------------

Description

Map-related actions.

Usage

```
e_map_select(e, ..., btn = NULL)
e_map_unselect(e, ..., btn = NULL)
e_map_toggle_select(e, ..., btn = NULL)
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
...	Any options, see official documentation
btn	A e_button id.

See Also

[e_map_register](#)

Examples

```
choropleth <- data.frame(
  countries = c(
    "France",
    "Brazil",
    "China",
    "Russia",
    "Canada",
    "India",
    "United States",
    "Argentina",
    "Australia"
  ),
  values = round(runif(9, 10, 25))
)

choropleth |>
  e_charts(countries) |>
  e_map(values) |>
  e_visual_map(min = 10, max = 25) |>
  e_map_toggle_select(name = "China", btn = "btn") |>
  e_button("btn", "Select China")
```

nesting

*Add nested data***Description**

Utility function to add data where the original JavaScript library expects nested data.

Usage

```
e_add(e, param, ..., .serie = NULL, .data = NULL)
```

```
e_add_nested(e, param, ..., .serie = NULL, .data = NULL)
```

```
e_add_unnested(e, param, value, .serie = NULL, .data = NULL)
```

Arguments

<code>e</code>	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
<code>param</code>	The nested parameter to add data to.
<code>...</code>	Any other option to pass, check See Also section.
<code>.serie</code>	Serie's index to add the data to, if 'NULL' then it is added to all.
<code>.data</code>	A dataset to use, if none are specified than the original dataset passed to 'e_charts' is used.
<code>value</code>	The column to map to the parameter.

Details

For instance, [e_funnel](#) lets you pass values and labels (from your initial data.frame) which corresponds to name and value in the [original library](#). However the latter also takes, label, itemStyle, and emphasis but being JSON arrays they translate to lists in R and dealing with nested data.frames is not ideal. `e_add` remedies to that. It allows adding those nested data points, see the examples below.

Functions

- 'e_add_nested': Adds nested data, e.g.: 'e_add_nested("itemStyle", color, fontBold)' creates 'itemStyle: color: 'red', fontBold: 'bold''. - 'e_add_unnested': Adds unnested data, e.g.: 'e_add_unnested("symbolSize", size)' creates 'symbolSize: 4'.

Examples

```
# funnel can take nested itemStyle
# https://echarts.apache.org/en/option.html#series-funnel.data
funnel <- data.frame(
  stage = c("View", "Click", "Purchase"),
  value = c(80, 30, 20),
```

```

    color = c("blue", "red", "green")
  )

  funnel |>
    e_charts() |>
    e_funnel(value, stage) |>
    e_add_nested("itemStyle", color)

  # Heatmap can take nested label
  # https://echarts.apache.org/en/option.html#series-heatmap.data
  v <- LETTERS[1:10]
  matrix <- data.frame(
    x = sample(v, 300, replace = TRUE),
    y = sample(v, 300, replace = TRUE),
    z = rnorm(300, 10, 1),
    stringsAsFactors = FALSE
  ) |>
  dplyr::group_by(x, y) |>
  dplyr::summarise(z = sum(z)) |>
  dplyr::ungroup() |>
  dplyr::mutate(
    show = TRUE,
    fontStyle = round(runif(dplyr::n(), 5, 12))
  )

  matrix |>
    e_charts(x) |>
    e_heatmap(y, z) |>
    e_visual_map(z) |>
    e_add_nested(
      "label",
      show,
      fontStyle
    )

```

pie_action

Select & Unselect Pie

Description

Actions related to [e_pie](#).

Usage

```
e_pie_select(e, ..., btn = NULL)
```

```
e_pie_unselect(e, ..., btn = NULL)
```

Arguments

- e An echarts4r object as returned by [e_charts](#) or a proxy as returned by [echarts4rProxy](#).
- ... Any options, see [official documentation](#)
- btn A [e_button](#) id.

Examples

```
mtcars |>
  head() |>
  tibble::rownames_to_column("model") |>
  e_charts(model) |>
  e_pie(carb) |>
  e_pie_select(dataIndex = 0)
```

radius_axis	<i>Radius axis</i>
-------------	--------------------

Description

Customise radius axis.

Usage

```
e_radius_axis(e, serie, show = TRUE, ...)

e_radius_axis_(e, serie = NULL, show = TRUE, ...)
```

Arguments

- e An echarts4r object as returned by [e_charts](#) or a proxy as returned by [echarts4rProxy](#).
- serie Serie to use as axis labels.
- show Whether to display the axis.
- ... Any other option to pass, check [See Also](#) section.

See Also

[Additional arguments](#)

Examples

```
df <- data.frame(x = LETTERS[1:10], y = seq(1, 20, by = 2))

df |>
  e_charts(x) |>
  e_polar() |>
  e_angle_axis() |>
  e_radius_axis(x) |>
  e_bar(y, coord.system = "polar")
```

renderEcharts4rBox	<i>Render box</i>
--------------------	-------------------

Description

Render an echarts4r box.

Usage

```
renderEcharts4rBox(expr, env = parent.frame(), quoted = FALSE)
```

Arguments

expr	An expression that produces as echarts4rBox .
env	The environment in which to evaluate 'expr'.
quoted	Is 'expr' a quoted expression (with 'quote()')? This is useful if you want to save an expression in a variable.

timeline-opts	<i>Timeline</i>
---------------	-----------------

Description

Set timeline options

Usage

```
e_timeline_opts(e, axis_type = "category", ...)
e_timeline_serie(e, ..., index = 1)
e_timeline_on_serie(e, ..., serie_index)
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
axis_type	Type of axis, time, value, or category.
...	Named options.
index	The index of the element to apply options to, see examples.
serie_index	The index of the serie to add elements to.

Functions

- `e_timeline_opts`: Pass general timeline options, see [official documentation](#).
- `e_timeline_serie`: Pass options to each serie, each options *must* be a vector or list the same length as their are steps, see examples.
- `e_timeline_make`: Helper function that wraps your data and `e_timeline_serie` to dynamically add options to series.

Examples

```
# general options
iris |>
  group_by(Species) |>
  e_charts(Sepal.Length, timeline = TRUE) |>
  e_line(Sepal.Width) |>
  e_timeline_opts(
    autoPlay = TRUE,
    rewind = TRUE
  )

# serie options
iris |>
  group_by(Species) |>
  e_charts(Sepal.Length, timeline = TRUE) |>
  e_line(Sepal.Width) |>
  e_timeline_serie(
    title = list(
      list(text = "setosa"),
      list(text = "versicolor"),
      list(text = "virginica")
    )
  )
```

tooltip_action

Show & Hide Tooltip

Description

Show or hide tooltip.

Usage

```
e_showtip(e, ..., btn = NULL)
```

```
e_hidetip(e, ..., btn = NULL)
```

Arguments

e	An echarts4r object as returned by e_charts or a proxy as returned by echarts4rProxy .
...	Any options, see official documentation
btn	A e_button id.

Note

The tooltip must be initialised with [e_tooltip](#) for this to work.

Examples

```
cars |>
  e_charts(dist) |>
  e_scatter(speed) |>
  e_tooltip() |>
  e_hidetip(btn = "btn") |>
  e_button("btn", "Hide tooltip")
```

Index

angle_axis, 4

band, 5

band2, 6

callbacks, 7

colorRampPalette, 35

connections, 8

corrMatOrder, 36

countrycode, 37

e_add(nesting), 146

e_add_nested(nesting), 146

e_add_unnested(nesting), 146

e_angle_axis(angle_axis), 4

e_angle_axis_(angle_axis), 4

e_animation, 13

e_append1_p, 11, 14

e_append1_p_(e_append1_p), 14

e_append2_p, 11

e_append2_p(e_append1_p), 14

e_append2_p_(e_append1_p), 14

e_arc_g(e_graphic_g), 59

e_area, 16, 142

e_area_(e_area), 16

e_aria, 18

e_arrange(connections), 8

e_axis, 18, 50

e_axis_(e_axis), 18

e_axis_3d, 20

e_axis_formatter, 19

e_axis_formatter(e_axis), 18

e_axis_labels, 22

e_axis_pointer, 22

e_axis_stagger, 23

e_band(band), 5

e_band2(band2), 6

e_band2_(band2), 6

e_band_(band), 5

e_bar, 23, 44, 142

e_bar_(e_bar), 23

e_bar_3d, 25, 142

e_bar_3d_(e_bar_3d), 25

e_bezier_curve_g(e_graphic_g), 59

e_boxplot, 27, 142

e_boxplot_(e_boxplot), 27

e_brush, 17, 24, 28, 31, 63, 74, 98, 110, 121

e_button, 29, 106, 137–139, 143, 145, 148, 151

e_calendar, 30

e_candle, 31, 142

e_candle_(e_candle), 31

e_capture, 32

e_chart(init), 140

e_charts, 4, 6–8, 14, 17–19, 21–25, 27–34, 36, 38, 40, 42, 44–46, 50–56, 60–63, 65, 68, 69, 71–74, 76, 78, 80–84, 86, 89, 90, 92, 94, 97, 98, 101, 103, 106, 108, 110, 113, 115, 118, 120, 121, 123, 125–130, 132–135, 137–139, 143–146, 148, 149, 151

e_charts(init), 140

e_charts_(init), 140

e_circle_g(e_graphic_g), 59

e_cloud, 33

e_cloud_(e_cloud), 33

e_color, 34

e_color_range, 35

e_color_range_(e_color_range), 35

e_common, 36

e_connect(connections), 8

e_connect_group(connections), 8

e_correlations, 36

e_country_names, 37, 54, 56, 86

e_country_names_(e_country_names), 37

e_data(init), 140

e_datazoom, 37

e_density, 142

e_density(e_histogram), 67

- e_density_ (e_histogram), 67
- e_dims, 38
- e_disconnect_group (connections), 8
- e_dispatch_action_p, 11, 39
- e_downplay (highlight_action), 139
- e_downplay_p, 11
- e_downplay_p (e_highlight_p), 66
- e_draft, 40
- e_draw_p, 40, 141
- e_effect_scatter, 142
- e_effect_scatter (e_scatter), 108
- e_effect_scatter_ (e_scatter), 108
- e_error_bar, 41
- e_error_bar_ (e_error_bar), 41
- e_execute, 11, 43
- e_execute_p (e_execute), 43
- e_facet, 43
- e_flip_coords, 44
- e_flow_gl, 45
- e_flow_gl_ (e_flow_gl), 45
- e_focus_adjacency, 11
- e_focus_adjacency (graph_action), 138
- e_focus_adjacency_p, 48
- e_format_axis, 50
- e_format_x_axis (e_format_axis), 50
- e_format_y_axis (e_format_axis), 50
- e_funnel, 51, 146
- e_funnel_ (e_funnel), 51
- e_gauge, 52, 142
- e_gauge_ (e_gauge), 52
- e_geo, 53
- e_geo_3d, 54
- e_geo_3d_ (e_geo_3d), 54
- e_get_data, 55
- e_get_zr, 56
- e_glm, 142
- e_glm (e_lm), 82
- e_globe, 56
- e_graph, 57, 138
- e_graph_edges (e_graph), 57
- e_graph_gl (e_graph), 57
- e_graph_nodes (e_graph), 57
- e_graphic_g, 59
- e_grid, 61
- e_grid_3d, 62
- e_group (connections), 8
- e_group_g (e_graphic_g), 59
- e_heatmap, 36, 63, 142
- e_heatmap_ (e_heatmap), 63
- e_hide_grid_lines, 65
- e_hide_loading (e_show_loading), 118
- e_hidetip (tooltip_action), 150
- e_hidetip_p, 11
- e_hidetip_p (e_showtip_p), 116
- e_highlight (highlight_action), 139
- e_highlight_p, 11, 66
- e_histogram, 67, 142
- e_histogram_ (e_histogram), 67
- e_image_g (e_graphic_g), 59
- e_inspect, 69
- e_labels, 70
- e_leaflet, 71
- e_leaflet_tile (e_leaflet), 71
- e_legend, 72
- e_legend_scroll (legend_action), 143
- e_legend_select (legend_action), 143
- e_legend_toggle_select (legend_action), 143
- e_legend_unselect (legend_action), 143
- e_line, 15, 69, 73, 83, 142
- e_line_ (e_line), 73
- e_line_3d, 15, 142
- e_line_3d (e_lines_3d), 77
- e_line_3d_ (e_lines_3d), 77
- e_line_g (e_graphic_g), 59
- e_lines, 75, 142
- e_lines_ (e_lines), 75
- e_lines_3d, 77, 142
- e_lines_3d_ (e_lines_3d), 77
- e_lines_gl, 80
- e_liquid, 81
- e_liquid_ (e_liquid), 81
- e_list, 81
- e_lm, 82, 142
- e_locale, 84
- e_locale_manual (e_locale), 84
- e_loess, 142
- e_loess (e_lm), 82
- e_map, 85, 89, 142
- e_map_ (e_map), 85
- e_map_3d, 142
- e_map_3d (e_map), 85
- e_map_3d_ (e_map), 85
- e_map_3d_custom (e_map), 85
- e_map_register, 88, 145
- e_map_register_p (e_map_register), 88

- e_map_register_ui (e_map_register), 88
- e_map_select (map_actions), 145
- e_map_toggle_select (map_actions), 145
- e_map_unselect (map_actions), 145
- e_mapbox (mapbox), 144
- e_mark_area (e_mark_point), 91
- e_mark_line (e_mark_point), 91
- e_mark_p, 89
- e_mark_p_ (e_mark_p), 89
- e_mark_point, 91
- e_merge, 94
- e_modularity, 58, 94
- e_morph, 95
- e_off (callbacks), 7
- e_on (callbacks), 7
- e_parallel, 96
- e_parallel_ (e_parallel), 96
- e_pictorial, 97, 142
- e_pictorial_ (e_pictorial), 97
- e_pie, 100, 130, 142, 147
- e_pie_ (e_pie), 100
- e_pie_select (pie_action), 147
- e_pie_unselect (pie_action), 147
- e_polar, 101
- e_polygon_g (e_graphic_g), 59
- e_polyline_g (e_graphic_g), 59
- e_radar, 102
- e_radar_ (e_radar), 102
- e_radar_opts, 103, 103
- e_radius_axis (radius_axis), 148
- e_radius_axis_ (radius_axis), 148
- e_rect_g (e_graphic_g), 59
- e_remove, 104
- e_remove_series (e_remove), 104
- e_remove_series_p, 11
- e_remove_series_p (e_remove), 104
- e_resize, 105
- e_restore, 105
- e_ring_g (e_graphic_g), 59
- e_river, 106
- e_river_ (e_river), 106
- e_rm_axis (e_axis), 18
- e_sankey, 107
- e_sankey_ (e_sankey), 107
- e_scale (e_scatter), 108
- e_scatter, 15, 108, 142
- e_scatter_ (e_scatter), 108
- e_scatter_3d, 15, 112, 142
- e_scatter_3d_ (e_scatter_3d), 112
- e_scatter_gl, 115, 142
- e_scatter_gl_ (e_scatter_gl), 115
- e_sector_g (e_graphic_g), 59
- e_show_loading, 118
- e_showtip (tooltip_action), 150
- e_showtip_p, 11, 116
- e_single_axis, 120
- e_step, 121, 142
- e_step_ (e_step), 121
- e_sunburst, 122
- e_sunburst_ (e_sunburst), 122
- e_surface, 125
- e_surface_ (e_surface), 125
- e_svg (e_map), 85
- e_svg_ (e_map), 85
- e_svg_register (e_map_register), 88
- e_text_g (e_graphic_g), 59
- e_text_style, 126
- e_theme, 34, 126
- e_theme_custom (e_theme), 126
- e_theme_register (e_theme), 126
- e_timeline_on_series (timeline-opts), 149
- e_timeline_opts (timeline-opts), 149
- e_timeline_series (timeline-opts), 149
- e_title, 128
- e_toolbox (e_toolbox_feature), 128
- e_toolbox_feature, 38, 128
- e_tooltip, 129, 151
- e_tooltip_choro_formatter (e_tooltip), 129
- e_tooltip_item_formatter, 130, 131
- e_tooltip_item_formatter (e_tooltip), 129
- e_tooltip_pie_formatter, 130
- e_tooltip_pie_formatter (e_tooltip), 129
- e_tooltip_pointer_formatter, 130, 131
- e_tooltip_pointer_formatter (e_tooltip), 129
- e_tree, 131
- e_tree_ (e_tree), 131
- e_treemap, 132
- e_treemap_ (e_treemap), 132
- e_unfocus_adjacency, 11
- e_unfocus_adjacency (graph_action), 138
- e_unfocus_adjacency_p (e_focus_adjacency_p), 48
- e_utc, 134

`e_visual_map`, 36, 134
`e_visual_map_(e_visual_map)`, 134
`e_visual_map_range`, 136
`e_x_axis(e_axis)`, 18
`e_x_axis_(e_axis)`, 18
`e_x_axis_3d(e_axis_3d)`, 20
`e_y_axis(e_axis)`, 18
`e_y_axis_(e_axis)`, 18
`e_y_axis_3d(e_axis_3d)`, 20
`e_z_axis(e_axis)`, 18
`e_z_axis_(e_axis)`, 18
`e_z_axis_3d(e_axis_3d)`, 20
`e_zoom`, 137
`echarts4r-shiny`, 10
`echarts4r_proxy(echarts4r-shiny)`, 10
`echarts4rBox`, 11, 149
`echarts4rBoxOutput`, 12, 13
`echarts4rOutput(echarts4r-shiny)`, 10
`echarts4rProxy`, 4, 6–8, 14, 15, 17–19, 21–25, 27–34, 36, 38–40, 42–46, 48, 50, 52–56, 60–63, 65, 66, 68, 69, 71–74, 76, 78, 80–84, 86, 90, 92, 94, 97, 98, 101, 103–106, 108, 110, 113, 115, 116, 118, 120, 121, 123, 125–130, 132–135, 137–139, 143–146, 148, 149, 151
`echarts4rProxy(echarts4r-shiny)`, 10
`echarts_from_json(e_inspect)`, 69

`graph_action`, 138

`highlight_action`, 139
`hist`, 69

`init`, 140

`JS`, 8

`legend_action`, 143
`lm`, 83

`map_actions`, 145
`mapbox`, 144

`nesting`, 146

`pie_action`, 147

`radius_axis`, 148
`renderEcharts4r(echarts4r-shiny)`, 10

`renderEcharts4rBox`, 12, 149

`timeline-opts`, 149
`toJSON`, 69
`tooltip_action`, 150