

Package ‘emcAdr’

July 22, 2025

Type Package

Title Evolutionary Version of the Metropolis-Hastings Algorithm

Version 1.2

Date 2025-01-31

Author Jules Bangard [aut, cre] (ORCID:
<<https://orcid.org/0009-0007-4670-7860>>)

Maintainer Jules Bangard <jules.bangard@etu.unistra.fr>

Description Provides computational methods for detecting adverse high-order drug interactions from individual case safety reports using statistical techniques, allowing the exploration of higher-order interactions among drug cocktails.

License GPL-3

Imports Rcpp (>= 1.0.7), ggplot2, dplyr, umap, dbscan, stats

LinkingTo Rcpp, RcppArmadillo

RoxygenNote 7.2.3

LazyData true

Suggests knitr, rmarkdown, gridExtra

VignetteBuilder knitr

NeedsCompilation yes

Depends R (>= 3.5.0)

Repository CRAN

Date/Publication 2025-02-27 17:00:02 UTC

Contents

emcAdr-package	2
ATCtoNumeric	3
ATC_Tree_UpperBound_2024	3
calculate_divergence	4
clustering_genetic_algorithm	5
computeMetrics_size2	6

compute_hypergeom_on_list	7
compute_RR_on_list	8
csv_to_population	8
DistributionApproximation	9
FAERS_myopathy	11
GeneticAlgorithm	11
get_dissimilarity_from_cocktail_list	12
get_dissimilarity_from_genetic_results	13
get_dissimilarity_from_txt_file	14
hclust_genetic_solution	15
histogramToDitribution	16
hyperparam_test_genetic_algorithm	17
int_cocktail_to_string_cocktail	18
OutsandingScoreToDistribution	19
plot_evolution	20
plot_frequency	21
print_csv	22
p_value_cocktails	23
p_value_csv_file	24
p_value_genetic_results	25
p_value_on_sampled	26
qq_plot_output	27
string_list_to_int_cocktails	28
trueDistributionDrugs	29
trueDistributionSizeTwoCocktail	30
Index	32

emcAdr-package	<i>Evolutionary Version of the Metropolis-Hastings Algorithm</i>
----------------	--

Description

Provides computational methods for detecting adverse high-order drug interactions from individual case safety reports using statistical techniques, allowing the exploration of higher-order interactions among drug cocktails.

Author(s)

Jules Bangard [aut, cre] (<<https://orcid.org/0009-0007-4670-7860>>)
Maintainer: Jules Bangard <jules.bangard@etu.unistra.fr>

See Also

[Rcpp](#), [RcppArmadillo](#)

ATCtoNumeric	<i>Convert ATC Code for each patients to the corresponding DFS number of the ATC tree</i>
--------------	---

Description

Convert ATC Code for each patients to the corresponding DFS number of the ATC tree

Usage

```
ATCtoNumeric(patientATC, tree)
```

Arguments

- patientATC : patients observations, for each patient we got a string containing taken medications (ATC code)
- tree : ATC tree (we assume that there is a column 'ATCCode')

Value

a matrix of the same size as patientATC but containing integer that are the index of the corresponding ATC code.

Examples

```
ATC_code <- c('A01AA30 A01AB03', 'A10AC30')
ATCtoNumeric(ATC_code, ATC_Tree_UpperBound_2024)
```

ATC_Tree_UpperBound_2024	<i>ATC Tree Upper Bound 2024</i>
--------------------------	----------------------------------

Description

Example dataset representing the ATC tree structure, sourced from the WHO website (2024-02-23). This dataset is provided for demonstration and testing purposes with the package.

Usage

```
ATC_Tree_UpperBound_2024
```

Format

A data frame with 4 variables:

ATCCode The code of ATC nodes

Name The name of ATC nodes

ATC_length The number of characters in the ATCCode

upperBound The index of the last child node in the tree

Source

World Health Organization, ATC classification register

calculate_divergence	<i>Calculate the divergence between 2 distributions (the true Distribution and the learned one)</i>
----------------------	---

Description

Calculate the divergence between 2 distributions (the true Distribution and the learned one)

Usage

```
calculate_divergence(
  empirical_distribution,
  true_distribution,
  method = "TV",
  Filtered = FALSE
)
```

Arguments

empirical_distribution	A numeric vector of values representing the empirical distribution (return value of DistributionAproximation function)
true_distribution	A numeric vector of values representing the true distribution computed by the trueDistributionSizeTwoCocktail function
method	A string, either "TV" or "KL" to respectively use the total variation distance or the Kullback-Leibler divergence. (default = "TV")
Filtered	Should we use the filtered distribution or the normal one

Value

A numeric value representing the divergence of the 2 distributions

Examples

```

data("ATC_Tree_UpperBound_2024")
data("FAERS_myopathy")

estimated_score_distribution = DistributionApproximation(epochs = 10,
  ATCtree = ATC_Tree_UpperBound_2024,
  observations = FAERS_myopathy[1:100,], Smax = 2)

true_score_distribution = trueDistributionSizeTwoCocktail(ATCtree = ATC_Tree_UpperBound_2024,
  observations = FAERS_myopathy[1:100,], beta = 4)

divergence <- calculate_divergence(empirical_distribution = estimated_score_distribution,
  true_distribution = true_score_distribution)

```

```
clustering_genetic_algorithm
```

Clustering of the solutions of the genetic algorithm using the hclust algorithm

Description

Clustering of the solutions of the genetic algorithm using the hclust algorithm

Usage

```

clustering_genetic_algorithm(
  genetic_results,
  ATCtree,
  dist.normalize = TRUE,
  umap_config = NULL
)

```

Arguments

genetic_results	A list of cocktails in the form of integer vector
ATCtree	ATC tree with upper bound of the DFS
dist.normalize	Do we normalize the distance (so it belongs to [0;1])
umap_config	The configuration to use in order to project the cocktails in a smaller space (umap::umap.defaults by default)

Value

A dataframe containing UMAP 1/2 the two coordinates of each cocktails in the plane as well as the cluster number of each cocktails

Examples

```
data("ATC_Tree_UpperBound_2024")

results = GeneticAlgorithm(epochs = 10, nbIndividuals = 10,
  ATCtree = ATC_Tree_UpperBound_2024,
  observations = FAERS_myopathy)

hclust_genetic_solution(genetic_results = results,
  ATCtree = ATC_Tree_UpperBound_2024)
```

computeMetrics_size2 *Function used in the reference article to compare diverse Disproportionality Analysis metrics*

Description

Function used in the reference article to compare diverse Disproportionality Analysis metrics

Usage

```
computeMetrics_size2(CocktailList, ATCtree, observations, num_thread = 1L)
```

Arguments

CocktailList : A list of cocktails on which the Disproportionality analysis metrics should be computed

ATCtree : ATC tree with upper bound of the DFS (without the root)

observations : observation of the AE based on the medications of each patients (a DataFrame containing the medication on the first column and the ADR (boolean) on the second) on which we want to compute the risk distribution

num_thread : Number of thread to run in parallel if openMP is available, 1 by default

Value

Multiple DA metrics computed on CocktailList cocktails

Examples

```
data("ATC_Tree_UpperBound_2024")
data("FAERS_myopathy")

cocktails = list(c(561, 904),
  c(1902, 4585)) # only size 2 cocktails allowed for this function

scores_of_cocktails = computeMetrics_size2(CocktailList = cocktails,
  ATCtree = ATC_Tree_UpperBound_2024,
  observations = FAERS_myopathy[1:100,])
```

compute_hypergeom_on_list

Function used to compute the Hypergeometric score on a list of cocktails

Description

Function used to compute the Hypergeometric score on a list of cocktails

Usage

```
compute_hypergeom_on_list(cocktails, ATCtree, observations, num_thread = 1L)
```

Arguments

cocktails	: A list containing cocktails in the form of vector of integers (ATC index)
ATCtree	: ATC tree with upper bound of the DFS (without the root)
observations	: observation of the AE based on the medications of each patients (a DataFrame containing the medication on the first column and the ADR (boolean) on the second) on which we want to compute the risk distribution
num_thread	: Number of thread to run in parallel if openMP is available, 1 by default

Value

Hypergeometric score among "cocktails" parameters

Examples

[illegible]

compute_RR_on_list	<i>Function used to compute the Relative Risk on a list of cocktails</i>
--------------------	--

Description

Function used to compute the Relative Risk on a list of cocktails

Usage

```
compute_RR_on_list(cocktails, ATCtree, observations, num_thread = 1L)
```

Arguments

cocktails	: A list containing cocktails in the form of vector of integers (ATC index)
ATCtree	: ATC tree with upper bound of the DFS (without the root)
observations	: observation of the AE based on the medications of each patients (a DataFrame containing the medication on the first column and the ADR (boolean) on the second) on which we want to compute the risk distribution
num_thread	: Number of thread to run in parallel if openMP is available, 1 by default

Value

RR score among "cocktails" parameters

Examples

```
data("ATC_Tree_UpperBound_2024")
data("FAERS_myopathy")

cocktails = list(c(561, 904),
                 c(1902, 4585))

RR_of_cocktails = compute_RR_on_list(cocktails = cocktails,
                                     ATCtree = ATC_Tree_UpperBound_2024,
                                     observations = FAERS_myopathy)
```

csv_to_population	<i>Function used to convert your genetic algorithm results that are stored into a .csv file to a Data structure that can be used by the clustering algorithm</i>
-------------------	--

Description

Function used to convert your genetic algorithm results that are stored into a .csv file to a Data structure that can be used by the clustering algorithm

Usage

```
csv_to_population(ATC_name, filename, sep = ";")
```

Arguments

ATC_name	the ATC_name column of the ATC tree
filename	Name of the file where the results are located
sep	the separator to use when opening the csv file (',' by default)

Value

An R List that can be used by other algorithms (e.g. clustering algorithm)

Examples

```
data("ATC_Tree_UpperBound_2024")
genetic_results = csv_to_population(ATC_Tree_UpperBound_2024$Name,
                                   "path/to/output.csv")
```

DistributionApproximation

The MCMC method that runs the random walk on a single cocktail in order to estimate the distribution of score among cocktails of size Smax.

Description

The MCMC method that runs the random walk on a single cocktail in order to estimate the distribution of score among cocktails of size Smax.

Usage

```
DistributionApproximation(
  epochs,
  ATCtree,
  observations,
  temperature = 1L,
  nbResults = 5L,
  Smax = 2L,
  p_type1 = 0.01,
  beta = 4L,
  max_score = 500L,
  num_thread = 1L,
  verbose = FALSE
)
```

Arguments

epochs	: number of steps for the MCMC algorithm
ATCtree	: ATC tree with upper bound of the DFS (without the root, also see on the github repo for an example)
observations	: real observation of the AE based on the medications of each patients (a DataFrame containing the medication on the first column and the ADR (boolean) on the second)
temperature	: starting temperature, default = 1 (denoted T in the article)
nbResults	: Number of returned solution (Cocktail of size Smax with the best observed score during the run), 5 by default
Smax	: Size of the cocktail we approximate the distribution from
p_type1	: probability to operate type1 mutation. Note : the probability to operate the type 2 mutation is then 1 - P_type1. P_type1 must be in [0;1]. Default is .01
beta	: filter the minimum number of patients that must have taken the cocktail for his risk to be taken into account in the DistributionScoreBeta default is 4
max_score	: maximum number the score can take. Score greater than this one would be added to the distribution as the value max_score. Default is 500
num_thread	: Number of thread to run in parallel if openMP is available, 1 by default
verbose	: Output summary (default is false)

Value

I no problem, return a List containing : - ScoreDistribution : the distribution of the score as an array with each cells representing the number of risks = (index-1)/ 10 - Outstanding_score : An array of the score greater than max_score, - Best_cocktails : the nbResults bests cocktails encountered during the run. - Best_scores : Score corresponding to the bestCocktails. - FilteredDistribution : Distribution containing score for cocktails taken by at least beta patients. - Best_cocktails_beta : the nbResults bests cocktails taken by at least beta patients encountered during the run. - Best_scores_beta : Score corresponding to the bestCocktailsBeta. - cocktailSize : Smax parameter used during the run. ; Otherwise the list is empty

Examples

```
data("ATC_Tree_UpperBound_2024")
data("FAERS_myopathy")

estimation = DistributionApproximation(epochs = 10, ATCtree = ATC_Tree_UpperBound_2024,
  observations = FAERS_myopathy)
```

FAERS_myopathy	<i>FAERS Myopathy Dataset</i>
----------------	-------------------------------

Description

Example dataset representing drug intake and adverse event reports from FAERS. This dataset is provided to demonstrate the functionality of genetic and MCMC algorithms in the package.

Usage

```
FAERS_myopathy
```

Format

A data frame with 2 columns:

patientATC Drug intake for each patient as a vector of ATC tree indices

patientADR Indicates if the patient experienced myopathy as an adverse event

Source

Food & Drug Administration Event Reporting System (FAERS)

GeneticAlgorithm	<i>Genetic algorithm, trying to reach riskiest cocktails (the ones which maximize the fitness function, Hypergeometric score in our case)</i>
------------------	---

Description

Genetic algorithm, trying to reach riskiest cocktails (the ones which maximize the fitness function, Hypergeometric score in our case)

Usage

```
GeneticAlgorithm(
  epochs,
  nbIndividuals,
  ATCtree,
  observations,
  num_thread = 1L,
  diversity = FALSE,
  p_crossover = 0.8,
  p_mutation = 0.01,
  nbElite = 0L,
  tournamentSize = 2L,
  alpha = 1,
  summary = TRUE
)
```

Arguments

epochs	: number of step or the algorithm
nbIndividuals	: size of the population
ATCtree	: ATC tree with upper bound of the DFS (without the root)
observations	: real observation of the AE based on the medications of each patients (a DataFrame containing the medication on the first column and the ADR (boolean) on the second)
num_thread	: Number of thread to run in parallel if openMP is available, 1 by default
diversity	: enable the diversity mechanism of the algorithm (favor the diversity of cocktail in the population), default is false
p_crossover	: probability to operate a crossover on the crossover phase. Default is 80%
p_mutation	: probability to operate a mutation after the crossover phase. Default is 1%
nbElite	: number of best individual we keep from generation to generation. Default is 0
tournamentSize	: size of the tournament (select the best individual between tournamentSize sampled individuals)
alpha	: when making a type 1 mutation you have (alpha / size of cocktail) chance to add a drug.
summary	: print the summary of population at each steps ?

Value

If no problem, return a List : - meanFitnesses : The mean score of the population at each epochs of the algorithm. - BestFitnesses : The best score of the population at each epochs of the algorithm. - FinalPopulation : The final population of the algorithm when finished (medications and corresponding scores)

Examples

```
data("ATC_Tree_UpperBound_2024")
data("FAERS_myopathy")

results = GeneticAlgorithm(epochs = 10, nbIndividuals = 10,
                           ATCtree = ATC_Tree_UpperBound_2024,
                           observations = FAERS_myopathy)
```

```
get_dissimilarity_from_cocktail_list
```

Recover the square matrix of distance between cocktails where the index (i,j) of the matrix is the distance between cocktails i and j in an arbitrary cocktail list

Description

Recover the square matrix of distance between cocktails where the index (i,j) of the matrix is the distance between cocktails i and j in an arbitrary cocktail list

Usage

```
get_dissimilarity_from_cocktail_list(cocktails, ATCtree, normalization = TRUE)
```

Arguments

cocktails : A list of cocktails in the form of a vector of integer
 ATCtree : ATC tree with upper bound of the DFS (without the root)
 normalization : Do we keep the distance between cocktail in the range [0;1] ?

Value

The square matrix of distances between cocktails

Examples

```
data("ATC_Tree_UpperBound_2024")

cocktails = list(c(561, 904),
                 c(1902, 4585)) # only size 2 cocktails allowed for this function

distance_matrix = get_dissimilarity_from_cocktail_list(cocktails = cocktails,
                                                       ATCtree = ATC_Tree_UpperBound_2024,
                                                       normalization = TRUE)
```

```
get_dissimilarity_from_genetic_results
```

Recover the square matrix of distance between cocktails where the index (i,j) of the matrix is the distance between cocktails i and j in the genetic_results list.

Description

Recover the square matrix of distance between cocktails where the index (i,j) of the matrix is the distance between cocktails i and j in the genetic_results list.

Usage

```
get_dissimilarity_from_genetic_results(genetic_results, ATCtree, normalization)
```

Arguments

genetic_results the List returned by the genetic algorithm.

ATCtree : ATC tree with upper bound of the DFS (without the root)

normalization : Do we keep the distance between cocktail in the range [0;1] ?

Value

The square matrix of distances between cocktails

Examples

```
data("ATC_Tree_UpperBound_2024")
data("FAERS_myopathy")

genetic_results = GeneticAlgorithm(epochs = 10, nbIndividuals = 10,
                                   ATCtree = ATC_Tree_UpperBound_2024,
                                   observations = FAERS_myopathy)
distance_matrix = get_dissimilarity_from_genetic_results(genetic_results = genetic_results,
                                                         ATCtree = ATC_Tree_UpperBound_2024, normalization = TRUE)
```

get_dissimilarity_from_txt_file

Recover the square matrix of distance between cocktails where the index (i,j) of the matrix is the distance between cocktails i and j in the csv file containing results of genetic algorithm

Description

Recover the square matrix of distance between cocktails where the index (i,j) of the matrix is the distance between cocktails i and j in the csv file containing results of genetic algorithm

Usage

```
get_dissimilarity_from_txt_file(filename, ATCtree, normalization = TRUE)
```

Arguments

filename : the name of the file returned by the print_csv function.

ATCtree : ATC tree with upper bound of the DFS (without the root)

normalization : Do we keep the distance between cocktail in the range [0;1] ?

Value

The square matrix of distances between cocktails

Examples

```
data("ATC_Tree_UpperBound_2024")

distance_matrix = get_dissimilarity_from_txt_file(filename = '250e_700ind_0.2mr_0ne_2alpha.txt',
          ATCtree = ATC_Tree_UpperBound_2024, normalization = TRUE)
```

```
hclust_genetic_solution
```

Clustering of the solutions of the genetic algorithm using the hclust algorithm

Description

Clustering of the solutions of the genetic algorithm using the hclust algorithm

Usage

```
hclust_genetic_solution(
  genetic_results,
  ATCtree,
  dist.normalize = TRUE,
  method = "complete"
)
```

Arguments

genetic_results	The return value of the genetic algorithm
ATCtree	ATC tree with upper bound of the DFS
dist.normalize	Do we normalize the distance (so it belongs to [0;1])
method	(from hclust function) the agglomeration method to be used. This should be (an unambiguous abbreviation of) one of "ward.D", "ward.D2", "single", "complete", "average" (= UPGMA), "mcquitty" (= WPGMA), "median" (= WPGMC) or "centroid" (= UPGMC).

Value

the hierarchical clustering of the results of the genetic algorithm

Examples

```
data("ATC_Tree_UpperBound_2024")
data("FAERS_myopathy")

results = GeneticAlgorithm(epochs = 10, nbIndividuals = 10,
          ATCtree = ATC_Tree_UpperBound_2024,
```

```

      observations = FAERS_myopathy)

hclust_genetic_solution(genetic_results = results,
      ATCtree = ATC_Tree_UpperBound_2024)

```

histogramToDitribution

Convert the histogram returned by the DistributionApproximation function, to a real number distribution (that can be used in a test for example)

Description

Convert the histogram returned by the DistributionApproximation function, to a real number distribution (that can be used in a test for example)

Usage

```
histogramToDitribution(vec)
```

Arguments

vec : distribution returned by the DistributionAproximationFunction

Value

A vector containing sampled risk during the MCMC algorithm

Examples

```

data("ATC_Tree_UpperBound_2024")
data("FAERS_myopathy")

DistributionApproximationResults = DistributionApproximation(epochs = 10,
      ATCtree = ATC_Tree_UpperBound_2024, observations = FAERS_myopathy)
histogramToDitribution(DistributionApproximationResults$ScoreDistribution)

```

hyperparam_test_genetic_algorithm

This function can be used in order to try different set of parameters for the genetic algorithm in a convenient way. This will run each combination of mutation_rate, nb_elite and alphas possible nb_test_desired times. For each sets of parameters, results will be saved in a file named according to the set of parameter. One can regroup the results of each run in a csv file by using the print_csv function specifying the names of each file that needs to be treated and the number of performed runs on each parameter set

Description

This function can be used in order to try different set of parameters for the genetic algorithm in a convenient way. This will run each combination of mutation_rate, nb_elite and alphas possible nb_test_desired times. For each sets of parameters, results will be saved in a file named according to the set of parameter. One can regroup the results of each run in a csv file by using the print_csv function specifying the names of each file that needs to be treated and the number of performed runs on each parameter set

Usage

```
hyperparam_test_genetic_algorithm(
  epochs,
  nb_individuals,
  ATCtree,
  observations,
  nb_test_desired,
  mutation_rate,
  nb_elite,
  alphas,
  path = "./",
  num_thread = 1L
)
```

Arguments

epochs : the number of epochs for the genetic algorithm

nb_individuals : the size of the population in the genetic algorithm

ATCtree : ATC tree with upper bound of the DFS (without the root)

observations : observation of the AE based on the medications of each patients (a DataFrame containing the medication on the first column and the ADR (boolean) on the second) on which we want to compute the risk distribution

nb_test_desired : number of genetic algorithm runs on each sets of parameters

mutation_rate : a vector with each mutation_rate to be tested

nb_elite : a vector with each nb_elite to be tested
 alphas : a vector with each alphas to be tested
 path : the path where the resulting files should be written
 num_thread : Number of thread to run in parallel if openMP is available, 1 by default

Value

No return value, this function should output results of the runs of the genetic algorithm in a specific format supported by function print_csv and p_value_csv_file. The files are outputted in path which is current directory by default.

Examples

```

data("ATC_Tree_UpperBound_2024")
data("FAERS_myopathy")

# different parameter to test for
mutation_rate = c(.1,.2,.3)
nb_elite = c(0,1,2)
alphas = c(0.5,1,2)
hyperparam_test_genetic_algorithm(epochs = 2, nb_individuals = 2,
                                   ATCtree = ATC_Tree_UpperBound_2024,
                                   observations = FAERS_myopathy,
                                   nb_test_desired = 5, mutation_rate = mutation_rate,
                                   nb_elite = nb_elite, alphas = alphas)

```

int_cocktail_to_string_cocktail

Function used to convert integer cocktails (like the one outputted by the distributionApproximation function) to string cocktail in order to make them more readable

Description

Function used to convert integer cocktails (like the one outputted by the distributionApproximation function) to string cocktail in order to make them more readable

Usage

```
int_cocktail_to_string_cocktail(cocktails, ATC_name)
```

Arguments

cocktails cocktails vector to be converted (index in the ATC tree)
 ATC_name The ATC_name column of the ATC tree

Value

The name of integer cocktails in cocktails

Examples

```
data("ATC_Tree_UpperBound_2024")
int_list = list(c(561, 904),
               c(1902, 4585))
int_cocktail_to_string_cocktail(int_list, ATC_Tree_UpperBound_2024$Name)
```

OutstandingScoreToDistribution

Output the outstanding score (Outstanding_score) outputed by the MCMC algorithm in a special format

Description

Output the outstanding score (Outstanding_score) outputed by the MCMC algorithm in a special format

Usage

```
OutstandingScoreToDistribution(outstanding_score, max_score)
```

Arguments

```
outstanding_score
    : Outstanding_score outputed by MCMC algorithm to be converted to the Score-
    Distribution format
max_score
    : max_score parameter used during the MCMC algorithm
```

Value

outstanding_score in a format compatible with MCMC algorithm output

Examples

```
data("ATC_Tree_UpperBound_2024")
data("FAERS_myopathy")

DistributionApproximationResults = DistributionApproximation(epochs = 10,
  ATCtree = ATC_Tree_UpperBound_2024, observations = FAERS_myopathy)
OutstandingScoreToDistribution(DistributionApproximationResults$Outstanding_score, max_score = 100)
```

plot_evolution	<i>Plot the evolution of the mean and the best value of the population used by the GeneticAlgorithm</i>
----------------	---

Description

Plot the evolution of the mean and the best value of the population used by the GeneticAlgorithm

Usage

```
plot_evolution(  
  list,  
  mean_color = "#F2A900",  
  best_color = "#008080",  
  xlab = "Epochs",  
  ylab = "Score"  
)
```

Arguments

list	A list with 2 elements returned by the GeneticAlgorithm: "mean" and "best", containing the numeric vectors representing the mean and best fitness of the population
mean_color	A string specifying the color of the mean values
best_color	A string specifying the color of the best values
xlab	A string specifying the label for the x-axis
ylab	A string specifying the label for the y-axis

Value

no returned value, should plot the evolution of the genetic algorithm results (mean/max score for each epoch).

Examples

```
data("ATC_Tree_UpperBound_2024")  
data("FAERS_myopathy")  
  
results = GeneticAlgorithm(epochs = 10, nbIndividuals = 10,  
  ATCtree = ATC_Tree_UpperBound_2024,  
  observations = FAERS_myopathy)  
  
plot_evolution(list = results)
```

plot_frequency	<i>Plot the histogram of the approximation of the RR distribution</i>
----------------	---

Description

Plot the histogram of the approximation of the RR distribution

Usage

```
plot_frequency(
  estimated,
  sqrt = FALSE,
  binwidth = 0.1,
  hist_color = "#69b3a2",
  density_color = "#FF5733",
  xlab = "Score"
)
```

Arguments

estimated	The ScoreDistribution element in the list returned by the DistributionApproximation function
sqrt	A Boolean to specify whether we normalize the estimated or not, it is recommended on large random walk.
binwidth	The width of the histogram bins
hist_color	The fill color for the histogram bars
density_color	The color for the density curve
xlab	Label of X axis

Value

no returned value, should plot the histogram of the estimated distribution (estimated).

Examples

```
data("ATC_Tree_UpperBound_2024")
data("FAERS_myopathy")

estimation = DistributionApproximation(epochs = 10, ATCtree = ATC_Tree_UpperBound_2024,
  observations = FAERS_myopathy)

plot_frequency(estimated = estimation$ScoreDistribution)
```

print_csv	<i>Print every cocktails found during the genetic algorithm when used with the hyperparam_test_genetic_algorithm function. This enables to condense the solutions found in each files by collapsing similar cocktail in a single row by cocktail.</i>
-----------	---

Description

Print every cocktails found during the genetic algorithm when used with the hyperparam_test_genetic_algorithm function. This enables to condense the solutions found in each files by collapsing similar cocktail in a single row by cocktail.

Usage

```
print_csv(
  input_filenames,
  observations,
  repetition,
  ATCtree,
  csv_filename = "solutions.csv"
)
```

Arguments

input_filenames	
observations	: A List containing filename of hyperparam_test_genetic_algorithm output file
repetition	: observation of the AE based on the medications of each patients (a DataFrame containing the medication on the first column and the ADR (boolean) on the second) on which we want to compute the risk distribution
ATCtree	: The parameter nb_test_desired used in the hyperparam test function
csv_filename	: ATC tree with upper bound of the DFS (without the root)
	: Name of the output file, "solutions.csv" by default

Value

No return value, should process the output of the genetic algorithm in files produced by hyperparam_test_genetic_algorithm and output a summary csv file. The csv file is outputted in current directory and named after the csv_filename variable (solutions.csv by default).

Examples

```
data("ATC_Tree_UpperBound_2024")
data("FAERS_myopathy")
files = c('250e_700ind_0.2mr_0ne_2alpha.txt') # results of hyperparam_test_genetic_algorithm

print_csv(input_filenames = files, observations = FAERS_myopathy,
          repetition = 5, ATCtree = ATC_Tree_UpperBound_2024)
```

p_value_cocktails	<i>Used to add the p_value to each cocktail of cocktail list</i>
-------------------	--

Description

Used to add the p_value to each cocktail of cocktail list

Usage

```
p_value_cocktails(
  distribution_outputs,
  cocktails,
  ATCtree,
  observations,
  num_thread = 1L,
  filtred_distribution = FALSE
)
```

Arguments

distribution_outputs	A list of distribution of cocktails of different sizes in order to compute the p_value for multiple cocktail sizes
cocktails	A list containing cocktails in the form of vector of integers (ATC index)
ATCtree	ATC tree with upper bound of the DFS (without the root)
observations	observation of the AE based on the medications of each patients (a DataFrame containing the medication on the first column and the ADR (boolean) on the second) on which we want to compute the risk distribution
num_thread	Number of thread to run in parallel if openMP is available, 1 by default
filtred_distribution	Does the p-values have to be computed using filtered distribution or normal distribution (filtered distribution by default)

Value

A real valued number vector representing the p-value of the inputted cocktails computed on the distribution_outputs List.

Examples

```
data("ATC_Tree_UpperBound_2024")
data("FAERS_myopathy")

DistributionApproximationResults_size2 = DistributionApproximation(epochs = 10,
  ATCtree = ATC_Tree_UpperBound_2024, observations = FAERS_myopathy, Smax = 2)

DistributionApproximationResults_size3 = DistributionApproximation(epochs = 10,
```

```
ATCtree = ATC_Tree_UpperBound_2024, observations = FAERS_myopathy, Smax = 3)

score_distribution_list = list(DistributionApproximationResults_size2,
                              DistributionApproximationResults_size3)

cocktails = list(c(561, 904),
                 c(1902, 4585))

p_value_cocktails(score_distribution_list, cocktails, ATC_Tree_UpperBound_2024,
                  FAERS_myopathy)
```

<code>p_value_csv_file</code>	<i>Used to add the p_value to each cocktail of a csv_file that is an output of the genetic algorithm</i>
-------------------------------	--

Description

Used to add the p_value to each cocktail of a csv_file that is an output of the genetic algorithm

Usage

```
p_value_csv_file(
  distribution_outputs,
  filename,
  filtred_distribution = FALSE,
  sep = ";"
)
```

Arguments

- `distribution_outputs` A list of distribution of cocktails of different sizes in order to compute the p_value for multiple cocktail sizes
- `filename` The file name of the .csv file containing the output
- `filtred_distribution` Does the p-values have to be computed using filtered distribution or normal distribution (filtered distribution by default)
- `sep` The separator used in the csv file (',' by default)

Value

A real valued number vector representing the p-value of the inputed csv file filename, computed on the `distribution_outputs` List.

Examples

```
data("ATC_Tree_UpperBound_2024")
data("FAERS_myopathy")

DistributionApproximationResults_size2 = DistributionApproximation(epochs = 10,
  ATCtree = ATC_Tree_UpperBound_2024, observations = FAERS_myopathy, Smax = 2)

DistributionApproximationResults_size3 = DistributionApproximation(epochs = 10,
  ATCtree = ATC_Tree_UpperBound_2024, observations = FAERS_myopathy, Smax = 3)

score_distribution_list = list(DistributionApproximationResults_size2,
  DistributionApproximationResults_size3)
p_value_csv_file(score_distribution_list, "path/to/output.csv")
```

p_value_genetic_results

Used to add the p_value to each cocktail of an output of the genetic algorithm

Description

Used to add the p_value to each cocktail of an output of the genetic algorithm

Usage

```
p_value_genetic_results(
  distribution_outputs,
  genetic_results,
  filtred_distribution = FALSE
)
```

Arguments

distribution_outputs

A list of distribution of cocktails of different sizes in order to compute the p_value for multiple cocktail sizes

genetic_results

outputs of the genetic algorithm

filtred_distribution

Does the p-values have to be computed using filtered distribution or normal distribution (filtered distribution by default)

Value

A real valued number vector representing the p-value of the inputed genetic algorithm results (genetic_results) computed on the distribution_outputs List.

Examples

```

data("ATC_Tree_UpperBound_2024")
data("FAERS_myopathy")
DistributionApproximationResults_size2 = DistributionApproximation(epochs = 10,
  ATCtree = ATC_Tree_UpperBound_2024, observations = FAERS_myopathy, Smax = 2)

DistributionApproximationResults_size3 = DistributionApproximation(epochs = 10,
  ATCtree = ATC_Tree_UpperBound_2024, observations = FAERS_myopathy, Smax = 3)

score_distribution_list = list(DistributionApproximationResults_size2,
  DistributionApproximationResults_size3)
genetic_results = GeneticAlgorithm(epochs = 10, nbIndividuals = 20,
  ATCtree = ATC_Tree_UpperBound_2024,
  observations = FAERS_myopathy)
p_value_genetic_results(score_distribution_list, genetic_results)

```

<code>p_value_on_sampled</code>	<i>Calculate p-value of sampled value</i>
---------------------------------	---

Description

Calculate p-value of sampled value

Usage

```

p_value_on_sampled(
  empirical_distribution,
  sampled_values,
  isFiltered = FALSE,
  includeZeroValue = FALSE
)

```

Arguments

<code>empirical_distribution</code>	A numeric vector of values representing the empirical distribution (return value of DistributionAproximation function)
<code>sampled_values</code>	A scalar or a vector of real valued number representing the sampled value (score to be tested)
<code>isFiltered</code>	A boolean representing if we want to use the filtered distribution or the distribution as is (False by default)
<code>includeZeroValue</code>	A boolean that indicate if you want to take into account the null score (False by default)

Value

A numeric value representing the empirical p-value

Examples

```
data("ATC_Tree_UpperBound_2024")
data("FAERS_myopathy")

cocktails = list(c(561, 904),
                 c(1902, 4585))

estimated_score_distribution = DistributionApproximation(epochs = 10,
  ATCtree = ATC_Tree_UpperBound_2024,
  observations = FAERS_myopathy)

Hypergeom_of_cocktails = compute_hypergeom_on_list(cocktails = cocktails,
  ATCtree = ATC_Tree_UpperBound_2024,
  observations = FAERS_myopathy)

p_value = p_value_on_sampled(empirical_distribution = estimated_score_distribution,
  sampled_values = Hypergeom_of_cocktails)
```

qq_plot_output	<i>Make a Quantile-Quantile diagram from the output of the MCMC algorithm (DistributionAproximation) and the algorithm that exhaustively calculates the distribution</i>
----------------	--

Description

Make a Quantile-Quantile diagram from the output of the MCMC algorithm (DistributionAproximation) and the algorithm that exhaustively calculates the distribution

Usage

```
qq_plot_output(estimated, true, filtered = FALSE, color = "steelblue")
```

Arguments

estimated	Outputed object of DistributionApproximation function
true	Outputed object of either DistributionApproximation function or True distribution computation function
filtered	Make use of the classic distribuion estimation or of the filtred one (number of patient taking the cocktail > beta)
color	The color of the dashed line of the qq-plot

Value

no returned value, should plot the quantile-quantile plot of the estimated distribution (estimated) vs the true distribution (true).

Examples

```
data("ATC_Tree_UpperBound_2024")
data("FAERS_myopathy")

estimated_score_distribution = DistributionApproximation(epochs = 10,
  ATCtree = ATC_Tree_UpperBound_2024,
  observations = FAERS_myopathy[1:100,], Smax =2)

true_score_distribution = trueDistributionSizeTwoCocktail(ATCtree = ATC_Tree_UpperBound_2024,
  observations = FAERS_myopathy[1:100,], beta = 4)

qq_plot_output(estimated = estimated_score_distribution,
  true = true_score_distribution)
```

```
string_list_to_int_cocktails
```

Function used to convert a string vector of drugs in form "drug1:drug2" to a vector of index of the ATC tree ex: c(ATC_index(drug1), ATC_index(drugs2))

Description

Function used to convert a string vector of drugs in form "drug1:drug2" to a vector of index of the ATC tree ex: c(ATC_index(drug1), ATC_index(drugs2))

Usage

```
string_list_to_int_cocktails(ATC_name, lines)
```

Arguments

ATC_name	the ATC_name column of the ATC tree
lines	A string vector of drugs cocktail in the form "drug1:drug2:...:drug_n"

Value

An R List that can be used by other algorithms (e.g. clustering algorithm)

Examples

```
data("ATC_Tree_UpperBound_2024")
string_list = c('hmg coa reductase inhibitors:nervous system',
                'metformin:prasugrel')
string_list_to_int_cocktails(ATC_Tree_UpperBound_2024$Name,
                             string_list)
```

trueDistributionDrugs *The true distribution of the score among every single nodes of the ATC*

Description

The true distribution of the score among every single nodes of the ATC

Usage

```
trueDistributionDrugs(
  ATCtree,
  observations,
  beta,
  max_score = 1000L,
  nbResults = 100L,
  num_thread = 1L
)
```

Arguments

ATCtree	: ATC tree with upper bound of the DFS (without the root)
observations	: observation of the AE based on the medications of each patients (a DataFrame containing the medication on the first column and the ADR (boolean) on the second) on which we want to compute the risk distribution
beta	: minimum number of person taking the cocktails in order to consider it in the beta score distribution
max_score	: maximum number the score can take. Score greater than this one would be added to the distribution as the value max_score. Default is 1000
nbResults	: Number of returned solution (Cocktail with the best observed score during the run), 100 by default
num_thread	: Number of thread to run in parallel if openMP is available, 1 by default

Value

Return a List containing : - ScoreDistribution : the distribution of the score as an array with each cells representing the number of risks = (index-1)/ 10 - Filtered_score_distribution : Distribution containing score for cocktails taken by at least beta patients. - Outstanding_score : An array of the score greater than max_score, - Best_cocktails : the nbResults bests cocktails encountered during

the run. - Best_cocktails_beta : the nbResults bests cocktails taken by at least beta patients encountered during the run. - Best_scores : Score corresponding to the Best_cocktails. - Best_scores_beta : Score corresponding to the Best_cocktails_beta.

Examples

```
data("ATC_Tree_UpperBound_2024")
data("FAERS_myopathy")

size_1_score_distribution = trueDistributionDrugs(ATCtree = ATC_Tree_UpperBound_2024,
  observations = FAERS_myopathy[1:100,], beta = 4)
```

trueDistributionSizeTwoCocktail

The true distribution of the score among every size-two cocktails

Description

The true distribution of the score among every size-two cocktails

Usage

```
trueDistributionSizeTwoCocktail(
  ATCtree,
  observations,
  beta,
  max_score = 100L,
  nbResults = 100L,
  num_thread = 1L
)
```

Arguments

ATCtree	: ATC tree with upper bound of the DFS (without the root)
observations	: observation of the AE based on the medications of each patients (a DataFrame containing the medication on the first column and the ADR (boolean) on the second) on which we want to compute the risk distribution
beta	: minimum number of person taking the cocktails in order to consider it in the beta score distribution
max_score	: maximum number the score can take. Score greater than this one would be added to the distribution as the value max_score. Default is 1000
nbResults	: Number of returned solution (Cocktail with the best observed score during the run), 100 by default
num_thread	: Number of thread to run in parallel if openMP is available, 1 by default

Value

Return a List containing : - `ScoreDistribution` : the distribution of the score as an array with each cells representing the number of risks = (index-1)/ 10 - `Filtered_score_distribution` : Distribution containing score for cocktails taken by at least beta patients. - `Outstanding_score` : An array of the score greater than `max_score`, - `Best_cocktails` : the `nbResults` bests cocktails encountered during the run. - `Best_cocktails_beta` : the `nbResults` bests cocktails taken by at least beta patients encountered during the run. - `Best_scores` : Score corresponding to the `Best_cocktails`. - `Best_scores_beta` : Score corresponding to the `Best_cocktails_beta`.

Examples

```
data("ATC_Tree_UpperBound_2024")
data("FAERS_myopathy")

size_2_score_distribution = trueDistributionSizeTwoCocktail(ATCtree = ATC_Tree_UpperBound_2024,
  observations = FAERS_myopathy[1:100,], beta = 4)
```

Index

- * **datasets**
 - ATC_Tree_UpperBound_2024, [3](#)
 - FAERS_myopathy, [11](#)
- * **package**
 - emcAdr-package, [2](#)
- ATC_Tree_UpperBound_2024, [3](#)
- ATCtoNumeric, [3](#)
- calculate_divergence, [4](#)
- clustering_genetic_algorithm, [5](#)
- compute_hypergeom_on_list, [7](#)
- compute_RR_on_list, [8](#)
- computeMetrics_size2, [6](#)
- csv_to_population, [8](#)
- DistributionApproximation, [9](#)
- emcAdr (emcAdr-package), [2](#)
- emcAdr-package, [2](#)
- FAERS_myopathy, [11](#)
- GeneticAlgorithm, [11](#)
- get_dissimilarity_from_cocktail_list, [12](#)
- get_dissimilarity_from_genetic_results, [13](#)
- get_dissimilarity_from_txt_file, [14](#)
- hclust_genetic_solution, [15](#)
- histogramToDitribution, [16](#)
- hyperparam_test_genetic_algorithm, [17](#)
- int_cocktail_to_string_cocktail, [18](#)
- OutsandingScoreToDistribution, [19](#)
- p_value_cocktails, [23](#)
- p_value_csv_file, [24](#)
- p_value_genetic_results, [25](#)
- p_value_on_sampled, [26](#)
- plot_evolution, [20](#)
- plot_frequency, [21](#)
- print_csv, [22](#)
- qq_plot_output, [27](#)
- Rcpp, [2](#)
- RcppArmadillo, [2](#)
- string_list_to_int_cocktails, [28](#)
- trueDistributionDrugs, [29](#)
- trueDistributionSizeTwoCocktail, [30](#)