

Package ‘eponge’

July 22, 2025

Type Package

Title Keep Your Environment Clean

Version 0.1.0

Description Provides a set of functions, which facilitates removing objects from an environment. It allows to delete objects specified with regular expression or with other conditions (e.g. if object is numeric), using one function call.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

BugReports <https://github.com/krzjoa/eponge/issues>

URL <https://github.com/krzjoa/eponge>, <https://krzjoa.github.io/eponge/>

RoxygenNote 6.1.1

Suggests testthat

Imports rlang

NeedsCompilation no

Author Krzysztof Joachimiak [aut, cre] (ORCID:
<<https://orcid.org/0000-0003-4780-7947>>)

Maintainer Krzysztof Joachimiak <joachimiak.krzysztof@gmail.com>

Repository CRAN

Date/Publication 2020-03-24 15:30:08 UTC

Contents

eponge-package	2
erase	2
erase_data	3
erase_df	4
erase_functions	4
erase_if	5

erase_masking	6
erase_non_functions	7
erase_values	8

Index	9
-------	---

eponge-package	Package eponge
----------------	----------------

Description

Provides a set of functions, which facilitates removing objects from an environment. It allows to delete objects specified with regular expression or with other conditions (e.g. if object is numeric), using one function call.

Author(s)

Krzysztof Joachimiak

erase	Remove (all) objects from environment
-------	---------------------------------------

Description

Remove (all) objects from environment

Usage

erase(pattern = NULL, envir = parent.frame(), verbose = FALSE)

Arguments

pattern	regex pattern to select a set of objects; default: NULL
envir	environment; default: caller environment
verbose	print removed objects' names

Details

Function can be used with envir = globalenv() argument.

Value

NULL (function returns nothing)

Examples

```

create_data <- function() data.frame(a = 1:10, b = 11:20)
x <- cars
y <- 1:20
z <- function(x) x + 2
# Typically, we don't have to specify environment
erase()
ls()

```

erase_data	<i>Remove all objects, which are listed in 'Data' section in RStudio</i>
------------	--

Description

Remove all objects, which are listed in 'Data' section in RStudio

Usage

```
erase_data(pattern = NULL, envir = parent.frame(), verbose = FALSE)
```

Arguments

pattern	regex pattern to select a set of objects; default: NULL
envir	environment; default: caller environment
verbose	print removed objects' names

Details

Function can be used with `envir = globalenv()` argument.

Value

NULL (function returns nothing)

Examples

```

cars.2 <- cars
test_fun <- function(x) x + 2
value <- 7
erase_data(verbose = TRUE)

```

erase_df	<i>Remove all the 'data.frame' objects</i>
----------	--

Description

Remove all the 'data.frame' objects

Usage

```
erase_df(pattern = NULL, envir = parent.frame(), verbose = FALSE)
```

Arguments

pattern	regex pattern to select a set of objects; default: NULL
envir	environment; default: caller environment
verbose	print removed objects' names

Details

Function can be used with `envir = globalenv()` argument.

Value

NULL (function returns nothing)

Examples

```
cars.2 <- cars
test_fun <- function(x) x + 2
value <- 7
erase_df(verbose = TRUE)
```

erase_functions	<i>Remove (all) functions from environment</i>
-----------------	--

Description

Remove (all) functions from environment

Usage

```
erase_functions(pattern = NULL, envir = parent.frame(),
  verbose = FALSE)
```

Arguments

pattern	regex pattern to select a set of objects; default: NULL
envir	environment; default: caller environment
verbose	print removed objects' names

Details

Function can be used with `envir = globalenv()` argument. Be careful: uncontrolled use may cause undesired side effects.

Value

NULL (function returns nothing)

Examples

```
create_data <- function() data.frame(a = 1:10, b = 11:20)
x <- cars
y <- 1:20
z <- function(x) x +2
erase_functions()
ls()
```

`erase_if`*Remove objects, which fulfill determined conditions*

Description

Remove objects, which fulfill determined conditions

Usage

```
erase_if(condition, pattern = NULL, envir = parent.frame(),
  verbose = FALSE)
```

Arguments

condition	function or lambda expression (one side formula)
pattern	regex pattern to select a set of objects; default: NULL
envir	environment; default: caller environment
verbose	print removed objects' names

Details

Function can be used with `envir = globalenv()` argument.

Value

NULL (function returns nothing)

Examples

```
create_data <- function() data.frame(a = 1:10, b = 11:20)
x <- cars
y <- 1:20
z <- function(x) x +2
l <- list(1,2,3,4)
erase_if(is.list)
ls()
# You may use lambda expression
create_data <- function() data.frame(a = 1:10, b = 11:20)
x <- cars
y <- 1:20
z <- function(x) x +2
l <- list(1,2,3,4)
erase_if(~ is.function(.x) | is.data.frame(.x))
ls()
```

erase_masking	<i>Erase objects from GlobalEnv, which are masking objects from attached packages</i>
---------------	---

Description

Erase objects from GlobalEnv, which are masking objects from attached packages

Usage

```
erase_masking(pattern = NULL, verbose = FALSE)
```

```
erase_masking_functions(pattern = NULL, verbose = FALSE)
```

Arguments

pattern	a regex pattern
verbose	print removed objects' names

Details

We have to highlight, that for now it only allows us to remove objects from the Global Environment. Be careful: uncontrolled use may cause undesired side effects.

Value

NULL (function returns nothing)

Examples

```
# It works only if objects are assigned in the global environment
matrix <- matrix(0, 3, 3)
gamma <- 0.9
erase_masking()
```

erase_non_functions	<i>Remove all the objects, that are not functions</i>
---------------------	---

Description

Remove all the objects, that are not functions

Usage

```
erase_non_functions(pattern = NULL, envir = parent.frame(),
  verbose = FALSE)
```

Arguments

pattern	regex pattern to select a set of objects; default: NULL
envir	environment; default: caller environment
verbose	print removed objects' names

Details

Function can be used with `envir = globalenv()` argument.

Value

NULL (function returns nothing)

Examples

```
cars.2 <- cars
test_fun <- function(x) x + 2
value <- 7
erase_non_functions(verbose = TRUE)
```

`erase_values`*Remove all objects, which are listed in ‘Values’ section in RStudio*

Description

Remove all objects, which are listed in ‘Values’ section in RStudio

Usage

```
erase_values(pattern = NULL, envir = parent.frame(), verbose = FALSE)
```

Arguments

<code>pattern</code>	regex pattern to select a set of objects; default: NULL
<code>envir</code>	environment; default: caller environment
<code>verbose</code>	print removed objects’ names

Details

Function can be used with `envir = globalenv()` argument.

Value

NULL (function returns nothing)

Examples

```
cars.2 <- cars
test_fun <- function(x) x + 2
value <- 7
erase_values(verbose = TRUE)
```

Index

* **package**

 eponge-package, [2](#)

eponge (eponge-package), [2](#)

eponge-package, [2](#)

erase, [2](#)

erase_data, [3](#)

erase_df, [4](#)

erase_functions, [4](#)

erase_if, [5](#)

erase_masking, [6](#)

erase_masking_functions
 (erase_masking), [6](#)

erase_non_functions, [7](#)

erase_values, [8](#)