

Package ‘gfonts’

July 22, 2025

Title Offline 'Google' Fonts for 'Markdown' and 'Shiny'

Version 0.2.0

Description Download 'Google' fonts and generate 'CSS' to use in 'rmarkdown' documents and 'shiny' applications. Some popular fonts are included and ready to use.

URL <https://dreamrs.github.io/gfonts/>,
<https://github.com/dreamRs/gfonts>

BugReports <https://github.com/dreamRs/gfonts/issues>

License GPL-3

Encoding UTF-8

LazyData true

Depends R (>= 2.10)

Imports utils, htmltools, shiny, crul, jsonlite, glue, crayon

RoxygenNote 7.2.2

Suggests knitr, rmarkdown, testthat (>= 2.1.0), vcr, covr

VignetteBuilder knitr

NeedsCompilation no

Author Victor Perrier [aut, cre],
Fanny Meyer [aut],
Mario Ranftl [ctb, cph] (google-webfonts-helper)

Maintainer Victor Perrier <victor.perrier@dreamrs.fr>

Repository CRAN

Date/Publication 2023-01-08 18:50:02 UTC

Contents

download_font	2
generate_css	3
get_all_fonts	4
get_font_info	5

gfonts	5
included_fonts	6
setup_font	6
tag_example	8
use_font	8
use_pkg_gfont	10
Index	12

download_font	<i>Download font files</i>
---------------	----------------------------

Description

Download font files

Usage

download_font(id, output_dir, variants = NULL, ..., http_options = list())

Arguments

- id Id of the font, correspond to column id from [get_all_fonts](#).
- output_dir Output directory where to save font files.
- variants Variant(s) to download, default is to includes all available ones.
- ... Additional parameters to API query.
- http_options Arguments passed to `curl::HttpClient$new`.

Value

a character vector of the filepaths extracted to, invisibly.

Examples

```
if (interactive()) {  
  
  # For example, we use a temporary directory  
  path_to_dir <- tempfile()  
  dir.create(path_to_dir)  
  
  # Download Roboto font  
  download_font(  
    id = "roboto",  
    output_dir = path_to_dir  
  )  
  
  # Get only regular, italic and bold  
  download_font(  
    id = "roboto",
```

```

    output_dir = path_to_dir,
    variants = c("regular", "300italic", "700")
)

# Clean up
unlink(path_to_dir, recursive = TRUE)

}

```

generate_css

*Generate CSS to import fonts***Description**

Generate CSS to import fonts

Usage

```

generate_css(
  id,
  variants = NULL,
  subsets = NULL,
  output = NULL,
  font_dir = "../fonts/",
  prefer_local_source = TRUE,
  browser_support = c("best", "modern"),
  ...
)

```

Arguments

id	Id of the font, correspond to column id from get_all_fonts .
variants	Variant of font to use.
subsets	Subsets to use.
output	Specifies path to output file for CSS generated.
font_dir	Fonts directory relative to output.
prefer_local_source	Generate CSS font-face rules in which user installed fonts are preferred. Use FALSE if you want to force the use of the downloaded font.
browser_support	Browser to support, choose "best" to support old browser or "modern" for only recent ones.
...	Arguments passed to <code>curl::HttpClient\$new</code> .

Value

a character string with CSS code (invisibly).

Examples

```
if (interactive()) {  
  
  # Generate CSS code to use Roboto font  
  cat(generate_css("roboto", "regular"))  
  
}
```

get_all_fonts

Get infos about all fonts available

Description

Retrieve from API all fonts currently available. Use the id field in other functions to reference the font you want to use.

Usage

```
get_all_fonts(...)
```

Arguments

... Arguments passed to `curl::HttpClient$new`.

Value

a `data.frame`.

Examples

```
if (interactive()) {  
  
  # Retrieve all fonts currently available  
  all_fonts <- get_all_fonts()  
  
}
```

get_font_info	<i>Get detailed information about a font</i>
---------------	--

Description

Get detailed information about a font

Usage

```
get_font_info(id, subsets = NULL, ...)
```

Arguments

id	Id of the font, correspond to column id from get_all_fonts .
subsets	Select charsets, for example "latin".
...	Arguments passed to <code>curl::HttpClient\$new</code> .

Value

a data.frame.

Examples

```
if (interactive()) {  
  
  # Info about Roboto  
  roboto <- get_font_info("roboto")  
  
}
```

gfonts	<i>Use Google fonts offline</i>
--------	---------------------------------

Description

Download Google fonts and generate CSS to use in rmarkdown documents and shiny applications. Some popular fonts are included and ready to use.

Download a font

Use [setup_font](#) to get a font inside your current project, then in a {shiny} application or {rmarkdown} document, you can use [use_font](#) to import the font.

Ready-to-use fonts

Some fonts are included in this package and can be used directly with [use_pkg_gfont](#).

Author(s)

Victor Perrier (@dreamRs_fr)

included_fonts	<i>Detail about included fonts.</i>
----------------	-------------------------------------

Description

Id and version of fonts included and available through [use_pkg_gfont](#).

Usage

```
included_fonts
```

Format

A data frame with 8 rows and 5 variables:

id Id for the font.

family Name of the font.

category Category.

version Version number.

lastModified Last modified date.

Source

<https://gwfh.mranftl.com>

setup_font	<i>Setup a font to be used in Shiny or Markdown</i>
------------	---

Description

This function will download the specified font into a directory of your project and generate CSS code to use it in a Shiny application or RMarkdown document.

Usage

```
setup_font(
  id,
  output_dir,
  variants = NULL,
  subsets = NULL,
  prefer_local_source = TRUE,
  browser_support = c("best", "modern"),
  ...
)
```

Arguments

id	Id of the font, correspond to column id from get_all_fonts .
output_dir	Output directory where to save font and CSS files. Must be a directory.
variants	Variant(s) to download, default is to includes all available ones.
subsets	Subsets to download.
prefer_local_source	Generate CSS font-face rules in which user installed fonts are preferred. Use FALSE if you want to force the use of the downloaded font.
browser_support	Browser to support, choose "best" to support old browser or "modern" for only recent ones.
...	Arguments passed to <code>curl::HttpClient\$new</code> .

Value

None.

Note

Two directories will be created (if they do not exist) in the `output_dir` specified: **fonts/** and **css/**.

Examples

```
if (interactive()) {

  # For example, we use a temporary directory
  path_to_www <- tempfile()
  dir.create(path_to_www)

  # In a Shiny app, you can use the www/ directory
  # in Markdown, use a subfolder of your Rmd directory
  setup_font(
    id = "open-sans-condensed",
    output_dir = path_to_www
  )

  # Clean up
  unlink(path_to_www, recursive = TRUE)

}
```

tag_example	<i>Generate HTML tags used in examples</i>
-------------	--

Description

Generate HTML tags used in examples

Usage

```
tag_example(class = NULL)
```

Arguments

class	Class of the main div.
-------	------------------------

Value

HTML tags.

Examples

```
tag_example()
```

use_font	<i>Use a downloaded font in Shiny or Markdown</i>
----------	---

Description

Use a downloaded font in Shiny or Markdown

Usage

```
use_font(id, css_path, selector = "body", css = NULL)
```

Arguments

id	Id of the font downloaded.
css_path	Path to CSS generated by setup_font .
selector	CSS selector for which to use the font, usually an HTML tag, default to "body" (all document).
css	CSS variables needed to use font, normally this should be automatic.

Value

an HTML tag with an HTML dependency ([htmlDependency](#)).

Examples

```
if (interactive()) {
  library(gfonts)

  # Here we use a temp directory
  # but in Shiny, it can be www/ folder
  directory <- tempfile()
  dir.create(directory)

  # Setup a font (only needed once)
  setup_font(
    id = "dancing-script",
    output_dir = directory
  )

  library(shiny)

  ui <- fluidPage(

    # Use font
    use_font(
      id = "dancing-script",
      css_path = file.path(directory, "css/dancing-script.css")
    ),

    tags$p(
      paste(letters, collapse = "")
    ),
    tags$p(
      paste(LETTERS, collapse = "")
    ),
    tags$p(
      style = "font-weight: bold;",
      paste(letters, collapse = "")
    ),
    tags$p(
      style = "font-weight: bold;",
      paste(LETTERS, collapse = "")
    ),
    tags$p(
      style = "font-style: italic;",
      paste(letters, collapse = "")
    ),
    tags$p(
      style = "font-style: italic;",
      paste(LETTERS, collapse = "")
    ),
    tags$h1("First level title"),
    tags$h2("Second level title"),
    tags$h3("Third level title"),
    tags$h4("Fourth level title"),
    tags$h5("Fifth level title"),
```

```

      tags$h6("Sixth level title")
    )

    server <- function(input, output, session) {

    }
    shinyApp(ui, server)
  }

```

use_pkg_gfont

Use a Google Font included in gfonts

Description

For convenience, some fonts are included in the package, you can use them without having to download them, but only few variants are available.

Usage

```

use_pkg_gfont(
  font = c("roboto", "open-sans", "lato", "montserrat", "alegreya", "nunito-sans",
    "baloo", "happy-monkey", "henny-penny", "poppins", "oswald"),
  selector = "body"
)

```

Arguments

font	Name of the font to use, possible choices are: "roboto", "open-sans", "lato", "montserrat", "alegreya", "nunito-sans", "baloo", "happy-monkey", "henny-penny".
selector	CSS selector for which to use the font, usually an HTML tag, default to "body" (all document).

Value

An HTML tag with an [htmlDependency](#).

Examples

```
if (interactive()) {  
  
  library(gfonts)  
  library(htmltools)  
  
  browsable(tags$div(  
    use_pkg_gfont("open-sans"),  
    tag_example(),  
    tags$h1("First level title"),  
    tags$h2("Second level title"),  
    tags$h3("Third level title"),  
    tags$h4("Fourth level title"),  
    tags$h5("Fifth level title"),  
    tags$h6("Sixth level title")  
  ))  
  
  browsable(tags$div(  
    use_pkg_gfont("henny-penny"),  
    tag_example(),  
    tags$h1("First level title"),  
    tags$h2("Second level title"),  
    tags$h3("Third level title"),  
    tags$h4("Fourth level title"),  
    tags$h5("Fifth level title"),  
    tags$h6("Sixth level title")  
  ))  
  
}
```

Index

* **datasets**

included_fonts, [6](#)

download_font, [2](#)

generate_css, [3](#)

get_all_fonts, [2](#), [3](#), [4](#), [5](#), [7](#)

get_font_info, [5](#)

gfonts, [5](#)

htmlDependency, [8](#), [10](#)

included_fonts, [6](#)

setup_font, [5](#), [6](#), [8](#)

tag_example, [8](#)

use_font, [5](#), [8](#)

use_pkg_gfont, [5](#), [6](#), [10](#)