

Package ‘ggPMX’

July 22, 2025

Title 'ggplot2' Based Tool to Facilitate Diagnostic Plots for NLME Models

Description At Novartis, we aimed at standardizing the set of diagnostic plots used for modeling activities in order to reduce the overall effort required for generating such plots. For this, we developed a guidance that proposes an adequate set of diagnostics and a toolbox, called 'ggPMX' to execute them. 'ggPMX' is a toolbox that can generate all diagnostic plots at a quality sufficient for publication and submissions using few lines of code. This package focuses on plots recommended by ISoP

<[doi:10.1002/psp4.12161](https://doi.org/10.1002/psp4.12161)>. While not required, you can get/install the 'R' 'lixoftConnectors' package in the 'Monolix' installation, as described at the following url <<https://monolixsuite.slp-software.com/r-functions/2024R1/installation-and-initialization>>.

When 'lixoftConnectors' is available, 'R' can use 'Monolix' directly to create the required Chart Data instead of exporting it from the 'Monolix' gui.

Version 1.3.0

URL <https://github.com/ggPMXdevelopment/ggPMX>

BugReports <https://github.com/ggPMXdevelopment/ggPMX/issues>

Depends R (>= 3.5)

Imports data.table, yaml, R6, gtable, ggplot2 (>= 3.4.0), ggforce, magrittr, stringr, assertthat, GGally, zoo, knitr, rmarkdown, tidyr, dplyr, purrr, readr, rlang, checkmate, scales

License GPL-2

Suggests testthat, xtable, vdiff, rxode2, nlmixr2est, nlmixr2data, nlme, lixoftConnectors, xgxr, withr, lifecycle

VignetteBuilder knitr

NeedsCompilation no

RoxygenNote 7.3.2

Encoding UTF-8

Author Amine Gasseem [aut],
Bruno Bieth [aut],

Irina Baltcheva [aut],
 Thomas Dumortier [aut],
 Christian Bartels [aut],
 Souvik Bhattacharya [aut],
 Inga Ludwig [aut],
 Ines Paule [aut],
 Didier Renard [aut],
 Matthew Fidler [aut] (ORCID: <<https://orcid.org/0000-0001-8538-6691>>),
 Seid Hamzic [aut],
 Benjamin Guiastronnec [ctb],
 Kyle T Baron [ctb] (ORCID: <<https://orcid.org/0000-0001-7252-5656>>),
 Qing Xi Ooi [ctb],
 Aleksandr Pogodaev [aut, cre] (ORCID:
 <<https://orcid.org/0000-0002-1371-207X>>),
 Danielle Navarro [aut],
 Ibtissem Rebai [ctb],
 Mahmoud Ali [ctb],
 Novartis Pharma AG [cph]

Maintainer Aleksandr Pogodaev <alex.pogodaev@novartis.com>

Repository CRAN

Date/Publication 2025-07-16 10:20:02 UTC

Contents

abbrev	4
add_draft	5
check_shrink	6
distrib	6
eta_cov	7
eta_cov_plot	9
eta_distribution_plot	12
eta_pairs	15
eval_sym_parent_env	17
getPmxOption	17
get_abbrev	18
get_cats	18
get_conts	19
get_covariates	19
get_data	20
get_occ	20
get_plot	21
get_plot_config	22
get_strats	22
gtable_remove_grobs	23
individual	23
input_finegrid	25
is.pmx_gpar	25

load_config	26
load_data_set	26
load_source	27
l_left_join	27
n_pages	28
param_table	28
parse_mlxtran	29
pk_occ	29
pk_pd	30
plots	30
plot_names	31
plot_pmx	31
plot_pmx.distrib	32
plot_pmx.eta_cov	33
plot_pmx.eta_pairs	33
plot_pmx.individual	34
plot_pmx.pmx_dens	35
plot_pmx.pmx_gpar	35
plot_pmx.pmx_param_history	36
plot_pmx.pmx_qq	37
plot_pmx.residual	37
plot_shrink	38
pmx	39
pmxOptions	42
pmx_bloq	43
pmx_comp_shrink	44
pmx_config	45
pmx_copy	46
pmx_cov	47
pmx_dens	47
pmx_endpoint	49
pmx_filter	50
pmx_get_configs	51
pmx_gpar	52
pmx_list_nm_tables	53
pmx_manual_nm_import	54
pmx_nlmixr	55
pmx_nm	55
pmx_plot	58
pmx_plot_cats	59
pmx_plot_eta_matrix	59
pmx_plot_individual	62
pmx_plot_iwres_dens	66
pmx_plot_saem_convergence	68
pmx_plot_vpc	69
pmx_qq	72
pmx_qq_plot	74
pmx_read_nm_files	77

pmx_read_nm_model	78
pmx_read_nm_tables	79
pmx_register_plot	81
pmx_report	81
pmx_report_template	84
pmx_settings	84
pmx_shrink	86
pmx_sim	86
pmx_theme	88
pmx_update	89
pmx_vpc	90
pmx_vpc_bin	91
pmx_vpc_ci	92
pmx_vpc_obs	93
pmx_vpc_pi	93
pmx_vpc_rug	94
print.abbreviation	95
print.configs	96
print.pmxClass	96
print.pmxConfig	97
print.pmx_gpar	97
read_extfile	98
read_input	99
read_mlx_ind_est	100
read_mlx_par_est	100
read_mlx_pred	101
read_mlx_saem_conv	101
residual	102
residual_scatter	103
set_abbrev	107
set_data	108
set_plot	109
theophylline	110
wrap_formula	110
[.pmx_gpar	111

Index**112**

abbrev

*Give the whole abbreviation definition***Description**

Give the whole abbreviation definition

Usage

abbrev(param)

Arguments

param abbreviation term

Value

character abbreviation definition

Examples

abbrev("VPC")

add_draft	<i>Add draft layer annotation</i>
-----------	-----------------------------------

Description

This function adds the word draft to certain graphics.

Usage

```
add_draft(  
  label = "DRAFT",  
  size = 10,  
  colour = "grey50",  
  x = Inf,  
  y = -Inf,  
  ...  
)
```

Arguments

label	draft layer default to DRAFT
size	size of the annotation
colour	color of the annotation default to grey50
x	numeric x coordinate of the draft label
y	numeric y coordinate of the draft label
...	extra parameters to geom text used to annotate the draft

Value

ggplot2 annotation

check_shrink	<i>Performs checks of names in shrink list</i>
--------------	--

Description

Performs checks of names in shrink list

Usage

```
check_shrink(shrink_list)
```

Arguments

shrink_list	list list of shrink arguments
-------------	-------------------------------

distrib	<i>creates a graphic distribution object</i>
---------	--

Description

creates a graphic distribution object

Usage

```
distrib(
  labels,
  is.shrink,
  type = c("box", "hist"),
  is.jitter = FALSE,
  jitter = NULL,
  facets = NULL,
  histogram = NULL,
  shrink = NULL,
  dname = NULL,
  ...
)
```

Arguments

labels	list of texts/titles used within the plot
is.shrink	logical if TRUE add shrinkage layer
type	box for boxplot or histogram
is.jitter	logical if TRUE add jitter operator for points
jitter	list set jitter parameter

facets	list set the facet setting in case of histogram plot
histogram	list histogram graphical parameters
shrink	pmxShrinkClass shrinkage graphical parameter or list coercible into one
dname	name of dataset to be used
...	others graphics arguments passed to <code>pmx_gpar</code> internal object.

Details

labels is a list that contains:

- **title:** plot title default "EBE distribution"
- **subtitle:** plot subtitle default empty
- **x:** x axis label default to "Etas"
- **y:** y axis label default to empty
- **legend:** legend title default to "random Effect"

shrink is a list that contains:

- **fun:** shrinkage function can be sd or var
- **size:** shrinkage text size
- **color:** shrinkage text color
- **vjust:** shrinkage position vertical adjustment

Value

distrib object

See Also

Other plot_pmx: `eta_cov()`, `eta_pairs()`, `individual()`, `plot_pmx()`, `plot_pmx.distrib()`, `plot_pmx.eta_cov()`, `plot_pmx.eta_pairs()`, `plot_pmx.individual()`, `plot_pmx.pmx_dens()`, `plot_pmx.pmx_gpar()`, `plot_pmx.pmx_param_history()`, `plot_pmx.pmx_qq()`, `plot_pmx.residual()`

eta_cov

This creates an ETA covariance matrix which can be used to define the co-relation between the parameters and its shrinkage..

Description

This creates an ETA covariance matrix which can be used to define the co-relation between the parameters and its shrinkage..

Usage

```
eta_cov(
  labels,
  type = c("cats", "conts"),
  dname = NULL,
  show.correl = TRUE,
  correl = NULL,
  facets = NULL,
  point = NULL,
  covariates = NULL,
  is.strat.color = FALSE,
  ...
)
```

Arguments

labels	list of texts/titles used within the plot
type	box for cats or conts
dname	name of dataset to be used
show.correl	logical if TRUE add correlation to the plot
correl	list correl geom text graphical parameter
facets	list facetting graphical parameter
point	list geom point graphical parameter
covariates	pmxCOVObject pmx_cov
is.strat.color	logical if 'TRUE' use a different color for the spline stratification.
...	others graphics arguments passed to pmx_gpar internal object.

Details

labels is a list that contains:

- **title:** plot title default "EBE vs. covariates"
- **x:** x axis label default to "Etas"
- **y:** y axis label default to empty

Value

eta_cov object

See Also

Other plot_pmx: [distrib\(\)](#), [eta_pairs\(\)](#), [individual\(\)](#), [plot_pmx\(\)](#), [plot_pmx.distrib\(\)](#), [plot_pmx.eta_cov\(\)](#), [plot_pmx.eta_pairs\(\)](#), [plot_pmx.individual\(\)](#), [plot_pmx.pmx_dens\(\)](#), [plot_pmx.pmx_gpar\(\)](#), [plot_pmx.pmx_param_history\(\)](#), [plot_pmx.pmx_qq\(\)](#), [plot_pmx.residual\(\)](#)

eta_cov_plot	<i>Eta Covariates plots</i>
--------------	-----------------------------

Description

Eta Covariates plots

Relationships between (ETA) and categorical covariates

Relationships between (ETA) and continuous covariates

Usage

```
dummy(  
  dname,  
  show.correl,  
  correl,  
  point,  
  facets,  
  covariates,  
  filter,  
  strat.facet,  
  strat.color,  
  trans,  
  pmxgpar,  
  labels,  
  axis.title,  
  axis.text,  
  ranges,  
  is.smooth,  
  smooth,  
  is.band,  
  band,  
  is.draft,  
  draft,  
  is.identity_line,  
  identity_line,  
  scale_x_log10,  
  scale_y_log10,  
  color.scales  
)  
  
pmx_plot_eta_cats(ctr, ...)  
  
pmx_plot_eta_confs(ctr, ...)
```

Arguments

dname	character name of dataset to be used
-------	--------------------------------------

show.correl	logical if TRUE add correlation to the plot
correl	list correl geom text graphical parameter
point	list geom point graphical parameter
facets	list facetting graphical parameter
covariates	list of selected covariates and custom labels, e.g. <code>pmx_cov(values = list("SEX"), labels = list("Sex"))</code> list <code>pmxCovObject</code> pmx_cov
pmx_update parameters	
filter	expression filter which will be applied to plotting data.
strat.facet	formula optional stratification parameter by facetting. This split plot by strats(each strat in a facet)
strat.color	character optional stratification parameter by grouping. This will split the plot by group (color) of strat.
trans	character define the transformation to apply on x or y or both variables
pmxgpar	a object of class <code>pmx_gpar</code> possibly the output of the pmx_gpar: Shared basic graphics parameters
labels	list list containing plot and/or axis labels: title, subtitle, x , y
axis.title	list containing <code>element_text</code> attributes to customize the axis title. (similar to <code>ggplot2</code> <code>axis.title</code> theme)
axis.text	list containing <code>element_text</code> attributes to customize the axis text (similar to <code>ggplot2</code> <code>axis.text</code> theme)
ranges	list limits of x/y ranges
is.smooth	logical if set to TRUE add smooth layer
smooth	list <code>geom_smooth</code> graphical/smoothing fun parameters
is.band	logical if TRUE add horizontal band
band	list horizontal band parameters. <code>geom_hline</code> graphical parameters.
is.draft	logical if TRUE add draft layer
draft	list draft layer parameters. <code>geom_text</code> graphical parameters.
is.identity_line	logical if TRUE add an identity line
identity_line	list <code>geom_abline</code> graphical parameters.
scale_x_log10	logical if TRUE use log10 scale for x axis.
scale_y_log10	logical if TRUE use log10 scale for y axis.
color.scales	list define scales parameter in case of <code>strat.color</code> pmx_settings
ctr	pmx controller
...	others graphics parameters passed : • pmx_gpar internal function to customize shared graphical parameters • eta_cov generic object for eta/covariates plots. • pmx_update function.
eta_cov parameters	

Value

ggplot2 object

ggplot2 object

ggplot2 object

Examples

```

# basic use -----

ctr <- theophylline()
ctr %>% pmx_plot_eta_cats
ctr %>% pmx_plot_eta_conts

# update graphical parameter -----

## plot selected covariates
ctr %>% pmx_plot_eta_cats(
  covariates = pmx_cov(values = list("SEX"))
)

## update labels
ctr %>% pmx_plot_eta_cats(
  labels = list(title = "New eta cats title")
)

## remove draft
ctr %>% pmx_plot_eta_cats(is.draft = FALSE)

## change text color line
ctr %>% pmx_plot_eta_conts(
  correl=list(colour="magenta")
)

## set covariates custom labels

ctr %>% pmx_plot_eta_conts(
  covariates=pmx_cov(values=list("WT0", "AGE0"),
    labels=list("Weight", "Age"))
)

## set effects and covaraites custom labels

ctr <- theophylline( settings = pmx_settings(
  effects=list( levels=c("ka", "V", "Cl"),
    labels=c("Concentration", "Volume", "Clearance")
  )
)

```

```
)  
ctr %>% pmx_plot_eta_conts(  
  covariates=pmx_cov(values=list("WT0", "AGE0"),  
    labels=list("Weight", "Age"))  
)
```

eta_distribution_plot *Eta distribution plots*

Description

Eta distribution plots

Eta Distribution boxplot

Eta Distribution histogram plot

Usage

```
eta_distribution_plot(  
  jitter,  
  type,  
  dname,  
  is.shrink,  
  shrink,  
  is.jitter,  
  histogram,  
  filter,  
  strat.facet,  
  facets,  
  strat.color,  
  trans,  
  pmxgpar,  
  labels,  
  axis.title,  
  axis.text,  
  ranges,  
  is.smooth,  
  smooth,  
  is.band,  
  band,  
  is.draft,  
  draft,  
  is.identity_line,
```

```

    identity_line,
    scale_x_log10,
    scale_y_log10,
    color.scales,
    ...
)

pmx_plot_eta_box(ctr, ...)

pmx_plot_eta_hist(ctr, ...)

```

Arguments

jitter	list set jitter parameter
type	box for boxplot or histogram
dname	name of dataset to be used
is.shrink	logical if TRUE add shrinkage layer
shrink	list parameters to control shrinkage, must contain "fun"
is.jitter	logical if TRUE add jitter operator for points
histogram	list histogram graphical parameters
pmx_update parameters	
filter	expression filter which will be applied to plotting data.
strat.facet	formula optional stratification parameter by facetting. This split plot by strats(each strat in a facet)
facets	list facet_wrap parameters.
strat.color	character optional stratification parameter by grouping. This will split the plot by group (color) of strat.
trans	character define the transformation to apply on x or y or both variables
pmxgpar	a object of class pmx_gpar possibly the output of the
pmx_gpar: Shared basic graphics parameters	
labels	list list containing plot and/or axis labels: title, subtitle, x , y
axis.title	list containing element_text attributes to customize the axis title. (similar to ggplot2 axis.title theme)
axis.text	list containing element_text attributes to customize the axis text (similar to ggplot2 axis.text theme)
ranges	list limits of x/y ranges
is.smooth	logical if set to TRUE add smooth layer
smooth	list geom_smooth graphical/smoothing fun parameters
is.band	logical if TRUE add horizontal band
band	list horizontal band parameters. geom_hline graphical parameters.
is.draft	logical if TRUE add draft layer
draft	list draft layer parameters. geom_text graphical parameters.

```

is.identity_line      logical if TRUE add an identity line
identity_line         listgeom_abline graphical parameters.
scale_x_log10          logical if TRUE use log10 scale for x axis.
scale_y_log10          logical if TRUE use log10 scale for y axis.
color.scales          list define scales parameter in case of strat.color pmx\_settings
...                   others graphics parameters passed :
                      • pmx\_gpar internal function to customize shared graphical parameters
                      • distrib generic object for distribution plots (histogram/boxplot).
                      • pmx\_update function.

distrib parameters

ctr                   pmx controller

```

Value

ggplot2 object

Examples

```

# ***** basic use ***** -----

ctr <- theophylline()
## boxplot variation
p <- ctr %>% pmx_plot_eta_box()
## histogram variation
p <- ctr %>% pmx_plot_eta_hist()

# update graphical parameter -----

## add jitter
ctr %>%
  pmx_plot_eta_hist(is.jitter = TRUE, jitter = list(alpha = 0.4, color = "red"))

## remove shrinkage
ctr %>%
  pmx_plot_eta_hist(is.shrink = FALSE)

## update histogram graphical parameters
ctr %>%
  pmx_plot_eta_hist(
    histogram = list(
      color = NA,
      position = "fill",
      binwidth = 1 / 100
    )
  )

```

```

# stratification -----

## categorical stratification color parameter
ctr %>% pmx_plot_eta_hist(is.jitter = TRUE, strat.facet = ~STUD, strat.color = ~SEX)

## categorical stratification facetting
ctr %>% pmx_plot_eta_hist(strat.facet = ~SEX)

## using formula categorical stratification facetting
ctr %>% pmx_plot_eta_hist(
  strat.facet = STUD ~ SEX,
  shrink = pmx_shrink(hjust = 0.5)
)

# subsetting -----

## select a set of random effect
ctr %>% pmx_plot_eta_hist(filter = EFFECT %in% c("ka", "Cl"))
## filter and stratify by facets
ctr %>% pmx_plot_eta_hist(
  filter = EFFECT %in% c("ka", "Cl"), strat.facet = ~SEX
)
ctr %>% pmx_plot_eta_hist(
  filter = EFFECT %in% c("ka", "Cl"), strat.facet = ~SEX
)

```

eta_pairs

This creates an eta correlation which defines the relationship between parameters

Description

This creates an eta correlation which defines the relationship between parameters

Usage

```

eta_pairs(
  is.title,
  title,
  dname = NULL,
  type.eta = c("mode", "mean"),
  text_color = "black",
  is.shrink = TRUE,
  is.smooth = TRUE,
  smooth = NULL,
  point = NULL,
  shrink = NULL,
  is.hline = FALSE,

```

```

    hline = NULL,
    is.vreference_line = FALSE,
    vreference_line = list(colour = "orange", linetype = "longdash"),
    ...
  )

```

Arguments

<code>is.title</code>	logical if TRUE then a title is used for the plot
<code>title</code>	character the plot title
<code>dname</code>	name of dataset to be used
<code>type.eta</code>	character type of eat can be 'mode' or 'mean'. 'mode' by default
<code>text_color</code>	color of the correlation text in the upper matrix
<code>is.shrink</code>	logical if TRUE add shrinkage to the plot
<code>is.smooth</code>	logical if TRUE add smoothing to lower matrix plots
<code>smooth</code>	list <code>geom_smooth</code> graphical parameters
<code>point</code>	list <code>geom_point</code> graphical parameter
<code>shrink</code>	<code>pmxShrinkClass</code> shrinkage graphical parameter or list coercible into one
<code>is.hline</code>	logical if TRUE add horizontal line to lower matrix plots
<code>hline</code>	list <code>geom_hline</code> graphical parameters
<code>is.vreference_line</code>	logical if TRUE add the ± 1.96 lines
<code>vreference_line</code>	list <code>geom_hline</code> graphical parameters for the reference lines
<code>...</code>	others graphics arguments passed to <code>pmx_gpar</code> internal object.

Value

ecorrel object

See Also

Other `plot_pmx`: `distrib()`, `eta_cov()`, `individual()`, `plot_pmx()`, `plot_pmx.distrib()`, `plot_pmx.eta_cov()`, `plot_pmx.eta_pairs()`, `plot_pmx.individual()`, `plot_pmx.pmx_dens()`, `plot_pmx.pmx_gpar()`, `plot_pmx.pmx_param_history()`, `plot_pmx.pmx_qq()`, `plot_pmx.residual()`

eval_sym_parent_env	<i>Try to evaluate a symbol in the parent frame (on error return the symbol)</i>
---------------------	--

Description

Try to evaluate a symbol in the parent frame (on error return the symbol)

Usage

```
eval_sym_parent_env(x)
```

Arguments

x	any object
---	------------

Value

evaluated symbol or the symbol in case of evaluation error

getPmxOption	<i>Get ggPMX Option</i>
--------------	-------------------------

Description

Get ggPMX Option

Usage

```
getPmxOption(name, default = NULL)
```

Arguments

name	Name of an option to get.
default	Value to be returned if the option is not currently set.

Value

value of the option or NULL

Examples

```
## Not run:
pmxOptions(myOption = 10)
getPmxOption("myOption")

## End(Not run)
```

get_abbrev	<i>Get abbreviation definition by key</i>
------------	---

Description

Get abbreviation definition by key

Usage

```
get_abbrev(ctr, param)
```

Arguments

ctr	pmxClass controller
param	abbreviation term

Value

character abbreviation definition

get_cats	<i>Get category covariates</i>
----------	--------------------------------

Description

Get category covariates

Usage

```
get_cats(ctr)
```

Arguments

ctr	the controller object
-----	-----------------------

Value

a charcater vector

See Also

Other pmxclass: [get_confs\(\)](#), [get_covariates\(\)](#), [get_data\(\)](#), [get_occ\(\)](#), [get_plot\(\)](#), [get_plot_config\(\)](#), [get_strats\(\)](#), [plot_names\(\)](#), [plots\(\)](#), [pmx_update\(\)](#), [set_data\(\)](#), [set_plot\(\)](#)

get_conts	<i>Get continuous covariates</i>
-----------	----------------------------------

Description

Get continuous covariates

Usage

```
get_conts(ctr)
```

Arguments

ctr	the controller object
-----	-----------------------

Value

a charcater vector

See Also

Other pmxclass: [get_cats\(\)](#), [get_covariates\(\)](#), [get_data\(\)](#), [get_occ\(\)](#), [get_plot\(\)](#), [get_plot_config\(\)](#), [get_strats\(\)](#), [plot_names\(\)](#), [plots\(\)](#), [pmx_update\(\)](#), [set_data\(\)](#), [set_plot\(\)](#)

get_covariates	<i>Get covariates variables</i>
----------------	---------------------------------

Description

Get covariates variables

Usage

```
get_covariates(ctr)
```

Arguments

ctr	the controller object
-----	-----------------------

Value

a charcater vector

See Also

Other pmxclass: [get_cats\(\)](#), [get_conts\(\)](#), [get_data\(\)](#), [get_occ\(\)](#), [get_plot\(\)](#), [get_plot_config\(\)](#), [get_strats\(\)](#), [plot_names\(\)](#), [plots\(\)](#), [pmx_update\(\)](#), [set_data\(\)](#), [set_plot\(\)](#)

get_data	<i>Get controller data set</i>
----------	--------------------------------

Description

Get controller data set

Usage

```
get_data(
  ctr,
  data_set = c("estimates", "predictions", "eta", "finegrid", "input", "sim",
    "individual")
)
```

Arguments

ctr	the controller object
data_set	the data set name

Value

a data.table of the named data set if available.

See Also

Other pmxclass: [get_cats\(\)](#), [get_confs\(\)](#), [get_covariates\(\)](#), [get_occ\(\)](#), [get_plot\(\)](#), [get_plot_config\(\)](#), [get_strats\(\)](#), [plot_names\(\)](#), [plots\(\)](#), [pmx_update\(\)](#), [set_data\(\)](#), [set_plot\(\)](#)

get_occ	<i>Get controller occasional covariates</i>
---------	---

Description

Get controller occasional covariates

Usage

```
get_occ(ctr)
```

Arguments

ctr	the controller object
-----	-----------------------

Value

a character vector

See Also

Other pmxclass: [get_cats\(\)](#), [get_conts\(\)](#), [get_covariates\(\)](#), [get_data\(\)](#), [get_plot\(\)](#), [get_plot_config\(\)](#), [get_strats\(\)](#), [plot_names\(\)](#), [plots\(\)](#), [pmx_update\(\)](#), [set_data\(\)](#), [set_plot\(\)](#)

get_plot	<i>Get plot object</i>
----------	------------------------

Description

Get plot object

Usage

```
get_plot(ctr, nplot, which_pages = "all")
```

Arguments

ctr	pmxClass controller object
nplot	character the plot name
which_pages	integer vector (can be length 1), set page number in case of multi pages plot, or character "all" to plot all pages.

Value

ggplot object

See Also

Other pmxclass: [get_cats\(\)](#), [get_conts\(\)](#), [get_covariates\(\)](#), [get_data\(\)](#), [get_occ\(\)](#), [get_plot_config\(\)](#), [get_strats\(\)](#), [plot_names\(\)](#), [plots\(\)](#), [pmx_update\(\)](#), [set_data\(\)](#), [set_plot\(\)](#)

Examples

```
library(ggPMX)
ctr <- theophylline()
p1 <- ctr %>% get_plot("iwres_ipred")
## get all pages or some pages
p2 <- ctr %>% get_plot("individual")
## returns one page of individual plot
p2 <- ctr %>% get_plot("individual", which_pages = 1)
p3 <- ctr %>% get_plot("individual", which_pages = c(1, 3))
## get distribution plot
pdistri <- ctr %>% get_plot("eta_hist")
```

get_plot_config	<i>Get the plot config by name</i>
-----------------	------------------------------------

Description

Get the plot config by name

Usage

```
get_plot_config(ctr, pname)
```

Arguments

ctr	the controller object
pname	the plot name

Value

the config object

See Also

Other pmxclass: [get_cats\(\)](#), [get_conts\(\)](#), [get_covariates\(\)](#), [get_data\(\)](#), [get_occ\(\)](#), [get_plot\(\)](#), [get_strats\(\)](#), [plot_names\(\)](#), [plots\(\)](#), [pmx_update\(\)](#), [set_data\(\)](#), [set_plot\(\)](#)

Examples

```
ctr <- theophylline()
ctr %>% set_plot("IND", pname = "indiv1")
ctr %>% get_plot_config("distr1")
```

get_strats	<i>Get extra stratification variables</i>
------------	---

Description

Get extra stratification variables

Usage

```
get_strats(ctr)
```

Arguments

ctr	the controller object
-----	-----------------------

Value

a character vector

See Also

Other pmxclass: [get_cats\(\)](#), [get_conts\(\)](#), [get_covariates\(\)](#), [get_data\(\)](#), [get_occ\(\)](#), [get_plot\(\)](#), [get_plot_config\(\)](#), [plot_names\(\)](#), [plots\(\)](#), [pmx_update\(\)](#), [set_data\(\)](#), [set_plot\(\)](#)

gtable_remove_grobs	<i>Remove named elements from gtable</i>
---------------------	--

Description

Remove named elements from gtable

Usage

```
gtable_remove_grobs(table, names, ...)
```

Arguments

table	The table from which grobs should be removed
names	A character vector of the grob names (as listed in <code>table\$layout</code>) that should be removed
...	Other parameters passed through to <code>gtable_filter</code> .

Value

table The table with removed grobs

individual	<i>This function can be used to obtain individual prediction and compare with observed data and population prediction for each individual separately</i>
------------	--

Description

This function can be used to obtain individual prediction and compare with observed data and population prediction for each individual separately

Usage

```
individual(
  labels,
  facets = NULL,
  dname = NULL,
  ipred_line = NULL,
  pred_line = NULL,
  point = NULL,
  bloq = NULL,
  is.legend,
  use.finegrid,
  ...
)
```

Arguments

<code>labels</code>	plot texts. labels, axis,
<code>facets</code>	list facets settings nrow/ncol
<code>dname</code>	name of dataset to be used
<code>ipred_line</code>	list some pred line geom properties aesthetics
<code>pred_line</code>	list some ipred line geom properties aesthetics
<code>point</code>	list some point geom properties aesthetics
<code>bloq</code>	pmxBLOQ object created by pmx_bloq
<code>is.legend</code>	logical if TRUE add a legend
<code>use.finegrid</code>	logical if FALSE use predictions data set
<code>...</code>	others graphics arguments passed to pmx_gpar internal object.

Value

individual fit object

See Also

[plot_pmx.individual](#)

Other plot_pmx: [distrib\(\)](#), [eta_cov\(\)](#), [eta_pairs\(\)](#), [plot_pmx\(\)](#), [plot_pmx.distrib\(\)](#), [plot_pmx.eta_cov\(\)](#), [plot_pmx.eta_pairs\(\)](#), [plot_pmx.individual\(\)](#), [plot_pmx.pmx_dens\(\)](#), [plot_pmx.pmx_gpar\(\)](#), [plot_pmx.pmx_param_history\(\)](#), [plot_pmx.pmx_qq\(\)](#), [plot_pmx.residual\(\)](#)

input_finegrid	<i>Merge input and fingrid data sets</i>
----------------	--

Description

Merge input and fingrid data sets

Usage

```
input_finegrid(input, finegrid)
```

Arguments

input	data.table input data set
finegrid	data.table finegrid data set

Value

data.table

is.pmx_gpar	<i>Check if an object is a pmx_gpar class</i>
-------------	---

Description

Check if an object is a pmx_gpar class

Usage

```
is.pmx_gpar(x)
```

Arguments

x	pmx_gpar object
---	-----------------

Value

logical returns TRUE if it is a pmx_gpar object

load_config	<i>Obtain the data source config</i>
-------------	--------------------------------------

Description

Obtain the data source config

Usage

```
load_config(x, sys = c("mlx", "nm", "mlx18"))
```

Arguments

- x the config name.
- sys can be mlx,nm,...

Value

a list :data configuration object

load_data_set	<i>Load data set</i>
---------------	----------------------

Description

Load data set

Usage

```
load_data_set(x, path, sys, ...)
```

Arguments

- x data set config
- path character path to the directory
- sys character mlx or nm
- ... extra parameter passed to special readers

Value

data.table

load_source	<i>Load all/or some source data set</i>
-------------	---

Description

Load all/or some source data set

Usage

```
load_source(sys, path, dconf, ...)
```

Arguments

sys	type cane mlx/nom
path	character directory path containing all sources.
dconf	configuration object
...	any extra parameters for readers

Value

list of data.table

l_left_join	<i>Merge 2 lists</i>
-------------	----------------------

Description

left join , the first list is updated by the seond one

Usage

```
l_left_join(base_list, overlay_list, recursive = TRUE)
```

Arguments

base_list	list to update
overlay_list	list used to update the first list
recursive	logical if TRUE do the merge in depth

Value

list

n_pages	<i>Determine the number of pages in a paginated facet plot</i>
---------	--

Description

This is a simple helper that returns the number of pages it takes to plot all panels when using [facet_wrap_paginate](#). It partially builds the plot so depending on the complexity of your plot it might take some time to calculate...

Usage

```
n_pages(plot)
```

Arguments

plot	A ggplot object using either <code>facet_wrap_paginate</code> or <code>facet_grid_paginate</code>
------	---

Value

If the plot uses using either `facet_wrap_paginate` or `facet_grid_paginate` it returns the total number of pages. Otherwise it returns NULL

param_table	<i>Creates parameter kable</i>
-------------	--------------------------------

Description

Creates parameter kable

Usage

```
param_table(ctr, fun, return_table = FALSE, scientific = FALSE, digits = 2)
```

Arguments

ctr	Generated controller from e.g. pmx_mlx for Monolix.
fun	character can be "sd" or "var" for shrinkage computation, see pmx_comp_shrink
return_table	If TRUE, returns the same table as in <code>get_data('estimates')</code> otherwise it returns a kable
scientific	logical set to TRUE to get scientific notation of parameter values, or FALSE otherwise
digits	integer the number of significant digits to use when rounding parameter values

Value

Returns a kable with the parameter estimates from `get_data('estimates')`

Examples

```
#ctr <- theophylline()
#my_params <- ctr %>% param_table(fun = "var")
```

parse_mlxtran	<i>Parse MONOLIX mlxtran file</i>
---------------	-----------------------------------

Description

Parse MONOLIX mlxtran file

Usage

```
parse_mlxtran(file_name)
```

Arguments

file_name absolute path to mlxtran file

Value

list key/values to initialize ggPMX controller

pk_occ	<i>Creates pmx controller using monlix data having Occasional variable</i>
--------	--

Description

Creates pmx controller using monlix data having Occasional variable

Usage

```
pk_occ()
```

Value

pmx controller

Examples

```
## Not run:
pk_occ()

## End(Not run)
```

pk_pd	<i>Creates pkpd pmx controller using package internal data</i>
-------	--

Description

Creates pkpd pmx controller using package internal data

Usage

```
pk_pd(code = "3")
```

Arguments

code	can be 3 or 4
------	---------------

plots	<i>Get plots description</i>
-------	------------------------------

Description

Get plots description

Usage

```
plots(ctr)
```

Arguments

ctr	pmxClass controller object
-----	----------------------------

Value

data.frame of plots

See Also

Other pmxclass: [get_cats\(\)](#), [get_conts\(\)](#), [get_covariates\(\)](#), [get_data\(\)](#), [get_occ\(\)](#), [get_plot\(\)](#), [get_plot_config\(\)](#), [get_strats\(\)](#), [plot_names\(\)](#), [pmx_update\(\)](#), [set_data\(\)](#), [set_plot\(\)](#)

plot_names	<i>Get plot names</i>
------------	-----------------------

Description

Get plot names

Usage

```
plot_names(ctr)
```

Arguments

ctr	pmxClass controller object
-----	----------------------------

Value

list of plot names

See Also

Other pmxclass: [get_cats\(\)](#), [get_conts\(\)](#), [get_covariates\(\)](#), [get_data\(\)](#), [get_occ\(\)](#), [get_plot\(\)](#), [get_plot_config\(\)](#), [get_strats\(\)](#), [plots\(\)](#), [pmx_update\(\)](#), [set_data\(\)](#), [set_plot\(\)](#)

plot_pmx	<i>This is a generic plot method that produces all plots by default described in pmx model evaluation guidance.</i>
----------	---

Description

This is a generic plot method that produces all plots by default described in pmx model evaluation guidance.

Usage

```
plot_pmx(x, dx, ...)

## S3 method for class 'pmx_vpc'
plot_pmx(x, dx, ...)
```

Arguments

x	object to plot
dx	data.table , plot source data
...	extra argument (not used)

See Also

[pmx_gpar](#).

Other plot_pmx: [distrib\(\)](#), [eta_cov\(\)](#), [eta_pairs\(\)](#), [individual\(\)](#), [plot_pmx.distrib\(\)](#), [plot_pmx.eta_cov\(\)](#), [plot_pmx.eta_pairs\(\)](#), [plot_pmx.individual\(\)](#), [plot_pmx.pmx_dens\(\)](#), [plot_pmx.pmx_gpar\(\)](#), [plot_pmx.pmx_param_history\(\)](#), [plot_pmx.pmx_qq\(\)](#), [plot_pmx.residual\(\)](#)

plot_pmx.distrib	<i>Plot EBE distribution</i>
------------------	------------------------------

Description

Plot EBE distribution

Usage

```
## S3 method for class 'distrib'
plot_pmx(x, dx, ...)
```

Arguments

x	distribution object
dx	data set
...	not used for the moment

Value

ggplot2 plot

See Also

[distrib](#)

Other plot_pmx: [distrib\(\)](#), [eta_cov\(\)](#), [eta_pairs\(\)](#), [individual\(\)](#), [plot_pmx\(\)](#), [plot_pmx.eta_cov\(\)](#), [plot_pmx.eta_pairs\(\)](#), [plot_pmx.individual\(\)](#), [plot_pmx.pmx_dens\(\)](#), [plot_pmx.pmx_gpar\(\)](#), [plot_pmx.pmx_param_history\(\)](#), [plot_pmx.pmx_qq\(\)](#), [plot_pmx.residual\(\)](#)

plot_pmx.eta_cov	<i>This plots an ETA covariance matrix which can be used to define the co-relation between the parameters and its shrinkage</i>
------------------	---

Description

This plots an ETA covariance matrix which can be used to define the co-relation between the parameters and its shrinkage

Usage

```
## S3 method for class 'eta_cov'
plot_pmx(x, dx, ...)
```

Arguments

x	eta_cov object
dx	data set
...	not used for the moment

Value

ggplot2 plot

See Also

[eta_cov](#)

Other plot_pmx: [distrib\(\)](#), [eta_cov\(\)](#), [eta_pairs\(\)](#), [individual\(\)](#), [plot_pmx\(\)](#), [plot_pmx.distrib\(\)](#), [plot_pmx.eta_pairs\(\)](#), [plot_pmx.individual\(\)](#), [plot_pmx.pmx_dens\(\)](#), [plot_pmx.pmx_gpar\(\)](#), [plot_pmx.pmx_param_history\(\)](#), [plot_pmx.pmx_qq\(\)](#), [plot_pmx.residual\(\)](#)

plot_pmx.eta_pairs	<i>Plot random effect correlation plot</i>
--------------------	--

Description

Plot random effect correlation plot

Usage

```
## S3 method for class 'eta_pairs'
plot_pmx(x, dx, ...)
```

Arguments

x	distribution object
dx	data set
...	not used for the moment

Value

ggpairs plot

See Also

[distrib](#)

Other plot_pmx: [distrib\(\)](#), [eta_cov\(\)](#), [eta_pairs\(\)](#), [individual\(\)](#), [plot_pmx\(\)](#), [plot_pmx.distrib\(\)](#), [plot_pmx.eta_cov\(\)](#), [plot_pmx.individual\(\)](#), [plot_pmx.pmx_dens\(\)](#), [plot_pmx.pmx_gpar\(\)](#), [plot_pmx.pmx_param_history\(\)](#), [plot_pmx.pmx_qq\(\)](#), [plot_pmx.residual\(\)](#)

plot_pmx.individual	<i>This function can be used to plot individual prediction and compare with observed data and population prediction for each individual separately</i>
---------------------	--

Description

This function can be used to plot individual prediction and compare with observed data and population prediction for each individual separately

Usage

```
## S3 method for class 'individual'
plot_pmx(x, dx, ...)
```

Arguments

x	individual object
dx	data set
...	not used for the moment

Value

a list of ggplot2

See Also

Other plot_pmx: [distrib\(\)](#), [eta_cov\(\)](#), [eta_pairs\(\)](#), [individual\(\)](#), [plot_pmx\(\)](#), [plot_pmx.distrib\(\)](#), [plot_pmx.eta_cov\(\)](#), [plot_pmx.eta_pairs\(\)](#), [plot_pmx.pmx_dens\(\)](#), [plot_pmx.pmx_gpar\(\)](#), [plot_pmx.pmx_param_history\(\)](#), [plot_pmx.pmx_qq\(\)](#), [plot_pmx.residual\(\)](#)

plot_pmx.pmx_dens	<i>This function plots EBE versus covariates using qq plots</i>
-------------------	---

Description

This function plots EBE versus covariates using qq plots

Usage

```
## S3 method for class 'pmx_dens'
plot_pmx(x, dx, ...)
```

Arguments

x	eta_cov object
dx	data set
...	not used for the moment

Value

ggplot2 plot

See Also

[eta_cov](#)

Other plot_pmx: [distrib\(\)](#), [eta_cov\(\)](#), [eta_pairs\(\)](#), [individual\(\)](#), [plot_pmx\(\)](#), [plot_pmx.distrib\(\)](#), [plot_pmx.eta_cov\(\)](#), [plot_pmx.eta_pairs\(\)](#), [plot_pmx.individual\(\)](#), [plot_pmx.pmx_gpar\(\)](#), [plot_pmx.pmx_param_history\(\)](#), [plot_pmx.pmx_qq\(\)](#), [plot_pmx.residual\(\)](#)

plot_pmx.pmx_gpar	<i>The ggPMX base plot function</i>
-------------------	-------------------------------------

Description

This function should be called internally by other plots to set general settings like , smoothing, add band, labelling, theming,...

Usage

```
## S3 method for class 'pmx_gpar'
plot_pmx(x, dx, ...)
```

Arguments

x	object of pmx_gpar type
dx	plot
...	ignored parameters

Value

ggplot2 object

See Also

Other plot_pmx: [distrib\(\)](#), [eta_cov\(\)](#), [eta_pairs\(\)](#), [individual\(\)](#), [plot_pmx\(\)](#), [plot_pmx.distrib\(\)](#), [plot_pmx.eta_cov\(\)](#), [plot_pmx.eta_pairs\(\)](#), [plot_pmx.individual\(\)](#), [plot_pmx.pmx_dens\(\)](#), [plot_pmx.pmx_param_history\(\)](#), [plot_pmx.pmx_qq\(\)](#), [plot_pmx.residual\(\)](#)

plot_pmx.pmx_param_history

S3 method for plots of class pmx_param_history

Description

S3 method for plots of class pmx_param_history

Usage

```
## S3 method for class 'pmx_param_history'
plot_pmx(x, dx, ...)
```

Arguments

x	pmx_param_history object
dx	data set
...	not used

Value

ggplot2 plot

See Also

Other plot_pmx: [distrib\(\)](#), [eta_cov\(\)](#), [eta_pairs\(\)](#), [individual\(\)](#), [plot_pmx\(\)](#), [plot_pmx.distrib\(\)](#), [plot_pmx.eta_cov\(\)](#), [plot_pmx.eta_pairs\(\)](#), [plot_pmx.individual\(\)](#), [plot_pmx.pmx_dens\(\)](#), [plot_pmx.pmx_gpar\(\)](#), [plot_pmx.pmx_qq\(\)](#), [plot_pmx.residual\(\)](#)

plot_pmx.pmx_qq	<i>This function plot EBE versus covariates using qq plots</i>
-----------------	--

Description

This function plot EBE versus covariates using qq plots

Usage

```
## S3 method for class 'pmx_qq'
plot_pmx(x, dx, ...)
```

Arguments

x	pmx_qq object
dx	data set
...	not used for the moment

Value

ggplot2 plot

See Also

[eta_cov](#)

Other plot_pmx: [distrib\(\)](#), [eta_cov\(\)](#), [eta_pairs\(\)](#), [individual\(\)](#), [plot_pmx\(\)](#), [plot_pmx.distrib\(\)](#), [plot_pmx.eta_cov\(\)](#), [plot_pmx.eta_pairs\(\)](#), [plot_pmx.individual\(\)](#), [plot_pmx.pmx_dens\(\)](#), [plot_pmx.pmx_gpar\(\)](#), [plot_pmx.pmx_param_history\(\)](#), [plot_pmx.residual\(\)](#)

plot_pmx.residual	<i>This function plots residual for each observed value by finding the difference between observed and predicted points. It also fits a distribution to the residual value.</i>
-------------------	---

Description

This function plots residual for each observed value by finding the difference between observed and predicted points. It also fits a distribution to the residual value.

Usage

```
## S3 method for class 'residual'
plot_pmx(x, dx, ...)
```

Arguments

x	residual object
dx	data set
...	not used for the moment

Value

ggplot2 object

See Also

[residual](#)

Other plot_pmx: [distrib\(\)](#), [eta_cov\(\)](#), [eta_pairs\(\)](#), [individual\(\)](#), [plot_pmx\(\)](#), [plot_pmx.distrib\(\)](#), [plot_pmx.eta_cov\(\)](#), [plot_pmx.eta_pairs\(\)](#), [plot_pmx.individual\(\)](#), [plot_pmx.pmx_dens\(\)](#), [plot_pmx.pmx_gpar\(\)](#), [plot_pmx.pmx_param_history\(\)](#), [plot_pmx.pmx_qq\(\)](#)

plot_shrink	<i>Plot shrink in eta matrix</i>
-------------	----------------------------------

Description

Plot shrink in eta matrix

Usage

plot_shrink(x, shrink.dx, shrink)

Arguments

x	pmx_gpar object
shrink.dx	data.table of shrinkage
shrink	pmxShrinkClass shrinkage graphical parameter or list coercible into one

Value

ggplot2 object

pmx

Create a pmx object

Description

Create a pmx object from a data source

Usage

```
pmx(  
  config,  
  sys = "mlx",  
  directory,  
  input,  
  dv,  
  dvid,  
  cats = NULL,  
  conts = NULL,  
  occ = NULL,  
  strats = NULL,  
  settings = NULL,  
  endpoint = NULL,  
  sim = NULL,  
  bloq = NULL,  
  id = NULL,  
  time = NULL,  
  sim_blq = NULL  
)
```

```
pmx_mlx(  
  config,  
  directory,  
  input,  
  dv,  
  dvid,  
  cats,  
  conts,  
  occ,  
  strats,  
  settings,  
  endpoint,  
  sim,  
  bloq,  
  id,  
  time,  
  sim_blq  
)
```

```

pmx_mlxtran(
  file_name,
  config = "standing",
  call = FALSE,
  endpoint,
  version = -1,
  ...
)

```

Arguments

config	Can be either : The complete path for the configuration file, the name of configuration within the built-in list of configurations, or a configuration object.
sys	the system name can "mlx" (for Monolix 2016) or "mlx18" (for Monolix 2018/19 and later)
directory	character modelling output directory.
input	character complete path to the modelling input file
dv	character the name of measurable variable used in the input modelling file
dvid	<i>[Optional]</i> character observation type parameter. This is mandatory in case of multiple endpoint (PKPD).
cats	<i>[Optional]</i> character vector of categorical covariates
conts	<i>[Optional]</i> character vector of continuous covariates
occ	<i>[Optional]</i> character occasional covariate variable name
strats	<i>[Optional]</i> character extra stratification variables
settings	<i>[Optional]</i> pmxSettingsClass pmx_settings shared between all plots
endpoint	pmxEndpointClass or integer or character default to NULL of the endpoint code. pmx_endpoint
sim	pmxSimClass default to NULL. pmx_sim used for VPC, e.g.: sim = pmx_sim(file=vpc_file, irun="rep", idv="TIME")
bloq	pmxBLOQClass default to NULL. pmx_bloq specify bloq, within controller: e.g. bloq=pmx_bloq(cens = "BLOQ_name", limit = "LIMIT_name")
id	<i>[Optional]</i> character the name of Individual variable used in the input modelling file
time	<i>[Optional]</i> character Time variable.
sim_bloq	logical if TRUE uses sim_bloq values for plotting. Only for Monolix 2018 and later.
file_name	character mlxtran file path.
call	logical if TRUE the result is the parameters parsed
version	integer Non-negative integer. Non-obligatory option, if you don't use a wildcard in the file_name. Otherwise you MUST provide version and wildcard will be substituted with "version", which represents the mlxtran model version.
...	extra arguments passed to pmx_mlx.

Details

`pmx_mlx` is a wrapper to `mlx` for the MONOLIX system (`sys="mlx"`)

`pmx_mlxtran` parses `mlxtran` file and guess `pmx_mlx` arguments. In case of multi endpoint the first endpoint is selected. You can though set the endpoint through the same argument. When you set `call=TRUE`, no controller is created but only the parameters parsed by `mlxtran`. This can be very helpful, in case you would like to customize parameters (adding settings via `pmx_settings`, changing default endpoint.)

Value

`pmxClass` controller object.

Examples

```
## Example to create the controller using theophylline data
theophylline <- file.path(system.file(package = "ggPMX"), "testdata",
                           "theophylline")
WORK_DIR <- file.path(theophylline, "Monolix")
input_file <- file.path(theophylline, "data_pk.csv")

## using only mandatory variables
ctr <- pmx(
  sys="mlx",
  config = "standing",
  directory = WORK_DIR,
  input = input_file,
  dv = "Y",
  dvid ="DVID"
)

## Using covariates
ctr <- pmx(
  sys="mlx",
  config = "standing",
  directory = WORK_DIR,
  input = input_file,
  dv = "Y",
  dvid ="DVID",
  cats=c("SEX"),
  conts=c("WT0", "AGE0"),
  strats="STUD"
)

## using settings parameter
ctr <- pmx(
  sys="mlx",
  config = "standing",
  directory = WORK_DIR,
  input = input_file,
  dv = "Y",
  dvid ="DVID",
  settings=list(is.draft=FALSE)
```

```

)

## using mlxtran file
mlxtran_file <-
  file.path(system.file(package = "ggPMX"),
    "testdata", "1_popPK_model", "project.mlxtran")
pmx_mlxtran(mlxtran_file)

## mlxtran , call =TRUE to get the pmx_mlx argument parsed by pmx_mlxtran
params <- pmx_mlxtran(mlxtran_file, call=TRUE)

str(params)
# $ directory: chr results_pathile
# $ input    : chr observation file path
# $ dv       : chr "DV"
# $ cats     : chr [1:4] "SEX" "RACE" "DISE" "ILOW"
# $ conts    : chr [1:4] "AGE0" "WT0" "HT0" "TRT"
# $ occ      : chr "ISS"
# $ dvid     : chr "YTYPE"
# $ endpoint :List of 5
# ..$ code   : chr "1"
# ..$ label  : chr ""
# ..$ unit   : chr ""
# ..$ file.code: chr "1"
# ..$ trans  : NULL
# ..$ attr(*, "class")= chr "pmxEndpointClass"
# $ config   : chr "standing"

```

pmxOptions

This function can be used to set ggPMX options

Description

getPmxOption retrieves the value of a ggPMX option. ggPMXOptions sets the value of ggPMX options; it can also be used to return a list of all currently-set ggPMX options.

Usage

```
pmxOptions(...)
```

Arguments

... Options to set, with the form name = value.

Details

There is a global option set, which is available by default.

Value

list with options that were set by the user

Options used in ggPMX

- **template_dir**: path to template directory

Examples

```
## Not run:
pmxOptions(template_dir = PATH_TO_CUSTOM_CONFIGURATION)

## End(Not run)
```

pmx_bloq

Creates BLOQ object attributes

Description

Creates BLOQ object attributes

Usage

```
pmx_bloq(
  cens = "CENS",
  limit = "LIMIT",
  colour = "pink",
  size = 2,
  linewidth = 1,
  alpha = 0.9,
  show = TRUE,
  ...
)
```

Arguments

cens	character the censoring column name
limit	character the limit column name (optional)
colour	character the color of the geom
size	numeric the size of the geom when using geom_point()
linewidth	numeric the line width of the segment when using geom_segment()
alpha	numeric the alpha of the geom
show	logical if FALSE remove all censory observations
...	any other graphical parameter

Details

To define that a measurement is censored, the observation data set should include a CENSORING column (default to 'CENS') and put 1 for lower limit or -1 for upper limit.
Optionally, data set can contain have a limit column (default to 'LIMIT') column to set the other limit.

pmx_comp_shrink	<i>Compute Shrinkage</i>
-----------------	--------------------------

Description

Compute Shrinkage

Usage

```
pmx_comp_shrink(  
  ctr,  
  fun = c("var", "sd"),  
  strat.facet,  
  strat.color,  
  filter,  
  ...  
)
```

Arguments

- ctr pmxClass controller object
- fun character can be sd or var , var by default
- strat.facet formula optional stratification parameter
- strat.color character optional stratification parameter
- filter optional filter which will be applied to plotting data
- ... others parameters not used for the moment

Value

data.table

pmx_config	<i>This function can be used to define the pmx configuration used in plots. e.g. Monolix/Nonmem</i>
------------	---

Description

This function can be used to define the pmx configuration used in plots. e.g. Monolix/Nonmem

Usage

```
pmx_config(sys = "mlx", inputs, plots, ...)
```

Arguments

sys	charcarter system used , monolix,nonmem,...
inputs	charcater path to the inputs settings file (yaml format)
plots	charcater path to the inputs settings file (yaml format)
...	extra arguments not used

Details

To create a controller user can create a pmxConfig object using

- either an input template file
- or a plot template file
- or both.

By default the 'standing' configuration will be used.

Value

pmxConfig object

Examples

```
# ***** Create a controller using custom plot configuration ***** -----

library(ggPMX)
theophylline <- file.path(
  system.file(package = "ggPMX"), "testdata",
  "theophylline"
)
WORK_DIR <- file.path(theophylline, "Monolix")
input_file <- file.path(theophylline, "data_pk.csv")

# create a controller with a custom plots template
ctr <- pmx_mlx(
  config = pmx_config(
    plots=file.path( system.file(package = "ggPMX"),"examples/plots.yaml"),
```

```

    inputs = system.file(package = "ggPMX", "examples/custom_inputs.yaml")
  ),
  directory = WORK_DIR,
  input = input_file,
  dv = "Y",
  dvid = "DVID",
  cats = c("SEX"),
  conts = c("WT0", "AGE0"),
  strats = "STUD"
)

## get the list of plots
ctr %>% plots
ctr %>% get_plot("custom_res_time")
ctr %>% get_plot("custom_npde_time")

```

pmx_copy

Creates a deep copy of the controller

Description

Creates a deep copy of the controller

Usage

```
pmx_copy(ctr, keep_globals = FALSE, ...)
```

Arguments

ctr	pmxClass object
keep_globals	logical if TRUE we keep the global parameters changed by pmx_settings
...	extra parameters passed to pmx_settings

Details

The controller is an ‘R6’ object, it behaves like a reference object. Some functions (methods) can have a side effect on the controller and modify it internally. Technically speaking we talk about chaining not piping here. However , using pmx_copy user can work on a copy of the controller.

By default the copy does not keep global parameters set using pmx_settings.

Value

an object of pmxClass

Examples

```
ctr <- theophylline()
cctr <- ctr %>% pmx_copy()
## Any change in the ctr has no side effect in the ctr and vice versa
```

pmx_cov	Select/Map covariates using human labels
---------	--

Description

Select/Map covariates using human labels

Usage

```
pmx_cov(values, labels = NULL)
```

Arguments

- values list of covariates to use to create the plot
- labels list of covariates facets labels

Details

In case of ‘pmx_plot_eta_cats’ and ‘pmx_plot_eta_conts’ you can customize the covariates and covaraites labels using ‘pmx_cov’.

Value

pmxCOVObject object

pmx_dens	Creates a density plot object
----------	-------------------------------

Description

Creates a density plot object

Usage

```
pmx_dens(
  x,
  labels,
  dname = NULL,
  xlim = 3,
  var_line = NULL,
  snd_line = NULL,
  vline = NULL,
  is.legend = TRUE,
  ...
)
```

Arguments

<code>x</code>	character variable name to sample
<code>labels</code>	list of texts/titles used within the plot
<code>dname</code>	name of dataset to be used
<code>xlim</code>	numeric x axis limits
<code>var_line</code>	list variable density graphics parameters
<code>snd_line</code>	list normal density graphics parameters
<code>vline</code>	list vertical line graphics parameters
<code>is.legend</code>	logical whether to add a legend (defaults TRUE)
<code>...</code>	others graphics arguments passed to pmx_gpar internal object.

Details

labels is a list that contains:

- **title:** plot title default "IWRES density plot"
- **x:** x axis label default to "Etas"
- **y:** y axis label default to empty

var_line is a list that contains:

- **linetype:** default to 1
- **color:** default to black
- **linewidth:** default to 1

snd_line is a list that contains:

- **linetype:** default to 2
- **color:** default to black
- **linewidth:** default to 1

vline is a list that contains:

- **linetype:** default to 3
- **color:** default to black
- **linewidth:** default to 1

Value

list with options for density plot object

pmx_endpoint	<i>Creates pmx endpoint object</i>
--------------	------------------------------------

Description

Creates pmx endpoint object

Usage

```
pmx_endpoint(code, label = "", unit = "", file.code = code, trans = NULL)
```

Arguments

code	character endpoint code : used to filter observations <code>DVID==code</code> .
label	character endpoint label: used to set title and axis labels
unit	character endpoint unit : used to set title and axis labels
file.code	character endpoint file code : used to set predictions and finegrid files extensions in case using code parameter is not enough.
trans	list Transformation parameter not used yet.

Details

In case of multiple endpoints, pkpd case for example, we need to pass endpoint to the pmx call. Internally , ggPMX will filter the observations data set to keep only rows satisfying `DVID==code`. The code is also used to find the right predictions and or finegrid files. ggPMX use the configuration file to find the path of the predictions file (like the single endpoint case) and then filter the right file using the code parameter.

For example:

- `predictions{code}.txt` for `mlx16`
- `predictions{code}.txt` and `y{code}_residual` for `mlx18`

For some tricky examples the code parameter is not enough to find the files. In that case the `file.code` parameter is used to distinguish the endpoint files.

Examples

```
## Use file.code parameter
pk_pd_path <- file.path(system.file(package = "ggPMX"), "testdata", "pk_pd")

WORK_DIR <- file.path(pk_pd_path, "RESULTS")

ep <- pmx_endpoint(
  code="4",
  file.code="2"
)

input_file <- file.path(pk_pd_path, "pk_pd.csv")

ctr <- pmx_mlx(
  config = "standing",
  directory = WORK_DIR,
  input = input_file,
  dv = "dv",
  dvid = "dvid",
  cats = "sex",
  conts = "wt",
  endpoint = ep
)

## using mlxtran

ep <- pmx_endpoint(
  code="3",
  file.code="1"
)

mlxtran_file <- file.path(pk_pd_path, "pk_pd.mlxtran")
ctr <- pmx_mlxtran(mlxtran_file, endpoint=ep)
```

pmx_filter

filter data in a pmx controller

Description

filter data in a pmx controller

Usage

```
pmx_filter(
  ctr,
  data_set = c("estimates", "predictions", "eta", "finegrid", "shrink", "input",
    "individual", "sim_blk"),
  pmx_exp
)
```

Arguments

ctr	A controller. An object of 'pmxClass'
data_set	A data_set within the controller to apply a filter to.
pmx_exp	A filter expression

Value

Returns a pmx controller with a filtered data set.

Examples

```
## example of global filter
ctr <- theophylline()
ctr %>% pmx_filter(data_set = "prediction", ID == 5 & TIME < 2)
ctr %>% get_data("prediction")
```

pmx_get_configs	<i>Get List of built-in configurations</i>
-----------------	--

Description

Get List of built-in configurations

Usage

```
pmx_get_configs(sys = "mlx")
```

Arguments

sys	can be mlx, by default all configurations will be listed
-----	--

Value

names of the config

Examples

```
pmx_get_configs()
```

pmx_gpar

*Handling pmx Graphical parameters***Description**

Handling pmx Graphical parameters

Usage

```
pmx_gpar(
  is.title,
  labels,
  axis.title,
  which_pages,
  print,
  axis.text,
  ranges,
  is.smooth,
  smooth,
  is.band,
  band,
  is.draft,
  draft,
  discrete,
  is.identity_line,
  identity_line,
  smooth_with_bloq,
  scale_x_log10,
  scale_y_log10,
  color.scales,
  is.legend,
  legend.position
)
```

Arguments

is.title	logical if TRUE then a title is used for the plot
labels	list of labels, like title, subtitle, x , y
axis.title	list or element_text (same as ggplot2 axis.title theme)
which_pages	page(s) to display; if "all" display all pages, if 1 display first page, if c(1,2) display first and second pages
print	if TRUE the ouptut will be a print not a ggplot2. This is useful for rmarkdwon output to avoid verbose list index print.
axis.text	list or element_text (same as ggplot2 axis.text theme)
ranges	limits of x/y ranges

is.smooth	logical if set to TRUE add smooth layer
smooth	smooth layer parameters
is.band	logical if TRUE add horizontal band
band	horizontal band parameters
is.draft	logical if TRUE add draft layer
draft	draft layer parameters
discrete	logical if TRUE x axis is discrete(FALSE by default)
is.identity_line	logical if TRUE add y=x line
identity_line	list y=x aes properties
smooth_with_bloq	logical if TRUE perform spline in plots with BLOQ data
scale_x_log10	logical if TRUE add scale_x_log10 layer
scale_y_log10	logical if TRUE add scale_y_log10 layer
color.scales	list define scales parameter in case of strat.color pmx_settings
is.legend	logical if TRUE x axis is discrete(FALSE by default)
legend.position	character legend position it takes the same value as the equivalent ggplot2 parameter

Details

This object contains all general graphic settings. It used internally by all `pmx_plot`(generic function) to set the default behavior.

Value

An object of class "pmx_gpar".

pmx_list_nm_tables	<i>List NONMEM output tables</i>
--------------------	----------------------------------

Description

List NONMEM output tables file names from a `nm_model` object.

Usage

```
pmx_list_nm_tables(nm_model = NULL)
```

Arguments

`nm_model` An `nm_model` object generated with [pmx_read_nm_model](#).

See Also

[pmx_read_nm_model](#), [pmx_read_nm_tables](#)

Examples

```
## Not run:
pmx_read_nm_model(file = 'run001.lst') %>%
  pmx_list_nm_tables()

## End(Not run)
```

pmx_manual_nm_import *Manually define nonmem tables to be imported*

Description

Manually provide names of the table files to be imported.

Usage

```
pmx_manual_nm_import(
  tab_names = c("sdtab", "mutab", "patab", "catab", "cotab", "mytab", "extra", "xptab",
    "cwtab"),
  tab_suffix = "",
  sim_suffix = "sim"
)
```

Arguments

tab_names	Provide the name of the tables to import e.g. 'sdtab', 'patab', 'cotab', 'catab' for NONMEM.
tab_suffix	Default is "", but can be changed to any character string to be used as suffix in the table names.
sim_suffix	Default is 'sim', but can be changed to any character string to be used as suffix in the simulation table names e.g. sdtab001sim.

pmx_nlmixr	<i>Creates pmx controller from an nlmixr fit object</i>
------------	---

Description

Creates pmx controller from an nlmixr fit object

Usage

```
pmx_nlmixr(fit, dvid, conts, cats, strats, endpoint, settings, vpc = FALSE)
```

Arguments

fit	nlmixr object
dvid	<i>[Optional]</i> character observation type parameter.
conts	<i>[Optional]</i> character vector of continuous covariates
cats	<i>[Optional]</i> character vector of categorical covariates
strats	<i>[Optional]</i> character extra stratification variables
endpoint	pmxEndpointClass or integer or character default to NULL of the endpoint code. pmx_endpoint
settings	<i>[Optional]</i> pmxSettingsClass pmx_settings
vpc	<i>[Optional]</i> logical a boolean indicating if vpc should be calculated (by default TRUE)

Value

pmxClass controller object.

pmx_nm	<i>Creates pmx controller from NONMEM model outputs</i>
--------	---

Description

Creates pmx controller from NONMEM model outputs

Usage

```

pmx_nm(
  file = NULL,
  directory = ".",
  runno = NULL,
  ext = ".lst",
  table_suffix = "",
  sim_suffix = "sim",
  simfile = NULL,
  prefix = "run",
  table_names = c("sdtab", "mutab", "patab", "catab", "cotab", "mytab", "extra", "xptab",
    "cwtab"),
  dvid = "DVID",
  pred = "PRED",
  time = "TIME",
  dv = "DV",
  conts,
  cats,
  npde,
  iwres,
  ipred,
  endpoint,
  strats = "",
  settings = pmx_settings(),
  vpc = TRUE,
  bloq = NULL,
  obs = FALSE,
  quiet = FALSE
)

```

Arguments

file	A character vector of path to the files or a nm_table_list object created with pmx_list_nm_tables.
directory	directory of the model files.
runno	run number which is used for generating the model file name, or used for alternative import of NONMEM-output tables.
ext	Extension to be used to generate model file name. Should be one of '.lst' (default), '.out', '.res', '.mod' or '.ctl' for NONMEM.
table_suffix	suffix of the output tables, standard is "" (no suffix).
sim_suffix	suffix of the simulation output tables, standard is "sim" (e.g. stdab1sim).
simfile	Useful if the simulation is performed post-hoc and an additional simulation model file is generated e.g. "simulation.lst"; similar to "file" see above.
prefix	Prefix to be used to generate model file name. Used in combination with runno and ext.

table_names	contains the names of the NONMEM-output tables e.g. "sdtab", "patlab", "cotab", "catab".
dvid	[Optional] character observation type parameter, mandatory in case of multiple endpoint (PKPD). Standard = "DVID"
pred	[Optional] character specifying variable name of the population prediction (standard ggPMX nomenclature = "PRED")
time	[Optional] character specifying variable name of time (standard ggPMX nomenclature = "TIME")
dv	character the name of measurable variable used in the input modelling file (standard ggPMX nomenclature = "DV")
conts	[Optional] character vector of continuous covariates (automatically detected if "cotab" is provided)
cats	[Optional] character vector of categorical covariates (automatically detected if "catab" is provided)
npde	[Optional] character specifying variable name of the normalized population predictor (standard ggPMX nomenclature = "NPDE")
iwres	[Optional] character specifying variable name of the individual weighted residuals (standard ggPMX nomenclature = "IWRES")
ipred	[Optional] character specifying variable name of the individual population prediction (standard ggPMX nomenclature = "IPRED")
endpoint	[Optional] pmxEndpointClass or integer or character default to NULL of the endpoint code. pmx_endpoint
strats	[Optional] character extra stratification variables
settings	pmxSettingsClass pmx_settings shared between all plots
vpc	logical a boolean indicating if vpc should be calculated, simulation tables are required for VPC generation (by default TRUE)
bloq	pmxBLOQClass default to NULL. pmx_bloq specify bloq, within controller: e.g. bloq=pmx_bloq(cens = "BLOQ_name", limit = "LIMIT_name")
obs	logical if set to TRUE will filter dataset according to "MDV", default is FALSE
quiet	Logical, if FALSE messages are printed to the console.

Value

pmxClass controller object.

Author(s)

The ggPMX NONMEM reader (pmx_nm) is strongly based on NONMEM reading functions of the xpose package (v.0.4.11) (Thanks to Benjamin Guastrenec) To avoid conflicts with the xpose package, the necessary xpose-based functions have been renamed with a "pmx_" prefix. If the user wants to use individual functions e.g. "read_nm_tables" please use the xpose-package

Examples

```
## using only runnumber
# ctr <- pmx_nm(
#   directory=model_dir,
#   runno = "001"
#)

## using a model file (e.g. run001.lst)
#ctr <- pmx_nm(
#   directory=model_dir,
#   file = "run001.lst"
#)

## if simulation was performed post-hoc, an additional simulation file can be loaded for VPC
#ctr <- pmx_nm(
#   directory=model_dir,
#   file = "run001.lst",
#   simfile = "simulation.ct1"
#)

## loading with individual table(s)-names
#ctr <- pmx_nm(directory = model_dir,
#              #           runno = 3,
#              #           table_names = "xptab")
```

pmx_plot

Generic pmx plot

Description

Generic pmx plot

Usage

```
pmx_plot(ctr, pname, ...)
```

Arguments

ctr	pmxClass pmx controller
pname	plot name
...	others graphics parameters passed :
	• pmx_gpar internal function to customize shared graphical parameters • pmx_qq quantile-quantile plot object • pmx_update function.

Value

ggplot2 object

pmx_plot_cats	<i>Generic pmx stratified plot</i>
---------------	------------------------------------

Description

Generic pmx stratified plot

Usage

```
pmx_plot_cats(ctr, pname, cats, chunk = "", print = TRUE, ...)
```

Arguments

ctr	pmxClass pmx controller
pname	plot name
cats	list of categorical variables. By default all of them
chunk	chunk name
print	logical if TRUE print plots otherwise the list of plots is returned
...	others graphics parameters passed : • pmx_gpar internal function to customize shared graphical parameters • pmx_qq quantile-quantile plot object • pmx_update function.

Value

ggplot2 object(s)

pmx_plot_eta_matrix	<i>Eta matrix plot</i>
---------------------	------------------------

Description

Eta matrix plot

Usage

```
pmx_plot_eta_matrix(
  ctr,
  title,
  dname,
  type.eta,
  text_color,
  is.shrink,
```

```

    shrink,
    point,
    is.smooth,
    smooth,
    is.hline,
    hline,
    is.vreference_line,
    vreference_line,
    filter,
    strat.facet,
    facets,
    strat.color,
    trans,
    pmxgpar,
    labels,
    axis.title,
    axis.text,
    ranges,
    is.band,
    band,
    is.draft,
    draft,
    is.identity_line,
    identity_line,
    scale_x_log10,
    scale_y_log10,
    color.scales,
    ...
  )

```

Arguments

ctr	pmx controller
title	character the plot title
dname	name of dataset to be used
type.eta	character type of eat can be 'mode' or 'mean'. 'mode' by default
text_color	color of the correlation text in the upper matrix
is.shrink	logical if TRUE add shrinkage to the plot
shrink	pmxShrinkClass shrinkage graphical parameter or list coercible into one
point	list geom_point graphical parameter
is.smooth	logical if TRUE add smoothing to lower matrix plots
smooth	list geom_smooth graphical parameters
is.hline	logical if TRUE add horizontal line to lower matrix plots
hline	list geom_hline graphical parameters
is.vreference_line	logical if TRUE add reference line to diag plots

vreference_line	list geom_vline graphical parameters
pmx_update parameters	
filter	expression filter which will be applied to plotting data.
strat.facet	formula optional stratification parameter by facetting. This split plot by strats(each strat in a facet)
facets	list facet_wrap parameters.
strat.color	character optional stratification parameter by grouping. This will split the plot by group (color) of strat.
trans	character define the transformation to apply on x or y or both variables
pmxgpar	a object of class pmx_gpar possibly the output of the
pmx_gpar: Shared basic graphics parameters	
labels	list list containing plot and/or axis labels: title, subtitle, x , y
axis.title	list containing element_text attributes to customize the axis title. (similar to ggplot2 axis.title theme)
axis.text	list containing element_text attributes to customize the axis text (similar to ggplot2 axis.text theme)
ranges	list limits of x/y ranges
is.band	logical if TRUE add horizontal band
band	list horizontal band parameters. geom_hline graphical parameters.
is.draft	logical if TRUE add draft layer
draft	list draft layer parameters. geom_text graphical parameters.
is.identity_line	logical if TRUE add an identity line
identity_line	listgeom_abline graphical parameters.
scale_x_log10	logical if TRUE use log10 scale for x axis.
scale_y_log10	logical if TRUE use log10 scale for y axis.
color.scales	list define scales parameter in case of strat.color pmx_settings
...	others graphics parameters passed : • pmx_gpar internal function to customize shared graphical parameters • eta_pairs ggPMX internal function for eta matrix plot. • pmx_update function.

eta_pairs parameters**Value**

ggplot2 object

Examples

```

# basic use -----

ctr <- theophylline()
p <- ctr %>% pmx_plot_eta_matrix

# update graphical parameter -----

## update labels
ctr %>% pmx_plot_eta_matrix(
  labels = list(title = "Eta matrix new title")
)

## remove draft
ctr %>% pmx_plot_eta_matrix(is.draft = FALSE)

## change text color line
ctr %>% pmx_plot_eta_matrix(
  text_color="red",
  shrink=pmx_shrink(mapping=aes(color="magenta"))
)

## custom point aes and static parameters
## we can customize any geom_point parameter
ctr %>% pmx_plot_eta_matrix(
  point = list(color = "blue", shape = 4)
)

# stratification -----

## IGNORE continuous stratification
ctr %>% pmx_plot_eta_matrix(strat.color = "WT0")
## IGNORE categorical stratification
ctr %>% pmx_plot_eta_matrix(strat.facet = ~SEX)

# subsetting -----

## we can use any expression involving the data
ctr %>% pmx_plot_eta_matrix(filter = EFFECT%in% c("C1", "ka"))

```

pmx_plot_individual *Individual plot*

Description

Individual plot

Usage

```
pmx_plot_individual(
  ctr,
  which_pages = 1L,
  print = FALSE,
  dname,
  pred_line,
  ipred_line,
  point,
  is.legend,
  use.finegrid,
  bloq,
  filter,
  strat.facet,
  facets,
  strat.color,
  trans,
  pmxgpar,
  labels,
  axis.title,
  axis.text,
  ranges,
  is.smooth,
  smooth,
  is.band,
  band,
  is.draft,
  draft,
  is.identity_line,
  identity_line,
  scale_x_log10,
  scale_y_log10,
  color.scales,
  ...
)
```

Arguments

ctr	pmx controller
which_pages	integer page(s) to display, or character "all" to display all pages (argument previously called npage, now deprecated)
print	logical if TRUE the ouptut will be a print not a ggplot2. This is useful for rmarkdwon output to avoid verbose list index print.
dname	character name of dataset to be used. User can create his own dataset using set_data and pass it as dname to be plotted.
pred_line	list some ipred line geom properties aesthetics
ipred_line	list some pred line geom properties aesthetics

point	list some point geom properties aesthetics
is.legend	logical if TRUE add a legend
use.finegrid	logical if FALSE use predictions data set
bloq	pmxBLOQ object created by pmx_bloq .
pmx_update parameters	
filter	expression filter which will be applied to plotting data.
strat.facet	formula optional stratification parameter by facetting. This split plot by strats(each strat in a facet)
facets	list facet_wrap parameters.
strat.color	character optional stratification parameter by grouping. This will split the plot by group (color) of strat.
trans	character define the transformation to apply on x or y or both variables
pmxgpar	a object of class pmx_gpar possibly the output of the
pmx_gpar: Shared basic graphics parameters	
labels	list list containing plot and/or axis labels: title, subtitle, x , y
axis.title	list containing element_text attributes to customize the axis title. (similar to ggplot2 axis.title theme)
axis.text	list containing element_text attributes to customize the axis text (similar to ggplot2 axis.text theme)
ranges	list limits of x/y ranges
is.smooth	logical if set to TRUE add smooth layer
smooth	list geom_smooth graphical/smoothing fun parameters
is.band	logical if TRUE add horizontal band
band	list horizontal band parameters. geom_hline graphical parameters.
is.draft	logical if TRUE add draft layer
draft	list draft layer parameters. geom_text graphical parameters.
is.identity_line	logical if TRUE add an identity line
identity_line	listgeom_abline graphical parameters.
scale_x_log10	logical if TRUE use log10 scale for x axis.
scale_y_log10	logical if TRUE use log10 scale for y axis.
color.scales	list define scales parameter in case of strat.color pmx_settings
...	others graphics parameters passed : • pmx_gpar internal function to customize shared graphical parameters • individual generic object for individual plots. • pmx_update function.

individual parameters**Value**

ggplot2 or list of ggplot2 objects

Examples

```

# basic use -----

ctr <- theophylline()
ctr %>% pmx_plot_individual(which_pages = 1)
## multiple pages
ctr %>% pmx_plot_individual(which_pages = c(1, 3))
## change faceting
ctr %>% pmx_plot_individual(facets = list(nrow = 5, ncol = 5), which_pages = 2)

# update graphical parameter -----

## update labels
ctr %>% pmx_plot_individual(
  labels = list(title = "Custom individual plot")
)

## remove draft
ctr %>% pmx_plot_individual(is.draft = FALSE)

## Customize ipred_line with any geom_line parameter
ctr %>% pmx_plot_individual(
  pred_line = list(color = "red", linetype = 20, alpha = 0.5)
)

## Customize ipred_line with any geom_line parameter
ctr %>% pmx_plot_individual(
  ipred_line = list(size = 5)
)

## Customize any geom_point parameter
ctr %>% pmx_plot_individual(
  point = list(aes(alpha = DV), color = "green", shape = 4)
)

## legend

p <- ctr %>% pmx_plot_individual(
  is.legend=TRUE,
  point=list(shape=20),
  pred_line=list(linetype=6)
)

# # stratification -----
#
# ## continuous stratification
ctr %>% pmx_plot_individual(strat.color = "WT0")

# # subsetting -----

```

```
#
# ## we can use any expression involving the data
# ## filter and stratify
ctr %>% pmx_plot_individual(
  filter = SEX == 1, strat.facet = ~SEX,
  facets = list(nrow = 5, ncol = 5))

# # transformation -----
#
# ## apply a log transformation in y
ctr %>% pmx_plot_individual(trans = "log10_y")
# ## apply a custom transformation to normalize axis between 0 and 1

## get a list of parameter
p <- ctr %>% pmx_plot_individual(
  which_pages="all",
  point=list(shape=4,color='blue',size=10),
  facets = list(nrow = 5, ncol = 5),
  labels = list(title = "My individuals",x='my time',y='PD data')
)
```

pmx_plot_iwres_dens *IWRES density plot*

Description

IWRES density plot

Usage

```
pmx_plot_iwres_dens(
  ctr,
  sim_blk,
  dname,
  xlim,
  var_line,
  snd_line,
  vline,
  filter,
  strat.facet,
  facets,
  strat.color,
  trans,
  pmxgpar,
  labels,
  axis.title,
  axis.text,
```

```

    ranges,
    is.smooth,
    smooth,
    is.band,
    band,
    is.draft,
    draft,
    is.identity_line,
    identity_line,
    scale_x_log10,
    scale_y_log10,
    color.scales,
    ...
  )

```

Arguments

ctr	pmx controller
sim_blq	logical if TRUE uses sim_blq as dataset for plotting instead of predictions.
dname	character name of dataset to be used. User can create his own dataset using set_data and pass it as dtype to be plotted.
xlim	numeric x axis limits
var_line	list variable density graphics parameters
snd_line	list normal density graphics parameters
vline	list vertical line graphics parameters
	pmx_update parameters
filter	expression filter which will be applied to plotting data.
strat.facet	formula optional stratification parameter by faceting. This split plot by strats(each strat in a facet)
facets	list facet_wrap parameters.
strat.color	character optional stratification parameter by grouping. This will split the plot by group (color) of strat.
trans	character define the transformation to apply on x or y or both variables
pmxgpar	a object of class pmx_gpar possibly the output of the
	pmx_gpar: Shared basic graphics parameters
labels	list list containing plot and/or axis labels: title, subtitle, x , y
axis.title	list containing element_text attributes to customize the axis title. (similar to ggplot2 axis.title theme)
axis.text	list containing element_text attributes to customize the axis text (similar to ggplot2 axis.text theme)
ranges	list limits of x/y ranges
is.smooth	logical if set to TRUE add smooth layer
smooth	list geom_smooth graphical/smoothing fun parameters

is.band	logical if TRUE add horizontal band
band	list horizontal band parameters. geom_hline graphical parameters.
is.draft	logical if TRUE add draft layer
draft	list draft layer parameters. geom_text graphical parameters.
is.identity_line	logical if TRUE add an identity line
identity_line	listgeom_abline graphical parameters.
scale_x_log10	logical if TRUE use log10 scale for x axis.
scale_y_log10	logical if TRUE use log10 scale for y axis.
color.scales	list define scales parameter in case of strat.color pmx_settings
...	others graphics parameters passed : • pmx_gpar internal function to customize shared graphical parameters • pmx_dens pmx density object. • pmx_update function.

pmx_dens parameters

Value

ggplot2 or list of ggplot2 objects

pmx_plot_saem_convergence

SAEM Convergence Plot

Description

This plot displays the sequence of estimates for population parameters computed after each iteration of the SAEM algorithm. The purpose is to check the convergence of the algorithm. In addition, a convergence indicator gives the estimation for $-2 \times \log\text{-likelihood}$ along the iterations.

Usage

```
pmx_plot_saem_convergence(ctr, ...)
```

Arguments

ctr	pmxClass controller.
...	additional parameters (not used).

Value

A ggplot object showing SAEM convergence plot.

pmx_plot_vpc*VPC plot*

Description

VPC plot

Usage

```
pmx_plot_vpc(  
  ctr,  
  type,  
  idv,  
  obs,  
  pi,  
  ci,  
  rug,  
  bin,  
  is.legend,  
  sim_blk,  
  dname,  
  filter,  
  strat.facet,  
  facets,  
  strat.color,  
  trans,  
  pmxgpar,  
  labels,  
  axis.title,  
  axis.text,  
  ranges,  
  is.smooth,  
  smooth,  
  is.band,  
  band,  
  is.draft,  
  draft,  
  is.identity_line,  
  identity_line,  
  scale_x_log10,  
  scale_y_log10,  
  color.scales,  
  is.footnote,  
  ...  
)
```

Arguments

ctr	pmx controller
type	character can be either percentile or scatter
idv	character individual variable
obs	pmx_vpc_obs object observation layer pmx_vpc_obs
pi	pmx_vpc_pi object percentile layer pmx_vpc_pi
ci	pmx_vpc_ci object confidence interval layer pmx_vpc_ci
rug	pmx_vpc_rug object rug layer pmx_vpc_rug . Note: consider not using a rug layer when bin[["within_strat"]]=TRUE, since the rugs plotted will not reflect the bins.
bin	pmx_vpc_bin object pmx_vpc_bin specify within pmx_plot_vpc() e.g.: bin = pmx_vpc_bin(style = "kmeans", n = 10)
is.legend	logical if TRUE add legend
sim_bld	logical if TRUE uses sim_bld values for plotting. Only for Monolix 2018 and later.
dname	added for compatibility with other ggPMX plots pmx_update parameters
filter	expression filter which will be applied to plotting data.
strat.facet	formula optional stratification parameter by faceting. This split plot by strats(each strat in a facet)
facets	list facet_wrap parameters.
strat.color	character optional stratification parameter by grouping. This will split the plot by group (color) of strat.
trans	character define the transformation to apply on x or y or both variables
pmxgpar	a object of class pmx_gpar possibly the output of the pmx_gpar: Shared basic graphics parameters
labels	list list containing plot and/or axis labels: title, subtitle, x , y
axis.title	list containing element_text attributes to customize the axis title. (similar to ggplot2 axis.title theme)
axis.text	list containing element_text attributes to customize the axis text (similar to ggplot2 axis.text theme)
ranges	list limits of x/y ranges
is.smooth	logical if set to TRUE add smooth layer
smooth	list geom_smooth graphical/smoothing fun parameters
is.band	logical if TRUE add horizontal band
band	list horizontal band parameters. geom_hline graphical parameters.
is.draft	logical if TRUE add draft layer
draft	list draft layer parameters. geom_text graphical parameters.
is.identity_line	logical if TRUE add an identity line

identity_line listgeom_abline graphical parameters.
 scale_x_log10 logical if TRUE use log10 scale for x axis.
 scale_y_log10 logical if TRUE use log10 scale for y axis.
 color.scales list define scales parameter in case of strat.color [pmx_settings](#)
 is.footnote logical if TRUE add footnote
 ... others graphics parameters passed :

- [pmx_gpar](#) internal function to customize shared graphical parameters
- [pmx_vpc](#) pmx vpc object.
- [pmx_update](#) function.

pmx_vpc parameters

Details

You can use [pmx_vpc_bin](#) to set the bin parameters. In case of stratification, binning can be different for each strat level (case within_strat equal to FALSE).

Value

ggplot2 or list of ggplot2 objects

See Also

Other vpc: [pmx_vpc\(\)](#), [pmx_vpc_bin\(\)](#), [pmx_vpc_ci\(\)](#), [pmx_vpc_obs\(\)](#), [pmx_vpc_pi\(\)](#), [pmx_vpc_rug\(\)](#)

Examples

```
library(ggPMX)

theo_path <- file.path(
  system.file(package = "ggPMX"), "testdata",
  "theophylline"
)
WORK_DIR <- file.path(theo_path, "Monolix")
input_file <- file.path(theo_path, "data_pk.csv")
vpc_file <- file.path(theo_path, "sim.csv")

ctr <- pmx_mlx(
  config = "standing",
  directory = WORK_DIR,
  input = input_file,
  dv = "Y",
  dvid = "dvid",
  cats = c("SEX"),
  conts = c("WT0", "AGE0"),
  strats = "STUD",
  settings = pmx_settings(
    use.labels=TRUE,
    cats.labels=list(
      SEX=c("0"="Male", "1"="Female")
    )
  )
)
```

```

    )
  ),
  sim = pmx_sim(
    file = vpc_file,
    irun = "rep",
    idv = "TIME"
  )
)

ctr %>% pmx_plot_vpc(
  strat.facet=~SEX,
  facets=list(nrow=2),
  type="percentile",
  is.draft = FALSE,
  pi = pmx_vpc_pi(interval = c(0.1,0.9),
    median=list(color="green"),
    extreme= list(color="green")),
  obs = pmx_vpc_obs(color="blue",shape=18,size=2),
  ci = pmx_vpc_ci(interval = c(0.1,0.9),
    median=list(fill="pink")),
  bin=pmx_vpc_bin("kmeans",n=5)
)

ctr %>%
  pmx_plot_vpc(bin= pmx_vpc_bin(
    style = "fixed",
    fixedBreaks=c(-10,2, 5, 10,15,50))
  )

# example with legend

ctr %>% pmx_plot_vpc(
  is.legend = TRUE,
  pi = pmx_vpc_pi(interval=c(0.02,0.98),median = list(linetype="dotted")),
  ci = pmx_vpc_ci(interval = c(0.05,0.95),median=list(fill="red"))
)

```

pmx_qq

This function creates a qq plot object

Description

This function creates a qq plot object

Usage

```
pmx_qq(
```



```

    x,
    labels,
    dname = NULL,
    point = NULL,
    xmax = TRUE,
    facets = NULL,
    is.reference_line = NULL,
    reference_line = NULL,
    is.shrink = NULL,
    shrink = NULL,
    is.hline = NULL,
    hline = NULL,
    is.vline = NULL,
    vline = NULL,
    ...
  )

```

Arguments

<code>x</code>	character variable name to sample
<code>labels</code>	list of texts/titles used within the plot
<code>dname</code>	name of dataset to be used
<code>point</code>	list <code>geom_point</code> attributes color, shape,...
<code>xmax</code>	logical if FALSE do not use <code>max(aes(x))</code> as limits default to TRUE
<code>facets</code>	list
<code>is.reference_line</code>	logical if TRUE add reference line to the plot
<code>reference_line</code>	list <code>geom_line</code> attributes. Used only for <code>pmx_plot_eta_qq</code>
<code>is.shrink</code>	logical if TRUE add shrinkage to the plot
<code>shrink</code>	<code>pmxShrinkClass</code> shrinkage graphical parameter or list coercible into one
<code>is.hline</code>	logical if TRUE add horizontal line $y=0$ (TRUE by default)
<code>hline</code>	geom hline graphical parameters
<code>is.vline</code>	logical if TRUE add vertical line $x=0$ (TRUE by default)
<code>vline</code>	geom vline graphical parameters
<code>...</code>	others graphics arguments passed to <code>pmx_gpar</code> internal object.

Details

labels is a list that contains:

- **title:** plot title default "EBE vs. covariates"
- **x:** x axis label default to "Etas"
- **y:** y axis label default to empty

point is a list that contains:

- **shape:** default to 1
- **color:** default to black
- **size:** default to 1

Value

pmx_qq object

pmx_qq_plot

Quantile-quantile plots

Description

Quantile-quantile plots

Quantile-quantile plot of IWRES

Quantile-quantile plot of eta variables

Quantile-quantile plot of NPDE

Quantile-quantile plot of NPD

Quantile-quantile plot of CWRES

Usage

```
pmx_qq_plot(
  dname,
  point,
  is.reference_line,
  reference_line,
  is.shrink,
  shrink,
  is.hline,
  hline,
  is.vline,
  vline,
  filter,
  strat.facet,
  facets,
  strat.color,
  trans,
  pmxgpar,
  labels,
  axis.title,
  axis.text,
  ranges,
  is.smooth,
  smooth,
```

```

    is.band,
    band,
    is.draft,
    draft,
    is.identity_line,
    identity_line,
    scale_x_log10,
    scale_y_log10,
    color.scales,
    ...
)

pmx_plot_iwres_qq(ctr, ...)

pmx_plot_eta_qq(ctr, ...)

pmx_plot_npde_qq(ctr, ...)

pmx_plot_npd_qq(ctr, ...)

pmx_plot_cwres_qq(ctr, ...)

```

Arguments

dtype	name of dataset to be used
point	list geom_point parameters.
is.reference_line	logical if TRUE add reference line to the plot
reference_line	list geom_abline parameters.
is.shrink	logical if TRUE add shrinkage to the plot
shrink	pmxShrinkClass shrinkage graphical parameter or list coercible into one
is.hline	logical if TRUE add horizontal line y=0 (TRUE by default)
hline	list geom_hline graphical parameters
is.vline	logical if TRUE add vertical line x=0 (TRUE by default)
vline	list geom_vline graphical parameters
	pmx_update parameters
filter	expression filter which will be applied to plotting data.
strat.facet	formula optional stratification parameter by facetting. This split plot by strats(each strat in a facet)
facets	list facet_wrap parameters.
strat.color	character optional stratification parameter by grouping. This will split the plot by group (color) of strat.
trans	character define the transformation to apply on x or y or both variables
pmxgpar	an object of class pmx_gpar

labels	list list containing plot and/or axis labels: title, subtitle, x , y
axis.title	list containing element_text attributes to customize the axis title. (similar to ggplot2 axis.title theme)
axis.text	list containing element_text attributes to customize the axis text (similar to ggplot2 axis.text theme)
ranges	list limits of x/y ranges
is.smooth	logical if set to TRUE add smooth layer
smooth	list geom_smooth graphical/smoothing fun parameters
is.band	logical if TRUE add horizontal band
band	list horizontal band parameters. geom_hline graphical parameters.
is.draft	logical if TRUE add draft layer
draft	list draft layer parameters. geom_text graphical parameters.
is.identity_line	logical if TRUE add an identity line
identity_line	listgeom_abline graphical parameters.
scale_x_log10	logical if TRUE use log10 scale for x axis.
scale_y_log10	logical if TRUE use log10 scale for y axis.
color.scales	list define scales parameter in case of strat.color pmx_settings
...	others graphics parameters passed : • pmx_gpar internal function to customize shared graphical parameters • pmx_qq quantile-quantile plot object. • pmx_update function.
	pmx_qq parameters
ctr	pmx controller

Value

ggplot2 object

Examples

```
# ***** basic use ***** -----

ctr <- theophylline()
ctr %>% pmx_plot_eta_qq
ctr %>% pmx_plot_npde_qq
ctr %>% pmx_plot_iwres_qq

# update graphical parameter -----

## add reference line
ctr %>% pmx_plot_npde_qq(reference_line=list(color="blue"))
```

```
## remove reference line
ctr %>% pmx_plot_eta_qq(reference_line=NULL)

# stratification -----

## categorical stratification color parameter
ctr %>% pmx_plot_iwres_qq(strat.facet=~STUD,strat.color="SEX")
## categorical stratification facetting
ctr %>% pmx_plot_eta_qq(strat.facet = ~SEX)

## do not use symmetric axis
ctr %>% pmx_plot_npde_qq(xmax=FALSE,reference_line=list())
```

pmx_read_nm_files	<i>NONMEM output file import function</i>
-------------------	---

Description

Quickly import NONMEM output files into R.

Usage

```
pmx_read_nm_files(
  runno = NULL,
  prefix = "run",
  ext = c(".ext", ".cor", ".cov", ".phi", ".grd", ".shk"),
  file = NULL,
  dir = NULL,
  quiet = FALSE
)
```

Arguments

runno	Run number to be evaluated.
prefix	Prefix of the model file names.
ext	A vector of the file extension to import. By default '.ext', '.cor', '.cov', '.phi', '.grd', '.shk' files are listed.
file	Names of the model output file to be imported. Alternative argument to prefix, runno and ext.
dir	Location of the model files.
quiet	Logical, if FALSE messages are printed to the console.

Examples

```
## Not run:
# Using the `file` argument to import a model file:
ext_file <- pmx_read_nm_files(file = 'run001.ext', dir = 'models')

# Using the `runno` argument to import a model file:
ext_file <- pmx_read_nm_files(runno = '001', ext = '.ext', dir = 'models')

## End(Not run)
```

pmx_read_nm_model	<i>NONMEM model file parser</i>
-------------------	---------------------------------

Description

Parse NONMEM model files in R format

Usage

```
pmx_read_nm_model(
  runno = NULL,
  prefix = "run",
  ext = ".lst",
  file = NULL,
  dir = NULL
)
```

Arguments

runno	run number which is used for generating the model file name
prefix	Prefix to be used to generate model file name. Used in combination with runno and ext.
ext	Extension to be used to generate model file name. Should be one of '.lst' (default), '.out', '.res', '.mod' or '.ctl' for NONMEM.
file	A character vector of path to the files or a nm_table_list object created with list_nm_tables.
dir	directory of the model files.

Value

A [tibble](#) of class `model` containing the following columns:

- **problem:** a numeric identifier for the \$PROBLEM associated with the code.
- **level:** a unique numeric identifier to each subroutine block associated with the code.

- **subroutine:** a character identifier named after the 3 first letters of the subroutine name e.g. '\$THETA' and '\$TABLE' will become 'the' and 'tab' respectively. In addition all output from the .lst is labeled 'lst', the general nonmem output e.g. NM-TRAN messages are labelled 'oth'. With priors thp, tpv, omp, opd, sip, spd abbreviations are given to the THETAP, THETAPV, OMEGAP, etc.
- **code:** the code without comments or subroutine names e.g. '\$THETA 0.5 ; TVCL' will return '0.5'.
- **comment:** the last comment of a record e.g. '0.5 ; Clearance (L/h) ; TVCL' will return 'TVCL'.

See Also

[pmx_read_nm_tables](#)

Examples

```
## Not run:
# Using the `file` argument to import a model file:
nm_model <- pmx_read_nm_model(file = 'run001.lst', dir = 'models')

# Using the `runno` argument to import a model file:
nm_model <- pmx_read_nm_model(runno = '001', ext = '.lst', dir = 'models')

## End(Not run)
```

pmx_read_nm_tables	<i>NONMEM output table import function</i>
--------------------	--

Description

Quickly import NONMEM output tables into R. This function automatically detects the optimal settings to import the tables from nonmem. It is based on the read_nm_tables function of xpose. Slight adjustment were made for purposes of pmx_nm()

Usage

```
pmx_read_nm_tables(
  file = NULL,
  dir = NULL,
  combined = TRUE,
  rm_duplicates = TRUE,
  quiet = FALSE,
  simtab = NULL,
  ziptab = TRUE,
  user_mode = TRUE,
  ...
)
```

Arguments

file	A character vector of path to the files or a nm_table_list object created with list_nm_tables.
dir	Location of the model files.
combined	Logical value indicating whether multiple tables should be combined into a single one. If the number of rows does not match an error will be returned.
rm_duplicates	Logical value indicating whether duplicated columns should be removed.
quiet	Logical, if FALSE messages are printed to the console.
simtab	If TRUE only reads in simulation tables, if FALSE only reads estimation tables. Default NULL reads all tables.
ziptab	If TRUE search for the tables that have been compressed and renamed ??<file>.zip'.
user_mode	Adjustment to the original code: usermode is set to "usermode = TRUE" in order to improve this function for purposes of pmx_nm() (nonmem_reader.R), In order to use this function separately, the use of the original function in the xpose package is advised.
...	Additional arguments to be passed to the read_table or read_csv functions.

Table format requirement

When using pmx_read_nm_tables with the combined argument set to FALSE an ID column must be present in all data tables. When combined is set to TRUE instead an ID column must be present in at least one table for each problem and for each 'firstonly' category. ID columns are required to properly combine/merge tables and removing NA records. If the ID column is missing from a table and combined = FALSE pmx_read_nm_tables will return the following warning: Unknown variables: `ID`. While the data is returned beware that NA records might be left in the data and the output should be checked carefully. If combined = TRUE pmx_read_nm_tables is more strict and will return the following warning instead: Dropped `<tablenames>` due to missing required `ID` column..

Examples

```
## Not run:

# Adjustment to the original code: usermode is set to "usermode = TRUE"
# in order to improve this function for purposes of pmx_nm() (nonmem_reader.R)
# In order to use this function separately, the use of the original function in
# the xpose package is advised.

# Import tables manually and return them as a list of individual tables
nm_tables <- pmx_read_nm_tables(file = c('sdtab001', 'patab001'),
                               dir = 'models', combined = FALSE)

# Import tables manually and return them as a single merged table
nm_tables <- pmx_read_nm_tables(file = c('sdtab001', 'patab001'),
                               dir = 'models', combined = TRUE)

## End(Not run)
```

pmx_register_plot	<i>Register plot (Jun2025, Alex: I believe it doesn't work at all)</i>
-------------------	--

Description

Register plot (Jun2025, Alex: I believe it doesn't work at all)

Usage

```
pmx_register_plot(ctr, pp, pname = NULL)
```

Arguments

ctr	pmxClass controller
pp	ggplot2 plot
pname	character plot nme

pmx_report	<i>Generates ggpmX report from a pre-defined template</i>
------------	---

Description

Generates ggpmX report from a pre-defined template

Usage

```
pmx_report(
  contr,
  name,
  save_dir,
  plots_subdir = "ggpmx_GOF",
  output = c("all", "plots", "report"),
  template = "standing",
  footnote = output == "all",
  edit = FALSE,
  format = NULL,
  title,
  ...
)
```

Arguments

contr	pmxClass controller
name	character The report name
save_dir	Output directory. A directory to write the results files to
plots_subdir	Output folder name, ggpmx_GOF by default
output	character the result type, can be a standalone directory of plots or a report document as defined in the template (pdf, docx,...) ,or both
template	character ggPMX predefined template or the path to a custom rmarkdown template. Use pmx_report_template to get the list of available templates
footnote	logical TRUE to add a footnote to the generated plots. The default footnote is to add the path where the plot is saved.
edit	logical TRUE to edit the template immediately
format	character The output document format. By default, a word report is generated. User can specify one or more formats from c("word","pdf","html","all"). format "all" to generate all formats.
title	character report title (optional)
...	extra parameters depending in the template used

Details

pmx_report uses pre-defined template .Rmd to generate the report. The idea is to pass the controller as a report argument using knitr params artifact.

Examples

```
library(ggPMX)
# you probably want to create the report in your own directory
# But using a temp directory allows for easy cleanup

## case1: generate a single report
withr::with_tempdir({
  ctr <- theophylline()
  ctr %>% pmx_report(
    name = "my_report",
    save_dir = getwd(),
    output="report"
  )
})

## case2: generate standalone plots
withr::with_tempdir({
  ctr <- theophylline()
```

```

ctr %>% pmx_report(
  name = "my_report",
  save_dir = getwd(),
  output="plots"
)
})

## case3: generate both : reports + plots
## by default add footnote
## Note, you can force footnote to FALSE using footnote parameter
withr::with_tempdir({
  ctr <- theophylline()
  ctr %>% pmx_report(
    name="my_report",
    save_dir=getwd(),
    output="all"
  )
})

## case4 : generate standalone plots with footnotes
withr::with_tempdir({
  ctr <- theophylline()
  ctr %>% pmx_report(
    name="my_report",
    save_dir=getwd(),
    footnote=TRUE,
    output="plots"
  )
})

## case6: dynamic edit
## uncomment to run
# ctr <- theophylline()
# ctr %>% pmx_report(
#   save_dir = file.path(getwd(),"case6"),
#   name="my_report",
#   output="report",
#   edit = TRUE)

## case7 : generate individual plots report
## ctr <- theophylline()
## ctr %>% pmx_report(
##   name="report2",
##   save_dir = getwd(),
##   template="individual",
##   format="all",
##   which_pages=1:2
## )

```

pmx_report_template	<i>Gets build-in report templates</i>
---------------------	---------------------------------------

Description

Gets build-in report templates

Usage

```
pmx_report_template()
```

Value

list of templates names

Examples

```
pmx_report_template()
```

pmx_settings	<i>Create controller global settings</i>
--------------	--

Description

Create controller global settings

Usage

```
pmx_settings(  
  is.draft = TRUE,  
  use.abbrev = TRUE,  
  color.scales = NULL,  
  cats.labels = NULL,  
  use.labels = FALSE,  
  use.titles = FALSE,  
  effects = NULL,  
  ...  
)
```

Arguments

<code>is.draft</code>	logical if FALSE any plot is without draft annotation
<code>use.abbrev</code>	logical if FALSE use full description from abbreviation mapping for axis names
<code>color.scales</code>	list list containing elements of <code>scale_color_manual</code>
<code>cats.labels</code>	list list of named vectors for each factor
<code>use.labels</code>	logical if TRUE replace factor named by <code>cats.labels</code>
<code>use.titles</code>	logical FALSE to generate plots without titles
<code>effects</code>	list list of effects levels and labels
<code>...</code>	extra parameter not used yet

Value

`pmxSettingsClass` object

Examples

```
library(ggPMX)
library(ggplot2)
ctr <- theophylline(
  settings=
    pmx_settings(
      color.scales=list(
        "Study",
        labels=c("Study 1", "Study 2"),
        values=c("1"="lightyellow", "2"="lightblue")),
      cats.labels=list(
        SEX=c("0"="M", "1"="F"),
        STUD=c("1"="Study 1", "2"="Study 2")
      ),
      use.abbrev=TRUE,
      is.draft=TRUE,
      use.labels=TRUE
    )
)

ctr %>%
  pmx_plot_npde_time(strat.color="STUD", strat.facet=~SEX)
#
#
ctr %>%
  pmx_plot_eta_box(strat.color="STUD", strat.facet =~SEX)

ctr %>% pmx_plot_eta_hist
```

pmx_shrink	<i>Create shrinkage parameter object</i>
------------	--

Description

Create shrinkage parameter object

Usage

```
pmx_shrink(
  fun = c("var", "sd"),
  size = 1,
  color = "green",
  vjust = 1.5,
  hjust = 0.5,
  ...
)
```

Arguments

fun	list shrinkage function can be sd or var
size	numeric shrinkage text size
color	character shrinkage text color
vjust	numeric shrinkage position vertical adjustment
hjust	numeric shrinkage position horizontal adjustment
...	any other parameter

Value

pmxShrinkClass object (list)

pmx_sim	<i>Create simulation object</i>
---------	---------------------------------

Description

Create simulation object

Usage

```
pmx_sim(file, data, irun, idv)
```

Arguments

file	character path to the simulation file
data	data.table simulation data
irun	character name of the simulation column
idv	character name of the ind. variable

Examples

```
library(ggPMX)

theo_path <- file.path(
  system.file(package = "ggPMX"), "testdata",
  "theophylline"
)
WORK_DIR <- file.path(theo_path, "Monolix")
input_file <- file.path(theo_path, "data_pk.csv")
vpc_file <- file.path(theo_path, "sim.csv")

ctr <- pmx_mlx(
  config = "standing",
  directory = WORK_DIR,
  input = input_file,
  dv = "Y",
  dvid = "dvid",
  cats = c("SEX"),
  conts = c("WT0", "AGE0"),
  strats = "STUD",
  settings = pmx_settings(
    use.labels=TRUE,
    cats.labels=list(
      SEX=c("0"="Male", "1"="Female")
    )
  ),
  sim = pmx_sim(
    file = vpc_file,
    irun = "rep",
    idv="TIME"
  )
)

ctr %>% pmx_plot_vpc(
  strat.facet=~SEX,
  facets=list(nrow=2),
  type="percentile",
  is.draft = FALSE,
  pi = pmx_vpc_pi(interval = c(0.1,0.9),
    median=list(color="green"),
    extreme= list(color="green")),
  obs = pmx_vpc_obs(color="blue",shape=18,size=2),
  ci = pmx_vpc_ci(interval = c(0.1,0.9),
```

```

      median=list(fill="pink")),
    bin=pmx_vpc_bin("kmeans",n=5)
  )

  ctr %>%
    pmx_plot_vpc(bin= pmx_vpc_bin(
      style = "fixed",
      fixedBreaks=c(-10,2, 5, 10,15,50))
    )

  # example with legend

  ctr %>% pmx_plot_vpc(
    is.legend = TRUE,
    pi = pmx_vpc_pi(interval=c(0.02,0.98),median = list(linetype="dotted")),
    ci = pmx_vpc_ci(interval = c(0.05,0.95),median=list(fill="red"))
  )

```

pmx_theme

Define ggPMX theme

Description

This theme is a simple wrapper gdoc theme from ggthemes package.

Usage

```
pmx_theme(...)
```

Arguments

... can contain any valid argument of ggplot2 [theme](#) object.

Value

ggplot2 theme object

pmx_update	<i>Update plot object</i>
------------	---------------------------

Description

Update plot object

Usage

```
pmx_update(
  ctr,
  pname,
  strat.color = NULL,
  strat.facet = NULL,
  color.scales = NULL,
  filter = NULL,
  trans = NULL,
  ...,
  pmxgpar = NULL
)
```

Arguments

ctr	pmxClass controller object
pname	character the plot name to update
strat.color	character optional stratification parameter
strat.facet	formula optional stratification parameter
color.scales	list can be used with strat.color to set scale_color_manual pmx_gpar function.
filter	optional filter which will be applied to plotting data
trans	character define the transformation to apply on x or y or both variables
...	others graphical parameters given to set the plot
pmxgpar	a object of class pmx_gpar possibly the output of the

Details

trans is a transformation that user can apply to x, or y coordinates. The transformation is applied to the data before the plotting. This gives more flexibility to the user and also conserves all static positions like annotations (draft specially)

For example:

var_x apply variance to x coordinates the variance function

var_xy apply variance to both This mechanism is applied internally to scale log.

Value

controller object with the plot updated

See Also

Other pmxclass: [get_cats\(\)](#), [get_conts\(\)](#), [get_covariates\(\)](#), [get_data\(\)](#), [get_occ\(\)](#), [get_plot\(\)](#), [get_plot_config\(\)](#), [get_strats\(\)](#), [plot_names\(\)](#), [plots\(\)](#), [set_data\(\)](#), [set_plot\(\)](#)

pmx_vpc

*Creates vpc object***Description**

Creates vpc object

Usage

```
pmx_vpc(
  type = c("percentile", "scatter"),
  idv = "TIME",
  obs = pmx_vpc_obs(),
  pi = pmx_vpc_pi(),
  ci = pmx_vpc_ci(),
  rug = pmx_vpc_rug(),
  bin = pmx_vpc_bin(),
  labels = NULL,
  facets = NULL,
  is.legend = TRUE,
  is.footnote = TRUE,
  dname = NULL,
  ...
)
```

Arguments

type	charcater can be either percentile or scatter
idv	chracater individual variable
obs	pmx_vpc_obs object observation layer pmx_vpc_obs
pi	pmx_vpc_pi object percentile layer pmx_vpc_pi
ci	pmx_vpc_ci object confidence interval layer pmx_vpc_ci
rug	pmx_vpc_rug object rug layer pmx_vpc_rug
bin	pmx_vpc_bin object pmx_vpc_bin
labels	list define title and axis labels
facets	is a list of parameters passed to facet_wrap in case of startification
is.legend	logical if TRUE add legend
is.footnote	logical if TRUE add footnote
dname	added for compatibility with other ggPMX plots
...	extra parameters passed to base graphical parameters

Value

list with parameters of the vpc object

See Also

Other vpc: [pmx_plot_vpc\(\)](#), [pmx_vpc_bin\(\)](#), [pmx_vpc_ci\(\)](#), [pmx_vpc_obs\(\)](#), [pmx_vpc_pi\(\)](#), [pmx_vpc_rug\(\)](#)

pmx_vpc_bin	<i>Creates vpc bins</i>
-------------	-------------------------

Description

Creates vpc bins

Usage

```
pmx_vpc_bin(style, within_strat = TRUE, seed = 42, ...)
```

Arguments

style	character style chosen on of the: "fixed", "sd", "equal", "pretty", "quantile", "kmeans", "hclust" or "jenks"
within_strat	logical if TRUE compute the binning for each strat level. By default it is false and binning are equal for all stratifications levels.
seed	integer used in set.seed call to ensure reproducibility if style is "kmeans". Set to NULL if this is not desired.
...	other classInt::classIntervals parameters except style and n

Details

This is a wrapper to the bin based VPC

Value

list with options for 'pmx_vpc_bin' object

See Also

Other vpc: [pmx_plot_vpc\(\)](#), [pmx_vpc\(\)](#), [pmx_vpc_ci\(\)](#), [pmx_vpc_obs\(\)](#), [pmx_vpc_pi\(\)](#), [pmx_vpc_rug\(\)](#)

pmx_vpc_ci	<i>Sets vpc confidence interval layer</i>
------------	---

Description

Sets vpc confidence interval layer

Usage

```
pmx_vpc_ci(
  show = c("all", "median"),
  interval = c(0.025, 0.975),
  method = c("ribbon", "rectangle"),
  median = list(fill = "red", alpha = 0.3),
  extreme = list(fill = "#3388cc", alpha = 0.3)
)
```

Arguments

show	character how areas are displayed: • show="all" areas will be displayed for each of the 3 percentiles. • show="median" Show only median area.
interval	numeric quantiles values default to c(.05, .95)
method	character which areas are displayed: • method="ribbon" areas are ribbons. • method="rectangle" areas are horizontal rectangles.
median	list containing: • fill character Color of the area representing the CI for the median. Default: "#3388cc". • alpha numeric Transparency of the area representing the PI for the median. Default=0.3.
extreme	list containing: • fill character Color of the area representing the CI for the extreme percentiles. Default: "#3388cc". • alpha numeric Transparency of the area representing the PI for the extreme percentiles. Default=0.3.

Value

list with options for Confidence Interval layer

See Also

Other vpc: [pmx_plot_vpc\(\)](#), [pmx_vpc\(\)](#), [pmx_vpc_bin\(\)](#), [pmx_vpc_obs\(\)](#), [pmx_vpc_pi\(\)](#), [pmx_vpc_rug\(\)](#)

pmx_vpc_obs	<i>Sets vpc observation layer</i>
-------------	-----------------------------------

Description

Sets vpc observation layer

Usage

```
pmx_vpc_obs(show = TRUE, color = "#000000", size = 1, alpha = 0.7, shape = 1)
```

Arguments

show	logical if TRUE show observation points
color	character Color of the observed endpoint values. Default: "#000000".
size	numeric Size of the observed endpoint values. Default: 1.
alpha	numeric Transparency of the observed endpoint values. Default: 0.7.
shape	numeric Shape of the observed endpoint values. Default: 1.

Value

list with options for ggplot2 layer with observations

See Also

Other vpc: [pmx_plot_vpc\(\)](#), [pmx_vpc\(\)](#), [pmx_vpc_bin\(\)](#), [pmx_vpc_ci\(\)](#), [pmx_vpc_pi\(\)](#), [pmx_vpc_rug\(\)](#)

pmx_vpc_pi	<i>Sets vpc percentile layer</i>
------------	----------------------------------

Description

Sets vpc percentile layer

Usage

```
pmx_vpc_pi(
  show = c("all", "median", "area"),
  interval = c(0.05, 0.95),
  median = list(color = "#000000", linewidth = 1, alpha = 0.7, linetype = "solid"),
  extreme = list(color = "#000000", linewidth = 1, alpha = 0.7, linetype = "dashed"),
  area = list(fill = "blue", alpha = 0.1)
)
```

Arguments

show	charcater how lines are displayed: • show=all lines will be displayed for each of the 3 percentiles. with a shaded area. • show=median Show only median line. • show=area Show only median line and the shaded area
interval	numeric quantiles values default to c(.05, .95)
median	list containing: • color charcater Color of the median percentile line. Default: "#000000". • linewidth numeric Thickness of the median percentile line. Default: 1. • alpha numeric Transparency of the median percentile line. Default: 0.7. • linetype charcater Linetype of the median percentile line. Default: "solid".
extreme	list containing: • color charcater Color of the median percentile line. Default: "#000000". • linewidth numeric Thickness of the median percentile line. Default: 1. • alpha numeric Transparency of the median percentile line. Default: 0.7. • linetype charcater Linetype of the median percentile line. Default: "solid"
area	list containing: • fill charcater Color of the shaded area. Default: "blue". • alpha numeric Transparency of the shaded area. Default: 0.1.

Value

list with options for Prediction Interval layer

See Also

Other vpc: [pmx_plot_vpc\(\)](#), [pmx_vpc\(\)](#), [pmx_vpc_bin\(\)](#), [pmx_vpc_ci\(\)](#), [pmx_vpc_obs\(\)](#), [pmx_vpc_rug\(\)](#)

pmx_vpc_rug	<i>Sets vpc rug layer</i>
-------------	---------------------------

Description

Sets vpc rug layer

Usage

pmx_vpc_rug(show = TRUE, color = "#000000", linewidth = 1, alpha = 0.7, size)

Arguments

show	logical If TRUE show bin separators
color	character Color of the rug. Default: "#000000".
linewidth	numeric Thickness of the rug. Default: 1.
alpha	numeric Transparency of the rug. Default: 0.7.
size	numeric Depreciated thickness of the rug. Default: 1.

Details

When the vpc confidence interval layer method is rectangles we don't show rug separators.

Value

list with options for the rug layer

See Also

Other vpc: [pmx_plot_vpc\(\)](#), [pmx_vpc\(\)](#), [pmx_vpc_bin\(\)](#), [pmx_vpc_ci\(\)](#), [pmx_vpc_obs\(\)](#), [pmx_vpc_pi\(\)](#)

print.abbreviation	<i>S3 print abbreviation</i>
--------------------	------------------------------

Description

S3 print abbreviation

Usage

```
## S3 method for class 'abbreviation'
print(x, ...)
```

Arguments

x	object of class configs
...	pass additional options (not used presently)

Value

print abbreviation

print.configs	<i>This function can be used to print configuration of the defined object using S3 method.</i>
---------------	--

Description

This function can be used to print configuration of the defined object using S3 method.

Usage

```
## S3 method for class 'configs'  
print(x, ...)
```

Arguments

x	object of class configs
...	pass additional options (not used presently)

Value

print result

print.pmxClass	<i>Print pmxClass object</i>
----------------	------------------------------

Description

Print pmxClass object

Usage

```
## S3 method for class 'pmxClass'  
print(x, ...)
```

Arguments

x	pmxClass object
...	additinal arguments to pass to print

Value

print object to screen

print.pmxConfig	<i>S3 method print pmxConfig object</i>
-----------------	---

Description

S3 method print pmxConfig object

Usage

```
## S3 method for class 'pmxConfig'  
print(x, ...)
```

Arguments

x	pmxConfig object
...	additional arguments to pass to print (unused currently)

Value

invisible object

print.pmx_gpar	<i>Print pmx_gpar object</i>
----------------	------------------------------

Description

Print pmx_gpar object

Usage

```
## S3 method for class 'pmx_gpar'  
print(x, ...)
```

Arguments

x	pmx_gpar object
...	argument passed to print (to satisfy generic)

Value

a character description of graphical parameters

read_extfile

*Reads .ext files generated by NONMEM***Description**

Reads .ext files generated by NONMEM

Usage

```
read_extfile(
  run = NA_real_,
  project = getwd(),
  file = paste0(run, ".ext"),
  path = NULL,
  read_fun = c("data.table", "read.table"),
  quiet
)
```

Arguments

run	run a run number or run identifier
project	project the NONMEM project directory
file	file the 'ext' file name
path	path full path and file name for 'ext' file
read_fun	read_fun function to read the 'ext' file
quiet	Logical, if FALSE messages are printed to the console.

Value

A list with param, omega, and sigma in a format ready to be used.

Author(s)

This function is based on read_nmext from mrgsolve, Original Author: Kyle T Baron. This function has some changes to the original code: Addition of param, "quiet", (option of pmx_msg function, from xpose package) (Line: 27) The code was slightly adjusted to check for multiple tables and also extract SE (ITERATION == 1000000001) (Line: 44-58, Line: 86-96, respectively) The output was also slightly adjusted to fit ggPMX output (df and df2) (Line: 105,106) as_bmat was replaced by bmat_like to create the diagonal matrix (Line 116:142)

Examples

```
#project <- system.file("nonmem", package = "mrgsolve")
#est <- read_nmext(1005, project = project)
```

read_input	<i>Read Modelling input data</i>
------------	----------------------------------

Description

Read Modelling input data

Usage

```
read_input(  
  ipath,  
  dv,  
  dvid,  
  cats = "",  
  conts = "",  
  strats = "",  
  occ = "",  
  endpoint = NULL,  
  id = NULL,  
  time = NULL  
)
```

Arguments

ipath	full path of the input file
dv	character the name of measurable variable used in the input modelling file
dvid	character observation type parameter
cats	<i>[Optional]</i> character vector of categorical covariates
conts	<i>[Optional]</i> character vector of continuous covariates
strats	<i>[Optional]</i> character extra stratification variables
occ	<i>[Optional]</i> character inter individual occasion variables
endpoint	integer null in case of a single endpoint otherwise the index of endpoints.
id	character the name of identifier variable used in the input modelling file.
time	character the name of time variable used in the input modelling file

Value

data.table well formatted containing modelling input data

read_mlx_ind_est	<i>Read MONOLIX individual parameters</i>
------------------	---

Description

Read MONOLIX individual parameters

Usage

read_mlx_ind_est(path, x, ...)

Arguments

- | | |
|------|----------------------------|
| path | character path to the file |
| x | dataset object |
| ... | extra parameter not used |

Value

data.table object

read_mlx_par_est	<i>Read MONOLIX parameter estimation file</i>
------------------	---

Description

Read MONOLIX parameter estimation file

Usage

read_mlx_par_est(path, x, ...)

Arguments

- | | |
|------|----------------------------|
| path | character path to the file |
| x | dataset object |
| ... | extra parameter not used |

Value

data.table object

read_mlx_pred	<i>Read MONOLIX model predictions</i>
---------------	---------------------------------------

Description

Read MONOLIX model predictions

Usage

```
read_mlx_pred(path, x, ...)
```

Arguments

path	character path to the file
x	dataset object
...	extra parameter not used

Value

data.table object

read_mlx_saem_conv	<i>Read MONOLIX SAEM convergence file</i>
--------------------	---

Description

Read MONOLIX SAEM convergence file

Usage

```
read_mlx_saem_conv(path, ...)
```

Arguments

path	string specifying data path folder
...	extra parameter not used

Value

data.table object

residual	<i>This function create a residual for each observed value and also generates a residual distribution</i>
----------	---

Description

This function create a residual for each observed value and also generates a residual distribution

Usage

```
residual(
  x,
  y,
  labels = NULL,
  point = NULL,
  is.hline = FALSE,
  hline = NULL,
  dname = NULL,
  facets = NULL,
  bloq = NULL,
  square_plot = TRUE,
  ...
)
```

Arguments

x	x axis aesthetics
y	y axis aesthetics
labels	list that contain title,subtitle, axis labels
point	geom point graphical parameters
is.hline	logical if TRUE add horizontal line y=0 (TRUE by default)
hline	geom hline graphical parameters
dname	name of dataset to be used
facets	list wrap facetting in case of strat.facet
bloq	pmxBLOQ object created by pmx_bloq
square_plot	square dv_pred plot (TRUE by default)
...	others graphics arguments passed to pmx_gpar internal object.

Details

Some parameters are a list of parameters :

point is a list that contains:

- **shape:** default to 1

- **color:** default to black
- **size:** default to 1

labels is a list that contains:

- **title:** plot title default to AES_X versus AES_Y
- **subtitle:** plot subtitle default empty
- **x:** x axis label default to AES_X
- **y:** y axis label default to AES_Y

Value

a residual object

See Also

[plot_pmx.residual](#)

residual_scatter

Scatter residual plots

Description

Scatter residual plots
DV vs PRED plot
DV vs IPRED plot
IWRES vs IPRED plot
|IWRES| vs IPRED plot
|IWRES| vs TIME plot
IWRES vs TIME plot
NPDE vs TIME plot
NPDE vs PRED plot
NPD vs TIME plot
NPD vs EPRED plot
NPD vs PRED plot
CWRES vs TIME plot
CWRES vs CPRED plot
CWRES vs PRED plot

Usage

```
residual_scatter(  
  sim_blk,  
  point,  
  is.hline,  
  hline,  
  dname,  
  bloq,  
  filter,  
  strat.facet,  
  facets,  
  strat.color,  
  trans,  
  pmxgpar,  
  labels,  
  axis.title,  
  axis.text,  
  ranges,  
  is.smooth,  
  smooth,  
  is.band,  
  band,  
  is.draft,  
  draft,  
  is.identity_line,  
  identity_line,  
  scale_x_log10,  
  scale_y_log10,  
  color.scales,  
  ...  
)  
  
pmx_plot_dv_pred(ctr, ...)  
  
pmx_plot_dv_ipred(ctr, ...)  
  
pmx_plot_iwres_ipred(ctr, ...)  
  
pmx_plot_abs_iwres_ipred(ctr, ...)  
  
pmx_plot_abs_iwres_time(ctr, ...)  
  
pmx_plot_iwres_time(ctr, ...)  
  
pmx_plot_npde_time(ctr, ...)  
  
pmx_plot_npde_pred(ctr, ...)
```



```

pmx_plot_npd_time(ctr, ...)

pmx_plot_npd_epred(ctr, ...)

pmx_plot_npd_pred(ctr, ...)

pmx_plot_cwres_time(ctr, ...)

pmx_plot_cwres_cpred(ctr, ...)

pmx_plot_cwres_pred(ctr, ...)

```

Arguments

sim_bloq	logical if TRUE uses sim_bloq values for plotting. Only for Monolix 2018 and later.
point	list geom_point graphical parameters.
is.hline	logical if TRUE add horizontal line y=0 (TRUE by default).
hline	list geom_hline graphical parameters.
dname	character name of dataset to be used. User can create his own dataset using set_data and pass it as dname to be plotted.
bloq	pmxBLOQ object created by pmx_bloq .
	pmx_update parameters
filter	expression filter which will be applied to plotting data.
strat.facet	formula optional stratification parameter by facetting. This split plot by strats(each strat in a facet)
facets	list facet_wrap parameters.
strat.color	character optional stratification parameter by grouping. This will split the plot by group (color) of strat.
trans	character define the transformation to apply on x or y or both variables
pmxgpar	a object of class pmx_gpar possibly the output of the pmx_gpar: Shared basic graphics parameters
labels	list list containing plot and/or axis labels: title, subtitle, x , y
axis.title	list containing element_text attributes to customize the axis title. (similar to ggplot2 axis.title theme)
axis.text	list containing element_text attributes to customize the axis text (similar to ggplot2 axis.text theme)
ranges	list limits of x/y ranges
is.smooth	logical if set to TRUE add smooth layer
smooth	list geom_smooth graphical/smoothing fun parameters
is.band	logical if TRUE add horizontal band
band	list horizontal band parameters. geom_hline graphical parameters.

is.draft	logical if TRUE add draft layer
draft	list draft layer parameters. geom_text graphical parameters.
is.identity_line	logical if TRUE add an identity line
identity_line	listgeom_abline graphical parameters.
scale_x_log10	logical if TRUE use log10 scale for x axis.
scale_y_log10	logical if TRUE use log10 scale for y axis.
color.scales	list define scales parameter in case of strat.color pmx_settings
...	others graphics parameters passed : • pmx_gpar internal function to customize shared graphical parameters • residual generic object for all residual (scatter) plots . • pmx_update function. • aess can be used to change time variable within the plot (e.g. aess = list(x="TADQBW"))

residual parameters

ctr	pmx controller
-----	----------------

Value

ggplot2 object

Examples

```
# NOTES #####
# examples are availables for all residual plots:
# - pmx_plot_abs_iwres_ipred
# - pmx_plot_dv_ipred
# - pmx_plot_dv_pred
# - pmx_plot_iwres_ipred
# - pmx_plot_iwres_time
# - pmx_plot_npde_time

# basic use -----

ctr <- theophylline()
p <- ctr %>% pmx_plot_dv_pred()
## p is a ggplot2 object you can add any layer here
p + ggplot2::theme_minimal()

# update graphical parameter -----

## update labels
ctr %>% pmx_plot_dv_pred(
  labels = list(title = "DV versus PRED new title")
)

## remove draft
ctr %>% pmx_plot_dv_pred(is.draft = FALSE)
```

```

## remove horizontal line
ctr %>% pmx_plot_dv_pred(is.hline = FALSE)

## custom point aes and static parameters
## we can customize any geom_point parameter
ctr %>% pmx_plot_dv_pred(
  point = list(aes(alpha = DV), color = "green", shape = 4)
)

# stratification -----

## continuous stratification
ctr %>% pmx_plot_dv_pred(strat.color = ~WT0)
## categorical stratification
ctr %>% pmx_plot_dv_pred(strat.facet = ~SEX)
## using formula notation
ctr %>% pmx_plot_dv_pred(strat.facet = STUD~SEX)

# subsetting -----

## we can use any expression involving the data
ctr %>% pmx_plot_dv_pred(filter = DV > mean(DV) & PRED < median(PRED))
## filter and stratify
ctr %>% pmx_plot_dv_pred(filter = SEX == 1, strat.facet = ~SEX)

# transformation -----

## apply a log transformation in y
ctr %>% pmx_plot_dv_pred(trans = "log10_y")

```

set_abbrev

update or add a new abbreviation

Description

update or add a new abbreviation

Usage

```
set_abbrev(ctr, ...)
```

Arguments

ctr	pmxClass controller object
...	Options to set or add, with the form name = value.

Examples

```
ctr <- theophylline()
ctr %>% set_abbrev("new_param" = "new value")
ctr %>% get_abbrev("new_param")
```

set_data

Set a controller data set

Description

Set a controller data set

Usage

```
set_data(ctr, ..., envir = parent.frame())
```

Arguments

ctr	the controller object
...	a named list parameters (see example)
envir	the environment in which expr is to be evaluated. May also be NULL, a list, a data frame, a pairlist or an integer as specified to sys.call .

Details

This function can be used to set an existing data set or to create a new one. The basic idea is to change the built-in data set (change the factor level names, change some rows values or apply any other data set operation) and use the new data set using the dname parameter of pmx_plot family functions.

See Also

Other pmxclass: [get_cats\(\)](#), [get_conts\(\)](#), [get_covariates\(\)](#), [get_data\(\)](#), [get_occ\(\)](#), [get_plot\(\)](#), [get_plot_config\(\)](#), [get_strats\(\)](#), [plot_names\(\)](#), [plots\(\)](#), [pmx_update\(\)](#), [set_plot\(\)](#)

Examples

```
ctr <- theophylline()
dx <- ctr %>% get_data("eta")
dx <- dx[, EFFECT := factor(
  EFFECT,
  levels = c("ka", "V", "Cl"),
  labels = c("Concentration", "Volume", "Clearance")
)]
## update existing data set
ctr %>% set_data(eta = dx)
## or create a new data set
```

```
ctr %>% set_data(eta_long = dx)
```

set_plot

Create a new plot of the desired type

Description

Create a new plot of the desired type

Usage

```
set_plot(
  ctr,
  ptype = c("IND", "DIS", "SCATTER", "ETA_PAIRS", "ETA_COV", "PMX_QQ", "VPC", "PMX_DENS",
    "PARAM_HISTORY"),
  pname,
  use.defaults = TRUE,
  filter = NULL,
  strat.color = NULL,
  strat.facet = NULL,
  color.scales = NULL,
  trans = NULL,
  ...
)
```

Arguments

ctr	pmxClass controller object
ptype	plot type can be: • "IND" Individual plot type: individual • "DIS" Distribution plot type : distrib • "SCATTER" Residual plot type : residual
pname	plot name, if missing it will be created using function aesthetics
use.defaults	logical if FALSE do not use defaults defined in yaml init files
filter	optional filter which will be applied to plotting data
strat.color	character
strat.facet	formula define categorical stratification as formula
color.scales	list can be used with strat.color to set scale_color_manual
trans	list transformation operator
...	other plot parameters to configure pmx_gpar .

Value

invisible ctr object

See Also

Other pmxclass: [get_cats\(\)](#), [get_conts\(\)](#), [get_covariates\(\)](#), [get_data\(\)](#), [get_occ\(\)](#), [get_plot\(\)](#), [get_plot_config\(\)](#), [get_strats\(\)](#), [plot_names\(\)](#), [plots\(\)](#), [pmx_update\(\)](#), [set_data\(\)](#)

theophylline	<i>Creates pmx controller using theophylline data</i>
--------------	---

Description

Creates pmx controller using theophylline data

Usage

```
theophylline(settings = NULL, ...)
```

Arguments

settings	pmxSettings object
...	other parameters of pmx_mlx like endpoint

Value

pmx controller

Examples

```
## Not run:
theophylline()

## End(Not run)
```

wrap_formula	<i>merge facets formula with new formula</i>
--------------	--

Description

merge facets formula with new formula

Usage

```
wrap_formula(x, origin = "lfacet")
```

Arguments

x	formula object
origin	the origin formula default to ~lfacets

Value

formula object

`[.pmx_gpar`*Method for subsetting "pmx_gpar" objects*

Description

Method for subsetting "pmx_gpar" objects

Usage

```
## S3 method for class 'pmx_gpar'  
x[index, ...]
```

Arguments

<code>x</code>	pmx_gpar object
<code>index</code>	can be character/integer of element
<code>...</code>	other parameter (not used just for generic)

Value

if exists the parameter description

Index

- * **eta_cov_plot**
 - eta_cov_plot, 9
- * **eta_distribution_plot**
 - eta_distribution_plot, 12
- * **plot_pmx**
 - distrib, 6
 - eta_cov, 7
 - eta_pairs, 15
 - individual, 23
 - plot_pmx, 31
 - plot_pmx.distrib, 32
 - plot_pmx.eta_cov, 33
 - plot_pmx.eta_pairs, 33
 - plot_pmx.individual, 34
 - plot_pmx.pmx_dens, 35
 - plot_pmx.pmx_gpar, 35
 - plot_pmx.pmx_param_history, 36
 - plot_pmx.pmx_qq, 37
 - plot_pmx.residual, 37
- * **pmxclass functions**
 - print.pmxClass, 96
- * **pmxclass**
 - get_cats, 18
 - get_confs, 19
 - get_covariates, 19
 - get_data, 20
 - get_occ, 20
 - get_plot, 21
 - get_plot_config, 22
 - get_strats, 22
 - plot_names, 31
 - plots, 30
 - pmx_update, 89
 - set_data, 108
 - set_plot, 109
- * **qq_plot**
 - pmx_qq, 72
- * **qqq**
 - pmx_qq_plot, 74
- * **residual**
 - residual_scatter, 103
- * **vpc**
 - pmx_plot_vpc, 69
 - pmx_vpc, 90
 - pmx_vpc_bin, 91
 - pmx_vpc_ci, 92
 - pmx_vpc_obs, 93
 - pmx_vpc_pi, 93
 - pmx_vpc_rug, 94
 - [.pmx_gpar, 111
- abbrev, 4
- add_draft, 5
- check_shrink, 6
- distrib, 6, 8, 14, 16, 24, 32–38, 109
- dummy (eta_cov_plot), 9
- environment, 108
- eta_cov, 7, 7, 10, 16, 24, 32–38
- eta_cov_plot, 9
- eta_distribution_plot, 12
- eta_pairs, 7, 8, 15, 24, 32–38, 61
- eval_sym_parent_env, 17
- facet_wrap_paginate, 28
- get_abbrev, 18
- get_cats, 18, 19–23, 30, 31, 90, 108, 110
- get_confs, 18, 19, 19, 20–23, 30, 31, 90, 108, 110
- get_covariates, 18, 19, 19, 20–23, 30, 31, 90, 108, 110
- get_data, 18, 19, 20, 21–23, 30, 31, 90, 108, 110
- get_occ, 18–20, 20, 21–23, 30, 31, 90, 108, 110
- get_plot, 18–21, 21, 22, 23, 30, 31, 90, 108, 110

- get_plot_config, [18–21](#), [22](#), [23](#), [30](#), [31](#), [90](#), [108](#), [110](#)
- get_strats, [18–22](#), [22](#), [30](#), [31](#), [90](#), [108](#), [110](#)
- getPmxOption, [17](#)
- gtable_remove_grobs, [23](#)
- individual, [7](#), [8](#), [16](#), [23](#), [32–38](#), [64](#), [109](#)
- input_finegrid, [25](#)
- is.pmx_gpar, [25](#)
- l_left_join, [27](#)
- load_config, [26](#)
- load_data_set, [26](#)
- load_source, [27](#)
- n_pages, [28](#)
- param_table, [28](#)
- parse_mlxtran, [29](#)
- pk_occ, [29](#)
- pk_pd, [30](#)
- plot_names, [18–23](#), [30](#), [31](#), [90](#), [108](#), [110](#)
- plot_pmx, [7](#), [8](#), [16](#), [24](#), [31](#), [32–38](#)
- plot_pmx.distrib, [7](#), [8](#), [16](#), [24](#), [32](#), [32](#), [33–38](#)
- plot_pmx.eta_cov, [7](#), [8](#), [16](#), [24](#), [32](#), [33](#), [34–38](#)
- plot_pmx.eta_pairs, [7](#), [8](#), [16](#), [24](#), [32](#), [33](#), [33](#), [34–38](#)
- plot_pmx.individual, [7](#), [8](#), [16](#), [24](#), [32–34](#), [34](#), [35–38](#)
- plot_pmx.pmx_dens, [7](#), [8](#), [16](#), [24](#), [32–34](#), [35](#), [36–38](#)
- plot_pmx.pmx_gpar, [7](#), [8](#), [16](#), [24](#), [32–35](#), [35](#), [36–38](#)
- plot_pmx.pmx_param_history, [7](#), [8](#), [16](#), [24](#), [32–36](#), [36](#), [37](#), [38](#)
- plot_pmx.pmx_qq, [7](#), [8](#), [16](#), [24](#), [32–36](#), [37](#), [38](#)
- plot_pmx.residual, [7](#), [8](#), [16](#), [24](#), [32–37](#), [37](#), [103](#)
- plot_shrink, [38](#)
- plots, [18–23](#), [30](#), [31](#), [90](#), [108](#), [110](#)
- pmx, [39](#)
- pmx_bloq, [24](#), [40](#), [43](#), [57](#), [64](#), [102](#), [105](#)
- pmx_comp_shrink, [28](#), [44](#)
- pmx_config, [45](#)
- pmx_copy, [46](#)
- pmx_cov, [8](#), [10](#), [47](#)
- pmx_dens, [47](#), [68](#)
- pmx_endpoint, [40](#), [49](#), [55](#), [57](#)
- pmx_filter, [50](#)
- pmx_get_configs, [51](#)
- pmx_gpar, [7](#), [8](#), [10](#), [14](#), [16](#), [24](#), [32](#), [48](#), [52](#), [58](#), [59](#), [61](#), [64](#), [68](#), [71](#), [73](#), [76](#), [89](#), [102](#), [106](#), [109](#)
- pmx_list_nm_tables, [53](#)
- pmx_manual_nm_import, [54](#)
- pmx_mlx, [28](#), [41](#)
- pmx_mlx (pmx), [39](#)
- pmx_mlxtran (pmx), [39](#)
- pmx_nlmixr, [55](#)
- pmx_nm, [55](#)
- pmx_plot, [58](#)
- pmx_plot_abs_iwres_ipred (residual_scatter), [103](#)
- pmx_plot_abs_iwres_time (residual_scatter), [103](#)
- pmx_plot_cats, [59](#)
- pmx_plot_cwres_cpred (residual_scatter), [103](#)
- pmx_plot_cwres_pred (residual_scatter), [103](#)
- pmx_plot_cwres_qq (pmx_qq_plot), [74](#)
- pmx_plot_cwres_time (residual_scatter), [103](#)
- pmx_plot_dv_ipred (residual_scatter), [103](#)
- pmx_plot_dv_pred (residual_scatter), [103](#)
- pmx_plot_eta_box (eta_distribution_plot), [12](#)
- pmx_plot_eta_cats (eta_cov_plot), [9](#)
- pmx_plot_eta_conts (eta_cov_plot), [9](#)
- pmx_plot_eta_hist (eta_distribution_plot), [12](#)
- pmx_plot_eta_matrix, [59](#)
- pmx_plot_eta_qq (pmx_qq_plot), [74](#)
- pmx_plot_individual, [62](#)
- pmx_plot_iwres_dens, [66](#)
- pmx_plot_iwres_ipred (residual_scatter), [103](#)
- pmx_plot_iwres_qq (pmx_qq_plot), [74](#)
- pmx_plot_iwres_time (residual_scatter), [103](#)
- pmx_plot_npd_epred (residual_scatter), [103](#)
- pmx_plot_npd_pred (residual_scatter), [103](#)
- pmx_plot_npd_qq (pmx_qq_plot), [74](#)
- pmx_plot_npd_time (residual_scatter),

- 103
- pmx_plot_npde_pred(residual_scatter), 103
- pmx_plot_npde_qq(pmx_qq_plot), 74
- pmx_plot_npde_time(residual_scatter), 103
- pmx_plot_saem_convergence, 68
- pmx_plot_vpc, 69, 91–95
- pmx_qq, 58, 59, 72, 76
- pmx_qq_plot, 74
- pmx_read_nm_files, 77
- pmx_read_nm_model, 53, 54, 78
- pmx_read_nm_tables, 54, 79, 79
- pmx_register_plot, 81
- pmx_report, 81
- pmx_report_template, 82, 84
- pmx_settings, 10, 14, 40, 53, 55, 57, 61, 64, 68, 71, 76, 84, 106
- pmx_shrink, 86
- pmx_sim, 40, 86
- pmx_theme, 88
- pmx_update, 10, 14, 18–23, 30, 31, 58, 59, 61, 64, 68, 71, 76, 89, 106, 108, 110
- pmx_vpc, 71, 90, 91–95
- pmx_vpc_bin, 70, 71, 90, 91, 91, 92–95
- pmx_vpc_ci, 70, 71, 90, 91, 92, 93–95
- pmx_vpc_obs, 70, 71, 90–92, 93, 94, 95
- pmx_vpc_pi, 70, 71, 90–93, 93, 95
- pmx_vpc_rug, 70, 71, 90–94, 94
- pmxOptions, 42
- print.abbreviation, 95
- print.configs, 96
- print.pmx_gpar, 97
- print.pmxClass, 96
- print.pmxConfig, 97

- read_csv, 80
- read_extfile, 98
- read_input, 99
- read_mlx_ind_est, 100
- read_mlx_par_est, 100
- read_mlx_pred, 101
- read_mlx_saem_conv, 101
- read_table, 80
- residual, 38, 102, 106, 109
- residual_scatter, 103

- set_abbrev, 107
- set_data, 18–23, 30, 31, 63, 67, 90, 105, 108, 110
- set_plot, 18–23, 30, 31, 90, 108, 109
- sys.call, 108

- theme, 88
- theophylline, 110
- tibble, 78

- wrap_formula, 110