

Package ‘gglm’

July 22, 2025

Type Package

Title Grammar of Graphics for Linear Model Diagnostic Plots

Version 1.0.4

Description Allows for easy creation of diagnostic plots for a variety of model objects using the Grammar of Graphics.
Provides functionality for both individual diagnostic plots and an array of four standard diagnostic plots.

License CC0

Date 2025-04-01

Encoding UTF-8

Depends ggplot2

Imports broom, broom.mixed, cli, dplyr, metafor, nlme, patchwork,
purrr, tibble, tidyr, utils, rlang, vctrs

Suggests lme4, testthat (>= 3.0.0)

URL <https://github.com/graysonwhite/gglm>,
<https://graysonwhite.com/gglm/>

BugReports <https://github.com/graysonwhite/gglm/issues>

RoxygenNote 7.2.3

Config/testthat/edition 3

NeedsCompilation no

Author Grayson White [aut, cre] (ORCID:
<https://orcid.org/0000-0003-4993-2792>)

Maintainer Grayson White <graysonwhite13@gmail.com>

Repository CRAN

Date/Publication 2025-04-01 19:40:02 UTC

Contents

<code>gglm</code>	2
<code>list_model_classes</code>	3
<code>stat_cooks_leverage</code>	3
<code>stat_cooks_obs</code>	4
<code>stat_fitted_resid</code>	5
<code>stat_normal_qq</code>	5
<code>stat_resid_hist</code>	6
<code>stat_resid_leverage</code>	6
<code>stat_scale_location</code>	7
Index	9

<code>gglm</code>	<i>gglm</i>
-------------------	-------------

Description

Provides four standard visual model diagnostic plots with ‘ggplot2’.

Usage

```
gglm(data, theme = ggplot2::theme_gray(), ...)
```

Arguments

- `data` A model object of type ‘lm’ or ‘glm’.
- `theme` The theme of the ‘ggplot’s to be produced.
- `...` Currently ignored. For extendability.

Value

A a ‘ggplot2’ object for visual diagnostic of model validity.

Examples

```
data(mtcars)
m1 <- lm(mpg ~ cyl + disp + hp, data = mtcars)
gglm(m1)
```

list_model_classes	<i>list_model_classes</i>
--------------------	---------------------------

Description

Returns the possible model classes that ‘ggglm’ works with.

Usage

```
list_model_classes(...)
```

Arguments

... Currently ignored. For extendability.

Value

A character vector containing the possible model classes that ‘ggglm’ works with.

Note

Note that these are not always the exact name of the class that that can be used. This is due to how some methods are written in the packages ‘ggglm’ imports. For example, the model class "merMod" refers to a variety of model outputs from ‘lme4’, even when the outputted class is not called "merMod".

Examples

```
list_model_classes()
```

stat_cooks_leverage	<i>stat_cooks_leverage</i>
---------------------	----------------------------

Description

Cook’s Distance vs. Leverage

Usage

```
stat_cooks_leverage(  
  alpha = 0.5,  
  method = "loess",  
  color = "steelblue",  
  se = FALSE,  
  ...  
)
```

Arguments

<code>alpha</code>	Adjust transparency of points.
<code>method</code>	Method for fitting the line to the points.
<code>color</code>	Color of the line.
<code>se</code>	Keep standard error bands around line?
<code>...</code>	Currently ignored. For extendability.

Value

A ‘ggplot2’ layer for plotting Cook’s Distance vs. Leverage.

Examples

```
data(mtcars)
model <- lm(mpg ~ cyl + disp + hp, data = mtcars)
ggplot2::ggplot(data = model) + stat_cooks_leverage()
```

stat_cooks_obs

stat_cooks_obs

Description

‘ggplot2’ layer for plotting cook’s distance by observation number.

Usage

```
stat_cooks_obs(...)
```

Arguments

`...` Currently ignored. For extendability.

Value

A ‘ggplot2’ layer for plotting cook’s distance by observation number.

Examples

```
data(mtcars)
model <- lm(mpg ~ cyl + disp + hp, data = mtcars)
ggplot2::ggplot(data = model) + stat_cooks_obs()
```

stat_fitted_resid	<i>stat_fitted_resid</i>
-------------------	--------------------------

Description

‘ggplot2’ layer for plotting a fitted vs. residual scatter plot.

Usage

```
stat_fitted_resid(alpha = 0.5, ...)
```

Arguments

alpha	Adjust transparency of points.
...	Currently ignored. For extendability.

Value

A ‘ggplot2’ layer for plotting a fitted vs. residual scatter plot.

Examples

```
data(mtcars)
model <- lm(mpg ~ cyl + disp + hp, data = mtcars)
ggplot2::ggplot(data = model) + stat_fitted_resid()
```

stat_normal_qq	<i>stat_normal_qq</i>
----------------	-----------------------

Description

Normal QQ plot.

Usage

```
stat_normal_qq(alpha = 0.5, ...)
```

Arguments

alpha	Adjust transparency of points.
...	Currently ignored. For extendability.

Value

A ‘ggplot2’ layer for plotting a Normal Q-Q plot.

Examples

```
data(mtcars)
model <- lm(mpg ~ cyl + disp + hp, data = mtcars)
ggplot2::ggplot(data = model) + stat_normal_qq()
```

stat_resid_hist	<i>stat_resid_hist</i>
-----------------	------------------------

Description

Visualize the distribution of the residuals of a model.

Usage

```
stat_resid_hist(bins = 30, ...)
```

Arguments

bins	Adjust the number of bins.
...	Currently ignored. For extendability.

Value

A ‘ggplot2’ layer for plotting a histogram of residuals.

Examples

```
data(mtcars)
model <- lm(mpg ~ cyl + disp + hp, data = mtcars)
ggplot2::ggplot(data = model) + stat_resid_hist()
```

stat_resid_leverage	<i>stat_resid_leverage</i>
---------------------	----------------------------

Description

Residual vs. leverage plot.

Usage

```
stat_resid_leverage(
  alpha = 0.5,
  method = "loess",
  se = FALSE,
  color = "steelblue",
  ...
)
```

Arguments

alpha	Adjust transparency of points.
method	Method for fitting the line to the points.
se	Keep standard error bands around line?
color	Color of the line.
...	Currently ignored. For extendability.

Value

A 'ggplot2' layer for plotting a fitted vs. residual scatter plot.

Examples

```
data(mtcars)
model <- lm(mpg ~ cyl + disp + hp, data = mtcars)
ggplot2::ggplot(data = model) + stat_resid_leverage()
```

stat_scale_location *stat_scale_location*

Description

Scale location diagnostic plot.

Usage

```
stat_scale_location(
  alpha = 0.5,
  na.rm = TRUE,
  se = FALSE,
  method = "loess",
  color = "steelblue",
  ...
)
```

Arguments

alpha	Adjust the transparency of points.
na.rm	Remove points with value NA?
se	Keep standard error bands around line?
method	Method for fitting the line to the points.
color	Color of the line.
...	Currently ignored. For extendability.

Value

A ‘ggplot2’ layer for plotting the scale location diagnostic plot.

Examples

```
data(mtcars)
model <- lm(mpg ~ cyl + disp + hp, data = mtcars)
ggplot2::ggplot(data = model) + stat_scale_location()
```

Index

`ggglm`, [2](#)

`list_model_classes`, [3](#)

`stat_cooks_leverage`, [3](#)

`stat_cooks_obs`, [4](#)

`stat_fitted_resid`, [5](#)

`stat_normal_qq`, [5](#)

`stat_resid_hist`, [6](#)

`stat_resid_leverage`, [6](#)

`stat_scale_location`, [7](#)