

Package ‘ggsci’

July 22, 2025

Type Package

Title Scientific Journal and Sci-Fi Themed Color Palettes for
'ggplot2'

Version 3.2.0

Maintainer Nan Xiao <me@nanx.me>

Description A collection of 'ggplot2' color palettes inspired by
plots in scientific journals, data visualization libraries,
science fiction movies, and TV shows.

License GPL (>= 3)

URL <https://nanx.me/ggsci/>, <https://github.com/nanxstats/ggsci>

BugReports <https://github.com/nanxstats/ggsci/issues>

Depends R (>= 3.5.0)

Imports ggplot2 (>= 2.0.0), grDevices, scales

Suggests gridExtra, knitr, ragg, rmarkdown

VignetteBuilder knitr

Encoding UTF-8

RoxygenNote 7.3.1

NeedsCompilation no

Author Nan Xiao [aut, cre] (ORCID: <<https://orcid.org/0000-0002-0250-5673>>),
Joshua Cook [ctb],
Clara Jégousse [ctb],
Hui Chen [ctb],
Miaozhu Li [ctb]

Repository CRAN

Date/Publication 2024-06-18 00:20:02 UTC

Contents

pal_aaas	3
pal_bmj	4
pal_bs5	4
pal_cosmic	5
pal_d3	6
pal_flatui	7
pal_frontiers	8
pal_futurama	8
pal_gsea	9
pal_igv	10
pal_jama	10
pal_jco	11
pal_lancet	12
pal_locuszoom	12
pal_material	13
pal_nejm	14
pal_npg	15
pal_observable	15
pal_rickandmorty	16
pal_simpsons	17
pal_startrek	17
pal_tron	18
pal_tw3	19
pal_uchicago	20
pal_ucscgb	21
rgb_bs5	21
rgb_gsea	23
rgb_material	23
rgb_tw3	25
scale_color_aaas	26
scale_color_bmj	27
scale_color_bs5	28
scale_color_cosmic	30
scale_color_d3	31
scale_color_flatui	33
scale_color_frontiers	34
scale_color_futurama	35
scale_color_gsea	36
scale_color_igv	37
scale_color_jama	39
scale_color_jco	40
scale_color_lancet	41
scale_color_locuszoom	42
scale_color_material	43
scale_color_nejm	45
scale_color_npg	46

pal_aaas 3

scale_color_observable	47
scale_color_rickandmorty	48
scale_color_simpsons	49
scale_color_startrek	50
scale_color_tron	51
scale_color_tw3	52
scale_color_uchicago	54
scale_color_ucscgb	55

Index 57

pal_aaas	AAAS journal color palettes
----------	-----------------------------

Description

Color palettes inspired by plots in journals published by American Association for the Advancement of Science (AAAS), such as *Science* and *Science Translational Medicine*.

Usage

```
pal_aaas(palette = c("default"), alpha = 1)
```

Arguments

palette	Palette type. Currently there is one available option: "default" (10-color palette inspired by <i>Science</i>).
alpha	Transparency level, a real number in (0, 1]. See alpha in <code>grDevices::rgb()</code> for details.

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

Examples

```
library("scales")
show_col(pal_aaas("default")(10))
show_col(pal_aaas("default", alpha = 0.6)(10))
```

pal_bmj	<i>BMJ color palettes</i>
---------	---------------------------

Description

Color palette from the BMJ living style guide.

Usage

```
pal_bmj(palette = c("default"), alpha = 1)
```

Arguments

palette	Palette type. Currently there is one available option: "default" (9-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.

Author(s)

Hui Chen | <huichen@zju.edu.cn>

References

<https://technology.bmj.com/living-style-guide/colour.html>

Examples

```
library("scales")
show_col(pal_bmj("default")(9))
show_col(pal_bmj("default", alpha = 0.6)(9))
```

pal_bs5	<i>Bootstrap 5 color palettes</i>
---------	-----------------------------------

Description

Bootstrap 5 color palettes.

Usage

```
pal_bs5(
  palette = c("blue", "indigo", "purple", "pink", "red", "orange", "yellow", "green",
    "teal", "cyan", "gray"),
  n = 10,
  alpha = 1,
  reverse = FALSE
)
```

Arguments

palette	Palette type. There are 11 available options: • "blue" • "indigo" • "purple" • "pink" • "red" • "orange" • "yellow" • "green" • "teal" • "cyan" • "gray"
n	Number of individual colors to be generated.
alpha	Transparency level, a real number in (0, 1]. See alpha in <code>grDevices::rgb()</code> for details.
reverse	Logical. Should the order of the colors be reversed?

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

Examples

```
library("scales")
show_col(pal_bs5("indigo")(10))
show_col(pal_bs5("indigo", n = 30, alpha = 0.6, reverse = TRUE)(30))
```

pal_cosmic

COSMIC color palettes

Description

Color palettes inspired by the colors used in projects from the [Catalogue Of Somatic Mutations in Cancers \(COSMIC\)](#).

Usage

```
pal_cosmic(
  palette = c("hallmarks_light", "hallmarks_dark", "signature_substitutions"),
  alpha = 1
)
```

Arguments

palette	Palette type. Currently there are three available options: • "signature_substitutions" (6-color palette). • "hallmarks_light" (10-color palette). • "hallmarks_dark" (10-color palette). The "hallmarks_light" option is from Hanahan and Weinberg (2011) .
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.

Author(s)

Joshua H. Cook | <joshuacook0023@gmail.com> | [@jhrcook](#)

Examples

```
library("scales")
show_col(pal_cosmic("hallmarks_light")(10))
show_col(pal_cosmic("hallmarks_light", alpha = 0.6)(10))
show_col(pal_cosmic("hallmarks_dark")(10))
show_col(pal_cosmic("hallmarks_dark", alpha = 0.6)(10))
show_col(pal_cosmic("signature_substitutions")(6))
show_col(pal_cosmic("signature_substitutions", alpha = 0.6)(6))
```

pal_d3

D3.js color palettes

Description

Color palettes based on the colors used by D3.js.

Usage

```
pal_d3(
  palette = c("category10", "category20", "category20b", "category20c"),
  alpha = 1
)
```

Arguments

palette	Palette type. There are four available options: • "category10" (10-color palette). • "category20" (20-color palette). • "category20b" (20-color palette). • "category20c" (20-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

References

<https://github.com/d3/d3-3.x-api-reference/blob/master/Ordinal-Scales.md>

Examples

```
library("scales")
show_col(pal_d3("category10")(10))
show_col(pal_d3("category20")(20))
show_col(pal_d3("category20b")(20))
show_col(pal_d3("category20c")(20))
```

pal_flatui	<i>Flat UI color palettes</i>
------------	-------------------------------

Description

Color palettes inspired by the Flat UI colors.

Usage

```
pal_flatui(palette = c("default", "flattastic", "aussie"), alpha = 1)
```

Arguments

palette	Palette type. Currently there are three available options: • "default" (10-color palette). • "flattastic" (12-color palette). • "aussie" (10-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.

Author(s)

Clara Jégousse | <cat3@hi.is>

Examples

```
library("scales")
show_col(pal_flatui("default")(10))
show_col(pal_flatui("flattastic")(12))
show_col(pal_flatui("aussie")(10))
show_col(pal_flatui("aussie", alpha = 0.6)(10))
```

pal_frontiers	<i>Frontiers journal color palettes</i>
---------------	---

Description

Color palettes inspired by the colors used in *Frontiers* journals.

Usage

```
pal_frontiers(palette = c("default"), alpha = 1)
```

Arguments

palette	Palette type. Currently there is one available option: "default" (10-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.

Author(s)

Clara Jégousse | <cat3@hi.is>

Examples

```
library("scales")
show_col(pal_frontiers("default")(7))
show_col(pal_frontiers("default", alpha = 0.6)(7))
```

pal_futurama	<i>Futurama color palettes</i>
--------------	--------------------------------

Description

Color palettes inspired by the colors used in *Futurama*.

Usage

```
pal_futurama(palette = c("planetexpress"), alpha = 1)
```

Arguments

palette	Palette type. Currently there is one available option: "planetexpress" (12-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

Examples

```
library("scales")
show_col(pal_futurama("planetexpress")(12))
show_col(pal_futurama("planetexpress", alpha = 0.6)(12))
```

pal_gsea

The GSEA GenePattern color palettes

Description

Color palette inspired by the colors used in the heatmaps plotted by GSEA GenePattern.

Usage

```
pal_gsea(palette = c("default"), n = 12, alpha = 1, reverse = FALSE)
```

Arguments

palette	Palette type. Currently there is one available option: "default" (continuous palette with 12 base colors).
n	Number of individual colors to be generated.
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
reverse	Logical. Should the order of the colors be reversed?

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

Examples

```
library("scales")
show_col(pal_gsea("default")(12))
show_col(pal_gsea("default", n = 30, alpha = 0.6, reverse = TRUE)(30))
```

pal_igv	<i>Integrative Genomics Viewer (IGV) color palettes</i>
---------	---

Description

Color palettes based on the colors used by Integrative Genomics Viewer (IGV).

Usage

```
pal_igv(palette = c("default", "alternating"), alpha = 1)
```

Arguments

palette	Palette type. There are two available options: • "default" (51-color palette). • "alternating" (2-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in <code>grDevices::rgb()</code> for details.

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

References

James T. Robinson, Helga Thorvaldsdóttir, Wendy Winckler, Mitchell Guttman, Eric S. Lander, Gad Getz, Jill P. Mesirov. Integrative Genomics Viewer. *Nature Biotechnology* 29, 24–26 (2011).

Examples

```
library("scales")
show_col(pal_igv("default")(51))
show_col(pal_igv("alternating")(2))
```

pal_jama	<i>Journal of the American Medical Association color palettes</i>
----------	---

Description

Color palette inspired by plots in *The Journal of the American Medical Association*.

Usage

```
pal_jama(palette = c("default"), alpha = 1)
```

Arguments

palette	Palette type. Currently there is one available option: "default" (7-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.

Author(s)

Nan Xiao | [<me@nanx.me>](mailto:me@nanx.me) | <https://nanx.me>

Examples

```
library("scales")
show_col(pal_jama("default")(7))
show_col(pal_jama("default", alpha = 0.6)(7))
```

pal_jco

Journal of Clinical Oncology color palettes

Description

Color palette inspired by plots in *Journal of Clinical Oncology*.

Usage

```
pal_jco(palette = c("default"), alpha = 1)
```

Arguments

palette	Palette type. Currently there is one available option: "default" (10-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.

Author(s)

Nan Xiao | [<me@nanx.me>](mailto:me@nanx.me) | <https://nanx.me>

Examples

```
library("scales")
show_col(pal_jco("default")(10))
show_col(pal_jco("default", alpha = 0.6)(10))
```

pal_lancet	<i>Lancet journal color palettes</i>
------------	--------------------------------------

Description

Color palettes inspired by plots in Lancet journals, such as *Lancet Oncology*.

Usage

```
pal_lancet(palette = c("lanonc"), alpha = 1)
```

Arguments

palette	Palette type. Currently there is one available option: "lanonc" (9-color palette inspired by <i>Lancet Oncology</i>).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.

Author(s)

Nan Xiao | [<me@nanx.me>](mailto:me@nanx.me) | <https://nanx.me>

Examples

```
library("scales")
show_col(pal_lancet("lanonc")(9))
show_col(pal_lancet("lanonc", alpha = 0.6)(9))
```

pal_locuszoom	<i>LocusZoom color palette</i>
---------------	--------------------------------

Description

Color palettes based on the colors used by LocusZoom.

Usage

```
pal_locuszoom(palette = c("default"), alpha = 1)
```

Arguments

palette	Palette type. Currently there is one available option: "default" (7-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

References

Pruim, Randall J., et al. (2010). LocusZoom: regional visualization of genome-wide association scan results. *Bioinformatics*, 26(18), 2336–2337.

Examples

```
library("scales")
show_col(pal_locuszoom("default")(7))
show_col(pal_locuszoom("default", alpha = 0.6)(7))
```

pal_material	<i>Material Design color palettes</i>
--------------	---------------------------------------

Description

Material Design 2 color palettes.

Usage

```
pal_material(
  palette = c("red", "pink", "purple", "deep-purple", "indigo", "blue", "light-blue",
    "cyan", "teal", "green", "light-green", "lime", "yellow", "amber", "orange",
    "deep-orange", "brown", "grey", "blue-grey"),
  n = 10,
  alpha = 1,
  reverse = FALSE
)
```

Arguments

palette Palette type. There are 19 available options:

- "red"
- "pink"
- "purple"
- "deep-purple"
- "indigo"
- "blue"
- "light-blue"
- "cyan"
- "teal"
- "green"

	• "light-green" • "lime" • "yellow" • "amber" • "orange" • "deep-orange" • "brown" • "grey" • "blue-grey"
n	Number of individual colors to be generated.
alpha	Transparency level, a real number in (0, 1]. See alpha in <code>grDevices::rgb()</code> for details.
reverse	Logical. Should the order of the colors be reversed?

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

Examples

```
library("scales")
show_col(pal_material("indigo")(10))
show_col(pal_material("indigo", n = 30, alpha = 0.6, reverse = TRUE)(30))
```

pal_nejm

NEJM color palettes

Description

Color palette inspired by plots in *The New England Journal of Medicine*.

Usage

```
pal_nejm(palette = c("default"), alpha = 1)
```

Arguments

palette	Palette type. Currently there is one available option: "default" (8-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in <code>grDevices::rgb()</code> for details.

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

Examples

```
library("scales")
show_col(pal_nejm("default")(8))
show_col(pal_nejm("default", alpha = 0.6)(8))
```

pal_npg	<i>NPG journal color palettes</i>
---------	-----------------------------------

Description

Color palettes inspired by plots in journals published by Nature Publishing Group, such as *Nature Reviews Cancer*.

Usage

```
pal_npg(palette = c("nrc"), alpha = 1)
```

Arguments

palette	Palette type. Currently there is one available option: "nrc" (10-color palette inspired by <i>Nature Reviews Cancer</i>).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.

Author(s)

Nan Xiao | me@nanx.me | <https://nanx.me>

Examples

```
library("scales")
show_col(pal_npg("nrc")(10))
show_col(pal_npg("nrc", alpha = 0.6)(10))
```

pal_observable	<i>Observable 10 color palette</i>
----------------	------------------------------------

Description

The Observable 10 palette.

Usage

```
pal_observable(palette = c("observable10"), alpha = 1)
```

Arguments

palette	Palette type. Currently there is one available option: "observable10" (10-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

References

Pettiross J (2023). "Crafting data colors and staying on brand." *Observable blog*. <https://observablehq.com/blog/crafting-data-colors>

Examples

```
library("scales")
show_col(pal_observable("observable10")(10))
show_col(pal_observable("observable10", alpha = 0.6)(10))
```

pal_rickandmorty	<i>Rick and Morty color palettes</i>
------------------	--------------------------------------

Description

Color palettes inspired by the colors used in *Rick and Morty*.

Usage

```
pal_rickandmorty(palette = c("schwifty"), alpha = 1)
```

Arguments

palette	Palette type. Currently there is one available option: "schwifty" (12-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

Examples

```
library("scales")
show_col(pal_rickandmorty("schwifty")(12))
show_col(pal_rickandmorty("schwifty", alpha = 0.6)(12))
```

pal_simpsons	<i>The Simpsons color palettes</i>
--------------	------------------------------------

Description

Color palettes inspired by the colors used in *The Simpsons*.

Usage

```
pal_simpsons(palette = c("springfield"), alpha = 1)
```

Arguments

palette	Palette type. Currently there is one available option: "springfield" (16-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.

Author(s)

Nan Xiao | [<me@nanx.me>](mailto:me@nanx.me) | <https://nanx.me>

Examples

```
library("scales")
show_col(pal_simpsons("springfield")(16))
show_col(pal_simpsons("springfield", alpha = 0.6)(16))
```

pal_startrek	<i>Star Trek color palettes</i>
--------------	---------------------------------

Description

Color palettes inspired by the colors used in *Star Trek*.

Usage

```
pal_startrek(palette = c("uniform"), alpha = 1)
```

Arguments

palette	Palette type. Currently there is one available option: "uniform" (7-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

Examples

```
library("scales")
show_col(pal_startrek("uniform")(7))
show_col(pal_startrek("uniform", alpha = 0.6)(7))
```

pal_tron

Tron Legacy color palettes

Description

Color palettes inspired by the colors used in *Tron Legacy*.

Usage

```
pal_tron(palette = c("legacy"), alpha = 1)
```

Arguments

palette	Palette type. Currently there is one available option: "legacy" (7-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

Examples

```
library("scales")
show_col(pal_tron("legacy")(7))
show_col(pal_tron("legacy", alpha = 0.6)(7))
```

`pal_tw3`*Tailwind CSS color palettes*

Description

Tailwind CSS color palettes.

Usage

```
pal_tw3(  
  palette = c("slate", "gray", "zinc", "neutral", "stone", "red", "orange", "amber",  
    "yellow", "lime", "green", "emerald", "teal", "cyan", "sky", "blue", "indigo",  
    "violet", "purple", "fuchsia", "pink", "rose"),  
  n = 10,  
  alpha = 1,  
  reverse = FALSE  
)
```

Arguments

`palette` Palette type. There are 22 available options:

- "slate"
- "gray"
- "zinc"
- "neutral"
- "stone"
- "red"
- "orange"
- "amber"
- "yellow"
- "lime"
- "green"
- "emerald"
- "teal"
- "cyan"
- "sky"
- "blue"
- "indigo"
- "violet"
- "purple"
- "fuchsia"
- "pink"
- "rose"

n	Number of individual colors to be generated.
alpha	Transparency level, a real number in (0, 1]. See alpha in <code>grDevices::rgb()</code> for details.
reverse	Logical. Should the order of the colors be reversed?

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

Examples

```
library("scales")
show_col(pal_tw3("rose")(10))
show_col(pal_tw3("rose", n = 30, alpha = 0.6, reverse = TRUE)(30))
```

pal_uchicago	<i>The University of Chicago color palettes</i>
--------------	---

Description

Color palettes based on the colors used by the University of Chicago.

Usage

```
pal_uchicago(palette = c("default", "light", "dark"), alpha = 1)
```

Arguments

palette	Palette type. There are three available options: • "default" (9-color palette); • "light" (9-color light palette); • "dark" (9-color dark palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in <code>grDevices::rgb()</code> for details.

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

References

https://news.uchicago.edu/sites/default/files/attachments/_uchicago.identity.guidelines.pdf

Examples

```
library("scales")
show_col(pal_uchicago("default")(9))
show_col(pal_uchicago("light")(9))
show_col(pal_uchicago("dark")(9))
```

pal_ucscgb

*UCSC Genome Browser color palette***Description**

Color palette from UCSC Genome Browser chromosome colors.

Usage

```
pal_ucscgb(palette = c("default"), alpha = 1)
```

Arguments

palette	Palette type. Currently there is one available option: "default" (26-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.

Author(s)

Nan Xiao | [<me@nanx.me>](mailto:me@nanx.me) | <https://nanx.me>

Examples

```
library("scales")
show_col(pal_ucscgb("default")(26))
show_col(pal_ucscgb("default", alpha = 0.6)(26))
```

rgb_bs5

*Bootstrap 5 color palettes***Description**

Bootstrap 5 color palettes.

Usage

```
rgb_bs5(
  palette = c("blue", "indigo", "purple", "pink", "red", "orange", "yellow", "green",
    "teal", "cyan", "gray"),
  n = 10,
  alpha = 1,
  reverse = FALSE
)
```

Arguments

palette	Palette type. There are 11 available options: • "blue" • "indigo" • "purple" • "pink" • "red" • "orange" • "yellow" • "green" • "teal" • "cyan" • "gray"
n	Number of individual colors to be generated.
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
reverse	Logical. Should the order of the colors be reversed?

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

References

<https://getbootstrap.com/docs/5.3/customize/color/#all-colors>

Examples

```
library("scales")
show_col(pal_bs5("indigo")(10))
show_col(pal_bs5("indigo", n = 30, alpha = 0.6, reverse = TRUE)(30))
```

rgb_gsea*The GSEA GenePattern color palettes*

Description

Color palette inspired by the colors used in the heatmaps plotted by GSEA GenePattern.

Usage

```
rgb_gsea(palette = c("default"), n = 12, alpha = 1, reverse = FALSE)
```

Arguments

palette	Palette type. Currently there is one available option: "default" (continuous palette with 12 base colors).
n	Number of individual colors to be generated.
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
reverse	Logical. Should the order of the colors be reversed?

Note

The 12 base colors used in this palette are derived from the [HeatMapImage documentation](#).

Author(s)

Nan Xiao | me@nanx.me | <https://nanx.me>

Examples

```
library("scales")
show_col(pal_gsea("default")(12))
show_col(pal_gsea("default", n = 30, alpha = 0.6, reverse = TRUE)(30))
```

rgb_material*Material Design color palettes*

Description

Material Design 2 color palettes.

Usage

```
rgb_material(  
  palette = c("red", "pink", "purple", "deep-purple", "indigo", "blue", "light-blue",  
    "cyan", "teal", "green", "light-green", "lime", "yellow", "amber", "orange",  
    "deep-orange", "brown", "grey", "blue-grey"),  
  n = 10,  
  alpha = 1,  
  reverse = FALSE  
)
```

Arguments

palette	Palette type. There are 19 available options: • "red" • "pink" • "purple" • "deep-purple" • "indigo" • "blue" • "light-blue" • "cyan" • "teal" • "green" • "light-green" • "lime" • "yellow" • "amber" • "orange" • "deep-orange" • "brown" • "grey" • "blue-grey"
n	Number of individual colors to be generated.
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
reverse	Logical. Should the order of the colors be reversed?

Author(s)

Nan Xiao | me@nanx.me | <https://nanx.me>

References

<https://m2.material.io/design/color/the-color-system.html>

Examples

```
library("scales")
show_col(pal_material("indigo")(10))
show_col(pal_material("indigo", n = 30, alpha = 0.6, reverse = TRUE)(30))
```

rgb_tw3

Tailwind CSS color palettes

Description

Tailwind CSS color palettes.

Usage

```
rgb_tw3(
  palette = c("slate", "gray", "zinc", "neutral", "stone", "red", "orange", "amber",
    "yellow", "lime", "green", "emerald", "teal", "cyan", "sky", "blue", "indigo",
    "violet", "purple", "fuchsia", "pink", "rose"),
  n = 10,
  alpha = 1,
  reverse = FALSE
)
```

Arguments

palette Palette type. There are 22 available options:

- "slate"
- "gray"
- "zinc"
- "neutral"
- "stone"
- "red"
- "orange"
- "amber"
- "yellow"
- "lime"
- "green"
- "emerald"
- "teal"
- "cyan"
- "sky"
- "blue"
- "indigo"
- "violet"

	• "purple" • "fuchsia" • "pink" • "rose"
n	Number of individual colors to be generated.
alpha	Transparency level, a real number in (0, 1]. See alpha in <code>grDevices::rgb()</code> for details.
reverse	Logical. Should the order of the colors be reversed?

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

References

<https://tailwindcss.com/docs/customizing-colors>

Examples

```
library("scales")
show_col(pal_tw3("rose")(10))
show_col(pal_tw3("rose", n = 30, alpha = 0.6, reverse = TRUE)(30))
```

scale_color_aaas	<i>AAAS journal color scales</i>
------------------	----------------------------------

Description

See `pal_aaas()` for details.

Usage

```
scale_color_aaas(palette = c("default"), alpha = 1, ...)
```

```
scale_colour_aaas(palette = c("default"), alpha = 1, ...)
```

```
scale_fill_aaas(palette = c("default"), alpha = 1, ...)
```

Arguments

palette	Palette type. Currently there is one available option: "default" (10-color palette inspired by <i>Science</i>).
alpha	Transparency level, a real number in (0, 1]. See alpha in <code>grDevices::rgb()</code> for details.
...	Additional parameters for <code>ggplot2::discrete_scale()</code> .

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

Examples

```
library("ggplot2")
data("diamonds")

ggplot(
  subset(diamonds, carat >= 2.2),
  aes(x = table, y = price, colour = cut)
) +
  geom_point(alpha = 0.7) +
  geom_smooth(method = "loess", alpha = 0.1, size = 1, span = 1) +
  theme_bw() +
  scale_color_aaas()

ggplot(
  subset(diamonds, carat > 2.2 & depth > 55 & depth < 70),
  aes(x = depth, fill = cut)
) +
  geom_histogram(colour = "black", binwidth = 1, position = "dodge") +
  theme_bw() +
  scale_fill_aaas()
```

scale_color_bmj

BMJ color scales

Description

See [pal_bmj\(\)](#) for details.

Usage

```
scale_color_bmj(palette = c("default"), alpha = 1, ...)
```

```
scale_colour_bmj(palette = c("default"), alpha = 1, ...)
```

```
scale_fill_bmj(palette = c("default"), alpha = 1, ...)
```

Arguments

palette	Palette type. Currently there is one available option: "default" (9-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
...	Additional parameters for ggplot2::discrete_scale() .

Author(s)

Hui Chen | <huichen@zju.edu.cn>

References

<https://technology.bmj.com/living-style-guide/colour.html>

Examples

```
library("ggplot2")
data("diamonds")

ggplot(
  subset(diamonds, carat >= 2.2),
  aes(x = table, y = price, colour = cut)
) +
  geom_point(alpha = 0.7) +
  geom_smooth(method = "loess", alpha = 0.1, size = 1, span = 1) +
  theme_bw() +
  scale_color_bmj()

ggplot(
  subset(diamonds, carat > 2.2 & depth > 55 & depth < 70),
  aes(x = depth, fill = cut)
) +
  geom_histogram(colour = "black", binwidth = 1, position = "dodge") +
  theme_bw() +
  scale_fill_bmj()
```

scale_color_bs5

Bootstrap 5 color scales

Description

See [pal_bs5\(\)](#) for details.

Usage

```
scale_color_bs5(
  palette = c("blue", "indigo", "purple", "pink", "red", "orange", "yellow", "green",
    "teal", "cyan", "gray"),
  alpha = 1,
  reverse = FALSE,
  ...
)

scale_colour_bs5(
  palette = c("blue", "indigo", "purple", "pink", "red", "orange", "yellow", "green",
```

```

    "teal", "cyan", "gray"),
  alpha = 1,
  reverse = FALSE,
  ...
)

scale_fill_bs5(
  palette = c("blue", "indigo", "purple", "pink", "red", "orange", "yellow", "green",
    "teal", "cyan", "gray"),
  alpha = 1,
  reverse = FALSE,
  ...
)

```

Arguments

palette	Palette type. There are 11 available options: • "blue" • "indigo" • "purple" • "pink" • "red" • "orange" • "yellow" • "green" • "teal" • "cyan" • "gray"
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
reverse	Logical. Should the order of the colors be reversed?
...	Additional parameters for ggplot2::discrete_scale() .

Author(s)

Nan Xiao | me@nanx.me | <https://nanx.me>

Examples

```

library("ggplot2")

data("mtcars")
cor <- abs(cor(mtcars))
cor_melt <- data.frame(
  Var1 = rep(seq_len(nrow(cor)), times = ncol(cor)),
  Var2 = rep(seq_len(ncol(cor)), each = nrow(cor)),
  value = as.vector(cor)
)

```

```

)

ggplot(
  cor_melt,
  aes(x = Var1, y = Var2, fill = value)
) +
  geom_tile(colour = "black", size = 0.3) +
  theme_bw() +
  scale_fill_bs5("teal")

```

scale_color_cosmic *COSMIC color scales*

Description

See [pal_cosmic\(\)](#) for details.

Usage

```

scale_color_cosmic(
  palette = c("hallmarks_light", "hallmarks_dark", "signature_substitutions"),
  alpha = 1,
  ...
)

scale_colour_cosmic(
  palette = c("hallmarks_light", "hallmarks_dark", "signature_substitutions"),
  alpha = 1,
  ...
)

scale_fill_cosmic(
  palette = c("hallmarks_light", "hallmarks_dark", "signature_substitutions"),
  alpha = 1,
  ...
)

```

Arguments

palette	Palette type. Currently there are three available options: • "signature_substitutions" (6-color palette). • "hallmarks_light" (10-color palette). • "hallmarks_dark" (10-color palette). The "hallmarks_light" option is from Hanahan and Weinberg (2011) .
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
...	Additional parameters for ggplot2::discrete_scale() .

Author(s)

Joshua H. Cook | <joshuacook0023@gmail.com> | [@jhrcook](#)

Examples

```
library("ggplot2")
data("diamonds")

ggplot(
  subset(diamonds, carat >= 2.2),
  aes(x = table, y = price, colour = cut)
) +
  geom_point(alpha = 0.7) +
  geom_smooth(method = "loess", alpha = 0.1, size = 1, span = 1) +
  theme_bw() +
  scale_color_cosmic()

ggplot(
  subset(diamonds, carat > 2.2 & depth > 55 & depth < 70),
  aes(x = depth, fill = cut)
) +
  geom_histogram(colour = "black", binwidth = 1, position = "dodge") +
  theme_bw() +
  scale_fill_cosmic()
```

scale_color_d3

D3.js color scales

Description

See [pal_d3\(\)](#) for details.

Usage

```
scale_color_d3(
  palette = c("category10", "category20", "category20b", "category20c"),
  alpha = 1,
  ...
)

scale_colour_d3(
  palette = c("category10", "category20", "category20b", "category20c"),
  alpha = 1,
  ...
)

scale_fill_d3(
  palette = c("category10", "category20", "category20b", "category20c"),
```

```
alpha = 1,
...
)
```

Arguments

palette	Palette type. There are four available options: • "category10" (10-color palette). • "category20" (20-color palette). • "category20b" (20-color palette). • "category20c" (20-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in <code>grDevices::rgb()</code> for details.
...	Additional parameters for <code>ggplot2::discrete_scale()</code> .

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

References

<https://github.com/d3/d3-3.x-api-reference/blob/master/Ordinal-Scales.md>

Examples

```
library("ggplot2")
data("diamonds")

p1 <- ggplot(
  subset(diamonds, carat >= 2.2),
  aes(x = table, y = price, colour = cut)
) +
  geom_point(alpha = 0.7) +
  geom_smooth(method = "loess", alpha = 0.1, size = 1, span = 1) +
  theme_bw()

p2 <- ggplot(
  subset(diamonds, carat > 2.2 & depth > 55 & depth < 70),
  aes(x = depth, fill = cut)
) +
  geom_histogram(colour = "black", binwidth = 1, position = "dodge") +
  theme_bw()

p1 + scale_color_d3()
p2 + scale_fill_d3()

p1 + scale_color_d3(palette = "category20")
p2 + scale_fill_d3(palette = "category20")

p1 + scale_color_d3(palette = "category20b")
```

```
p2 + scale_fill_d3(palette = "category20b")

p1 + scale_color_d3(palette = "category20c")
p2 + scale_fill_d3(palette = "category20c")
```

scale_color_flatui *Flat UI color scales*

Description

See [pal_flatui\(\)](#) for details.

Usage

```
scale_color_flatui(
  palette = c("default", "flattastic", "aussie"),
  alpha = 1,
  ...
)

scale_colour_flatui(
  palette = c("default", "flattastic", "aussie"),
  alpha = 1,
  ...
)

scale_fill_flatui(
  palette = c("default", "flattastic", "aussie"),
  alpha = 1,
  ...
)
```

Arguments

palette	Palette type. Currently there are three available options: • "default" (10-color palette). • "flattastic" (12-color palette). • "aussie" (10-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
...	Additional parameters for ggplot2::discrete_scale() .

Author(s)

Clara Jégousse | <cat3@hi.is>

Examples

```
library("ggplot2")
data("diamonds")

p1 <- ggplot(
  subset(diamonds, carat >= 2.2),
  aes(x = table, y = price, colour = cut)
) +
  geom_point(alpha = 0.7) +
  geom_smooth(method = "loess", alpha = 0.1, size = 1, span = 1) +
  theme_bw()

p2 <- ggplot(
  subset(diamonds, carat > 2.2 & depth > 55 & depth < 70),
  aes(x = depth, fill = cut)
) +
  geom_histogram(colour = "black", binwidth = 1, position = "dodge") +
  theme_bw()

p1 + scale_color_flatui()
p2 + scale_fill_flatui()

p1 + scale_color_flatui(palette = "default")
p2 + scale_fill_flatui(palette = "default")

p1 + scale_color_flatui(palette = "flattastic")
p2 + scale_fill_flatui(palette = "flattastic")

p1 + scale_color_flatui(palette = "aussie")
p2 + scale_fill_flatui(palette = "aussie")
```

scale_color_frontiers *Frontiers journal color scales*

Description

See [pal_frontiers\(\)](#) for details.

Usage

```
scale_color_frontiers(palette = c("default"), alpha = 1, ...)

scale_colour_frontiers(palette = c("default"), alpha = 1, ...)

scale_fill_frontiers(palette = c("default"), alpha = 1, ...)
```

Arguments

palette	Palette type. Currently there is one available option: "default" (10-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
...	Additional parameters for ggplot2::discrete_scale() .

Author(s)

Clara Jégousse | [<cat3@hi.is>](mailto:cat3@hi.is)

Examples

```
library("ggplot2")
data("diamonds")

ggplot(
  subset(diamonds, carat >= 2.2),
  aes(x = table, y = price, colour = cut)
) +
  geom_point(alpha = 0.7) +
  geom_smooth(method = "loess", alpha = 0.1, size = 1, span = 1) +
  theme_dark() +
  theme(
    panel.background = element_rect(fill = "#2D2D2D"),
    legend.key = element_rect(fill = "#2D2D2D")
  ) +
  scale_color_frontiers()

ggplot(
  subset(diamonds, carat > 2.2 & depth > 55 & depth < 70),
  aes(x = depth, fill = cut)
) +
  geom_histogram(colour = "black", binwidth = 1, position = "dodge") +
  theme_dark() +
  theme(
    panel.background = element_rect(fill = "#2D2D2D")
  ) +
  scale_fill_frontiers()
```

scale_color_futurama *Futurama color scales*

Description

See [pal_futurama\(\)](#) for details.

Usage

```
scale_color_futurama(palette = c("planetexpress"), alpha = 1, ...)

scale_colour_futurama(palette = c("planetexpress"), alpha = 1, ...)

scale_fill_futurama(palette = c("planetexpress"), alpha = 1, ...)
```

Arguments

palette	Palette type. Currently there is one available option: "planetexpress" (12-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
...	Additional parameters for ggplot2::discrete_scale() .

Author(s)

Nan Xiao | me@nanx.me | <https://nanx.me>

Examples

```
library("ggplot2")
data("diamonds")

ggplot(
  subset(diamonds, carat >= 2.2),
  aes(x = table, y = price, colour = cut)
) +
  geom_point(alpha = 0.7) +
  geom_smooth(method = "loess", alpha = 0.1, size = 1, span = 1) +
  theme_bw() +
  scale_color_futurama()

ggplot(
  subset(diamonds, carat > 2.2 & depth > 55 & depth < 70),
  aes(x = depth, fill = cut)
) +
  geom_histogram(colour = "black", binwidth = 1, position = "dodge") +
  theme_bw() +
  scale_fill_futurama()
```

scale_color_gsea

The GSEA GenePattern color scales

Description

See [pal_gsea\(\)](#) for details.

Usage

```
scale_color_gsea(palette = c("default"), alpha = 1, reverse = FALSE, ...)

scale_colour_gsea(palette = c("default"), alpha = 1, reverse = FALSE, ...)

scale_fill_gsea(palette = c("default"), alpha = 1, reverse = FALSE, ...)
```

Arguments

palette	Palette type. Currently there is one available option: "default" (continuous palette with 12 base colors).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
reverse	Logical. Should the order of the colors be reversed?
...	Additional parameters for ggplot2::discrete_scale() .

Author(s)

Nan Xiao | me@nanx.me | <https://nanx.me>

Examples

```
library("ggplot2")

data("mtcars")
cor <- cor(mtcars)
cor_melt <- data.frame(
  Var1 = rep(seq_len(nrow(cor)), times = ncol(cor)),
  Var2 = rep(seq_len(ncol(cor)), each = nrow(cor)),
  value = as.vector(cor)
)

ggplot(
  cor_melt,
  aes(x = Var1, y = Var2, fill = value)
) +
  geom_tile(colour = "black", size = 0.3) +
  theme_bw() +
  scale_fill_gsea()
```

Description

See [pal_igv\(\)](#) for details.

Usage

```
scale_color_igv(palette = c("default", "alternating"), alpha = 1, ...)

scale_colour_igv(palette = c("default", "alternating"), alpha = 1, ...)

scale_fill_igv(palette = c("default", "alternating"), alpha = 1, ...)
```

Arguments

palette	Palette type. There are two available options: • "default" (51-color palette). • "alternating" (2-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in <code>grDevices::rgb()</code> for details.
...	Additional parameters for <code>ggplot2::discrete_scale()</code> .

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

Examples

```
library("ggplot2")
data("diamonds")

p1 <- ggplot(
  subset(diamonds, carat >= 2.2),
  aes(x = table, y = price, colour = cut)
) +
  geom_point(alpha = 0.7) +
  geom_smooth(method = "loess", alpha = 0.1, size = 1, span = 1) +
  theme_bw()

p2 <- ggplot(
  subset(diamonds, carat > 2.2 & depth > 55 & depth < 70),
  aes(x = depth, fill = cut)
) +
  geom_histogram(colour = "black", binwidth = 1, position = "dodge") +
  theme_bw()

p1 + scale_color_igv()
p2 + scale_fill_igv()

p1 + scale_colour_manual(
  values = rep(pal_igv("alternating")(2), times = 3)
)
p2 + scale_fill_manual(
  values = rep(pal_igv("alternating")(2), times = 3)
)
```

scale_color_jama*Journal of the American Medical Association color scales*

Description

See `pal_jama()` for details.

Usage

```
scale_color_jama(palette = c("default"), alpha = 1, ...)
```

```
scale_colour_jama(palette = c("default"), alpha = 1, ...)
```

```
scale_fill_jama(palette = c("default"), alpha = 1, ...)
```

Arguments

palette	Palette type. Currently there is one available option: "default" (7-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in <code>grDevices::rgb()</code> for details.
...	Additional parameters for <code>ggplot2::discrete_scale()</code> .

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

Examples

```
library("ggplot2")
data("diamonds")

ggplot(
  subset(diamonds, carat >= 2.2),
  aes(x = table, y = price, colour = cut)
) +
  geom_point(alpha = 0.7) +
  geom_smooth(method = "loess", alpha = 0.1, size = 1, span = 1) +
  theme_bw() +
  scale_color_jama()

ggplot(
  subset(diamonds, carat > 2.2 & depth > 55 & depth < 70),
  aes(x = depth, fill = cut)
) +
  geom_histogram(colour = "black", binwidth = 1, position = "dodge") +
  theme_bw() +
  scale_fill_jama()
```

scale_color_jco	<i>Journal of Clinical Oncology color scales</i>
-----------------	--

Description

See `pal_jco()` for details.

Usage

```
scale_color_jco(palette = c("default"), alpha = 1, ...)

scale_colour_jco(palette = c("default"), alpha = 1, ...)

scale_fill_jco(palette = c("default"), alpha = 1, ...)
```

Arguments

palette	Palette type. Currently there is one available option: "default" (10-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in <code>grDevices::rgb()</code> for details.
...	Additional parameters for <code>ggplot2::discrete_scale()</code> .

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

Examples

```
library("ggplot2")
data("diamonds")

ggplot(
  subset(diamonds, carat >= 2.2),
  aes(x = table, y = price, colour = cut)
) +
  geom_point(alpha = 0.7) +
  geom_smooth(method = "loess", alpha = 0.1, size = 1, span = 1) +
  theme_bw() +
  scale_color_jco()

ggplot(
  subset(diamonds, carat > 2.2 & depth > 55 & depth < 70),
  aes(x = depth, fill = cut)
) +
  geom_histogram(colour = "black", binwidth = 1, position = "dodge") +
  theme_bw() +
  scale_fill_jco()
```

scale_color_lancet	<i>Lancet journal color scales</i>
--------------------	------------------------------------

Description

See `pal_lancet()` for details.

Usage

```
scale_color_lancet(palette = c("lanonc"), alpha = 1, ...)
```

```
scale_colour_lancet(palette = c("lanonc"), alpha = 1, ...)
```

```
scale_fill_lancet(palette = c("lanonc"), alpha = 1, ...)
```

Arguments

palette	Palette type. Currently there is one available option: "lanonc" (9-color palette inspired by <i>Lancet Oncology</i>).
alpha	Transparency level, a real number in (0, 1]. See alpha in <code>grDevices::rgb()</code> for details.
...	Additional parameters for <code>ggplot2::discrete_scale()</code> .

Author(s)

Nan Xiao | me@nanx.me | <https://nanx.me>

Examples

```
library("ggplot2")
data("diamonds")

ggplot(
  subset(diamonds, carat >= 2.2),
  aes(x = table, y = price, colour = cut)
) +
  geom_point(alpha = 0.7) +
  geom_smooth(method = "loess", alpha = 0.1, size = 1, span = 1) +
  theme_bw() +
  scale_color_lancet()

ggplot(
  subset(diamonds, carat > 2.2 & depth > 55 & depth < 70),
  aes(x = depth, fill = cut)
) +
  geom_histogram(colour = "black", binwidth = 1, position = "dodge") +
  theme_bw() +
  scale_fill_lancet()
```

scale_color_locuszoom *LocusZoom color scales*

Description

See [pal_locuszoom\(\)](#) for details.

Usage

```
scale_color_locuszoom(palette = c("default"), alpha = 1, ...)
scale_colour_locuszoom(palette = c("default"), alpha = 1, ...)
scale_fill_locuszoom(palette = c("default"), alpha = 1, ...)
```

Arguments

palette	Palette type. Currently there is one available option: "default" (7-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
...	Additional parameters for ggplot2::discrete_scale() .

Author(s)

Nan Xiao | me@nanx.me | <https://nanx.me>

Examples

```
library("ggplot2")
data("diamonds")

ggplot(
  subset(diamonds, carat >= 2.2),
  aes(x = table, y = price, colour = cut)
) +
  geom_point(alpha = 0.7) +
  geom_smooth(method = "loess", alpha = 0.1, size = 1, span = 1) +
  theme_bw() +
  scale_color_locuszoom()

ggplot(
  subset(diamonds, carat > 2.2 & depth > 55 & depth < 70),
  aes(x = depth, fill = cut)
) +
  geom_histogram(colour = "black", binwidth = 1, position = "dodge") +
  theme_bw() +
  scale_fill_locuszoom()
```

scale_color_material *Material Design color scales*

Description

See [pal_material\(\)](#) for details.

Usage

```
scale_color_material(  
  palette = c("red", "pink", "purple", "deep-purple", "indigo", "blue", "light-blue",  
             "cyan", "teal", "green", "light-green", "lime", "yellow", "amber", "orange",  
             "deep-orange", "brown", "grey", "blue-grey"),  
  alpha = 1,  
  reverse = FALSE,  
  ...  
)  
  
scale_colour_material(  
  palette = c("red", "pink", "purple", "deep-purple", "indigo", "blue", "light-blue",  
             "cyan", "teal", "green", "light-green", "lime", "yellow", "amber", "orange",  
             "deep-orange", "brown", "grey", "blue-grey"),  
  alpha = 1,  
  reverse = FALSE,  
  ...  
)  
  
scale_fill_material(  
  palette = c("red", "pink", "purple", "deep-purple", "indigo", "blue", "light-blue",  
             "cyan", "teal", "green", "light-green", "lime", "yellow", "amber", "orange",  
             "deep-orange", "brown", "grey", "blue-grey"),  
  alpha = 1,  
  reverse = FALSE,  
  ...  
)
```

Arguments

palette	Palette type. There are 19 available options: • "red" • "pink" • "purple" • "deep-purple" • "indigo" • "blue" • "light-blue"
---------	--

	• "cyan" • "teal" • "green" • "light-green" • "lime" • "yellow" • "amber" • "orange" • "deep-orange" • "brown" • "grey" • "blue-grey"
alpha	Transparency level, a real number in (0, 1]. See alpha in <code>grDevices::rgb()</code> for details.
reverse	Logical. Should the order of the colors be reversed?
...	Additional parameters for <code>ggplot2::discrete_scale()</code> .

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

Examples

```
library("ggplot2")

data("mtcars")
cor <- abs(cor(mtcars))
cor_melt <- data.frame(
  Var1 = rep(seq_len(nrow(cor)), times = ncol(cor)),
  Var2 = rep(seq_len(ncol(cor)), each = nrow(cor)),
  value = as.vector(cor)
)

ggplot(
  cor_melt,
  aes(x = Var1, y = Var2, fill = value)
) +
  geom_tile(colour = "black", size = 0.3) +
  theme_bw() +
  scale_fill_material("blue-grey")
```

scale_color_nejm	<i>NEJM color scales</i>
------------------	--------------------------

Description

See [pal_nejm\(\)](#) for details.

Usage

```
scale_color_nejm(palette = c("default"), alpha = 1, ...)
```

```
scale_colour_nejm(palette = c("default"), alpha = 1, ...)
```

```
scale_fill_nejm(palette = c("default"), alpha = 1, ...)
```

Arguments

palette	Palette type. Currently there is one available option: "default" (8-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
...	Additional parameters for ggplot2::discrete_scale() .

Author(s)

Nan Xiao | [<me@nanx.me>](mailto:me@nanx.me) | <https://nanx.me>

Examples

```
library("ggplot2")
data("diamonds")

ggplot(
  subset(diamonds, carat >= 2.2),
  aes(x = table, y = price, colour = cut)
) +
  geom_point(alpha = 0.7) +
  geom_smooth(method = "loess", alpha = 0.1, size = 1, span = 1) +
  theme_bw() +
  scale_color_nejm()

ggplot(
  subset(diamonds, carat > 2.2 & depth > 55 & depth < 70),
  aes(x = depth, fill = cut)
) +
  geom_histogram(colour = "black", binwidth = 1, position = "dodge") +
  theme_bw() +
  scale_fill_nejm()
```

scale_color_npg	<i>NPG journal color scales</i>
-----------------	---------------------------------

Description

See `pal_npg()` for details.

Usage

```
scale_color_npg(palette = c("nrc"), alpha = 1, ...)
```

```
scale_colour_npg(palette = c("nrc"), alpha = 1, ...)
```

```
scale_fill_npg(palette = c("nrc"), alpha = 1, ...)
```

Arguments

palette	Palette type. Currently there is one available option: "nrc" (10-color palette inspired by <i>Nature Reviews Cancer</i>).
alpha	Transparency level, a real number in (0, 1]. See alpha in <code>grDevices::rgb()</code> for details.
...	Additional parameters for <code>ggplot2::discrete_scale()</code> .

Author(s)

Nan Xiao | me@nanx.me | <https://nanx.me>

Examples

```
library("ggplot2")
data("diamonds")

ggplot(
  subset(diamonds, carat >= 2.2),
  aes(x = table, y = price, colour = cut)
) +
  geom_point(alpha = 0.7) +
  geom_smooth(method = "loess", alpha = 0.1, size = 1, span = 1) +
  theme_bw() +
  scale_color_npg()

ggplot(
  subset(diamonds, carat > 2.2 & depth > 55 & depth < 70),
  aes(x = depth, fill = cut)
) +
  geom_histogram(colour = "black", binwidth = 1, position = "dodge") +
  theme_bw() +
  scale_fill_npg()
```

`scale_color_observable`*Observable 10 color scales*

Description

See `pal_observable()` for details.

Usage

```
scale_color_observable(palette = c("observable10"), alpha = 1, ...)
```

```
scale_colour_observable(palette = c("observable10"), alpha = 1, ...)
```

```
scale_fill_observable(palette = c("observable10"), alpha = 1, ...)
```

Arguments

<code>palette</code>	Palette type. Currently there is one available option: "observable10" (10-color palette).
<code>alpha</code>	Transparency level, a real number in (0, 1]. See <code>alpha</code> in <code>grDevices::rgb()</code> for details.
<code>...</code>	Additional parameters for <code>ggplot2::discrete_scale()</code> .

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

References

Pettiross J (2023). "Crafting data colors and staying on brand." *Observable blog*. <https://observablehq.com/blog/crafting-data-colors>

Examples

```
library("ggplot2")
data("diamonds")

ggplot(
  subset(diamonds, carat >= 2.2),
  aes(x = table, y = price, colour = cut)
) +
  geom_point(alpha = 0.7) +
  geom_smooth(method = "loess", alpha = 0.1, size = 1, span = 1) +
  theme_bw() +
  scale_color_observable()

ggplot(
```

```
subset(diamonds, carat > 2.2 & depth > 55 & depth < 70),
aes(x = depth, fill = cut)
) +
geom_histogram(colour = "black", binwidth = 1, position = "dodge") +
theme_bw() +
scale_fill_observable()
```

scale_color_rickandmorty

Rick and Morty color scales

Description

See [pal_rickandmorty\(\)](#) for details.

Usage

```
scale_color_rickandmorty(palette = c("schwifty"), alpha = 1, ...)
```

```
scale_colour_rickandmorty(palette = c("schwifty"), alpha = 1, ...)
```

```
scale_fill_rickandmorty(palette = c("schwifty"), alpha = 1, ...)
```

Arguments

palette	Palette type. Currently there is one available option: "schwifty" (12-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
...	Additional parameters for ggplot2::discrete_scale() .

Author(s)

Nan Xiao | me@nanx.me | <https://nanx.me>

Examples

```
library("ggplot2")
data("diamonds")

ggplot(
  subset(diamonds, carat >= 2.2),
  aes(x = table, y = price, colour = cut)
) +
  geom_point(alpha = 0.7) +
  geom_smooth(method = "loess", alpha = 0.1, size = 1, span = 1) +
  theme_bw() +
  scale_color_rickandmorty()
```

```
ggplot(  
  subset(diamonds, carat > 2.2 & depth > 55 & depth < 70),  
  aes(x = depth, fill = cut)  
) +  
  geom_histogram(colour = "black", binwidth = 1, position = "dodge") +  
  theme_bw() +  
  scale_fill_rickandmorty()
```

scale_color_simpsons *The Simpsons color scales*

Description

See [pal_simpsons\(\)](#) for details.

Usage

```
scale_color_simpsons(palette = c("springfield"), alpha = 1, ...)
```

```
scale_colour_simpsons(palette = c("springfield"), alpha = 1, ...)
```

```
scale_fill_simpsons(palette = c("springfield"), alpha = 1, ...)
```

Arguments

palette	Palette type. Currently there is one available option: "springfield" (16-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
...	Additional parameters for ggplot2::discrete_scale() .

Author(s)

Nan Xiao | me@nanx.me | <https://nanx.me>

Examples

```
library("ggplot2")  
data("diamonds")  
  
ggplot(  
  subset(diamonds, carat >= 2.2),  
  aes(x = table, y = price, colour = cut)  
) +  
  geom_point(alpha = 0.7) +  
  geom_smooth(method = "loess", alpha = 0.1, size = 1, span = 1) +  
  theme_bw() +
```

```

scale_color_simpsons()

ggplot(
  subset(diamonds, carat > 2.2 & depth > 55 & depth < 70),
  aes(x = depth, fill = cut)
) +
  geom_histogram(colour = "black", binwidth = 1, position = "dodge") +
  theme_bw() +
  scale_fill_simpsons()

```

scale_color_startrek *Star Trek color scales*

Description

See [pal_startrek\(\)](#) for details.

Usage

```
scale_color_startrek(palette = c("uniform"), alpha = 1, ...)
```

```
scale_colour_startrek(palette = c("uniform"), alpha = 1, ...)
```

```
scale_fill_startrek(palette = c("uniform"), alpha = 1, ...)
```

Arguments

palette	Palette type. Currently there is one available option: "uniform" (7-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
...	Additional parameters for ggplot2::discrete_scale() .

Author(s)

Nan Xiao | [<me@nanx.me>](mailto:me@nanx.me) | <https://nanx.me>

Examples

```

library("ggplot2")
data("diamonds")

ggplot(
  subset(diamonds, carat >= 2.2),
  aes(x = table, y = price, colour = cut)
) +
  geom_point(alpha = 0.7) +
  geom_smooth(method = "loess", alpha = 0.1, size = 1, span = 1) +
  theme_bw() +
  scale_color_startrek()

```

```
ggplot(
  subset(diamonds, carat > 2.2 & depth > 55 & depth < 70),
  aes(x = depth, fill = cut)
) +
  geom_histogram(colour = "black", binwidth = 1, position = "dodge") +
  theme_bw() +
  scale_fill_startrek()
```

scale_color_tron	<i>Tron Legacy color scales</i>
------------------	---------------------------------

Description

See [pal_tron\(\)](#) for details.

Usage

```
scale_color_tron(palette = c("legacy"), alpha = 1, ...)
scale_colour_tron(palette = c("legacy"), alpha = 1, ...)
scale_fill_tron(palette = c("legacy"), alpha = 1, ...)
```

Arguments

palette	Palette type. Currently there is one available option: "legacy" (7-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
...	Additional parameters for ggplot2::discrete_scale() .

Author(s)

Nan Xiao | me@nanx.me | <https://nanx.me>

Examples

```
library("ggplot2")
data("diamonds")

ggplot(
  subset(diamonds, carat >= 2.2),
  aes(x = table, y = price, colour = cut)
) +
  geom_point(alpha = 0.7) +
  geom_smooth(method = "loess", alpha = 0.1, size = 1, span = 1) +
  theme_dark() +
  theme(
    panel.background = element_rect(fill = "#2D2D2D"),
```

```

    legend.key = element_rect(fill = "#2D2D2D")
  ) +
  scale_color_tron()

ggplot(
  subset(diamonds, carat > 2.2 & depth > 55 & depth < 70),
  aes(x = depth, fill = cut)
) +
  geom_histogram(colour = "black", binwidth = 1, position = "dodge") +
  theme_dark() +
  theme(
    panel.background = element_rect(fill = "#2D2D2D")
  ) +
  scale_fill_tron()

```

scale_color_tw3

Tailwind CSS color scales

Description

See [pal_tw3\(\)](#) for details.

Usage

```

scale_color_tw3(
  palette = c("slate", "gray", "zinc", "neutral", "stone", "red", "orange", "amber",
    "yellow", "lime", "green", "emerald", "teal", "cyan", "sky", "blue", "indigo",
    "violet", "purple", "fuchsia", "pink", "rose"),
  alpha = 1,
  reverse = FALSE,
  ...
)

scale_colour_tw3(
  palette = c("slate", "gray", "zinc", "neutral", "stone", "red", "orange", "amber",
    "yellow", "lime", "green", "emerald", "teal", "cyan", "sky", "blue", "indigo",
    "violet", "purple", "fuchsia", "pink", "rose"),
  alpha = 1,
  reverse = FALSE,
  ...
)

scale_fill_tw3(
  palette = c("slate", "gray", "zinc", "neutral", "stone", "red", "orange", "amber",
    "yellow", "lime", "green", "emerald", "teal", "cyan", "sky", "blue", "indigo",
    "violet", "purple", "fuchsia", "pink", "rose"),
  alpha = 1,
  reverse = FALSE,

```

```
    ...  
  )
```

Arguments

palette	Palette type. There are 22 available options: • "slate" • "gray" • "zinc" • "neutral" • "stone" • "red" • "orange" • "amber" • "yellow" • "lime" • "green" • "emerald" • "teal" • "cyan" • "sky" • "blue" • "indigo" • "violet" • "purple" • "fuchsia" • "pink" • "rose"
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
reverse	Logical. Should the order of the colors be reversed?
...	Additional parameters for ggplot2::discrete_scale() .

Author(s)

Nan Xiao | me@nanx.me | <https://nanx.me>

Examples

```
library("ggplot2")  
  
data("mtcars")  
cor <- abs(cor(mtcars))  
cor_melt <- data.frame(  
  Var1 = rep(seq_len(nrow(cor)), times = ncol(cor)),
```

```

  Var2 = rep(seq_len(ncol(cor)), each = nrow(cor)),
  value = as.vector(cor)
)

ggplot(
  cor_melt,
  aes(x = Var1, y = Var2, fill = value)
) +
  geom_tile(colour = "black", size = 0.3) +
  theme_bw() +
  scale_fill_tw3("slate")

```

scale_color_uchicago *The University of Chicago color scales*

Description

See [pal_uchicago\(\)](#) for details.

Usage

```

scale_color_uchicago(palette = c("default", "light", "dark"), alpha = 1, ...)

scale_colour_uchicago(palette = c("default", "light", "dark"), alpha = 1, ...)

scale_fill_uchicago(palette = c("default", "light", "dark"), alpha = 1, ...)

```

Arguments

palette	Palette type. There are three available options: • "default" (9-color palette); • "light" (9-color light palette); • "dark" (9-color dark palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
...	Additional parameters for ggplot2::discrete_scale() .

Author(s)

Nan Xiao | me@nanx.me | <https://nanx.me>

References

https://news.uchicago.edu/sites/default/files/attachments/_uchicago.identity.guidelines.pdf

Examples

```
library("ggplot2")
data("diamonds")

p1 <- ggplot(
  subset(diamonds, carat >= 2.2),
  aes(x = table, y = price, colour = cut)
) +
  geom_point(alpha = 0.7) +
  geom_smooth(method = "loess", alpha = 0.1, size = 1, span = 1) +
  theme_bw()

p2 <- ggplot(
  subset(diamonds, carat > 2.2 & depth > 55 & depth < 70),
  aes(x = depth, fill = cut)
) +
  geom_histogram(colour = "black", binwidth = 1, position = "dodge") +
  theme_bw()

p1 + scale_color_uchicago()
p2 + scale_fill_uchicago()

p1 + scale_color_uchicago(palette = "light")
p2 + scale_fill_uchicago(palette = "light")

p1 + scale_color_uchicago(palette = "dark")
p2 + scale_fill_uchicago(palette = "dark")
```

scale_color_ucscgb *UCSC Genome Browser color scales*

Description

See [pal_ucscgb\(\)](#) for details.

Usage

```
scale_color_ucscgb(palette = c("default"), alpha = 1, ...)

scale_colour_ucscgb(palette = c("default"), alpha = 1, ...)

scale_fill_ucscgb(palette = c("default"), alpha = 1, ...)
```

Arguments

palette	Palette type. Currently there is one available option: "default" (26-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
...	Additional parameters for ggplot2::discrete_scale() .

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

Examples

```
library("ggplot2")
data("diamonds")

ggplot(
  subset(diamonds, carat >= 2.2),
  aes(x = table, y = price, colour = cut)
) +
  geom_point(alpha = 0.7) +
  geom_smooth(method = "loess", alpha = 0.1, size = 1, span = 1) +
  theme_bw() +
  scale_color_ucscgb()

ggplot(
  subset(diamonds, carat > 2.2 & depth > 55 & depth < 70),
  aes(x = depth, fill = cut)
) +
  geom_histogram(colour = "black", binwidth = 1, position = "dodge") +
  theme_bw() +
  scale_fill_ucscgb()
```

Index

ggplot2::discrete_scale(), 26, 27, 29, 30, 32, 33, 35–42, 44–51, 53–55
grDevices::rgb(), 3–12, 14–18, 20–24, 26, 27, 29, 30, 32, 33, 35–42, 44–51, 53–55

pal_aaas, 3
pal_aaas(), 26
pal_bmj, 4
pal_bmj(), 27
pal_bs5, 4
pal_bs5(), 28
pal_cosmic, 5
pal_cosmic(), 30
pal_d3, 6
pal_d3(), 31
pal_flatui, 7
pal_flatui(), 33
pal_frontiers, 8
pal_frontiers(), 34
pal_futurama, 8
pal_futurama(), 35
pal_gsea, 9
pal_gsea(), 36
pal_igv, 10
pal_igv(), 37
pal_jama, 10
pal_jama(), 39
pal_jco, 11
pal_jco(), 40
pal_lancet, 12
pal_lancet(), 41
pal_locuszoom, 12
pal_locuszoom(), 42
pal_material, 13
pal_material(), 43
pal_nejm, 14
pal_nejm(), 45
pal_npg, 15
pal_npg(), 46

pal_observable, 15
pal_observable(), 47
pal_rickandmorty, 16
pal_rickandmorty(), 48
pal_simpsons, 17
pal_simpsons(), 49
pal_startrek, 17
pal_startrek(), 50
pal_tron, 18
pal_tron(), 51
pal_tw3, 19
pal_tw3(), 52
pal_uchicago, 20
pal_uchicago(), 54
pal_ucscgb, 21
pal_ucscgb(), 55

rgb_bs5, 21
rgb_gsea, 23
rgb_material, 23
rgb_tw3, 25

scale_color_aaas, 26
scale_color_bmj, 27
scale_color_bs5, 28
scale_color_cosmic, 30
scale_color_d3, 31
scale_color_flatui, 33
scale_color_frontiers, 34
scale_color_futurama, 35
scale_color_gsea, 36
scale_color_igv, 37
scale_color_jama, 39
scale_color_jco, 40
scale_color_lancet, 41
scale_color_locuszoom, 42
scale_color_material, 43
scale_color_nejm, 45
scale_color_npg, 46
scale_color_observable, 47

scale_color_rickandmorty, 48
 scale_color_simpsons, 49
 scale_color_startrek, 50
 scale_color_tron, 51
 scale_color_tw3, 52
 scale_color_uchicago, 54
 scale_color_ucscgb, 55
 scale_colour_aaas (scale_color_aaas), 26
 scale_colour_bmj (scale_color_bmj), 27
 scale_colour_bs5 (scale_color_bs5), 28
 scale_colour_cosmic
 (scale_color_cosmic), 30
 scale_colour_d3 (scale_color_d3), 31
 scale_colour_flatui
 (scale_color_flatui), 33
 scale_colour_frontiers
 (scale_color_frontiers), 34
 scale_colour_futurama
 (scale_color_futurama), 35
 scale_colour_gsea (scale_color_gsea), 36
 scale_colour_igv (scale_color_igv), 37
 scale_colour_jama (scale_color_jama), 39
 scale_colour_jco (scale_color_jco), 40
 scale_colour_lancet
 (scale_color_lancet), 41
 scale_colour_locuszoom
 (scale_color_locuszoom), 42
 scale_colour_material
 (scale_color_material), 43
 scale_colour_nejm (scale_color_nejm), 45
 scale_colour_npg (scale_color_npg), 46
 scale_colour_observable
 (scale_color_observable), 47
 scale_colour_rickandmorty
 (scale_color_rickandmorty), 48
 scale_colour_simpsons
 (scale_color_simpsons), 49
 scale_colour_startrek
 (scale_color_startrek), 50
 scale_colour_tron (scale_color_tron), 51
 scale_colour_tw3 (scale_color_tw3), 52
 scale_colour_uchicago
 (scale_color_uchicago), 54
 scale_colour_ucscgb
 (scale_color_ucscgb), 55
 scale_fill_aaas (scale_color_aaas), 26
 scale_fill_bmj (scale_color_bmj), 27
 scale_fill_bs5 (scale_color_bs5), 28
 scale_fill_cosmic (scale_color_cosmic),
 30
 scale_fill_d3 (scale_color_d3), 31
 scale_fill_flatui (scale_color_flatui),
 33
 scale_fill_frontiers
 (scale_color_frontiers), 34
 scale_fill_futurama
 (scale_color_futurama), 35
 scale_fill_gsea (scale_color_gsea), 36
 scale_fill_igv (scale_color_igv), 37
 scale_fill_jama (scale_color_jama), 39
 scale_fill_jco (scale_color_jco), 40
 scale_fill_lancet (scale_color_lancet),
 41
 scale_fill_locuszoom
 (scale_color_locuszoom), 42
 scale_fill_material
 (scale_color_material), 43
 scale_fill_nejm (scale_color_nejm), 45
 scale_fill_npg (scale_color_npg), 46
 scale_fill_observable
 (scale_color_observable), 47
 scale_fill_rickandmorty
 (scale_color_rickandmorty), 48
 scale_fill_simpsons
 (scale_color_simpsons), 49
 scale_fill_startrek
 (scale_color_startrek), 50
 scale_fill_tron (scale_color_tron), 51
 scale_fill_tw3 (scale_color_tw3), 52
 scale_fill_uchicago
 (scale_color_uchicago), 54
 scale_fill_ucscgb (scale_color_ucscgb),
 55