

Package ‘gwavr’

July 22, 2025

Title Get Water Attributes Visually in R

Version 0.3.2

Description Provides methods to Get Water Attributes Visually in R ('gwavr'). This allows the user to point and click on areas within the United States and get back hydrological data, e.g. flowlines, catchments, basin boundaries, comids, etc.

URL <https://github.com/joshualerickson/gwavr/>

BugReports <https://github.com/joshualerickson/gwavr/issues/>

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.1

Imports dplyr, httr, jsonlite, leaflet, leaflet.extras, nhplusTools, purrr, scales, sf, shiny, promises, miniUI, shinyWidgets, tidyr, units, utils, elevatr, whitebox, terra, rlang, htmlwidgets

Suggests spelling, knitr, rmarkdown, stringr, readr, magick, testthat (>= 3.0.0)

Language en-US

Config/testthat/edition 3

LazyData true

NeedsCompilation no

Author Joshua Erickson [aut, cre]

Maintainer Joshua Erickson <joshualerickson@gmail.com>

Depends R (>= 3.5.0)

Repository CRAN

Date/Publication 2024-12-17 18:00:01 UTC

Contents

base_map	2
basinMod	3
basinModUI	3
convert_sf_geocollection	4
df_site_new	4
get_basin_interactively	5
get_nhdplus_interactively	6
get_nldi_interactively	7
get_noaatlas	8
get_noaatlas_interactively	9
get_noaatlas_png	10
get_stream_network_interactively	11
get_usgs_dv_interactively	12
get_usgs_iv_interactively	13
nhdplusMod	15
nhdplusModUI	15
noaatlasMod	16
noaatlasModUI	16
rename_geometry	17
streamnetworkMod	17
streamnetworkModUI	18
usgsdvMod	19
usgsdvModUI	19
usgsinstMod	20
usgsinstModUI	20
Index	21

base_map	<i>Base Map</i>
----------	-----------------

Description

A generic leaflet base map used in the shiny apps.

Usage

base_map()

Value

A leaflet map with provider layers: "Esri.WorldImagery", "CartoDB.Positron", "OpenStreetMap", "CartoDB.DarkMatter", "OpenTopoMap" "Hydrography"

basinMod	<i>Shiny Module Server for basin generation</i>
----------	---

Description

Shiny Module Server for basin generation

Usage

```
basinMod(input, output, session, values, dem, threshold = 1000, map, ...)
```

Arguments

input	Shiny server function input
output	Shiny server function output
session	Shiny server function session
values	A reactive Values list to pass
dem	A raster or terra object dem.
threshold	A threshold for stream initiation. 1000 (default).
map	a background leaflet or mapview map to be used for editing. If NULL a blank mapview canvas will be provided.
...	arguments to pass to wbt_* functions.

Value

server function for Shiny module

basinModUI	<i>Shiny Module UI for basin generation</i>
------------	---

Description

A shiny Module to.

Usage

```
basinModUI(id, ...)
```

Arguments

id	character id for the the Shiny namespace
...	other arguments to leafletOutput()

Value

UI function for Shiny module

convert_sf_geocollection	<i>Convert GEOMETRYCOLLECTION to POLYGONS</i>
--------------------------	---

Description

Convert GEOMETRYCOLLECTION to POLYGONS

Usage

convert_sf_geocollection(x)

Arguments

x A sf object

Value

A converted sf object from GEOMETRYCOLLECTION to POLYGON or MULTIPOLYGON.

df_site_new	<i>Retired USGS Sites</i>
-------------	---------------------------

Description

A subset of data that has retired USGS sites and coordinates.

Usage

df_site_new

Format

df_site_new:
A data frame with 14,966 rows and 4 columns:
SiteNumber Site Number
SiteName Site Name
location.coordinates1 Longitude coordinates
location.coordinates2 Latitude coordinates ...

`get_basin_interactively`*Get Watershed Basin Interactively*

Description

This function allows the user to delineate watershed basins interactively with a shiny app. It uses the `elevatr` package to acquire the Digital Elevation Model (DEM) or user inputted DEM and `whitebox` package to delineate the basin (see details).

Usage

```
get_basin_interactively(  
  map = NULL,  
  ns = "basin-ui",  
  viewer = shiny::paneViewer(),  
  title = "Delineate Basin",  
  dem = NULL,  
  threshold = 1000,  
  ...  
)
```

Arguments

<code>map</code>	a background leaflet or mapview map to be used for editing. If <code>NULL</code> a blank mapview canvas will be provided.
<code>ns</code>	string name for the Shiny namespace to use. The <code>ns</code> is unlikely to require a change.
<code>viewer</code>	function for the viewer. See Shiny viewer . NOTE: when using <code>browserViewer(browser = getOption("browser"))</code> to open the app in the default browser, the browser window will automatically close when closing the app (by pressing "done" or "cancel") in most browsers. Firefox is an exception. See Details for instructions on how to enable this behaviour in Firefox.
<code>title</code>	string to customize the title of the UI window. The default is "Delineate Basin".
<code>dem</code>	A 'SpatRaster' object <code>dem</code> . (optional)
<code>threshold</code>	A threshold for stream initiation. 1000 (default).
<code>...</code>	other arguments to <code>leafletOutput()</code> in module and/or <code>wbt_*</code> functions.

Details

This function will throw an error if you don't draw the bounding box (rectangle) first and you didn't include your own DEM. Once the user has drawn the bounding box (or added own DEM) then you can use the marker as a pour point location.

Steps

1. Input a well-suited DEM zoom level and threshold. (skip if own DEM is inputted)
2. Draw bounding box (rectangle or polygon) (skip if own DEM is inputted).
3. Use marker to place pour point(s).
4. If necessary, change 'Cell Threshold' to change drainage density.
5. Repeat steps 1-4 if needed.
6. When finished, press 'done' and basins will be saved as a list in local environment.

In addition, this function uses both `whitebox::wbt_feature_preserving_smoothing()` and `whitebox::wbt_breach_dep` prior to running the flow direction and flow accumulation (both d8) algorithms.

Value

A sf object that contains watershed polygons the user collected during shiny session.

Note

The marker will only work for the most current stream raster. You can have multiple areas but you need to make sure that you are on the most current raster when selecting basins or the app will crash. If you add your own DEM then you don't need to draw a bounding box.

Examples

```
if(interactive()){
  basin_data <- get_basin_interactively()
}
```

```
get_nhdplus_interactively
  Get NHDPlus Interactively
```

Description

This function allows the user go get NHDPlus realizations interactively with a shiny app.

Usage

```
get_nhdplus_interactively(
  ns = "hydro-ui",
  viewer = shiny::paneViewer(),
  title = "NHDPlus",
  ...
)
```

Arguments

ns	string name for the Shiny namespace to use. The ns is unlikely to require a change.
viewer	function for the viewer. See Shiny viewer . NOTE: when using <code>browserViewer(browser = getOption("browser"))</code> to open the app in the default browser, the browser window will automatically close when closing the app (by pressing "done" or "cancel") in most browsers. Firefox is an exception. See Details for instructions on how to enable this behaviour in Firefox.
title	string to customize the title of the UI window. The default is "NHDPlus".
...	other arguments to <code>leafletOutput()</code> in module.

Value

A list of sf objects that the user collected during shiny session.

Note

The picker list has several options right now: NHDPlus Catchments, NHDPlus Flowlines, NHDPlus Waterbodies, NHDPlus Outlet, HUC 2-12, NWIS Site.

Examples

```
if(interactive()){
  nhdplus_data <- get_nhdplus_interactively()
}
```

get_nldi_interactively

Get Hydro Network-Linked Data Index (NLDI) Interactively

Description

This function uses the NLDI API to allow the user to visually select a location (point) to get numerous hydrologic realizations.

Usage

```
get_nldi_interactively()
```

Value

A list with sf objects.

Note

The picker list has three options right now: Total Basin, All Local Catchments and Only Local Catchment. Descriptions below:

- **Total Basin:** This will return the upstream tributaries (UT), upstream main (UM), basin boundary and site data above the user point.
- **All Local Catchments:** This will return the upstream tributaries (UT) and all the local NHD-PlusV2 catchments above the user point. In addition, each catchment will contain the zonal stats associated with 'CAT' in NLDI.
- **Only Local Catchment:** This will only return the catchment at the point and tributary. In addition, it will also include the zonal stat for that catchment.

Examples

```
if(interactive()){
  nldi_data <- get_nldi_interactively()
}
```

get_noaatlas	<i>Get National Oceanic and Atmospheric Administration (NOAA) Atlas 14</i>
--------------	--

Description

Get National Oceanic and Atmospheric Administration (NOAA) Atlas 14

Usage

```
get_noaatlas(point, data_type = "depth", units = "english", series = "pds")
```

Arguments

point	An sf POINT object.
data_type	A character, e.g. 'depth' or 'intensity'.
units	A character, e.g. 'english' or 'metric'.
series	A character, e.g. 'pds' or 'ams'

Value

A tibble with quantiles, lower and upper bounds.

`get_noaatlas_interactively`*Get National Oceanic and Atmospheric Administration (NOAA) Atlas 14 Interactively*

Description

This function uses the National Oceanic and Atmospheric Administration (NOAA) Atlas 14 API to allow the user to visually select a location (point) to get numerous precipitation-frequency statistics.

Usage

```
get_noaatlas_interactively(  
  map = NULL,  
  ns = "noaatlas-ui",  
  viewer = shiny::paneViewer(),  
  title = "NOAA Atlas 14"  
)
```

Arguments

map	A background leaflet or mapview map to be used for editing. If NULL a blank mapview canvas will be provided.
ns	string name for the Shiny namespace to use. The ns is unlikely to require a change.
viewer	function for the viewer. See Shiny viewer . NOTE: when using <code>browserViewer(browser = getOption("browser"))</code> to open the app in the default browser, the browser window will automatically close when closing the app (by pressing "done" or "cancel") in most browsers. Firefox is an exception. See Details for instructions on how to enable this behaviour in Firefox.
title	string to customize the title of the UI window. The default is "NOAA Atlas 14".

Value

A data.frame.

Examples

```
if(interactive()){  
  noaatlas_data <- get_noaatlas_interactively()  
}
```

get_noaatlas_png	<i>Get National Oceanic and Atmospheric Administration (NOAA) Atlas 14 Graphics</i>
------------------	---

Description

Get National Oceanic and Atmospheric Administration (NOAA) Atlas 14 Graphics

Usage

```
get_noaatlas_png(  
  point,  
  data_type = "depth",  
  units = "english",  
  series = "pds",  
  dur,  
  print = TRUE,  
  destfile = NULL  
)
```

Arguments

point	An sf POINT object.
data_type	A character, e.g. 'depth' or 'intensity'.
units	A character, e.g. 'english' or 'metric'.
series	A character, e.g. 'pds' or 'ams'
dur	A character, e.g. '10m', '4d', '24h', etc.
print	Logical, default printing of PNG in Rstudio Viewer
destfile	A character file path, default in NULL.

Value

A Portable Network Graphic printed to Rstudio Viewer.

Note

If print = FALSE, then the Graphic will be saved to tempfile or destination.

```
get_stream_network_interactively
```

Get Stream Network Interactively

Description

This function allows the user to get stream networks and watersheds interactively with a shiny app. It uses the `elevatr` package to acquire the Digital Elevation Model (DEM) or user inputted DEM and `whitebox` package to delineate the stream network and watersheds (see details).

Usage

```
get_stream_network_interactively(
  map = NULL,
  ns = "streamnetwork-ui",
  viewer = shiny::paneViewer(),
  title = "Streamnetwork",
  dem = NULL,
  threshold = 1000,
  ...
)
```

Arguments

<code>map</code>	a background leaflet or mapview map to be used for editing. If NULL a blank mapview canvas will be provided.
<code>ns</code>	string name for the Shiny namespace to use. The ns is unlikely to require a change.
<code>viewer</code>	function for the viewer. See Shiny viewer . NOTE: when using <code>browserViewer(browser = getOption("browser"))</code> to open the app in the default browser, the browser window will automatically close when closing the app (by pressing "done" or "cancel") in most browsers. Firefox is an exception. See Details for instructions on how to enable this behaviour in Firefox.
<code>title</code>	string to customize the title of the UI window. The default is "Streamnetwork".
<code>dem</code>	A raster or terra object dem. (optional)
<code>threshold</code>	A threshold for stream initiation. 1000 (default).
<code>...</code>	other arguments to <code>leafletOutput()</code> in module and/or <code>wbt_*</code> functions.

Details

This function uses the package `elevatr` to download the DEM (unless you provide your own). Once the user has drawn the bounding box or inputted DEM and selected appropriate zoom (resolution) and threshold then the app will create basins and streams.

Steps

1. Input a well-suited DEM zoom level and threshold. (skip if own DEM is inputted)
2. Draw bounding box (rectangle or polygon) (skip if own DEM is inputted).
3. Wait for layers to respond.
4. Repeat steps 1-4 if needed.
5. when finished, press 'done' and stream network and watersheds will be saved as a list in local environment with the associated flow accumulation and flow direction.

In addition, this function uses both `whitebox::wbt_feature_preserving_smoothing()` and `whitebox::wbt_breach_dep` prior to running the flow direction and flow accumulation (both d8) algorithms.

Value

A list of sf objects that the user collected during shiny session as well as flow accumulation and direction paths to tif. Each list will contain two sf objects: watersheds and streams. The streams object will also return these attributes: `tribid`, `strahler`, `slope`, `length`, `mainstem`, `FID`, `STRM_VAL`.

Note

If you add your own DEM then you don't need to draw a bounding box.

Examples

```
if(interactive()){
  streamnetwork <- get_stream_network_interactively()
}
```

`get_usgs_dv_interactively`

Get United States Geologic Survey (USGS) Daily Flow Values Interactively

Description

This function allows the user to select United States Geologic Survey (USGS) stations and get back daily flow values based on station selected. It uses the USGS Water Services to get the values as well as the USGS Sites.

Usage

```
get_usgs_dv_interactively(
  ns = "usgsdv-ui",
  viewer = shiny::paneViewer(),
  title = "Get USGS Daily Flow Values",
  ...
)
```

Arguments

ns	string name for the Shiny namespace to use. The ns is unlikely to require a change.
viewer	function for the viewer. See Shiny viewer . NOTE: when using browserViewer(browser = getOption("browser")) to open the app in the default browser, the browser window will automatically close when closing the app (by pressing "done" or "cancel") in most browsers. Firefox is an exception. See Details for instructions on how to enable this behaviour in Firefox.
title	string to customize the title of the UI window. The default is "Get USGS Instantaneous Flow Values".
...	other arguments to leafletOutput() in module.

Details**Steps**

1. Select the sites you want to retrieve.
2. When finished, press 'done' and sites daily flow values will be saved to a data.frame in local environment.

Value

A data.frame that contains flow values based on the station(s) selected during shiny session.

Note

You can select multiple stations. The information from the hover details is not included in the data.frame that is returned, e.g. rate of change, percentile description.

Examples

```
if(interactive()){
  dv_usgs <- get_usgs_dv_interactively()
}
```

get_usgs_iv_interactively

Get United States Geologic Survey (USGS) Instantaneous Flow Values Interactively

Description

This function allows the user to select United States Geologic Survey (USGS) stations and get back instantaneous flow values based on control number of days from now. It uses the USGS Water Services to get the values as well as the USGS Dashboard to get current conditions (circle markers on map).

Usage

```
get_usgs_iv_interactively(
  ns = "usgsiv-ui",
  viewer = shiny::paneViewer(),
  title = "Get USGS Instantaneous Flow Values",
  ...
)
```

Arguments

ns	string name for the Shiny namespace to use. The ns is unlikely to require a change.
viewer	function for the viewer. See Shiny viewer . NOTE: when using browserViewer(browser = getOption("browser")) to open the app in the default browser, the browser window will automatically close when closing the app (by pressing "done" or "cancel") in most browsers. Firefox is an exception. See Details for instructions on how to enable this behaviour in Firefox.
title	string to customize the title of the UI window. The default is "Get USGS Instantaneous Flow Values".
...	other arguments to leafletOutput() in module.

Details**Steps**

1. Select the sites you want to retrieve.
2. Make sure you have the right days.
3. When finished, press 'done' and sites instantaneous flow values will be saved to a data.frame in local environment.

Value

A data.frame that contains flow values based on the station(s) selected during shiny session.

Note

You can select multiple stations but the number of days from now control will take the final number when you select the done button. The information from the hover details is not included in the data.frame that is returned, e.g. rate of change, percentile description.

Examples

```
if(interactive()){  
  iv_usgs <- get_usgs_iv_interactively()  
}
```

nhdplusMod	<i>Shiny Module Server for nhdplus</i>
------------	--

Description

Shiny Module Server for nhdplus

Usage

```
nhdplusMod(input, output, session, values)
```

Arguments

input	Shiny server function input
output	Shiny server function output
session	Shiny server function session
values	A reactive Values list to pass

Value

server function for Shiny module

nhdplusModUI	<i>Shiny Module UI for nhdplus</i>
--------------	------------------------------------

Description

A shiny Module to.

Usage

```
nhdplusModUI(id, ...)
```

Arguments

id	character id for the the Shiny namespace
...	other arguments to leafletOutput()

Value

UI function for Shiny module

noaatlasMod	<i>Shiny Module Server for National Oceanic and Atmospheric Administration (NOAA) Atlas 14</i>
-------------	--

Description

Shiny Module Server for National Oceanic and Atmospheric Administration (NOAA) Atlas 14

Usage

```
noaatlasMod(input, output, session, values, map)
```

Arguments

input	Shiny server function input
output	Shiny server function output
session	Shiny server function session
values	A reactive Values list to pass
map	A background leaflet or mapview map to be used for editing. If NULL a blank mapview canvas will be provided.

Value

server function for Shiny module

noaatlasModUI	<i>Shiny Module UI for National Oceanic and Atmospheric Administration (NOAA) Atlas 14</i>
---------------	--

Description

A shiny Module to get numerous precipitation-frequency statistics.

Usage

```
noaatlasModUI(id, ...)
```

Arguments

id	character id for the the Shiny namespace
...	other arguments to leafletOutput()

Value

UI function for Shiny module

rename_geometry	<i>Rename Geometry Column</i>
-----------------	-------------------------------

Description

Rename Geometry Column

Usage

```
rename_geometry(g, name)
```

Arguments

g	A sf object
name	character.

Value

A sf object with a renamed geometry column.

Note

This function was grabbed from [stack overflow](#) from the legend spacedman.

streamnetworkMod	<i>Shiny Module Server for stream networks</i>
------------------	--

Description

Shiny Module Server for stream networks

Usage

```
streamnetworkMod(  
  input,  
  output,  
  session,  
  values,  
  dem,  
  threshold = 1000,  
  map,  
  ...  
)
```

Arguments

input	Shiny server function input
output	Shiny server function output
session	Shiny server function session
values	A reactive Values list to pass
dem	A raster or terra object dem. (optional)
threshold	A threshold for stream initiation. 1000 (default).
map	a background leaflet or mapview map to be used for editing. If NULL a blank mapview canvas will be provided.
...	arguments to pass to wbt_* functions.

Value

server function for Shiny module

streamnetworkModUI	<i>Shiny Module UI for stream network generation</i>
--------------------	--

Description

A shiny Module to.

Usage

```
streamnetworkModUI(id, ...)
```

Arguments

id	character id for the the Shiny namespace
...	other arguments to leafletOutput()

Value

UI function for Shiny module

usgsdvMod	<i>Shiny Module Server for United States Geologic Survey (USGS) daily values</i>
-----------	--

Description

Shiny Module Server for United States Geologic Survey (USGS) daily values

Usage

usgsdvMod(input, output, session, values)

Arguments

- | | |
|---------|--------------------------------|
| input | Shiny server function input |
| output | Shiny server function output |
| session | Shiny server function session |
| values | A reactive Values list to pass |

Value

server function for Shiny module

usgsdvModUI	<i>Shiny Module UI for United States Geologic Survey (USGS) daily values</i>
-------------	--

Description

A shiny Module to.

Usage

usgsdvModUI(id, ...)

Arguments

- | | |
|-----|--|
| id | character id for the the Shiny namespace |
| ... | other arguments to leafletOutput() |

Value

UI function for Shiny module

usgsinstMod	<i>Shiny Module Server for United States Geologic Survey (USGS) instantaneous values</i>
-------------	--

Description

Shiny Module Server for United States Geologic Survey (USGS) instantaneous values

Usage

```
usgsinstMod(input, output, session, values)
```

Arguments

input	Shiny server function input
output	Shiny server function output
session	Shiny server function session
values	A reactive Values list to pass

Value

server function for Shiny module

usgsinstModUI	<i>Shiny Module UI for United States Geologic Survey (USGS) instantaneous values</i>
---------------	--

Description

A shiny Module to.

Usage

```
usgsinstModUI(id, ...)
```

Arguments

id	character id for the the Shiny namespace
...	other arguments to leafletOutput()

Value

UI function for Shiny module

Index

* datasets

- df_site_new, [4](#)
- base_map, [2](#)
- basinMod, [3](#)
- basinModUI, [3](#)
- convert_sf_geocollection, [4](#)
- df_site_new, [4](#)
- get_basin_interactively, [5](#)
- get_nhdplus_interactively, [6](#)
- get_nldi_interactively, [7](#)
- get_noaatlas, [8](#)
- get_noaatlas_interactively, [9](#)
- get_noaatlas_png, [10](#)
- get_stream_network_interactively, [11](#)
- get_usgs_dv_interactively, [12](#)
- get_usgs_iv_interactively, [13](#)
- nhdplusMod, [15](#)
- nhdplusModUI, [15](#)
- noaatlasMod, [16](#)
- noaatlasModUI, [16](#)
- rename_geometry, [17](#)
- streamnetworkMod, [17](#)
- streamnetworkModUI, [18](#)
- usgsdvMod, [19](#)
- usgsdvModUI, [19](#)
- usgsinstMod, [20](#)
- usgsinstModUI, [20](#)
- viewer, [5](#), [7](#), [9](#), [11](#), [13](#), [14](#)