

Package ‘hmsidwR’

July 22, 2025

Title Health Metrics and the Spread of Infectious Diseases

Version 1.1.2

Description A collection of datasets and supporting functions accompanying Health Metrics and the Spread of Infectious Diseases by Federica Gazzelloni (2024). This package provides data for health metrics calculations, including Disability-Adjusted Life Years (DALYs), Years of Life Lost (YLLs), and Years Lived with Disability (YLDs), as well as additional tools for analyzing and visualizing health data. Federica Gazzelloni (2024) <[doi:10.5281/zenodo.10818338](https://doi.org/10.5281/zenodo.10818338)>.

License MIT + file LICENSE

URL <https://github.com/Fgazzelloni/hmsidwR>,
<https://fgazzelloni.github.io/hmsidwR/>

BugReports <https://github.com/Fgazzelloni/hmsidwR/issues>

Depends R (>= 2.10)

Imports ggplot2, gstat, purrr, showtext, sysfonts, tibble

Suggests devtools, dplyr, geomtextpath, ggthemes, httr, janitor,
knitr, lubridate, maps, pkgdown, plotly, readr, readxl,
rmarkdown, sessioninfo, sf, stats, testthat (>= 3.0.0), tidyr,
tidyverse

Config/testthat/edition 3

Encoding UTF-8

LazyData true

RoxygenNote 7.3.2

VignetteBuilder knitr

NeedsCompilation no

Author Federica Gazzelloni [aut, cre] (ORCID:
<<https://orcid.org/0000-0002-4285-611X>>)

Maintainer Federica Gazzelloni <fede.gazzelloni@gmail.com>

Repository CRAN

Date/Publication 2024-11-13 15:00:02 UTC

Contents

deaths2019	2
deaths9	3
disweights	4
g7_hmetrics	4
germany_lungc	5
getunz	6
gho_le_hale	7
gho_lifetables	7
idDALY_map_data	8
id_affected_countries	9
incprev_stroke	9
infectious_diseases	10
kbfir	11
rabies	12
sdi90_19	13
spatialdalys2021	13
string_search	14
theme_hmsid	15
Index	16

deaths2019	<i>Dataset: Health Metrics Data - Number of Deaths Due to 9 Causes in 2019</i>
------------	--

Description

A dataset containing the number of Deaths due to 9 causes in 6 regions for 2019.

Usage

```
data(deaths2019)
```

Format

A dataframe with 2754 rows and 7 variables:

The variables are as follows:

location character, France, Germany, Global, Italy, United Kingdom, United States of America

sex character, Female, Male, Both

age character, age groups from <1 to 85+ each 5 years

cause character, Alzheimer's disease and other dementias, Breast cancer, Chronic obstructive pulmonary disease, Colon and rectum cancer, Diabetes and kidney diseases, Lower respiratory infections, Road injuries, Stroke, Tracheal, bronchus, and lung cancer

val numeric, deaths number estimation

upper numeric, upper value estimation

lower numeric, lower value estimation

Source

2019 data from the [IHME](#) website

Examples

```
data(deaths2019)
head(deaths2019)
```

deaths9

Health Metrics Data - Number of Deaths Due to 9 Causes in 6 Locations for the Years 2011 and 2021.

Description

Health Metrics Data - Number of Deaths Due to 9 Causes in 6 Locations for the Years 2011 and 2021.

Usage

```
data(deaths9)
```

Format

A dataframe with 5112 rows and 7 variables:

The variables are as follows:

location character, France, Germany, Global, Italy, UK, USA

iso2 character, country code

sex character, female, male, both

age character, 5-year age groups from <5 to 85+

cause character, Alzheimer's disease and other dementias, Breast cancer, Chronic obstructive pulmonary disease, Colon and rectum cancer, Diabetes and kidney diseases, Lower respiratory infections, Road injuries, Stroke, Tracheal, bronchus, and lung cancer

year integer, years 2011 and 2019

dx numeric, deaths number estimation

Source

2021 data from the [IHME](#) website

Examples

```
data(deaths9)
head(deaths9)
```

disweights	<i>Dataset: Health Metrics Data - Disability Weights and Severity in 2019 and 2021</i>
------------	--

Description

A dataset containing the Disability Weights estimates, upper and lower values, and the Severity level for Stroke, Tuberculosis, and HIV for all countries.

Usage

disweights

Format

A dataframe with 463 rows and 9 variables:
The variables are as follows:

- sequela** character, disease sequela
- specification** character, disease specification
- cause1** character, first cause of disease - morbidity
- cause2** character, second cause of disease - morbidity
- severity** character, mild, moderate, severe, mean
- dw** numeric, disability weights estimation
- upper** numeric, upper value estimation
- lower** numeric, lower value estimation

Source

Global Burden of Disease Collaborative Network. Global Burden of Disease Study 2019 and 2021 Disability Weights. Seattle, United States of America: Institute for Health Metrics and Evaluation (IHME), 2024.

g7_hmetrics	<i>Dataset: Health Metrics Data - G7 Countries</i>
-------------	--

Description

A subset of data from the IHME GBD on Deaths, Disability-Adjusted Life Years (DALYs), Years of Life Lost (YLLs), and Years Lived with Disability (YLDs), Incidence and Prevalence, age standardized for all causes and respiratory infections and tuberculosis. For years 2010, 2019 and 2021.

Usage

```
g7_hmetrics
```

Format

A dataframe with 3402 rows and 9 variables:

The variables are as follows:

measure character, metric name

location character, country

sex character, Female, Male, Both

cause character, all causes, and respiratory infections and tuberculosis

year integer, year

val numeric, estimated values

upper numeric, estimated upper values

lower numeric, estimated lower values

Details

Locations available are Global, Canada, France, Germany, Italy, Japan, UK, and US.

Source

<https://vizhub.healthdata.org/gbd-results/>

germany_lungc

Dataset: Health Metrics Data - Germany lungcancer Deaths 2019

Description

A dataset containing deaths number due to lungcancer in Germany 2019.

Usage

```
germany_lungc
```

Format

A dataframe with 48 rows and 8 variables:

The variables are as follows:

age character, age groups from 10-14 to 85+ each 5 years

sex character, both, male, female

prevalence numeric, prevalence rate estimation due to lungcancer

prev_upper numeric, upper value estimation
prev_lower numeric, lower value estimation
dx numeric, deaths rate estimation due to lungcancer
dx_upper numeric, upper value estimation
dx_lower numeric, lower value estimation

Source

2019 data from the [IHME](#) website

getunz

Download, Unzip and Read Data: getunz

Description

Download, Unzip and Read Data: getunz

Usage

```
getunz(url)
```

Arguments

`url` A url string for a .zip file.

Value

A dataframe object from a zipped file. Particularly useful For downloading data from IHME GBD Results: "https://vizhub.healthdata.org/gbd-results/". The function takes the url, creates a temp directory, unzip the file, if more than one csv files is available, it lists the files, and reads them.

Select a dataset from the IHME GBD results and download it. You will receive an email with a url. Use the url to download the data.

Examples

```
## Not run:
# This is a dontrun example because it requires a valid url.
url <- "https://www.healthdata.org/.../some-file.zip"
getunz(url)

## End(Not run)
```

gho_le_hale	<i>Dataset: Global Health Observatory (GHO) - Countries Life Expectancy and Healthy Life Expectancy(HALE) 2000-2019</i>
-------------	---

Description

A dataset containing World countries Life Expectancy and HALE from 2000 to 2019.

Usage

gho_le_hale

Format

A dataframe with 8784 rows and 6 variables:

The variables are as follows:

indicator character, Healthy life expectancy (HALE) at age 60 (years), Healthy life expectancy (HALE) at birth (years), Life expectancy at age 60 (years), Life expectancy at birth (years)

year numeric, from 2000 to 2019

region character, 6 World regions: Africa, Americas, Eastern Mediterranean, Europe, South-East Asia, and Western Pacific

country character, 183 World countries

sex character, both, male, female

value numeric, value of the indicator

Source

WHO

gho_lifetables	<i>Dataset: Global Health Observatory (GHO) Life tables: WHO Global Life table values</i>
----------------	---

Description

A dataset containing the Global region Life tables from 2000 to 2019.

Usage

gho_lifetables

Format

A dataframe with 1995 rows and 5 variables:
The variables are as follows:

indicator character, Tx - person-years lived above age x, ex - expectation of life at age x, lx - number of people left alive at age x, nLx - person-years lived between ages x and x+n, nMx - age-specific death rate between ages x and x+n, ndx - number of people dying between ages x and x+n, nqx - probability of dying between ages x and x+n

year numeric, from 2000 to 2019

age character, from <1 to 85+ each 5 years

sex character, both, male, female

value numeric, value of the tables

Source

WHO

idDALY_map_data	Dataset: Health Metrics Data - Simple Feature Collection Average Disability-Adjusted Life Years (DALYs) per 100,000 population from 1990 to 2021
-----------------	--

Description

Dataset: Health Metrics Data - Simple Feature Collection Average Disability-Adjusted Life Years (DALYs) per 100,000 population from 1990 to 2021

Usage

idDALY_map_data

Format

A Simple feature collection with 1402 rows and 4 variables:

group double, country's polygon

location_name character, 200 Countries affected by Infectious Diseases

DALYs double, Average DALYs per 100,000 population from 1990 to 2021

geometry POLYGON

Source

2021 data from the IHME website

id_affected_countries *Dataset: Health Metrics Data - Infectious Diseases 1980-2021*

Description

A dataset containing average values for deaths rates, Disability-Adjusted Life Years (DALYs), Years of Life Lost (YLLs), and Years Lived with Disability (YLDs) due to 37 infectious diseases from 1980 to 2012 for all countries.

Usage

```
id_affected_countries
```

Format

A dataframe with 3066 rows and 6 variables:

The variables are as follows:

location_name character, list of countries

year numeric, from 1980 to 2021

DALYs numeric, DALYs for 100 000

YLLs numeric, YLLs for 100 000

YLDs numeric, YLDs for 100 000

Deaths numeric, deaths rate

Source

[IHME](#) website

incprev_stroke	<i>Global Region Health Metrics Data - Incidence and Prevalence for Stroke 2019 and 2021 Numbers - 5-year age groups from <1 to 85+ and both Location available Global</i>
----------------	---

Description

Global Region Health Metrics Data - Incidence and Prevalence for Stroke 2019 and 2021 Numbers - 5-year age groups from <1 to 85+ and both Location available Global

Usage

```
incprev_stroke
```

Format

A dataframe with 228 rows and 7 variables:

The variables are as follows:

measure character, metric name
sex character, female, male, both
age character, age groups from <1 to 85+ each 5 years
year integer, years 2019 and 2021
val numeric, estimated values
upper numeric, estimated upper values
lower numeric, estimated lower values

Source

<https://vizhub.healthdata.org/gbd-results/>

infectious_diseases	<i>Dataset: Health Metrics Data - Infectious Diseases 1980-2021</i>
---------------------	---

Description

A dataset containing Deaths rates, Disability-Adjusted Life Years (DALYs), Years of Life Lost (YLLs), and Years Lived with Disability (YLDs), Prevalence and Incidence due to Infectious Diseases from 1980 to 2021 for Lesotho, Eswatini, Malawi, Central African Republic, and Zambia.

Usage

```
infectious_diseases
```

Format

A dataframe with 7470 rows and 10 variables:

The variables are as follows:

year numeric, from 1980 to 2021
location_name character, list of countries
location_id numeric, list of countries by id
cause_name character, type of infectious disease
Deaths numeric, deaths rate
DALYs numeric, DALYs for 100 000
YLDs numeric, YLDs for 100 000
YLLs numeric, YLLs for 100 000
Prevalence numeric, prevalence rate
Incidence numeric, incidence rate
val numeric, estimated values

Source

[IHME](#) website

kbfir	<i>Kriging Best Fit: kbfir - Fit variogram models and kriging models to spatial data and select the best model based on the metrics values</i>
-------	--

Description

Kriging Best Fit: kbfir - Fit variogram models and kriging models to spatial data and select the best model based on the metrics values

Usage

```
kbfir(response, formula, data, models, initial_values)
```

Arguments

response	A character string specifying the response variable
formula	A formula object specifying the model to fit: response ~ predictors
data	A simple feature object containing the variables in the formula
models	A list of characters vector specifying the variogram models to fit
initial_values	A list of named numeric vectors specifying the initial values for the variogram models: psill, range, nugget

Value

A list with two elements: all_models and best_model

Examples

```
## Not run:
# This is a dontrun example because it requires a spatial data object(data_sf).
# Try different initial values for fitting the variogram models
initial_values <- list(
  list(psill = 1, range = 100000, nugget = 10),
  list(psill = 0.5, range = 50000, nugget = 5),
  list(psill = 2, range = 150000, nugget = 15)
)

# Set some models to fit
models <- c("Sph", "Exp", "Gau")

# Select Best: Fit variogram models and kriging models
result <- hmsidwr::kbfir(response = "response",
  formula = response ~ predictor1 + predictor2,
  data = data_sf,
```

```

models = c("Sph", "Exp", "Gau", "Mat"),
initial_values = initial_values)

result$all_models
result$best_model

## End(Not run)

```

rabies	<i>Dataset: Health Metrics Data - Rabies Deaths and DALYs from 1980 to 2021</i>
--------	---

Description

A subset of data from the IHME GBD on Disability-Adjusted Life Years (DALYs) and Deaths due to All Causes and Rabies. Locations available are Global Region and Asia.

Usage

```
rabies
```

Format

A dataframe with 296 rows and 7 variables:

The variables are as follows:

measure character, metric name

location character, country

cause character, cause

year integer, year

val numeric, estimated values

upper numeric, estimated upper values

lower numeric, estimated lower values

Source

<https://www.healthdata.org/>

sdi90_19	<i>Dataset: Health Metrics Data - Socio-Demographic Index (SDI) for 1990 and 2019</i>
----------	---

Description

A subset of data from the IHME GBD containing location, year and estimated values of the SDI for the years 1990 and 2019.

Usage

```
sdi90_19
```

Format

A dataframe with 20010 rows and 3 variables:

The variables are as follows:

location character, country

year integer, year

val numeric, estimated values

Source

<healthdata.org>

spatialdalys2021	<i>Health Metrics Data - Disability-Adjusted Life Years (DALYs) Estimations for 204 countries in 2021 with spatial information.</i>
------------------	---

Description

Health Metrics Data - Disability-Adjusted Life Years (DALYs) Estimations for 204 countries in 2021 with spatial information.

Usage

```
data(spatialdalys2021)
```

Format

A dataframe with 92862 rows and 7 variables:
The variables are as follows:

location character, France, Germany, Global, Italy, UK, USA, ...
value double, DALYs number estimation
lower_bound double, DALYs number estimation lower bound
upper_bound double, DALYs number estimation upper bound
long double, longitude
lat double, latitude
group double, polygons' group

Source

2021 data from the **IHME** website

Examples

```
data(spatialdalys2021)
head(spatialdalys2021)
```

string_search	Scan all folders and files to find a string: string_search
---------------	--

Description

Scan all folders and files to find a string: string_search

Usage

```
string_search(path = ".", pattern, string)
```

Arguments

path If NULL, the current directory is used
pattern A regular expression pattern such as '\.R\$'
string A string such as 'metric'

Value

A character vector with the names of the files that contain the string

Examples

```
string_search(path=".", "\\\.R$", "metric")

# function string_search
```

theme_hmsid	<i>Custom ggplot2 theme function</i>
-------------	--------------------------------------

Description

Custom ggplot2 theme function

Usage

```
theme_hmsid(  
  base_size,  
  text_size,  
  subtitle_size,  
  subtitle_margin,  
  plot_title_size,  
  plot_title_margin,  
  ...  
)
```

Arguments

base_size	base font size
text_size	plot text size
subtitle_size, subtitle_margin	plot subtitle size and margin
plot_title_size, plot_title_margin	plot title size and margin
...	Other arguments passed to theme_hmsid

Value

A customized theme for a ggplot object.

Examples

```
library(ggplot2)  
dat <- data.frame(  
  x = seq_along(1:5),  
  y = rnorm(n = 5, mean = 0.5, sd = 1)  
)  
dat |>  
  ggplot(aes(x = x, y = y)) +  
  geom_line() +  
  hmsidwR::theme_hmsid()
```

Index

* datasets

- deaths2019, [2](#)
- deaths9, [3](#)
- disweights, [4](#)
- g7_hmetrics, [4](#)
- germany_lungc, [5](#)
- gho_le_hale, [7](#)
- gho_lifetables, [7](#)
- id_affected_countries, [9](#)
- idDALY_map_data, [8](#)
- incprev_stroke, [9](#)
- infectious_diseases, [10](#)
- rabies, [12](#)
- sdi90_19, [13](#)
- spatialdalys2021, [13](#)

- deaths2019, [2](#)
- deaths9, [3](#)
- disweights, [4](#)

- g7_hmetrics, [4](#)
- germany_lungc, [5](#)
- getunz, [6](#)
- gho_le_hale, [7](#)
- gho_lifetables, [7](#)

- id_affected_countries, [9](#)
- idDALY_map_data, [8](#)
- incprev_stroke, [9](#)
- infectious_diseases, [10](#)

- kbfit, [11](#)

- rabies, [12](#)

- sdi90_19, [13](#)
- spatialdalys2021, [13](#)
- string_search, [14](#)

- theme_hmsid, [15](#)