

Package ‘incidence2’

July 22, 2025

Type Package

Title Compute, Handle and Plot Incidence of Dated Events

Version 2.6.3

Description Provides functions and classes to compute, handle and visualise incidence from dated events for a defined time interval. Dates can be provided in various standard formats. The class 'incidence2' is used to store computed incidence and can be easily manipulated, subsetted, and plotted.

Encoding UTF-8

License MIT + file LICENSE

URL <https://www.reconverse.org/incidence2/>,
<https://github.com/reconverse/incidence2>

BugReports <https://github.com/reconverse/incidence2/issues>

Depends grates (>= 1.3.0), R (>= 4.1.0)

Imports grDevices, data.table (>= 1.15.0), pillar, utils, stats,
tibble, tidyr, dplyr (>= 1.1.0), tidyselect, rlang, vctrs,
ympes (>= 1.3.0)

RoxygenNote 7.3.2

Suggests outbreaks, ggplot2, scales, litedown, testthat (>= 3.0.0),
ciTools, withr

VignetteBuilder litedown

Config/testthat/load-all list(export_all = FALSE, helpers = FALSE)

Config/testthat/edition 3

Config/testthat/parallel true

Config/testthat/start-first plot, incidence, bootstrap

LazyData true

NeedsCompilation no

Author Tim Taylor [aut, cre] (ORCID: <<https://orcid.org/0000-0002-8587-7113>>),
Thibaut Jombart [ctb]

Maintainer Tim Taylor <tim.taylor@hidden elephants.co.uk>

Repository CRAN
Date/Publication 2025-06-04 14:00:02 UTC

Contents

accessors	2
as	5
bootstrap_incidence	6
complete_dates	7
covidregionaldataUK	8
cumulate	9
dplyr-verbs	10
estimate_peak	12
incidence	13
keep	16
plot.incidence2	18
regroup	20
split.incidence2	21
summary.incidence2	22
vibrant	23
Index	24

accessors	<i>Access various elements of an incidence object</i>
-----------	---

Description

Access various elements of an incidence object

Usage

```
get_date_index_name(x, ...)

## Default S3 method:
get_date_index_name(x, ...)

## S3 method for class 'incidence2'
get_date_index_name(x, ...)

get_dates_name(x, ...)

get_count_variable_name(x, ...)

## Default S3 method:
get_count_variable_name(x, ...)
```

```
## S3 method for class 'incidence2'
get_count_variable_name(x, ...)

get_count_value_name(x, ...)

## Default S3 method:
get_count_value_name(x, ...)

## S3 method for class 'incidence2'
get_count_value_name(x, ...)

get_group_names(x, ...)

## Default S3 method:
get_group_names(x, ...)

## S3 method for class 'incidence2'
get_group_names(x, ...)

get_date_index(x, ...)

## Default S3 method:
get_date_index(x, ...)

## S3 method for class 'incidence2'
get_date_index(x, ...)

get_dates(x, ...)

get_count_variable(x, ...)

## Default S3 method:
get_count_variable(x, ...)

## S3 method for class 'incidence2'
get_count_variable(x, ...)

get_count_value(x, ...)

## Default S3 method:
get_count_value(x, ...)

## S3 method for class 'incidence2'
get_count_value(x, ...)

get_groups(x, ...)

## Default S3 method:
```

```
get_groups(x, ...)  
  
## S3 method for class 'incidence2'  
get_groups(x, ...)
```

Arguments

x	An R object.
...	Not currently used.

Value

- `get_date_index_name()`: The name of the `date_index` variable of `x`.
- `get_dates_name()`: Alias for `get_date_index_name()`.
- `get_count_variable_name()`: The name of the count variable of `x`.
- `get_count_value_name()`: The name of the count value of `x`.
- `get_group_names()`: The name(s) of the group variable(s) of `x`.
- `get_date_index()`: The `date_index` variable of `x`.
- `get_dates()`: Alias for `get_date_index()`.
- `get_count_variable()`: The count variable of `x`.
- `get_count_value()`: The count value of `x`.
- `get_groups()`: List of the group variable(s) of `x`.

Examples

```
if (requireNamespace("outbreaks", quietly = TRUE)) {  
  data(ebola_sim_clean, package = "outbreaks")  
  dat <- ebola_sim_clean$linelist  
  i <- incidence(  
    dat,  
    date_index = "date_of_onset",  
    groups = c("gender", "hospital")  
  )  
  get_count_variable_name(i)  
  get_group_names(i)  
  get_dates_name(i)  
}
```

as

*Coerce to and from an incidence object***Description**

Generic for coercion to an <incidence2> object.

Usage

```
as_incidence(x, ...)

## Default S3 method:
as_incidence(x, ...)

## S3 method for class 'incidence2'
as_incidence(x, ...)

## S3 method for class 'incidence2'
as.data.frame(x, row.names, optional, ...)

## S3 method for class 'incidence2'
as.data.table(x, keep.rownames, ...)

## S3 method for class 'incidence2'
as_tibble(x, ..., .rows, .name_repair, rownames)
```

Arguments

x	An R object.
...	Additional arguments to be passed to or from other methods.
row.names	Not used.
optional	Not used.
keep.rownames	Not used.
.rows	The number of rows, useful to create a 0-column tibble or just as an additional check.
.name_repair	Treatment of problematic column names: <ul style="list-style-type: none"> • "minimal": No name repair or checks, beyond basic existence, • "unique": Make sure names are unique and not empty, • "check_unique": (default value), no name repair, but check they are unique, • "universal": Make the names unique and syntactic • a function: apply custom name repair (e.g., <code>.name_repair = make.names</code> for names in the style of base R). • A purrr-style anonymous function, see rlang::as_function()

This argument is passed on as `repair` to `vctrs::vec_as_names()`. See there for more details on these terms and the strategies used to enforce them.

rownames

How to treat existing row names of a data frame or matrix:

- `NULL`: remove row names. This is the default.
- `NA`: keep row names.
- A string: the name of a new column. Existing rownames are transferred into this column and the `row.names` attribute is deleted. No name repair is applied to the new column name, even if `x` already contains a column of that name. Use `as_tibble(rownames_to_column(...))` to safeguard against this case.

Read more in [rownames](#).

Value

An object of the desired type with additional attributes dropped.

Examples

```
if (requireNamespace("outbreaks", quietly = TRUE)) {
  data(ebola_sim_clean, package = "outbreaks")
  dat <- ebola_sim_clean$linelist
  x <- incidence(dat, "date_of_onset")
  as.data.frame(dat)
  as.data.table(x)
  as_tibble(x)
}
```

bootstrap_incidence	<i>Bootstrap incidence time series</i>
---------------------	--

Description

This function can be used to bootstrap [incidence2](#) objects. Bootstrapping is done by sampling with replacement the original input dates.

Usage

```
bootstrap_incidence(x, randomise_groups = FALSE)
```

Arguments

`x` An [incidence2](#) object.

randomise_groups

bool.

Should groups be randomised as well in the resampling procedure; respective group sizes will be preserved, but this can be used to remove any group-specific temporal dynamics.

If FALSE (default), data are resampled within groups.

Details

As original data are not stored in [incidence2](#) objects, the bootstrapping is achieved by multinomial sampling of date bins weighted by their relative incidence.

Value

An [incidence2](#) object.

Author(s)

Thibaut Jombart, Tim Taylor

Examples

```
if (requireNamespace("outbreaks", quietly = TRUE)) {
  data(fluH7N9_china_2013, package = "outbreaks")
  i <- incidence(
    fluH7N9_china_2013,
    date_index = "date_of_onset",
    groups = "gender"
  )
  bootstrap_incidence(i)
}
```

complete_dates

Complete dates for all group combinations

Description

This function ensures that an incidence object has the same range of dates for each grouping. By default missing counts will be filled with 0L.

Usage

```
complete_dates(x, expand = TRUE, fill = 0L, by = 1L, allow_POSIXct = FALSE)
```

Arguments

<code>x</code>	<incidence2> object.
<code>expand</code>	logical. Should a range of dates from the minimum to maximum value of the date index also be created. If <code>expand</code> is TRUE (default) then <code>complete_dates</code> will attempt to use <code>function(x) seq(min(x), max(x), by = 1)</code> to generate a complete sequence of dates.
<code>fill</code>	numeric. The value to replace missing counts by. Defaults to 0L.
<code>by</code>	Defunct. Ignored.
<code>allow_POSIXct</code>	logical. Should this function work with POSIXct dates? Defaults to FALSE.

Value

An [incidence2](#) object.

Examples

```
x <- data.frame(
  dates = Sys.Date() + c(1,3,4),
  groups = c("grp1", "grp2", "grp1"),
  counts = 1:3
)

i <- incidence(x, date_index = "dates", groups = "groups", counts = "counts")
complete_dates(i)
```

covidregionaldataUK *Regional data for COVID-19 cases in the UK*

Description

A dataset containing the daily time-series of cases, tests, hospitalisations, and deaths for UK.

Usage

```
covidregionaldataUK
```


Format

A data frame with 6370 rows and 26 variables:

date the date that the counts were reported (YYYY-MM-DD)
region the region name
region_code the region code
cases_new new reported cases for that day
cases_total total reported cases up to and including that day
deaths_new new reported deaths for that day
deaths_total total reported deaths up to and including that day
recovered_new new reported recoveries for that day
recovered_total total reported coveries up to and including that day
hosp_new new reported hospitalisations for that day
hosp_total total reported hospitalisations up to and including that day (note this is cumulative total of new reported, not total currently in hospital).
tested_new tests for that day
tested_total total tests completed up to and including that day

Details

Extracted using the [covidregionaldata](#) package on 2021-06-03.

Source

<https://CRAN.R-project.org/package=covidregionaldata>

cumulate	<i>Compute cumulative 'incidence'</i>
----------	---------------------------------------

Description

cumulate() computes the cumulative incidence over time for an [incidence2](#) object.

Usage

```
cumulate(x)
```

Arguments

x [incidence2](#) object.

Examples

```
dat <- data.frame(
  dates = as.integer(c(0,1,2,2,3,5,7)),
  groups = factor(c(1, 2, 3, 3, 3, 3, 1))
)

i <- incidence(dat, date_index = "dates", groups = "groups")
cumulate(i)
```

dplyr-verbs

dplyr and tidyr verbs

Description

[dplyr](#) and [tidyr](#) methods that implicitly account for the inherent grouping structure of `incidence2` objects.

Usage

```
## S3 method for class 'incidence2'
mutate(
  .data,
  ...,
  .by,
  .keep = c("all", "used", "unused", "none"),
  .before = NULL,
  .after = NULL
)

## S3 method for class 'incidence2'
nest(.data, ..., .by, .key, .names_sep)

## S3 method for class 'incidence2'
summarise(.data, ..., .by, .groups)
```

Arguments

- | | |
|--------------------|---|
| <code>.data</code> | An incidence2 object. |
| <code>...</code> | Only used by <code>mutate()</code> and <code>summarise()</code> and, in which case, passed to underlying <code>dplyr</code> function. |
| <code>.by</code> | Not used as grouping structure implicit. |
| <code>.keep</code> | Control which columns from <code>.data</code> are retained in the output. Grouping columns and columns created by <code>...</code> are always kept. <ul style="list-style-type: none"> • "all" retains all columns from <code>.data</code>. This is the default. |

- "used" retains only the columns used in ... to create new columns. This is useful for checking your work, as it displays inputs and outputs side-by-side.
 - "unused" retains only the columns *not* used in ... to create new columns. This is useful if you generate new columns, but no longer need the columns used to generate them.
 - "none" doesn't retain any extra columns from .data. Only the grouping variables and columns created by ... are kept.
- .before, .after [<tidy-select>](#) Optionally, control where new columns should appear (the default is to add to the right hand side). See [relocate\(\)](#) for more details.
- .key The name of the resulting nested column. Only applicable when ... isn't specified, i.e. in the case of `df %>% nest(.by = x)`.
If NULL, then "data" will be used by default.
- .names_sep Not used.
- .groups Not used.

Value

- For `mutate()` a modified [incidence2](#) object if the necessary invariants are preserved, otherwise a [tibble](#).
- For `nest()` a nested [tibble](#) with rows corresponding to the count variable and (optionally) group columns of the input object.
- For `summarise` a [tibble](#) with rows corresponding to the underlying groupings. The columns are a combination of the grouping keys and the summary expressions provided.

See Also

[dplyr::mutate](#), [tidyr::nest](#) and [dplyr::summarise](#) for the underlying generics.

Examples

```
if (requireNamespace("outbreaks", quietly = TRUE) && requireNamespace("ggplot2", quietly = TRUE)) {
  data(ebola_sim_clean, package = "outbreaks")
  x <- subset(ebola_sim_clean$linelist, !is.na(hospital))
  dat <- incidence_(x, date_of_onset, hospital, interval = "isoweek")

  mutate(dat, ave = data.table::frollmean(count, n = 3L, align = "right")) |>
    plot(border_colour = "white", angle = 45) +
    ggplot2::geom_line(ggplot2::aes(x = date_index, y = ave))

  nest(dat)

  summarise(dat, model = list(glm(count ~ date_index, family = "poisson")))
}
```

estimate_peak	<i>Estimate the peak date of an incidence curve</i>
---------------	---

Description

This function can be used to estimate the peak of an epidemic curve using bootstrapped samples of the available data.

Usage

```
estimate_peak(x, n = 100L, alpha = 0.05, first_only = TRUE, progress = TRUE)
```

Arguments

x	An incidence2 object.
n	integer. The number of bootstrap datasets to be generated; defaults to 100. [double] vectors will be converted via <code>as.integer(n)</code> .
alpha	numeric. The type 1 error chosen for the confidence interval; defaults to 0.05.
first_only	bool. Should only the first peak (by date) be kept. Defaults to TRUE.
progress	bool. Should a progress bar be displayed (default = TRUE)

Details

Input dates are resampled with replacement to form bootstrapped datasets; the peak is reported for each, resulting in a distribution of peak times. When there are ties for peak incidence, only the first date is reported.

Note that the bootstrapping approach used for estimating the peak time makes the following assumptions:

- the total number of event is known (no uncertainty on total incidence)
- dates with no events (zero incidence) will never be in bootstrapped datasets
- the reporting is assumed to be constant over time, i.e. every case is equally likely to be reported

Value

A data frame with the the following columns:

- `observed_date`: the date of peak incidence of the original dataset.
- `observed_count`: the peak incidence of the original dataset.
- `estimated`: the median peak time of the bootstrap datasets.
- `lower_ci/upper_ci`: the confidence interval based on bootstrap datasets.
- `bootstrap_peaks`: a nested tibble containing the the peak times of the bootstrapped datasets.

Author(s)

Thibaut Jombart and Tim Taylor, with inputs on caveats from Michael Höhle.

See Also

[bootstrap_incidence\(\)](#) for the bootstrapping underlying this approach and [keep_peaks\(\)](#) to get the peaks in a single [incidence2](#) object.

Examples

```
if (requireNamespace("outbreaks", quietly = TRUE)) {

  # load data and create incidence
  data(fluH7N9_china_2013, package = "outbreaks")
  i <- incidence(fluH7N9_china_2013, date_index = "date_of_onset")

  # find 95% CI for peak time using bootstrap
  estimate_peak(i)
}
```

incidence

Compute the incidence of events

Description

`incidence()` calculates the *incidence* of different events across specified time periods and groupings. `incidence_()` does the same but with support for [tidy-select](#) semantics in some of its arguments.

Usage

```
incidence(
  x,
  date_index,
  groups = NULL,
  counts = NULL,
  count_names_to = "count_variable",
  count_values_to = "count",
  date_names_to = "date_index",
  rm_na_dates = TRUE,
  interval = NULL,
  offset = NULL,
  complete_dates = FALSE,
  fill = 0L,
  ...
)
```

```

incidence_(
  x,
  date_index,
  groups = NULL,
  counts = NULL,
  count_names_to = "count_variable",
  count_values_to = "count",
  date_names_to = "date_index",
  rm_na_dates = TRUE,
  interval = NULL,
  offset = NULL,
  complete_dates = FALSE,
  ...
)

```

Arguments

<code>x</code>	A data frame object representing a linelist or pre-aggregated dataset.
<code>date_index</code>	character for <code>incidence()</code> or tidy-select for <code>incidence_()</code> . The time index(es) of the given data. This should be the name(s) corresponding to the desired date column(s) in <code>x</code> . A named vector can be used for convenient relabelling of the resultant output. Multiple indices only make sense when <code>x</code> is a linelist.
<code>groups</code>	character for <code>incidence()</code> or tidy-select for <code>incidence_()</code> . An optional vector giving the names of the groups of observations for which incidence should be grouped. A named vector can be used for convenient relabelling of the resultant output.
<code>counts</code>	character for <code>incidence()</code> or tidy-select for <code>incidence_()</code> . The count variables of the given data. If <code>NULL</code> (default) the data is taken to be a linelist of individual observations. A named vector can be used for convenient relabelling of the resultant output.
<code>count_names_to</code>	character. The column to create which will store the counts column names provided that counts is not <code>NULL</code> .
<code>count_values_to</code>	character. The name of the column to store the resultant count values in.
<code>date_names_to</code>	character. The name of the column to store the date variables in.
<code>rm_na_dates</code>	bool. Should NA dates be removed prior to aggregation?
<code>interval</code>	An optional scalar integer or string indicating the (fixed) size of the desired time interval you wish to use for computing the incidence. Defaults to <code>NULL</code> in which case the <code>date_index</code> columns are left unchanged.

Numeric values are coerced to integer and treated as a number of days to group.
Text strings can be one of:

- * day or daily
- * week(s) or weekly
- * epiweek(s)
- * isoweek(s)
- * month(s) or monthly
- * yearmonth(s)
- * quarter(s) or quarterly
- * yearquarter(s)
- * year(s) or yearly

More details can be found in the "Interval specification" section.

offset

Only applicable when interval is not NULL.

An optional scalar integer or date indicating the value you wish to start counting periods from relative to the Unix Epoch:

- Default value of NULL corresponds to 0L.
- For other integer values this is stored scaled by n (`offset <- as.integer(offset) %% n`).
- For date values this is first converted to an integer offset (`offset <- floor(as.numeric(offset))`) and then scaled via n as above.

complete_dates bool.

Should the resulting object have the same range of dates for each grouping.

Missing counts will be filled with 0L unless the fill argument is provided (and this value will take precedence).

Will attempt to use `function(x) seq(min(x), max(x), by = 1)` on the resultant date_index column to generate a complete sequence of dates.

More flexible completion is possible by using the `complete_dates()` function.

fill

numeric.

Only applicable when `complete_dates = TRUE`.

The value to replace missing counts caused by completing dates.

If unset then will default to 0L.

...

Not currently used.

Details

incidence2 objects are a sub class of data frame with some additional invariants. That is, an incidence2 object must:

- have one column representing the date index (this does not need to be a date object but must have an inherent ordering over time);
- have one column representing the count variable (i.e. what is being counted) and one variable representing the associated count;
- have zero or more columns representing groups;
- not have duplicated rows with regards to the date and group variables.

Value

A `tibble` with subclass `incidence2`.

Interval specification

Where `interval` is specified, `incidence()`, predominantly uses the `grates` package to generate appropriate date groupings. The grouping used depends on the value of `interval`. This can be specified as either an integer value or a string corresponding to one of the classes:

- integer values: `<grates_period>` object, grouped by the specified number of days.
- day, daily: `<Date>` objects.
- week(s), weekly, isoweek: `<grates_isoweek>` objects.
- epiweek(s): `<grates_epiweek>` objects.
- month(s), monthly, yearmonth: `<grates_yearmonth>` objects.
- quarter(s), quarterly, yearquarter: `<grates_yearquarter>` objects.
- year(s) and yearly: `<grates_year>` objects.

For "day" or "daily" interval, we provide a thin wrapper around `as.Date()` that ensures the underlying data are whole numbers and that time zones are respected. Note that additional arguments are not forwarded to `as.Date()` so for greater flexibility users are advised to modifying your input prior to calling `incidence()`.

See Also

`browseVignettes("grates")` for more details on the grate object classes.

Examples

```
if (requireNamespace("outbreaks", quietly = TRUE)) {
  data(ebola_sim_clean, package = "outbreaks")
  dat <- ebola_sim_clean$linelist
  incidence(dat, "date_of_onset")
  incidence_(dat, date_of_onset)
  incidence(dat, "date_of_onset", groups = c("gender", "hospital"))
  incidence_(dat, date_of_onset, groups = c(gender, hospital))
}
```

keep

Keep first, last and peak occurrences

Description

`keep_first()` and `keep_last()` keep the first and last `n` rows to occur for each grouping when in ascending date order. `keep_peaks()` keeps the rows with the maximum count value for each group. `first_peak()` is a convenience wrapper around `keep_peaks()` with the `first_only` argument set to `TRUE`.

Usage

```
keep_first(x, n, complete_dates = TRUE, ...)  
keep_last(x, n, complete_dates = TRUE, ...)  
keep_peaks(x, complete_dates = TRUE, first_only = FALSE, ...)  
first_peak(x, complete_dates = TRUE, ...)
```

Arguments

x	incidence2 object.
n	integer. Number of entries to keep. double vectors will be converted via <code>as.integer(n)</code> .
complete_dates	bool. Should <code>complete_dates()</code> be called on the data prior to keeping the first entries. Defaults to TRUE.
...	Other arguments passed to <code>complete_dates()</code> .
first_only	bool. Should only the first peak (by date) be kept. Defaults to TRUE.

Value

[incidence2](#) object with the chosen entries.

Examples

```
if (requireNamespace("outbreaks", quietly = TRUE)) {  
  data(ebola_sim_clean, package = "outbreaks")  
  dat <- ebola_sim_clean$linelist  
  inci <- incidence(dat, "date_of_onset")  
  keep_first(inci, 3)  
  keep_last(inci, 3)  
}
```

plot.incidence2	<i>Plot an incidence object</i>
-----------------	---------------------------------

Description

plot() can be used to provide a bar plot of an incidence object. Due to the complexities with automating plotting it is some what experimental in nature and it may be better to use ggplot2 directly.

Usage

```
## S3 method for class 'incidence2'
plot(
  x,
  y,
  width = 1,
  colour_palette = vibrant,
  border_colour = NA,
  na_colour = "grey",
  alpha = 0.7,
  fill = NULL,
  legend = c("right", "left", "bottom", "top", "none"),
  title = NULL,
  angle = 0,
  size = NULL,
  nrow = NULL,
  n_breaks = 6L,
  show_cases = FALSE,
  ...
)
```

Arguments

x	incidence2 object.
y	Not used. Required for compatibility with the plot() generic.
width	numeric. Value between 0 and 1 indicating the relative size of the bars to the interval. Default 1.
colour_palette	function. The color palette to be used for the different count variables. Defaults to vibrant (see ?palettes).
border_colour	character. The color to be used for the borders of the bars. Use NA (default) for invisible borders.

na_colour	character. The colour to plot NA values in graphs. Defaults to grey.
alpha	numeric. The alpha level for color transparency, with 1 being fully opaque and 0 fully transparent Defaults to 0.7.
fill	character. Which variable to colour plots by. Must be a group or count variable and will mean that variable is not used for facetting. If NULL no distinction if made for plot colours.
legend	character. Position of legend in plot. Only applied if fill is not NULL. One of "right" (default), "left", "bottom", "top" or "none".
title	character. Optional title for the graph.
angle	numeric. Rotation angle for text.
size	numeric. text size in pts.
nrow	integer. Number of rows used for facetting if there are group variables present and just one count in the incidence object. Numeric values are coerced to integer via <code>as.integer()</code> .
n_breaks	integer. Approximate number of breaks calculated using <code>scales::breaks_pretty()</code> . Numeric values are coerced to integer via <code>as.integer()</code> . Default 6L.
show_cases	logical. if TRUE, then each observation will be shown individually in a square format. Normally only used for outbreaks with a small number of cases. Defaults to FALSE.
...	Not currently used.

Details

- Faceting will occur automatically if either grouping variables or multiple counts are present.
- If there are multiple count variables, each count will occupy a different row of the resulting plot.
- Utilises ggplot2 so this must be installed to use.

Value

- A `ggplot2::ggplot()` object.

Examples

```
if (requireNamespace("outbreaks", quietly = TRUE) && requireNamespace("ggplot2", quietly = TRUE)) {
  data(ebola_sim_clean, package = "outbreaks")
  dat <- ebola_sim_clean$linelist

  inci <- incidence(dat, date_index = "date_of_onset", groups = "hospital")
  plot(inci, angle = 45)

  inci2 <- regroup(inci)
  plot(inci2)
}
```

regroup

Regroup 'incidence' objects

Description

This function regroups an [incidence2](#) object across the specified groups. The resulting [incidence2](#) object will contains counts aggregated over the specified groups. The only difference between `regroup()` and `regroup_()` is that the latter is built on top of [tidy-select](#) semantics for the group input.

Usage

```
regroup(x, groups = NULL)
```

```
regroup_(x, groups = NULL)
```

Arguments

<code>x</code>	<incidence2> object.
<code>groups</code>	character for <code>regroup()</code> or tidy-select for <code>regroup_()</code> . The groups to sum over. If NULL (default) then the function returns the corresponding object with no groupings.

Examples

```

if (requireNamespace("outbreaks", quietly = TRUE)) {
  data(ebola_sim_clean, package = "outbreaks")
  dat <- ebola_sim_clean$linelist
  i <- incidence(
    dat,
    date_index = "date_of_onset",
    groups = c("gender", "hospital")
  )
  regroup(i)
  regroup_(i)
  regroup(i, "hospital")
  regroup_(i, hospital)
}

```

split.incidence2	<i>Divide an incidence2 object in to it's implicit groupings</i>
------------------	--

Description

Split divides and [incidence2](#) object in to it's underlying groupings (count variable and optionally groups).

Usage

```

## S3 method for class 'incidence2'
split(x, f, drop, ...)

```

Arguments

x	An incidence2 object.
f	Not used. Present only for generic compatibility.
drop	Not used. Present only for generic compatibility.
...	Not used. Present only for generic compatibility.

Value

A list of tibbles contained the split data. This list also has a "key" attribute which is a tibble with rows corresponding to the grouping of each split.

See Also

[vctrs::vec_split\(\)](#) on which `split.incidence2()` is built.

Examples

```
if (requireNamespace("outbreaks", quietly = TRUE)) {  
  data(ebola_sim_clean, package = "outbreaks")  
  ebola_sim_clean$linelist |>  
    subset(!is.na(hospital)) |>  
    incidence_(date_of_onset, hospital, interval = "isoweek") |>  
    split()  
}
```

summary.incidence2	<i>Summary of an incidence object</i>
--------------------	---------------------------------------

Description

Summary of an incidence object

Usage

```
## S3 method for class 'incidence2'  
summary(object, ...)
```

Arguments

object	An incidence2 object.
...	Not used.

Value

object (invisibly).

Examples

```
data(ebola_sim_clean, package = "outbreaks")  
dat <- ebola_sim_clean$linelist  
inci <- incidence(dat, "date_of_onset", groups = c("gender", "hospital"))  
summary(inci)
```

`vibrant`*Color palettes used in incidence*

Description

These functions are color palettes used in incidence. The palettes come from <https://personal.sron.nl/~pault/#sec:qualitative> and exclude grey, which is reserved for missing data.

Usage`vibrant(n)``muted(n)`**Arguments**

`n` integer.
Number of colours.
double vectors will be converted via `as.integer(n)`.

Examples

```
vibrant(5)
muted(10)
```

Index

- * **datasets**
 - covidregionaldataUK, 8
 - <Date>, 16
 - <grates_epiweek>, 16
 - <grates_isoweeek>, 16
 - <grates_period>, 16
 - <grates_year>, 16
 - <grates_yearmonth>, 16
 - <grates_yearquarter>, 16
- accessors, 2
- as, 5
- as_incidence(as), 5
- as_tibble.incidence2(as), 5
- bootstrap_incidence, 6
- bootstrap_incidence(), 13
- complete_dates, 7
- covidregionaldataUK, 8
- cumulate, 9
- dplyr, 10
- dplyr-verbs, 10
- dplyr::mutate, 11
- dplyr::summarise, 11
- estimate_peak, 12
- estimate_peaks(estimate_peak), 12
- first_peak(keep), 16
- get_count_value(accessors), 2
- get_count_value_name(accessors), 2
- get_count_variable(accessors), 2
- get_count_variable_name(accessors), 2
- get_date_index(accessors), 2
- get_date_index_name(accessors), 2
- get_dates(accessors), 2
- get_dates_name(accessors), 2
- get_group_names(accessors), 2
- get_groups(accessors), 2
- incidence, 13
- incidence2, 6–13, 17, 18, 20–22
- incidence_(incidence), 13
- keep, 16
- keep_first(keep), 16
- keep_last(keep), 16
- keep_peaks(keep), 16
- keep_peaks(), 13
- mutate.incidence2(dplyr-verbs), 10
- muted(vibrant), 23
- nest.incidence2(dplyr-verbs), 10
- palettes(vibrant), 23
- plot.incidence2, 18
- regroup, 20
- regroup_(regroup), 20
- relocate(), 11
- rlang::as_function(), 5
- rownames, 6
- split.incidence2, 21
- summarise.incidence2(dplyr-verbs), 10
- summary.incidence2, 22
- tibble, 11, 16
- tidy-select, 13, 14, 20
- tidyr, 10
- tidyr::nest, 11
- vctrs::vec_as_names(), 6
- vctrs::vec_split(), 21
- vibrant, 23