

Package ‘kisopenapi’

July 22, 2025

Title Korea Investment & Securities (KIS) Open Trading API

Version 0.0.2

Description API Wrapper to use Korea Investment & Securities (KIS) trading system that provides various financial services like stock price check, orders and balance check
<<https://apiportal.koreainvestment.com/>>.

License MIT + file LICENSE

Encoding UTF-8

Depends R (>= 3.5.0)

Imports cli (>= 3.3.0), data.table (>= 1.14.2), httr2 (>= 0.2.2),
jsonlite (>= 1.8.0)

RoxygenNote 7.2.3

NeedsCompilation no

Author Seokhoon Joo [aut, cre]

Maintainer Seokhoon Joo <seokhoonj@gmail.com>

Repository CRAN

Date/Publication 2024-01-24 15:30:02 UTC

Contents

change_trading_env	2
get_balance	2
get_buyable_cash	3
get_current_price	4
get_orders	4
get_order_history	5
get_stock_history	6
get_stock_history_by_ohlcv	6
get_stock_investor	7
get_stock_quotes	8
kis_order	8
kis_revise_cancel	9

print_acnt_prdt_cd	11
print_app_key	12
print_app_secret	12
print_base_url	13
print_cano	13
print_trading_env	14
set_auth	14
set_trading_env	15

Index	17
--------------	-----------

change_trading_env	<i>change trading environment</i>
--------------------	-----------------------------------

Description

if you wrote live trading and paper trading environment variables both in your .Renvirom file, you can change trading environment.

Usage

```
change_trading_env()
```

Value

"live" or "paper" string value

Examples

```
## Not run: change_trading_environment()
```

get_balance	<i>get account balance</i>
-------------	----------------------------

Description

Get your account balance.

Usage

```
get_balance(prdt_code, rt_cash_flag = FALSE)
```

Arguments

- prdt_code A string specifying account product code
- rt_cash_flag A boolean specifying total deposit or not

Value

balance data.frame

Examples

```
## get account balance
## Not run:
# detail
get_balance(rt_cash_flag = FALSE)
# total deposit
get_balance(rt_cash_flag = TRUE)
## End(Not run)
```

<code>get_buyable_cash</code>	<i>get buyable cash</i>
-------------------------------	-------------------------

Description

Get buyable amount of cash of the account

Usage

```
get_buyable_cash(prdt_code)
```

Arguments

`prdt_code` A string specifying account product code

Value

A numeric specifying buyable cash

Examples

```
# get buyable cash
## Not run:
get_buyable_cash()

## End(Not run)
```

get_current_price	<i>get current price</i>
-------------------	--------------------------

Description

Get current stock price.

Usage

```
get_current_price(stock_code)
```

Arguments

stock_code	A string specifying stock number (stock code)
------------	---

Value

current stock price

Examples

```
# get current price
## Not run:
get_current_price("005930")

## End(Not run)
```

get_orders	<i>get orders</i>
------------	-------------------

Description

Return a list of orders that can be revised or canceled.

Usage

```
get_orders()
```

Value

data.frame of orders

Examples

```
# get a list of orders
## Not run:
get_orders()

## End(Not run)
```

get_order_history	<i>get order history</i>
-------------------	--------------------------

Description

Get order history from start date to end date.

Usage

```
get_order_history(sdt, edt, prdt_code, zip_flag = TRUE)
```

Arguments

sdt	A string specifying start date "YYYYMMDD"
edt	A string specifying end date "YYYYMMDD"
prdt_code	A string specifying account product code
zip_flag	A boolean specifying choosing important columns

Value

Order history data frame

Examples

```
# get order history
## Not run:
get_order_history("20")

## End(Not run)
```

get_stock_history	<i>get stock history</i>
-------------------	--------------------------

Description

Get stock history.

Usage

```
get_stock_history(stock_code, unit = c("D", "W", "M"))
```

Arguments

stock_code	A string specifying stock code
unit	A string specifying day, week, month

Value

stock history data frame

Examples

```
# get stock history
## Not run:
get_stock_history("005930")

## End(Not run)
```

get_stock_history_by_ohlcv	<i>get stock history by ohlcv</i>
----------------------------	-----------------------------------

Description

Get stock history by open, high, low, close, volume.

Usage

```
get_stock_history_by_ohlcv(stock_code, unit = "D", add_var = FALSE)
```

Arguments

stock_code	A string specifying stock code
unit	A string specifying day, week, month
add_var	A boolean adding volatility and percentage change

Value

stock history by ohlcv data frame

Examples

```
# get stock history
## Not run:
get_stock_history_by_ohlcv("005930")

## End(Not run)
```

<code>get_stock_investor</code>	<i>get stock investor</i>
---------------------------------	---------------------------

Description

Get stock investor data using KIS API.

Usage

```
get_stock_investor(stock_code)
```

Arguments

`stock_code` A string specifying stock code

Value

stock investor data frame

Examples

```
# get stock investor
## Not run:
get_stock_investor("005930")

## End(Not run)
```

get_stock_quotes	<i>get stock quotes</i>
------------------	-------------------------

Description

Get current stock qutoes.

Usage

```
get_stock_quotes(stock_code)
```

Arguments

stock_code	A string specifying stock code
------------	--------------------------------

Value

current stock quotes data frame

Examples

```
# get stock quotes
## Not run:
get_stock_quotes("005930")

## End(Not run)
```

kis_order	<i>KIS order</i>
-----------	------------------

Description

Order stocks.

Usage

```
kis_order(
  stock_code,
  order_qty,
  order_price,
  prdt_code,
  order_type = "00",
  buy_flag = TRUE
)
```

```
kis_buy(stock_code, order_qty, order_price, prdt_code, order_type = "00")
```

```
kis_sell(stock_code, order_qty, order_price, prdt_code, order_type = "00")
```


Arguments

stock_code	A string specifying stock code
order_qty	A numeric or string specifying order quantity
order_price	A numeric or string specifying order price
prdt_code	A string specifying account product code
order_type	A string specifying order type
buy_flag	A boolean specifying flag

Value

A list contains rt_cd: return code, msg_cd: message code, msg1: message
An order result

Examples

```
## Not run:
## buy
kis_buy(
  stock_code = "stock code",
  order_qty = "your order quantity",
  order_price = "your order price"
)
## sell
kis_sell(
  stock_code = "stock code",
  order_qty = "your order quantity",
  order_price = "your order price"
)

## End(Not run)
```

kis_revise_cancel	<i>KIS revise and cancel orders</i>
-------------------	-------------------------------------

Description

Revise and cancel orders.

Usage

```
kis_revise_cancel(
  order_no,
  order_branch,
  order_qty,
  order_price,
```

```

    prdt_code,
    order_dv = "00",
    cncl_dv = c("01", "02"),
    qty_all_yn = c("Y", "N")
)

kis_revise(
  order_no,
  order_branch,
  order_qty,
  order_price,
  prdt_code,
  order_dv = "00",
  cncl_dv = "01",
  qty_all_yn = c("Y", "N")
)

kis_cancel(
  order_no,
  order_branch,
  order_qty,
  order_price,
  prdt_code,
  order_dv = "00",
  cncl_dv = "02",
  qty_all_yn = c("Y", "N")
)

kis_cancel_all()

```

Arguments

<code>order_no</code>	A string specifying order number
<code>order_branch</code>	A string specifying branch code
<code>order_qty</code>	A numeric or string specifying order quantity
<code>order_price</code>	A numeric or string specifying order price
<code>prdt_code</code>	A string specifying account product code
<code>order_dv</code>	A string specifying limit order(00) or market order(01)
<code>cncl_dv</code>	A string specifying revise(01) or cancel(02)
<code>qty_all_yn</code>	A string specifying total order quantity or not

Value

A list contains `rt_cd`: return code, `msg_cd`: message code, `msg1`: message response

Examples

```
## revise
## Not run:
kis_revise(
  order_no = "your order number",
  order_branch = "your order branch", order_qty = "your order quantity",
  order_price = "your order price"
)

## End(Not run)
## cancel
## Not run:
kis_cancel(
  order_no = "your order number",
  order_branch = "your order branch", order_qty = "your order quantity",
  order_price = "your order price"
)

## End(Not run)
## cancel all
## Not run:
kis_cancel_all()

## End(Not run)
```

<code>print_acnt_prdt_cd</code>	<i>print account product code</i>
---------------------------------	-----------------------------------

Description

Print your account product code in the current trading environemnt. it changes depending on the trading environment.

Usage

```
print_acnt_prdt_cd()
```

Value

account product code

Examples

```
## Not run: print_acnt_prdt_cd()
```

print_app_key	<i>print app key</i>
---------------	----------------------

Description

Print your app key in the current trading environemnt. it changes depending on the trading environment.

Usage

```
print_app_key()
```

Value

app key

Examples

```
## Not run: print_app_key()
```

print_app_secret	<i>print app secret</i>
------------------	-------------------------

Description

Print your app secret in the current trading environemnt. it changes depending on the trading environment.

Usage

```
print_app_secret()
```

Value

app secret

Examples

```
## Not run: print_app_secret()
```

print_base_url	<i>print base url</i>
----------------	-----------------------

Description

Print your base url in the current trading environemnt. it changes depending on the trading environment.

Usage

```
print_base_url()
```

Value

base url of current trading environment

Examples

```
## Not run: print_base_url()
```

print_cano	<i>print account number</i>
------------	-----------------------------

Description

Print your account number in the current trading environemnt. it changes depending on the trading environment.

Usage

```
print_cano()
```

Value

account number

Examples

```
## Not run: print_cano()
```

print_trading_env	<i>print trading environment</i>
-------------------	----------------------------------

Description

Print the current trading environment.

Usage

```
print_trading_env()
```

Value

"live" or "paper" string value

Examples

```
## Not run: print_trading_env()
```

set_auth	<i>set access token</i>
----------	-------------------------

Description

Set access token (hash key) using kis app key and kis app secret.

Usage

```
set_auth()
```

```
get_auth()
```

```
print_auth()
```

Value

An access token (access token is stored in environment variable at the same time)

Examples

```
# set authentication
## Not run:
set_auth()

## End(Not run)
```

set_trading_env	<i>Set KIS account number, account product code, app key and app secret</i>
-----------------	---

Description

Save environment variables for the current session. To set it permanently, please add the following line to your .Renviron file:

Usage

```
set_trading_env(cano, acnt_prdt_cd, app_key, app_secret, is_paper = FALSE)
```

Arguments

cano	A string specifying KIS common account number
acnt_prdt_cd	A string specifying KIS account product code
app_key	A string specifying KIS app key
app_secret	A string specifying KIS app secret
is_paper	A string specifying paper trading or not, default FALSE

Value

No return value, called to set environment variables

For live trading

```
KIS_CANO="YOUR ACCOUNT NUMBER" (first 8 digits of your account)
KIS_ACNT_PRDT_CD="01" (last 2 digits of your account)
KIS_APP_KEY="YOUR APP KEY"
KIS_APP_SECRET="YOUR APP SECRET"
```

For paper trading

```
KIS_PAPER_CANO="YOUR PAPER ACCOUNT NUMBER" (first 8 digits of your paper account)
KIS_PAPER_ACNT_PRDT_CD="01" (last 2 digits of your paper account)
KIS_PAPER_APP_KEY="YOUR PAPER APP KEY"
KIS_PAPER_APP_SECRET="YOUR PAPER APP SECRET"
```

Examples

```
## Set app key for the current session
## Not run:
## Set trading environment only for the current session
set_trading_env(
  cano = "your account number",
```

```
    acct_prdt_no = "your account product code",
    app_key = "your app key",
    app_secret = "your app secret"
)
## Check environment variables
print_cano()
print_acnt_prdt_cd()
print_app_key()
print_app_secret()
## End(Not run)
```


Index

`change_trading_env`, [2](#)

`get_auth` (`set_auth`), [14](#)
`get_balance`, [2](#)
`get_buyable_cash`, [3](#)
`get_current_price`, [4](#)
`get_order_history`, [5](#)
`get_orders`, [4](#)
`get_stock_history`, [6](#)
`get_stock_history_by_ohlcv`, [6](#)
`get_stock_investor`, [7](#)
`get_stock_quotes`, [8](#)

`kis_buy` (`kis_order`), [8](#)
`kis_cancel` (`kis_revise_cancel`), [9](#)
`kis_cancel_all` (`kis_revise_cancel`), [9](#)
`kis_order`, [8](#)
`kis_revise` (`kis_revise_cancel`), [9](#)
`kis_revise_cancel`, [9](#)
`kis_sell` (`kis_order`), [8](#)

`print_acnt_prdt_cd`, [11](#)
`print_app_key`, [12](#)
`print_app_secret`, [12](#)
`print_auth` (`set_auth`), [14](#)
`print_base_url`, [13](#)
`print_cano`, [13](#)
`print_trading_env`, [14](#)

`set_auth`, [14](#)
`set_trading_env`, [15](#)