

Package ‘ksNN’

July 22, 2025

Encoding UTF-8

Type Package

Title K* Nearest Neighbors Algorithm

Version 0.1.2

Description Prediction with k* nearest neighbor algorithm
based on a publication by Anava and Levy (2016) <[doi:10.48550/arXiv.1701.07266](https://doi.org/10.48550/arXiv.1701.07266)>.

License GPL (>= 2)

Author Kei Nakagawa [aut, cre] (ORCID:
<<https://orcid.org/0000-0001-5046-8128>>),
Shingo Sashida [aut]

Maintainer Kei Nakagawa <kei.nak.0315@gmail.com>

LazyData TRUE

Imports Rcpp

Depends R(>= 3.0.2)

LinkingTo Rcpp(>= 0.10.6)

RoxygenNote 6.1.1

NeedsCompilation yes

Repository CRAN

Date/Publication 2019-04-11 12:02:37 UTC

Contents

ksNN	2
rcpp_ksNN	3
Index	5

ksNN	<i>This function calculates the prediction value of k* nearest neighbors algorithm.</i>
------	---

Description

This function calculates the prediction value of k* nearest neighbors algorithm.

Usage

```
ksNN(Label, Distance, L_C = 1)
```

Arguments

Label	vectors of the known labels of the samples.
Distance	vectors of the distance between the target sample we want to predict and the other samples.
L_C	parameter of k* nearest neighbors algorithm.

Value

the prediction value(pred) and the weight of the samples(alpha).

Note

This algorithm is based on Anava and Levy(2017).

Examples

```
library(ksNN)
set.seed(1)

#make the nonlinear regression problem
X<-runif(100)
Y<-X^6-3*X^3+5*X^2+2

suffle<-order(rnorm(length(X)))
X<-X[suffle]
Y<-Y[suffle]

test_X<-X[1]
test_Y<-Y[1]

train_X<-X[-1]
train_Y<-Y[-1]

Label<-train_Y
Distance<-sqrt((test_X-train_X)^2)
```

```

pred_ksNN<-ksNN(Label,Distance,L_C=1)

#the predicted value with k*NN
pred_ksNN$pred

#the 'true' value
test_Y

```

rcpp_ksNN	<i>This function calculates the prediction value of k* nearest neighbors algorithm.</i>
-----------	---

Description

This function calculates the prediction value of k* nearest neighbors algorithm.

Usage

```
rcpp_ksNN(Label, Distance, L_C = 1)
```

Arguments

Label	vectors of the known labels of the samples.
Distance	vectors of the distance between the target sample we want to predict and the other samples.
L_C	parameter of k* nearest neighbors algorithm.

Value

the prediction value(pred) and the weight of the samples(alpha).

Note

This algorithm is based on Anava and Levy(2017).

Examples

```

library(ksNN)
set.seed(1)

#make the nonlinear regression problem
X<-runif(100)
Y<-X^6-3*X^3+5*X^2+2

suffle<-order(rnorm(length(X)))
X<-X[suffle]
Y<-Y[suffle]

test_X<-X[1]

```

```
test_Y<-Y[1]

train_X<-X[-1]
train_Y<-Y[-1]

Label<-train_Y
Distance<-sqrt((test_X-train_X)^2)

pred_ksNN<-rcpp_ksNN(Label,Distance,L_C=1)

#the predicted value with k*NN
pred_ksNN$pred

#the 'true' value
test_Y
```

Index

ksNN, [2](#)

rcpp_ksNN, [3](#)