# Package 'leem'

July 22, 2025

**Type** Package

**Title** Laboratory of Teaching to Statistics and Mathematics

**Version** 0.2.0

**Description** An educational package for teaching statistics and mathematics in both primary and higher education. The objective is to assist in the teaching/learning process, both for student study planning and teacher teaching strategies. The leem package aims to provide, in a simple yet in-depth manner, knowledge of statistics and mathematics to anyone who wants to study these areas of knowledge.

**Depends** R (>= 4.1.0)

**Imports** tcltk, tkRplotR, tkrplot, manipulate, crayon, grDevices, graphics, utils, diagram, methods

**License** GPL (>= 2)

**URL** https://bendeivide.github.io/project/leem/, https://github.com/bendeivide/leem

**BugReports** https://github.com/bendeivide/leem/issues

**RoxygenNote** 7.3.2

**NeedsCompilation** no

**Author** Ben Deivide [aut, cre] (ORCID: <https://orcid.org/0000-0001-7019-8794>), Andre Barboza [aut] (ORCID: <https://orcid.org/0000-0003-1190-3822>), Alexandre Celestino [ctb] (ORCID: <https://orcid.org/0000-0003-3475-3863>), Juliane Nassarala [ctb]

**Maintainer** Ben Deivide <ben.deivide@gmail.com>

**Repository** CRAN

**Date/Publication** 2025-03-08 21:50:02 UTC

## Contents

amplitude . . . . . 3
apf . . . . . 3

barplot.leem . . . 4
boxplot.leem . . . 6
cdfd . . . 7
cv . . . 8
Gumbel_distribution . . . 9
hist.leem . . . 10
insert . . . 11
insert.leem . . . 12
leem . . . 14
madev . . . 14
mean.leem . . . 15
medev . . . 16
median.leem . . . 17
mfreq . . . 18
mpos . . . 19
mstde . . . 20
new_leem . . . 21
ogive . . . 21
P . . . 24
piechart . . . 25
polyfreq . . . 26
polyfreq.leem . . . 26
probnormal . . . 28
propofnormal . . . 29
Q . . . 30
Regions_of_probability . . . 31
sdev . . . 33
showboxplot . . . 34
showcdf . . . 34
showci . . . 35
showkur . . . 35
showpar . . . 36
showskew . . . 37
showtabnormal . . . 37
skewness . . . 38
stickchart . . . 39
tabfreq . . . 40
tabfreq.leem . . . 41
variance . . . 43

**Index** **44**

amplitude *Amplitude*

## Description

Compute the sample range

## Usage

```
amplitude(x, rounding = 2, na.rm = FALSE, details = FALSE, grouped = TRUE)
```

## Arguments

| | |
|---|---|
| x | R object (list) of class leem. Use new_leem() function. |
| rounding | Numerical object. Rounds the values in its first argument to the specified number of decimal places (default 2). |
| na.rm | a logical value indicating whether NA values should be stripped before the computation proceeds. |
| details | Logical object. Details of data (default FALSE). |
| grouped | Logical object. Determines whether the measure of position result will be based on grouped data or not (default TRUE). |

## Examples

```
# Example 1: Poisson data
set.seed(10)
rpois(30, 2.5) |>
  new_leem() |>
  amplitude(grouped = FALSE)
# Example 2: Normal data
rnorm(50, 100, 2.5) |>
  new_leem(variable = 2) |>
  amplitude()
```

apf *Plot of probability function of any discrete variable*

## Description

Help in building the plot of the probability function of any discrete variable

## Usage

```
apf(x, p, main = NULL, xlab = NULL, ylab = NULL)
```

### Arguments

| | |
|---|---|
| x | numeric vector of values of $X$. See **Details**. |
| p | numeric vector of $p_X(x)$. See **Details**. |
| main | main title for the plot. |
| xlab | a label for the x axis. |
| ylab | a label for the y axis. |

### Details

Consider the $X$ distribution:

| | | | | | |
|---|---|---|---|---|---|
| $p_X(x)$: | 0.23 | 0.27 | 0.30 | 0.12 | 0.08 |
| $x$: | 1 | 2 | 3 | 4 | 5 |

where $p_X(x)$ and $x$ are probability function and values of $X$. See *Example 1*.

### Value

The output is plot of distribution function. See *Example 1*.

### Examples

```
# Example 1
x <- 1:5
p <- c(0.23, 0.27,0.30, 0.12, 0.08)
apf(x, p)
```

---

## barplot.leem *Barplot graph*

---

### Description

Class method leem for generic barplot

### Usage

```
## S3 method for class 'leem'
barplot(
  height,
  freq = "a",
  bg = TRUE,
  main = NULL,
  xlab = NULL,
  ylab = NULL,
  grids = grid(col = "white"),
```

```
  bgcol = "gray",
  bgborder = NA,
  barcol = "yellow",
  barborder = "gray",
  posx1 = 0,
  posx2 = 0,
  xang = 0,
  labels = NULL,
  ...
)
```

## Arguments

| | |
|---|---|
| height | R object (list) of class leem. Use new_leem() function. |
| freq | Character argument. Type of frequency with options: "a" (absolute and default), "r" relative and "p" percentage. |
| bg | Logical argument. Default is TRUE, it displays the background, and bg = FALSE otherwise. |
| main | Character argument. Insert the plot title. The default is NULL. |
| xlab | Character argument. Insert the title of the x-axis graphic label. The default is NULL. |
| ylab | Character argument. Insert the title of the y-axis graphic label. The default is NULL. |
| grids | Insert grids to plot. The default is grid(col = "white"). |
| bgcol | Insert the background color. This argument is only valid when bg = TRUE. The default is bgcol="gray". |
| bgborder | Character argument. Insert the background border color. This argument is only valid when bg = TRUE. The default is bgborder = NA. |
| barcol | Character argument. Insert the barplot color. The default is barcol = "yellow". This argument is only valid when bars = TRUE. |
| barborder | Numeric argument. Insert the barplot border color. This argument is only valid when bars = TRUE. The default is barborder = "gray". |
| posx1 | Numeric argument.Distance of the labels (horizontal) in relation to the x axis. |
| posx2 | Numeric argument.Distance of the labels (vertical) in relation to the x axis. |
| xang | Numeric argument.Angle of the labels in relation to the x axis |
| labels | Character argument. Labels name vector. |
| ... | further arguments passed to or from other methods. |

## Examples

```
library(graphics)
# Example 1 - Simple example
library(leem)
rep(1:5, 5:1) |>
  new_leem() |>
```

```
  barplot()
# Example 2 - Color bars
rep(1:5, 5:1) |>
  new_leem() |>
  barplot(barcol = heat.colors(5))
# Example 3 - Ordered data
library(leem)
school <- rep(c("high", "university", "basic"), 3:5)
sample(school, 30, TRUE) |>
 new_leem() |>
 tabfreq(ordered = c("basic", "high", "university")) |>
 barplot(xang = 15, posx2 = -0.2)
# Example 4 - Coerced to histogram
rnorm(100, 10, 2) |>
  new_leem(variable = 2) |>
  barplot(barcol = heat.colors(10))
```

---

`boxplot.leem` *Box plot*

---

## Description

Produce box-and-whisker plot(s) of leem class object and computes the necessary values for the development of the plot.

## Usage

```
## S3 method for class 'leem'
boxplot(
  x,
  type = "rawdata",
  details = FALSE,
  horizontal = FALSE,
  coef = 1.5,
  main = NULL,
  xlab = NULL,
  ylab = NULL,
  col = rgb(0, 175, 239, maxColorValue = 255),
  ...
)
```

## Arguments

| | |
|---|---|
| `x` | R object (list) of class leem. Use `new_leem()` function. |
| `type` | character argument. Default is `rawdata`. If `type = "classes"`, the function returns a boxplot plot for each set of data grouped of classes of `x` object. |
| `details` | Logical argument. Default is `FALSE`, otherwise, in addition to the plot, the measurements necessary for the development of the plot will be displayed on the console. |

| | |
|---|---|
| horizontal | Logical argument indicating if the boxplots should be horizontal; default FALSE means vertical boxes. |
| coef | this determines how far the plot whiskers extend out from the box. If coef is positive, the whiskers extend to the most extreme data point which is no more than coef times the interquartile range from the box. A value of zero causes the whiskers to extend to the data extremes. |
| main | Title name. Defaults is NULL. |
| xlab | a label for the x axis. Defaults is NULL. |
| ylab | a label for the y axis. Defaults is NULL. |
| col | Character vector. Default col = rgb(0, 175, 239, maxColorValue = 255). |
| ... | further arguments passed to or from other methods. |

## Examples

```
library(leem)
# Example 1
x <- rnorm(30, 100, 2) |>
  new_leem(variable = 2) |>
  tabfreq()
boxplot(x, details = TRUE)
# Example 2
boxplot(x, type = "classes")
```

---

# cdfd *Plot of cumulative distribution function of any discrete variable*

---

## Description

Help in building the plot of the cumulative distribution function of any discrete variable

## Usage

```
cdfd(x, fda, main = NULL, xlab = NULL, ylab = NULL)
```

## Arguments

| | |
|---|---|
| x | numeric vector of values of $X$. See **Details**. |
| fda | numeric vector of $F_X(x)$. See **Details**. |
| main | main title for the plot. |
| xlab | a label for the x axis. |
| ylab | a label for the y axis. |

## Details

Consider the $X$ distribution:

$$\begin{array}{rccccc} p_X(x): & 0.23 & 0.27 & 0.30 & 0.12 & 0.08 \\ x: & 1 & 2 & 3 & 4 & 5 \end{array}$$

where $p_X(x)$ and $x$ are probability function and values of $X$. Consider also the $X$ distribution function:

$$F_X(x) = \begin{cases} 0, & \text{if } x < 1; \\ 0.23, & \text{if } 1 \leq x < 2; \\ 0.50, & \text{if } 2 \leq x < 3; \\ 0.80, & \text{if } 3 \leq x < 4; \\ 0.92, & \text{if } 4 \leq x < 5; \\ 1.00 & \text{if } x \geq 5. \end{cases}$$

This way, the `cdfd` function needs to consider only the vectors `x <- 1:5` and `fda <- c(0.23, 0.50, 0.80, 0.92, 1)`, that is, only the equality conditions for $x$. See *Example 1*.

## Value

The output is plot of distribution function. See *Example 1*.

## Examples

```
# Example 1
x <- 1:5
fda <- c(0.23, 0.5, 0.8, 0.92, 1)
cdfd(x, fda)
```

---

`cv` *Coefficient of variation*

---

## Description

Compute the sample coeffient of variation

## Usage

```
cv(x, rounding = 2, na.rm = FALSE, details = FALSE, grouped = TRUE)
```

### Arguments

| | |
|---|---|
| x | R object (list) of class leem. Use new_leem() function. |
| rounding | Numerical object. Rounds the values in its first argument to the specified number of decimal places (default 2). |
| na.rm | a logical value indicating whether NA values should be stripped before the computation proceeds. |
| details | Logical object. Details of data (default FALSE). |
| grouped | Logical object. Determines whether the measure of position result will be based on grouped data or not (default TRUE). |

### Examples

```
# Example 1: Poisson data
rpois(30, 2.5) |>
  new_leem() |>
  cv()
# Example 2: Normal data
rnorm(50, 100, 2.5) |>
  new_leem(variable = 2) |>
  cv(grouped = FALSE)
```

---

## Gumbel_distribution *The Gumbel Distribution*

---

### Description

Density, distribution function, quantile function and random generation for the normal distribution with parameters: location and scale

### Usage

```
dgumbel(x, location, scale)

pgumbel(q, location, scale, lower.tail = TRUE)

qgumbel(p, location = 0, scale = 1, lower.tail = TRUE)
```

### Arguments

| | |
|---|---|
| x, q | vector of quantiles. |
| location | numerical. It represents location parameter. See Details. |
| scale | numerical. It represents scale parameter. See Details. |
| lower.tail | logical; if TRUE (default), probabilities are $P[X \leq x]$ otherwise, $P[X > x]$. |
| p | vector of probabilities. |

## Details

The CDF of Gumbel distribution is:

$$F(x;\mu,\beta) = e^{-e^{-(x-\mu)/\beta}}, \quad \mu \in \mathbf{R}, \beta > 0,$$

where $\mu$ is location parameter (`location`) and $\beta$ is scale parameter (`scale`). The PDF of Gumbel distribution is:

$$\frac{1}{\beta} e^{-(z+e^{-z})},$$

where $z = \frac{x-\mu}{\beta}$. The quantile is:

$$\mu - \beta \ln(-\ln(p)), \quad 0 < p < 1.$$

## Examples

```
# PDF
dgumbel(1, 0, 1)
# CDF
pgumbel(1, 0, 1)
# Quantile
qgumbel(0.2, 0, 1)
```

---

`hist.leem` *Histogram graph*

---

## Description

Class method leem for generic hist

## Usage

```
## S3 method for class 'leem'
hist(
  x,
  freq = "a",
  bg = TRUE,
  main = NULL,
  xlab = NULL,
  ylab = NULL,
  grids = grid(col = "white"),
  bgcol = "gray",
  bgborder = NA,
  barcol = "yellow",
  barborder = "gray",
  ...
)
```

### Arguments

| | |
|---|---|
| x | R object (list) of class leem. Use new_leem() function. |
| freq | Character argument. Type of frequency with options: "a" (absolute and default), "r" relative and "p" percentage. |
| bg | Logical argument. Default is TRUE, it displays the background, and bg = FALSE otherwise. |
| main | Insert the plot title. The default is NULL. |
| xlab | Insert the title of the x-axis graphic label. The default is NULL. |
| ylab | Insert the title of the y-axis graphic label. The default is NULL. |
| grids | Insert grids to plot. The default is grid(col = "white"). |
| bgcol | Insert the background color. This argument is only valid when bg = TRUE. The default is bgcol="gray". |
| bgborder | Insert the background border color. This argument is only valid when bg = TRUE. The default is bgborder = NA. |
| barcol | Insert the barplot color. The default is barcol = "yellow". This argument is only valid when bars = TRUE. |
| barborder | Numeric argument. Insert the barplot border color. This argument is only valid when bars = TRUE. The default is barborder = "gray". |
| ... | further arguments passed to or from other methods. |

### Examples

```
# Example 1
library(leem)
rnorm(36, 100, 50) |> new_leem(variable = "continuous") |> tabfreq() |> hist()

# Example 2
library(leem)
school <- rep(c("high", "university", "basic"), 3:5)
sample(school, 30, TRUE) |>
 new_leem() |>
 tabfreq(ordered = c("basic", "high", "university"))
```

---

## insert *Insert measures of position in plot*

---

### Description

Generic function that allows inserting measures of position in plots

### Usage

```
insert(x, ...)
```

### Arguments

| | |
|---|---|
| x | R object (list) of class leem. Use new_leem() function. |
| ... | further arguments passed to or from other methods. |

### Examples

```
# Example 1
library(leem)
set.seed(10)
rnorm(36, 100, 50) |>
 new_leem(variable = "continuous") |>
 tabfreq() |>
 hist() |>
 insert(
  lcol = "black",
  tcol = "purple",
  acol = "brown",
  parrow = 0.6,
  larrow = 0.6,
  ptext = 0.4,
  side = "left",
  lwd = 2,
  lwdarrow = 4
 )
```

---

## insert.leem *Insert measures of position in plot*

---

### Description

Method of insert function

### Usage

```
## S3 method for class 'leem'
insert(
  x,
  type = "mean",
  lty = 1,
  lcol = "black",
  tcol = lcol,
  acol = lcol,
  parrow = 0.5,
  larrow = 0.6,
  ptext = 0.06,
  side = "right",
  lwd = 2,
  lwdarrow = lwd,
```

```
  ...
)
```

## Arguments

| | |
|---|---|
| x | R object (list) of class leem. Use new_leem() function. |
| type | Type of measure of position. The default is type = "mean". Other options: "median", "mode" or "all". |
| lty | Line type. The default is lty = 1. |
| lcol | Vertical line color type. The default is lpcol = "black". This argument must be the same length as the type argument. |
| tcol | Text color type. The default is tcol = lcol. |
| acol | Arrow color type. The default is acol = lcol. |
| parrow | Text and arrow height. The default is parrow = 0.5. This argument must be the same length as the type argument. |
| larrow | Text and arrow length. The default is larrow = 0.6. |
| ptext | Distance between lines of text. The default is ptext = 0.06. |
| side | Side to insert the text. The default is side = "right". This argument must be the same length as the type argument. |
| lwd | numeric argument. The vertical line width. The default is lwd = 2. |
| lwdarrow | numeric argument. The arrow width. The default is lwdarrow = lwd. |
| ... | further arguments passed to or from other methods. |

## Value

No return value. This function adds elements to an existing plot.

## Examples

```
# Example 1
library(leem)
set.seed(10)
rnorm(36, 100, 50) |>
 new_leem(variable = "continuous") |>
 tabfreq() |>
 hist() |>
 insert(
  lcol = "black",
  tcol = "purple",
  acol = "brown",
  parrow = 0.6,
  larrow = 0.6,
  ptext = 0.4,
  side = "left",
  lwd = 2,
  lwdarrow = 4
 )
```

## leem *Graphical User Interface for leem package*

### Description

leem A Graphical User Interface (GUI) for the leem package

### Usage

```
leem(gui = TRUE)
```

### Arguments

| | |
|---|---|
| gui | Logical argument, TRUE or FALSE. The default is TRUE |

### Value

leem presents GUI with various problems for the teaching of statistics and mathematics. The idea is to use this package to learn these subjects without necessarily programming in R

### Examples

```
# Loading package
library(leem)
if (interactive()) {
  leem(gui = FALSE)
}
```

## madev *Mean absolute deviation*

### Description

Compute the sample mean absolute deviation

### Usage

```
madev(x, rounding = 2, na.rm = FALSE, details = FALSE, grouped = TRUE)
```

### Arguments

| | |
|---|---|
| x | R object (list) of class leem. Use new_leem() function. |
| rounding | Numerical object. Rounds the values in its first argument to the specified number of decimal places (default 2). |
| na.rm | a logical value indicating whether NA values should be stripped before the computation proceeds. |
| details | Logical object. Details of data (default FALSE). |
| grouped | Logical object. Determines whether the measure of position result will be based on grouped data or not (default TRUE). |

### Examples

```
# Example 1: Poisson data
set.seed(10)
rpois(30, 2.5) |>
  new_leem() |>
  madev(grouped = FALSE)
# Example 2: Normal data
rnorm(50, 100, 2.5) |>
  new_leem(variable = 2) |>
  madev()
```

---

## mean.leem *Arithmetic mean Class method leem for the generic mean function*

---

### Description

Arithmetic mean Class method leem for the generic mean function

### Usage

```
## S3 method for class 'leem'
mean(
  x,
  trim = 0,
  na.rm = FALSE,
  rounding = 2,
  grouped = TRUE,
  details = FALSE,
  ...
)
```

### Arguments

| | |
|---|---|
| x | R object (list) of class leem. Use new_leem() function. Complex vectors are allowed for trim = 0, only. |
| trim | The fraction (0 to 0.5) of observations to be trimmed from each end of x before the mean is computed. Values of trim outside that range are taken as the nearest endpoint. |
| na.rm | a logical value indicating whether NA values should be stripped before the computation proceeds. |
| rounding | Numerical object. Rounds the values in its first argument to the specified number of decimal places (default 2). |
| grouped | Logical object. Determines whether the measure of position result will be based on grouped data or not (default TRUE). |
| details | Logical object. Details of data (default FALSE). |
| ... | further arguments passed to or from other methods. |

### Examples

```
# Example 1
set.seed(10)
x <- rnorm(36, 100, 50)
y <- rbinom(36, 10, 0.8)
y |> new_leem(variable = "discrete") |> tabfreq() |> mean()
x |> new_leem(variable = "continuous") |> tabfreq() |> mean()
```

---

## medev *Median absolute deviation*

---

### Description

Compute the sample median absolute deviation

### Usage

```
medev(x, rounding = 2, na.rm = FALSE, details = FALSE, grouped = TRUE)
```

### Arguments

| | |
|---|---|
| x | R object (list) of class leem. Use new_leem() function. |
| rounding | Numerical object. Rounds the values in its first argument to the specified number of decimal places (default 2). |
| na.rm | a logical value indicating whether NA values should be stripped before the computation proceeds. |
| details | Logical object. Details of data (default FALSE). |
| grouped | Logical object. Determines whether the measure of position result will be based on grouped data or not (default TRUE). |

## Examples

```
# Example 1: Poisson data
set.seed(10)
rpois(30, 2.5) |>
  new_leem() |>
  medev(grouped = FALSE)
# Example 2: Normal data
rnorm(50, 100, 2.5) |>
  new_leem(variable = 2) |>
  medev()
```

---

`median.leem` *Median value*

---

## Description

Class method leem for the generic median function

## Usage

```
## S3 method for class 'leem'
median(x, na.rm = FALSE, rounding = 2, grouped = TRUE, details = FALSE, ...)
```

## Arguments

| | |
|---|---|
| `x` | R object (list) of class leem. Use `new_leem()` function. |
| `na.rm` | a logical value indicating whether `NA` values should be stripped before the computation proceeds. |
| `rounding` | Numerical object. Rounds the values in its first argument to the specified number of decimal places (default `2`). |
| `grouped` | Logical object. Determines whether the measure of position result will be based on grouped data or not (default `TRUE`). |
| `details` | Logical object. Details of data (default `FALSE`). |
| `...` | further arguments passed to or from other methods. |

## Examples

```
library(leem)
library(stats)
# Examples
rnorm(36, 100, 50) |> new_leem(variable = 2) |> tabfreq() |> median()
```

mfreq *Mode value*

## Description

Compute the sample mode.

## Usage

```
mfreq(x, na.rm = FALSE, rounding = 2, grouped = TRUE, details = FALSE)
```

## Arguments

| | |
|---|---|
| x | R object (list) of class leem. Use new_leem() function. |
| na.rm | a logical value indicating whether NA values should be stripped before the computation proceeds. |
| rounding | Numerical object. Rounds the values in its first argument to the specified number of decimal places (default 2). |
| grouped | Logical object. Determines whether the measure of position result will be based on grouped data or not (default TRUE). |
| details | Logical object. Details of data (default FALSE). |

## Examples

```
library(leem)
# set.seed(10)
x <- rnorm(36, 100, 50)
set.seed(10)
y <- rbinom(36, 10, 0.8)
w <- rep(letters[1:4], 1:4)
(tab1 <- y |> new_leem(variable = "discrete") |> tabfreq())
(tab2 <- x |> new_leem(variable = "continuous") |> tabfreq())
(tab3 <- w |> new_leem(variable = "discrete") |> tabfreq())
y |> new_leem(variable = "discrete") |> tabfreq() |> mfreq()
x |> new_leem(variable = "continuous") |> tabfreq() |> mfreq()
w |> new_leem(variable = "discrete") |> tabfreq() |> mfreq()
```

mpos *Measures of position*

## Description

Compute all measures of position

## Usage

```
mpos(
  x,
  trim = 0,
  na.rm = FALSE,
  rounding = 2,
  grouped = TRUE,
  details = FALSE,
  ...
)
```

## Arguments

| | |
|---|---|
| x | R object (list) of class leem. Use new_leem() function. Complex vectors are allowed for trim = 0, only. |
| trim | The fraction (0 to 0.5) of observations to be trimmed from each end of x before the mean is computed. Values of trim outside that range are taken as the nearest endpoint. |
| na.rm | a logical value indicating whether NA values should be stripped before the computation proceeds. |
| rounding | Numerical object. Rounds the values in its first argument to the specified number of decimal places (default 2). |
| grouped | Logical object. Determines whether the measure of position result will be based on grouped data or not (default TRUE). |
| details | Logical object. Details of data (default FALSE). |
| ... | further arguments passed to or from other methods. |

## Details

The measures of position are: average, median and mode.

## Examples

```
# Example 1: Poisson data
rpois(30, 2.5) |>
  new_leem() |>
  mpos()
# Example 2: Normal data
```

```
rnorm(50, 100, 2.5) |>
  new_leem(variable = 2) |>
  mpos(grouped = FALSE)
```

---

`mstde` *Mean standard error*

---

## Description

Compute the sample mean standard error

## Usage

```
mstde(x, rounding = 2, na.rm = FALSE, details = FALSE, grouped = TRUE)
```

## Arguments

| | |
|---|---|
| `x` | R object (list) of class leem. Use `new_leem()` function. |
| `rounding` | Numerical object. Rounds the values in its first argument to the specified number of decimal places (default `2`). |
| `na.rm` | a logical value indicating whether `NA` values should be stripped before the computation proceeds. |
| `details` | Logical object. Details of data (default `FALSE`). |
| `grouped` | Logical object. Determines whether the measure of position result will be based on grouped data or not (default `TRUE`). |

## Examples

```
# Example 1: Poisson data
set.seed(10)
rpois(30, 2.5) |>
  new_leem() |>
  mstde(rounding = 4)
# Example 2: Normal data
rnorm(50, 100, 2.5) |>
  new_leem(variable = 2) |>
  mstde(grouped = FALSE)
```

## new_leem *Constructor of object of leem class*

### Description

Function that assists other functions of leem package

### Usage

```
new_leem(x, variable = "discrete")
```

### Arguments

| | |
|---|---|
| x | R object (vector as data structure). |
| variable | Type of data. If discrete (default), the data are categorical (numeric or not). If continuous, the data are numeric. |

### Value

The variable argument also allows using variable = 1 for categorical variable and variable = 2 for continuous variable.

### Examples

```
# Example 1
library(leem)
x <- rbinom(36, 10, 0.6)
new_leem(x, variable = 1)

# Example 2 (Pipe operator)
rnorm(36, 100, 4) |> new_leem(variable = 2)
```

## ogive *Ogive chart*

### Description

Generic function that plots the culmulative frequency curve.

## Usage

```
ogive(x, ...)

## S3 method for class 'leem'
ogive(
  x,
  freq = "a",
  decreasing = FALSE,
  both = FALSE,
  bars = FALSE,
  histogram = FALSE,
  bg = TRUE,
  main = NULL,
  xlab = NULL,
  ylab = NULL,
  grids = grid(col = "white"),
  bgcol = "gray",
  bgborder = NA,
  barcol = "yellow",
  histcol = barcol,
  barborder = "gray",
  histborder = barborder,
  type = "b",
  lpcol = "black",
  lwd = 2,
  pch = 19,
  lty = 2,
  ...
)
```

## Arguments

| | |
|---|---|
| x | R object (list) of class leem. Use new_leem() function. |
| ... | further arguments passed to or from other methods. |
| freq | Character argument. Type of frequency with options: "a" (absolute and default), "r" relative and "p" percentage. |
| decreasing | Logical argument. Default is FALSE. If decreasing = FALSE, it represents the "ogive larger than", if decreasing = TRUE, it represents the "ogive less than". |
| both | Logical argument. Default is FALSE. If both = TRUE, both o will be plotted. If both = FALSE otherside. |
| bars | Logical argument. Default is FALSE. If bars = TRUE, the bars of the accumulated frequency will be inserted to plot, according to the decreasing argument. If bars = FALSE otherside. |
| histogram | Logical argument. Default is FALSE. If histogram = TRUE, the histogram will be inserted to plot. |
| bg | Logical argument. Default is TRUE, it displays the background, and bg = FALSE otherwise. |

| | |
|---|---|
| main | Insert the plot title. The default is NULL. |
| xlab | Insert the title of the x-axis graphic label. The default is NULL. |
| ylab | Insert the title of the y-axis graphic label. The default is NULL. |
| grids | Insert grids to plot. The default is grid(col = "white"). |
| bgcol | Insert the background color. This argument is only valid when bg = TRUE. The default is bgcol="gray". |
| bgborder | Insert the background border color. This argument is only valid when bg = TRUE. The default is bgborder = NA. |
| barcol | Insert the barplot color. The default is barcol = "yellow". This argument is only valid when bars = TRUE. |
| histcol | Insert the histogram color. The default is histcol = barcol. This argument is only valid when histogram = TRUE. |
| barborder | Insert the barplot border color. This argument is only valid when bars = TRUE. The default is barborder = "gray". |
| histborder | Insert the histogram border color. This argument is only valid when histogram = TRUE. The default is histborder = barborder. |
| type | Type of plot. The default is type = "b", i.e., line and points. See graphical parameter for details. |
| lpcol | Type of line color. The default is lpcol = "black". |
| lwd | numeric argument. The line width. The default is lwd = 2. |
| pch | Type of point. The default is pch = 19. |
| lty | Type of line. The default is lty = 2. |

## Value

Ogive plot.

## Examples

```
library(leem)
# Example 1 - Both ogives
rnorm(36, 100, 50) |> new_leem(variable = 2) |> tabfreq() |> ogive(both = TRUE)

# Example 2 - Insert barplot
rnorm(36, 100, 50) |> new_leem(variable = 2) |> tabfreq() |> ogive(both = TRUE, bars = TRUE)
# Example 3 - Insert histogram
rnorm(36, 100, 50) |> new_leem(variable = 2) |> tabfreq() |> ogive(both = TRUE, histogram = TRUE)
```

P *Cumulative distribution function*

## Description

P Compute the cumulative distribution function for multiple distributions

## Usage

```
P(
  q,
  dist = "normal",
  lower.tail = TRUE,
  rounding = 5,
  porcentage = FALSE,
  gui = "plot",
  main = NULL,
  ...
)
```

## Arguments

| | |
|---|---|
| q | quantile. The q argument can have length 1 or 2. See Details. |
| dist | distribution to use. The default is 'normal'. Options: 'normal', 't-student', 'gumbel', 'binomial', 'poisson', and .... |
| lower.tail | logical; if TRUE (default), probabilities are $P[X \leq x]$ otherwise, $P[X > x]$. This argument is valid only if q has length 1. |
| rounding | numerical; it represents the number of decimals for calculating the probability. |
| porcentage | logical; if FALSE (default), the result in decimal. Otherwise, probability is given in percentage. |
| gui | default is 'plot'; it graphically displays the result of the probability. Others options are: 'none', 'rstudio' or 'tcltk'. |
| main | defalt is NULL; it represents title of plot. |
| ... | additional arguments according to the chosen distribution. |

## Details

The argument that can have length 2, when we use the functions that give us the probability regions, given by: %<X<%, %<=X<%, %<X<=%, %<=X<=%, %>X>%, %>X=>%, %>X=>% and %>=X=>%. The additional arguments represent the parameters of the distributions, that is:

## Value

P returns the probability and its graphical representation. The result can be given as a percentage or not.

## Examples

```
# Loading package
library(leem)
# Example 1 - t-Student distribution
## Not run:
P(q = 2, dist = "t-student", df = 10)
P(q = 2, dist = "t-student", df = 10, gui = 'rstudio')
P(q = 2, dist = "t-student", df = 10, gui = 'tcltk')
P(-1 %<X<% 1, dist = "t-student", df = 10)

## End(Not run)
# Example 2 - Normal distribution
P(-2,  dist = "normal", mean = 3, sd = 2,
  main = expression(f(x) == (1 / sqrt(n * sigma^2)) *
  exp(-1/2 * (x - mu)^2/sigma^2)))
```

---

`piechart` *Pie Chart*

---

## Description

Draw a pie chart.

## Usage

```
piechart(
  x,
  labels = NULL,
  col = heat.colors(5, 1),
  border = FALSE,
  main = NULL,
  ...
)
```

## Arguments

| | |
|---|---|
| `x` | R object (list) of class leem. Use `new_leem()` function. |
| `labels` | One or more expressions or character strings giving names for the slices |
| `col` | Character vector. Default `col = heat.colors(5)`. |
| `border` | Logical argument (default `FALSE`). |
| `main` | Title name. |
| `...` | further arguments passed to or from other methods. |

## Examples

```
library(leem)
# Example 1
school <- rep(c("high", "university", "basic"), 3:5)
x <- sample(school, 30, TRUE) |>
  new_leem() |>
  tabfreq(ordered = c("basic", "high", "university"))
# Example 2
x <- rbinom(36, 10, 0.6)
x <- new_leem(x, variable = "discrete")
x <- tabfreq(x)
piechart(x)
```

---

# polyfreq *Frequency polygon Graph*

---

## Description

Generic function that plots the frequency polygon curve.

## Usage

```
polyfreq(x, ...)
```

## Arguments

| | |
|---|---|
| x | R object (list) of class leem. Use `new_leem()` function. |
| ... | further arguments passed to or from other methods. |

## Examples

```
# Example 1
library(leem)
rnorm(36, 100, 50) |> new_leem(variable = "continuous") |> tabfreq() |> polyfreq()
```

---

# polyfreq.leem *Frequency polygon Graph*

---

## Description

Plot the frequency polygon curve.

## Usage

```
## S3 method for class 'leem'
polyfreq(
  x,
  freq = "a",
  type = "b",
  bars = TRUE,
  bg = TRUE,
  main = NULL,
  xlab = NULL,
  ylab = NULL,
  grids = grid(col = "white"),
  bgcol = "gray",
  bgborder = NA,
  barcol = "yellow",
  barborder = "gray",
  lpcol = "black",
  lwd = 2,
  pch = 19,
  lty = 2,
  ...
)
```

## Arguments

| | |
|---|---|
| x | R object (list) of class leem. Use new_leem() function. |
| freq | Character argument. Type of frequency with options: "a" (absolute and default), "r" relative and "p" percentage. |
| type | Type of plot. The default is type = "b", i.e., line and points. See graphical parameter for details. |
| bars | Logical argument. Default is FALSE. If bars = TRUE, the histogram will be inserted to plot. |
| bg | Logical argument. Default is TRUE, it displays the background, and bg = FALSE otherwise. |
| main | Insert the plot title. The default is NULL. |
| xlab | Insert the title of the x-axis graphic label. The default is NULL. |
| ylab | Insert the title of the y-axis graphic label. The default is NULL. |
| grids | Insert grids to plot. The default is grid(col = "white"). |
| bgcol | Insert the background color. This argument is only valid when bg = TRUE. The default is bgcol="gray". |
| bgborder | Insert the background border color. This argument is only valid when bg = TRUE. The default is bgborder = NA. |
| barcol | Insert the barplot color. The default is barcol = "yellow". This argument is only valid when bars = TRUE. |

| | |
|---|---|
| barborder | Insert the barplot border color. This argument is only valid when bars = TRUE. The default is barborder = "gray". |
| lpcol | Type of line color. The default is lpcol = "black". |
| lwd | numeric argument. The line width. The default is lwd = 2. |
| pch | Type of point. The default is pch = 19. |
| lty | Type of line. The default is lty = 2. |
| ... | further arguments passed to or from other methods. |

## Examples

```
# Example 1
library(leem)
rnorm(36, 100, 50) |> new_leem(variable = "continuous") |> tabfreq() |> polyfreq()
```

---

# probnormal *Undertanding the probability of the normal distribution*

---

## Description

Using a graphical visualization, it is possible to understand the probabilities involved in a normal distribution.

## Usage

```
probnormal(
  a = 1,
  b = 2,
  col = "lightblue",
  mean = 0,
  sd = 1,
  type = 1,
  rounding = 4,
  zang = 0,
  xang = 0
)
```

## Arguments

| | |
|---|---|
| a | lower limit. The default is 1. |
| b | upper limit. The default is 2, and b must be greater than a. |
| col | plot color. The default is col = "lightblue". |
| mean | parameter. The default is 0. |
| sd | parameter. The default is 1. |
| type | type of visualization of the probability region plot. Default is 1, others: 2, 3, 4, 5, 6. See Details. |

| | |
|---|---|
| rounding | Numerical object. Rounds the values in its first argument to the specified number of decimal places (default 4). |
| zang | Angle of the values on the Z-axis. Default is zang = 0. |
| xang | Angle of the values on the X-axis. Default is xang = 0. |

## Details

- type = 1,2: a and b must be greater than mean;
- type = 3,4: a and b must be less than mean;
- type = 5,6: a and b can be any real value.

## Examples

```
## Not run:
probnormal(type = 2)
probnormal(-1, 0, type = 3)
probnormal(-1, 0, type = 4)
probnormal(-1, 0, type = 5)
probnormal(-1, 2, type = 5)
probnormal(1, 2, type = 5)
probnormal(1, 2, type = 6)

## End(Not run)
```

---

# propofnormal *Properties of the normal distribution*

---

## Description

Graphically it is possible to observe some properties of the normal distribution

## Usage

```
propofnormal(col = "lightblue2", type = 1)
```

## Arguments

| | |
|---|---|
| col | color type. |
| type | numerical. Type of properties. Options: 1, 2, 3, 4 and 5. Default code = 1. |

Q *Quantile distribution function.*

## Description

Q Quantile function for multiple distributions.

## Usage

```
Q(
  p,
  dist = "normal",
  lower.tail = TRUE,
  two.sided = FALSE,
  rounding = 2,
  gui = "plot",
  mfrow = c(1, 2),
  type = "both",
  ...
)
```

## Arguments

| | |
|---|---|
| p | probability. The p argument need have length 1 and value lower then 1. |
| dist | distribution to use. The default is 'normal'. Options: 'normal', 't-student', 'gumbel', 'binomial', 'poisson', and .... |
| lower.tail | logical; if TRUE (default), the quantile function is computed; otherwise, the complement of the quantile function (survival function) will be computed. The lower.tail argument will only be valid for two-sided = FALSE. |
| two.sided | logical. if TRUE (default), the calculation of the quantile function and survival will be presented; otherwise the Q() function will be based according to the lower.tail argument. |
| rounding | numerical; it represents the number of decimals for calculating the probability. |
| gui | default is 'plot'; it graphically displays the result of the probability. Others options are: "plot" and "rstudio" and "tcltk". |
| mfrow | numerical vector. Considering the arguments two.sided = TRUE and type = "both", the default will be to present two graphs (based on CDF and PDF) horizontally for the quantile function, that is, mfrow = c(1, 2) (default). |
| type | character argument. The default is "both"; the output will display two plots (based on CDF and PDF) to present the result of Q(). The other options are: "cdf" and "pdf". |
| ... | additional parameters according to the chosen distribution. |

## Details

The expression of quantile function is given by:

$$Q(p) = \inf x \in \mathbb{R} : p \leq F(x),$$

where p is the first argument of `Q()` and x its return value;

## Value

`Q` returns the quantile and its graphical representation for a given distribution. The output is a vector.

## Examples

```
# Attaching package
library(leem)
## Not run:
Q(p = 0.8, dist = "normal", mean = 200, sd=30)

## End(Not run)
```

---

# Regions_of_probability

*Regions of probability*

---

## Description

These binary operators return a vector of length 2, describing the desired probability region.

## Usage

```
a %>x>% b

a %>X>% b

a %<X<% b

a %<x<% b

a %>=X>=% b

a %>=x>=% b

a %<=X<=% b

a %<=x<=% b

a %>=X>% b
```

```
a %>=x>% b

a %>X>=% b

a %>x>=% b

a %<=X<% b

a %<=x<% b

a %<X<=% b

a %<x<=% b
```

## Arguments

| | |
|---|---|
| a | scalar. when referring to a discrete random variable, use the syntax "L" after the number. |
| b | scalar. when referring to a discrete random variable, use the syntax "L" after the number. |

## Value

A vector of lenght 2.

## Examples

```
# Example 1 - Discrete
2L %>x>% 5L
2L %>X>% 5L
2L %<X<% 5L
2L %<x<% 5L
2L %>=X>=% 5L
2L %>=x>=% 5L
2L %<=X<=% 5L
2L %<=x<=% 5L
2L %>=X>% 5L
2L %>=x>% 5L
2L %>x>=% 5L
2L %>X>=% 5L
2L %<=X<% 5L
2L %<=x<% 5L
2L %<X<=% 5L
2L %<x<=% 5L

# Example 2 - Continuous
2 %>x>% 5
2 %>X>% 5
2 %<X<% 5
2 %<x<% 5
2 %>=X>=% 5
```

```
2 %>=x>=% 5
2 %<=X<=% 5
2 %<=x<=% 5
2 %>=X>% 5
2 %>=x>% 5
2 %>x>=% 5
2 %>X>=% 5
2 %<=X<% 5
2 %<=x<% 5
2 %<X<=% 5
2 %<x<=% 5
```

---

sdev *Standard Deviation*

---

## Description

Compute the sample standard deviation

## Usage

```
sdev(x, rounding = 2, na.rm = FALSE, details = FALSE, grouped = TRUE)
```

## Arguments

| | |
|---|---|
| x | R object (list) of class leem. Use `new_leem()` function. |
| rounding | Numerical object. Rounds the values in its first argument to the specified number of decimal places (default 2). |
| na.rm | a logical value indicating whether NA values should be stripped before the computation proceeds. |
| details | Logical object. Details of data (default FALSE). |
| grouped | Logical object. Determines whether the measure of position result will be based on grouped data or not (default TRUE). |

## Examples

```
# Example 1: Poisson data
rpois(30, 2.5) |>
  new_leem() |>
  sdev()
# Example 2: Normal data
rnorm(50, 100, 2.5) |>
  new_leem(variable = 2) |>
  sdev(grouped = FALSE)
```

## showboxplot *Undertanding a box plot*

### Description

Detailing of a box plot, showing the main information contained in this type of graph

### Usage

```
showboxplot(horizontal = FALSE, col = rgb(0, 175, 239, maxColorValue = 255))
```

### Arguments

| | |
|---|---|
| horizontal | Logical argument indicating if the boxplots should be horizontal; default FALSE means vertical boxes. |
| col | Character vector. Default col = rgb(0, 175, 239, maxColorValue = 255). |

### Examples

```
library(leem)
# Example 1
showboxplot()
```

## showcdf *Distribution Function Properties*

### Description

Graphic presentation of properties for distribution function

### Usage

```
showcdf(variable = "discrete", prop = NULL)
```

### Arguments

| | |
|---|---|
| variable | Variabe type. Defaults variable = "discrete". The options are: discrete or "1" and continuous or "2". |
| prop | Properties for distribution function. See Details. |

### Details

- prop = 1: $\lim_{x\to\infty} F_X(x) = 1$ and $\lim_{x\to-\infty} F_X(x) = 0$;
- prop = 2: $F_X(x) \leq F_X(y),\ x \leq y\ \forall x, y \in \mathbb{R}$;
- prop = 3: $\lim_{x_n \downarrow x} F_X(x_n) \downarrow F_X(x)$.

## Examples

```
library(leem)
# Example 1
showcdf()
```

---

showci *Understanding the Confiance Indice*

---

## Description

Detailing the confiance indice plot, showing the main information contained in this type of graph.

## Usage

```
showci(dist = "normal", ci = "two.sided", main = NULL)
```

## Arguments

| | |
|---|---|
| dist | Parameter to indicate the distribution of the graphic, fixed for now. |
| ci | Parameter to indicate the region of the confiance indice. |
| main | Parameter to indicate the title of the graphic. |

## Examples

```
library(leem)
# Example 1
showci()
```

---

showkur *Plot of interpretation about Kurtosis*

---

## Description

showkur Interpretation of kutosis

## Usage

```
showkur()
```

## Value

showkur returns a plot with the kurtosis characteristics.

## Examples

```
# Loading package
library(leem)
## Not run:
showkur()

## End(Not run)
```

---

showpar *Interpretation of location and scale parameters*

---

## Description

showpar Function that exemplifies the interpretation of location and scale parameters

## Usage

```
showpar(gui = "rstudio")
```

## Arguments

| | |
|---|---|
| gui | character argument. The options are: "rstudio" (default) and "tcltk". |

## Details

The result of the showpar() call will interactively present a plot of the normal distribution showing the behavior of the location and scale parameters via RStudio. For showpar(gui = "tcltk") the result will be displayed in a tcltk interface.

## Value

showpar returns an interactive plot.

## Examples

```
# Loading package
library(leem)
## Not run:
showpar()

## End(Not run)
```

## showskew *Plot of interpretation about skewsness*

### Description

showskew Interpretation of asymmetry based on frequency distributions

### Usage

```
showskew(mpos = FALSE)
```

### Arguments

| | |
|---|---|
| mpos | Logical. It shows the measures of position or not (default FALSE). |

### Examples

```
# Loading package
library(leem)
## Not run:
showskew()

## End(Not run)
```

## showtabnormal *showtabnormal*

### Description

Detailing of the Ztable, showing the main information contained in this type of table.

### Usage

```
showtabnormal(z)
```

### Arguments

| | |
|---|---|
| z | Parameter for lacate the z value on the table; default NULL means error if not insert a number. |

### Examples

```
library(leem)
# Example 1
showtabnormal(1)
```

skewness *Skewness value*

## Description

Compute the skewness

## Usage

```
skewness(
  x,
  type = "pearson",
  rounding = 2,
  na.rm = FALSE,
  details = FALSE,
  grouped = TRUE
)
```

## Arguments

| | |
|---|---|
| x | R object (list) of class leem. Use `new_leem()` function. |
| type | character. methodology addressed. For now, we only have the `"pearson"` option (default). |
| rounding | Numerical object. Rounds the values in its first argument to the specified number of decimal places (default `2`). |
| na.rm | a logical value indicating whether `NA` values should be stripped before the computation proceeds. |
| details | Logical object. Details of data (default `FALSE`). |
| grouped | Logical object. Determines whether the measure of position result will be based on grouped data or not (default `TRUE`). |

## Examples

```
# Example 1: Poisson data
rpois(30, 2.5) |>
  new_leem() |>
  skewness()
# Example 2: Normal data
rnorm(50, 100, 2.5) |>
  new_leem(variable = 2) |>
  skewness(grouped = TRUE)
```

stickchart *Stick chart*

## Description

Stick chart for discrete data

## Usage

```
stickchart(
  x,
  freq = "a",
  bg = TRUE,
  main = NULL,
  xlab = NULL,
  ylab = NULL,
  grids = grid(col = "white"),
  bgcol = "gray",
  bgborder = NA,
  posx1 = 0,
  posx2 = 0,
  xang = 0,
  labels = NULL,
  lcol = "black",
  pcol = lcol,
  pty = 19,
  pwd = 3,
  lty = 1,
  lwd = 2,
  ...
)
```

## Arguments

| | |
|---|---|
| x | R object (list) of class leem. Use `new_leem()` function. |
| freq | Character argument. Type of frequency with options: `"a"` (absolute and default), `"r"` relative and `"p"` percentage. |
| bg | Logical argument. Default is `TRUE`, it displays the background, and `bg = FALSE` otherwise. |
| main | Insert the plot title. The default is `NULL`. |
| xlab | Insert the title of the x-axis graphic label. The default is `NULL`. |
| ylab | Insert the title of the y-axis graphic label. The default is `NULL`. |
| grids | Insert grids to plot. The default is `grid(col = "white")`. |
| bgcol | Insert the background color. This argument is only valid when `bg = TRUE`. The default is `bgcol="gray"`. |

| | |
|---|---|
| bgborder | Insert the background border color. This argument is only valid when bg = TRUE. The default is bgborder = NA. |
| posx1 | Numeric argument.Distance of the labels (horizontal) in relation to the x axis. |
| posx2 | Numeric argument.Distance of the labels (vertical) in relation to the x axis. |
| xang | Numeric argument.Angle of the labels in relation to the x axis |
| labels | Character argument. Labels name vector. |
| lcol | Line color. The default is lcol = "black". |
| pcol | Point color. The default is pcol = lcol. |
| pty | Point type. The default is pty = 19. |
| pwd | Point width. The default is pwd = 3. |
| lty | Line type. The default is lty = 2. |
| lwd | Line width. The default is lwd = 2. |
| ... | further arguments passed to or from other methods. |

## Value

The result of stickchart() is x object.

## Examples

```
library(leem)
# Example 1
rbinom(30, 10, 0.4) |>
  new_leem() |>
  tabfreq() |>
  stickchart()
# Example 2
school <- rep(c("high", "university", "basic"), 3:5)
sample(school, 30, TRUE) |>
  new_leem() |>
  tabfreq(ordered = c("basic", "high", "university")) |>
  stickchart(xang = 15, posx2 = -0.5)
```

---

# tabfreq *Frequency distribution table*

---

## Description

Generic function that allows you to tabulate continuous and categorical data (quantitative or qualitative) in frequency distribution. Depending on the nature of the data, they can be grouped into class ranges or not.

## Usage

```
tabfreq(data, ...)
```

### Arguments

| | |
|---|---|
| data | R object (data structure vector) of class leem. Use new_leem() function. |
| ... | further arguments passed to or from other methods. |

### Value

The result of tabfreq() is a list. This list has two elements: table and statistics. The first is the data frequency table, and the second represents some useful statistics for methods of leem class.

### Examples

```
# Example 1
library(leem)
x <- rbinom(36, 10, 0.6)
x <- new_leem(x, variable = "discrete")
tabfreq(x)

# Example 2 (Pipe operator)
rnorm(36, 100, 4) |>
  new_leem(variable = "continuous") |> tabfreq()

# Example 3
x <- rbinom(36, 10, 0.6)
# Constructor (object of leem class)
x <- new_leem(x, variable = "discrete")
tab <- tabfreq(x)
# Details
tab$table
tab$statistics

# Example 3 - ordered categories ("d","a", "b", "c")
w <- rep(letters[1:4], 1:4)
w |> new_leem(variable = "discrete") |> tabfreq(ordered = c("d","a", "b", "c"))
```

---

## tabfreq.leem *Frequency distribution table*

---

### Description

Allows you to tabulate continuous and categorical data (quantitative or qualitative) in frequency distribution. Depending on the nature of the data, they can be grouped into class ranges or not.

### Usage

```
## S3 method for class 'leem'
tabfreq(
  data,
```

```
  k = NULL,
  na.rm = FALSE,
  ordered = NULL,
  namereduction = TRUE,
  ...
)
```

## Arguments

| | |
|---|---|
| data | R object (data structure vector) of class leem. Use new_leem() function. |
| k | Number of classes. Default is NULL. |
| na.rm | a logical evaluating to TRUE or FALSE indicating whether NA values should be stripped before the computation proceeds. |
| ordered | Ordered vector of the same length and elements of data object. Default is NULL. |
| namereduction | Logical argument. If TRUE (default), the group names are reduzed the 10 characters. If FALSE, otherwise. |
| ... | further arguments passed to or from other methods. |

## Value

The result of tabfreq() is a list. This list has two elements: table and statistics. The first is the data frequency table, and the second represents some useful statistics for methods of leem class.

## Examples

```
# Example 1
library(leem)
x <- rbinom(36, 10, 0.6)
x <- new_leem(x, variable = "discrete")
tabfreq(x)

# Example 2 (Pipe operator)
rnorm(36, 100, 4) |>
  new_leem(variable = "continuous") |> tabfreq()

# Example 3
x <- rbinom(36, 10, 0.6)
# Constructor (object of leem class)
x <- new_leem(x, variable = "discrete")
tab <- tabfreq(x)
# Details
tab$table
tab$statistics

# Example 3 - ordered categories ("d","a", "b", "c")
w <- rep(letters[1:4], 1:4)
w |> new_leem(variable = "discrete") |> tabfreq(ordered = c("d","a", "b", "c"))
```

variance *Variance value*

## Description

Compute the sample variance

## Usage

```
variance(x, rounding = 2, na.rm = FALSE, details = FALSE, grouped = TRUE)
```

## Arguments

| | |
|---|---|
| x | R object (list) of class leem. Use new_leem() function. |
| rounding | Numerical object. Rounds the values in its first argument to the specified number of decimal places (default 2). |
| na.rm | a logical value indicating whether NA values should be stripped before the computation proceeds. |
| details | Logical object. Details of data (default FALSE). |
| grouped | Logical object. Determines whether the measure of position result will be based on grouped data or not (default TRUE). |

## Examples

```
# Example 1: Poisson data
rpois(30, 2.5) |>
  new_leem() |>
  variance()
# Example 2: Normal data
rnorm(50, 100, 2.5) |>
  new_leem(variable = 2) |>
  variance(grouped = FALSE)
```

# Index


%<=X<=% (Regions_of_probability), 31
%<=X<% (Regions_of_probability), 31
%<=x<=% (Regions_of_probability), 31
%<=x<% (Regions_of_probability), 31
%<X<=% (Regions_of_probability), 31
%<X<% (Regions_of_probability), 31
%<x<=% (Regions_of_probability), 31
%<x<% (Regions_of_probability), 31
%>=X>=% (Regions_of_probability), 31
%>=X>% (Regions_of_probability), 31
%>=x>=% (Regions_of_probability), 31
%>=x>% (Regions_of_probability), 31
%>X>=% (Regions_of_probability), 31
%>X>% (Regions_of_probability), 31
%>x>=% (Regions_of_probability), 31
%>x>% (Regions_of_probability), 31

amplitude, 3
apf, 3

barplot.leem, 4
boxplot.leem, 6

cdfd, 7
cv, 8

dgumbel (Gumbel_distribution), 9

Gumbel_distribution, 9

hist.leem, 10

insert, 11
insert.leem, 12

leem, 14

madev, 14
mean.leem, 15
medev, 16
median.leem, 17
mfreq, 18
mpos, 19
mstde, 20

new_leem, 21

ogive, 21

P, 24
pgumbel (Gumbel_distribution), 9
piechart, 25
polyfreq, 26
polyfreq.leem, 26
probnormal, 28
propofnormal, 29

Q, 30
qgumbel (Gumbel_distribution), 9

Regions_of_probability, 31

sdev, 33
showboxplot, 34
showcdf, 34
showci, 35
showkur, 35
showpar, 36
showskew, 37
showtabnormal, 37
skewness, 38
stickchart, 39

tabfreq, 40
tabfreq.leem, 41

variance, 43