

Package ‘matahari’

July 22, 2025

Type Package

Title Spy on Your R Session

Version 0.1.3

Description Conveniently log everything you type into the R console. Logs are stored as tidy data frames which can then be analyzed using 'tidyverse' style tools.

Depends R (>= 3.5.0)

Imports rstudioapi, tibble, readr, jsonlite, clipr, purrr, rlang

Suggests testthat, knitr, rmarkdown

License MIT + file LICENSE

URL <https://github.com/jhudsl/matahari>

Encoding UTF-8

LazyData true

RoxygenNote 7.0.2

BugReports <https://github.com/jhudsl/matahari/issues>

VignetteBuilder knitr

NeedsCompilation no

Author Sean Kross [aut, cre] (ORCID: <<https://orcid.org/0000-0001-5215-0316>>),
Lucy D'Agostino McGowan [aut] (ORCID:
<<https://orcid.org/0000-0001-7297-9359>>),
Jeff Leek [ldr] (ORCID: <<https://orcid.org/0000-0002-2873-2671>>)

Maintainer Sean Kross <sean@seankross.com>

Repository CRAN

Date/Publication 2020-02-06 10:30:02 UTC

Contents

dance_recital	2
dance_remove	3

dance_report	4
dance_save	5
dance_start	5
dance_stop	6
dance_tbl	7
Index	9

dance_recital	Create a matahari-esque data frame from a file.
---------------	---

Description

Create a matahari-esque data frame from a file.

Usage

dance_recital(code, evaluate = TRUE)

Arguments

- code A string or the path to a file containing R code.
- evaluate Logical, indicating whether to evaluate the code, default is TRUE

Examples

```
library(knitr)

# Evaluate a string of R code
kable(dance_recital("x <- 4; x *7"))

## |expr   |value |error |output |warnings   |messages   |
## |:-----|:-----|:-----|:-----|:-----|:-----|
## |x <- 4 |4     |NULL  |        |character(0)|character(0)|
## |x * 7  |28    |NULL  |        |character(0)|character(0)|

# Evaluate an R script. We have provided an R script for testing purposes.
code_file <- system.file("test", "sample_code.R", package = "matahari")
kable(dance_recital(code_file)[,1:3])

## |expr           |value |error
## |:-----|:-----|:-----|
## |4 + 4         |8     |NULL
## |wow!         |wow!  |NULL
## |mean(1:10)   |5.5   |NULL
## |stop("Error!")|NULL  |list(message = "Error!", call = .f(...))
## |warning("Warning!")|Warning!|NULL
## |message("Hello?")|NULL  |NULL
## |cat("Welcome!")|NULL  |NULL
```

dance_remove	<i>Remove your logging history.</i>
--------------	-------------------------------------

Description

Remove your logging history.

Usage

```
dance_remove()
```

Value

Either TRUE if the log was removed or FALSE if the log does not exist (invisibly).

Examples

```
## Not run:
library(knitr)

# Start recording
dance_start(value = TRUE)

# Execute some expressions
"Hello!"
4 + 4

# Stop recording
dance_stop()

# Access log of your session
kable(dance_tbl()[3:4, 1:5])

## |expr   |value |path |contents |selection |
## |:-----|:-----|:----|:-----|:-----|
## |Hello! |Hello! |NA   |NA       |NA       |
## |4 + 4  |8      |NA   |NA       |NA       |

# Deletes the lgo of your session
dance_remove()

# With no log, dance_tbl() returns NULL invisibly.
withVisible(dance_tbl())

## $value
## NULL
##
## $visible
## FALSE
```

```
## End(Not run)
```

dance_report	<i>Copy the log to your clipboard.</i>
--------------	--

Description

Copy the log to your clipboard.

Usage

```
dance_report(...)
```

Arguments

... Developer options.

Examples

```
## Not run:

# Start recording
dance_start(value = TRUE)

# Execute some expressions
"Hello!"
4 + 4

# Stop recording
dance_stop()

# Assign a base64 encoded tibble of your log to a variable
report_code <- dance_report()
substr(report_code, 1, 10)

## "WAoAAAADAA"

nchar(report_code)

## 397432

## End(Not run)
```

dance_save	<i>Save the log as an rds file.</i>
------------	-------------------------------------

Description

Save the log as an rds file.

Usage

```
dance_save(path)
```

Arguments

path	The path to the rds file.
------	---------------------------

Examples

```
## Not run:  
  
# Start recording  
dance_start(value = TRUE)  
  
# Execute some expressions  
"Hello!"  
4 + 4  
  
# Stop recording  
dance_stop()  
  
# Save your log locally  
dance_save("session.rds")  
  
## End(Not run)
```

dance_start	<i>Start Spying</i>
-------------	---------------------

Description

Start logging your R console activity. If you're using RStudio the contents of your current editor tab will also be tracked. All logging takes place when R code is executed in the R console.

Usage

```
dance_start(
  expr = TRUE,
  value = FALSE,
  path = FALSE,
  contents = FALSE,
  selection = FALSE
)
```

Arguments

expr	The R expressions typed into the R console will be logged unless this is set to FALSE.
value	Values that are computed on the R console will be logged unless this is set to FALSE.
path	The path to the file in focus on the RStudio editor will be logged unless this is set to FALSE.
contents	The file contents of the RStudio editor tab in focus will be logged unless this is set to FALSE.
selection	The text that is highlighted in the RStudio editor tab in focus will be logged unless this is set to FALSE.

Examples

```
## Not run:
# Begin recording your R session.
dance_start()

# Each of the following expressions adds a row to the tibble that tracks
# the execution of your R code.
"Hello!"
4 + 4
x <- 7
x^2
rm(x)
x

# This stops recording your R session.
dance_stop()

## End(Not run)
```

dance_stop

Stop Spying

Description

Pause the current logging session.

Usage

```
dance_stop()
```

Value

TRUE if logging was taking place, otherwise FALSE (invisibly).

Examples

```
## Not run:
# Begin recording your R session.
dance_start()

# Each expression adds a row to the tibble that tracks the execution of
# your R code.
x <- 7
x * 4

# This stops recording your R session.
dance_stop()

## End(Not run)
```

dance_tbl	<i>Get the log as a tibble</i>
-----------	--------------------------------

Description

Get the log as a tibble

Usage

```
dance_tbl()
```

Value

Either a `tibble::tibble()` containing your logged history or NULL, if there is no log.

Examples

```
## Not run:

library(knitr)

# Start recording
dance_start(value = TRUE)

# Execute some expressions
"Hello!"
```

```
4 + 4

# Stop recording
dance_stop()

# Access log of your session
dance_tbl()

# Display the log nicely
kable(dance_tbl()[3:4, 1:5])

## |expr   |value |path |contents |selection |
## |:-----|:-----|:----|:-----|:-----|
## |Hello! |Hello! |NA   |NA       |NA        |
## |4 + 4  |8      |NA   |NA       |NA        |

## End(Not run)
```


Index

`dance_recital`, [2](#)
`dance_remove`, [3](#)
`dance_report`, [4](#)
`dance_save`, [5](#)
`dance_start`, [5](#)
`dance_stop`, [6](#)
`dance_tbl`, [7](#)

`tibble::tibble()`, [7](#)