

Package ‘metaDigitise’

July 22, 2025

Title Extract and Summarise Data from Published Figures

Version 1.0.1

Description High-throughput, flexible and reproducible extraction of data from figures in primary research papers. metaDigitise() can extract data and / or automatically calculate summary statistics for users from box plots, bar plots (e.g., mean and errors), scatter plots and histograms.

Depends R (>= 3.4)

License GPL (>= 2)

Encoding UTF-8

LazyData true

RoxygenNote 6.1.1

Imports magick, stats, graphics, utils, purrr

Suggests mockery, testthat, knitr, rmarkdown

BugReports <https://github.com/daniel1noble/metaDigitise/issues>

VignetteBuilder knitr

NeedsCompilation no

Author Joel Pick [aut],
Shinichi Nakagawa [aut],
Daniel Noble [aut, cre]

Maintainer Daniel Noble <daniel.wa.noble@gmail.com>

Repository CRAN

Date/Publication 2020-03-13 06:10:02 UTC

Contents

ask_variable	3
bulk_edit	3
calibrate	4
cal_coords	4
cat_matrix	5
CI95_to_sd	5

convert_group_data	6
convert_histogram_data	6
delete_group	6
dir_details	7
edit_group	8
edit_metaDigitise	8
enter_N	9
error_to_sd	9
extract_digitised	10
filename	10
getExtracted	11
getVals	12
get_notDone_file_details	12
grandMean	13
grandSD	14
group_scatter_extract	15
histogram_extract	15
import_menu	16
import_metaDigitise	16
internal_digitise	17
internal_redraw	17
is.even	18
is.wholenumber	19
isNumeric	19
knownN	20
load_metaDigitise	20
locator_mD	21
logAxes	21
MB_extract	22
metaDigitise	22
order_lists	24
plot.metaDigitise	25
point_extraction	25
print.metaDigitise	26
print_cal_instructions	26
process_data	27
process_new_files	27
range_to_sd	28
redraw_calibration	29
redraw_points	29
redraw_rotation	30
rqm_to_mean	30
rqm_to_sd	31
setup_calibration_dir	32
se_to_sd	32
single_MB_extract	33
specify_type	33
summary.metaDigitise	34

<i>ask_variable</i>	3
---------------------	---

user_base	34
user_calibrate	35
user_count	35
user_numeric	35
user_options	36
user_rotate_graph	36
user_unique	37

Index	38
--------------	-----------

<i>ask_variable</i>	<i>ask_variable</i>
---------------------	---------------------

Description

asks user what variable(s) is depending on plot type

Usage

`ask_variable(plot_type)`

Arguments

<code>plot_type</code>	<code>plot_type</code>
------------------------	------------------------

<i>bulk_edit</i>	<i>bulk_edit</i>
------------------	------------------

Description

Function for bulk editing previous data extraction through ‘metaDigitise’

Usage

`bulk_edit(dir, summary = TRUE, cex)`

Arguments

<code>dir</code>	parent directory
<code>summary</code>	logical; whether summary is returned
<code>cex</code>	relative size of text and points in replotting

Author(s)

Joel Pick

calibrate

calibrate

Description

Converts x and y coordinates from original plot coords to actual coords using previous identified coordinates. Modified from digitise package

Usage

```
calibrate(raw_data, calpoints, point_vals, log_axes, ...)
```

Arguments

raw_data	The raw data
calpoints	The calibration points
point_vals	The point values
log_axes	whether x or y is logged
...	further arguments passed to or from other methods

cal_coords

cal_coords

Description

Prompts user to enter axis coordinates, and their values. Modified from the digitize package

Usage

```
cal_coords(plot_type, cex, ...)
```

Arguments

plot_type	plot type
cex	size of points
...	further arguments passed to or from other methods.

cat_matrix	<i>cat_matrix</i>
------------	-------------------

Description

prints a vector as a number list of items with a certain number of columns

Usage

```
cat_matrix(x, cols)
```

Arguments

x	vector
cols	number of columns

CI95_to_sd	<i>CI95_to_sd</i>
------------	-------------------

Description

Transforms symmetrical confidence interval to standard deviation

Usage

```
CI95_to_sd(CI, n)
```

Arguments

CI	Interval difference from the mean
n	Sample Size

Value

Returns vector of standard deviations

Author(s)

Joel Pick

Examples

```
CI95_to_sd(CI = 2, n = 10)
```

convert_group_data	<i>convert_group_data</i>
--------------------	---------------------------

Description

Converts, pre-calibrated points clicked into a meaningful dataframe

Usage

```
convert_group_data(cal_data, plot_type)
```

Arguments

cal_data	Calibrated data
plot_type	The type of plot

convert_histogram_data	<i>convert_histogram_data</i>
------------------------	-------------------------------

Description

Conversion of extracted data from histogram

Usage

```
convert_histogram_data(cal_data)
```

Arguments

cal_data	The calibration data
----------	----------------------

delete_group	<i>delete_points</i>
--------------	----------------------

Description

Delete groups from scatterplots

Usage

```
delete_group(raw_data)
```

Arguments

raw_data	data
----------	------

*dir_details**dir_details*

Description

Function will gather important directory details about calibration files and figures needed for processing

Usage

```
dir_details(dir)
```

Arguments

`dir` the path name to the directory / folder where the files are located

Author(s)

Daniel Noble - daniel.wa.noble@gmail.com

Examples

```
# temporary directory
tmp_dir <- tempdir()

setup_calibration_dir(paste0(tmp_dir, "/"))

# Simulate data
set.seed(103)
x <- rnorm(20,0,1)
y <- rnorm(20,0,1)
means <- c(mean(x),mean(y))
ses <- c(sd(x)/sqrt(length(x))*1.96, sd(y)/sqrt(length(y))*1.96)

#Generate mock figures
png(filename = paste0(tmp_dir, "/mean_error.png"), width = 480, height = 480)
plot(means, ylim = c(min(means-ses)-0.1,max(means+ses)+0.1), xlim=c(0.5,2.5),
xaxt="n", pch=19, cex=2, ylab="Variable +/- SE", xlab="Treatment", main="Mean Error")
arrows(1:length(means),means+ses, 1:length(means), means-ses, code=3, angle=90, length=0.1)
axis(1,1:length(means),names(means))
dev.off()
png(filename = paste0(tmp_dir, "/boxplot.png"), width = 480, height = 480)
boxplot(x,y, main="Boxplot")
dev.off()
png(filename = paste0(tmp_dir, "/histogram.png"),width = 480, height = 480)
hist(c(x,y), xlab= "variable", main="Histogram")
dev.off()
png(filename = paste0(tmp_dir, "/scatterplot.png"), width = 480, height = 480)
plot(x,y, main="Scatterplot")
dev.off()
```

```
#Obtain details on directory structure that are used for metaDigitise
data <- dir_details(tmp_dir)
```

edit_group	<i>edit_group</i>
------------	-------------------

Description

Edit group points in scatterplots

Usage

```
edit_group(raw_data, group_id, calpoints, cex, ...)
```

Arguments

raw_data	data
group_id	group_id
calpoints	The calibration points
cex	point size
...	other functions to pass to internal_redraw

edit_metaDigitise	<i>edit_metaDigitise</i>
-------------------	--------------------------

Description

Function for editing previous data extraction through ‘metaDigitise’

Usage

```
edit_metaDigitise(object)
```

Arguments

object	an R object of class ‘metaDigitise’
--------	-------------------------------------

Value

Data.frame

Author(s)

Joel Pick

enter_N	<i>enter_N</i>
---------	----------------

Description

Enter sample sizes for a group

Usage

```
enter_N(raw_data, ...)
```

Arguments

raw_data	raw_data
...	Pass additional arguments

Author(s)

Joel Pick

error_to_sd	<i>error_to_sd</i>
-------------	--------------------

Description

Transforms error to standard deviation

Usage

```
error_to_sd(error, n, error_type = c("se", "CI95", "sd", NA))
```

Arguments

error	some form of error
n	Sample Size
error_type	type of error measured

Value

Returns vector of standard errors

Author(s)

Joel Pick

extract_digitised	<i>extract_digitised</i>
-------------------	--------------------------

Description

Function for extracting the data from a metaDigitise list and creating either summary data or a list of the raw data.

Usage

```
extract_digitised(list, summary = TRUE)
```

Arguments

- list A list of objects returned from metaDigitise
- summary A logical 'TRUE' or 'FALSE' indicating whether metaDigitise should print summary statistics from each figure and group.

Value

The function will return a data frame with the data across all the digitised files

filename	<i>filename</i>
----------	-----------------

Description

extracts filename from filepath

Usage

```
filename(x)
```

Arguments

- x filepath

getExtracted	<i>getExtracted</i>
--------------	---------------------

Description

Extracts data from a directory that has been previously digitised using metaDigitise()

Usage

```
getExtracted(dir, summary = TRUE)
```

Arguments

dir	The directory where figures have already been digitised. There
summary	Logical indicating whether summarised (default) or calibrated data should be returned.

Value

Returns a data frame (summary = TRUE) or a list with slots for each plot type (summary = FALSE)

Examples

```
# Make some mock metaDigitise object
mock_metaDig <- list(
  image_file = "./image.png",
  flip=FALSE,
  rotate=0,
  plot_type="mean_error",
  variable="y",
  calpoints = data.frame(x=c(0,0),y=c(0,100)),
  point_vals = c(1,2),
  entered_N=TRUE,
  raw_data = data.frame(id=rep("control",2),
    x=c(60,60),
    y=c(75,50),
    n=rep(20,2)),
  knownN = NULL,
  error_type="sd",
  processed_data=data.frame(
    id=as.factor("control"),
    mean=1.5,
    error=0.25,
    n=20,
    variable="y",
    stringsAsFactors = FALSE)
)
class(mock_metaDig) <- 'metaDigitise'
```

```
# write image file to tmpdir()
dir <- tempdir()

# Setup directory as it would be if digitised images existed
setup_calibration_dir(dir)

# Save the digitised data
saveRDS(mock_metaDig, file = paste0(dir, "/caldat/", "image"))

#metaDigitise figures
data <- getExtracted(dir)
```

getVals	<i>getVals</i>
---------	----------------

Description

Gets values needed to calibrate axis coordinated. Modified from the digitize package

Usage

```
getVals(calpoints, ...)
```

Arguments

calpoints	Calibration points
...	further arguments passed to or from other methods.

get_notDone_file_details	<i>get_notDone_file_details</i>
--------------------------	---------------------------------

Description

Function will get file information from the directory and the calibration files. It will also exclude files that have already been processed, as is judged by the match between file names in the calibration folder and the imported details object

Usage

```
get_notDone_file_details(dir)
```

Arguments

dir	Path name to the directory / folder where the figure files are located.
-----	---

Value

Returns a list containing details on the images names and their paths, the calibration file names (or files already completed) as well as the paths to these files.

Author(s)

Daniel Noble - daniel.wa.noble@gmail.com

Examples

```
# temporary directory
tmp_dir <- tempdir()

# Simulate data
set.seed(103)
x <- rnorm(20,0,1)
y <- rnorm(20,0,1)
means <- c(mean(x),mean(y))
ses <- c(sd(x)/sqrt(length(x))*1.96, sd(y)/sqrt(length(y))*1.96)

#Generate mock figures
png(filename = paste0(tmp_dir,"/mean_error.png"), width = 480, height = 480)
plot(means, ylim = c(min(means-ses)-0.1,max(means+ses)+0.1), xlim=c(0.5,2.5),
xaxt="n", pch=19, cex=2, ylab="Variable +/- SE", xlab="Treatment", main="Mean Error")
arrows(1:length(means),means+ses, 1:length(means), means-ses, code=3, angle=90, length=0.1)
axis(1,1:length(means),names(means))
dev.off()
png(filename = paste0(tmp_dir, "/boxplot.png"), width = 480, height = 480)
boxplot(x,y, main="Boxplot")
dev.off()
png(filename = paste0(tmp_dir, "/histogram.png"),width = 480, height = 480)
hist(c(x,y), xlab= "variable", main="Histogram")
dev.off()
png(filename = paste0(tmp_dir, "/scatterplot.png"), width = 480, height = 480)
plot(x,y, main="Scatterplot")
dev.off()

#Obtain file names that are incomplete within the tmp directory
data <- get_notDone_file_details(tmp_dir)
```

grandMean

grandMean

Description

Pooled mean of a set of group means

Usage

```
grandMean(mean, n)
```

Arguments

mean	Mean
n	Sample size

Value

Returns vector of pooled mean

Author(s)

Joel Pick

Examples

```
grandMean(mean = 10, n = 30)
```

*grandSD**grandSD*

Description

Pooled standard deviation of a set of groups

Usage

```
grandSD(mean, sd, n, equal = FALSE)
```

Arguments

mean	Mean
sd	standard deviation
n	Sample size
equal	Logical: Whether to calculate pooled SD assuming groups have the same means (TRUE) or different means (FALSE)

Value

Returns vector of pooled mean

Author(s)

Joel Pick

Examples

```
grandSD(mean = 10, sd = 3, n = 40)
```

```
group_scatter_extract  group_scatter_extract
```

Description

Extraction of data from scatterplots

Usage

```
group_scatter_extract(edit = FALSE,
  raw_data = data.frame(stringsAsFactors = TRUE), cex, ...)
```

Arguments

edit	logical; whether in edit mode
raw_data	raw data
cex	point size
...	arguments passed to internal_redraw

```
histogram_extract      histogram_extract
```

Description

Extraction of data from histograms

Usage

```
histogram_extract(edit = FALSE, raw_data = data.frame(), calpoints,
  cex, ...)
```

Arguments

edit	logical; whether in edit mode
raw_data	raw data
calpoints	The calibration points
cex	point size
...	arguments to pass to internal_redraw

import_menu	<i>import_menu</i>
-------------	--------------------

Description

Imports metaDigitise() calibration files from a directory that is partially or fully digitised already

Usage

```
import_menu(dir, summary)
```

Arguments

dir	The directory where figures have already been digitised
summary	Logical indicating whether the imported data should be returned in summarised or processed form.

Value

Returns a list (summary = FALSE) or data frame (summary = TRUE)

import_metaDigitise	<i>import_metaDigitise</i>
---------------------	----------------------------

Description

Imports metaDigitise() calibration files from a directory that is partially or fully digitised already

Usage

```
import_metaDigitise(dir, summary)
```

Arguments

dir	The directory where figures have already been digitised
summary	Logical indicating whether the imported data should be returned in summarised form ('TRUE') or not ('FALSE')

Value

Returns a list (summary = FALSE) or data frame (summary = TRUE)

Author(s)

Daniel Noble - daniel.wa.noble@gmail.com

internal_digitise	<i>internal_digitise</i>
-------------------	--------------------------

Description

Extracts points from a single figure and processes data

Usage

```
internal_digitise(image_file, plot_type = NULL, cex)
```

Arguments

image_file	Image file
plot_type	Type of plot from "mean_error", "boxplot", "scatterplot" or "histogram". Function will prompt if not entered by user.
cex	point size for replotting

Value

List of user inputs and transformed data from digitisation

Author(s)

Joel Pick

internal_redraw	<i>internal_redraw</i>
-----------------	------------------------

Description

Redraws figure and extraction data

Usage

```
internal_redraw(image_file, flip = FALSE, rotate = 0,  
  plot_type = NULL, variable = NULL, cex = NULL, calpoints = NULL,  
  point_vals = NULL, raw_data = NULL, rotation = TRUE,  
  calibration = TRUE, points = TRUE, ...)
```

Arguments

<code>image_file</code>	Image filename
<code>flip</code>	whether to flip figure
<code>rotate</code>	how much to rotate figure
<code>plot_type</code>	<code>plot_type</code>
<code>variable</code>	variable
<code>cex</code>	relative size of points and text
<code>calpoints</code>	The calibration points
<code>point_vals</code>	The point values
<code>raw_data</code>	The raw data
<code>rotation</code>	logical, should figure be rotated
<code>calibration</code>	logical, should calibration be redrawn
<code>points</code>	logical, should points be redrawn
<code>...</code>	further arguments passed to or from other methods.

<code>is.even</code>	<i>is.even</i>
----------------------	----------------

Description

Checks whether a integer is even

Usage

`is.even(x)`

Arguments

<code>x</code>	integer value
----------------	---------------

Value

Logical (TRUE or FALSE) indicating whether value is an even number or not

is.wholenumber	<i>is.wholenumber</i>
----------------	-----------------------

Description

Checks whether value is a whole number

Usage

```
is.wholenumber(x, tol = .Machine$double.eps^0.5)
```

Arguments

x	object to be tested
tol	tolerance

Value

Logical value (TRUE or FALSE)

isNumeric	<i>isNumeric</i>
-----------	------------------

Description

Checks whether a character is a number

Usage

```
isNumeric(x)
```

Arguments

x	character to be tested
---	------------------------

Value

Logical (TRUE or FALSE) indicating whether value is numeric or not

knownN	<i>knownN</i>
--------	---------------

Description

prints a vector as a number list of items with a certain number of columns

Usage

```
knownN(plot_type, processed_data, knownN = NULL, ...)
```

Arguments

plot_type	plot type
processed_data	raw_data
knownN	previously entered N
...	arguments from other calls

load_metaDigitise	<i>load_metaDigitise</i>
-------------------	--------------------------

Description

Loads metaDigitise calibration / data files from a directory containing a set of figures that are partially or fully digitised already.

Usage

```
load_metaDigitise(doneCalFiles, names)
```

Arguments

doneCalFiles	The metaDigitise objects that have already been completed in the directory
names	The names of the finished metaDigitise objects

Value

Returns a list of metaDigitised objects that have already been completed

Author(s)

Daniel Noble - daniel.wa.noble@gmail.com

locator_mD	<i>locator_mD</i>
------------	-------------------

Description

Wrapper function for locator, with more control over point size etc

Usage

```
locator_mD(nPoints = 1, line = TRUE, cex = 1, col = "red", ...)
```

Arguments

nPoints	number of points in a sequence
line	logical; plot lines between points
cex	size of points
col	colour of points
...	further arguments passed to or from other methods.

Value

Plots clicked points, and returns their x.y coordinates as a data.frame

logAxes	<i>getVals</i>
---------	----------------

Description

Ask user for information about whether axes are on log scale

Usage

```
logAxes(...)
```

Arguments

...	further arguments passed to or from other methods.
-----	--

MB_extract

MB_extract

Description

Extraction of data from boxplots of mean_error plots, from multiple groups

Usage

```
MB_extract(edit = FALSE, plot_type, entered_N,
  raw_data = data.frame(stringsAsFactors = TRUE), cex, ...)
```

Arguments

edit	logical; whether in edit mode
plot_type	The type of plot
entered_N	ask for sample sizes?
raw_data	raw data
cex	point size
...	further arguments to MB_extract

metaDigitise

metaDigitise

Description

Single or batch processing of figures with .png, .jpg, .tiff, .pdf extensions within a set directory. metaDigitise() consolidates the data and exports the data for each image and image type. It can also summarise the data, provide the raw data (if scatterplots) and automatically imports previously finished data and merges it with newly digitised data. metaDigitise() also allows users to check their calibration along with editing previous digitisations.

Usage

```
metaDigitise(dir, summary = TRUE, cex = 1)
```

Arguments

dir	the path name to the directory / folder where the files are located
summary	whether the digitised data should be returned as a summary (TRUE) or as a concatenated list of similar types.
cex	relative size of points and text in replotting of digitisation. Default is 1.

Details

metaDigitise() can be used on a directory with a whole host of different figure types (mean and error, scatter plots, box plots and histograms) and file types (.jpeg, .png, .tiff, .pdf). There are three major options provided to users:

If the "1: Process new images" option is chosen, it will automatically cycle through all figures not already completed within a directory in order, prompting the user for specific information as they go. At the end of each figure users will be asked if they would like to continue or not, providing flexibility to leave a job should they need to. As figures are digitised it will automatically write metaDigitise() object files (in .RDS format containing processed and calibration data along with directory and file details), into a special caldat/ folder within the directory. Importantly, as new files are added to a directory that has already been "completed", metaDigitise() will recognize these unfinished files and only cycle through the digitisation of these new files. This easily allows users to pick up from where they left off. It will also automatically re-merge completed figure with any newly digitised figures at the end of this process keeping everything together throughout the process.

If the "2: Import existing data" is chosen, all existing files that have already been digitised will be automatically imported from the given directory.

Finally, metDigitise is built for ease of editing and reproducibility in mind. Hence, if "3: Edit existing data" is chosen by the user then users will have the options to "1: Cycle through images" (that are complete), overlaying digitisations with each figure and asking whether they would like to edit each figure or "2: Choose specific file to edit" allowing editing for a specific file. Here a list of all files are provided and the user simply needs to pick the one in the console they would like to view. Alternatively, the "3: Enter previously omitted sample sizes" option allows the user to go back and enter sample sizes that they may not have had on hand at the time of digitisation. This means that, so long as the caldat/ folder along with respective images are maintained, anyone using metaDigitise() can simply import existing digitisations, modify them and fix them. This folder can then be shared with colleagues to allow them to reproduce any data extraction.

Value

A data frame or list containing the raw digitised data or the processed, summary statistics from the digitised data

Author(s)

Joel Pick - joel.l.pick@gmail.com

Daniel Noble - daniel.wa.noble@gmail.com

Examples

```
# temporary directory
tmp_dir <- tempdir()

# Simulate data
set.seed(103)
x <- rnorm(20,0,1)
y <- rnorm(20,0,1)
means <- c(mean(x),mean(y))
```

```

ses <- c(sd(x)/sqrt(length(x))*1.96, sd(y)/sqrt(length(y))*1.96)

#Generate mock figures
png(filename = paste0(tmp_dir, "/mean_error.png"), width = 480, height = 480)
plot(means, ylim = c(min(means-ses)-0.1,max(means+ses)+0.1), xlim=c(0.5,2.5),
xaxt="n", pch=19, cex=2, ylab="Variable +/- SE", xlab="Treatment", main="Mean Error")
arrows(1:length(means),means+ses, 1:length(means), means-ses, code=3, angle=90, length=0.1)
axis(1,1:length(means),names(means))
dev.off()
png(filename = paste0(tmp_dir, "/boxplot.png"), width = 480, height = 480)
boxplot(x,y, main="Boxplot")
dev.off()
png(filename = paste0(tmp_dir, "/histogram.png"),width = 480, height = 480)
hist(c(x,y), xlab= "variable", main="Histogram")
dev.off()
png(filename = paste0(tmp_dir, "/scatterplot.png"), width = 480, height = 480)
plot(x,y, main="Scatterplot")
dev.off()

#metaDigitise figures
## Not run:
data <- metaDigitise(tmp_dir)

## End(Not run)

```

order_lists

order_lists

Description

Will re-order the processed data such that similar types of data are organised into a single list defined by their plot type.

Usage

```
order_lists(list, plot_types)
```

Arguments

list	The list of metaDigitise objects that have already been finished within the caldat/ folder
plot_types	The list of plot types extracted from metaDigitised objects

Value

Returns a list ordered by the plot type

Author(s)

Daniel Noble - daniel.wa.noble@gmail.com

plot.metaDigitise	<i>plot.metaDigitise</i>
-------------------	--------------------------

Description

Re-plots figure and extraction data

Usage

```
## S3 method for class 'metaDigitise'  
plot(x, cex = NULL, ...)
```

Arguments

x	an R object of class 'metaDigitise'
cex	size of points
...	further arguments passed to or from other methods.

Author(s)

Joel Pick

point_extraction	<i>point_extraction</i>
------------------	-------------------------

Description

Extracts or edits point of a digitisation

Usage

```
point_extraction(object, edit = FALSE)
```

Arguments

object	Object
edit	Logical (TRUE or FALSE) indicating whether a point would like to be edited

print.metaDigitise *print.metaDigitise*

Description

Print method for class 'metaDigitise'

Usage

```
## S3 method for class 'metaDigitise'  
print(x, ...)
```

Arguments

x an R object of class 'metaDigitise'
... further arguments passed to or from other methods.

Author(s)

Joel Pick

print_cal_instructions
 print_cal_instructions

Description

Prints instructions for calibration. Modified from the digitize package

Usage

```
print_cal_instructions(plot_type, ...)
```

Arguments

plot_type plot type
... further arguments passed to or from other methods.

process_data	<i>process_data</i>
--------------	---------------------

Description

Processes points clicked into a meaningful dataframe

Usage

```
process_data(object)
```

Arguments

object	object from metaDigitise
--------	--------------------------

process_new_files	<i>process_new_files</i>
-------------------	--------------------------

Description

Batch processes image files within a set directory, consolidates the data and exports the data for each image and type

Usage

```
process_new_files(dir, summary = TRUE, cex)
```

Arguments

dir	the path name to the directory / folder where the files are located
summary	summary = TRUE or FALSE is most relevant as it will print a simple summary statistics that are the same across all files
cex	relative size of points and text in replotting of digitisation.

Author(s)

Joel Pick - joel.l.pick@gmail.com

Daniel Noble - daniel.wa.noble@gmail.com

Examples

```
# temporary directory
tmp_dir <- tempdir()

# Simulate data
set.seed(103)
x <- rnorm(20,0,1)
y <- rnorm(20,0,1)
means <- c(mean(x),mean(y))
ses <- c(sd(x)/sqrt(length(x))*1.96, sd(y)/sqrt(length(y))*1.96)

#Generate mock mean error plot
png(filename = paste0(tmp_dir,"/mean_error.png"), width = 480, height = 480)
plot(means, ylim = c(min(means-ses)-0.1,max(means+ses)+0.1), xlim=c(0.5,2.5),
xaxt="n", pch=19, cex=2, ylab="Variable +/- SE", xlab="Treatment", main="Mean Error")
arrows(1:length(means),means+ses, 1:length(means), means-ses, code=3, angle=90, length=0.1)
axis(1,1:length(means),names(means))
dev.off()

## Not run:
#metaDigitise figures
data <- process_new_files(paste0(tmp_dir, "/"), summary = TRUE, cex = 2)

## End(Not run)
```

<code>range_to_sd</code>	<i>range_to_sd</i>
--------------------------	--------------------

Description

Converts a range to a standard deviation

Usage

```
range_to_sd(min, max, n)
```

Arguments

<code>min</code>	Minimum value
<code>max</code>	Maximum value
<code>n</code>	Sample size

Value

Returns vector of standard deviation

Author(s)

Joel Pick

Examples

```
range_to_sd(min = 3, max = 8, n = 40)
```

redraw_calibration	<i>redraw_calibration</i>
--------------------	---------------------------

Description

plots calibration data on graph

Usage

```
redraw_calibration(plot_type, variable, calpoints, point_vals,  
  image_details, cex)
```

Arguments

plot_type	plot_type
variable	variable
calpoints	The calibration points
point_vals	The point values
image_details	image_details
cex	relative size of points and text

redraw_points	<i>redraw_points</i>
---------------	----------------------

Description

plots clicked data on graph

Usage

```
redraw_points(plot_type, raw_data, image_details, cex)
```

Arguments

plot_type	plot_type
raw_data	The raw data
image_details	image_details
cex	relative size of points and text

redraw_rotation	<i>rotate_graph</i>
-----------------	---------------------

Description

Rotates/flips imported figures

Usage

```
redraw_rotation(image, flip, rotate)
```

Arguments

image	Image object from magick::image_read
flip	whether to flip figure
rotate	how much to rotate figure

rqm_to_mean	<i>rqm_to_mean</i>
-------------	--------------------

Description

Calculate the mean from the box plots

Usage

```
rqm_to_mean(min, LQ, median, UQ, max, n)
```

Arguments

min	Minimum value
LQ	Lower 75th quartile
median	Median
UQ	Upper 75th quartile
max	Maximum value
n	Sample size

Value

Returns vector of mean

Author(s)

Joel Pick

Examples

```
rqm_to_mean(min = 2, LQ = 3, median = 5, UQ = 6, max = 9, n = 30)
```

*rqm_to_sd**rqm_to_sd*

Description

Calculate the standard deviation from box plots

Usage

```
rqm_to_sd(min, LQ, UQ, max, n)
```

Arguments

min	Minimum value
LQ	Lower 75th quartile
UQ	Upper 75th quartile
max	Maximum value
n	Sample size

Value

Returns vector of standard deviation

Author(s)

Joel Pick

Examples

```
rqm_to_sd(min = 2, LQ = 3, UQ = 6, max = 9, n = 30)
```

```
setup_calibration_dir  setup_calibration_dir
```

Description

Function will check whether the calibration directory has been setup and if not, create one.

Usage

```
setup_calibration_dir(dir)
```

Arguments

`dir` Path name to the directory / folder where the files are located.

Value

Returns a caldat/ folder within the directory where all metaDigitise objects are stored.

Author(s)

Daniel Noble - daniel.wa.noble@gmail.com

Examples

```
# temporary directory
tmp_dir <- tempdir()

#Create the calibration folder in the directory specified that is used to store files.
setup_calibration_dir(paste0(tmp_dir, "/"))
```

```
se_to_sd                      se_to_sd
```

Description

Transforms standard error to standard deviation

Usage

```
se_to_sd(se, n)
```

Arguments

`se` Standard Error of the mean
`n` Sample Size

Value

Returns vector of standard errors

Author(s)

Joel Pick

Examples

```
se_to_sd(se = 5, n = 10)
```

single_MB_extract	<i>single_MB_extract</i>
-------------------	--------------------------

Description

Takes points user defined points from a single group mean_error plot or boxplot, in a set order, and returns them.

Usage

```
single_MB_extract(plot_type, cex)
```

Arguments

plot_type	Type of plot
cex	point size

specify_type	<i>specify_type</i>
--------------	---------------------

Description

Function that allows user to interface with function to specific each type of plot prior to digitising

Usage

```
specify_type()
```

Value

The function will return the type of plot specified by the user and feed this argument back into metDigitise

Author(s)

Daniel Noble - daniel.wa.noble@gmail.com

Joel Pick - joel.l.pick@gmail.com

summary.metaDigitise	<i>summary.metaDigitise</i>
----------------------	-----------------------------

Description

Summary method for class ‘metaDigitise’

Usage

```
## S3 method for class 'metaDigitise'  
summary(object, ...)
```

Arguments

object an R object of class ‘metaDigitise’
... further arguments passed to or from other methods.

Value

Data.frame

Author(s)

Joel Pick

user_base	<i>user_base</i>
-----------	------------------

Description

asks user for base of logarithm, accept numeric or "e"

Usage

```
user_base(...)
```

Arguments

... arguments passed to other functions

user_calibrate	<i>user_calibrate</i>
----------------	-----------------------

Description

Gets values needed to calibrate axis coordinated. Modified from the digitize package

Usage

user_calibrate(object)

Arguments

object metaDigitise object

user_count	<i>user_count</i>
------------	-------------------

Description

asks user for count

Usage

user_count(question)

Arguments

question question

user_numeric	<i>user_numeric</i>
--------------	---------------------

Description

asks user for numeric

Usage

user_numeric(question)

Arguments

question question

<code>user_options</code>	<i>user_options</i>
---------------------------	---------------------

Description

asks user for option from specified list

Usage

`user_options(question, allowed_answers)`

Arguments

<code>question</code>	question
<code>allowed_answers</code>	allowed answers

<code>user_rotate_graph</code>	<i>user_rotate_graph</i>
--------------------------------	--------------------------

Description

Rotates/flips imported figures according to user input, in order to align them properly. Asks the user after each change if further alteration is required

Usage

`user_rotate_graph(image_file)`

Arguments

<code>image_file</code>	Image filename
-------------------------	----------------

user_unique	<i>user_unique</i>
-------------	--------------------

Description

asks user for option from specified list

Usage

user_unique(question, previous_answers)

Arguments

- question question
- previous_answers allowed answers

Index

ask_variable, [3](#)

bulk_edit, [3](#)

cal_coords, [4](#)
calibrate, [4](#)
cat_matrix, [5](#)
CI95_to_sd, [5](#)
convert_group_data, [6](#)
convert_histogram_data, [6](#)

delete_group, [6](#)
dir_details, [7](#)

edit_group, [8](#)
edit_metaDigitise, [8](#)
enter_N, [9](#)
error_to_sd, [9](#)
extract_digitised, [10](#)

filename, [10](#)

get_notDone_file_details, [12](#)
getExtracted, [11](#)
getVals, [12](#)
grandMean, [13](#)
grandSD, [14](#)
group_scatter_extract, [15](#)

histogram_extract, [15](#)

import_menu, [16](#)
import_metaDigitise, [16](#)
internal_digitise, [17](#)
internal_redraw, [17](#)
is.even, [18](#)
is.wholenumber, [19](#)
isNumeric, [19](#)

knownN, [20](#)

load_metaDigitise, [20](#)

locator_mD, [21](#)
logAxes, [21](#)

MB_extract, [22](#)
metaDigitise, [22](#)

order_lists, [24](#)

plot.metaDigitise, [25](#)
point_extraction, [25](#)
print.metaDigitise, [26](#)
print_cal_instructions, [26](#)
process_data, [27](#)
process_new_files, [27](#)

range_to_sd, [28](#)
redraw_calibration, [29](#)
redraw_points, [29](#)
redraw_rotation, [30](#)
rqm_to_mean, [30](#)
rqm_to_sd, [31](#)

se_to_sd, [32](#)
setup_calibration_dir, [32](#)
single_MB_extract, [33](#)
specify_type, [33](#)
summary.metaDigitise, [34](#)

user_base, [34](#)
user_calibrate, [35](#)
user_count, [35](#)
user_numeric, [35](#)
user_options, [36](#)
user_rotate_graph, [36](#)
user_unique, [37](#)