

Package ‘muRty’

July 23, 2025

Title Murty's Algorithm for k-Best Assignments

Version 0.3.1

Author Aljaz Jelenko [aut, cre]

Maintainer Aljaz Jelenko <aljaz.jelenko@amis.net>

Description Calculates k-best solutions and costs for an assignment problem following the method outlined in Murty (1968) <doi:10.1287/opre.16.3.682>.

URL <https://github.com/argonaut91/muRty>

BugReports <https://github.com/argonaut91/muRty/issues>

Depends R (>= 3.1.0)

Imports clue, lpSolve

Suggests testthat

License MIT + file LICENSE

Encoding UTF-8

LazyData true

RoxygenNote 7.0.2

NeedsCompilation no

Repository CRAN

Date/Publication 2020-02-29 13:40:06 UTC

Contents

get_k_best	2
Index	3

get_k_best

Murty's algorithm for k-best assignments

Description

Find k-best assignments for a given matrix (returns both solved matrices and costs).

Usage

```
get_k_best(
  mat,
  k_best = NULL,
  algo = "hungarian",
  by_rank = FALSE,
  objective = "min",
  proxy_Inf = 10000000L
)
```

Arguments

mat	Square matrix (N x N) in which values represent the weights.
k_best	How many best scenarios should be returned. If by_rank = TRUE, this equals best ranks.
algo	Algorithm to be used, either 'lp' or 'hungarian'; defaults to 'hungarian'.
by_rank	Should the solutions with same cost be counted as one and stored in a sublist? Defaults to FALSE.
objective	Should the cost be minimized ('min') or maximized ('max')? Defaults to 'min'.
proxy_Inf	What should be considered as a proxy for Inf? Defaults to 10e06; if objective = 'max' the sign is automatically reversed.

Value

A list with solutions and costs (objective values).

Examples

```
set.seed(1)
mat <- matrix(sample.int(15, 10*10, TRUE), 10, 10)

get_k_best(mat, 3)
```

Index

`get_k_best`, [2](#)