

Package ‘naptime’

July 22, 2025

Type Package

Title A Flexible and Robust Sys.sleep() Replacement

Version 1.3.1

Date 2025-04-07

Description Provides a near drop-in replacement for base::Sys.sleep() that allows more types of input to produce delays in the execution of code and can silence/prevent typical sources of error.

License GPL-2

Imports methods, lubridate

Suggests testthat, covr

URL <https://github.com/russellpierce/naptime>

BugReports <https://github.com/russellpierce/naptime/issues>

RoxygenNote 7.3.2

Encoding UTF-8

NeedsCompilation no

Author Russell S. Pierce [aut, cre],
Timothy Gann [aut]

Maintainer Russell S. Pierce <russell.s.pierce@gmail.com>

Repository CRAN

Date/Publication 2025-04-07 21:10:02 UTC

Contents

naptime	2
Index	4

naptime*Safe sleep function*

Description

Acceptable inputs:

- numeric: time in seconds to nap
- POSIXct: time at which the nap should stop (timezone is respected)
- character: Date or date time at which nap should stop formatted as yyyy-mm-dd hh:mm:ss, time zone is assumed to be Sys.timezone() and hh:mm:ss is optional as three formats may be missing, cf. lubridate::ymd_hms().
- Period: time from now at which the nap should stop
- difftime: difference in time to nap
- logical: If TRUE, nap for default duration, otherwise don't nap.
- NULL: don't nap
- generic: error or nap for default duration depending on the option naptime.permissive

Usage

```
naptime(time, permissive = getOption("naptime.permissive", permissive_default))

## S4 method for signature 'numeric'
naptime(time, permissive = getOption("naptime.permissive", permissive_default))

## S4 method for signature 'Period'
naptime(time, permissive = getOption("naptime.permissive", permissive_default))

## S4 method for signature 'POSIXct'
naptime(time, permissive = getOption("naptime.permissive", permissive_default))

## S4 method for signature 'difftime'
naptime(time, permissive = getOption("naptime.permissive", permissive_default))

## S4 method for signature 'logical'
naptime(time, permissive = getOption("naptime.permissive", permissive_default))

## S4 method for signature 'NULL'
naptime(time, permissive = getOption("naptime.permissive", permissive_default))

## S4 method for signature 'character'
naptime(time, permissive = getOption("naptime.permissive", permissive_default))
```

Arguments

time	Time to sleep, polymorphic type inputs, leaning towards units as 'seconds'
permissive	An optional argument to override the <code>naptime.permissive</code> option for this call of the <code>naptime</code> function

Details

The default duration is set with a numeric for the option `naptime.default_delay` in seconds (default: 0.1) Whether a generic input is accepted is determined by the option `naptime.permissive` (default: FALSE)

Value

NULL; A side effect of a pause in program execution

Examples

```
## Not run:  
naptime(1)  
naptime(difftime("2016-01-01 00:00:01", "2016-01-01 00:00:00"))  
  
## End(Not run)
```

Index

`naptime`, [2](#)
`naptime,character-method (naptime)`, [2](#)
`naptime,difftime-method (naptime)`, [2](#)
`naptime,logical-method (naptime)`, [2](#)
`naptime,NULL-method (naptime)`, [2](#)
`naptime,numeric-method (naptime)`, [2](#)
`naptime,Period-method (naptime)`, [2](#)
`naptime,POSIXct-method (naptime)`, [2](#)