

Package ‘natcpp’

July 22, 2025

Type Package

Title Fast C++ Primitives for the 'NeuroAnatomy Toolbox'

Version 0.1.0

Description Fast functions implemented in C++ via 'Rcpp' to support the 'NeuroAnatomy Toolbox' ('nat') ecosystem. These functions provide large speed-ups for basic manipulation of neuronal skeletons over pure R functions found in the 'nat' package. The expectation is that end users will not use this package directly, but instead the 'nat' package will automatically use routines from this package when it is available to enable large performance gains.

License GPL (>= 3)

URL <https://github.com/natverse/natcpp>

BugReports <https://github.com/natverse/natcpp/issues>

Imports Rcpp (>= 1.0.6)

Suggests spelling, testthat (>= 3.0.0)

LinkingTo Rcpp

Config/testthat/edition 3

Encoding UTF-8

Language en-GB

RoxygenNote 7.1.1

NeedsCompilation yes

Author Gregory Jefferis [aut, cre] (ORCID:
<<https://orcid.org/0000-0002-0587-9355>>)

Maintainer Gregory Jefferis <jefferis@gmail.com>

Repository CRAN

Date/Publication 2021-07-13 14:50:02 UTC

Contents

c_EdgeListFromSegList	2
c_listlengths	3
c_seglengths	3
c_topntail	4
Index	5

c_EdgeListFromSegList *Turn a segment list into an edgelist suitable for constructing an ngraph*

Description

Turn a segment list into an edgelist suitable for constructing an ngraph

Usage

c_EdgeListFromSegList(L)

Arguments

L a list containing integer vectors from as.seglist

Details

It is up to the caller to generate the seglist. Note that isolated points will be dropped since they have no edges.

Value

An integer matrix of N rows and 2 columns

Examples

```
## Not run:
library(nat)
# make a neuron with multiple subtrees
n=prune_vertices(Cell07PNs[[1]], 48L)
# Must use flatten=T if including all subtrees
sl=as.seglist(n, all = TRUE, flatten = TRUE)
c_EdgeListFromSegList(sl)

## End(Not run)
```

c_listlengths	<i>A simple function to compute the lengths of the elements of an R list</i>
---------------	--

Description

A simple function to compute the lengths of the elements of an R list

Usage

```
c_listlengths(L)
```

Arguments

L	a list
---	--------

Details

This is equivalent to the base::lengths however it is much faster for long lists (and somewhat slower for short ones).

Value

An integer vector containing the length of each element of L

c_seglengths	<i>Compute summed segment lengths or total cable</i>
--------------	--

Description

c_seglengths computes the summed segment length equivalent to nat::seglengths(sumsegment = T)

c_total_cable computes the summed total cable for a whole neuron. It's intended use is the nat::summary.neuron function.

Usage

```
c_seglengths(sl, x, y, z)
```

```
c_total_cable(sl, x, y, z)
```

Arguments

sl	A seglist with 1-indices into vectors x,y,z
x, y, z	Numeric vectors with 3D coordinate data (which could be columns from a data frame)

c_topntail

Find the first and last elements of all vectors in a list

Description

c_topntail returns an 2xN matrix containing the start and end of each of the vectors in the input list. Length 0 vectors are ignored, while length 1 vectors are duplicated

For c_topntail_list, a list of the same length as L having the same elements when their length is <=2 or the first and last elements when length>2.

Usage

```
c_topntail(L)
```

```
c_topntail_list(L)
```

Arguments

L a list containing integer vectors, typically a seglist

Value

For c_topntail an integer matrix. For c_topntail_list a list.

Index

`c_EdgeListFromSegList`, 2
`c_listlengths`, 3
`c_seglengths`, 3
`c_topntail`, 4
`c_topntail_list (c_topntail)`, 4
`c_total_cable (c_seglengths)`, 3