

Package ‘optigrab’

July 22, 2025

Type Package

Title Command-Line Parsing for an R World

Version 0.9.2.1

Date 2019-01-05

Maintainer Christopher Brown <chris.brown@decisionpatterns.com>

URL <https://github.com/decisionpatterns/optigrab>

BugReports <https://github.com/decisionpatterns/optigrab/issues>

Description Parse options from the command-line using a simple, clean syntax.
It requires little or no specification and supports short and long options,
GNU-, Java- or Microsoft- style syntaxes, verb commands and more.

Depends R (>= 3.0.0), methods

Imports stringi (>= 0.4.1), magrittr (>= 1.5)

Suggests testthat (>= 0.9.1), knitr (>= 1.9), rmarkdown

License GPL (>= 3) | file LICENSE

LazyLoad no

VignetteBuilder knitr

RoxygenNote 6.1.1

Encoding UTF-8

Repository CRAN

NeedsCompilation no

Author Christopher Brown [aut, cre],
Daryl McCullough [aut],
Decision Patterns [cph]

Date/Publication 2019-01-07 18:40:03 UTC

Contents

gnu_style	2
is_flag	3
java_style	4
ms_style	4
optigrab	5
opt_assign	6
opt_expand	7
opt_fill	8
opt_get	9
opt_get_args	11
opt_get_path	12
opt_get_verb	12
opt_help	13
opt_split_args	14
opt_style	15
str_to_opts	16
this_file	17
Index	18

gnu_style	<i>GNU-style command line options</i>
-----------	---------------------------------------

Description

Functions for enabling GNU-style command-line option behavior.

Usage

gnu_style

Format

An object of class list of length 3.

Details

Functions for enabling GNU-style command-line options. GNU-style options are characterized by a single dash (-) before single character option flags and a double dash (--) before multiple character option flags.

By convention, gnu style options flags must begin with a letter; if numbers were allowed option flags would be ambiguous with negative option values.

References

[GNU Command Line Standards]<http://www.gnu.org/prep/standards/standards.html>

See Also

- Non-exported function *_flag_test, *_flag_to_name and *_name_to_flag
- [gnu_style](#)
- [java_style](#)
- [ms_style](#)

is_flag

*Determine if/which vector element are options flags***Description**

Determines if an element of a vector is an option flag (as opposed to a value) by checking against the option style

Usage

```
is_flag(x)
```

```
which.flag(x)
```

Arguments

x vector of options, for example commandArgs().

Details

is_flag and which.flag are internal functions not expected to be called directly.

They are used to identify which elements of the option vector are option names (as opposed to option values). Options are identified by getOptions('optigrab')\$style\$flag_test. By default, **optigrab** follows GNU-style command line arguments, i.e. those beginning with "--" or "-" and are set at the time of package loading.

Value

logical. indicating which arguments are flags.

numeric

Examples

```
optigrab:::is_flag( c( "--foo", "bar" ) )
optigrab:::is_flag( c( "--foo", "bar", "-f", "-b", "text" ) )

optigrab:::which.flag( c( "--foo", "bar" ) )
optigrab:::which.flag( c( "--foo", "bar", "-f", "-b", "text" ) )
```

java_style	<i>Java-style command line options</i>
------------	--

Description

Functions for enabling Java-style command-line option behavior.

Usage

java_style

Format

An object of class `list` of length 3.

Details

Functions for enabling Java-style command-line options. Java-style options are characterized by a single dash (-) before the option name.

By conventions, Java-style options cannot must begin with a upper or lower case letter.

See Also

- Non-exported function `*_flag_test`, `*_flag_to_name` and `*_name_to_flag`
- [gnu_style](#)
- [java_style](#)
- [ms_style](#)

ms_style	<i>Microsoft-style command line options</i>
----------	---

Description

Functions for enabling Microsoft-style command-line option behavior.

Usage

ms_style

Format

An object of class `list` of length 3.

Details

Functions for enabling Microsoft-style command-line options. Microsoft-style options are characterized by a single forward slash (/) before the option name.

Microsoft-style options can be supported by setting

See Also

- Non-exported function `*_flag_test`, `*_flag_to_name` and `*_name_to_flag`
- [gnu_style](#)
- [java_style](#)
- [ms_style](#)

Examples

```
opt_style(ms_style)
opt_get( "foo", opts=c("/foo", "bar") )
```

optigrab

Optigrab

Description

The optigrab package provides a function `opt_grab` to retrieve options/arguments from the command line. It is useful for running R in batch mode with `R CMD BATCH ...` or `Rscript`.

GNU-, Java- and Microsoft-style command line options are supported. GNU-style is the default.

See the *optigrab* vignettes or the github README file for details.

See Also

- [opt_get\(\)](#)
- [base::commandArgs\(\)](#)

Examples

```
## Not run:
opt_get( c("foo", "f"))

## End(Not run)

opts <- c( "--flag", "bar" )
flag <- opt_get( c("foo", "f"), opts=opts ) # bar
```

opt_assign	<i>Parse options and assign values</i>
------------	--

Description

Combines `opt_get` and `assign` for convenience.

Usage

```
opt_assign(x, pos = 1, inherits = FALSE, name = x, ...,
  assign.na = FALSE)
```

```
opt_assign_all(x, ..., assign.na = FALSE)
```

Arguments

<code>x</code>	character or list; variable names or alias. If no coercion is done, and the first element of a character vector of length greater than one will be used, with a warning.
<code>pos</code>	where to do the assignment. By default, assigns into the current environment. See 'Details' for other possibilities.
<code>inherits</code>	logical; should the enclosing frames of the environment be inspected? This argument is supplied to <code>base::assign()</code> .
<code>name</code>	character; name(s) of option as passed to <code>opt_get</code> . (Default: 'x')
<code>...</code>	arguments passed to <code>opt_get</code>
<code>assign.na</code>	logical; whether NA can be assigned. (Default: FALSE) <code>opt_assign</code> combines <code>opt_get</code> and <code>assign</code> in one call. The <code>name</code> argument is passed as <code>opt_get(name=...)</code> ; it defaults to <code>x</code> so it is generally not needed. <code>opt_assign_all</code> does multiple assignments but does not allow for a names arguments. Values are names by <code>x</code> .

See Also

- `opt_get()`
- `base::assign()`

Examples

```
opt_assign( "foo", opts=c("--foo","bar") )
opt_assign( c("foo","f"), opts=c("--foo","baz") )
```

opt_expand	<i>Expand opts to full vector</i>
------------	-----------------------------------

Description

Expand option vector to split names from values. This is an internal function and should generally not be called directly.

Usage

```
opt_expand(opts = commandArgs())
```

Arguments

opts character vector of arguments. (Default: `base::commandArgs()`)

Details

opt_expand does two things:

#1. Removes values preceding and including --args. #2. Splits and value containing an equal ('=') sign.

Note

non-exported

See Also

- `opt_grab()`
- `base::commandArgs()`

Examples

```
optigrab:::opt_expand()  
optigrab:::opt_expand( opts=c( "--foo", "bar" ) )
```

opt_fill

opt_fill

Description

Fill a recursive structure with command-line arguments

Usage

```
opt_fill(x, opts = commandArgs(), style = getOption("optigrab")$style)
```

Arguments

x	list-like (recursive)) object with names to use as a template.
opts	character command-line option list (Default: <code>commandArgs()</code>)
style	string; the command-line style (Default: <code>getOption('optigrab')\$style</code>)

Details

`opt_fill` uses `x` as a template of values to be retrieved. Named elements of `x` are retrieved from the command line using `opt_get()`. Values are coerced to the type/class of the elements of `x`.

This gives a handy way of defining and retrieving all setting at once overriding the defaults.

`opt_fill` is similar to `utils::modifyList()` but does not work recursively.

Value

(A copy of) `x`, with values filled from the command-line. If `x` is a reference structure, this is done by reference, returning the object invisibly.

See Also

`opt_get()` `utils::modifyList()`

Examples

```
defaults <- list( foo="a", bar=1 )

opt_fill( defaults, opts=c( '--foo', 'command-line-foo' ))
opt_fill( defaults, opts=c( '--foo', 'command-line-foo', '--bar', '9999' ))

defaults <- as.environment(defaults)
opt_fill( defaults, opts=c( '--foo', 'env-fill', '--bar', '555' ))

str( as.list(defaults) )
```

opt_get

Get option's values from the command-line

Description

Returns value(s) from the command-line associated with the desired option.

Usage

```
opt_get(name, default, n, required = FALSE, description = NULL,
        opts = commandArgs(), style = getOption("optigrab")$style)
```

```
opt_get_gnu(flag, ...)
```

```
opt_get_ms(flag, ...)
```

```
opt_get_java(flag, ...)
```

```
opt_grab(flag, n = 1, opts = commandArgs())
```

Arguments

name	character; vector of possible synonymes for the "flag" that identifies the option.
default	any; the value(s) provided if the flag is not found (default: NA)
n	integer; number of values to retrieve. See Details. (default: determined by default, see Details below.)
required	logical; whether the value is required. If not found or an incorrect, number of values are found, an error is thrown. (default: FALSE)
description	(character) message to be printed with opt_help
opts	character; vector to parse for options (default: commandArgs())
style	list; list of functions that define the parsing style
flag	character; vector of possible synonyms for the "flag" that identifies the option. These should be given as they would exactly appear on the command line.
...	additional arguments passed to opt_grab

Details

These functions support parsing of command arguments work when using Rscript, a #! on linux systems or R CMD BATCH. By default, they closely follows the ubiquitous GNU standards for command-line interfaces. opt_grab is the workhorse that does the actual parsing. It returns the options values or NA if it cannot discern them. It is currently exported, but this may change in future version to be an internal function. Its interface is not guarantted. The user should use opt_get instead.

opt_get supports default values, automated guessing for n and (attempts a) coercion of the return values to the correct class.

Value

opt_grab always returns a character; it is either the value for the flags or NA_character_ if they cannot be parsed.

opt_get returns a value the command-line value as specified by the arguments or produces an error if the value could not be determined and required==TRUE.

Selecting n

Except in rare-cases, the user should not have to specify n. This is determined from the value of default.

If default is a logical value, i.e. TRUE or FALSE, n is assumed to take no arguments. Presents of the flag on the command line will return TRUE, absense of the flag returns false.

If default is another type than logical, n is selected as length(default).

If default is missing, n is 1.

automatic coercion

Command-line arguments are character vectors. If default is supplied then the opt_get attempts to coerce the values it returns to class(default). The user might wish to supply the correct methods to handle the conversions.

side-effects

opt_grab has the additional side-effect of keeping track of the arguments. This is useful for keeping track of

flag is used to identify the command line flag. It can include all synonyms for the flags.

n the number of value(s) to retrieve from the command line. If n=0, then a logical value is returned indicating whether the flag exists

required indicates if a value is required. If the the flag is not found and there is no default given or if there is not the correct number of value(s) an error is raised.

opts is the vector from which options are parsed. By default, this is commandArgs().

References

[GNU Command Line Standards](#)

See Also

[commandArgs\(\)](#)

Examples

```
opts <- c( '--foo', 'bar' )

opt_get('foo')
opt_get( c('foo'), opts=opts )
opt_grab( c('--foo'), opts=opts )
```

```

opt_get_ms( c('foo'), opts=c('/foo', 'bar' ) )
opt_get_java( c('foo'), opts=c('-foo', 'bar' ) )

# Using pipes:
## Not run:
  c('foo', 'f') %>% opt_get('bar')

## End(Not run)

```

opt_get_args

Return arguments to Rscript

Description

Arguments to a script are those following the `--args` argument.

Usage

```
opt_get_args(opts = commandArgs())
```

Arguments

opts character; vector of arguments, (Default: `commandArgs()`)
Returns the user provided arguments, i.e. those following (the first) `--args` flag. This is identical to what is done by `commandArgs( trailingOnly = TRUE )` does. This is included an used since it supports testing/modifying the `commandArgs` array.

Value

character; vector stripping elements preceding and including (the first) `--args` flag.

See Also

- [base::commandArgs\(\)](#)
- [opt_grab\(\)](#)

Examples

```

opt_get_args()
opt_get_args( opts=c( "Rscript", "-a", "-b", "--args", "-c", 3, "-d" ) ) # "-c" "3" "-d"
opt_get_args( opts=c( "-a", "-b", "--args", "-c", "--args", "-d" ) ) # "-c" "-d"
opt_get_args( opts=c( "--foo", "bar" ) )

```

opt_get_path	<i>Get path current running script</i>
--------------	--

Description

Get path current running script

Usage

```
opt_get_path(opts = commandArgs(), full.name = FALSE)
```

Arguments

opts	character; cector from which to parse options (default: commandArgs())
full.name	boolean; expand to full path(?)

This function is deprecated, use this_file instead.

Value

character; path to Rscript or NA if there isn't one.

References

<http://stackoverflow.com/questions/1815606/rscript-determine-path-of-the-executing-script>

See Also

- [opt_grab\(\)](#)
- [base::commandArgs\(\)](#)

Examples

```
optigrab:::opt_get_path()
```

opt_get_verb	<i>Get verb from the command line</i>
--------------	---------------------------------------

Description

Return the verb for the application. The verb is the first argument that is not part of an option.

Usage

```
opt_get_verb(opts = commandArgs())
```

Arguments

opts character; Vector from which to parse options (default: `commandArgs()`)

Details

Some applications such as *git* support command verbs, e.g. push, fetch, etc. These style arguments can be retrieved by `opt_get_verb`.

`opt_get_verb` look for the first unaccounted for options (after `--args`). The number of options needed by each flags is determined by and saved by calls to `opt_get()`. See the details to see how `n` is automatically determined. When not explicitly defined the number of options needed by each flag is 1. Becasue of this, it convention to call `opt_get_verb` after all `opt_get` calls. For most simple applications, it likely doesn't matter.

Value

character of length 1; the verb found from the command-line. NA if a verb cannot be identified.

Assumptions

`opt_get_verb` assumes any flags occurring before the verb have exactly 1 value. A command line such as "> myscript -verbose verb" will be misparsed; the code will assume that "verb" is the value of the flag "-verbose"

See Also

- `opt_get()`
- `base::commandArgs()`

Examples

```
opt_get_verb() # commandArgs()
```

opt_help

Automatic usage/help information

Description

Prints program usage information and, if used non-interactively, exits.

Usage

```
opt_help(name = c("help", "?"), opts = commandArgs())
```

Arguments

name character; vector of names/aliases to use

opts character; vector from which to parse options (default: `commandArgs()`)

Usage information is generated from `opt_get` calls made prior to `opt_help`. `opt_help` shuded will will not be shown. It is considered best practice to handle all option parsing in a block at the beginning of the application. `opt_help()` would be best placed at the end of that block

Value

logical; returns TRUE if command-line options contain a help flag, FALSE otherwise. Mainly `opt_help` is used for side-effects of printing usage/help information,

See Also

[base::commandArgs\(\)](#)

Examples

```
opts <- c( "--foo", "bar")
optigrab:::opt_grab( "--foo")
optigrab:::opt_help()
```

opt_split_args	<i>Split command arguments</i>
----------------	--------------------------------

Description

Splits command argument vector to name, value pairs. This is an internal function and should generally not be called directly.

Usage

```
opt_split_args(opts = commandArgs())
```

Arguments

opts character; vector of arguments. (Default: `commandArgs()`)

`opt_split_args` splits and value containing an equal (=) sign

Note

non-exported

See Also

- [opt_grab\(\)](#)

Examples

```
optigrab:::opt_split_args()
optigrab:::opt_split_args( opts=c( "--foo=hello", "-b=goodbye" ) )
```

opt_style

*Get or set the optigrab style***Description**

Get or sets the optigrab style

Usage

```
opt_style(style)
```

Arguments

style named list; containing the following functions: `flag_test`, `flag_to_name` and `name_to_flag`

If style is not specified, `opt_style` gets the current optigrab style. If style is provided, it must be a named list containing three functions `flag_test`, `flag_to_name` and `name_to_flag`.

Value

If style is not provided, returns a list of styles, otherwise used for the side-effect of setting the option

flag_test

Accepts a character vector and returns a logical vector indicating whether the elements are flags.

flag_to_name

Accepts a character vector of flags and turns them into variable names, usually by stripping delimiters that indicate that they are flags

name_to_flag

Accepts a character vector of names and transforms them into the flags that would appear on the command line. This is used by `opt_grab()`.

See Also

[gnu_style](#), [java_style](#) or [ms_style](#)

Examples

```

opt_style()
opt_style( optigrab::gnu_style )
opt_style( optigrab::java_style )
opt_style( optigrab::ms_style )

```

str_to_opts

Split a string bases on whitespace

Description

Split a string based on whitespace ignore single- and double quoted entries

Usage

```
str_to_opts(x = character())
```

Arguments

x character; string to parse as if it is a command line
This is an internal function used predominantly for testing. It might be deprecated in the near future.

Value

A character array that could be similar to that provided by `commandArgs`.

Note

not-exported, by design

See Also

[base::commandArgs\(\)](#)

Examples

```

## Not run:
str <- 'cmd -t "Say Anything" --character \'Lloyd Dobler\''
str_to_opts(str)
split_ws_nonquote(str)

## End(Not run)

```

this_file	<i>this_file</i>
-----------	------------------

Description

Name or path to the current file

Usage

```
this_file(opts = commandArgs(), local = TRUE, full.path = TRUE)
```

Arguments

opts	character; vector of arguments. (Default: <code>commandArgs()</code>)
local	logical; if TRUE returns the most currently sourced script as opposed to the original/first source script. (Default: TRUE)
full.path	logical; Whether to return the full path to the sourced file. (Default: TRUE)

Details

`this_file` returns the name or path of the executing file whether the file was invoked from **Rscript** or in an interactive session. Further it source

Argument `local` controls whether it is the current file (TRUE) or the original, top-level file.

Value

one-element character vector with the path to the current file; returns NA is in an interactive session not in a file.

References

<http://stackoverflow.com/questions/1815606/rscript-determine-path-of-the-executing-script>

See Also

- [opt_grab\(\)](#)

Examples

```
this_file()
```

Index

- * **datasets**
 - gnu_style, [2](#)
 - java_style, [4](#)
 - ms_style, [4](#)
- * **package**
 - optigrab, [5](#)
- base::assign(), [6](#)
- base::commandArgs(), [5](#), [7](#), [11–14](#), [16](#)
- commandArgs(), [10](#)
- gnu_style, [2](#), [3–5](#), [15](#)
- is_flag, [3](#)
- java_style, [3](#), [4](#), [4](#), [5](#), [15](#)
- ms_style, [3](#), [4](#), [4](#), [5](#), [15](#)
- opt_assign, [6](#)
- opt_assign_all (opt_assign), [6](#)
- opt_expand, [7](#)
- opt_fill, [8](#)
- opt_get, [9](#)
- opt_get(), [5](#), [6](#), [8](#), [13](#)
- opt_get_args, [11](#)
- opt_get_gnu (opt_get), [9](#)
- opt_get_java (opt_get), [9](#)
- opt_get_ms (opt_get), [9](#)
- opt_get_path, [12](#)
- opt_get_verb, [12](#)
- opt_grab (opt_get), [9](#)
- opt_grab(), [7](#), [11](#), [12](#), [14](#), [15](#), [17](#)
- opt_help, [13](#)
- opt_split_args, [14](#)
- opt_style, [15](#)
- optigrab, [5](#)
- optigrab-package (optigrab), [5](#)
- str_to_opts, [16](#)
- styles (opt_style), [15](#)
- this_file, [17](#)
- utils::modifyList(), [8](#)
- which.flag (is_flag), [3](#)