

Package ‘patientProfilesVis’

July 23, 2025

Type Package

Title Visualization of Patient Profiles

Version 2.0.9

Date 2024-06-18

Description Creation of patient profile visualizations for exploration, diagnostic or monitoring purposes during a clinical trial. These static visualizations display a patient-specific overview of the evolution during the trial time frame of parameters of interest (as laboratory, ECG, vital signs), presence of adverse events, exposure to a treatment; associated with metadata patient information, as demography, concomitant medication. The visualizations can be tailored for specific domain(s) or endpoint(s) of interest. Visualizations are exported into patient profile report(s) or can be embedded in custom report(s).

Imports clinUtils, ggplot2 ($\geq 3.0.0$), plyr, cowplot, tools, reshape2, knitr, grid, stringr, parallel, gridExtra, scales, utils

Suggests pander, shiny, testthat, grDevices, rmarkdown, gtable, pdftools, viridisLite

URL <https://github.com/openanalytics/patientProfilesVis>

BugReports <https://github.com/openanalytics/patientProfilesVis/issues>

License MIT + file LICENSE

RoxygenNote 7.3.1

VignetteBuilder knitr

SystemRequirements latex, cairo (for report creation)

NeedsCompilation no

Author Laure Cougnaud [aut, cre],
Margaux Faes [rev] (tests),
Open Analytics [cph]

Maintainer Laure Cougnaud <laure.cougnaud@openanalytics.eu>

Repository CRAN

Date/Publication 2024-06-18 09:00:02 UTC

Contents

addReferenceLinesProfilePlot	3
checkTimeExpand	4
checkTimeTrans	5
checkVar	5
combineVerticallyGGplot	6
convertAesVar	7
countNLines	7
createSubjectProfileReport	8
defineIndex	11
filterData	12
filterMissingInVar	14
formatParamVarTextPlot	15
formatTimeInterval	16
formatTimeLim	19
getAesScaleManual	20
getColorPalettePatientProfile	20
getMaxNLinesCombinePlot	21
getNLinesLabel	22
getNLinesLegend	23
getNLinesSubjectProfile	23
getOptimalColWidth	24
getPageVar	25
getPathTemplate	26
getShapePalettePatientProfile	26
getSplitVectorByInt	27
getTimeLimSubjectProfilePlots	28
getTimeTrans	29
getWidthPlot	30
interactionWithMissing	31
isSubjectProfileTimeVariant	31
patientProfilesVis-common-args	32
patientProfilesVis-palette	33
prepareSubjectProfile	34
sortSubjects	35
subjectProfileCombine	36
subjectProfileEventPlot	38
subjectProfileExport	41
subjectProfileIntervalPlot	42
subjectProfileLinePlot	47
subjectProfileReportFormat	50
subjectProfileTextPlot	51
subjectProfileTheme	54

addReferenceLinesProfilePlot

Add reference lines to a profile plot

Description

Add reference lines to a profile plot

Usage

```
addReferenceLinesProfilePlot(
  gg,
  subjectVar = "USUBJID",
  refLines = NULL,
  refLinesData = NULL,
  refLinesTimeVar = NULL,
  refLinesLabelVar = NULL,
  refLinesColor = "black",
  refLinesLinetype = "dotted",
  timeLim = NULL,
  addLabel = FALSE
)
```

Arguments

gg	ggplot2 with a subject profile plot for a specific subject (and page) (subset of the output of the subjectProfile[X]Plot)
subjectVar	String, variable of data with subject ID
refLines	(optional) nested list with details for reference line(s). Each sublist contains: <ul style="list-style-type: none"> • (required) 'label': string with label for the reference line • (required) 'time': unique time (x) coordinate for the reference line • (optional) 'color': color for the reference line, 'black' by default • (optional) 'linetype': linetype for the reference line, 'dotted' by default
refLinesData	data.frame with data from which the reference line(s) should be extracted
refLinesTimeVar	string, variable of refLinesData with time for reference line(s)
refLinesLabelVar	string, variable of refLinesData with label for reference line(s)
refLinesColor	vector of length 1 with default color for reference line(s)
refLinesLinetype	vector of length 1 with default linetype for reference line(s)
timeLim	vector of length 2 with time limits. This is used to set the limits to the plot containing the reference lines labels (if requested).
addLabel	logical, if TRUE (FALSE by default) add the label of the reference line(s) at the bottom of the plot

Value

If addLabel is:

- TRUE: list with:
 - 'gg': `ggplot2` plot with reference lines
 - 'ggRefLines': `ggplot2` plot containing only the labels at the specified position
- FALSE: `ggplot2` plot with reference lines

Author(s)

Laure Cougnaud

checkTimeExpand	<i>Check if some of the modules are time expanded, and extract maximum time expand for each module.</i>
-----------------	---

Description

Check if some of the modules are time expanded, and extract maximum time expand for each module.

Usage

```
checkTimeExpand(listPlots, timeLim = NULL)
```

Arguments

listPlots	list of plots
timeLim	time limits

Value

List of time expand for each module (named by listPlots)

Author(s)

Laure Cougnaud

checkTimeTrans	<i>Check if the subject profiles are time transformed, and if some of the plots to align (with specified timeLim) have compatible time transformation alignments.</i>
----------------	---

Description

Check if the subject profiles are time transformed, and if some of the plots to align (with specified timeLim) have compatible time transformation alignments.

Usage

```
checkTimeTrans(listPlots, timeLim = NULL)
```

Arguments

listPlots	list of plots
timeLim	time limits

Value

List of time transformation for each module (named by listPlots)

Author(s)

Laure Cougnaud

checkVar	<i>Check if specified variable(s) are present in the data.</i>
----------	--

Description

Check if specified variable(s) are present in the data.

Usage

```
checkVar(var, data)
```

Arguments

var	Character vector with variable(s) of interest.
data	Data.frame with data.

Value

No returned value, an error message is triggered if some variable(s) are not available in the data.

Author(s)

Laure Cougnaud

combineVerticallyGGplot

Combine vertically multiple [ggplot](#).

Description

If the different modules for a subject don't fit in the page, there are automatically split in multiple pages. The margins are extracted across plots to ensure that plots will be probably aligned.

Usage

```
combineVerticallyGGplot(
  listPlots,
  maxNLines = NULL,
  nCores = 1,
  shiny = FALSE,
  verbose = FALSE,
  reportPerSubject = FALSE
)
```

Arguments

<code>listPlots</code>	listPlots per subject as created inside the subjectProfileCombine function.
<code>maxNLines</code>	Maximum number of lines for a combined plot, to fit in the page height. When the different visualizations are combined for each subject, they will be allocated to different pages if the number of lines of the combined visualization is higher than this number.
<code>nCores</code>	Integer containing the number of cores used for the computation (1 by default). If more than 1, computation is parallelized, in this case the package <code>parallel</code> is required.
<code>shiny</code>	logical, set to TRUE (FALSE by default) if the report is generated from a Shiny application. Messages during report creation will be included in the Shiny interface, and it will be mentioned at the end of the report. In this case, the shiny package should be available.
<code>verbose</code>	logical, if TRUE print messages during execution
<code>reportPerSubject</code>	Logical, if TRUE (FALSE by default) export a subject profile report by subject.

Value

a list (by subject) of list (by page) of [ggplot](#) object

Author(s)

Laure Cougnaud

convertAesVar	<i>Convert aesthetic variable for patient profile visualization.</i>
---------------	--

Description

This converts the empty values ("") to NA. The variable is then converted as a factor. Missing values are also included in the levels of the factor, to ensure that missing values are displayed in the legend of the plot.

Usage

```
convertAesVar(data, var)
```

Arguments

data	data.frame with data
var	variable of data with aesthetic

Value

updated factor var variable

Author(s)

Laure Cougnaud

countNLines	<i>Count number of lines ('\\n' character) per character in a vector</i>
-------------	--

Description

Count number of lines ('\\n' character) per character in a vector

Usage

```
countNLines(x)
```

Arguments

x	character vector
---	------------------

Value

numeric vector with same length than x containing number of lines in each element

Author(s)

Laure

createSubjectProfileReport
Create subject profile report.

Description

By default all subjects available in at least one module of listPlots are considered. If only a set of subjects are of interest, these are specified either:

- directly with the subject IDs of interest via subjectSubset
- by extracting subjects with a specific value (subjectSubsetValue) in a variable (subjectSubsetVar) in a specific dataset subjectSubsetData

Usage

```
createSubjectProfileReport(
  listPlots,
  timeLim = NULL,
  timeAlign = "all",
  timeAlignPerSubject = "none",
  refLines = NULL,
  refLinesData = NULL,
  refLinesTimeVar = NULL,
  refLinesLabelVar = NULL,
  bookmarkData = NULL,
  bookmarkVar = NULL,
  subjectSortData = bookmarkData,
  subjectSortVar = bookmarkVar,
  subjectSortDecreasing = FALSE,
  subjectVar = "USUBJID",
  subjectSubset = NULL,
  subjectSubsetData = NULL,
  subjectSubsetVar = NULL,
  subjectSubsetValue = NULL,
  subjectSample = NULL,
  seed = 123,
  subset = NULL,
  outputFile = "subjectProfile.pdf",
  exportFigures = FALSE,
```



```

    reportPerSubject = FALSE,
    exportBatchSize = NULL,
    labelVars = NULL,
    maxNLines = NULL,
    shiny = FALSE,
    formatReport = subjectProfileReportFormat(),
    verbose = FALSE,
    nCores = 1
  )

```

Arguments

listPlots	nested list of plots, as returned by the subjectProfileTextPlot , subjectProfileEventPlot , subjectProfileIntervalPlot or subjectProfileLinePlot functions.
timeLim	Time limits, as a numeric vector of length 2, or a list with time limits for each module, or nested list with time limits for each module and subject. If not specified, these are set to the time limits specified when creating each module (stored in <code>attributes(x)\$metaData\$timeLim</code>) otherwise to the range defined by <code>timeAlign</code> and <code>timeAlignPerSubject</code> . Note that this doesn't modify the geoms of the plots, it only extends the axis range. So for interval module(s) if the specified <code>timeLim</code> is smaller than the time limits in the input plot, no arrows are created in case that the time goes above/below specified <code>timeLim</code> (the segment is cut).
timeAlign	Character vector with time alignment across modules/subjects, either: <ul style="list-style-type: none"> • 'all' (by default): all plots have the same time limits • 'none': each of the plot (module*subject) has its own time limits • character vector with names of the modules which should have the same time limits (should correspond to the names of <code>listPlots</code>)
timeAlignPerSubject	Character vector, specifying if the plots should be aligned (or not) across subjects <ul style="list-style-type: none"> • 'none' (by default): all modules to align have the same time limit across subjects • 'all': all modules to align have different time limits per subject • character vector with subset of the modules to align per subject (should correspond to the names of <code>listPlots</code>) <p>Only the modules already specified in <code>timeAlign</code> can be aligned by subject.</p>
refLines	(optional) nested list with details for reference line(s). Each sublist contains: <ul style="list-style-type: none"> • (required) 'label': string with label for the reference line • (required) 'time': unique time (x) coordinate for the reference line • (optional) 'color': color for the reference line, 'black' by default • (optional) 'linetype': linetype for the reference line, 'dotted' by default
refLinesData	data.frame with data from which the reference line(s) should be extracted
refLinesTimeVar	string, variable of <code>refLinesData</code> with time for reference line(s)

<code>refLinesLabelVar</code>	string, variable of <code>refLinesData</code> with label for reference line(s)
<code>bookmarkData, bookmarkVar</code>	Data.frame with data containing information for the index, and character vector with corresponding variable(s) of interest. An index will be created at the end of the subject profile report. The index contains a section per variable, referencing the pages of the report containing subject profiles for each category/variable.
<code>subjectSortData</code>	Data.frame with data containing information on how the subjects should be sorted (by default same as <code>bookmarkData</code>): <ul style="list-style-type: none"> • in the report, in case one single report is created for all subjects • for the export, in case <code>reportPerSubject</code> is TRUE This data should contain <code>subjectSortVar</code> and <code>subjectVar</code> .
<code>subjectSortVar</code>	Character vector, variable(s) of <code>subjectSortData</code> indicating the order for the subjects in the report, (by default same as <code>bookmarkVar</code>).
<code>subjectSortDecreasing</code>	Logical, if TRUE (FALSE by default) subjects are sorted based on decreasing order of <code>subjectSortVar</code> .
<code>subjectVar</code>	String, variable of data with subject ID
<code>subjectSubset</code>	<code>subjectSubset</code> (optional) Character vector with subjects of interest (available in <code>subjectVar</code>), NULL by default.
<code>subjectSubsetData</code>	Data.frame used to select subset of subjects of interest.
<code>subjectSubsetVar</code>	String with variable of <code>subjectSubsetData</code> that should be considered to filter subjects. If not specified, all subjects available in <code>subjectSubsetData</code> are considered.
<code>subjectSubsetValue</code>	Character vector with value(s) of <code>subjectSubsetVar</code> of interest to filter subjects on.
<code>subjectSample</code>	(optional) Integer of length 1 with number of random subject(s) that should be considered in the specified subset dataset. By default, all specified subjects are considered (set to NULL).
<code>seed</code>	(optional) Integer of length 1 with seed used to select random subjects if <code>subjectSample</code> is specified (123 by default).
<code>subset</code>	Character vector with subjects of interest (among names of each list in <code>listPlots</code>).
<code>outputFile</code>	string, path to the output report
<code>exportFigures</code>	Logical, if TRUE (FALSE by default) the subject profile figures are also exported in pdf format in a 'figures' folder. Figures are named as <code>[subjectID]-[page].pdf</code>
<code>reportPerSubject</code>	Logical, if TRUE (FALSE by default) export a subject profile report by subject.

exportBatchSize	(optional) Integer, if specified, the patient-profile reports are created by batch of this number of subjects. This might speed up the export for a high number of subjects. Only available if report is created by subject (reportPerSubject is TRUE) and modules are not aligned across subjects (timeAlignPerSubject is 'all').
labelVars	Named character vector with variable labels (names are the variable code)
maxNLines	Maximum number of lines for a combined plot, to fit in the page height. When the different visualizations are combined for each subject, they will be allocated to different pages if the number of lines of the combined visualization is higher than this number.
shiny	logical, set to TRUE (FALSE by default) if the report is generated from a Shiny application. Messages during report creation will be included in the Shiny interface, and it will be mentioned at the end of the report. In this case, the shiny package should be available.
formatReport	list with parameters used to specify the format of the report, e.g. output of the subjectProfileReportFormat function
verbose	logical, if TRUE print messages during execution
nCores	Integer containing the number of cores used for the computation (1 by default). If more than 1, computation is parallelized, in this case the package <code>parallel</code> is required.

Value

The path(s) of the report(s) is returned invisibly, and the report is created at the location specified by `outputFile`.

If the report is created by subject, the name of the exported subject profile is built as: `[filename]-[subjectID].pdf`, with `[filename]` extracted from `outputFile`. Space and platform-specific file separator are replaced by a dash in the filename.

If no patient profiles are available in the input, nothing is returned and a warning is triggered.

Author(s)

Laure Cougnaud

defineIndex	<i>Define LaTeX index based on specified variable(s) of the dataset</i>
-------------	---

Description

Define LaTeX index based on specified variable(s) of the dataset

Usage

```
defineIndex(subjects, data, var, subjectVar = "USUBJID", labelVars = NULL)
```

Arguments

subjects	vector with subject IDs (based on the subjectVar variable)
data	data.frame with data containing information on which the index should be based
var	variable(s) of data of interest for the index
subjectVar	String, variable of data with subject ID
labelVars	Named character vector with variable labels (names are the variable code)

Value

list with elements:

- 'indexMake': string with LaTeX code for creation of index, to be included directly with `cat` in a knitr document (two backslashes)
- 'indexEntry': character vector, named with subject ID, containing LaTeX code for index for each subject specified in subjects parameter, to be included in a knitr document as text (four backslashes)
- 'indexPrint': string with LaTeX code for printing/inclusion of index, to be included directly with `cat` in a knitr document (two backslashes)

Author(s)

Laure Cougnaud

filterData	<i>Filter a dataset for records of interest, for use in the patient profiles.</i>
------------	---

Description

Data is filtered based on the following workflow:

1. The subset dataset (of data if not specified) is filtered based on subject variable and value (if specified).
2. If a external subset dataset is specified, only the subject IDs of this filtered dataset are considered.
3. The data is filtered based on the selected subjects, from subjectSubset (if specified) or from step 2.
4. The data is filtered based on a random selection of subjects, if subjectSample is specified.

This filtering workflow is used for all subject profile visualization functions of the package.

Usage

```
filterData(
  data,
  subsetData = NULL,
  subsetVar = NULL,
  subsetValue = NULL,
  subjectVar = "USUBJID",
  subjectSubset = NULL,
  subjectSample = NULL,
  seed = 123
)
```

Arguments

data	Data.frame with data
subsetData	(optional) Data.frame with extra dataset to filter on. This dataset is filtered, and only records from data with common subject IDs will be retained. If not specified, data is used.
subsetVar	(optional) String with variable of subset data to filter on. subsetValue should be specified too. If not specified, all records from the subset data are retained.
subsetValue	(optional) Character vector with value(s) of interest to retain in the filtered data. These values should be available in subsetVar. Missing values in the subject variable are not retained in the filtered data.
subjectVar	String, variable of data (and subset data) with subject ID.
subjectSubset	(optional) Character vector with subjects of interest (available in subjectVar), NULL by default.
subjectSample	(optional) Integer of length 1 with number of random subject(s) that should be considered, e.g. to check the created patient profiles for a subset of the data. By default, all specified subjects are considered (set to NULL).
seed	(optional) Integer of length 1 with seed used to select random subjects if subjectSample is specified (123 by default).

Value

possibly filtered dataset

Author(s)

Laure Cougnaud

Examples

```
library(clinUtils)

data(dataSDTMCDISCP01)
dataAll <- dataSDTMCDISCP01
```

```

# keep only a subset of subjects
# (e.g. to visualize specified patient profiles
# before creating them for all subject)
filterData(
  data = dataAll$AE,
  subjectSample = 2
)

# filter based on specified variable/value:
# only adverse events possibly related
filterData(
  data = dataAll$AE,
  subsetVar = "AEREL",
  subsetValue = "POSSIBLE"
)

# filter based on a different dataset:
# keep only adverse events for subjects in a specific treatment arm
filterData(
  data = dataAll$AE,
  subsetData = dataAll$DM,
  subsetVar = "ACTARM",
  subsetValue = "Placebo"
)

# filter based on subjects of interest
filterData(
  data = dataAll$AE,
  subjectSubset = c("01-701-1148", "01-701-1211")
)

```

filterMissingInVar	<i>Filter missing records in data in the time and y variables, with informative message.</i>
--------------------	--

Description

Filter missing records in data in the time and y variables, with informative message.

Usage

```

filterMissingInVar(
  data,
  var,
  varLab = getLabelVar(var, labelVars = labelVars),
  labelVars = NULL
)

```

Arguments

data	Data.frame with data.
var	String with variable of interest.
varLab	String, label for var.
labelVars	Named character vector with variable labels (names are the variable code)

Value

Update data with filtered records + message in the console.

Author(s)

Laure Cougnaud

formatParamVarTextPlot

Format text variables for the subject profile text plotting function.

Description

Text variables are wrapped across multiple lines if needed, and optionally sorted according to the levels of a grouping variable.

Usage

```
formatParamVarTextPlot(
  data,
  paramVar = NULL,
  paramValueVar = NULL,
  paramValueLab = NULL,
  paramGroupVar = NULL,
  revert = FALSE,
  width = formatReport$yLabelWidth,
  widthValue = ifelse(formatReport$landscape, 240, 190),
  formatReport = subjectProfileReportFormat(),
  table = FALSE,
  colWidth = NULL
)
```

Arguments

data	data.frame with data
paramVar	string, variable of data with parameter
paramValueVar	string, variable of data containing the parameter value.
paramValueLab	Character vector with labels for paramValueVar.

paramGroupVar	(optional) character vector with variable(s) of data with grouping. If specified, the parameters will be grouped by this(these) variable(s) in the y-axis.
revert	logical, if TRUE revert the order of the levels of the variable
width	max number of characters in the paramVar parameter.
widthValue	max number of characters in the paramValueVar parameter.
formatReport	list with parameters used to specify the format of the report, e.g. output of the subjectProfileReportFormat function
table	Logical, if TRUE the paramValueVar variables are displayed as table (so are not concatenated).
colWidth	Numeric vector with approximate width of each parameter value column for a table layout. For example in case two parameters are specified: <code>c(0.8, 0.2)</code> such as the first column takes 80% of plot area, and the second column 20%. Note: columns can be slightly bigger if their content is larger than the specified width. If not specified, column width is optimized based on the max length of the character in each column.

Value

data with reformatted paramVar and paramValueVar variables, with additional attribute: colWidth.

Author(s)

Laure Cougnaud

See Also

[subjectProfileTextPlot](#)

formatTimeInterval	<i>Set missing start/end time variable in the data.</i>
--------------------	---

Description

Set missing start/end time variable in the data.

Usage

```
formatTimeInterval(
  data,
  timeStartVar,
  timeStartLab = getLabelVar(timeStartVar, labelVars = labelVars),
  timeEndVar,
  timeEndLab = getLabelVar(timeEndVar, labelVars = labelVars),
  timeStartShapeVar = NULL,
```



```

timeEndShapeVar = NULL,
subjectVar = "USUBJID",
timeLim = NULL,
timeLimData = NULL,
timeLimStartVar = NULL,
timeLimStartLab = getLabelVar(timeLimStartVar, labelVars = labelVars),
timeLimEndVar = NULL,
timeLimEndLab = getLabelVar(timeLimEndVar, labelVars = labelVars),
timeImpType = c("minimal", "data-based", "none"),
labelVars = NULL
)

```

Arguments

data	Data.frame with data.
timeStartVar	String, variable of data with start of time interval.
timeStartLab	String, label for timeStartVar, displayed in a message and in the plot caption.
timeEndVar	String, variable of data with end of time interval.
timeEndLab	String, label for timeEndVar, displayed in a message and in the plot caption.
timeStartShapeVar	(optional) String, variable of data used for the shape of the symbol displayed at the start of the time interval. If not specified, default shape palette is used, see section 'Time interval representation'.
timeEndShapeVar	String, variable of data used for the shape of the symbol displayed at the end of the time interval. If not specified, default shape palette is used, see section 'Time interval representation'.
subjectVar	String, variable of data with subject ID
timeLim	(optional) Vector of length 2 with time limits (x-axis). If not specified, these are extracted from the minimum timeStartVar and maximum timeEndVar per subject. The time limits are stored as attributes of the plots, used to align the plots in the final report.
timeLimData	Data.frame with data used to impute time in case some time records are missing in data, see section: 'Time interval representation'.
timeLimStartVar	String, variable of timeLimData with start of the time interval.
timeLimStartLab	String, label for timeLimeStartVar, displayed in a message and in the plot caption.
timeLimEndVar	String, variable of timeLimData with end of the time interval.
timeLimEndLab	String, label for timeLimEndVar, displayed in a message and in the plot caption.
timeImpType	String with imputation type: 'minimal' (default), 'data-based' or 'none', see section: 'Time interval representation'. This imputation type is not used if a dataset used to impute time is specified.
labelVars	Named character vector with variable labels (names are the variable code)

Value

list with:

- 'data': Data with:
 - imputed timeStartVar and timeEndVar
 - new column 'timeStartStatus': character vector containing status of timeStartVar variable: 'Complete' or 'Missing start' or NA
 - new column 'timeEndStatus': character vector containing status of timeEndVar variable: 'Complete' or 'Missing end' or NA
- 'timeLim': vector of length 2 with minimum/maximum time limits across subjects.
- 'timeLimSpecified': vector of length 2 with time limits as specified by the user, either extracted from timeLim or from timeLimData. If missing value within timeLim, the corresponding minimum/maximum value in the (updated) data is used.
- 'timeShapePalette': Named character vector with symbols for the different time status
- 'caption': String with extra explanation concerning imputation that could be included in plot caption.

Time interval representation

In case the start or the end of the time interval contain missing values:

- if a dataset (timeLimData), start (timeLimStartVar) and end (timeLimEndVar) variables are specified:
 1. for each subject:
 - the minimum and maximum time values across these specified time variables are extracted
 - missing start values are replaced by the minimum time
 - missing end values are replaced by the maximum time
 2. if all values are missing for this subject, they are taken across subjects
- otherwise, depending on the imputation type (timeImpType):
 - 'minimal' (by default):
 - * if the start and the end of the interval are missing: no imputation is done, only the label is displayed
 - * if the start time is missing and the end time is not missing: start time is imputed with end time, and status is set to 'Missing start'
 - * if the end time is missing and the start time is not missing: end time is imputed with start time, and status is set to 'Missing end'
 - 'data-based' (default in version < 1.0.0): minimum/maximum values in the start/end time variables in the data are considered for the specific subject (if available). If there are missing for a specific subject, they are taken across subjects. If all time are missings, the range is set to 0 and Inf
 - 'none': no imputation is done

The symbols displayed at the start and end of the interval are:

- by default:

- a filled square labelled 'Complete' if the time is not missing
- a filled left-directed arrow in case of missing start time
- a filled right-directed arrow in case of missing end time
- if the variable(s) used for the shape of the start or end of the interval are specified (via timeStartShapeVar/timeEndShapeVar): labels are based on these variables, and a standard shape palette is used

The time limits are the same across subjects, and set to:

- timeLim if specified
- maximum time range in timeLimStartVar and timeLimEndVar in timeLimData if specified
- the maximum range on the data obtained after imputation of missing values

Author(s)

Laure Cougnaud

formatTimeLim	<i>Format specified timeLim.</i>
---------------	----------------------------------

Description

In case one of the limits is missing, the corresponding minimum/maximum across subjects is used.

Usage

```
formatTimeLim(
  data,
  subjectVar = "USUBJID",
  timeStartVar,
  timeEndVar,
  timeLim = NULL
)
```

Arguments

data	Data.frame with data.
subjectVar	String, variable of data with subject ID
timeStartVar	String, variable of data with start of time interval.
timeEndVar	String, variable of data with end of time interval.
timeLim	(optional) Vector of length 2 with time limits (x-axis). If not specified, these are extracted from the minimum timeStartVar and maximum timeEndVar per subject. The time limits are stored as attributes of the plots, used to align the plots in the final report.

Value

Numeric vector of length 2 or list of such element for each subject.

Author(s)

Laure Cougnaud

getAesScaleManual	<i>Get custom 'scale_[type]_manual' function</i>
-------------------	--

Description

Get custom 'scale_[type]_manual' function

Usage

```
getAesScaleManual(lab, palette, type)
```

Arguments

lab	label for the scale (title of the legend)
palette	named vector with color palette
type	string with type of scale, e.g. 'color'

Value

output of the 'scale_[type]_manual' function

Author(s)

Laure Cougnaud

getColorPalettePatientProfile	<i>Get a color palette for patient profile visualizations.</i>
-------------------------------	--

Description

This is a simple wrapper around [getColorPalette](#), with different defaults:

- inclusion of missing values by default (includeNA set to TRUE)

Usage

```
getColorPalettePatientProfile(..., includeNA = TRUE)
```

Arguments

- ... Arguments passed on to `clinUtils::getColorPalette`
- n Integer of length 1, number of elements in palette.
- x Vector with elements used for palette. If factor, the levels are used, otherwise the unique elements of the vector. Missing values are automatically removed, excepted if `includeNA` is set to `TRUE`.
- palette A vector of custom colors, or a function returning this vector from a specific number of colors.
Default is the the colorblind `viridis` color palette.
- includeNA Logical (`TRUE` by default), should NA elements be retained in the palette in case x is specified?

Value

Vector of shapes, named with the elements in x if x is specified.

Author(s)

Laure Cougnaud

See Also

[getColorPalette](#)

getMaxNLinesCombinePlot

Get maximum number of lines of a 'combined plot' for a specific document

Description

Get maximum number of lines of a 'combined plot' for a specific document

Usage

```
getMaxNLinesCombinePlot(
  heightLineIn = subjectProfileReportFormat()$heightLineIn,
  margin = subjectProfileReportFormat()$margin,
  landscape = subjectProfileReportFormat()$landscape,
  aspectRatio = subjectProfileReportFormat()$aspectRatio
)
```

Arguments

heightLineIn	Numeric of length 1 with height of a line in inches, 0.2 by default.
margin	Numeric of length 1, with margin in inches.
landscape	Logical, if TRUE the created report is in landscape format. FALSE by default, the report is created in portrait format.
aspectRatio	Numeric of length 1 (0.75 by default) with ratio between size of image in inches (derived from specified margin, landscape and heightLineIn) and real size for exported image.

Value

numeric with maximum height for plot

Author(s)

Laure Cougnaud

getNLinesLabel	<i>Get number of lines for specific label either from a ggplot2 object via gg or from the label via value</i>
----------------	---

Description

Get number of lines for specific label either from a [ggplot2](#) object via gg or from the label via value

Usage

```
getNLinesLabel(
  gg,
  value,
  elName = c("x", "y", "title", "caption"),
  elNLines = NULL
)
```

Arguments

gg	ggplot2 object
value	String with label value.
elName	string with name of label to extract, among 'x', 'y' and 'title'
elNLines	(optional) Named integer with number of lines, by default 2 for 'x'/'y', 3 for 'title' and 1 for caption.

Value

integer with (approximated) number of lines

Author(s)

Laure Cougnaud

getNLinesLegend	<i>Get number of lines in the legend, either from directly the ggplot2 object, or from the values of the legend (legendValues) and title (legendTitle)</i>
-----------------	--

Description

Get number of lines in the legend, either from directly the [ggplot2](#) object, or from the values of the legend (legendValues) and title (legendTitle)

Usage

```
getNLinesLegend(gg, values, title)
```

Arguments

gg	ggplot2 object
values	Vector with unique legend values
title	String, title for the plot.

Value

integer with (approximated) number of lines

Author(s)

Laure Cougnaud

getNLinesSubjectProfile	<i>Get approximately the number of 'lines' in the vertical direction of a subject profile.</i>
-------------------------	--

Description

This is extracted from the presence of labels in the y-axis, labels and title in the x-axis, general title and number of lines in the legend. Can be used to specify plot-specific height during the export.

Usage

```
getNLinesSubjectProfile(gg)
```

Arguments

`gg` [ggplot2](#) object, subset of the output of the `subjectProfile[X]Plot` function, for a particular subject/module/page.

Value

integer with (approximated) number of lines

Author(s)

Laure Cougnaud

<code>getOptimalColWidth</code>	<i>Get optimal column widths, based on the minimum word size and median number of characters in each column.</i>
---------------------------------	--

Description

Get optimal column widths, based on the minimum word size and median number of characters in each column.

Usage

```
getOptimalColWidth(
  data,
  widthValue = ifelse(formatReport$landscape, 240, 190),
  labels = NULL,
  formatReport = subjectProfileReportFormat()
)
```

Arguments

<code>data</code>	Data.frame with columns for which optimal width should be extracted.
<code>widthValue</code>	max number of characters in the <code>paramValueVar</code> parameter.
<code>labels</code>	(optional) Character vector with column labels for data.
<code>formatReport</code>	list with parameters used to specify the format of the report, e.g. output of the subjectProfileReportFormat function

Value

Numeric vector of `length(ncol(data))` with optimal widths.

Author(s)

Laure Cougnaud

getPageVar	<i>Get variable with page of the plot, used for automatic paging of a plot</i>
------------	--

Description

Get variable with page of the plot, used for automatic paging of a plot

Usage

```
getPageVar(
  data,
  var,
  typeVar = c("y", "panel"),
  formatReport = subjectProfileReportFormat(),
  title = TRUE,
  xLab = TRUE,
  caption = TRUE,
  paging = TRUE,
  table = FALSE
)
```

Arguments

data	data.frame with data
var	string, variable of data with variable for the y-axis
typeVar	string, type of the variable, either: 'y': the variable is displayed in the x-axis or 'panel': the variable is displayed as separated facets. This is used to compute height for each line of the plot.
formatReport	list with parameters used to specify the format of the report, e.g. output of the subjectProfileReportFormat function
title	logical, has the plot a title?
xLab	logical, has the plot a label for the x-axis?
caption	logical, has the plot a caption?
paging	Logical, if TRUE (by default), automatic paging is enabled, so patient profiles module too big to fit in one page will span multiple pages. Please note that the size of the graphic window (or report page) may need to be re-sized in order that the plot fits. If FALSE, the entire plot is included in one single page.
table	Logical, if TRUE the paramValueVar variables are displayed as table (so are not concatenated).

Value

input data with additional column 'pagePlot' containing the page for the plot

Author(s)

Laure Cougnaud

getPathTemplate	<i>Get path of the report template in the patientProfilesVis package</i>
-----------------	--

Description

Get path of the report template in the patientProfilesVis package

Usage

```
getPathTemplate(file)
```

Arguments

file	file name (with extension)
------	----------------------------

Value

String with path to the template in the installed patientProfilesVis package

Author(s)

Laure Cougnaud

getShapePalettePatientProfile	<i>Get a shape palette for patient profile visualizations.</i>
-------------------------------	--

Description

This is a simple wrapper around [getShapePalette](#), with different defaults:

- inclusion of missing values by default (includeNA set to TRUE)
- the extraction of shapes as text by default (asText set to TRUE)

Usage

```
getShapePalettePatientProfile(..., includeNA = TRUE, asText = TRUE)
```

Arguments

- ... Arguments passed on to [clinUtils::getShapePalette](#)
- n Integer of length 1, number of elements in palette.
 - x Vector with elements used for palette. If factor, the levels are used, otherwise the unique elements of the vector. Missing values are automatically removed, excepted if includeNA is set to TRUE.
 - palette A vector of custom shapes, or a function returning this vector from a specific number of shapes.
The vector should be a character if asText is set to TRUE.
Default is the [clinShapes](#) shape palette, or [clinShapesText](#) if asText is set to TRUE.
 - includeNA Logical (TRUE by default), should NA elements be retained in the palette in case x is specified?
 - asText Logical (TRUE by default), should the palette be expressed as integer (base R plot and ggplot2 compatible) or in text format (e.g. required if combined with unicode symbols in ggplot2)?

Value

Vector of shapes, named with the elements in x if x is specified.

Author(s)

Laure Cougnaud

See Also

[getShapePalette](#)

getSplitVectorByInt *Split/combine a vector of size(s) to have a fixed combined size*

Description

Split/combine a vector of size(s) to have a fixed combined size

Usage

```
getSplitVectorByInt(sizes, max = NULL)
```

Arguments

- sizes vector with size
- max integer with maximum combined size in output, Inf by default.

Value

vector of same length as sizeVect, containing corresponding class

Author(s)

Laure Cougnaud

```
getTimeLimSubjectProfilePlots
```

Get the limits to set for the subject profile plots, depending on the alignment policy set.

Description

These limits are extracted from specified timeLim for each module (stored in the attributes()\$metaData\$timeLim), and if empty for all modules: from the maximal range of the x-coordinates across all plots.

Usage

```
getTimeLimSubjectProfilePlots(
  listPlots,
  timeAlign = "all",
  timeAlignPerSubject = "none"
)
```

Arguments

- | | |
|---------------------|---|
| listPlots | list of list of subjectProfile[X]Plot plots |
| timeAlign | Character vector with time alignment across modules/subjects, either: <ul style="list-style-type: none"> • 'all' (by default): all plots have the same time limits • 'none': each of the plot (module*subject) has its own time limits • character vector with names of the modules which should have the same time limits (should correspond to the names of listPlots) |
| timeAlignPerSubject | Character vector, specifying if the plots should be aligned (or not) across subjects <ul style="list-style-type: none"> • 'none' (by default): all modules to align have the same time limit across subjects • 'all': all modules to align have different time limits per subject • character vector with subset of the modules to align per subject (should correspond to the names of listPlots) |

Only the modules already specified in timeAlign can be aligned by subject.

Value

Time limits, as a numeric vector of length 2. If time limits should be set by module, named list with time limits by module. If time limits should be set by module and subject, nested list with time limits 1) by module 2) by subject.

The names of the list contains the module/subject name extracted from the names of `listPlots`.

The time limits are only returned if they will need to be explicitly set for a plot. Otherwise, NULL is returned.

Author(s)

Laure Cougnaud

getTimeTrans

Get useful transformation for the time variable in patient profiles.

Description

Get useful transformation for the time variable in patient profiles.

Usage

```
getTimeTrans(
  type = c("asinh", "asinh-neg"),
  scale = 1,
  formatFct = prettyNum,
  n = 10
)
```

Arguments

type	String with transformation type, either: <ul style="list-style-type: none"> 'asinh': hyperbolic arc-sine (asinh) transformation 'asinh-neg': hyperbolic arc-sine transformation only for the negative values, otherwise linear scale
scale	Numeric vector of length 1 (1 by default) with size of the linear region around 0, only used if in case type is: 'asinh'. If specified, the time variable is first scaled with: $x/scale$, then transformed.
formatFct	function formatting the time axis breaks, (prettyNum by default), see format parameter of the trans_new .
n	Integer of length 1 with number of breaks, 10 by default.

Value

ggplot2 transformation (see [trans_new](#))

Author(s)

Pieter-Jan Stiers, Laure Cougnaud

getWidthPlot

Get width for a plot for a certain page layout

Description

Get width for a plot for a certain page layout

Usage

```
getWidthPlot(  
  margin = subjectProfileReportFormat()$margin,  
  landscape = subjectProfileReportFormat()$landscape,  
  aspectRatio = subjectProfileReportFormat()$aspectRatio  
)
```

Arguments

margin	Numeric of length 1, with margin in inches.
landscape	Logical, if TRUE the created report is in landscape format. FALSE by default, the report is created in portrait format.
aspectRatio	Numeric of length 1 (0.75 by default) with ratio between size of image in inches (derived from specified margin, landscape and heightLineIn) and real size for exported image.

Value

width for the plot in inches

Author(s)

Laure Cougnaud

```
interactionWithMissing
```

Get interaction variable between different variables.

Description

This ensures that missing values in one of the variable(s) don't propagate, so the combined result will be: 'NA - a', and that the levels of the combined vector are sorted as the levels of the specified variables (levels of the first variable varying first).

Usage

```
interactionWithMissing(data, vars, varSep = " - ")
```

Arguments

data	Data.frame with data.
vars	Character vector with variable(s) of interest.
varSep	String with separator to which the variable(s) should be combined.

Value

Vector of length: nrow(data), with interaction vector.

Author(s)

Laure Cougnaud

```
isSubjectProfileTimeVariant
```

Check if the all profile(s) is/are 'time-variant', so not a subject profile 'text' module or empty plot

Description

Check if the all profile(s) is/are 'time-variant', so not a subject profile 'text' module or empty plot

Usage

```
isSubjectProfileTimeVariant(gg, empty = TRUE)
```

Arguments

gg	object of class subjectProfileX (and ggplot) or potentially nested list of such objects.
empty	Logical, should empty subject profile be considered as time-variant?

Value

Logical, is plot time variant?

Author(s)

Laure Cougnaud

patientProfilesVis-common-args

Arguments used across the functions of the patientProfilesVis package.

Description

Arguments used across the functions of the patientProfilesVis package.

Arguments

data	Data.frame with data.
colorVar	String, variable of data with color.
colorLab	String, label for colorVar.
colorPalette	Named vector with color palette. The variable should be named with the corresponding element in colorVar. Colors can also be defined for the entire session, by setting <code>options(patientProfilesVis.colors = X)</code> with X either: <ul style="list-style-type: none"> • a vector with colors • a function returning a vector of colors for a specified number of elements (viridis by default)
shapeVar	String, variable of data for shape of the points. By default, same as colorVar.
shapeLab	String, label for shapeVar. Set by default to colorLab if colorVar but not shapeVar is not specified.
shapePalette	Named character vector with shape palette for shapeVar. The variable should be named with the corresponding element in shapeVar. Shapes can also be defined for the entire session, by setting <code>options(patientProfilesVis.shapes = X)</code> with X either: <ul style="list-style-type: none"> • a vector with shapes • a function returning a vector of shapes for a specified number of elements Note it is advised to specify the shapes as character, e.g. 'cross' instead of 4, in case Unicode symbols should also be used.
paramGroupVar	(optional) Character vector with variable(s) of data based on which the data will be grouped and sorted (in the y-axis) in the plot.
xLab	String, label for the x-axis.
yLab	String, label for the y-axis.

label	String, label for the visualization. This label is stored as attributes of the output from the <code>subjectProfile[]Plot</code> function. This label is displayed in the final profile report, in case no data is available for a specific patient, as: 'No [label] available.'
title	String, title for the plot.
timeVar	String, variable of data with time, displayed in the x axis. Records with missing time are not displayed in the plot.
timeLab	String, label for timeVar. This is used in the message indicating missing values for timeVar, and for the default label of the x-axis.
paramVar	Character vector with variable(s) of data with parameters. Variable content is displayed in the y-axis.
paramLab	Named character vector, with label for the parameter variable(s) (paramVar). This is used to set the default title.
timeLim	(optional) Vector of length 2 with time limits (x-axis). If not specified, these are extracted from the minimum timeStartVar and maximum timeEndVar per subject. The time limits are stored as attributes of the plots, used to align the plots in the final report.
timeTrans	transformation for the time variable, (see trans parameter in scale_x_continuous , and trans_new). For example, produced by the getTimeTrans function.
timeExpand	Vector of range expansion constants for the time axis (see expand parameter in scale_x_continuous).
listPlots	Named list of subject profiles. Each sublist contains subject profiles as returned by the <code>subjectProfile[X]Plot</code> function, so nested by subject and page. The names of the list should be unique, and are used
alpha	Numeric with transparency, 1 by default.
labelVars	Named character vector with variable labels (names are the variable code)
subjectVar	String, variable of data with subject ID
formatReport	list with parameters used to specify the format of the report, e.g. output of the subjectProfileReportFormat function
paramVarSep	string with character(s) used to concatenate multiple paramVar, ' - ' by default.

Value

No return value, used for the documentation of the functions of the package.

patientProfilesVis-palette

Parameters for all patient profiles visualization palette functions.

Description

Parameters for all patient profiles visualization palette functions.

Arguments

includeNA Logical (TRUE by default), should NA elements be retained in the palette in case x is specified?

Value

No return value, used for the documentation of the palette functions of the package.

prepareSubjectProfile *prepare list of subject profile (s) to be combined with the [combineVerticallyGGplot](#)*

Description

prepare list of subject profile (s) to be combined with the [combineVerticallyGGplot](#)

Usage

```
prepareSubjectProfile(
  ...,
  labels,
  timeLim = NULL,
  refLines = NULL,
  refLinesData = NULL,
  refLinesTimeVar = NULL,
  refLinesLabelVar = NULL,
  subjectVar = "USUBJID",
  timeTrans = NULL,
  timeExpand = NULL
)
```

Arguments

... list of subject profiles (across modules)

labels string with labels for the plots

timeLim time limits, as returned by the [getTimeLimSubjectProfilePlots](#) function.

refLines (optional) nested list with details for reference line(s). Each sublist contains:

- (required) 'label': string with label for the reference line
- (required) 'time': unique time (x) coordinate for the reference line
- (optional) 'color': color for the reference line, 'black' by default
- (optional) 'linetype': linetype for the reference line, 'dotted' by default

refLinesData data.frame with data from which the reference line(s) should be extracted

refLinesTimeVar string, variable of refLinesData with time for reference line(s)

refLinesLabelVar	string, variable of refLinesData with label for reference line(s)
subjectVar	String, variable of data with subject ID
timeTrans	Time transformation, or list of such transformation named by module. If NULL, no transformation are done.
timeExpand	Vector of range expansion constants for the time axis (see expand parameter in scale_x_continuous).

Value

subjectProfilePlot object, containing the combined profile plots

Author(s)

Laure Cougnaud

sortSubjects	<i>Sort subjects based on a specified dataset/variable.</i>
--------------	---

Description

Sort subjects based on a specified dataset/variable.

Usage

```
sortSubjects(
  subjects,
  subjectVar = "USUBJID",
  subjectSortData = NULL,
  subjectSortVar = NULL,
  subjectSortDecreasing = FALSE,
  verbose = FALSE
)
```

Arguments

subjects	Character vector with subjects of interest
subjectVar	String, variable of data with subject ID
subjectSortData	Data.frame with data containing information on how the subjects should be sorted.
subjectSortVar	Variable(s) of subjectSortData used to order the subjects
subjectSortDecreasing	Logical, if TRUE (FALSE by default) subjects are sorted based on inverse order of subjectSortVar.
verbose	logical, if TRUE print messages during execution

Value

Updated subjects

Author(s)

Laure Cougnaud

subjectProfileCombine *Combine subject profile plots.*

Description

Visualizations of different modules are combined by subject. The plots are aligned in the time axis (if requested). If the plots should be aligned:

- the same time limits are set for all plots
- the time axis is transformed if any of the plot was created with a time transformation
- the time axis is expanded for all plots if any of the plot was created with a time axis expanded. The [expansion](#) object for the combined plot is created from the max of each expansion element across modules.

If some plots are missing for a specific subject, an empty plot is created, containing information as a text based on the label with which the plot was created.

Usage

```
subjectProfileCombine(
  listPlots,
  timeLim = NULL,
  timeAlign = "all",
  timeAlignPerSubject = "none",
  subjectVar = "USUBJID",
  maxNLines = NULL,
  refLines = NULL,
  refLinesData = NULL,
  refLinesTimeVar = NULL,
  refLinesLabelVar = NULL,
  shiny = FALSE,
  verbose = FALSE,
  nCores = 1,
  reportPerSubject = FALSE
)
```

Arguments

<code>listPlots</code>	listPlots per subject as created inside the <code>subjectProfileCombine</code> function.
<code>timeLim</code>	time limits, as returned by the <code>getTimeLimSubjectProfilePlots</code> function.
<code>timeAlign</code>	Character vector with time alignment across modules/subjects, either: <ul style="list-style-type: none"> • 'all' (by default): all plots have the same time limits • 'none': each of the plot (module*subject) has its own time limits • character vector with names of the modules which should have the same time limits (should correspond to the names of <code>listPlots</code>)
<code>timeAlignPerSubject</code>	Character vector, specifying if the plots should be aligned (or not) across subjects <ul style="list-style-type: none"> • 'none' (by default): all modules to align have the same time limit across subjects • 'all': all modules to align have different time limits per subject • character vector with subset of the modules to align per subject (should correspond to the names of <code>listPlots</code>) <p>Only the modules already specified in <code>timeAlign</code> can be aligned by subject.</p>
<code>subjectVar</code>	String, variable of data with subject ID
<code>maxNLines</code>	Maximum number of lines for a combined plot, to fit in the page height. When the different visualizations are combined for each subject, they will be allocated to different pages if the number of lines of the combined visualization is higher than this number.
<code>refLines</code>	(optional) nested list with details for reference line(s). Each sublist contains: <ul style="list-style-type: none"> • (required) 'label': string with label for the reference line • (required) 'time': unique time (x) coordinate for the reference line • (optional) 'color': color for the reference line, 'black' by default • (optional) 'linetype': linetype for the reference line, 'dotted' by default
<code>refLinesData</code>	data.frame with data from which the reference line(s) should be extracted
<code>refLinesTimeVar</code>	string, variable of <code>refLinesData</code> with time for reference line(s)
<code>refLinesLabelVar</code>	string, variable of <code>refLinesData</code> with label for reference line(s)
<code>shiny</code>	logical, set to TRUE (FALSE by default) if the report is generated from a Shiny application. Messages during report creation will be included in the Shiny interface, and it will be mentioned at the end of the report. In this case, the shiny package should be available.
<code>verbose</code>	logical, if TRUE print messages during execution
<code>nCores</code>	Integer containing the number of cores used for the computation (1 by default). If more than 1, computation is parallelized, in this case the package <code>parallel</code> is required.
<code>reportPerSubject</code>	Logical, if TRUE (FALSE by default) export a subject profile report by subject.

Value

a nested list of `ggplot` object, containing the combined profile plots across modules for each subject/page.

Each plot object contains in the associated attribute: `metaData` containing: `nLines`: an estimation of the number of 'lines' each plot occupies (e.g. to set height of the exported figure).

Author(s)

Laure Cougnaud

subjectProfileEventPlot

Visualize events in subject profiles, so event with a single time.

Description

Visualize events in subject profiles, so event with a single time.

Usage

```
subjectProfileEventPlot(
  data,
  paramVar,
  paramLab = getLabelVar(paramVar, labelVars = labelVars),
  paramVarSep = " - ",
  paramGroupVar = NULL,
  colorVar = NULL,
  colorLab = getLabelVar(colorVar, labelVars = labelVars),
  colorPalette = NULL,
  shapeVar = colorVar,
  shapeLab = if (isTRUE(colorVar == shapeVar)) {
    colorLab
  } else
    getLabelVar(shapeVar, labelVars = labelVars),
  shapePalette = NULL,
  alpha = 1,
  timeVar,
  timeLab = getLabelVar(timeVar, labelVars = labelVars),
  timeTrans = NULL,
  timeExpand = NULL,
  subjectVar = "USUBJID",
  subjectSubset = NULL,
  subjectSample = NULL,
  seed = 123,
  subsetData = NULL,
  subsetVar = NULL,
  subsetValue = NULL,
```

```

xLab = timeLab,
yLab = "",
timeLim = NULL,
title = toString(getLabelVar(paramVar, labelVars = labelVars, label = paramLab)),
label = title,
labelVars = NULL,
formatReport = subjectProfileReportFormat(),
paging = TRUE
)

```

Arguments

data	Data.frame with data.
paramVar	Character vector with variable(s) of data with parameters. Variable content is displayed in the y-axis.
paramLab	Named character vector, with label for the parameter variable(s) (paramVar). This is used to set the default title.
paramVarSep	string with character(s) used to concatenate multiple paramVar, ' - ' by default.
paramGroupVar	(optional) Character vector with variable(s) of data based on which the data will be grouped and sorted (in the y-axis) in the plot.
colorVar	String, variable of data with color. This variable is used for the colors and the filling of the points.
colorLab	String, label for colorVar.
colorPalette	Named vector with color palette. The variable should be named with the corresponding element in colorVar. Colors can also be defined for the entire session, by setting <code>options(patientProfilesVis.colors = X)</code> with X either: <ul style="list-style-type: none"> • a vector with colors • a function returning a vector of colors for a specified number of elements (viridis by default)
shapeVar	String, variable of data for shape of the points. By default, same as colorVar.
shapeLab	String, label for shapeVar. Set by default to colorLab if colorVar but not shapeVar is not specified.
shapePalette	Named character vector with shape palette for shapeVar. The variable should be named with the corresponding element in shapeVar. Shapes can also be defined for the entire session, by setting <code>options(patientProfilesVis.shapes = X)</code> with X either: <ul style="list-style-type: none"> • a vector with shapes • a function returning a vector of shapes for a specified number of elements <p>Note it is advised to specify the shapes as character, e.g. 'cross' instead of 4, in case Unicode symbols should also be used.</p>
alpha	Numeric with transparency, 1 by default.
timeVar	String, variable of data with time, displayed in the x axis. Records with missing time are not displayed in the plot.

timeLab	String, label for timeVar. This is used in the message indicating missing values for timeVar, and for the default label of the x-axis.
timeTrans	transformation for the time variable, (see trans parameter in scale_x_continuous , and trans_new). For example, produced by the getTimeTrans function.
timeExpand	Vector of range expansion constants for the time axis (see expand parameter in scale_x_continuous).
subjectVar	String, variable of data with subject ID
subjectSubset	(optional) Character vector with subjects of interest (available in subjectVar), NULL by default.
subjectSample	(optional) Integer of length 1 with number of random subject(s) that should be considered, e.g. to check the created patient profiles for a subset of the data. By default, all specified subjects are considered (set to NULL).
seed	(optional) Integer of length 1 with seed used to select random subjects if subjectSample is specified (123 by default).
subsetData	(optional) Data.frame with extra dataset to filter on. This dataset is filtered, and only records from data with common subject IDs will be retained. If not specified, data is used.
subsetVar	(optional) String with variable of subset data to filter on. subsetValue should be specified too. If not specified, all records from the subset data are retained.
subsetValue	(optional) Character vector with value(s) of interest to retain in the filtered data. These values should be available in subsetVar. Missing values in the subject variable are not retained in the filtered data.
xLab	String, label for the x-axis.
yLab	String, label for the y-axis.
timeLim	(optional) Vector of length 2 with time limits (x-axis). If not specified, these are extracted from the minimum timeStartVar and maximum timeEndVar per subject. The time limits are stored as attributes of the plots, used to align the plots in the final report.
title	String with title, label of the parameter variable by default.
label	String, label for the visualization. This label is stored as attributes of the output from the <code>subjectProfile[]Plot</code> function. This label is displayed in the final profile report, in case no data is available for for a specific patient, as: 'No [label] available.'
labelVars	Named character vector with variable labels (names are the variable code)
formatReport	list with parameters used to specify the format of the report, e.g. output of the subjectProfileReportFormat function
paging	Logical, if TRUE (by default), automatic paging is enabled, so patient profiles module too big to fit in one page will span multiple pages. Please note that the size of the graphic window (or report page) may need to be re-sized in order that the plot fits. If FALSE, the entire plot is included in one single page.

Value

list of (across subjects) of list (across modules) of [ggplot2](#) objects, also of class `subjectProfileEventPlot`, with additional `metaData` attributes containing 'label', 'timeLim' and 'timeTrans' (if specified).

Author(s)

Laure Cougnaud

See Also

Other patient profiles plotting function: [subjectProfileIntervalPlot\(\)](#), [subjectProfileLinePlot\(\)](#), [subjectProfileTextPlot\(\)](#)

subjectProfileExport *Create report*

Description

Create report

Usage

```
subjectProfileExport(
  listPlotsSubject,
  outputFile = "subjectProfile.pdf",
  index = NULL,
  formatReport = subjectProfileReportFormat(),
  shiny = FALSE,
  verbose = FALSE,
  nCores = NULL,
  exportFigures = FALSE
)
```

Arguments

<code>listPlotsSubject</code>	List of plots for each subject
<code>outputFile</code>	string, path to the output report
<code>index</code>	Index, output from defineIndex
<code>formatReport</code>	list with parameters used to specify the format of the report, e.g. output of the subjectProfileReportFormat function
<code>shiny</code>	logical, set to TRUE (FALSE by default) if the report is generated from a Shiny application. Messages during report creation will be included in the Shiny interface, and it will be mentioned at the end of the report. In this case, the shiny package should be available.
<code>verbose</code>	logical, if TRUE print messages during execution

nCores	Integer containing the number of cores used for the computation (1 by default). If more than 1, computation is parallelized, in this case the package parallel is required.
exportFigures	Logical, if TRUE (FALSE by default) the subject profile figures are also exported in pdf format in a 'figures' folder. Figures are named as [subjectID]-[page].pdf

Value

No returned value, the plots are exported to outputDir

Author(s)

Laure Cougnaud

subjectProfileIntervalPlot

Visualize time interval in subject profiles, so event with a start and end time.

Description

Visualize time interval in subject profiles, so event with a start and end time.

Usage

```
subjectProfileIntervalPlot(
  data,
  paramVar,
  paramVarSep = " - ",
  paramLab = getLabelVar(paramVar, labelVars = labelVars),
  paramGroupVar = NULL,
  timeStartVar,
  timeStartLab = getLabelVar(timeStartVar, labelVars = labelVars),
  timeEndVar,
  timeEndLab = getLabelVar(timeEndVar, labelVars = labelVars),
  timeLab = toString(c(timeStartLab, timeEndLab)),
  subjectVar = "USUBJID",
  subjectSubset = NULL,
  subjectSample = NULL,
  seed = 123,
  subsetData = NULL,
  subsetVar = NULL,
  subsetValue = NULL,
  timeImpType = c("minimal", "data-based", "none"),
  timeLim = NULL,
  timeLimData = NULL,
```

```

timeLimStartVar = NULL,
timeLimStartLab = getLabelVar(timeLimStartVar, labelVars = labelVars),
timeLimEndVar = NULL,
timeLimEndLab = getLabelVar(timeLimEndVar, labelVars = labelVars),
timeTrans = NULL,
timeExpand = NULL,
timeAlign = TRUE,
xLab = timeLab,
yLab = "",
colorVar = NULL,
colorLab = getLabelVar(colorVar, labelVars = labelVars),
colorPalette = NULL,
alpha = 1,
timeStartShapeVar = NULL,
timeEndShapeVar = NULL,
shapePalette = NULL,
shapeLab = toString(unique(getLabelVar(c(timeStartShapeVar, timeEndShapeVar), labelVars
  = labelVars))),
shapeSize = rel(3),
title = toString(getLabelVar(paramVar, labelVars = labelVars, label = paramLab)),
label = title,
caption,
labelVars = NULL,
formatReport = subjectProfileReportFormat(),
paging = TRUE
)

```

Arguments

data	Data.frame with data.
paramVar	Character vector with variable(s) of data with parameters. Variable content is displayed in the y-axis.
paramVarSep	string with character(s) used to concatenate multiple paramVar, ' - ' by default.
paramLab	Named character vector, with label for the parameter variable(s) (paramVar). This is used to set the default title.
paramGroupVar	(optional) Character vector with variable(s) of data based on which the data will be grouped and sorted (in the y-axis) in the plot.
timeStartVar	String, variable of data with start of time interval.
timeStartLab	String, label for timeStartVar, displayed in a message and in the plot caption.
timeEndVar	String, variable of data with end of time interval.
timeEndLab	String, label for timeEndVar, displayed in a message and in the plot caption.
timeLab	String, label for timeVar. This is used in the message indicating missing values for timeVar, and for the default label of the x-axis.
subjectVar	String, variable of data with subject ID
subjectSubset	(optional) Character vector with subjects of interest (available in subjectVar), NULL by default.

<code>subjectSample</code>	(optional) Integer of length 1 with number of random subject(s) that should be considered, e.g. to check the created patient profiles for a subset of the data. By default, all specified subjects are considered (set to NULL).
<code>seed</code>	(optional) Integer of length 1 with seed used to select random subjects if <code>subjectSample</code> is specified (123 by default).
<code>subsetData</code>	(optional) Data.frame with extra dataset to filter on. This dataset is filtered, and only records from data with common subject IDs will be retained. If not specified, data is used.
<code>subsetVar</code>	(optional) String with variable of subset data to filter on. <code>subsetValue</code> should be specified too. If not specified, all records from the subset data are retained.
<code>subsetValue</code>	(optional) Character vector with value(s) of interest to retain in the filtered data. These values should be available in <code>subsetVar</code> . Missing values in the subject variable are not retained in the filtered data.
<code>timeImpType</code>	String with imputation type: 'minimal' (default), 'data-based' or 'none', see section: 'Time interval representation'. This imputation type is not used if a dataset used to impute time is specified.
<code>timeLim</code>	(optional) Vector of length 2 with time limits (x-axis). If not specified, these are extracted from the minimum <code>timeStartVar</code> and maximum <code>timeEndVar</code> per subject. The time limits are stored as attributes of the plots, used to align the plots in the final report.
<code>timeLimData</code>	Data.frame with data used to impute time in case some time records are missing in data, see section: 'Time interval representation'.
<code>timeLimStartVar</code>	String, variable of <code>timeLimData</code> with start of the time interval.
<code>timeLimStartLab</code>	String, label for <code>timeLimeStartVar</code> , displayed in a message and in the plot caption.
<code>timeLimEndVar</code>	String, variable of <code>timeLimData</code> with end of the time interval.
<code>timeLimEndLab</code>	String, label for <code>timeLimEndVar</code> , displayed in a message and in the plot caption.
<code>timeTrans</code>	transformation for the time variable, (see <code>trans</code> parameter in scale_x_continuous , and trans_new). For example, produced by the getTimeTrans function.
<code>timeExpand</code>	Vector of range expansion constants for the time axis (see <code>expand</code> parameter in scale_x_continuous).
<code>timeAlign</code>	Logical, if TRUE (by default) the different plots are horizontally aligned. If set to FALSE, each plot has its own time-limits. If set to FALSE, this is not compatible with the specification of <code>timeLim</code> .
<code>xLab</code>	String, label for the x-axis.
<code>yLab</code>	String, label for the y-axis.
<code>colorVar</code>	String, variable of data with color, used both for the point(s) and segment(s).
<code>colorLab</code>	String, label for <code>colorVar</code> .

colorPalette	Named vector with color palette. The variable should be named with the corresponding element in colorVar. Colors can also be defined for the entire session, by setting options(patientProfilesVis.colors = X) with X either: <ul style="list-style-type: none"> • a vector with colors • a function returning a vector of colors for a specified number of elements (viridis by default)
alpha	Numeric with transparency, 1 by default.
timeStartShapeVar	(optional) String, variable of data used for the shape of the symbol displayed at the start of the time interval. If not specified, default shape palette is used, see section 'Time interval representation'.
timeEndShapeVar	String, variable of data used for the shape of the symbol displayed at the end of the time interval. If not specified, default shape palette is used, see section 'Time interval representation'.
shapePalette	Named vector with (combined) shape palette for timeStartShapeVar/timeEndShapeVar.
shapeLab	String with label for timeStartShapeVar/timeEndShapeVar
shapeSize	Size for symbols (only used if timeStartShapeVar/timeEndShapeVar is specified).
title	String with title, label of the parameter variable by default.
label	String, label for the visualization. This label is stored as attributes of the output from the subjectProfile[]Plot function. This label is displayed in the final profile report, in case no data is available for a specific patient, as: 'No [label] available.'
caption	(optional) String with caption (NULL for no caption). By default the caption contains information on the imputation strategy for missing time.
labelVars	Named character vector with variable labels (names are the variable code)
formatReport	list with parameters used to specify the format of the report, e.g. output of the subjectProfileReportFormat function
paging	Logical, if TRUE (by default), automatic paging is enabled, so patient profiles module too big to fit in one page will span multiple pages. Please note that the size of the graphic window (or report page) may need to be re-sized in order that the plot fits. If FALSE, the entire plot is included in one single page.

Value

list of (across subjects) of list (across pages) of [ggplot2](#) objects, also of class subjectProfileIntervalPlot. with additional 'metaData' attributes containing 'label', 'timeLim' timeTrans and timeExpand (if specified).

Time interval representation

In case the start or the end of the time interval contain missing values:

- if a dataset (`timeLimData`), start (`timeLimStartVar`) and end (`timeLimEndVar`) variables are specified:
 1. for each subject:
 - the minimum and maximum time values across these specified time variables are extracted
 - missing start values are replaced by the minimum time
 - missing end values are replaced by the maximum time
 2. if all values are missing for this subject, they are taken across subjects
- otherwise, depending on the imputation type (`timeImpType`):
 - 'minimal' (by default):
 - * if the start and the end of the interval are missing: no imputation is done, only the label is displayed
 - * if the start time is missing and the end time is not missing: start time is imputed with end time, and status is set to 'Missing start'
 - * if the end time is missing and the start time is not missing: end time is imputed with start time, and status is set to 'Missing end'
 - 'data-based' (default in version < 1.0.0): minimum/maximum values in the start/end time variables in the data are considered for the specific subject (if available). If there are missing for a specific subject, they are taken across subjects. If all time are missings, the range is set to 0 and Inf
 - 'none': no imputation is done

The symbols displayed at the start and end of the interval are:

- by default:
 - a filled square labelled 'Complete' if the time is not missing
 - a filled left-directed arrow in case of missing start time
 - a filled right-directed arrow in case of missing end time
- if the variable(s) used for the shape of the start or end of the interval are specified (via `timeStartShapeVar/timeEndShapeVar`): labels are based on these variables, and a standard shape palette is used

The time limits are the same across subjects, and set to:

- `timeLim` if specified
- maximum time range in `timeLimStartVar` and `timeLimEndVar` in `timeLimData` if specified
- the maximum range on the data obtained after imputation of missing values

Author(s)

Laure Cougnaud

See Also

Other patient profiles plotting function: [subjectProfileEventPlot\(\)](#), [subjectProfileLinePlot\(\)](#), [subjectProfileTextPlot\(\)](#)

subjectProfileLinePlot

Visualize subject profiles of the evolution of continuous parameters versus time (spaghetti plot).

Description

Visualize subject profiles of the evolution of continuous parameters versus time (spaghetti plot).

Usage

```
subjectProfileLinePlot(
  data,
  paramValueVar,
  paramLab = getLabelVar(paramValueVar, labelVars = labelVars),
  paramNameVar = NULL,
  paramVarSep = " - ",
  paramValueRangeVar = NULL,
  colorValueRange = "lightgreen",
  yLimFrom = c("all", "value"),
  colorVar = NULL,
  colorLab = getLabelVar(colorVar, labelVars = labelVars),
  colorPalette = NULL,
  shapeVar = colorVar,
  shapeLab = if (isTRUE(colorVar == shapeVar)) {
    colorLab
  } else
    getLabelVar(shapeVar, labelVars = labelVars),
  shapePalette = NULL,
  paramGroupVar = NULL,
  timeVar,
  timeLab = getLabelVar(timeVar, labelVars = labelVars),
  timeTrans = NULL,
  timeExpand = NULL,
  subjectVar = "USUBJID",
  subjectSubset = NULL,
  subjectSample = NULL,
  seed = 123,
  subsetData = NULL,
  subsetVar = NULL,
  subsetValue = NULL,
  xLab = timeLab,
```

```

yLab = "",
timelim = NULL,
title = toString(getLabelVar(paramValueVar, labelVars = labelVars, label = paramLab)),
label = title,
labelVars = NULL,
formatReport = subjectProfileReportFormat(),
paging = TRUE,
alpha = 1,
shapeSize = rel(1)
)

```

Arguments

data	Data.frame with data.
paramValueVar	String, variable of data with parameter value to represent. Records with missing values are discarded.
paramLab	Named character vector, with label for the parameter variable(s) (paramNameVar). This is used to set the default title.
paramNameVar	Character vector with variable(s) of data with parameter name. If multiple, they are concatenated with paramVarSep.
paramVarSep	string with character(s) used to concatenate multiple paramNameVar, ' - ' by default.
paramValueRangeVar	Character vector of length 2 containing variables of data with minimum and maximum value for paramValueVar, typically reference range indicators. Range can differ per parameter and even per time point. This range is repre- sented as a ribbon in the plot background. e.g. to represent the reference range of the variable.
colorValueRange	String with color for the filling of the ribbon represented by paramValueRangeVar.
yLimFrom	String with specification on the limits of the y-axis, either: <ul style="list-style-type: none"> • 'all' (by default): for each parameter (paramNameVar), the y-axis range contains the minimum/maximum value of the reference range (paramValueRangeVar) or data • 'value': for each parameter (paramNameVar), the y-axis minimum/maximum value is restricted to the data range only. Please note that the ribbon visual- izing the reference range is also restricted to the data range if wider.
colorVar	String, variable of data with color. This variable is used for the colors and the filling of the points.
colorLab	String, label for colorVar.
colorPalette	Named vector with color palette. The variable should be named with the corre- sponding element in colorVar. Colors can also be defined for the entire session, by setting options(patientProfilesVis.colors = X) with X either: <ul style="list-style-type: none"> • a vector with colors

	<ul style="list-style-type: none"> • a function returning a vector of colors for a specified number of elements (viridis by default)
shapeVar	String, variable of data for shape of the points. By default, same as colorVar.
shapeLab	String, label for shapeVar. Set by default to colorLab if colorVar but not shapeVar is not specified.
shapePalette	<p>Named character vector with shape palette for shapeVar. The variable should be named with the corresponding element in shapeVar.</p> <p>Shapes can also be defined for the entire session, by setting options(patientProfilesVis.shapes = X) with X either:</p> <ul style="list-style-type: none"> • a vector with shapes • a function returning a vector of shapes for a specified number of elements <p>Note it is advised to specify the shapes as character, e.g. 'cross' instead of 4, in case Unicode symbols should also be used.</p>
paramGroupVar	(optional) Character vector with variable(s) of data based on which the data will be grouped and sorted (in the y-axis) in the plot.
timeVar	String, variable of data with time, displayed in the x axis. Records with missing time are not displayed in the plot.
timeLab	String, label for timeVar. This is used in the message indicating missing values for timeVar, and for the default label of the x-axis.
timeTrans	transformation for the time variable, (see trans parameter in scale_x_continuous , and trans_new). For example, produced by the getTimeTrans function.
timeExpand	Vector of range expansion constants for the time axis (see expand parameter in scale_x_continuous).
subjectVar	String, variable of data with subject ID
subjectSubset	(optional) Character vector with subjects of interest (available in subjectVar), NULL by default.
subjectSample	(optional) Integer of length 1 with number of random subject(s) that should be considered, e.g. to check the created patient profiles for a subset of the data. By default, all specified subjects are considered (set to NULL).
seed	(optional) Integer of length 1 with seed used to select random subjects if subjectSample is specified (123 by default).
subsetData	<p>(optional) Data.frame with extra dataset to filter on. This dataset is filtered, and only records from data with common subject IDs will be retained.</p> <p>If not specified, data is used.</p>
subsetVar	<p>(optional) String with variable of subset data to filter on. subsetValue should be specified too.</p> <p>If not specified, all records from the subset data are retained.</p>
subsetValue	<p>(optional) Character vector with value(s) of interest to retain in the filtered data. These values should be available in subsetVar.</p> <p>Missing values in the subject variable are not retained in the filtered data.</p>
xLab	String, label for the x-axis.
yLab	String, label for the y-axis.

timeLim	(optional) Vector of length 2 with time limits (x-axis). If not specified, these are extracted from the minimum timeStartVar and maximum timeEndVar per subject. The time limits are stored as attributes of the plots, used to align the plots in the final report.
title	String with title, label of the parameter value variable by default.
label	String, label for the visualization. This label is stored as attributes of the output from the subjectProfile[]Plot function. This label is displayed in the final profile report, in case no data is available for for a specific patient, as: 'No [label] available.'
labelVars	Named character vector with variable labels (names are the variable code)
formatReport	list with parameters used to specify the format of the report, e.g. output of the subjectProfileReportFormat function
paging	Logical, if TRUE (by default), automatic paging is enabled, so patient profiles module too big to fit in one page will span multiple pages. Please note that the size of the graphic window (or report page) may need to be re-sized in order that the plot fits. If FALSE, the entire plot is included in one single page.
alpha	Numeric with transparency, 1 by default.
shapeSize	Size for the symbols, any integer or object supported by size in geom_point .

Value

List of (across subjects) of list (across modules) of [ggplot2](#) objects, also of class subjectProfileLinePlot. Each subject profile contains attributes: 'subjectID' and 'nLines' (estimated number of lines of space the plot will take). The entire list also contains attributes: 'label', 'timeLim' and 'time-Trans' (if specified).

Author(s)

Laure Cougnaud

See Also

Other patient profiles plotting function: [subjectProfileEventPlot\(\)](#), [subjectProfileIntervalPlot\(\)](#), [subjectProfileTextPlot\(\)](#)

subjectProfileReportFormat

Get list with format specification for subject profile report.

Description

This format is used to set default for the created subject profile report: line height, margin, report in landscape or portrait format, aspect ratio and width for the y-label.

Usage

```
subjectProfileReportFormat(
  heightLineIn = 0.2,
  margin = 0.75,
  landscape = FALSE,
  aspectRatio = 0.5,
  yLabelWidth = 30
)
```

Arguments

heightLineIn	Numeric of length 1 with height of a line in inches, 0.2 by default.
margin	Numeric of length 1, with margin in inches.
landscape	Logical, if TRUE the created report is in landscape format. FALSE by default, the report is created in portrait format.
aspectRatio	Numeric of length 1 (0.75 by default) with ratio between size of image in inches (derived from specified margin, landscape and heightLineIn) and real size for exported image.
yLabelWidth	Integer of length 1 with approximate maximum number of characters in the y-label of the plot, 30 by default. If the label of the y-axis is longer than this number of character, it will be splitted between words in separated lines.

Value

List with parameters to set format of the subject profile report. If not specified, default are used.

Author(s)

Laure Cougnaud

subjectProfileTextPlot

Visualize text-information in subject profiles.

Description

There are two ways to specify the variables of interest to include:

- by specifying column(s) of interest containing parameter values, passed to the paramValueVar parameter.
In this case, variable value is displayed in the plot area, and variable name in the label of the y-axis, as:
variable 1 | value 1 - value 2 - ...
variable 2 | value 1 - value 2 - ...

- by specifying column(s) of interest containing parameter values, displayed as a table.
In this case, variable are displayed in columns in the plot area. Variable names are displayed on top of table, and associated values below, as:
| variable 1 variable 2
| value 1 value 1 | ...
- by specifying a combination of a variable containing the parameter name (paramNameVar), coupled with a variable containing the parameter values (paramValueVar).
In this case, parameter values (if multiple) are concatenated and displayed in the plot area for each parameter name, displayed in the label of the y-axis, as:
variable name 1 | variable value 1 - variable value 2 - ...
variable name 2 | variable value 1 - ...

Usage

```
subjectProfileTextPlot(
  data,
  paramValueVar,
  paramValueLab = getLabelVar(paramValueVar, labelVars = labelVars),
  paramNameVar = NULL,
  paramGroupVar = NULL,
  subsetData = NULL,
  subsetVar = NULL,
  subsetValue = NULL,
  subjectVar = "USUBJID",
  subjectSubset = NULL,
  subjectSample = NULL,
  seed = 123,
  xLab = "",
  yLab = "",
  title = "Subject information",
  label = title,
  labelVars = NULL,
  paramVarSep = " - ",
  formatReport = subjectProfileReportFormat(),
  paging = TRUE,
  table = FALSE,
  colWidth = NULL
)
```

Arguments

- | | |
|---------------|--|
| data | Data.frame with data. |
| paramValueVar | Character vector, either: <ul style="list-style-type: none"> • vector with names of variable(s) (multiple are possible) of data of interest. The values are displayed in the plot area and variable name in the labels of the y-axis.
Multiple variables can be concatenated in the same line by specifying them, |

as an unique string separated by a 'pipe', e.g 'SEX|AGE'. Variable label(s) are concatenated (with ', ') and displayed in the y-axis.

- if paramNameVar is specified:
 - character vector with names of variable(s) (multiple possible) of data with values to represent in the plot area.
 - function taking data as input and returning a new variable (of length equal to number of rows in data) with parameter value to represent

paramValueLab	(optional) Named character vector with labels for paramValueVar.
paramNameVar	(optional) Character vector of length 1 with variable of data with parameter name. This is displayed in the labels of the y-axis.
paramGroupVar	(optional) Character vector with variable(s) of data based on which the data will be grouped and sorted (in the y-axis) in the plot.
subsetData	(optional) Data.frame with extra dataset to filter on. This dataset is filtered, and only records from data with common subject IDs will be retained. If not specified, data is used.
subsetVar	(optional) String with variable of subset data to filter on. subsetValue should be specified too. If not specified, all records from the subset data are retained.
subsetValue	(optional) Character vector with value(s) of interest to retain in the filtered data. These values should be available in subsetVar. Missing values in the subject variable are not retained in the filtered data.
subjectVar	String, variable of data with subject ID
subjectSubset	(optional) Character vector with subjects of interest (available in subjectVar), NULL by default.
subjectSample	(optional) Integer of length 1 with number of random subject(s) that should be considered, e.g. to check the created patient profiles for a subset of the data. By default, all specified subjects are considered (set to NULL).
seed	(optional) Integer of length 1 with seed used to select random subjects if subjectSample is specified (123 by default).
xLab	String, label for the x-axis.
yLab	String, label for the y-axis.
title	String with title, 'Subject information' by default.
label	String, label for the visualization. This label is stored as attributes of the output from the subjectProfile[]Plot function. This label is displayed in the final profile report, in case no data is available for for a specific patient, as: 'No [label] available.'
labelVars	Named character vector with variable labels (names are the variable code)
paramVarSep	String (' - ' by default) with character(s) used to concatenate multiple variables for the same record in the plot area.
formatReport	list with parameters used to specify the format of the report, e.g. output of the subjectProfileReportFormat function

paging	Logical, if TRUE (by default), automatic paging is enabled, so patient profiles module too big to fit in one page will span multiple pages. Please note that the size of the graphic window (or report page) may need to be re-sized in order that the plot fits. If FALSE, the entire plot is included in one single page.
table	Logical, if TRUE (FALSE by default) the information contained in the variables: paramValueVar is displayed as a table. Otherwise, the values of the different variables are concatenated in the same line.
colWidth	Numeric vector with approximate width of each parameter value column for a table layout. For example in case two parameters are specified: <code>c(0.8, 0.2)</code> such as the first column takes 80% of plot area, and the second column 20%. Note: columns can be slightly bigger if their content is larger than the specified width. If not specified, column width is optimized based on the max length of the character in each column.

Value

list of (across subjects) of list (across modules) of `ggplot2` objects, also of class `subjectProfileTextPlot`, with additional `metaData` attributes containing 'label' and 'timeLim'.

Author(s)

Laure Cougnaud

See Also

Other patient profiles plotting function: `subjectProfileEventPlot()`, `subjectProfileIntervalPlot()`, `subjectProfileLinePlot()`

subjectProfileTheme	Custom <code>theme</code> for subject profile plot. Currently classic dark-on-light <code>ggplot2</code> theme with alternated grey color for vertical grid lines
---------------------	---

Description

Custom `theme` for subject profile plot. Currently classic dark-on-light `ggplot2` theme with alternated grey color for vertical grid lines

Usage

`subjectProfileTheme()`

Value

`theme` object

Author(s)

Laure Cougnaud

Index

* patient profiles plotting function

- subjectProfileEventPlot, 38
- subjectProfileIntervalPlot, 42
- subjectProfileLinePlot, 47
- subjectProfileTextPlot, 51

addReferenceLinesProfilePlot, 3

asinh, 29

cat, 12

checkTimeExpand, 4

checkTimeTrans, 5

checkVar, 5

clinShapes, 27

clinShapesText, 27

clinUtils::getColorPalette, 21

clinUtils::getShapePalette, 27

combineVerticallyGGplot, 6, 34

convertAesVar, 7

countNLines, 7

createSubjectProfileReport, 8

defineIndex, 11, 41

expansion, 36

filterData, 12

filterMissingInVar, 14

formatParamVarTextPlot, 15

formatTimeInterval, 16

formatTimeLim, 19

geom_point, 50

getAesScaleManual, 20

getColorPalette, 20, 21

getColorPalettePatientProfile, 20

getMaxNLinesCombinePlot, 21

getNLinesLabel, 22

getNLinesLegend, 23

getNLinesSubjectProfile, 23

getOptimalColWidth, 24

getPageVar, 25

getPathTemplate, 26

getShapePalette, 26, 27

getShapePalettePatientProfile, 26

getSplitVectorByInt, 27

getTimeLimSubjectProfilePlots, 28, 34, 37

getTimeTrans, 29, 33, 40, 44, 49

getWidthPlot, 30

ggplot, 6, 31, 38

ggplot2, 3, 4, 22–24, 41, 45, 50, 54

interactionWithMissing, 31

isSubjectProfileTimeVariant, 31

patientProfilesVis-common-args, 32

patientProfilesVis-palette, 33

prepareSubjectProfile, 34

prettyNum, 29

scale_x_continuous, 33, 35, 40, 44, 49

sortSubjects, 35

subjectProfileCombine, 6, 36, 37

subjectProfileEventPlot, 9, 38, 47, 50, 54

subjectProfileExport, 41

subjectProfileIntervalPlot, 9, 41, 42, 50, 54

subjectProfileLinePlot, 9, 41, 47, 47, 54

subjectProfileReportFormat, 11, 16, 24, 25, 33, 40, 41, 45, 50, 50, 53

subjectProfileTextPlot, 9, 16, 41, 47, 50, 51

subjectProfileTheme, 54

theme, 54

trans_new, 29, 33, 40, 44, 49

viridis, 21