

Package ‘populationPDXdesign’

July 23, 2025

Type Package

Title Designing Population PDX Studies

Version 1.0.3

Date 2018-08-08

Description Run simulations to assess the impact of various designs features and the underlying biological behaviour on the outcome of a Patient Derived Xenograft (PDX) population study. This project can either be deployed to a server as a 'shiny' app or installed locally as a package and run the app using the command 'populationPDXdesignApp()'.

License GPL (>= 3)

Depends R (>= 3.0.0)

Imports devtools, ggplot2, plyr, roxygen2, shiny, shinycssloaders

Suggests testthat

RoxygenNote 6.0.1

NeedsCompilation no

Author Maria Luisa Guerriero [aut, cre],
Natasha Karp [aut]

Maintainer Maria Luisa Guerriero <maria.guerriero@astrazeneca.com>

Repository CRAN

Date/Publication 2018-08-08 14:40:07 UTC

Contents

callsInSingleExperiment	2
getMode	3
noFalseCalls	3
noMissedCalls	4
outcomeInSingleExperiment	5
outcomeMultipleExperiments	5
plotFalsepositive	6
plotSensitivity	7

populationPDXdesignApp	7
server	8
ui	8
varyingPDXnPDXrBiolRR	9

Index	10
--------------	-----------

callsInSingleExperiment

Simulation of a single population PDX experiment

Description

This is an internal function. Please use cautiously if calling directly. Samples some animals and classify as responders or non-responders based on number of models studied (PDXn), number of mice measured per model (PDXr), the classification accuracy (C_Acc) and the underlying biological response rate (Biol_RR). Example usage: callsInSingleExperiment(PDXn=8, PDXr=3, C_Acc=0.95, Biol_RR=30)

Usage

```
callsInSingleExperiment(PDXn, PDXr, C_Acc, Biol_RR)
```

Arguments

PDXn	number of PDX models studied
PDXr	number of mice measured per PDX model
C_Acc	classification accuracy
Biol_RR	underlying biological response rate for this treatment

Value

dataframe with three columns:

- PDXModel is a string that indicates the model id
- PDXclassification is a numeric value that indicates the true biological classification of that PDX - 0 equal non-responder and 1 equal responder
- StudyResult is a numeric value that indicates the classification of the PDX model after sampling - 0 equal non-responder and 1 equal responder

Author(s)

Maria Luisa Guerriero, <maria.guerriero@astrazeneca.com>

Natasha A. Karp, <natasha.karp@astrazeneca.com>

getMode	<i>Function to return the mode of a vector of values</i>
---------	--

Description

This is an internal function. Please use cautiously if calling directly. Returns the mode from numeric vector. Example usage: `getMode(c(0,1,1))`

Usage

```
getMode(v)
```

Arguments

v	vector of numeric values
---	--------------------------

Value

a numeric value

Author(s)

Maria Luisa Guerriero, <maria.guerriero@astrazeneca.com>

Natasha A. Karp, <natasha.karp@astrazeneca.com>

noFalseCalls	<i>Function to calculate the number of false calls for a design for a go-no go threshold</i>
--------------	--

Description

This is an internal function. Please use cautiously if calling directly. Returns the number of false calls from a simulation study exploring the impact of varying PDXn and PDXr for an underlying Biol_RR for a particularly go-no go threshold. A false call can only arise in the situation where the underlying Biol_RR is below the go-no go threshold. Example usage: `noFalseCalls(ImpactVarying_PDXn_PDXr_BRR, GoNoGoThreshold=30)`

Usage

```
noFalseCalls(dataset, GoNoGoThreshold)
```

Arguments

dataset	dataset obtained as output from the 'varying_PDXn_PDXr' function
GoNoGoThreshold	go-no go threshold

Value

vector with three elements:

- numeric value indicating the number of experiments simulated
- numeric value indicating the number of experiments which were above the go-no go threshold
- numeric value indicating the FPR

Author(s)

Maria Luisa Guerriero, <maria.guerriero@astrazeneca.com>

Natasha A. Karp, <natasha.karp@astrazeneca.com>

noMissedCalls	<i>Function to calculate the number of missed calls for a design for a go-no go threshold</i>
---------------	---

Description

This is an internal function. Please use cautiously if calling directly. Returns the number of missed calls from a simulation study exploring the impact of varying PDXn and PDXr for an underlying Biol_RR for a particularly go-no go threshold. A missed call can only arise in the situation where the underlying Biol_RR exceeds the go-no go threshold. Example usage: noMissedCalls(ImpactVarying_PDXn_PDXr_BRR, GoNoGoThreshold=30)

Usage

```
noMissedCalls(dataset, GoNoGoThreshold)
```

Arguments

dataset	dataset obtained as output from the 'varying_PDXn_PDXr' function
GoNoGoThreshold	go-no go threshold

Value

vector with three elements:

- numeric value indicating the number of experiments simulated
- numeric value indicating the number of experiments which were below the go-no go threshold
- numeric value indicating the percent of missed calls

Author(s)

Maria Luisa Guerriero, <maria.guerriero@astrazeneca.com>

Natasha A. Karp, <natasha.karp@astrazeneca.com>

`outcomeInSingleExperiment`*Function to summarise the results for a single simulation representing one experiment*

Description

This is an internal function. Please use cautiously if calling directly. From a simulation of a single experiment, the estimated response rate is determined and captured with the meta data (e.g. PDXn, PDXr) for that experiment. Example usage: `outcomeInSingleExperiment(df=outcomeInSingleExperiment_1, PDXn=8, PDXr=3, C_Acc=0.95, Biol_RR=30)`

Usage

```
outcomeInSingleExperiment(df, PDXn, PDXr, C_Acc, Biol_RR)
```

Arguments

<code>df</code>	data frame from <code>callsInSingleExperiment</code>
<code>PDXn</code>	PDXn
<code>PDXr</code>	PDXr
<code>C_Acc</code>	the classification accuracy (numeric value between 0 and 1)
<code>Biol_RR</code>	Biol_RR

Value

a vector with 8 values that captures the input design and the estimated response rate for that design from a single simulation

Author(s)

Maria Luisa Guerriero, <maria.guerriero@astrazeneca.com>

Natasha A. Karp, <natasha.karp@astrazeneca.com>

`outcomeMultipleExperiments`*Function to run simulations to mimic population PDX studies for a defined scenario*

Description

This is an internal function. Please use cautiously if calling directly. Simulations are used to mimic population PDX studies for specified values of PDXn, PDXr, Biol_RR and C_Acc. Example usage: `outcomeMultipleExperiments(PDXn=8, PDXr=3, C_Acc=0.95, Biol_RR=30, iterations=500)`

Usage

```
outcomeMultipleExperiments(PDXn, PDXr, C_Acc, Biol_RR, iterations)
```

Arguments

PDXn	PDXn
PDXr	PDXr
C_Acc	the classification accuracy (numeric value between 0 and 1)
Biol_RR	Biol_RR
iterations	no of experiments to simulated

Value

a dataframe where each row represents the results from a simulation mimicking an individual experiment for a particular design with meta data returned to describe the experimental design

Author(s)

Maria Luisa Guerriero, <maria.guerriero@astrazeneca.com>
 Natasha A. Karp, <natasha.karp@astrazeneca.com>

plotFalsepositive	<i>A function to visualise the false positive rate as a function of PDXn and PDXr</i>
-------------------	---

Description

This is an internal function. Please use cautiously if calling directly. A visualisation of the false positive rate behaviour from the simulations

Usage

```
plotFalsepositive(data)
```

Arguments

data	data frame with four columns which indicate the PDXn, PDXr, Biol_RR and the FPR for a specified go-no go threshold
------	--

Value

a graphic visualisation

Author(s)

Maria Luisa Guerriero, <maria.guerriero@astrazeneca.com>
 Natasha A. Karp, <natasha.karp@astrazeneca.com>

plotSensitivity	<i>A function to visualise the sensitivity as a function of PDXn and PDXr</i>
-----------------	---

Description

This is an internal function. Please use cautiously if calling directly. A visualisation of the sensitivity from the simulations

Usage

```
plotSensitivity(data)
```

Arguments

data	data frame with four columns which indicate the PDXn, PDXr, Biol_RR and the MissedCalls for a specified go-no go threshold
------	--

Value

a graphic visualisation

Author(s)

Maria Luisa Guerriero, <maria.guerriero@astrazeneca.com>
Natasha A. Karp, <natasha.karp@astrazeneca.com>

populationPDXdesignApp	<i>Function</i> populationPDXdesignApp
------------------------	--

Description

Runs the 'shiny' app.

Usage

```
populationPDXdesignApp()
```

Author(s)

Maria Luisa Guerriero, <maria.guerriero@astrazeneca.com>
Natasha A. Karp, <natasha.karp@astrazeneca.com>

Examples

```
if (interactive()) {  
  populationPDXdesignApp()  
}
```

server	<i>'shiny' app server function</i>
--------	------------------------------------

Description

This is an internal function. Please use cautiously if calling directly

Usage

```
server(input, output, session)
```

Arguments

input	input
output	output
session	session

Author(s)

Maria Luisa Guerriero, <maria.guerriero@astrazeneca.com>
Natasha A. Karp, <natasha.karp@astrazeneca.com>

ui	<i>'shiny' app user interface function</i>
----	--

Description

This is an internal function. Please use cautiously if calling directly.

Usage

```
ui()
```

Author(s)

Maria Luisa Guerriero, <maria.guerriero@astrazeneca.com>
Natasha A. Karp, <natasha.karp@astrazeneca.com>

`varyingPDXnPDXrBiolRR` *Function to run simulations to mimic population PDX studies for variety of experimental and biological scenarios*

Description

This is an internal function. Please use cautiously if calling directly. Simulations are used to mimic population PDX studies by inputting a variety of experimental factors (PDXn and PDXr) and biological factors (Biol_RR and C_Acc). Example usage: `varyingPDXnPDXrBiolRR(PDXn_range=c(8,10,12), PDXr_range=c(1,3,5), Biol_RR_range=c(30,40,50), C_Acc=0.95, iterations=500)`

Usage

```
varyingPDXnPDXrBiolRR(PDXn_range, PDXr_range, Biol_RR_range, C_Acc, iterations)
```

Arguments

<code>PDXn_range</code>	a vector of PDXn values to study
<code>PDXr_range</code>	a vector of PDXr values to study
<code>Biol_RR_range</code>	a vector of values between 0 and 100 to indicate the Biol_RR to study
<code>C_Acc</code>	the classification accuracy (numeric value between 0 and 1)
<code>iterations</code>	iterations

Value

a dataframe where each row represents the results from a simulation mimicking an individual experiment for a particular design with meta data returned to describe the experimental design

Author(s)

Maria Luisa Guerriero, <maria.guerriero@astrazeneca.com>
 Natasha A. Karp, <natasha.karp@astrazeneca.com>

Index

`callsInSingleExperiment`, [2](#)

`getMode`, [3](#)

`noFalseCalls`, [3](#)

`noMissedCalls`, [4](#)

`outcomeInSingleExperiment`, [5](#)

`outcomeMultipleExperiments`, [5](#)

`plotFalsepositive`, [6](#)

`plotSensitivity`, [7](#)

`populationPDXdesignApp`, [7](#)

`server`, [8](#)

`ui`, [8](#)

`varyingPDXnPDXrBio1RR`, [9](#)