

Package ‘probe’

July 23, 2025

Type Package

Title Sparse High-Dimensional Linear Regression with PROBE

Version 1.1

Date 2023-10-01

Description Implements an efficient and powerful Bayesian approach for sparse high-dimensional linear regression. It uses minimal prior assumptions on the parameters through plug-in empirical Bayes estimates of hyperparameters. An efficient Parameter-Expanded Expectation-Conditional-Maximization (PX-ECM) algorithm estimates maximum a posteriori (MAP) values of regression parameters and variable selection probabilities. The PX-ECM results in a robust computationally efficient coordinate-wise optimization, which adjusts for the impact of other predictor variables. The E-step is motivated by the popular two-group approach to multiple testing. The result is a PaRtitiOned empirical Bayes Ecm (PROBE) algorithm applied to sparse high-dimensional linear regression, implemented using one-at-a-time or all-at-once type optimization. More information can be found in McLain, Zgodic, and Bondell (2022) <[doi:10.48550/arXiv.2209.08139](https://doi.org/10.48550/arXiv.2209.08139)>.

BugReports <https://github.com/alexmcclain/PROBE/issues>

License GPL (>= 2)

Encoding UTF-8

RoxygenNote 7.2.3

Imports Rcpp, glmnet

LinkingTo Rcpp, RcppArmadillo

NeedsCompilation yes

Depends R (>= 4.00)

Author Alexander McLain [aut, cre] (ORCID:
<<https://orcid.org/0000-0002-5475-0670>>),
Anja Zodiac [aut, ctb]

Maintainer Alexander McLain <mclaina@mailbox.sc.edu>

Repository CRAN

Date/Publication 2023-10-31 16:30:02 UTC

Contents

probe-package	2
e_step_func	3
m_step_regression	4
predict_probe_func	4
probe	5
probe_one	7
Sim_data	10
Sim_data_cov	11
Sim_data_test	11
Index	13

probe-package	<i>probe: Sparse High-Dimensional Linear Regression with PROBE</i>
---------------	--

Description

Implements an efficient and powerful Bayesian approach for sparse high-dimensional linear regression. It uses minimal prior assumptions on the parameters through plug-in empirical Bayes estimates of hyperparameters. An efficient Parameter-Expanded Expectation-Conditional-Maximization (PX-ECM) algorithm estimates maximum a posteriori (MAP) values of regression parameters and variable selection probabilities. The PX-ECM results in a robust computationally efficient coordinate-wise optimization, which adjusts for the impact of other predictor variables. The E-step is motivated by the popular two-group approach to multiple testing. The result is a PaRtitiOned empirical Bayes Ecm (PROBE) algorithm applied to sparse high-dimensional linear regression, implemented using one-at-a-time or all-at-once type optimization. More information can be found in McLain, Zgodic, and Bondell (2022) [arXiv:2209.08139](#).

Details

Examples for applying PROBE to sparse high-dimensional linear regression are given for one-at-a-time [probe_one](#) or all-at-once [probe](#) type optimization.

Author(s)

Maintainer: Alexander McLain <mclaina@mailbox.sc.edu> ([ORCID](#))

Authors:

- Anja Zodiac [contributor]

References

- McLain, A. C., Zgodic, A., & Bondell, H. (2022). Sparse high-dimensional linear regression with a partitioned empirical Bayes ECM algorithm. arXiv preprint arXiv:2209.08139.

See Also

Useful links:

- Report bugs at <https://github.com/alexmclain/PROBE/issues>

e_step_func

Function for fitting the empirical Bayes portion of the E-step

Description

A wrapper function estimating posterior expectations of the γ variables using an empirical Bayesian technique.

Usage

```
e_step_func(beta_t, beta_var, df, adj = 5, lambda = 0.1, monotone = TRUE)
```

Arguments

beta_t	Expectation of the posterior mean (assuming $\gamma = 1$)
beta_var	Current posterior variance (assuming $\gamma = 1$)
df	Degrees of freedom for the t-distribution (use to calculate p-values).
adj	Bandwidth multiplier to Silverman's 'rule of thumb' for calculating the marginal density of the test-statistics (default = 5).
lambda	Value of the λ parameter for estimating the proportion of null hypothesis using Storey et al. (2004) (default = 0.1).
monotone	Logical - Should the estimated marginal density of the test-statistics be monotone non-increasing from zero (default = TRUE).

Value

A list including

delta estimated posterior expectations of the γ .

pi0 estimated proportion of null hypothesis

References

Storey, J. D., Taylor, J. E., and Siegmund, D. (2004), "Strong control, conservative point estimation and simultaneous conservative consistency of false discovery rates: A unified approach," J. R. Stat. Soc. Ser. B. Stat. Methodol., 66, 187–205. McLain, A. C., Zgodic, A., & Bondell, H. (2022). Sparse high-dimensional linear regression with a partitioned empirical Bayes ECM algorithm. arXiv preprint arXiv:2209.08139.

m_step_regression	<i>Function for fitting the initial part of the M-step</i>
-------------------	--

Description

A wrapper function providing the quantities related to the M-step for α_0 and σ^2 .

Usage

```
m_step_regression(Y, W, W2, Z = NULL, a = -3/2, Int = TRUE)
```

Arguments

Y	A matrix containing the outcome Y
W	Quantity $E(W_0)$ as outlined in citation, output from W_update_fun
W2	Quantity $E(W_0^2)$ as outlined in citation, output from W_update_fun
Z	A matrix or dataframe of other predictors to account for
a	(optional) parameter for changing the hyperparameter a (default, $a = -3/2$ uses $n - 2$ as denominator for MAP of σ^2)
Int	(optional) Logical - should an intercept be used?

Value

A list including
 coef the MAP estimates of the α_0 parameters
 sigma2_est the MAP estimate of σ^2
 VCV posterior variance covariance matrix of α_0 ,
 res_data dataframe containing MAP estimates, posterior variances, t-test statistics and associated p-values for α_0

References

McLain, A. C., Zgodic, A., & Bondell, H. (2022). Sparse high-dimensional linear regression with a partitioned empirical Bayes ECM algorithm. arXiv preprint arXiv:2209.08139.

predict_probe_func	<i>Obtaining predictions, confidence intervals and prediction intervals from probe</i>
--------------------	--

Description

A function providing predictions, along with $(1 - \alpha) * 100\%$ credible, and prediction intervals for new observations.

Usage

```
predict_probe_func(res, X, Z = NULL, alpha = 0.05, X_2 = NULL)
```

Arguments

<code>res</code>	The results from the probe function.
<code>X</code>	A matrix containing the predictors on which to apply the probe algorithm
<code>Z</code>	(optional) A matrix or dataframe of predictors not subjected to the sparsity assumption to account for.
<code>alpha</code>	significance level for $(100(1 - \alpha)\%)$ credible and prediction intervals.
<code>X_2</code>	(optional) Square of X matrix.

Value

A dataframe with predictions, credible intervals, and prediction intervals for each new observation.

References

McLain, A. C., Zgodic, A., & Bondell, H. (2022). Sparse high-dimensional linear regression with a partitioned empirical Bayes ECM algorithm. arXiv preprint arXiv:2209.08139. Zgodic, A., Bai, R., Zhang, J., Wang, Y., Rorden, C., & McLain, A. (2023). Heteroscedastic sparse high-dimensional linear regression with a partitioned empirical Bayes ECM algorithm. arXiv preprint arXiv:2309.08783.

Examples

```
### Example
data(Sim_data)
data(Sim_data_test)
attach(Sim_data)
attach(Sim_data_test)
alpha <- 0.05
plot_ind <- TRUE
adj <- 10

# Run the analysis. Y_test and X_test are included for plotting purposes only
full_res <- probe( Y = Y, X = X, Y_test = Y_test,
X_test = X_test, alpha = alpha, plot_ind = plot_ind, adj = adj)

# Predicting for test data
pred_res <- predict_probe_func(full_res, X = X_test, alpha = alpha)
sqrt(mean((Y_test - pred_res$Pred)^2))
head(pred_res)
```

probe	<i>Fitting PaRtitiOned empirical Bayes Ecm (PROBE) algorithm to sparse high-dimensional linear models.</i>
-------	--

Description

A wrapper function for the all-at-once variant of the PROBE algorithm.

Usage

```
probe(Y, X, Z = NULL, ep = 0.1, maxit = 10000, Y_test = NULL, X_test = NULL,
      Z_test = NULL, verbose = FALSE, signal = NULL, eta_i = NULL, alpha = 0.05,
      plot_ind = FALSE, adj = 5)
```

Arguments

Y	The outcome variable.
X	An $n \times M$ matrix of sparse predictors variables.
Z	(optional) An $n \times p$ matrix or dataframe of other predictors not subjected to the sparsity assumption.
ep	Value against which to compare convergence criterion (default = 0.1).
maxit	Maximum number of iterations the algorithm will run for (default = 10000).
Y_test	(optional) Test Y data used plotting purposes only (doesn't impact results).
X_test	(optional) Test X data used plotting purposes only (doesn't impact results).
Z_test	(optional) Test Z data used plotting purposes only (doesn't impact results).
verbose	A logical (true/false) value whether to print algorithm iteration progress and summary quantities (default = FALSE).
signal	(optional) A vector of indices of the true non-null coefficients. This is used to calculate the true and false discovery rates by iteration for simulated data. Used plotting purposes only (doesn't impact results).
eta_i	(optional) A vector of the true signal. This is used to calculate the MSE by iteration for simulated data. Used plotting purposes only (doesn't impact results).
alpha	(optional) significance level
plot_ind	A logical values (True/False) for whether to output plots on algorithm results and progress (default = FALSE)
adj	Bandwidth parameter for empirical Bayes E-step. The bandwidth will be equal to adj times Silverman's 'rule of thumb' (default = 2).

Value

A list including

beta_ast_hat MAP estimates of the regression coefficients (β^*),

beta_hat, beta_hat_var MAP estimates of the posterior expectation (beta_hat) and variance (beta_hat_var) of the prior mean (β) of the regression coefficients assuming $\gamma = 1$,

gamma_hat the posterior expectation of the latent γ variables,

sigma2_est MAP estimate of the residual variance,

E_step full results of the final E_step,

Calb_mod results of first (α_0) part of the M-step,

count the total number of iterations before convergence.

References

McLain, A. C., Zgodic, A., & Bondell, H. (2022). Sparse high-dimensional linear regression with a partitioned empirical Bayes ECM algorithm. arXiv preprint arXiv:2209.08139..

See Also

`predict_probe_func` to obtain predictions, credible intervals and prediction intervals from PROBE.

Examples

```
### Example
data(Sim_data)
data(Sim_data_test)
attach(Sim_data)
attach(Sim_data_test)
alpha <- 0.05
plot_ind <- TRUE
adj <- 10

# Run the analysis. Y_test and X_test are included for plotting purposes only
full_res <- probe( Y = Y, X = X, Y_test = Y_test,
X_test = X_test, alpha = alpha, plot_ind = plot_ind, adj = adj)

# Predicting for test data
pred_res <- predict_probe_func(full_res, X = X_test)
sqrt(mean((Y_test - pred_res$Pred)^2))

# Estimate of the residual variance and true value
full_res$sigma2_est
sigma2_tr

# RMSE of estimated beta coefficients
beta_ast_est <- full_res$beta_ast_hat
sqrt(mean((beta_ast_est - beta_tr)^2))

# Posterior expectation of gamma by true
gamma_est <- full_res$E_step$gamma
sum(gamma_est)
sum(gamma_est[beta_tr>0])

### Examples that incorporate additional covariate data (Z)
### not subjected to the sparsity assumption available on Github.
```

Description

A wrapper function for the one-at-a-time variant of the PROBE algorithm.

Usage

```
probe_one(Y, X, ep = 0.001, maxit = 10000, Y_test = NULL, X_test = NULL,
  verbose = FALSE, signal = NULL, eta_i = NULL, alpha = 0.05, plot_ind = FALSE,
  order.method = "lasso", adj = 10, delta = 0.4, update_order = NULL, beta_start = NULL,
  seed = NULL)
```

Arguments

Y	The outcome variable.
X	An n x M matrix of sparse predictors variables.
ep	Value against which to compare convergence criterion (default = 0.001).
maxit	Maximum number of iterations the algorithm will run for (default = 10000).
Y_test	(optional) Test Y data used plotting purposes only (doesn't impact results).
X_test	(optional) Test X data used plotting purposes only (doesn't impact results).
verbose	A logical (true/false) value whether to print algorithm iteration progress and summary quantities (default = FALSE).
signal	(optional) A vector of indices of the true non-null coefficients. This is used to calculate the true and false discovery rates by iteration for simulated data. Used plotting purposes only (doesn't impact results).
eta_i	(optional) A vector of the true signal. This is used to calculate the MSE by iteration for simulated data. Used plotting purposes only (doesn't impact results).
alpha	(optional) significance level
plot_ind	A logical values (True/False) for whether to output plots on algorithm results and progress (default = FALSE)
order.method	Updating order and initial values of the algorithm. For lasso (default) or ridge, a lasso or a ridge regression model (fit with 10-fold CV) will be fitted and used. The update_order is defined by the absolute values of the coefficient and beta_start is the coefficient values. When using none, update_order and beta_start must be given. random will randomly select the updating order and use very small values for beta_start.
adj	Bandwidth parameter for empirical Bayes E-step. The bandwidth will be equal to adj times Silverman's 'rule of thumb' (default = 10).
delta	Learning rate for iteration t is $(1 + t)^{-1 + \delta}$ (default delta = 0.4).
update_order	Manual value for the updating order for when order.method = "none" is used.
beta_start	Manual value for the starting beta coefficients for when order.method = "none" is used.
seed	Seed value to ensure reproducibility when order.method = "lasso", order.method = "ridge", or order.method = "random".

Value

A list including

- beta_ast_hat MAP estimates of the regression coefficients (β^*),
- beta_hat, beta_hat_var MAP estimates of the posterior expectation (beta_hat) and variance (beta_hat_var) of the prior mean (β) of the regression coefficients assuming $\gamma = 1$,
- gamma_hat the posterior expectation of the latent γ variables,
- sigma2_est MAP estimate of the residual variance,
- E_step full results of the final E_step,
- count the total number of iterations before convergence.

References

McLain, A. C., Zgodic, A., & Bondell, H. (2022). Sparse high-dimensional linear regression with a partitioned empirical Bayes ECM algorithm. arXiv preprint arXiv:2209.08139..

See Also

predict_probe_func to obtain predictions.

Examples

```
### Example
data(Sim_data)
data(Sim_data_test)
attach(Sim_data)
attach(Sim_data_test)
plot_ind <- TRUE
adj <- 10

# Run the analysis. Y_test and X_test are included for plotting purposes only
full_res <- probe_one( Y = Y, X = X, Y_test = Y_test, order.method = "random",
X_test = X_test, plot_ind = plot_ind, adj = adj)

# Predicting for test data
pred_res <- predict_probe_func(full_res, X = X_test)
sqrt(mean((Y_test - pred_res$Pred)^2))

# Estimate of the residual variance and true value
full_res$sigma2_est
sigma2_tr

# RMSE of estimated beta coefficients
beta_ast_est <- c(full_res$beta_ast_hat)
sqrt(mean((beta_ast_est - beta_tr)^2))

# Posterior expectation of gamma by true
gamma_est <- full_res$E_step$gamma
table(gamma_est > 0.5, beta_tr > 0)
sum(gamma_est)
```

```
sum(gamma_est[beta_tr>0])
```

Sim_data

Simulated high-dimensional data set for sparse linear regression

Description

This dataset was simulated using a 20×20 2-dimensional setting described in the reference. The data contains 400 subjects with one outcome and 400 predictor variables. The test outcomes and predictor variables are contained in Sim_data_test.

Usage

```
data("Sim_data")
```

Format

A data frame with 400 observations and the following objects:

Y Outcome variable of length 400.

X A 400×400 matrix of binary predictor variables.

signal The locations of the non-zero regression coefficients.

beta_tr The true values of all 400 regression coefficients.

sigma2_tr The true value of the residual variance.

Source

Simulated data.

Examples

```
data(Sim_data)
attach(Sim_data)
length(Y)
dim(X)
```

Sim_data_cov	<i>Simulated high-dimensional data set for sparse linear regression with non-sparse covariates.</i>
--------------	---

Description

This dataset was simulated using a 100×100 2-dimensional setting described in the reference only two covariates are added. The data contains 400 subjects with one outcome, 10000 predictor variables which are to be subjected to the sparsity assumption, and 2 covariates which are not to be subjected to the sparsity assumption.

Usage

```
data("Sim_data_cov")
```

Format

A data frame with 400 observations and the following objects:

Y Outcome variable of length 400.

Z A dataframe of a continuous (Cont_cov) and binary (Binary_cov) covariate.

X A 400×10000 matrix of binary predictor variables.

beta_tr The true values of all 10000 regression coefficients.

beta_Z_tr The true values of the intercept, Cont_cov, and Binary_cov.

signal The locations of the non-zero regression coefficients.

Examples

```
data(Sim_data_cov)
str(Sim_data_cov)
```

Sim_data_test	<i>Simulated high-dimensional test data set for sparse linear regression</i>
---------------	--

Description

A test set of outcomes and predictor variables to be used with Sim_data.

Usage

```
data("Sim_data_test")
```

Format

A data frame with 400 observations and the following objects:

Y_test Outcome variable of length 400 for test set.

Z_test A 400×400 matrix of binary predictor variables for test set.

Source

Simulated data.

Examples

```
data(Sim_data_test)
attach(Sim_data_test)
length(Y_test)
dim(X_test)
```

Index

* datasets

- Sim_data, [10](#)
- Sim_data_cov, [11](#)
- Sim_data_test, [11](#)
- _PACKAGE (probe-package), [2](#)

e_step_func, [3](#)

m_step_regression, [4](#)

predict_probe_func, [4](#)

probe, [2](#), [5](#)

probe-package, [2](#)

probe_one, [2](#), [7](#)

Sim_data, [10](#)

Sim_data_cov, [11](#)

Sim_data_test, [11](#)