

Package ‘rawKS’

July 23, 2025

Title Easily Get True-Positive Rate and False-Positive Rate and KS
Statistic

Version 0.1.0

Description

The Kolmogorov-Smirnov (K-S) statistic is a standard method to measure the model strength for credit risk scoring models. This package calculates the K-S statistic and plots the true-positive rate and false-positive rate to measure the model strength.

This package was written with the credit marketer, who uses risk models in conjunction with his campaigns. The users could read more details from Thrasher (1992) <[doi:10.1002/dir.4000060408](https://doi.org/10.1002/dir.4000060408)> and 'pyks' <<https://pypi.org/project/pyks/>>.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Imports dplyr, magrittr, ROCR, ggplot2, tidyr

RoxygenNote 6.1.1

Depends R (>= 2.10)

Suggests knitr, rmarkdown

VignetteBuilder knitr

NeedsCompilation no

Author Jiaxiang Li [aut, cre] (ORCID: <<https://orcid.org/0000-0003-3196-6492>>)

Maintainer Jiaxiang Li <alex.lijiaxiang@foxmail.com>

Repository CRAN

Date/Publication 2020-02-06 16:00:06 UTC

Contents

ks_plot	2
ks_table	2
two_class_example_edited	3

Index	4
--------------	----------

`ks_plot`*Plot KS chart*

Description

Plot KS chart

Usage

```
ks_plot(df)
```

Arguments

`df` data.frame created by `ks_table`

Value

The 'ggplot2' object

Examples

```
data("two_class_example_edited")
max(ks_table(two_class_example_edited$yhat, two_class_example_edited$y)$ks)
ks_table(two_class_example_edited$yhat, two_class_example_edited$y) %>%
  ks_plot()
```

`ks_table`*Get KS statistics*

Description

Output a `data.frame` with inputs (`y`, `yhat`) and `tpr`, `fpr` and `ks`.

Usage

```
ks_table(yhat, y)
```

Arguments

`yhat` numeric the value predicted by your model.
`y` numeric the target values.

Value

The data frame containing `tpr`, `fpr` and `ks`.

Examples

```
data("two_class_example_edited")
max(ks_table(two_class_example_edited$yhat, two_class_example_edited$y)$ks)
```

```
two_class_example_edited
```

A sample with the target and predictions

Description

A dataset containing two columns, yhat and y as the inputs for the function ks_table.

Usage

```
two_class_example_edited
```

Format

A data frame with 500 rows and 2 variables:

yhat predictions

y target

Source

```
package yardstick::two_class_example
```

Index

* **datasets**

two_class_example_edited, [3](#)

ks_plot, [2](#)

ks_table, [2](#)

two_class_example_edited, [3](#)