

Package ‘rchroma’

July 23, 2025

Type Package

Title A Client for 'ChromaDB'

Version 0.2.0

Description Client for 'ChromaDB', a vector database for storing and querying embeddings. This package provides a convenient interface to interact with the REST API of 'ChromaDB' <<https://docs.trychroma.com>>.

License MIT + file LICENSE

URL <https://github.com/cynkra/rchroma>

BugReports <https://github.com/cynkra/rchroma/issues>

Language en-US

Encoding UTF-8

RoxygenNote 7.3.2

Imports cli, glue, httr2 (>= 1.0.0), processx

Suggests testthat (>= 3.0.0), knitr, rmarkdown, covr, spelling

Config/testthat/edition 3

VignetteBuilder knitr

NeedsCompilation no

Author David Schoch [aut, cre] (ORCID:
<<https://orcid.org/0000-0003-2952-4812>>),
Christoph Sax [aut],
cynkra LLC [cph]

Maintainer David Schoch <david@schochastics.net>

Repository CRAN

Date/Publication 2025-03-26 18:50:01 UTC

Contents

add_documents	2
chroma_connect	3

chroma_docker_run	4
chroma_docker_running	4
chroma_docker_stop	5
count_collections	5
create_collection	6
create_database	7
create_tenant	7
delete_collection	8
delete_documents	8
get_auth_identity	9
get_collection	10
get_database	10
get_tenant	11
heartbeat	11
list_collections	12
pre_flight_checks	12
query	13
reset	14
update_collection	14
update_documents	15
upsert_documents	16
version	17
Index	18

add_documents	<i>Add Documents to a Collection</i>
---------------	--------------------------------------

Description

Add Documents to a Collection

Usage

```
add_documents(  
    client,  
    collection_name,  
    documents,  
    ids,  
    metadatas = NULL,  
    embeddings = NULL,  
    uris = NULL,  
    tenant = "default_tenant",  
    database = "default_database"  
)
```

Arguments

client	A ChromaDB client object
collection_name	Name of the collection
documents	List of documents to add
ids	Vector of unique IDs for the documents (required)
metadatas	List of metadata for each document (optional)
embeddings	Optional pre-computed embeddings
uris	Optional vector of URIs associated with the documents
tenant	The tenant name (default: "default")
database	The database name (default: "default")

Value

TRUE on success

chroma_connect	<i>ChromaDB Client</i>
----------------	------------------------

Description

Create a new ChromaDB client connection

Usage

```
chroma_connect(  
    host = "http://localhost",  
    port = 8000L,  
    api_path = "/api/v2",  
    verify = TRUE  
)
```

Arguments

host	The host URL of the ChromaDB server. Default is "http://localhost".
port	The port number of the ChromaDB server. Default is 8000.
api_path	The API path. Default is "/api/v2".
verify	Whether to verify the connection. Default is TRUE.

Value

A ChromaDB client object

chroma_docker_run	<i>Start ChromaDB Docker Container</i>
-------------------	--

Description

This function uses Docker to start a ChromaDB server container in the background.

Usage

```
chroma_docker_run(
    port = 8000,
    volume_host_dir = "./chroma",
    is_persistent = TRUE,
    anonymized_telemetry = FALSE,
    version = "0.6.3",
    container_name = "chromadb"
)
```

Arguments

port	The port for the ChromaDB container.
volume_host_dir	A string specifying the host directory to persist data.
is_persistent	Logical; whether to enable persistence. Defaults to TRUE.
anonymized_telemetry	Logical; whether to enable anonymous telemetry. Defaults to FALSE.
version	A string specifying the version of the ChromDB Docker image. Default is "0.6.3".
container_name	A string specifying the name for the Docker container. Default is "chromadb".

Value

Invisibly returns TRUE if the container is already running or started successfully.

chroma_docker_running	<i>Check ChromaDB Docker Container Status</i>
-----------------------	---

Description

This function checks the status of the ChromaDB Docker container.

Usage

```
chroma_docker_running(container_name = "chromadb")
```

Arguments

container_name A string specifying the name of the Docker container to check.

Value

TRUE if container is running and FALSE otherwise.

chroma_docker_stop	<i>Stop ChromaDB Docker Container</i>
--------------------	---------------------------------------

Description

This function stops the running ChromaDB Docker container. It uses the processx package to issue the Docker stop command.

Usage

```
chroma_docker_stop(container_name = "chromadb")
```

Arguments

container_name A string specifying the name of the Docker container to stop.

Value

Invisibly returns TRUE if the container was stopped or is not running.

count_collections	<i>Count Collections in a Database</i>
-------------------	--

Description

Count Collections in a Database

Usage

```
count_collections(  
  client,  
  tenant = "default_tenant",  
  database = "default_database"  
)
```

Arguments

client	A ChromaDB client object
tenant	The tenant name (default: "default")
database	The database name (default: "default")

Value

Number of collections in the database

create_collection	Create a Collection in ChromaDB
-------------------	---------------------------------

Description

Create a Collection in ChromaDB

Usage

```
create_collection(  
    client,  
    name,  
    metadata = NULL,  
    configuration = NULL,  
    tenant = "default_tenant",  
    database = "default_database",  
    get_or_create = FALSE  
)
```

Arguments

client	A ChromaDB client object
name	The name of the collection
metadata	Optional metadata for the collection
configuration	Optional configuration for the collection. For HNSW configuration, use a list with hnspace (e.g., "cosine", "l2", "ip").
tenant	The tenant name (default: "default")
database	The database name (default: "default")
get_or_create	Whether to get the collection if it exists (default: FALSE)

Value

A collection object

create_database	<i>Create a Database</i>
-----------------	--------------------------

Description

Create a Database

Usage

```
create_database(client, name, tenant = "default_tenant")
```

Arguments

client	A ChromaDB client object
name	The name of the database
tenant	The tenant name

Value

NULL invisibly on success

create_tenant	<i>Create a Tenant</i>
---------------	------------------------

Description

Create a Tenant

Usage

```
create_tenant(client, name)
```

Arguments

client	A ChromaDB client object
name	The name of the tenant

Value

A tenant object containing the tenant details

delete_collection	<i>Delete a Collection</i>
-------------------	----------------------------

Description

Delete a Collection

Usage

```
delete_collection(  
    client,  
    name,  
    tenant = "default_tenant",  
    database = "default_database"  
)
```

Arguments

client	A ChromaDB client object
name	The name of the collection
tenant	The tenant name (default: "default")
database	The database name (default: "default")

Value

Invisible NULL on success

delete_documents	<i>Delete Documents from a Collection</i>
------------------	---

Description

Delete Documents from a Collection

Usage

```
delete_documents(  
    client,  
    collection_name,  
    ids = NULL,  
    where = NULL,  
    tenant = "default_tenant",  
    database = "default_database"  
)
```


Arguments

client	A ChromaDB client object
collection_name	Name of the collection
ids	Vector of document IDs to delete
where	Optional filtering conditions
tenant	The tenant name (default: "default")
database	The database name (default: "default")

Value

NULL invisibly on success

get_auth_identity	<i>Get Authentication Identity</i>
-------------------	------------------------------------

Description

Get Authentication Identity

Usage

get_auth_identity(client)

Arguments

client	A ChromaDB client object
--------	--------------------------

Value

Authentication identity information

get_collection	<i>Get a Collection</i>
----------------	-------------------------

Description

Get a Collection

Usage

```
get_collection(  
    client,  
    name,  
    tenant = "default_tenant",  
    database = "default_database"  
)
```

Arguments

client	A ChromaDB client object
name	The name of the collection
tenant	The tenant name (default: "default")
database	The database name (default: "default")

Value

A collection object

get_database	<i>Get a Database</i>
--------------	-----------------------

Description

Get a Database

Usage

```
get_database(client, name, tenant = "default_tenant")
```

Arguments

client	A ChromaDB client object
name	The name of the database
tenant	The tenant name

Value

NULL invisibly on success

`get_tenant`*Get a Tenant*

Description

Get a Tenant

Usage

```
get_tenant(client, name)
```

Arguments

<code>client</code>	A ChromaDB client object
<code>name</code>	The name of the tenant

Value

A tenant object containing the tenant details

`heartbeat`*Check ChromaDB Server Heartbeat*

Description

Check ChromaDB Server Heartbeat

Usage

```
heartbeat(client)
```

Arguments

<code>client</code>	A ChromaDB client object
---------------------	--------------------------

Value

Server heartbeat response as a numeric value

list_collections	List Collections in a Database
------------------	--------------------------------

Description

List Collections in a Database

Usage

```
list_collections(  
  client,  
  tenant = "default_tenant",  
  database = "default_database",  
  limit = NULL,  
  offset = NULL  
)
```

Arguments

client	A ChromaDB client object
tenant	The tenant name (default: "default")
database	The database name (default: "default")
limit	Maximum number of collections to return (optional)
offset	Number of collections to skip (optional)

Value

List of collections

pre_flight_checks	Get ChromaDB Server Information
-------------------	---------------------------------

Description

Returns server capabilities and settings.

Usage

```
pre_flight_checks(client)
```

Arguments

client	A ChromaDB client object
--------	--------------------------

Value

List containing server information

query

Query Documents in a Collection

Description

Query Documents in a Collection

Usage

```
query(  
    client,  
    collection_name,  
    query_embeddings,  
    n_results = 10L,  
    where = NULL,  
    where_document = NULL,  
    include = c("documents", "metadatas", "distances"),  
    tenant = "default_tenant",  
    database = "default_database"  
)
```

Arguments

client	A ChromaDB client object
collection_name	Name of the collection
query_embeddings	List of query embeddings (must be a list of numeric vectors)
n_results	Number of results to return per query (default: 10)
where	Optional filtering conditions
where_document	Optional document-based filtering conditions
include	Optional vector of what to include in results. Possible values: "documents", "embeddings", "metadatas", "distances", "uris", "data" (default: c("documents", "metadatas", "distances"))
tenant	The tenant name (default: "default")
database	The database name (default: "default")

Details

Note that ChromaDB's API only accepts embeddings for queries. If you want to query using text, you need to first convert your text to embeddings using an embedding model (e.g., using OpenAI's API, HuggingFace's API, or a local model).

Example:

```
# First convert text to embeddings using your preferred method
text_embedding <- your_embedding_function("your search text")
# Then query using the embedding
result <- query(client, "my_collection",
               query_embeddings = list(text_embedding))
```

Value

A list containing the query results. Each element (documents, metadatas, distances) is a nested list, so use double brackets [[]] to access individual elements.

reset

Reset ChromaDB

Description

This function resets the entire ChromaDB instance. Use with caution as this will delete all data. Note: This function requires setting ALLOW_RESET=TRUE in the environment variables or allow_reset=True in the ChromaDB Settings.

Usage

```
reset(client)
```

Arguments

client	A ChromaDB client object
--------	--------------------------

Value

TRUE on success

update_collection

Update a Collection

Description

Update a Collection

Usage

```
update_collection(
  client,
  name,
  new_name = NULL,
  new_metadata = NULL,
  tenant = "default_tenant",
  database = "default_database"
)
```

Arguments

client	A ChromaDB client object
name	The name of the collection
new_name	Optional new name for the collection
new_metadata	Optional new metadata for the collection
tenant	The tenant name (default: "default")
database	The database name (default: "default")

Value

NULL on success (invisibly)

update_documents	<i>Update Documents in a Collection</i>
------------------	---

Description

Update Documents in a Collection

Usage

```
update_documents(  
    client,  
    collection_name,  
    ids,  
    documents = NULL,  
    metadatas = NULL,  
    embeddings = NULL,  
    tenant = "default_tenant",  
    database = "default_database"  
)
```

Arguments

client	A ChromaDB client object
collection_name	Name of the collection
ids	Vector of document IDs to update
documents	List of new document contents
metadatas	List of new metadata
embeddings	Optional new pre-computed embeddings
tenant	The tenant name (default: "default")
database	The database name (default: "default")

Value

NULL invisibly on success

upsert_documents	<i>Upsert Documents to a Collection</i>
------------------	---

Description

Upsert Documents to a Collection

Usage

```
upsert_documents(  
  client,  
  collection_name,  
  documents,  
  metadatas = NULL,  
  ids = NULL,  
  embeddings = NULL,  
  uris = NULL  
)
```

Arguments

client	A ChromaDB client object
collection_name	Name of the collection
documents	List of documents to upsert
metadatas	List of metadata for each document
ids	Vector of unique IDs for the documents
embeddings	Optional pre-computed embeddings
uris	Optional vector of URIs associated with the documents

Value

Response from the API

version	<i>Get ChromaDB Server Version</i>
---------	------------------------------------

Description

Get ChromaDB Server Version

Usage

version(client)

Arguments

client A ChromaDB client object

Value

Server version string

Index

`add_documents`, [2](#)

`chroma_connect`, [3](#)
`chroma_docker_run`, [4](#)
`chroma_docker_running`, [4](#)
`chroma_docker_stop`, [5](#)
`count_collections`, [5](#)
`create_collection`, [6](#)
`create_database`, [7](#)
`create_tenant`, [7](#)

`delete_collection`, [8](#)
`delete_documents`, [8](#)

`get_auth_identity`, [9](#)
`get_collection`, [10](#)
`get_database`, [10](#)
`get_tenant`, [11](#)

`heartbeat`, [11](#)

`list_collections`, [12](#)

`pre_flight_checks`, [12](#)

`query`, [13](#)

`reset`, [14](#)

`update_collection`, [14](#)
`update_documents`, [15](#)
`upsert_documents`, [16](#)

`version`, [17](#)