

Package ‘rct3’

July 23, 2025

Version 1.0.4

Date 2020-09-17

Title Predict Fish Year-Class Strength from Survey Data

LazyData yes

Description Predict fish year-class strength by calibration
regression analysis of multiple recruitment index series.

License GPL-3

Encoding UTF-8

RoxygenNote 7.1.1

NeedsCompilation no

Author Colin Millar [aut, cre],
Marc Taylor [aut]

Maintainer Colin Millar <colin.millar@ices.dk>

Repository CRAN

Date/Publication 2020-09-25 13:10:02 UTC

Contents

rct3-package	2
print.rct3	2
rct3	3
recdata	5
summary.rct3	6
Index	8

rct3-package

*Predict Fish Year-Class Strength from Survey Data***Description**

Predict fish year-class strength by calibration regression analysis of multiple recruitment index series.

Details

Functions:

<code>rct3</code>	run a calibrated regression to predict recruitment
<code>print.rct3</code>	print a rct3 object
<code>summary.rct3</code>	summarise a rct3 object

#' Data sets:

<code>recdata</code>	example dataset of recruitment and survey indices
----------------------	---

References

J. G. Shepherd, Prediction of year-class strength by calibration regression analysis of multiple recruit index series, ICES Journal of Marine Science, Volume 54, Issue 5, October 1997, Pages 741–752, <https://doi.org/10.1006/jmsc.1997.0222>

print.rct3

*Print an rct3 fit***Description**

Print an rct3 fit showing the model settings and predicted recruitments

Usage

```
## S3 method for class 'rct3'
print(x, digits = max(3, getOption("digits") - 3), ...)
```

Arguments

<code>x</code>	an object of class rct3 - an output from the rct3 function.
<code>digits</code>	optional integer for how much to round the values in the output tables.
<code>...</code>	additional arguments to print.data.frame

Value

invisibly returns a summary data frame.

See Also

[rct3](#) run a calibrated regression to predict recruitment.

[summary.rct3](#) summarise a rct3 object

[rct3-package](#) gives an overview of the package.

Examples

```
# load recruitment data
data(recdata)

formula <-
  recruitment ~ NT1 + NT2 + NT3 + NAK1 + NAK2 + NAK3 +
    RT1 + RT2 + RT3 + EC01 + EC02 + EC03

my_rct3 <- rct3(formula, recdata, predictions = 2012:2017, shrink = TRUE)

# see a short summary
my_rct3

# for a full summary do:
summary(my_rct3)

# the components are here:
my_rct3$rct3
my_rct3$rct3.summary

# predicted recruitment
t(my_rct3$rct3.summary["WAP"])
```

rct3

Run a calibrated regression to predict recruitment

Description

Function to run a calibrated regression to predict recruitment using the method described by Shepherd (1997)

Usage

```
rct3(
  formula,
  data,
  predictions = NULL,
```

```

    shrink = FALSE,
    power = 3,
    range = 20,
    min.se = 0.2,
    old = TRUE
  )

```

Arguments

formula	a formula to define which surveys to use in the recruitment estimation.
data	a dataframe with one column named 'yearclass' and other columns with the recruitment and the survey index relevant for that recruitment value
predictions	which yearclasses to make recruitment predictions for
shrink	shrink predictions to the VPA mean?
power	the power to use 0 - no weighting, 2 - bisquare, 3 - tricubic
range	the year range to use in the time tapered weighting
min.se	the minimum standard error used in the weighting of predictions
old	default TRUE, defines how to treat zero values. In the original implementation values were transformed using $\log(x + 1)$, old=TRUE maintains this.

Value

Object of class rct3.

Note

This function was written based on the publication by Shepherd (1997) with additional reverse engineering by comparing results to previous examples run using the RCT3 ver3.1 dos program

References

J. G. Shepherd, Prediction of year-class strength by calibration regression analysis of multiple recruit index series, ICES Journal of Marine Science, Volume 54, Issue 5, October 1997, Pages 741–752, <https://doi.org/10.1006/jmsc.1997.0222>

See Also

[rct3-package](#) gives an overview of the package.

Examples

```

# load recruitment data
data(repdata)

formula <- recruitment ~ NT1 + NT2 + NT3 +
  NAK1 + NAK2 + NAK3 +
  RT1 + RT2 + RT3 +
  EC01 + EC02 + EC03

```

```

my_rct3 <- rct3(formula, reodata, predictions = 2012:2017, shrink = TRUE)

# see a short summary
my_rct3

# for a full summary do:
summary(my_rct3)

# the components are here:
my_rct3$rct3
my_rct3$rct3.summary

# predicted recruitment
t(my_rct3$rct3.summary["WAP"])

```

reodata	<i>Recruitment and survey index data</i>
---------	--

Description

data.frame containing recruitment (age 3) and survey indices from several surveys over ages 1 to 3

Usage

```
reodata
```

Format

Data frame containing 14 columns:

yearclass	the yearclass
recruitment	the recruitment (age 3) for that yearclass
NT1	The age 1 survey index from 'NT' survey
NT2	The age 2 survey index from 'NT' survey
...	and so on

See Also

[rct3](#) run a calibrated regression to predict recruitment.

[rct3-package](#) gives an overview of the package.

summary.rct3	<i>Summarise an rct3 fit</i>
--------------	------------------------------

Description

Print an rct3 fit showing the model settings, a summary of the prediction for each yearclass and the overall predicted recruitments

Usage

```
## S3 method for class 'rct3'
summary(object, digits = max(3, getOption("digits") - 3), ...)
```

Arguments

object	an object of class rct3 - an output from the rct3 function.
digits	optional integer for how much to round the values in the output tables.
...	additional arguments to print.data.frame

Value

invisibly returns a summary data frame.

See Also

[rct3](#) run a calibrated regression to predict recruitment.

[rct3-package](#) gives an overview of the package.

Examples

```
# load recruitment data
data(recdata)

formula <- recruitment ~ NT1 + NT2 + NT3 +
  NAK1 + NAK2 + NAK3 +
  RT1 + RT2 + RT3 +
  EC01 + EC02 + EC03

my_rct3 <- rct3(formula, recdata, predictions = 2012:2017, shrink = TRUE)

# see a short summary
my_rct3

# for a full summary do:
summary(my_rct3)

# the components are here:
my_rct3$rct3
```

summary.rct3

7

```
my_rct3$rct3.summary  
  
# predicted recruitment  
t(my_rct3$rct3.summary["WAP"])
```

Index

`print.rct3`, [2](#), [2](#)

`rct3`, [2](#), [3](#), [3](#), [5](#), [6](#)

`rct3-package`, [2](#)

`reodata`, [2](#), [5](#)

`summary.rct3`, [2](#), [3](#), [6](#)