

Package ‘rdian’

July 23, 2025

Type Package
Title Client Library for The Guardian
Version 0.1.1
Date 2016-02-05
Author Oliver Keyes
Maintainer Oliver Keyes <ironholds@gmail.com>
Description A client library for 'The Guardian' (<https://www.guardian.com/>) and their API, this package allows users to search for Guardian articles and retrieve both the content and metadata.
License MIT + file LICENSE
Suggests testthat
Imports httr, curl
URL <https://github.com/ironholds/rdian>
BugReports <https://github.com/ironholds/rdian>
RoxygenNote 5.0.1
NeedsCompilation no
Repository CRAN
Date/Publication 2016-02-05 21:49:14

Contents

guardian_and	2
guardian_content	2
guardian_editions	4
guardian_sections	4
guardian_tags	5
rdian	6
Index	7

guardian_and	<i>AND and OR operators for Guardian filters and queries.</i>
--------------	---

Description

guardian_and and guardian_or provide (respectively) the AND and OR logical operators. If you pass them your query terms, it passes them back either separated (so that the Guardian API knows to consider a match to any *one* term a match) or grouped (so that the API only matches if every term appears).

Usage

```
guardian_and(...)
```

```
guardian_or(...)
```

Arguments

... a vector of terms (or several vector of terms)

Value

a single string containing the terms, separated by the AND (.) or OR (!) separators used by the Guardian API.

Examples

```
# Simple AND example
guardian_and("sausage", "mash")

# With ORs
guardian_or("sausage", "mash")
```

guardian_content	<i>Search Guardian Content</i>
------------------	--------------------------------

Description

guardian_content lets you directly search The Guardian for content, including support for conditional searches, date-range based filtering, and section or tag based filtering.

Usage

```
guardian_content(api_key, query, from = NULL, to = NULL, section = NULL,
  reference = NULL, reference_type = NULL, tags = NULL, rights = NULL,
  ids = NULL, production_office = NULL, page = NULL, page_size = 50,
  fields = NULL, collapse = TRUE, ...)
```

Arguments

api_key	A key to the Guardian API, which can be obtained here .
query	Your search query. This can contain operators (sausage AND mash) or phrases ("sausage & mash"); by default, searches work as an OR, looking for the presence of any one individual word in the query.
from	the date to limit by. If set, the search will only cover data written after this date. Optional (NULL) by default. Can be set in conjunction with to.
to	Another date to limit by. If set, the search will only cover data written before this date. Optional (NULL) by default. Can be set in conjunction with from.
section	the section, or sections, of <i>The Guardian</i> that you want to limit the search to. Multiple sections may be concatenated together using boolean operators; see guardian_and and guardian_or .
reference	the references to limit the search to; only articles that include those references (and meet other conditions) will be returned. Also accepts boolean operators.
reference_type	the type of reference (such as isbn). Also accepts boolean operators.
tags	the tags to limit the search to; only articles that contain these tags will be returned. Also accepts boolean operators.
rights	limit a search to content with these rights (syndicable content, for example). Options are syndicable and subscription-database. Does not accept boolean operators.
ids	limit a search to content with these IDs, an ID being the standard URL fragment after guardian.com (or co.uk, or...). Does not accept boolean operators.
production_office	the production office(s) to limit to, such as "aus". Accepts boolean operators.
page	a particular page of results to return. Useful when returning multiple sets of data with the same query; you can repeat the query, incrementing the value in page.
page_size	the maximum number of items to return; anywhere between 1 and 50. Set to 50 by default.
fields	additional fields to include in the returned data (when available). Possible values (which should appear in a vector) appear here .
collapse	whether to collapse the actual content into a data.frame. Set to TRUE by default.
...	further arguments to pass to httr's GET.

See Also

[guardian_tags](#) to retrieve metadata about tags.

Examples

```
# Simple example
## Not run:
result <- guardian_content("test", "debate AND economy")

## End(Not run)
```

guardian_editions	<i>Search Guardian Editions</i>
-------------------	---------------------------------

Description

guardian_editions lets you directly search The Guardian for metadata about their editions - country-specific (or international) standard releases for their website's content.

Usage

```
guardian_editions(api_key, query, ...)
```

Arguments

api_key	A key to the Guardian API, which can be obtained here .
query	Your search query.
...	further arguments to pass to httr's GET.

See Also

[guardian_sections](#) for retrieving sections, another category of content.

Examples

```
## Not run:  
# Simple example  
uk_edition_data <- guardian_editions("test", "uk")  
  
## End(Not run)
```

guardian_sections	<i>Search Guardian Sections</i>
-------------------	---------------------------------

Description

guardian_sections lets you directly search The Guardian for metadata about sections - individual categories of content, such as world or US news.

Usage

```
guardian_sections(api_key, query, ...)
```

Arguments

api_key	A key to the Guardian API, which can be obtained here .
query	Your search query. This can contain operators (sausage AND mash) or phrases ("sausage & mash"); by default, searches work as an OR, looking for the presence of any one individual word in the query.
...	further arguments to pass to httr's GET.

See Also

[guardian_tags](#) for retrieving tags, another class of content metadata.

Examples

```
## Not run:
# Simple example
business_sections <- guardian_sections("test", "business")

## End(Not run)
```

guardian_tags	<i>Search Guardian Tags</i>
---------------	-----------------------------

Description

guardian_tags lets you directly search The Guardian for their tags - metadata used to classify content.

Usage

```
guardian_tags(api_key, query, section = NULL, reference = NULL,
  reference_type = NULL, page = NULL, page_size = 50, ...)
```

Arguments

api_key	A key to the Guardian API, which can be obtained here .
query	Your search query. This can contain operators (sausage AND mash) or phrases ("sausage & mash"); by default, searches work as an OR, looking for the presence of any one individual word in the query.
section	the section, or sections, of <i>The Guardian</i> that you want to limit the search to. Multiple sections may be concatenated together using boolean operators; see guardian_and and guardian_and .
reference	the references to limit the search to; only tags that include those references (and meet other conditions) will be returned. Also accepts boolean operators.
reference_type	the type of reference (such as isbn). Also accepts boolean operators.
page	a particular page of results to return. Useful when returning multiple sets of data with the same query; you can repeat the query, incrementing the value in page.

page_size	the maximum number of items to return; anywhere between 1 and 50. Set to 50 by default.
...	further arguments to pass to httr's GET.

See Also

[guardian_content](#).

Examples

```
## Not run:  
# Simple example  
results <- guardian_tags("test", "green")  
  
## End(Not run)
```

rdian

Modern API client for The Guardian

Description

This package provides a modern (httr/curl/jsonlite-based) API client for The Guardian (<https://guardian.co.uk>), allowing useRs to retrieve content and content metadata.

Index

guardian_and, [2](#), [3](#), [5](#)
guardian_content, [2](#), [6](#)
guardian_editions, [4](#)
guardian_operators (guardian_and), [2](#)
guardian_or, [3](#)
guardian_or (guardian_and), [2](#)
guardian_sections, [4](#), [4](#)
guardian_tags, [3](#), [5](#), [5](#)

rdian, [6](#)
rdian-package (rdian), [6](#)