

Package ‘rdoxygen’

July 23, 2025

Title Create Doxygen Documentation for Source Code

Version 1.0.0

Maintainer Clemens Schmid <clemens@nevrome.de>

Description Create doxygen documentation for source code in R packages.
Includes a RStudio Addin, that allows to trigger the doxygenize process.

Date 2017-05-23

Depends R (>= 3.3.3)

License GPL-2 | file LICENSE

Encoding UTF-8

LazyData true

URL <https://github.com/nevrome/rdoxygen>

BugReports <https://github.com/nevrome/rdoxygen/issues>

RoxygenNote 6.0.1

Imports devtools (>= 1.12.0)

Suggests testthat

SystemRequirements doxygen

NeedsCompilation yes

Author Clemens Schmid [cre, cph, aut]

Repository CRAN

Date/Publication 2017-05-25 21:39:04 UTC

Contents

check_for_doxygen	2
c_test	2
doxy	3
doxy_edit	3
doxy_init	4
replace_tag	5

Index	6
--------------	----------

check_for_doxygen	<i>check for doxygen</i>
-------------------	--------------------------

Description

helper function to check if doxygen is in the system path

Usage

```
check_for_doxygen()
```

Value

TRUE

c_test	<i>R frontend of the C function bar</i>
--------	---

Description

A mask function to test if the dummy C code in src/bar.c works.

Usage

```
c_test(x)
```

Arguments

x	a numeric vector
---	------------------

Details

$c_test(x) = x^2$.

Value

a numeric vector x^2

Examples

```
## Not run:
x <- rnorm(10)
c_test(x)

## End(Not run)
```

doxy	<i>Calls doxygen for an R package</i>
------	---------------------------------------

Description

Triggers doxygen documentation for the code in src/. Triggers also the setup (with doxy_init()) at the first run.

Usage

```
doxy(doxxygen = file.exists("src"), roxygen = FALSE,
     pathToDoxyfile = "../inst/doxygen/Doxyfile")
```

Arguments

doxxygen	A boolean: should doxygen be ran on documents in src/? Default: TRUE if a src folder exist and FALSE if not
roxygen	A boolean: should devtools::document() be ran after the creation of the doxygen documentation? Default: FALSE
pathToDoxyfile	A string with the relative path to the Doxyfile. Default: "../inst/doxygen/Doxyfile"

Value

NULL or the value returned by devtools::document()

Examples

```
## Not run:
doxy()

## End(Not run)
```

doxy_edit	<i>Edits an existing Doxyfile</i>
-----------	-----------------------------------

Description

Changes options in doxygen config files.

Usage

```
doxy_edit(pathToDoxyfile = "../inst/doxygen/Doxyfile", options = c())
```

Arguments

`pathToDoxyfile` A string with the relative path to the Doxyfile. Default: `"/inst/doxygen/Doxyfile"`

`options` A named vector with new settings. The names represent the tags. A list of options can be found here: <https://www.stack.nl/~dimitri/doxygen/manual/config.html>

Examples

```
## Not run:
doxy_init(options = c("EXTRACT_PRIVATE" = "YES"))

## End(Not run)
```

`doxy_init`*Prepares the R package structure for use with doxygen*

Description

Creates a configuration file in `inst/doxygen/` and sets a few options:

- `EXTRACT_ALL` = YES
- `INPUT` = `src/`
- `OUTPUT_DIRECTORY` = `inst/doxygen/`

Usage

```
doxy_init(rootFolder = ".")
```

Arguments

`rootFolder` A string with the path to the root directory of the R package. Default: `"."`

Examples

```
## Not run:
doxy_init()

## End(Not run)
```

replace_tag	<i>Updates and adds doxygen options in a line string vector</i>
-------------	---

Description

Scans the lines and changes the value for the named tag if one line has this tag, adds a line at the end if no line has this tag and returns a warning if several lines match the tag.

Usage

```
replace_tag(fileStrings, tag, newVal)
```

Arguments

fileStrings	A vector with each string containing a line of the file
tag	A string with the tag to be searched for
newVal	A string with the new value for the tag

Value

The vector of strings with the new value

Index

c_test, [2](#)
check_for_doxygen, [2](#)

doxy, [3](#)
doxy_edit, [3](#)
doxy_init, [4](#)

replace_tag, [5](#)