

Package ‘readmission’

July 23, 2025

Title Hospital Readmission Data for Patients with Diabetes

Version 0.1.0

Description Clinical care data from 130 U.S. hospitals in the years 1999-2008 adapted from the study Strack et al. (2014) <[doi:10.1155/2014/781670](https://doi.org/10.1155/2014/781670)>. Each row describes an ``encounter" with a patient with diabetes, including variables on demographics, medications, patient history, diagnostics, payment, and readmission.

License MIT + file LICENSE

Suggests knitr

Config/testthat/edition 3

Encoding UTF-8

RoxygenNote 7.2.3

Depends R (>= 2.10)

LazyData true

NeedsCompilation no

Author Simon Couch [aut, cre]

Maintainer Simon Couch <simonpatrickcouch@gmail.com>

Repository CRAN

Date/Publication 2023-12-07 16:20:05 UTC

Contents

readmission	2
Index	4

readmission

*Hospital Readmission Data for Patients with Diabetes***Description**

Clinical care data from 130 U.S. hospitals in years 1999-2008. Each row describes an "encounter" with a patient with diabetes, including variables on demographics, medications, patient history, diagnostics, payment, and readmission.

Usage

readmission

Format

A data frame with 71,515 rows and 12 columns:

readmitted Whether the patient was readmitted within the 30 days following discharge. A factor with levels "Yes" and "No".

race Reported race of the patient. Source data does not document data collection strategy. A factor with levels "African American", "Asian", "Caucasian", "Hispanic", "Other", and "Unknown".

sex Reported sex of the patient. Source data does not document data collection strategy. A factor with levels "Female" and "Male".

age Age range for the patient, binned in 10-year intervals. A factor with levels "[0-10)", "[10-20)", "[20-30)", "[30-40)", "[40-50)", "[50-60)", "[60-70)", "[70-80)", "[80-90)", and "[90-100)".

admission_source Whether the patient was referred from a physician, admitted via the ER, or arrived via some other source. A factor with levels "Emergency", "Other", and "Referral".

blood_glucose Results from an A1C test, estimating the patient's average blood sugar over the past 2-3 months. Higher estimated average blood glucose levels are linked to diabetes complications. A factor with levels "Normal", "High", and "Very High", and many missing values.

insurer The health insurance provider (or lack thereof, via "Self-Pay") for the patient. A factor with levels "Medicaid", "Medicare", "Private", and "Self-Pay", and many missing values.

duration Number of days in the hospital between admission and discharge.

n_previous_visits Number of emergency, inpatient, and outpatient visits in the year preceding the encounter.

n_diagnoses "Number of diagnoses entered to the system" during the encounter.

n_procedures "Number of procedures (other than lab tests) performed" during the encounter.

n_medications "Number of distinct generic names administered" during the encounter.

Source

Original source data from the following paper (CC BY 3.0):

Strack, B., DeShazo, J. P., Gennings, C., Olmo, J. L., Ventura, S., Cios, K. J., & Clore, J. N. 2014. Impact of HbA1c measurement on hospital readmission rates: analysis of 70,000 clinical database patient records. BioMed research international, 781670. doi:[10.1155/2014/781670](https://doi.org/10.1155/2014/781670).

Shared freely through the UCI Machine Learning Repository (CC BY 4.0):

Clore, J., Cios, K., DeShazo, J. P., and Strack, B. 2014. Diabetes 130-US hospitals for years 1999-2008. UCI Machine Learning Repository. doi:[10.24432/C5230J](https://doi.org/10.24432/C5230J).

Downloaded from resources shared by the Fairlearn team (MIT):

Weerts, H., Dudík M., Edgar, R., Jalali, A., Lutz, R., & Madaio, M. 2023. Fairlearn: Assessing and Improving Fairness of AI Systems. Journal of Machine Learning Research, 24(257):1-8.

Examples

```
str(readmission)
```

```
head(readmission)
```

Index

* **datasets**

readmission, [2](#)

readmission, [2](#)