

Package ‘readstata13’

July 23, 2025

Type Package

Title Import 'Stata' Data Files

Version 0.11.0

Description Function to read and write the 'Stata' file format.

URL <https://github.com/sjewo/readstata13>

BugReports <https://github.com/sjewo/readstata13/issues>

License GPL-2 | file LICENSE

Imports Rcpp (>= 0.11.5)

LinkingTo Rcpp

ByteCompile yes

Suggests testthat, knitr, rmarkdown, curl, png, expss, labelled

VignetteBuilder knitr

Encoding UTF-8

RoxygenNote 7.3.2

NeedsCompilation yes

Author Jan Marvin Garbuszus [aut],
Sebastian Jeworutzki [aut, cre] (ORCID:
<<https://orcid.org/0000-0002-2671-5253>>),
R Core Team [cph],
Magnus Thor Torfason [ctb],
Luke M. Olson [ctb],
Giovanni Righi [ctb],
Kevin Jin [ctb]

Maintainer Sebastian Jeworutzki <Sebastian.Jeworutzki@ruhr-uni-bochum.de>

Repository CRAN

Date/Publication 2025-04-25 11:20:02 UTC

Contents

as.caldays	2
get.frames	3
get.label	4
get.label.name	5
get.label.tables	5
get.lang	6
get.origin.codes	7
maxchar	8
read.dta13	8
read.dtas	11
readstata13	12
save.dta13	13
saveToExport	15
set.label	15
set.lang	16
stbcal	17
varlabel	18

Index	19
--------------	-----------

as.caldays	<i>Convert Stata business calendar dates in readable dates.</i>
------------	---

Description

Convert Stata business calendar dates in readable dates.

Usage

```
as.caldays(buisdays, cal, format = "%Y-%m-%d")
```

Arguments

buisdays	numeric Vector of business dates
cal	data.frame Conversion table for business calendar dates
format	character String with date format as in as.Date

Value

Returns a vector of readable dates.

Author(s)

Jan Marvin Garbuszus <jan.garbuszus@ruhr-uni-bochum.de>
Sebastian Jeworutzki <sebastian.jeworutzki@ruhr-uni-bochum.de>

Examples

```
# read business calendar and data
sp500 <- stbcal(system.file("extdata/sp500.stbcal", package="readstata13"))
dat <- read.dta13(system.file("extdata/statacar.dta", package="readstata13"))

# convert dates and check
dat$ldatescal2 <- as.caldays(dat$ldate, sp500)
all(dat$ldatescal2==dat$ldatescal)
```

get.frames

*List frames in Stata dta files***Description**

Stata 18 introduced framesets (file extension ‘.dtas’) that contain zipped ‘dta’ files. This helper functions imports those files and returns a list of data.frames.

Usage

```
get.frames(path)
```

Arguments

path path to .dtas file

Value

Returns a data.frame with frame names, internal filenames and dta file format version.

Examples

```
path <- system.file("extdata", "myproject2.dtas", package="readstata13")

# print all frames in myproject2.dtas
get.frames(path)
```

`get.label`*Get Stata Label Table for a Label Set*

Description

Retrieve the value labels for a specific Stata label set.

Usage

```
get.label(dat, label.name)
```

Arguments

<code>dat</code>	<i>data.frame</i> . Data.frame created by <code>read.dta13</code> .
<code>label.name</code>	<i>character</i> . Name of the Stata label set

Details

This function returns the table of factor levels which represent a Stata label set. The name of a label set for a variable can be obtained by [get.label.name](#).

Value

Returns a named vector of code numbers

Author(s)

Jan Marvin Garbuszus <jan.garbuszus@ruhr-uni-bochum.de>

Sebastian Jeworutzki <sebastian.jeworutzki@ruhr-uni-bochum.de>

Examples

```
dat <- read.dta13(system.file("extdata/statacar.dta", package="readstata13"))
labname <- get.label.name(dat,"type")
get.label(dat, labname)
```

get.label.name	<i>Get Names of Stata Label Set</i>
----------------	-------------------------------------

Description

Retrieves the Stata label set in the dataset for all or an vector of variable names.

Usage

```
get.label.name(dat, var.name = NULL, lang = NA)
```

Arguments

dat	<i>data.frame.</i> Data.frame created by <code>read.dta13</code> .
var.name	<i>character vector.</i> Variable names. If <code>NULL</code> , get names of all label sets.
lang	<i>character.</i> Label language. Default language defined by <code>get.lang</code> is used if <code>NA</code>

Details

Stata stores factor labels in variable independent labels sets. This function retrieves the name of the label set for a variable.

Value

Returns an named vector of variable labels

Author(s)

Jan Marvin Garbuszus <jan.garbuszus@ruhr-uni-bochum.de>
Sebastian Jeworutzki <sebastian.jeworutzki@ruhr-uni-bochum.de>

get.label.tables	<i>Get all Stata Label Sets for a Data.frame</i>
------------------	--

Description

Retrieve the value labels for all variables.

Usage

```
get.label.tables(dat)
```

Arguments

dat	<i>data.frame.</i> Data.frame created by <code>read.dta13</code> .
-----	--

Details

This function returns the factor levels which represent a Stata label set for all variables.

Value

Returns a named list of label tables

Author(s)

Jan Marvin Garbuszus <jan.garbuszus@ruhr-uni-bochum.de>

Sebastian Jeworutzki <sebastian.jeworutzki@ruhr-uni-bochum.de>

Examples

```
dat <- read.dta13(system.file("extdata/statacar.dta", package="readstata13"))
get.label.tables(dat)
```

get.lang

Show Default Label Language

Description

Displays informations about the defined label languages.

Usage

```
get.lang(dat, print = T)
```

Arguments

dat *data.frame*. Data.frame created by read.dta13.

print *logical*. If TRUE, print available languages and default language.

Details

Stata allows to define multiple label sets in different languages. This functions reports the available languages and the selected default language.

Value

Returns a list with two components:

languages: Vector of label languages used in the dataset

default: Name of the actual default label language, otherwise NA

Author(s)

Jan Marvin Garbuszus <jan.garbuszus@ruhr-uni-bochum.de>

Sebastian Jeworutzki <sebastian.jeworutzki@ruhr-uni-bochum.de>

get.origin.codes	<i>Get Origin Code Numbers for Factors</i>
------------------	--

Description

Recreates the code numbers of a factor as stored in the Stata dataset.

Usage

```
get.origin.codes(x, label.table)
```

Arguments

x	<i>factor</i> . Factor to obtain code for
label.table	<i>table</i> . Table with factor levels obtained by get.label .

Details

While converting numeric variables into factors, the original code numbers are lost. This function reconstructs the codes from the attribute `label.table`.

Value

Returns an integer with original codes

Author(s)

Jan Marvin Garbuszus <jan.garbuszus@ruhr-uni-bochum.de>

Sebastian Jeworutzki <sebastian.jeworutzki@ruhr-uni-bochum.de>

Examples

```
dat <- read.dta13(system.file("extdata/statacar.dta", package="readstata13"))
labname <- get.label.name(dat,"type")
labtab <- get.label(dat, labname)

# comparsion
get.origin.codes(dat$type, labtab)
as.integer(dat$type)
```

maxchar

Check max char length of data.frame vectors

Description

Stata requires us to provide the maximum size of a character vector as every row is stored in a bit region of this size.

Usage

```
maxchar(x)
```

Arguments

x vector of data frame

Details

Ex: If the max chars size is four, _ is no character in this vector: 1. row: four 3. row: one_ 4. row:

If a character vector contains only missings or is empty, we will assign it a value of one, since Stata otherwise cannot handle what we write.

read.dta13

Read Stata Binary Files

Description

read.dta13 reads a Stata dta-file and imports the data into a data.frame.

Usage

```
read.dta13(
  file,
  convert.factors = TRUE,
  generate.factors = FALSE,
  encoding = "UTF-8",
  fromEncoding = NULL,
  convert.underscore = FALSE,
  missing.type = FALSE,
  convert.dates = TRUE,
  replace.str1 = TRUE,
  add.rownames = FALSE,
  nonint.factors = FALSE,
  select.rows = NULL,
```

```

    select.cols = NULL,
    strlexport = FALSE,
    strlpath = ".",
    tz = "GMT"
)

```

Arguments

<code>file</code>	<i>character</i> . Path to the dta file you want to import.
<code>convert.factors</code>	<i>logical</i> . If TRUE, factors from Stata value labels are created.
<code>generate.factors</code>	<i>logical</i> . If TRUE and <code>convert.factors</code> is TRUE, missing factor labels are created from integers. If duplicated labels are found, unique labels will be generated according the following scheme: "label_(integer code)".
<code>encoding</code>	<i>character</i> . Strings can be converted from Windows-1252 or UTF-8 to system encoding. Options are "latin1" or "UTF-8" to specify target encoding explicitly. Since Stata 14 files are UTF-8 encoded and may contain strings which can't be displayed in the current locale. Set <code>encoding=NULL</code> to stop reencoding.
<code>fromEncoding</code>	<i>character</i> . We expect strings to be encoded as "CP1252" for Stata Versions 13 and older. For dta files saved with Stata 14 or newer "UTF-8" is used. In some situation the used encoding can differ for Stata 14 files and must be manually set.
<code>convert.underscore</code>	<i>logical</i> . If TRUE, "_" in variable names will be changed to ".".
<code>missing.type</code>	<i>logical</i> . Stata knows 27 different missing types: ., .a, .b, ..., .z. If TRUE, attribute missing will be created.
<code>convert.dates</code>	<i>logical</i> . If TRUE, Stata dates are converted.
<code>replace.strl</code>	<i>logical</i> . If TRUE, replace the reference to a strL string in the data.frame with the actual value. The strl attribute will be removed from the data.frame (see details).
<code>add.rownames</code>	<i>logical</i> . If TRUE, the first column will be used as rownames. Variable will be dropped afterwards.
<code>nonint.factors</code>	<i>logical</i> . If TRUE, factors labels will be assigned to variables of type float and double.
<code>select.rows</code>	<i>integer</i> . Vector of one or two numbers. If single value rows from 1:val are selected. If two values of a range are selected the rows in range will be selected.
<code>select.cols</code>	<i>character</i> . or <i>numeric</i> . Vector of variables to select. Either variable names or position.
<code>strlexport</code>	<i>logical</i> . Should strl content be exported as binary files?
<code>strlpath</code>	<i>character</i> . Path for strl export.
<code>tz</code>	<i>character</i> . time zone specification to be used for POSIXct values. "" is the current time zone, and "GMT" is UTC (Universal Time, Coordinated).

Details

If the filename is a url, the file will be downloaded as a temporary file and read afterwards.

Stata files are encoded in ansinew. Depending on your system's default encoding certain characters may appear wrong. Using a correct encoding may fix these.

Variable names stored in the dta-file will be used in the resulting data.frame. Stata types char, byte, and int will become integer; float and double will become numerics. R only knows a single missing type, while Stata knows 27, so all Stata missings will become NA in R. If you need to keep track of Stata's original missing types, you may use `missing.type=TRUE`.

Stata dates are converted to R's Date class the same way foreign handles dates.

Stata 13 introduced a new character type called strL. strLs are able to store strings up to 2 billion characters. While R is able to store strings of this size in a character vector, the printed representation of such vectors looks rather cluttered, so it's possible to save only a reference in the data.frame with option `replace.strl=FALSE`.

In R, you may use rownames to store characters (see for instance `data(swiss)`). In Stata, this is not possible and rownames have to be stored as a variable. If you want to use rownames, set `add.rownames` to TRUE. Then the first variable of the dta-file will hold the rownames of the resulting data.frame.

Reading dta-files of older and newer versions than 13 was introduced with version 0.8.

Stata 18 introduced alias variables and frame files. Alias variables are currently ignored when reading the file and a warning is printed. Stata frame files (file extension '.dtas') contain zipped 'dta' files which can be imported with [read.dtas](#).

Value

The function returns a data.frame with attributes. The attributes include

datalabel: Dataset label

time.stamp: Timestamp of file creation

formats: Stata display formats. May be used with [sprintf](#)

types: Stata data type (see Stata Corp 2014)

val.labels: For each variable the name of the associated value labels in "label"

var.labels: Variable labels

version: dta file format version

label.table: List of value labels.

strl: Character vector with long strings for the new strl string variable type. The name of every element is the identifier.

expansion.fields: list providing variable name, characteristic name and the contents of Stata characteristic field.

missing: List of numeric vectors with Stata missing type for each variable.

byteorder: Byteorder of the dta-file. LSF or MSF.

orig.dim: Dimension recorded inside the dta-file.

Note

read.dta13 uses GPL 2 licensed code by Thomas Lumley and R-core members from `foreign::read.dta()`.

Author(s)

Jan Marvin Garbuszus <jan.garbuszus@ruhr-uni-bochum.de>

Sebastian Jeworutzki <sebastian.jeworutzki@ruhr-uni-bochum.de>

References

Stata Corp (2014): Description of .dta file format <https://www.stata.com/help.cgi?dta>

See Also

[read.dta](#) in package `foreign` and `memisc` for dta files from Stata versions < 13 and `read_dta` in package `haven` for Stata version >= 13.

Examples

```
## Not run:
library(readstata13)
r13 <- read.dta13("https://www.stata-press.com/data/r13/auto.dta")

## End(Not run)
```

read.dtas

Read frames from Stata dtas files

Description

Stata 18 introduced framesets (file extension ‘.dtas’) that contain zipped ‘dta’ files. This helper functions imports those files and returns a list of `data.frames`.

Usage

```
read.dtas(path, select.frames = NULL, read.dta13.options = NULL)
```

Arguments

`path` path to .dtas file

`select.frames` character vector

`read.dta13.options`

list of parameters used in [read.dta13](#). The list must have the following structure: `list(framename = list(param = value))`

Value

Returns a named list of `data.frames`.

Examples

```
path <- system.file("extdata", "myproject2.dtas", package="readstata13")

# read all frames in myproject2.dtas
read.dtas(path)

# read selected frames
read.dtas(path, select.frames = c("persons", "counties"))

# read only frame counties
read.dtas(path, select.frames = c("counties"))

# read frames with different arguments
read.dtas(path,
  read.dta13.options = list(counties = list(select.cols = "median_income"),
    persons = list(select.cols = "income")))
```

readstata13

Import Stata Data Files

Description

Function to read the Stata file format into a data.frame.

Note

If you catch a bug, please do not sue us, we do not have any money.

Author(s)

Marvin Garbuszus <jan.garbuszus@ruhr-uni-bochum.de>

Sebastian Jeworutzki <sebastian.jeworutzki@ruhr-uni-bochum.de>

See Also

[read.dta](#) and [memisc](#) for dta files from Stata Versions < 13

save.dta13

*Write Stata Binary Files***Description**

save.dta13 writes a Stata dta-file byte-wise and saves the data into a dta-file.

Usage

```
save.dta13(
  data,
  file,
  data.label = NULL,
  time.stamp = TRUE,
  convert.factors = TRUE,
  convert.dates = TRUE,
  tz = "GMT",
  add.rownames = FALSE,
  compress = FALSE,
  version = 117,
  convert.underscore = FALSE
)
```

Arguments

data	<i>data.frame</i> . A data.frame Object.
file	<i>character</i> . Path to the dta file you want to export.
data.label	<i>character</i> . Name of the dta-file.
time.stamp	<i>logical</i> . If TRUE, add a time.stamp to the dta-file.
convert.factors	<i>logical</i> . If TRUE, factors will be converted to Stata variables with labels. Stata expects strings to be encoded as Windows-1252, so all levels will be recoded. Character which can not be mapped in Windows-1252 will be saved as hexcode.
convert.dates	<i>logical</i> . If TRUE, dates will be converted to Stata date time format. Code from <code>foreign::write.dta</code>
tz	<i>character</i> . time zone specification to be used for POSIXct values and dates (if <code>convert.dates</code> is TRUE). "" is the current time zone, and "GMT" is UTC (Universal Time, Coordinated).
add.rownames	<i>logical</i> . If TRUE, a new variable rownames will be added to the dta-file.
compress	<i>logical</i> . If TRUE, the resulting dta-file will use all of Stata's numeric-vartypes.
version	<i>numeric</i> . Stata format for the resulting dta-file either Stata version number (6 - 16) or the internal Stata dta-format (e.g. 117 for Stata 13). Support for large datasets: Use <code>version="15mp"</code> to save the dataset in the new Stata 15/16 MP file format. This feature is not thoroughly tested yet.

`convert.underscore`

logical. If TRUE, all non numerics or non alphabet characters will be converted to underscores.

Value

The function writes a dta-file to disk. The following features of the dta file format are supported:

datalabel: Dataset label

time.stamp: Timestamp of file creation

formats: Stata display formats. May be used with `sprintf`

type: Stata data type (see Stata Corp 2014)

var.labels: Variable labels

version: dta file format version

strl: List of character vectors for the new strL string variable type. The first element is the identifier and the second element the string.

Author(s)

Jan Marvin Garbuszus <jan.garbuszus@ruhr-uni-bochum.de>

Sebastian Jeworutzki <sebastian.jeworutzki@ruhr-uni-bochum.de>

References

Stata Corp (2014): Description of .dta file format <https://www.stata.com/help.cgi?dta>

See Also

`read.dta` in package `foreign` and `memisc` for dta files from Stata versions < 13 and `read_dta` in package `haven` for Stata version >= 13.

Examples

```
## Not run:
library(readstata13)
save.dta13(cars, file="cars.dta")

## End(Not run)
```

saveToExport	<i>Check if numeric vector can be expressed as integer vector</i>
--------------	---

Description

Compression can reduce numeric vectors as integers if the vector does only contain integer type data.

Usage

```
saveToExport(x)
```

Arguments

x	vector of data frame
---	----------------------

set.label	<i>Assign Stata Labels to a Variable</i>
-----------	--

Description

Assign value labels from a Stata label set to a variable. If duplicated labels are found, unique labels will be generated according the following scheme: "label_(integer code)". Levels without labels will become <NA>.

Usage

```
set.label(dat, var.name, lang = NA)
```

Arguments

dat	<i>data.frame</i> . Data.frame created by read.dta13.
var.name	<i>character</i> : Name of the variable in the data.frame
lang	<i>character</i> : Label language. Default language defined by get.lang is used if NA

Value

Returns a labeled factor

Examples

```

dat <- read.dta13(system.file("extdata/statacar.dta", package="readstata13"),
                  convert.factors=FALSE)

# compare vectors
set.label(dat, "type")
dat$type

# German label
set.label(dat, "type", "de")

```

set.lang

*Assign Stata Language Labels***Description**

Changes default label language for a dataset. Variables with generated labels (option generate.labels=TRUE) are kept unchanged.

Usage

```
set.lang(dat, lang = NA, generate.factors = FALSE)
```

Arguments

dat	<i>data.frame</i> . Data.frame created by read.dta13.
lang	<i>character</i> . Label language. Default language defined by get.lang is used if NA
generate.factors	<i>logical</i> . If TRUE, missing factor levels are generated.

Value

Returns a data.frame with value labels in language "lang".

Author(s)

Jan Marvin Garbuszus <jan.garbuszus@ruhr-uni-bochum.de>

Sebastian Jeworutzki <sebastian.jeworutzki@ruhr-uni-bochum.de>

Examples

```

dat <- read.dta13(system.file("extdata/statacar.dta", package="readstata13"))
get.lang(dat)
varlabel(dat)

# set German label
datDE <- set.lang(dat, "de")
get.lang(datDE)
varlabel(datDE)

```

stbcal*Parse Stata business calendar files*

Description

Create conversion table for business calendar dates.

Usage

```
stbcal(stbcalfile)
```

Arguments

`stbcalfile` *stbcal-file* Stata business calendar file created by Stata.

Details

Stata 12 introduced business calendar format. Business dates are integer numbers in a certain range of days, weeks, months or years. In this range some days are omitted (e.g. weekends or holidays). If a business calendar was created, a stbcal file matching this calendar was created. This file is required to read the business calendar. This parser reads the stbcal- file and returns a data.frame with dates matching business calendar dates.

A dta-file containing Stata business dates imported with `read.stata13()` shows in formats which stdcal file is required (e.g. " sp500.stbcal").

Stata allows adding a short description called purpose. This is added as an attribute of the resulting data.frame.

Value

Returns a data.frame with two cols:

range: The date matching the businessdate. Date format.

buisdays: The Stata business calendar day. Integer format.

Author(s)

Jan Marvin Garbuszus <jan.garbuszus@ruhr-uni-bochum.de>

Sebastian Jeworutzki <sebastian.jeworutzki@ruhr-uni-bochum.de>

Examples

```
sp500 <- stbcal(system.file("extdata/sp500.stbcal", package="readstata13"))
```

varlabel	<i>Get and assign Stata Variable Labels</i>
----------	---

Description

Retrieve or set variable labels for a dataset.

Usage

```
varlabel(dat, var.name = NULL, lang = NA)
```

```
varlabel(dat) <- value
```

Arguments

<code>dat</code>	<i>data.frame</i> . Data.frame created by <code>read.dta13</code> .
<code>var.name</code>	<i>character vector</i> . Variable names. If <code>NULL</code> , get label for all variables.
<code>lang</code>	<i>character</i> . Label language. Default language defined by <code>get.lang</code> is used if <code>NA</code>
<code>value</code>	<i>character vector</i> . Character vector of size <code>ncol(data)</code> with variable names.

Value

Returns an named vector of variable labels

Author(s)

Jan Marvin Garbuszus <jan.garbuszus@ruhr-uni-bochum.de>

Sebastian Jeworutzki <sebastian.jeworutzki@ruhr-uni-bochum.de>

Examples

```
dat <- read.dta13(system.file("extdata/statacar.dta", package="readstata13"),
  convert.factors=FALSE)

# display variable labels
varlabel(dat)

# display german variable labels
varlabel(dat, lang="de")

# display german variable label for brand
varlabel(dat, var.name = "brand", lang="de")

# define new variable labels
varlabel(dat) <- letters[1:ncol(dat)]

# display new variable labels
varlabel(dat)
```

Index

'varlabel<-' (varlabel), [18](#)

as.caldays, [2](#)

as.Date, [2](#)

get.frames, [3](#)

get.label, [4](#), [7](#)

get.label.name, [4](#), [5](#)

get.label.tables, [5](#)

get.lang, [5](#), [6](#), [15](#), [16](#), [18](#)

get.origin.codes, [7](#)

maxchar, [8](#)

read.dta, [11](#), [12](#), [14](#)

read.dta13, [8](#), [11](#)

read.dtas, [10](#), [11](#)

readstata13, [12](#)

readstata13-package (readstata13), [12](#)

save.dta13, [13](#)

saveToExport, [15](#)

set.label, [15](#)

set.lang, [16](#)

sprintf, [10](#), [14](#)

stbcal, [17](#)

varlabel, [18](#)

varlabel<- (varlabel), [18](#)