

Package ‘recogito’

July 23, 2025

Title Interactive Annotation of Text and Images

Version 0.2.1

Description Annotate text with entities and the relations between them. Annotate areas of interest in images with your labels.
Providing 'htmlwidgets' bindings to the 'recogito' <<https://github.com/recogito/recogito-js>> and 'annotorious' <<https://github.com/recogito/annotorious>> libraries.

License BSD_3_clause + file LICENSE

Encoding UTF-8

URL <https://github.com/DIGI-VUB/recogito>

RoxygenNote 7.1.2

Depends R (>= 2.10)

Suggests shiny, magick, opencv, sf

Imports utils, htmlwidgets, htmltools, jsonlite

NeedsCompilation no

Author Jan Wijffels [aut, cre, cph],
Vrije Universiteit Brussel - DIGI: Brussels Platform for Digital
Humanities [cph],
Pelagios Network [cph] (code in inst/htmlwidgets/lib),
CodePlex Foundation [cph] (code in
inst/htmlwidgets/lib/openseadragon-2.4.2),
OpenSeadragon contributors [cph] (code in
inst/htmlwidgets/lib/openseadragon-2.4.2)

Maintainer Jan Wijffels <jwi.jffels@bnosac.be>

Repository CRAN

Date/Publication 2022-08-17 10:50:05 UTC

Contents

annotorious	2
annotorious-shiny	3
ocv_crop_annotorious	5

ocv_read_annotorious	6
openseadragon_areas	7
read_annotorious	8
read_recogito	10
recogito	11
recogito-shiny	12
Index	15

annotorious	<i>Annotate images with areas of interest</i>
-------------	---

Description

Functionality to label areas in images

Usage

```
annotorious(  
  inputId = "annotations",  
  src,  
  tags = c(),  
  type = c("annotorious", "openseadragon", "openseadragon-notoolbar"),  
  quickselector = TRUE,  
  width = NULL,  
  height = NULL,  
  elementId = NULL,  
  dependencies = NULL  
)
```

Arguments

inputId	character string with the name to use where annotations will be put into
src	character string with the image/url to annotate
tags	character vector of possible labels you want to use
type	either 'annotorious', 'openseadragon', 'openseadragon-notoolbar' in order to allow zooming with openseadragon or not, with or without a toolbar
quickselector	logical indicating if for type 'openseadragon' the possible tags should be shows as quick buttons to click. Defaults to TRUE.
width	passed on to createWidget
height	passed on to createWidget
elementId	passed on to createWidget
dependencies	passed on to createWidget

Value

An object of class htmlwidget as returned by [createWidget](#)

See Also[annotorious-shiny](#)

annotorious-shiny	<i>Shiny bindings for annotorious</i>
-------------------	---------------------------------------

Description

Output and render functions for using annotorious within Shiny applications.

Usage

```
annotoriousOutput(outputId, width = "100%", height = "400px")  
  
renderAnnotorious(expr, env = parent.frame(), quoted = FALSE)  
  
openseadragonOutput(outputId, width = "100%", height = "400px")  
  
renderOpenSeaDragon(expr, env = parent.frame(), quoted = FALSE)  
  
openseadragonOutputNoToolbar(outputId, width = "100%", height = "400px")  
  
renderOpenSeaDragonNoToolbar(expr, env = parent.frame(), quoted = FALSE)
```

Arguments

outputId	output variable to read from
width, height	Must be a valid CSS unit (like '100%', '400px', 'auto') or a number, which will be coerced to a string and have 'px' appended.
expr	An expression that generates a annotorious
env	The environment in which to evaluate expr.
quoted	Is expr a quoted expression (with quote())? This is useful if you want to save an expression in a variable.

Value

An output element for use in a Shiny user interface.
Consisting of a toggle button to switch between rectangle / polygon mode and the html-widget (id: outputId) which contains an image (id: outputId-img)

Examples

```

if(interactive() && require(shiny)){
##
## Annotorious using OpenSeaDragon, allowing to zoom in,
## to select an area, press shift and next select the area
##
library(shiny)
library(recogito)
urls <- paste("https://upload.wikimedia.org/",
              c("wikipedia/commons/a/a0/Pamphlet_dutch_tulipomania_1637.jpg",
                "wikipedia/commons/6/64/Cat_and_dog_standoff_%283926784260%29.jpg"),
              sep = "")
ui <- fluidPage(actionButton(inputId = "ui_switch", label = "Sample image"),
               openseadragonOutput(outputId = "anno"),
               tags$h3("Results"),
               verbatimTextOutput(outputId = "annotation_result"))
server <- function(input, output) {
  current_image <- reactive({
    input$ui_switch
    list(url = sample(urls, size = 1))
  })
  output$anno <- renderOpenSeaDragon({
    info <- current_image()
    annotorious("annotations", tags = c("IMAGE", "TEXT"), src = info$url, type = "openseadragon")
  })
  output$annotation_result <- renderPrint({
    read_annotorious(input$annotations)
  })
}
shinyApp(ui, server)

##
## Annotorious using OpenSeaDragon, allowing to zoom in, no selection possibilities
## showing how to load a local image
##
library(shiny)
library(recogito)
url <- system.file(package = "recogito", "examples", "Pamphlet_dutch_tulipomania_1637.jpg")
addResourcePath(prefix = "img", directoryPath = dirname(url))
ui <- fluidPage(openseadragonOutputNoToolbar(outputId = "anno", width = "100%", height = "250px"))
server <- function(input, output) {
  output$anno <- renderOpenSeaDragonNoToolbar({
    annotorious("annotations", src = sprintf("img/%s", basename(url)),
               type = "openseadragon-notoolbar")
  })
}
shinyApp(ui, server)

##
## Annotorious without openseadragon
##
library(shiny)

```

```

library(recogito)
url <- paste("https://upload.wikimedia.org/",
            "wikipedia/commons/a/a0/Pamphlet_dutch_tulipomania_1637.jpg",
            sep = "")

ui <- fluidPage(annotoriousOutput(outputId = "anno", height = "600px"),
               tags$h3("Results"),
               verbatimTextOutput(outputId = "annotation_result"))
server <- function(input, output) {
  output$anno <- renderAnnotorious({
    annotorious("annotations", tags = c("IMAGE", "TEXT"), src = url, type = "annotorious")
  })
  output$annotation_result <- renderPrint({
    read_annotorious(input$annotations)
  })
}
shinyApp(ui, server)

##
## Annotorious, without openseadragon changing the url
##
library(shiny)
library(recogito)
urls <- paste("https://upload.wikimedia.org/",
              c("wikipedia/commons/a/a0/Pamphlet_dutch_tulipomania_1637.jpg",
                "wikipedia/commons/6/64/Cat_and_dog_standoff_%283926784260%29.jpg"),
              sep = "")

ui <- fluidPage(actionButton(inputId = "ui_switch", label = "Sample image"),
               annotoriousOutput(outputId = "anno", height = "600px"),
               tags$h3("Results"),
               verbatimTextOutput(outputId = "annotation_result"))
server <- function(input, output) {
  current_image <- reactive({
    input$ui_switch
    list(url = sample(urls, size = 1))
  })
  output$anno <- renderAnnotorious({
    info <- current_image()
    annotorious("annotations", tags = c("IMAGE", "TEXT"), src = info$url, type = "annotorious")
  })
  output$annotation_result <- renderPrint({
    read_annotorious(input$annotations)
  })
}
shinyApp(ui, server)

}

```

Description

Crop annotations to a bounding box

Usage

```
ocv_crop_annotorious(data, bbox)
```

Arguments

data	an object as returned by read_annotorious
bbox	a vector with elements x, y, xmax, ymax

Value

data where column polygon and the rectangle information in x, y, width, height is limited to the provided bounding box

Examples

```
library(opencv)
data(openseadragon_areas)

url <- attr(openseadragon_areas, "src")
img <- ocv_read(url)
bbox <- ocv_info(img)
bbox <- c(xmin = 0, ymin = 0, xmax = bbox$width - 1, ymax = bbox$height - 1)
x <- ocv_crop_annotorious(data = openseadragon_areas)
x <- ocv_crop_annotorious(data = openseadragon_areas, bbox = bbox)

img
area <- x[2, ]
ocv_polygon(img, pts = area$polygon[[1]], crop = TRUE)
area <- x[1, ]
ocv_rectangle(img, x = area$x, y = area$y, width = area$width, height = area$height)
area <- x[3, ]
ocv_rectangle(img, x = area$x, y = area$y, width = area$width, height = area$height)
```

ocv_read_annotorious *Extract the areas of interests of an image*

Description

Extract the areas of interests of an image

Usage

```
ocv_read_annotorious(data, image)
```

Arguments

data	an object as returned by read_annotorious
image	an ocv image object

Value

a list of ocv images with the extracted areas of interest

Examples

```
library(opencv)
library(magick)
data(openseadragon_areas)

url <- attr(openseadragon_areas, "src")
img <- ocv_read(url)

areas <- ocv_read_annotorious(data = openseadragon_areas, image = img)
areas[[1]]
areas[[2]]
img <- lapply(areas, FUN = function(x) image_read(ocv_bitmap(x)))
img <- do.call(c, img)
img <- image_append(img, stack = FALSE)
image_resize(img, "x200")
```

openseadragon_areas	<i>A dataset of annotations using openseadragon</i>
---------------------	---

Description

A dataset of annotations using openseadragon

Examples

```
data(openseadragon_areas)
openseadragon_areas
attr(openseadragon_areas, "src")
```

read_annotorious	<i>Parse annotorious annotations</i>
------------------	--------------------------------------

Description

Parse annotorious annotations

Usage

```
read_annotorious(x, src = character())
```

Arguments

x	a character string with json as returned by the htmlwidget
src	a character string with the image src which was used in x

Value

a data.frame with annotations with columns: id, type, label, comment, x, y, width, height, polygon and an attribute src with the provided src

Examples

```
url <- paste("https://upload.wikimedia.org/",
            "wikipedia/commons/a/a0/Pamphlet_dutch_tulipomania_1637.jpg",
            sep = "")
url <- system.file(package = "recogito", "examples", "Pamphlet_dutch_tulipomania_1637.jpg")
x <- '[
{
  "type": "Annotation",
  "body": [{"type": "TextualBody", "value": "IMAGE", "purpose": "tagging"}],
  "target": {"selector": {
    "type": "FragmentSelector",
    "conformsTo": "http://www.w3.org/TR/media-frags/",
    "value": "xywh=pixel:41,249.5234375,371,245"}},
  "@context": "http://www.w3.org/ns/anno.jsonld",
  "id": "#58f0096c-4675-4ea8-9f38-bffce0887ab8"
},
{
  "type": "Annotation",
  "body": [{"type": "TextualBody", "value": "TEXT", "purpose": "tagging"}],
  "target": {"selector": {
    "type": "FragmentSelector",
    "conformsTo": "http://www.w3.org/TR/media-frags/",
    "value": "xywh=pixel:46,5.523437976837158,371,239.99999952316284"}},
  "@context": "http://www.w3.org/ns/anno.jsonld",
  "id": "#50035dda-c62b-4f30-bf95-1879d60288a5"}]'
anno <- read_annotorious(x, src = url)
anno
```

```

library(magick)
img <- image_read(url)
area <- head(anno, n = 1)
image_crop(img, geometry_area(x = area$x, y = area$y,
                             width = area$width, height = area$height))
area <- subset(anno, type == "RECTANGLE")
allrectangles <- Map(
  x      = area$x,
  y      = area$y,
  width  = area$width,
  height = area$height,
  f = function(x, y, width, height){
    image_crop(img, geometry_area(x = x, y = y, width = width, height = height))
  })
allrectangles <- do.call(c, allrectangles)
allrectangles

x <- '[
{
  "type": "Annotation",
  "body": [{"type": "TextualBody", "value": "IMAGE", "purpose": "tagging"}],
  "target": {"selector": {
    "type": "FragmentSelector",
    "conformsTo": "http://www.w3.org/TR/media-frags/",
    "value": "xywh=pixel:43,244.5234375,362,252"
  }},
  "@context": "http://www.w3.org/ns/anno.jsonld",
  "id": "#4eaa8788-0c7e-42d2-b004-4d66b57018a1"}
]
{
  "type": "Annotation",
  "body": [{"type": "TextualBody", "value": "TEXT", "purpose": "tagging"}],
  "target": {"selector": {
    "type": "SvgSelector",
    "value": "<svg>
<polygon points=\\\\"75,4 75,58 32,95 32,194 410,195 391,70 373,63 368,3 222,1.5\\\\">
</polygon></svg>"}}
  "@context": "http://www.w3.org/ns/anno.jsonld",
  "id": "#8bf0a557-c847-4a07-91bc-68a98c499615"}]'
x <- gsub(x, pattern = "\\n", replacement = "")
anno <- read_annotorious(x, src = url)
anno
anno$polygon

library(opencv)
img <- ocv_read(url)
area <- subset(anno, type == "POLYGON")
ocv_polygon(img, pts = area$polygon[[1]])

```

read_recogito

Parse recogito annotations

Description

Parse recogito annotations

Usage

```
read_recogito(x, text = character())
```

Arguments

x	a character string with json as returned by the htmlwidget
text	a character string with the text which was used in x

Value

a data.frame with annotations with columns: id, type, label, chunk_text, chunk_start, chunk_end, relation_from, relation_to, chunk_comment and an attribute text with the provided text

Examples

```
x <- '[
{
  "type": "Annotation",
  "body": [
    { "type": "TextualBody", "value": "sdfsd", "purpose": "commenting" },
    { "type": "TextualBody", "value": "Person", "purpose": "tagging" } ],
  "target": { "selector": [
    { "type": "TextQuoteSelector", "exact": "ngenious hero" },
    { "type": "TextPositionSelector", "start": 42, "end": 55 } ] },
  "@context": "http://www.w3.org/ns/anno.jsonld",
  "id": "#a4ea53d4-69f3-4392-a3dd-cbb7e9ad50cb"
},
{
  "type": "Annotation",
  "body": [ { "type": "TextualBody", "value": "Person", "purpose": "tagging" },
    { "type": "TextualBody", "value": "Location", "purpose": "tagging" } ],
  "target": { "selector": [ { "type": "TextQuoteSelector", "exact": "far and" },
    { "type": "TextPositionSelector", "start": 70, "end": 77 } ] },
  "@context": "http://www.w3.org/ns/anno.jsonld",
  "id": "#d7050196-2537-42bf-9d1b-a3f9e4c9fbc6"
}
]'
read_recogito(x)
```

`recogito`*Annotate text with tags and relations*

Description

Functionality to tag text with entities and relations between these

Usage

```
recogito(  
  inputId = "annotations",  
  text,  
  type = c("relations", "tags"),  
  tags = c("Location", "Person", "Place", "Other"),  
  mode = c("html", "pre"),  
  annotations = "{}",  
  width = NULL,  
  height = NULL,  
  elementId = NULL,  
  dependencies = NULL  
)
```

Arguments

<code>inputId</code>	character string with the name to use where annotations will be put into
<code>text</code>	character string with the text to annotate
<code>type</code>	either 'relations' or 'tags' in order to label relations between tags or only plain tags
<code>tags</code>	character vector of possible tags
<code>mode</code>	either 'html' or 'pre'
<code>annotations</code>	character string with a predefined set of annotations
<code>width</code>	passed on to <code>createWidget</code>
<code>height</code>	passed on to <code>createWidget</code>
<code>elementId</code>	passed on to <code>createWidget</code>
<code>dependencies</code>	passed on to <code>createWidget</code>

Value

An object of class `htmlwidget` as returned by `createWidget`

See Also

[recogito-shiny](#)

Examples

```

txt <- "Josh went to the bakery in Brussels.\nWhat an adventure!"
x  <- recogito(inputId = "annotations", txt)
x
x  <- recogito(inputId = "annotations", txt, type = "tags",
               tags = c("LOCATION", "TIME", "PERSON"))
x
txt <- "Lorem ipsum dolor sit amet consectetur adipiscing elit Quisque tellus urna
      placerat in tortor ac imperdiet sollicitudin mi Integer vel dolor mollis feugiat
      sem eu porttitor elit Sed aliquam urna sed placerat euismod In risus sem ornare
      nec malesuada eu ornare quis dui Nunc finibus fermentum sollicitudin Fusce vel
      imperdiet mi ac faucibus leo Cras massa massa ultricies et justo vitae molestie
      auctor turpis Vestibulum euismod porta risus euismod dapibus Nullam facilisis
      ipsum sed est tempor et aliquam sapien auctor Aliquam velit ligula convallis a
      dui id varius bibendum quam Cras malesuada nec justo sed
      aliquet Fusce urna magna malesuada"
x  <- recogito(inputId = "annotations", txt)
x
x  <- recogito(inputId = "annotations", txt, type = "tags",
               tags = c("LOCATION", "TIME", "PERSON", "OTHER"))
x

##
## Color the tags by specifying CSS - they should have .tag-{TAGLABEL}
##
library(htmltools)
cat(readLines(system.file(package = "recogito", "examples", "example.css")), sep = "\n")
tagsetcss <- htmlDependency(name = "mytagset", version = "1.0",
                           src = system.file(package = "recogito", "examples"),
                           stylesheet = "example.css")
x  <- recogito(inputId = "annotations", txt,
               tags = c("LOCATION", "TIME", "PERSON", "OTHER"),
               dependencies = tagsetcss)
x

```

recogito-shiny

Shiny bindings for recogito

Description

Output and render functions for using recogito within Shiny applications and interactive Rmd documents.

Usage

```
recogitoOutput(outputId, width = "100%", height = "400px")
```

```
renderRecogito(expr, env = parent.frame(), quoted = FALSE)
```

```
recogitotagonlyOutput(outputId, width = "100%", height = "400px")

renderRecogitotagonly(expr, env = parent.frame(), quoted = FALSE)
```

Arguments

outputId	output variable to read from
width, height	Must be a valid CSS unit (like '100%', '400px', 'auto') or a number, which will be coerced to a string and have 'px' appended.
expr	An expression that generates a recogito
env	The environment in which to evaluate expr.
quoted	Is expr a quoted expression (with quote())? This is useful if you want to save an expression in a variable.

Value

An output element for use in a Shiny user interface.
 Consisting of a div of class plaintext which contains an optional toggle button to switch between annotation / relation mode (id: outputId-toggle) and the html-widget (id: outputId)

Examples

```
if(interactive() && require(shiny)){

##
## Tagging only, no relations
##
library(shiny)
library(recogito)
txt <- "Josh went to the bakery in Brussels.\nWhat an adventure!"
ui <- fluidPage(tags$h3("Provide some text to annotate"),
  textAreaInput(inputId = "ui_text", label = "Provide some text", value = txt),
  tags$h3("Annotation area"),
  recogitotagonlyOutput(outputId = "annotation_text"),
  tags$hr(),
  tags$h3("Results"),
  verbatimTextOutput(outputId = "annotation_result"))
server <- function(input, output) {
  output$annotation_text <- renderRecogitotagonly({
    recogito("annotations", text = input$ui_text, tags = c("LOCATION", "TIME", "PERSON"))
  })
  output$annotation_result <- renderPrint({
    read_recogito(input$annotations)
  })
}
shinyApp(ui, server)

##
## Tagging and relations
##
```

```

library(shiny)
library(recogito)
txt <- "Josh went to the bakery in Brussels.\nWhat an adventure!"
ui <- fluidPage(tags$h3("Provide some text to annotate"),
  textAreaInput(inputId = "ui_text", label = "Provide some text", value = txt),
  tags$h3("Annotation area"),
  recogitoOutput(outputId = "annotation_text"),
  tags$hr(),
  tags$h3("Results"),
  verbatimTextOutput(outputId = "annotation_result"))
server <- function(input, output) {
  output$annotation_text <- renderRecogito({
    recogito("annotations", text = input$ui_text, tags = c("LOCATION", "TIME", "PERSON"))
  })
  output$annotation_result <- renderPrint({
    read_recogito(input$annotations)
  })
}
shinyApp(ui, server)

}

recogitoOutput(outputId = "annotation_text")
recogitoTagsonlyOutput(outputId = "annotation_text")

```

Index

annotorious, [2](#)
annotorious-shiny, [3](#)
annotoriousOutput (annotorious-shiny), [3](#)

createWidget, [2](#), [11](#)

ocv_crop_annotorious, [5](#)
ocv_read_annotorious, [6](#)
openseadragon_areas, [7](#)
openseadragonOutput
 (annotorious-shiny), [3](#)
openseadragonOutputNoToolbar
 (annotorious-shiny), [3](#)

read_annotorious, [6](#), [7](#), [8](#)
read_recogito, [10](#)
recogito, [11](#)
recogito-shiny, [12](#)
recogitoOutput (recogito-shiny), [12](#)
recogitotagsonlyOutput
 (recogito-shiny), [12](#)
renderAnnotorious (annotorious-shiny), [3](#)
renderOpenSeaDragon
 (annotorious-shiny), [3](#)
renderOpenSeaDragonNoToolbar
 (annotorious-shiny), [3](#)
renderRecogito (recogito-shiny), [12](#)
renderRecogitotagsonly
 (recogito-shiny), [12](#)