

Package ‘rgeopat2’

July 23, 2025

Title Additional Functions for 'GeoPAT' 2

Version 0.4.0

Description Supports analysis of spatial data processed with the 'GeoPAT' 2 software <<https://github.com/Nowosad/geopat2>>. Available features include creation of a grid based on the 'GeoPAT' 2 grid header file and reading a 'GeoPAT' 2 text outputs.

Depends R (>= 3.3.0)

Imports readr, sf, stringr

License MIT + file LICENSE

Encoding UTF-8

LazyData true

RoxygenNote 7.2.3

Suggests covr, testthat

URL <https://github.com/Nowosad/rgeopat2>

BugReports <https://github.com/Nowosad/rgeopat2/issues>

NeedsCompilation no

Author Jakub Nowosad [aut, cre] (ORCID: <<https://orcid.org/0000-0002-1057-3721>>),
Space Informatics Lab [cph]

Maintainer Jakub Nowosad <nowosad.jakub@gmail.com>

Repository CRAN

Date/Publication 2023-09-18 12:50:02 UTC

Contents

british_isles	2
gpat_create_grid	2
gpat_header_parser	3
gpat_read_distmtx	3
gpat_read_txt	4
gpat_st_make_grid	5

Index	6
-------	---

british_isles	<i>British Isles</i>
---------------	----------------------

Description

A dataset containing the British Isles outline map

Usage

british_isles

Format

An object of class sf (inherits from data.frame) with 1 rows and 1 columns.

Source

The rnaturalearth package

gpat_create_grid	<i>Grid polygon creator</i>
------------------	-----------------------------

Description

Creates a polygon of a GeoPAT 2 grid based on the grid header

Usage

gpat_create_grid(x, brick = FALSE)

Arguments

- | | |
|-------|---|
| x | A filepath to the GeoPAT 2 grid header file |
| brick | TRUE/FALSE; should a new grid polygon have a brick topology |

Value

sf

Examples

```
header_filepath = system.file("rawdata/Augusta2011_grid100.hdr", package="rgeopat2")
my_grid = gpat_create_grid(header_filepath)
my_grid_brick = gpat_create_grid(header_filepath, brick = TRUE)

plot(my_grid)
plot(my_grid_brick, add = TRUE, border = "red", lwd = 3)
```

gpat_header_parser	<i>Parse a header of a GeoPAT 2 grid file</i>
--------------------	---

Description

Extracts basic information from a geoPAT 2 grid header file

Usage

```
gpat_header_parser(x)
```

Arguments

x	A filepath to the GeoPAT 2 grid header file
---	---

Value

data_frame

gpat_read_distmtx	<i>Read a GeoPAT distance matrix</i>
-------------------	--------------------------------------

Description

Read a GeoPAT distance matrix into R

Usage

```
gpat_read_distmtx(x)
```

Arguments

x	A filepath to the geoPAT 2 distance matrix file
---	---

Value

dist

Examples

```
distmtx_filepath = system.file("rawdata/Augusta2011_matrix_grid.csv", package="rgeopat2")  
my_distmtx = gpat_read_distmtx(distmtx_filepath)
```

gpat_read_txt	<i>Read a GeoPAT 2 text output</i>
---------------	------------------------------------

Description

Read a text output of the GeoPAT 2 functions into R

Usage

```
gpat_read_txt(x, signature = NULL)
```

Arguments

x	A filepath to the GeoPAT 2 text file
signature	A signature used to create the GeoPAT 2 text output (supported signatures: "lind", "linds", "ent", and "ts")

Value

data.frame

Examples

```

polygon_filepath = system.file("rawdata/Augusta2011_polygon.txt", package = "rgeopat2")
my_polygon = gpat_read_txt(polygon_filepath)

# points_filepath = system.file("rawdata/Augusta2011_points.txt", package = "rgeopat2")
# my_points = gpat_read_txt(points_filepath)

# lind_filepath = system.file("rawdata/Augusta2011_lind.txt", package = "rgeopat2")
# my_lind = gpat_read_txt(lind_filepath, signature = "lind")

# linds_filepath = system.file("rawdata/Augusta2011_linds.txt", package = "rgeopat2")
# my_linds = gpat_read_txt(linds_filepath, signature = "linds")

# grid_filepath = system.file("rawdata/Augusta2011_grid100.txt", package = "rgeopat2")
# my_grid = gpat_read_txt(grid_filepath)

# gridlinds_filepath = system.file("rawdata/Augusta2011_grid_linds.txt", package = "rgeopat2")
# my_grid = gpat_read_txt(gridlinds_filepath, signature = "linds")

# gridts_filepath = system.file("rawdata/barent_ts_grd.txt", package = "rgeopat2")
# my_gridts = gpat_read_txt(gridts_filepath, signature = "ts")

```

gpat_st_make_grid	<i>Grid polygon creator (without a header)</i>
-------------------	--

Description

Creates a polygon of a GeoPAT grid based on a given parameters

Usage

```
gpat_st_make_grid(x, n = c(10, 10), brick = FALSE)
```

Arguments

x	An object of class sf or sfc
n	An integer of length 1 or 2, number of grid cells in x and y direction (columns, rows)
brick	TRUE/FALSE; should a new grid polygon have a brick topology

Value

sf

References

Based on the st_make_grid function from the sf package

Examples

```
## Not run:
library(sf)
nc = st_read(system.file("shape/nc.shp", package="sf"))

my_grid = gpat_st_make_grid(nc)
my_grid$id = 1:100

grid_centroids = st_centroid(my_grid) %>%
  st_coordinates(grid_centroids) %>%
  as_data_frame() %>%
  mutate(id = 1:100)

ggplot() +
  geom_sf(data = my_grid) +
  geom_text(data = grid_centroids, aes(x = X, y = Y, label = id)) +
  theme_void()

## End(Not run)
```

Index

* **datasets**

british_isles, [2](#)

british_isles, [2](#)

gpat_create_grid, [2](#)

gpat_header_parser, [3](#)

gpat_read_distmtx, [3](#)

gpat_read_txt, [4](#)

gpat_st_make_grid, [5](#)