

Package ‘rhype’

July 23, 2025

Title Work with Hypergraphs in R

Version 0.3.0

Description Create and manipulate hypergraph objects. This early version of rhype allows for the output of matrices associated with the hypergraphs themselves. It also uses these matrices to calculate hypergraph spectra and perform spectral comparison. Functionality coming soon includes calculation of hyperpaths and hypergraph centrality measures.

License GPL (>= 3)

Encoding UTF-8

RoxygenNote 7.2.1

Imports Matrix, R6, RSpectra

Suggests spelling, testthat (>= 3.0.0)

Config/testthat/edition 3

Language en-US

NeedsCompilation no

Author Hugh Warden [aut, cre] (ORCID: <<https://orcid.org/0000-0002-4308-7316>>)

Maintainer Hugh Warden <hugh.warden@outlook.com>

Repository CRAN

Date/Publication 2022-08-06 13:30:02 UTC

Contents

adjacency_matrix	2
degree	3
eigenvector_centrality	4
eigenvector_centrality_factor	4
example_hype	5
has_real_coef	6
hyperedge_list	6
hyperedge_names	7
hyperedge_weights	7

hype_from_edge_list	8
hype_from_inc_mat	9
hype_info	10
hype_norm_lap_mat	12
hype_order	12
hype_size	13
incidence_matrix	13
is_directed	14
is_oriented	15
is_weighted	15
laplacian_matrix	16
pseudo_invert	16
spectra	17
spectral_distance	17
spectral_distance_disc	18
validate_hypergraph	19
vertex_names	19
vertex_weights	20
vert_norm_lap_mat	21

Index 22

adjacency_matrix	<i>Find the Adjacency Matrix of a Hypergraph</i>
------------------	--

Description

An adjacency matrix is a square matrix with both rows and columns being indexed by vertices. For each entry, the number is proportional to the strength of the connection going from the vertex represented as the row and the vertex represented by the column. For undirected hypergraphs, this matrix is symmetric but this is usually not the case for directed.

Usage

```
adjacency_matrix(hype, normalise = TRUE, self_adj = TRUE, as_matrix = FALSE)
```

Arguments

hype	A hypergraph object
normalise	Whether the matrix should be normalised to either 1 or 0
self_adj	Whether self adjacency should be represented
as_matrix	Whether the output should be coerced into a simple matrix

Details

Great care should be taken when using a hypergraph with mixed positive and negative real coefficients as there is a chance no adjacency will be registered for two adjacent vertices. hype does not check for these cases and they must be checked for by the user.

Value

A matrix of adjacencies between vertices of a hypergraph.

Examples

```
h1 <- example_hype()
adjacency_matrix(h1)

h2 <- example_hype(oriented = TRUE, directed = TRUE)
adjacency_matrix(h2)
```

degree

Find the Degree of Vertices in a Hypergraph

Description

The degree of a vertex is a way of expressing how many connections there are from a vertex to the rest of the hypergraph. The current version of rhype has three methods for computing degree.

Usage

```
degree(hype, method = "vertex")
```

Arguments

hype	A hypergraph object
method	The method for calculating degree. Out of "vertex", "vertex_simple", "hyperedge" and "hyperedge_simple"

Details

"vertex" counts the number of ways it is possible to move to another vertex. If there are multiple hyperedges connecting two vertices, then each of these hyperedges will be counted as a new way to move between these two vertices. For weighted hypergraphs or hypergraphs with real coefficients, the strength of connection between two vertices is a functions of the weights and real coefficients.

"vertex_simple" just counts the number of vertices it is possible to reach in one step from the given vertex, no matter how many hyperedges connect them.

"hyperedge" represents the strength with which a vertex connects with itself through the hyperedges it is a member of. This is taken from the work of Jurgen Jost and Raffaella Mulas doi: [10.1016/j.aim.2019.05.025](https://doi.org/10.1016/j.aim.2019.05.025). For unweighted hypergraphs without real coefficients this is equivalent to "hyperedge_simple".

"hyperedge_simple" just counts the number of hyperedges a vertex is a member of.

Value

A vector representing the degree of each vertex with respect to the given method.

Examples

```
h1 <- example_hype()
degree(h1)
```

`eigenvector_centrality`*Calculate The Eigenvector Centrality Of A Hypergraph*

Description

To calculate the eigenvector centrality of a hypergraph, each vertex is assigned a value that is proportional to the sum of the value of its neighbours.

Usage

```
eigenvector_centrality(hype)
```

Arguments

`hype` A hypergraph object

Value

A vector of values representing the eigenvector centrality of each node

Examples

```
h1 <- example_hype()
eigenvector_centrality(h1)
```

`eigenvector_centrality_factor`*Calculate The Eigenvector Centrality Scaling Factor Of A Hypergraph*

Description

To calculate the eigenvector centrality of a hypergraph, each vertex is assigned a value that is proportional to the sum of the value of its neighbours. This function gives the scaling factor relating the value of each node to the sum of the value of its neighbours.

Usage

```
eigenvector_centrality_factor(hype)
```

Arguments

hype A hypergraph object

Value

A number representing the scaling factor relating the value of each node to the sum of the value of its neighbours

Examples

```
h1 <- example_hype()
eigenvector_centrality_factor(h1)
```

example_hype	<i>Generate an Example Hypergraph</i>
--------------	---------------------------------------

Description

Quickly generate an example hypergraph. Can be used for quickly testing and trialing examples.

Usage

```
example_hype(  
  oriented = FALSE,  
  directed = FALSE,  
  vertex_weighted = FALSE,  
  edge_weighted = FALSE,  
  real_coef = FALSE  
)
```

Arguments

oriented	Logical value representing whether the example hypergraph should be oriented
directed	Logical value representing whether the example hypergraph should be directed
vertex_weighted	Logical value representing whether the example hypergraph should have vertex weights
edge_weighted	Logical value representing whether the example hypergraph should have hyper-edge weights
real_coef	Logical value representing whether the example hypergraph should have real coefficients relating vertices to hyperedges

Value

An example hypergraph with the given properties

Examples

```
h1 <- example_hype()
h2 <- example_hype(oriented = TRUE)
h3 <- example_hype(oriented = TRUE, directed = TRUE)
h4 <- example_hype(oriented = TRUE, directed = TRUE, real_coef = TRUE)
```

has_real_coef

Does a Hypergraph Have Real Coefficients

Description

Takes a hypergraph object and returns whether there are real coefficients associating vertices to hyperedges.

Usage

```
has_real_coef(hype)
```

Arguments

hype A hypergraph object.

Value

A logical value indicating whether there are real coefficients associating vertices to hyperedges.

Examples

```
h <- example_hype()
has_real_coef(h)
```

hyperedge_list

Get Hyperedge List

Description

Take a hypergraph object and return its hyperedge list.

Usage

```
hyperedge_list(hype)
```

Arguments

hype A hypergraph object

Value

A hyperedge list. See main documentation for more details on its structure

Examples

```
h <- example_hype()
hyperedge_list(h)
```

hyperedge_names	<i>Get Hyperedge Names</i>
-----------------	----------------------------

Description

Takes a hypergraph object and returns the names of the hyperedges.

Usage

```
hyperedge_names(hype)
```

Arguments

hype A hypergraph object.

Value

A vector of strings representing the names of the the hyperedges. If the hyperedges have no names associated with them it will return NULL instead.

Examples

```
h <- example_hype()
hyperedge_names(h)
```

hyperedge_weights	<i>Get Hyperedge Weights</i>
-------------------	------------------------------

Description

Takes a hypergraph object and returns the weights associated with each hyperedge

Usage

```
hyperedge_weights(hype)
```

Arguments

hype A hypergraph object.

Value

A vector of weights associated with the hyperedges. If there are no weights associated with the hyperedges then NULL is returned instead.

Examples

```
h <- example_hype()
hyperedge_weights(h)
```

hype_from_edge_list *Create a Hypergraph From a Hyperedge List*

Description

Create a Hypergraph From a Hyperedge List

Usage

```
hype_from_edge_list(elist, directed = FALSE)
```

Arguments

elist	A hyperedge list. For an unoriented hypergraph, a hyperedge is just a vector of the vertices contained within the hyperedge. Each vertex is represented as a string. For an oriented hypergraph, each hyperedge is itself a list of two vectors. Each of these vectors contains strings representing the vertices contained in one end of the hyperedge. For a directed hypergraph, each hyperedge is also a list of two vectors. In the directed case, the first vector represents the vertices contained in the tail of the hyperedge and the second the vertices contained in the head. These two entries are also named from and to.
directed	A logical value representing whether the hypergraph should be directed.

Value

A hypergraph object with the given hyperedge structure.

Examples

```
l1 <- list(
  h1 = c("a", "b", "c"),
  h2 = c("c", "d", "e"),
  h3 = c("a", "e")
)
hype1 <- hype_from_edge_list(l1)

l2 <- list(
  h1 = list(
    c("a", "b"),
```



```

      c("b", "c")
    ),
    h2 = list(
      c("b", "c", "d"),
      c("e", "f")
    ),
    h3 = list(
      "f",
      "a"
    )
  )
)
hype2 <- hype_from_edge_list(l2)
hype3 <- hype_from_edge_list(l2, directed = TRUE)

```

hype_from_inc_mat	<i>Create a Hypergraph From an Incidence Matrix</i>
-------------------	---

Description

Create a Hypergraph From an Incidence Matrix

Usage

```
hype_from_inc_mat(inc_mat, directed = FALSE, real_coef = FALSE)
```

Arguments

inc_mat	An incidence matrix or, for an oriented hypergraph, a list of two incidence matrices.
directed	A logical value representing whether the hypergraph should be directed.
real_coef	A logical value representing whether the hypergraph should have real coefficients associating vertices to hyperedges.

Value

A hypergraph object with the given incidence structure.

Examples

```

i1 <- matrix(
  c(1, 1, 1, 0, 0, 0, 0, 1, 1, 1, 0, 1, 0, 1, 0),
  nrow = 5,
  ncol = 3,
  dimnames = list(
    paste0("v", 1:5),
    paste0("h", 1:3)
  )
)
hype1 <- hype_from_inc_mat(i1)

```

```

i2 <- list(
  matrix(
    c(1, 1, 0, 0, 1, 0, 0, 1, 0, 1, 1, 0),
    nrow = 4,
    ncol = 3,
    dimnames = list(
      paste0("v", 1:4),
      paste0("h", 1:3)
    )
  ),
  matrix(
    c(0, 0, 1, 1, 1, 1, 0, 0, 1, 0, 1, 0),
    nrow = 4,
    ncol = 3,
    dimnames = list(
      paste0("v", 1:4),
      paste0("h", 1:3)
    )
  )
)
hype2 <- hype_from_inc_mat(i2)
hype3 <- hype_from_inc_mat(i2, directed = TRUE)

```

hype_info

Print More Detail About a Hypergraph

Description

Get a more detailed printout of what is contained within a hypergraph object to understand more about its structure as a whole without having to repeatedly call other functions.

Usage

```

hype_info(
  hype,
  numv = TRUE,
  elist = TRUE,
  vnames = TRUE,
  vweights = TRUE,
  enames = TRUE,
  eweights = TRUE,
  weighted = TRUE,
  oriented = TRUE,
  directed = TRUE,
  real_coef = TRUE,
  inc_mat = TRUE
)

```

Arguments

hype	A hypergraph object
numv	A logical variable indicating whether information about the number of vertices should be printed
elist	A logical variable indicating whether information about the hyperedge list should be printed
vnames	A logical variable indicating whether information about the vertex names should be printed
vweights	A logical variable indicating whether information about the vertex weights should be printed
enames	A logical variable indicating whether information about the hyperedge names should be printed
eweights	A logical variable indicating whether information about the hyperedge weights should be printed
weighted	A logical variable indicating whether information about the hypergraph weighting should be printed
oriented	A logical variable indicating whether information about the hypergraph orientation should be printed
directed	A logical variable indicating whether information about the hypergraph direction should be printed
real_coef	A logical variable indicating whether information about the hypergraph real coefficients should be printed
inc_mat	A logical variable indicating whether information about the hypergraph incidence matrix should be printed

Details

This gives a more detailed look at the whole hypegraph object. It is intended solely to aid the user when using `rhype` and generally should not be included in final scripts. If a user wants to include this in their final script it is instead heavily encouraged that they use other `rhype` functions to generate their own bespoke messages.

Examples

```
hype1 <- example_hype()
hype_info(hype1)

hype2 <- example_hype(vertex_weighted = TRUE, edge_weighted = TRUE)
hype_info(hype2)

hype3 <- example_hype(oriented = TRUE, directed = TRUE, real_coef = TRUE)
hype_info(hype3)
```

hype_norm_lap_mat	<i>Find the Hyperedge Normalised Laplacian Matrix of a Hypergraph</i>
-------------------	---

Description

As defined by Jurgen Jost and Raffaella Mulas doi: [10.1016/j.aim.2019.05.025](https://doi.org/10.1016/j.aim.2019.05.025)

Usage

```
hype_norm_lap_mat(hype)
```

Arguments

hype A hypergraph object

Value

The hyperedge normalised laplacian matrix of the hypergraph

Examples

```
h1 <- example_hype()
hype_norm_lap_mat(h1)
```

hype_order	<i>Get The Order Of A Hypergraph</i>
------------	--------------------------------------

Description

The order of a hypergraph is the number of vertices it has

Usage

```
hype_order(hype)
```

Arguments

hype A hypergraph object

Value

A number representing the number of vertices in the hypergraph

Examples

```
hype <- example_hype()
hype_order(hype)
```

hype_size	<i>Get The Size Of A Hypergraph</i>
-----------	-------------------------------------

Description

The size of a hypergraph is the number of hyperedges it contains

Usage

```
hype_size(hype)
```

Arguments

hype	A hypergraph object
------	---------------------

Value

A number representing the number of hyperedges in a hypergraph

incidence_matrix	<i>Find the Incidence Matrix of a Hypergraph</i>
------------------	--

Description

An incidence matrix has rows indexed by vertices and columns indexed by hyperedges. Each entry is non-zero if the associated vertex is a member of the associated hyperedge. For an oriented hypergraph, this returns a list of two matrices with the first representing incidence to one end of the hyperedges and the second representing incidence to the other end. For a directed hypergraph the first represents incidence to the tail of a hyperedge and the second represents incidence to the head.

Usage

```
incidence_matrix(hype, augment_oriented = TRUE, as_matrix = FALSE)
```

Arguments

hype	A hypergraph object
augment_oriented	Whether to augment an oriented hypergraph
as_matrix	Whether to coerce the result to a simple matrix

Details

It is hard to use the incidence matrices of oriented undirected hypergraphs in calculations. The `augment_oriented` option turns the hypergraph into a directed hypergraph, but each hyperedge is represented twice, once pointing in each direction. This is much easier to use for further calculations.

Value

An incidence matrix or a list of two incidence matrices.

Examples

```
h1 <- example_hype()
incidence_matrix(h1)

h2 <- example_hype(oriented = TRUE, directed = TRUE)
incidence_matrix(h2)
```

is_directed

Is a Hypergraph Directed

Description

Takes a hypergraph object and returns whether the hyperedges are directed.

Usage

```
is_directed(hype)
```

Arguments

hype A hypeprgraph object.

Value

A logical value indicating whether the hyperedges are directed.

Examples

```
h <- example_hype()
is_directed(h)
```

is_oriented	<i>Is a Hypergraph Oriented</i>
-------------	---------------------------------

Description

Takes a hypergraph object and returns whether the hyperedges are oriented.

Usage

```
is_oriented(hype)
```

Arguments

hype A hypergraph object.

Value

A logical value indicating whether the hyperedges are oriented.

Examples

```
h <- example_hype()
is_oriented(h)
```

is_weighted	<i>Is a Hypergraph Weighted</i>
-------------	---------------------------------

Description

Takes a hypergraph object and returns whether a hypergraph has weights associated with its vertices or hyperedges.

Usage

```
is_weighted(hype)
```

Arguments

hype A hypergraph object.

Value

A logical value indicating whether the hypergraph has weights associated with its vertices or hyperedges.

Examples

```
h <- example_hype()
is_weighted(h)
```

laplacian_matrix	<i>Find the Laplacian Matrix of a Hypergraph</i>
------------------	--

Description

Find the Laplacian Matrix of a Hypergraph

Usage

```
laplacian_matrix(hype)
```

Arguments

hype A hypergraph object

Value

The laplacian matrix of the hypergraph

Examples

```
h1 <- example_hype()
laplacian_matrix(h1)
```

pseudo_invert	<i>Pseudo-Invert a Vector</i>
---------------	-------------------------------

Description

Pseudoinversion is where a vector has each non-zero element inverted and each zero element remains untouched. This is useful for pseudoinverting matrices that only have non-zero entries on the leading diagonal.

Usage

```
pseudo_invert(vec)
```

Arguments

vec A vector of numbers

Value

A vector of pseudo-inverted numbers

spectra	<i>Find the Spectra of a Hypergraph</i>
---------	---

Description

Find the Spectra of a Hypergraph

Usage

```
spectra(hype, matrix = "laplacian", n = NULL)
```

Arguments

hype	A hypergraph object
matrix	The matrix to calculate the spectra with respect to. Out of "laplacian", "adjacency", "vert_norm_lap_mat" and "hype_norm_lap_mat"
n	The number of eigenvalues or eigenvectors to calculate. If left empty or as NULL all will be calculated.

Value

The eigen decomposition of the given matrix of the given hypergraph

Examples

```
h <- example_hype()
spectra(h)
```

spectral_distance	<i>Find the Spectral Distance Between Two Hypergraphs</i>
-------------------	---

Description

Find the Spectral Distance Between Two Hypergraphs

Usage

```
spectral_distance(hype1, hype2, matrix = "laplacian")
```

Arguments

hype1	A hypergraph object
hype2	A hypergraph object
matrix	The matrix to calculate the spectral distance with respect to. Out of "laplacian", "adjacency", "vert_norm_lap_mat" and "hype_norm_lap_mat"

Value

A number representing the spectral distance between the two hypergraphs with respect to the given matrix

Examples

```
h1 <- example_hype()
h2 <- example_hype()
spectral_distance(h1, h2)
```

spectral_distance_disc

Find the Spectral Distance From the Fully Disconnected Hypergraph

Description

Find the Spectral Distance From the Fully Disconnected Hypergraph

Usage

```
spectral_distance_disc(hype, matrix = "vert_norm_lap_mat")
```

Arguments

hype	A hypergraph object
matrix	The matrix to calculate the spectra with respect to. Out of "vert_norm_lap_mat" and "hype_norm_lap_mat"

Value

The spectral distance from the disconnected hypergraph

Examples

```
h <- example_hype()
spectral_distance_disc(h)
```

validate_hypergraph	<i>Quickly Validate a Hypergraph</i>
---------------------	--------------------------------------

Description

When using the rhype functions, the integrity of a hypergraph object should remain intact. However, as the properties of a hypergraph object are dependent on one another, it is possible in the case of an error or direct object manipulation by the user that a hypergraph object's integrity is corrupted. This will cause other rhype functions to either throw errors or to calculate incorrect answers. This function is not exhaustive but will perform multiple sanity checks on hypergraph objects and is a good place to start when debugging.

Usage

```
validate_hypergraph(hype, return = FALSE, verbose = TRUE)
```

Arguments

hype	A hypergraph object
return	A logical variable stating whether any output should be returned from the function
verbose	A logical variable indicating whether the function should output text to the screen

Value

Outputs text to screen of any problems found within the hypergraph object. If return is set to TRUE then a logical output will be returned. This logical output will be TRUE if it passed all of the tests, FALSE if it failed any test that proves the structure of the hypergraph is broken or NULL if it failed a test that most hypergraphs used practically should pass, but doesn't necessarily mean the hypergraph is broken, see text output for more details.

Examples

```
h <- example_hype()
validate_hypergraph(h)
```

vertex_names	<i>Get Vertex Names</i>
--------------	-------------------------

Description

Takes a hypergraph object and returns the names of its vertices.

Usage

```
vertex_names(hype)
```

Arguments

hype A hypergraph object.

Value

A vector of strings of vertex names

Examples

```
h <- example_hype()
vertex_names(h)
```

vertex_weights	<i>Get Vertex Weights</i>
----------------	---------------------------

Description

Takes a hypergraph object and returns the weights associated with its vertices.

Usage

```
vertex_weights(hype)
```

Arguments

hype A hypergraph object.

Value

A vector of weights associated with each vertex. If the hypergraph has no weights associated with its vertices it will return NULL instead.

Examples

```
h <- example_hype()
vertex_weights(h)
```

vert_norm_lap_mat	<i>Find the Vertex Normalised Laplacian Matrix of a Hypergraph</i>
-------------------	--

Description

As defined by Jurgen Jost and Raffaella Mulas doi: [10.1016/j.aim.2019.05.025](https://doi.org/10.1016/j.aim.2019.05.025)

Usage

```
vert_norm_lap_mat(hype)
```

Arguments

hype	A hypergraph object
------	---------------------

Value

The vertex normalised laplacian matrix of the hypergraph

Examples

```
h1 <- example_hype()
vert_norm_lap_mat(h1)
```

Index

adjacency_matrix, [2](#)

degree, [3](#)

eigenvector_centrality, [4](#)
eigenvector_centrality_factor, [4](#)
example_hype, [5](#)

has_real_coef, [6](#)
hype_from_edge_list, [8](#)
hype_from_inc_mat, [9](#)
hype_info, [10](#)
hype_norm_lap_mat, [12](#)
hype_order, [12](#)
hype_size, [13](#)
hyperedge_list, [6](#)
hyperedge_names, [7](#)
hyperedge_weights, [7](#)

incidence_matrix, [13](#)
is_directed, [14](#)
is_oriented, [15](#)
is_weighted, [15](#)

laplacian_matrix, [16](#)

pseudo_invert, [16](#)

spectra, [17](#)
spectral_distance, [17](#)
spectral_distance_disc, [18](#)

validate_hypergraph, [19](#)
vert_norm_lap_mat, [21](#)
vertex_names, [19](#)
vertex_weights, [20](#)