

Package ‘sampbias’

July 23, 2025

Type Package

Title Evaluating Geographic Sampling Bias in Biological Collections

Version 2.0.0

Description Evaluating the biasing impact of geographic features such as airports, cities, roads, rivers in datasets of coordinates based biological collection datasets, by Bayesian estimation of the parameters of a Poisson process. Enables also spatial visualization of sampling bias and includes a set of convenience functions for publication level plotting. Also available as 'shiny' app. The reference for the methodology is: Zizka et al. (2020) <[doi:10.1111/ecog.05102](https://doi.org/10.1111/ecog.05102)>.

Language en-gb

License GPL-3

URL <https://github.com/azizka/sampbias>

BugReports <https://github.com/azizka/sampbias/issues>

Depends R(>= 3.5.0)

Imports cowplot, dplyr, forcats, ggplot2, graphics, magrittr, methods, rlang, tidyr, viridis, terra, sf, rnatualearth

Suggests knitr, rmarkdown, testthat (>= 3.0.0)

LazyData TRUE

LazyDataCompression xz

RoxygenNote 7.3.1

VignetteBuilder knitr

Encoding UTF-8

Config/testthat/edition 3

NeedsCompilation no

Author Alexander Zizka [aut, cre],
Daniele Silvestro [aut],
Bruno Vilela [ctb] (Bruno updated the code to use new spatial packages)

Maintainer Alexander Zizka <alexander.zizka@biologie.uni-marburg.de>

Repository CRAN

Date/Publication 2024-02-06 18:20:05 UTC

Contents

area_example	2
borneo	2
calculate_bias	3
dis_rast	6
ea_raster	7
ecoregion_example	7
is.sampbias	8
map_bias	9
plot.sampbias	10
project_bias	11
summary.sampbias	12
Index	13

area_example	<i>Example Dataset for a Custom Study Area</i>
--------------	--

Description

An example of the format needed to provide custom areas for `calculate_bias`

Usage

`area_example`

Format

An object of class `sf` (inherits from `data.frame`) with 2 rows and 1 columns.

Examples

`data(area_example)`

borneo	<i>Borneo</i>
--------	---------------

Description

The outline of Borneo, as example data for the user-defined study area option of `calculate_bias`.
From <https://www.naturalearthdata.com>.

Usage

`borneo`

Format

An object of class `sf` (inherits from `data.frame`) with 1 rows and 3 columns.

Examples

```
data(borneo)
```

calculate_bias

Evaluating Sampling Bias in Species Distribution Data

Description

The major function of the package, calculating the bias effect of sampling bias due to geographic structures, such as the vicinity to cities, airports, rivers and roads. Results are projected to space, and can be compared numerically.

Usage

```
calculate_bias(
  x,
  gaz = NULL,
  res = 1,
  buffer = NULL,
  restrict_sample = NULL,
  terrestrial = TRUE,
  inp_raster = NULL,
  mcmc_rescale_distances = 1000,
  mcmc_iterations = 1e+05,
  mcmc_burnin = 20000,
  mcmc_outfile = NULL,
  prior_q = c(1, 0.01),
  prior_w = c(1, 1),
  plot_raster = FALSE,
  verbose = FALSE,
  run_null_model = FALSE,
  use_hyperprior = TRUE
)
```

Arguments

<code>x</code>	an object of the class <code>data.frame</code> , with one species occurrence record per line, and at least three columns, named ‘species’, ‘decimalLongitude’, and ‘decimalLatitude’.
<code>gaz</code>	a list of geographic gazetteers as <code>SpatVector</code> or <code>sf</code> . If <code>NULL</code> , a set of default gazetteers, representing large scale occurrence of airports, cities, rivers, and roads is used. See Details.

res	numerical. The raster resolution for the distance calculation to the geographic features and the data visualization, in decimal degrees. The default is to one degree, but higher resolution will be desirable for most analyses. res together with the extent of the input data determine computation time and memory requirements.
buffer	numerical. The size of the geographic buffer around the extent of ras for the distance calculations in degrees, to account for geographic structures neighbouring the study area (such as a road right outside the study area). Should be a multiple of res. Default is to res * 10. See Details.
restrict_sample	a SpatVector object. If provided the area for the bias test will be restricted to raster cells within these polygons (and the extent of the sampled points in x). Make sure to use adequate values for res. Default = NULL.
terrestrial	logical. If TRUE, the empirical distribution (and the output maps) are restricted to terrestrial areas. Uses the <code>rnaturalearth::ne_countries</code> to define what is terrestrial. Default = TRUE.
inp_raster	an object of class SpatRaster. A template raster for the counts and distance calculation. Can be used to provide a special resolution, or for different coordinate reference systems. See vignette.
mcmc_rescale_distances	numerical. rescaling factor for the distance calculation
mcmc_iterations	numerical. the number of iterations for the MCMC, by default 100,000
mcmc_burnin	numerical. the burn-in for the MCMC, default is to 20,000
mcmc_outfile	character string. the path on where to write the results of the MCMC, optional.
prior_q	the gamma prior for the sampling rate q , which represents the expected number of occurrences per cell in the absence of biases. In the format <code>c(shape,rate)</code> .
prior_w	the gamma prior for the steepness of the Poisson rate decline, such that w approximating 0 results in a null model of uniform sampling rate q across cells. In the format <code>c(shape,rate)</code> .
plot_raster	logical. If TRUE, a plot of the occurrence raster is shown for diagnostic purposes. Default = FALSE
verbose	logical. If TRUE, progress is reported. Default = FALSE.
run_null_model	logical. Run a null model with bias weights set to zero.
use_hyperprior	logical. If TRUE a hyperprior on the bias weights is used for regularization to avoid over-parametrization.

Details

The default gazetteers delivered with the package are simplified from <http://www.naturalearthdata.com/downloads/>. They include major features, and for small scale analyses custom gazetteers should be used.

For computational convenience, the gazetteers are cropped to the extent of the point occurrence data sets. To account for the fact, that, relevant structures might lay directly outside this extent, but still influencing the distribution of samples in the study area, the buffer option, gives the area, around the extent that should be included in the distance calculation.

Visit <https://github.com/azizka/sampbias/wiki> for more information on distance calculation and the algorithm behind sampbias.

Value

An object of the S3-class 'sampbias', which is a list including the following objects:

summa	A list of summary statistics for the sampbias analyses, including the total number of occurrence points in x, the total number of species in x, the extent of the output rasters as well as the settings for res, binsize, and convexhull used in the analyses.
occurrences	a SpatRaster indicating occurrence records per grid cell, with resolution res.
species	a SpatRaster with indicating the number of species per grid cell, with resolution res.
biasmaps	a list of SpatRaster, with the same length as gaz. Each element is the spatial projection of the bias effect for a sources of bias in gaz. The last raster in the list is the average over all bias sources.
biastable	a data.frame, with the estimated bias effect for each bias source in gaz, at the distances specified by biasdist.

Note

Check <https://github.com/azizka/sampbias/wiki> for a tutorial on sampbias.

See Also

`summary.sampbias` `is.sampbias` `plot.sampbias`

Examples

```
#simulate data
x <- data.frame(species = rep(sample(x = LETTERS, size = 5), times = 20),
                decimalLongitude = runif(n = 100, min = 0, max = 20),
                decimalLatitude = runif(n = 100, min = -4, max = 4))

out <- calculate_bias(x, terrestrial = TRUE, buffer = 0)
summary(out)
plot(out)
```

dis_rast

*Distance Rasters from a List of Geographic Gazetteers***Description**

Creates a list of distances rasters based on a list of geographic gazetteers, as SpatVector objects, and a template SpatRaster, indicating the desired extent and resolution.

Usage

```
dis_rast(gaz, ras, buffer = NULL)
```

Arguments

gaz	an object of the class list, including one or more geographic gazetteers of the class SpatVector.
ras	an object of the class SpatRaster. Defining the extent and resolution of the distances rasters.
buffer	numerical. The size of the geographic buffer around the extent of ras for the distance calculations in degrees, to account for geographic structures neighbouring the study area (such as a road right outside the study area) Default is to the resolution of ras.

Value

a list of SpatRaster objects of the same length as gaz. The values in each raster correspond to the planar geographic distance to the next feature in gaz, given the resolution of ras

Note

Check <https://github.com/azizka/sampbias/wiki> for a tutorial on sampbias.

See Also

[calculate_bias](#)

Examples

```
#create raster for resolution and extent
ras <- terra::rast(terra::ext(-5,5,-4,4), res = 1)

#create point gazeteer
pts <- data.frame(long = runif(n = 5, min = -5, max = 5),
                  lat = runif(n = 5, min = -4, max = 4),
                  dat = rep("A", 5))

pts <- terra::vect(pts, geom = c("long", "lat"))
```

```
lin <- as.matrix(data.frame(long = seq(-5, 5, by = 1),  
                           lat = rep(2, times = 11)))  
lin <- terra::vect(lin, type = "line")  
  
gaz <- list(point.structure = pts, lines.strucutre = lin)  
  
out <- dis_rast(gaz, ras)
```

ea_raster

Equal Area Raster

Description

An example for an global equal area raster (in Behrmann projection) for the format needed for a custom grid provided to [calculate_bias](#).

Usage

```
ea_raster
```

Format

An object of class PackedSpatRaster of length 1.

Examples

```
data(ea_raster)  
ea_raster <- terra::unwrap(ea_raster)
```

ecoregion_example

Detailed Example for a Custom Study Area

Description

An example of the format needed to provide custom areas for [calculate_bias](#) based on a publicly available set of global ecoregions.

Usage

```
ecoregion_example
```

Format

An object of class sf (inherits from data.frame) with 7 rows and 22 columns.

Source

<https://www.worldwildlife.org/publications/terrestrial-ecoregions-of-the-world>

Examples

```
data(ecoregion_example)
```

is.sampbias

Is Method for Class sampbias

Description

Check class of sampbias objects.

Usage

```
## S3 method for class 'sampbias'
is(object, class2 = "sampbias")
```

Arguments

object	an object of the class sampbias
class2	the names of the class to which is relations are to be examined defined, or (more efficiently) the class definition objects for the classes.

Details

With two arguments, tests whether object can be treated as from class2. With one argument, returns all the super-classes of this object's class.

Value

The function returns a logical indicating whether the object is a is of the class sampbias.

Examples

```
#simulate data
occ <- data.frame(species = rep(sample(x = LETTERS, size = 5), times = 10),
                  decimalLongitude = runif(n = 50, min = 12, max = 20),
                  decimalLatitude = runif(n = 50, min = -4, max = 4))

out <- calculate_bias(x = occ, terrestrial = TRUE)
is(out)
```


map_bias

*Mapping Projected Bias Effects***Description**

A plotting function to visualize the effect of accessibility bias caused by different biasing factors in space.

Usage

```
map_bias(x, gaz = NULL, sealine = TRUE, type = "sampling_rate")
```

Arguments

x	a raster stack as generate by project_bias
gaz	a list of SpatialObjects, to be printed on the maps. Should be the same objects provided to calculate_bias when creating the Object. If gaz is not supplied, the sampbias package standard gazetteers are used.
sealine	logical. Should the coastline be added to the plots? Default is to TRUE.
type	character vector. One of c("sampling_rate", "log_sampling_rate", "diff_to_max"). If "sampling_rate". the plot shows the raw projected sampling rate depending on the biasing factors, if "log_sampling_rate", the plot shows the log10 transformed sampling rate, and if "diff_to_max", the relative deviation of sampling rate from the maximum rate as calculated using calculate_bias and projected using project_bias . For instance, a value of -25 indicates a drop of 25 (e.g. in a road on river flowing through the city airport).

Value

A series of R plots based on ggplot2.

See Also

[calculate_bias](#), [project_bias](#)

Examples

```
#simulate data
occ <- data.frame(species = rep(sample(x = LETTERS, size = 5), times = 10),
                  decimalLongitude = runif(n = 50, min = 12, max = 20),
                  decimalLatitude = runif(n = 50, min = -4, max = 4))

out <- calculate_bias(x = occ, terrestrial = TRUE)
proj <- project_bias(out)
map_bias(proj)
```

plot.sampbias

Plotting the Posterior Estimates of the Bias Weights

Description

Plotting method for class sampbias, generating a box-whiskers-plot showing the bias weights for all biasing factors indicating the effect strength for each gazetteer provided to calculate_bias.

Usage

```
## S3 method for class 'sampbias'  
plot(x, ...)
```

Arguments

x an object of the class sampbias.
... Additional arguments passed to summary.

Value

A plot

See Also

[calculate_bias](#), [summary.sampbias](#)

Examples

```
#simulate data  
occ <- data.frame(species = rep(sample(x = LETTERS, size = 5), times = 10),  
                  decimalLongitude = runif(n = 50, min = 12, max = 20),  
                  decimalLatitude = runif(n = 50, min = -4, max = 4))  
  
out <- calculate_bias(x = occ, terrestrial = TRUE)  
summary(out)  
plot(out)
```

project_bias	<i>Projecting Bias Effects in Space</i>
--------------	---

Description

Uses the the estimated bias weights from a `sampbias` object to project the bias through space, using the same raster as used for the distance calculation.#'

Usage

```
project_bias(x, factors = NULL)
```

Arguments

x	an object of the class <code>sampbias</code> .
factors	a character vector indicating which biasing factors to project

Value

A raster stack, with the same length as the number of biasing factors used in `calculate_bias`. The names indicate the factors included for each layer.

See Also

[calculate_bias](#), [summary.sampbias](#)

Examples

```
#simulate data
occ <- data.frame(species = rep(sample(x = LETTERS, size = 5), times = 10),
                  decimalLongitude = runif(n = 50, min = 12, max = 20),
                  decimalLatitude = runif(n = 50, min = -4, max = 4))

out <- calculate_bias(x = occ, terrestrial = TRUE)
proj <- project_bias(out)
```

summary.sampbias

Summary Method for Class sampbias

Description

Summary method for objects of the class sampbias.

Usage

```
## S3 method for class 'sampbias'  
summary(object, ...)
```

Arguments

object	An object of the class sampbias
...	Additional arguments passed to summary.

Value

Summary printed to screen.

See Also

[calculate_bias](#) [is.sampbias](#) [plot.sampbias](#)

Examples

```
#simulate data  
occ <- data.frame(species = rep(sample(x = LETTERS, size = 5), times = 10),  
                  decimalLongitude = runif(n = 50, min = 12, max = 20),  
                  decimalLatitude = runif(n = 50, min = -4, max = 4))  
  
out <- calculate_bias(x = occ, terrestrial = TRUE)  
summary(out)
```

Index

- * **datasets**
 - area_example, [2](#)
 - borneo, [2](#)
 - ea_raster, [7](#)
 - ecoregion_example, [7](#)
- * **maths**
 - calculate_bias, [3](#)
- * **methods**
 - is.sampbias, [8](#)
 - map_bias, [9](#)
 - plot.sampbias, [10](#)
 - project_bias, [11](#)
 - summary.sampbias, [12](#)
- * **spatial**
 - calculate_bias, [3](#)
 - dis_rast, [6](#)

area_example, [2](#)

borneo, [2](#)

calculate_bias, [2](#), [3](#), [6](#), [7](#), [9–12](#)

dis_rast, [6](#)

ea_raster, [7](#)

ecoregion_example, [7](#)

is.sampbias, [5](#), [8](#), [12](#)

map_bias, [9](#)

plot.sampbias, [5](#), [10](#), [12](#)

project_bias, [9](#), [11](#)

summary.sampbias, [5](#), [10](#), [11](#), [12](#)