

Package ‘sazedR’

July 23, 2025

Type Package

Title Parameter-Free Domain-Agnostic Season Length Detection in Time Series

Version 2.0.2

Description Spectral and Average Autocorrelation Zero Distance Density ('sazed') is a method for estimating the season length of a seasonal time series. 'sazed' is aimed at practitioners, as it employs only domain-agnostic preprocessing and does not depend on parameter tuning or empirical constants. The computation of 'sazed' relies on the efficient autocorrelation computation methods suggested by Thibault Nion (2012, URL: https://etudes.tibonihoo.net/literate_musing/autocorrelations.html) and by Bob Carpenter (2012, URL: <https://lingpipe-blog.com/2012/06/08/autocorrelation-fft-kiss-eigen/>).

License GPL-2

URL https://github.com/mtoller/autocorr_season_length_detection/

Encoding UTF-8

LazyData true

Imports bspec (>= 1.5), dplyr (>= 0.8.0.1), fftwtools (>= 0.9.8),
pracma (>= 2.1.4), zoo (>= 1.8-3)

RoxygenNote 6.1.1

NeedsCompilation no

Author Maximilian Toller [aut],
Tiago Santos [aut, cre],
Roman Kern [aut]

Maintainer Tiago Santos <teixeiradossantos@tugraz.at>

Repository CRAN

Date/Publication 2020-09-29 18:30:02 UTC

Contents

aze 2

azed	3
computeAcf	3
downsample	4
preprocessTs	4
S	5
Sa	5
sazed	6
sazed.maj	6
sazedR	7
ze	7
zed	8
Index	9

aze	<i>Compute the AZE component of the SAZED ensemble</i>
-----	--

Description

aze estimates the season length of its argument from the mean autocorrelation zero distance

Usage

aze(y, preprocess = T)

Arguments

- y The input time series.
- preprocess If true, y is detrended and z-normalized before computation.

Value

The AZE season length estimate of y.

Examples

```
season_length <- 26
y <- sin(1:400*2*pi/season_length)
aze(y)
aze(y, preprocess = FALSE)
```

azed	<i>Compute the AZED component of the SAZED ensemble</i>
------	---

Description

azed computes the autocorrelation of its argument, and then derives the season length from its the autocorrelations zero density.

Usage

```
azed(y, preprocess = T)
```

Arguments

y	The input time series.
preprocess	If true, y is detrended and z-normalized before computation.

Value

The AZED season length estimate of y.

Examples

```
season_length <- 26
y <- sin(1:400*2*pi/season_length)
azed(y)
azed(y, preprocess = FALSE)
```

computeAcf	<i>Compute and shorten autocorrelation</i>
------------	--

Description

computeAcf computes the autocorrelation function of its argument and discards the zero lag and all lags greater than 2/3 of the argument's length

Usage

```
computeAcf(y)
```

Arguments

y	The input time series.
---	------------------------

Value

The shortened autocorrelation

Examples

```
season_length <- 26
y <- sin(1:400*2*pi/season_length)
computeAcf(y)
```

downsample	<i>Downsample Time Series</i>
------------	-------------------------------

Description

downsample samples down a time series with a rolling mean.

Usage

```
downsample(data, window_size = 2)
```

Arguments

data	The input time series.
window_size	The size of the rolling mean window used.

Value

The downsampled time series.

preprocessTs	<i>Preprocess Time Series for SAZED ensemble</i>
--------------	--

Description

preprocessTs detrends and z-normalizes its argument.

Usage

```
preprocessTs(y)
```

Arguments

y	The input time series.
---	------------------------

Value

The detrended and z-normalized time series.

Examples

```
season_length <- 26
y <- sin(1:400*2*pi/season_length)
preprocessTs(y)
```

S	<i>Compute the S component of the SAZED ensemble</i>
---	--

Description

S computes the spectral density of its argument, and then derives the season length from it.

Usage

```
S(y, preprocess = T)
```

Arguments

y	The input time series.
preprocess	If true, y is detrended and z-normalized before computation.

Value

The S season length estimate of y.

Examples

```
season_length <- 26  
y <- sin(1:400*2*pi/season_length)  
S(y)  
S(y, preprocess = FALSE)
```

Sa	<i>Compute the SA component of the SAZED ensemble</i>
----	---

Description

Sa computes the autocorrelation of its argument, and then derives the season length from its spectral density.

Usage

```
Sa(y, preprocess = T)
```

Arguments

y	The input time series.
preprocess	If true, y is detrended and z-normalized before computation.

Value

The SA season length estimate of y.

Examples

```
season_length <- 26
y <- sin(1:400*2*pi/season_length)
Sa(y)
Sa(y, preprocess = FALSE)
```

sazed	<i>SAZED Ensemble (Optimum)</i>
-------	---------------------------------

Description

sazed estimates a time series' season length by combining 3 different estimates computed on an input time series and its 10-fold self-composed autocorrelation.

Usage

```
sazed(y)
```

Arguments

y The input time series.

Value

The season length of the input time series.

Examples

```
season_length <- 26
y <- sin(1:400*2*pi/season_length)
sazed(y)
```

sazed.maj	<i>SAZED Ensemble (Majority)</i>
-----------	----------------------------------

Description

sazed.maj estimates a time series' season length by computing 6 different estimates and taking a majority vote.

Usage

```
sazed.maj(y, iter = 0, method = "down", preprocess = T)
```

Arguments

y	The input time series.
iter	The recursion depth.
method	The method used for breaking ties. One of c("alt", "diff", "down").
preprocess	If true, y is detrended and z-normalized before computation.

Value

The season length of the input time series.

Examples

```
season_length <- 26
y <- sin(1:400*2*pi/season_length)
sazed.maj(y)
```

sazedR	<i>sazedR: A package for for estimating the season length of a seasonal time series.</i>
--------	--

Description

The `sazedR` package provides the main function to compute season length, `sazed`, which is an ensemble of many season length estimation methods, also included in this package.

ze	<i>Compute the ZE component of the SAZED ensemble</i>
----	---

Description

`ze` estimates the season length of its argument from the mean zero distance

Usage

```
ze(y, preprocess = T)
```

Arguments

y	The input time series.
preprocess	If true, y is detrended and z-normalized before computation.

Value

The ZE season length estimate of y.

Examples

```
season_length <- 26
y <- sin(1:400*2*pi/season_length)
zed(y)
zed(y, preprocess = FALSE)
```

zed

Compute the ZED component of the SAZED ensemble

Description

zed computes the zero density of its argument, and then derives the season length from it.

Usage

```
zed(y, preprocess = T)
```

Arguments

y	The input time series.
preprocess	If true, y is detrended and z-normalized before computation.

Value

The ZED season length estimate of y.

Examples

```
season_length <- 26
y <- sin(1:400*2*pi/season_length)
zed(y)
zed(y, preprocess = FALSE)
```

Index

aze, [2](#)

azed, [3](#)

computeAcf, [3](#)

downsample, [4](#)

preprocessTs, [4](#)

S, [5](#)

Sa, [5](#)

sazed, [6](#)

sazed.maj, [6](#)

sazedR, [7](#)

sazedR-package (sazedR), [7](#)

ze, [7](#)

zed, [8](#)